End-to-End Autonomous Scale Racing: High-Resolution Boundary Segmentation, Neural Steering Architectures, Edge INT8 Optimization, and Environmental Drift Resilience

Autonomous Driving & Edge AI Research Group

Abstract—Autonomous scale-vehicle racing at velocities exceeding 20 km/h (> 5.5 m/s) imposes stringent physical deadlines, demanding deterministic steering decisions within 10 ms (≤ 5 cm of chassis displacement) under sub-watt embedded compute budgets. Historically, end-to-end vision systems relied on discrete, manual tri-state labels ($\{-30^\circ, 0^\circ, +30^\circ\}$) and purely convolutional neural backbones (such as NVIDIA DAVE-2 and the ENSICAEN baseline). When deployed on physical canvas tracks, discrete commands trigger limit-cycle servo chattering, while localized convolutional receptive fields suffer catastrophic performance breakdown under environmental domain shifts—including sharp cast shadows from track barricades, overhead illumination transitions, and gymnasium clutter. In this comprehensive technical monograph, we present an exhaustive, production-grade autonomy pipeline bridging data engineering, deep learning, edge hardware compilation, and drift monitoring. Our contributions are fourfold: (1) **Track Boundary Segmentation and Ground-Truth Synthesis:** A dual-domain boundary detection pipeline combining camera-space Canny and Black Top-Hat transforms with multi-scale Bird's Eye View (BEV) elliptical kernels, complemented by deep neural segmenters (`NXPUNetDeep` with ASPP/SE-attention and `NXPU2NetDeep` with 6-stage nested RSU blocks), coupled with a hybrid Stanley and Lookahead Pure Pursuit control law that synthesizes continuous ground-truth steering angles $\delta_{\text{next_step}} \in [-30.0^\circ, +30.0^\circ]$ across 3,433 frames with 0% background leakage; (2) **Architectural Benchmark of Four Neural Models:** We implement, analyze, and train four distinct steering architectures: the NVIDIA DAVE-2 baseline (1.59M parameters), the PalhanoCNN paper baseline (886k parameters), the proposed **MicroViT** hybrid Vision Transformer (359k parameters, $> 77\%$ reduction vs. DAVE-2), and **`MicroViTSmoothed`** (a 4th system variant featuring online causal temporal filtering); (3) **Sub-Millisecond Edge Optimization:** An end-to-end compilation pipeline utilizing dynamic ONNX graph simplification and TensorRT INT8 entropy calibration, achieving execution latencies as low as **0.71 ms to 2.18 ms P50 (437 to 1324 FPS)**—safely within the 10 ms control budget ($> 73\%$ safety margin); (4) **Photometric Data Drift and Resilience Study:** Using Evidently AI covariate shift monitoring across 7 optical features, we demonstrate that while NVIDIA DAVE-2 and PalhanoCNN suffer catastrophic breakdown under severe shadows (+76.9% and +59.5% error explosion, respectively), MicroViT restricts drift degradation to **+21.1%**. Furthermore, `MicroViTSmoothed` achieves near-complete environmental immunity with only **+8.2% degradation** (+0.90° delta), suppresses servo actuator jitter by $-$**75.0%** ($2.33^\circ \rightarrow 0.58^\circ$/frame), and attains the lowest continuous lap tracking error (**4.91**°). Full validation across 3,433 high-resolution track frames and 31 unit test suites establishes an authoritative foundation for agile scale autonomous driving.

Index Terms—Autonomous Racing, Edge AI, NXP Cup, Track Segmentation, U-Net, U2-Net, Vision Transformers, MicroViT, Inverse Perspective Mapping, Pure Pursuit, Stanley Controller, TensorRT, INT8 Quantization, Data Drift, Evidently AI, Temporal Smoothing, Steering Jitter.

1 Introduction

Autonomous scale-vehicle racing provides an ideal proving ground for evaluating safety-critical perception, localization, and control algorithms under aggressive kinematic regimes and stringent real-time execution constraints [1]. In the international NXP Cup competition, scale 1:10 rear-wheel-drive electric karts equipped with front Ackermann steering servos must navigate complex, unfamiliar canvas tracks at maximum speed without human intervention. The front mechanical steering saturation is physically bounded to:

$$\delta \in [\delta_{\min},\, \delta_{\max}] = [-30.0^\circ,\, +30.0^\circ] \tag{1}$$

where $\delta < 0$ denotes left steering, $\delta > 0$ denotes right steering, and $\delta = 0.0^\circ$ corresponds to straight-line tracking.

To complete competitive laps at racing velocities $v \geq 20\,\text{km/h}$ ($5.56\,\text{m/s}$), the perception and control loop must execute within a strict physical displacement deadline:

$$\Delta s = v \cdot \Delta t_{\text{ctrl}} \leq 0.05\,\text{m} \implies \Delta t_{\text{ctrl}} \leq 9.0\,\text{ms} \approx 10\,\text{ms} \tag{2}$$

With physical Ackermann steering servos exhibiting mechanical latency $\tau_d \approx 80$–$120\,\text{ms}$, any computational delay spike or high-frequency perception chattering induces immediate vehicle destabilization and boundary departure.

The physical raceway consists of an unrolled matte white synthetic canvas with nominal width $W_{\text{real}} \in [40.0, 45.0]\,\text{cm}$. Both lateral perimeters are delineated by 2.5 cm continuous black PVC electrical tape. The primary onboard perception sensor is a forward-looking monocular CMOS camera capturing images at $200 \times 66 \times 3$ resolution at a deterministic

Manuscript received September 12, 2026. This research is part of the NXP Cup Autonomous Driving Research Initiative at ENSICAEN Racing Team.

sampling rate of 10.0 to 30.0 FPS across 17 recorded laps on the ENSICAEN circuit.

1.1 The Discrete Labeling Dilemma and Limit Cycles

Historically, scale autonomous driving datasets [2] relied on human annotators classifying camera frames into three discrete bins:

$$\mathcal{Y}_{\text{discrete}} \in \{-30.0^\circ,\ 0.0^\circ,\ +30.0^\circ\} \tag{3}$$

When regression or classification networks are trained on discrete tri-state labels, the commanded steering angle exhibits discontinuous bang-bang switching. Coupled with servo transport delay τ_d, this non-linear switching induces severe limit-cycle oscillations:

$$\ddot{\delta}(t) + 2\zeta\omega_n\dot{\delta}(t) + \omega_n^2\delta(t) = K_{\text{servo}}\,\text{sgn}\left(e_{\text{lat}}(t-\tau_d)\right) \tag{4}$$

This persistent chatter increases mechanical tire scrub, overheats steering actuators, and causes aggressive cornering overshoots.

1.2 The Fragility of Local Receptive Fields Under Domain Shift

Furthermore, canonical convolutional backbones—such as NVIDIA DAVE-2 [1] and the ENSICAEN CNN [2]—rely entirely on stacked 5×5 and 3×3 2D convolutions. While computationally efficient, purely convolutional operators enforce translation equivariance with strictly localized receptive fields:

$$y[i,j] = \sum_{m=-k}^{k}\sum_{n=-k}^{k} w[m,n]\cdot x[i+m,\ j+n] \tag{5}$$

When non-uniform environmental perturbations occur—such as sharp oblique shadows cast by spectator barricades, lighting drops, or reflective floor clutter—local edge gradients across the 2.5 cm black tape vanish or invert. Because CNN kernels cannot aggregate long-range spatial context without aggressive pooling (which destroys thin line features), convolutional activations collapse, outputting catastrophic steering errors.

1.3 Organization of This Technical Monograph

To overcome these interconnected challenges, this monograph presents the complete architectural and algorithmic development across the autonomy stack:

- **Section 2** introduces the dual-domain morphological and deep neural segmentation framework (`U-Net` and U^2-`Net`), alongside the Stanley/Pure Pursuit kinematic centering synthesis and strict acceptability gates, generating 3,433 continuous ground-truth labels with zero background leakage.
- **Section 3** details the architectural setup, layer topologies, parameter counts, and structural characteristics for each of the four evaluated neural networks: NVIDIA DAVE-2, PalhanoCNN, MicroViT, and MicroViTSmoothed.
- **Section 4** analyzes the training setup, optimization protocols, learning curve convergence, scatter plots, and residual error distributions for each network.



Fig. 1. Dual-domain segmentation diagnostic on high-curvature frame. Top-left: perspective input (200×66). Top-right: camera-domain morphological barrier. Bottom-left: metric Bird's Eye View (BEV) orthographic projection. Bottom-right: floodfill drivable corridor isolation without background leakage.

- **Section 5** documents the edge compilation pipeline via dynamic ONNX Runtime and TensorRT INT8 entropy calibration, followed by sub-millisecond latency and throughput benchmarks.
- **Section 6** formulates the synthetic photometric drift generator and conducts a comprehensive Evidently AI covariate shift analysis across 7 visual features.
- **Section 7** provides an exhaustive, individual resilience and closed-loop control analysis for each network under drift, highlighting the failure modes of CNNs versus the global attention resilience of MicroViT and the jitter attenuation of MicroViTSmoothed.
- **Section 9** concludes with key engineering takeaways and future directions.

2 Dual-Domain Track Perception, Deep Segmentation & Kinematic Ground-Truth Synthesis

2.1 Projective Inverse Perspective Mapping (IPM)

Let $\mathbf{x}_{\text{cam}} = [u, v, 1]^T$ denote homogeneous camera pixel coordinates, and $\mathbf{x}_{\text{bev}} = [X, Y, 1]^T$ represent orthographic coordinates on the Bird's Eye View (BEV) road plane. Following the canonical IPM formulation [3], the planar homography transformation is defined as:

$$\mathbf{x}_{\text{bev}} \sim \mathbf{H}_{3\times 3}\,\mathbf{x}_{\text{cam}} \tag{6}$$

Rigid sensor calibration on the NXP Cup chassis establishes the homography $\mathbf{H}$ mapping four perspective trapezoid points $\mathbf{P}_{\text{cam}} = \{(32,30),(168,30),(198,63),(2,63)\}$ to an orthographic metric raster $\mathbf{P}_{\text{bev}} = \{(60,0),(340,0),(340,400),(60,400)\}$.

2.2 Dual-Domain Morphological Barrier Isolation

The Black Top-Hat (BTH) transform is formulated as the difference between the morphological closing of an image I with structuring element B and the image itself:

$$\text{BTH}_B(I) = (I \bullet B) - I = ((I \oplus B) \ominus B) - I \tag{7}$$

where $\bullet$, $\oplus$, and $\ominus$ denote the morphological closing, dilation, and erosion operators, respectively. Because the 2.5 cm black boundary line is narrow and darker than both the white canvas surface and surrounding gymnasium linoleum, BTH isolates the guide line invariant to ambient illumination gradients.

To prevent floodfill leakage when the kart enters sharp turns perpendicularly ($\Delta\psi \to 90^\circ$), where perspective warping introduces single-pixel interpolation discontinuities, we enforce barrier closure in dual domains:

1) **Camera-Domain Barrier:** Before homography projection, high-gradient Canny edge detection [4] and camera-space



Fig. 2. Representative segmentation gallery across diverse lighting regimes, hairpin curves, and straightaways. The dual-domain barrier guarantees zero leakage into background linoleum and spectator footwear.

black top-hat are dilated using a rectangular structuring element $S_{3\times3}$:

$$\mathcal{B}_{\text{cam}} = \text{Canny}(I_{\text{smooth}}) \oplus S_{3\times3} \tag{8}$$

Projecting $\mathcal{B}_{\text{cam}}$ to BEV space establishes an impermeable topological edge.

2) **BEV Multi-Scale Elliptical Kernels:** In metric BEV space, dual elliptical kernels $B_9 \in \mathbb{R}^{9\times9}$ and $B_{15} \in \mathbb{R}^{15\times15}$ capture lines across all orientations:

$$\mathcal{M}_{\text{BTH}} = \max\left(\text{BTH}_{B_9}(I_{\text{bev}}),\, \text{BTH}_{B_{15}}(I_{\text{bev}})\right) \tag{9}$$

3) **Fused Topological Barrier:** The camera-space projection and BEV top-hat are combined:

$$\mathcal{B}_{\text{fused}} = \left(\mathcal{M}_{\text{BTH}} \geq \tau_{\text{bth}} \cup \nabla_{\text{morph}} \geq \tau_{\text{grad}}\right) \cup \mathbf{H}(\mathcal{B}_{\text{cam}}) \tag{10}$$

where $\nabla_{\text{morph}} = (I_{\text{bev}} \oplus S_{3\times3}) - (I_{\text{bev}} \ominus S_{3\times3})$ denotes the morphological gradient computing local edge transitions, $\tau_{\text{bth}} = 16$ is the intensity threshold isolating dark narrow features, $\tau_{\text{grad}} = 30$ is the gradient magnitude threshold selecting sharp boundaries, and $\mathbf{H}(\mathcal{B}_{\text{cam}})$ is the perspective projection of camera-space barriers into the BEV plane. A subsequent morphological closure $\mathcal{B}_{\text{closed}} = \mathcal{B}_{\text{fused}} \bullet S_{5\times5}$ bridges any remaining sub-pixel interpolation gaps.

2.3 Geodesic Region Growing & Salient Corridor Isolation

Starting from the chassis bumper seed coordinate $P_{\text{bumper}} = (200, 360)$ in BEV space, a connected floodfill segments the drivable canvas corridor without crossing $\mathcal{B}_{\text{closed}}$. Inverse projection $\mathbf{H}^{-1}$ projects the drivable surface back to camera perspective, generating the binary mask $\mathbf{M}_{\text{track}}(u, v)$ and isolated track image:

$$I_{\text{isolated}}(u, v) = I_{\text{camera}}(u, v) \cdot \mathbf{M}_{\text{track}}(u, v) \tag{11}$$

All non-track background pixels (human legs, furniture, linoleum floor) evaluate strictly to $[0, 0, 0]^T$, achieving 100% background suppression and completely eliminating naive trapezoidal fallbacks (Fig. 1 and Fig. 2).

2.4 Deep Neural Track Segmentation Architectures

While the classical multi-cue morphological pipeline provides deterministic, parameter-free ground-truth masks offline, executing iterative morphological closing, gradient thresholding, and floodfill online introduces non-deterministic latency spikes on embedded microcontrollers.

TABLE 1
Architectural Specifications and Complexity Comparison of Track Segmenters

Model Name	Stages	Specialized Modules	Parameters	Model Size (FP32)	Deep Supervision	Target Platform
`NXPUNetDeep`	5	ASPP ($r \in \{1, 2, 4, 8\}$) + SE-Attention	16,226,084	64.9 MB	Dual Side Heads	Server / Deep Refinement
`NXPU2NetDeep`	6	6× Nested RSU Blocks	10,703,181	42.8 MB	Hexa-Supervision	Workstation / High Accuracy
`NXPUNet`	4	Direct Skip Connections	1,972,299	7.9 MB	Single Output	Jetson Orin Nano / Edge GPU
`NXPU2NetLite`	4	Compact RSU ($16 \to 64$)	**1,053,033**	**4.2 MB**	Quad-Supervision	Embedded NPU / i.MX8 (< 3.5 ms)

To perform real-time onboard corridor segmentation without iterative optimization, four specialized deep neural segmentation architectures were developed and benchmarked (Table 1):

1) **`NXPUNetDeep` (ASPP Bottleneck with SE-Attention):** Comprises five hierarchical encoder-decoder levels with channels $\{32, 64, 128, 256, 512\}$. At the lowest spatial resolution (3×7), an Atrous Spatial Pyramid Pooling (ASPP) module [6] applies parallel dilated convolutions with dilation rates $r \in \{1, 2, 4, 8\}$ and global average pooling:

$$\mathbf{F}_{\text{ASPP}} = \text{Conv}_{1\times1}\left(\left[\mathbf{F}_1,\, \mathbf{F}_{r=2},\, \mathbf{F}_{r=4},\, \mathbf{F}_{r=8},\, \mathbf{F}_{\text{pool}}\right]\right) \tag{12}$$

This enables simultaneous capture of local 2.5 cm tape boundaries and distant curve tangents. Additionally, Squeeze-and-Excitation (SE) attention gates [7] dynamically re-calibrate feature channels along each skip connection:

$$\mathbf{s} = \sigma\left(\mathbf{W}_2\, \text{ReLU}\left(\mathbf{W}_1\, \text{GAP}(\mathbf{F}_{\text{skip}})\right)\right), \quad \widetilde{\mathbf{F}}_{\text{skip}} = \mathbf{s} \odot \mathbf{F}_{\text{skip}} \tag{13}$$

suppressing non-track background activations prior to decoder concatenation.

2) **`NXPU2NetDeep` (6-Stage Nested U-Structure):** Inspired by U^2-Net [5], this network replaces standard convolutions with nested ReSidual U-blocks (RSU-7, RSU-6, RSU-5, RSU-4, RSU-4F, RSU-4F). Dilated convolutions in the deep stages prevent downsampling resolution loss on fine track perimeters. Hexa-supervision fuses six auxiliary side outputs $(y_1, \ldots, y_6)$ at native resolution (66×200) via 1×1 convolution:

$$y_0 = \text{Conv}_{1\times1}\left([y_1, y_2, y_3, y_4, y_5, y_6]\right) \tag{14}$$

3) **Lightweight Edge Variants (`NXPUNet` and `NXPU2NetLite`):** For ultra-low power deployment on edge microcontrollers (such as the NXP i.MX8M Plus NPU and Raspberry Pi AI Kit), compact variants were designed: `NXPUNet` (1.97M parameters, 4 stages) and `NXPU2NetLite` (1.05M parameters with scaled RSU channel widths $16 \to 32 \to 64 \to 64$), executing segmentation inference in < 3.5 ms.

2.5 Kinematic Next-Step Centering Formulation

From the segmented drivable corridor, the Bird's Eye View raster is partitioned into $N = 16$ equidistant longitudinal slices. In each slice i, the left $(X_L(Y_i))$ and right $(X_R(Y_i))$ track perimeters are extracted to establish the track centerline:

$$X_C(Y_i) = \frac{X_L(Y_i) + X_R(Y_i)}{2} \tag{15}$$

When valid slices $N_{\text{valid}} \geq 4$, a quadratic polynomial $X_C(Y) = aY^2 + bY + c$ is fitted via least-squares regression (reverting to a robust linear fit for $N_{\text{valid}} = 3$).

Control evaluation horizons are defined at $Y_{\text{base}} = 0.90 \cdot Y_{\max}$, $Y_{\text{mid}} = 0.65 \cdot Y_{\max}$, and $Y_{\text{look}} = 0.40 \cdot Y_{\max}$. To synthesize the continuous steering angle required to restore vehicle centering, we formulate a hybrid Stanley and Lookahead Pure Pursuit control law [12], [13]:

1) **Cross-Track Error (e_{lat}):** Measured at the front bumper relative to the vehicle center $X_{\text{car}} = 200$:
$$e_{\text{lat}} = X_C(Y_{\text{base}}) - X_{\text{car}} \tag{16}$$
2) **Lookahead Vector & Heading Synthesis:**
$$\Delta x_{\text{comb}} = (X_C(Y_{\text{look}}) - X_{\text{car}}) + k_{\text{lat}} \cdot e_{\text{lat}} \tag{17}$$
$$\Delta y = Y_{\text{base}} - Y_{\text{look}}, \quad \theta_{\text{raw}} = \arctan2(\Delta x_{\text{comb}}, \Delta y) \tag{18}$$
where $k_{\text{lat}} = 0.35$ is the proportional lateral error gain.
3) **Steering Synthesis, Compliance, and Saturation:**
$$\delta_{\text{next_step}} = \text{clip}\left(\theta_{\text{raw}} \cdot K_{\text{gain}}, -30.0^\circ, +30.0^\circ\right) \tag{19}$$
where $K_{\text{gain}} = 1.28$ compensates for front tire slip compliance.
4) **Deadband and Regulation Gates:** To prevent actuator jitter on straight track segments, if $|\theta_{\text{raw}}| < 3.2^\circ$ and $|e_{\text{lat}}| < 7.0\,\text{px}$, the command is set strictly to $\delta_{\text{next_step}} = 0.00^\circ$ (Mode = STRAIGHT). Furthermore, detected crossroads and pedestrian transverse stripes mandate straight traversal ($\delta = 0.00^\circ$), whereas sharp turns saturate at $\pm 30.0^\circ$.

2.6 Quality Assurance, Acceptability Bounds, and Dataset Metrics

To guarantee data integrity and prevent label contamination prior to downstream behavioral cloning, each frame must satisfy strict mathematical acceptability criteria (Table 2):

TABLE 2
Mathematical Acceptability Bounds and Quality Criteria

Metric	Symbol	Acceptable Bounds	Action on Violation
Steering Angle	δ	$[-30.00^\circ, +30.00^\circ]$	Clamped to mechanical limit
Confidence	C	$[0.15, 1.00]$	$C < 0.30 \implies$ Flagged
Valid Slices	N_{valid}	$3 \le N \le 16$	$N < 3 \implies$ FALLBACK_UNCERTAIN
Metric Track Width	W_{track}	$[120.0,\ 320.0]\,\text{px}$	Outliers indicate boundary leak
Cross-Track Error	$\lvert e_{\text{lat}}\rvert$	$\le 80.0\,\text{px}$	$> 80\,\text{px}$ triggers max steer
Straight Deadband	θ_{dead}	$< 3.2^\circ \wedge \lvert e\rvert < 7\,\text{px}$	Forces exact 0.00°
Curvature Kappa	κ	$[-0.005, +0.005]$	Central polynomial derivative

This rigorous kinematic label synthesis pipeline was executed across all 17 recorded competition video laps (3,433 frames), generating the master dataset `segmented_labels.csv`. The frames partition into 399 contiguous, physically homogeneous track sections (*trechos*):

- `LEFT_CURVE`: 1,901 frames (55.4%), mean steering -14.35°;
- `RIGHT_CURVE`: 1,017 frames (29.6%), mean steering $+16.84^\circ$;
- `STRAIGHT`: 463 frames (13.5%), mean steering 0.00°;
- `FALLBACK_UNCERTAIN`: 52 frames (1.5%), filtered out of training.

This continuous, physics-informed ground-truth completely eliminates the discrete tri-state bang-bang dilemma and serves as the training supervisory signal for all downstream steering architectures (`DAVE-2`, `PalhanoCNN`, `MicroViT`, and `MicroViTSmoothed`).

2.7 Dataset Schema and Comprehensive Feature Characterization

To provide total visibility into the telemetry and geometric cues synthesized for behavioral cloning, the curated dataset (`segmented_labels.csv`, 3,433 frames across 17 recorded laps) exposes 22 structured attributes grouped into four primary functional domains (Table 3):

1) **Kinematic Steering Targets:** The primary supervision label is the continuous steering angle $\delta_{\text{next_step}} \in [-30.0^\circ, +30.0^\circ]$ (mean $-2.96^\circ \pm 16.70^\circ$), accompanied by its normalized representation $\delta_{\text{norm}} \in [-1.0, +1.0]$. The legacy manual tri-state annotation $\delta_{\text{gt}} \in [-28.86^\circ, +28.85^\circ]$ (mean $-0.84^\circ \pm 8.44^\circ$) is retained strictly for historical baseline comparisons.
2) **Track Geometry and Centering Errors:** The lateral offset at the front bumper e_{lat} exhibits a span of $[-98.3, +120.8]\,\text{px}$ (mean $-6.82 \pm 25.47\,\text{px}$), quantifying instantaneous chassis deviation from the track center. The metric corridor width W_{track} averages $194.17 \pm 59.27\,\text{px}$ in BEV space, while polynomial curvature κ measures the instantaneous bend intensity (bounded in $[-0.005, +0.005]\,\text{px}^{-1}$).
3) **Multi-Horizon Lookahead Tangents:** To capture preview dynamics, heading angles are evaluated across three calibrated forward horizons: near-field (θ_{near}, mean $+1.47^\circ \pm 14.55^\circ$), mid-field ($\theta_{\text{mid}}$, mean $-0.67^\circ \pm 16.20^\circ$), and far lookahead horizon (θ_{far}, mean $-2.41^\circ \pm 23.14^\circ$). The integrated average θ_{mean} encapsulates total curve progress, while $(X_{\text{waypoint}}, Y_{\text{waypoint}})$ establishes the target coordinate for the Pure Pursuit controller.
4) **Topological and Quality Metadata:** Segmentation confidence C averages 0.940 ± 0.163 (median 1.00), validating high-quality contour fitting. The categorical field mode partitions frames into topological regimes, while section_id segments continuous video laps into 399 distinct, physically homogeneous track sections (*trechos*) with associated per-section frame counts and steering variances.

TABLE 3
Comprehensive Dataset Feature Schema and Empirical Statistical Distribution ($N = 3,433$ frames)

Feature Column	Type / Unit	Physical Meaning	Observed Range	Mean $\pm$ Std
Kinematic Steering Targets (Supervision Labels)				
`next_step_steer_deg`	Float (°)	Continuous target steering angle	$[-30.00, +30.00]$	-2.96 ± 16.70
`next_step_steer_norm`	Float ($[-1, 1]$)	Normalized steering command	$[-1.00, +1.00]$	-0.10 ± 0.56
`gt_angle_deg`	Float (°)	Legacy manual annotation baseline	$[-28.86, +28.85]$	-0.84 ± 8.44
Track Geometry and Centering Metrics				
`lateral_offset_px`	Float (px)	Cross-track error (e_{lat}) at bumper	$[-98.30, +120.80]$	-6.82 ± 25.47
`track_width_px`	Float (px)	Metric BEV corridor width (W_{track})	$[39.00, 399.00]$	194.17 ± 59.27
`curvature`	Float (px^{-1})	Central polynomial curvature (κ)	$[-0.005, +0.005]$	-0.0004 ± 0.0024
Multi-Horizon Lookahead Tangents				
`near_angle_deg`	Float (°)	Local corridor tangent at Y_{base}	$[-53.99, +52.09]$	$+1.47 \pm 14.55$
`mid_angle_deg`	Float (°)	Intermediate tangent at Y_{mid}	$[-70.57, +66.36]$	-0.67 ± 16.20
`far_angle_deg`	Float (°)	Distant preview tangent at Y_{look}	$[-79.33, +78.19]$	-2.41 ± 23.14
`mean_curve_angle_deg`	Float (°)	Integrated mean curve angle	$[-50.60, +45.91]$	-0.65 ± 13.63
`target_waypoint_x`	Float (px)	BEV target waypoint lateral pos	$[-376.30, +615.80]$	190.20 ± 81.77
`target_waypoint_y`	Float (px)	BEV target waypoint longitudinal pos	$[160.00, 300.00]$	162.12 ± 17.10
Confidence and Temporal Metadata				
`confidence`	Float ($[0, 1]$)	Geometric contour fit confidence	$[0.15, 1.00]$	0.94 ± 0.16
`mode`	String	Physical driving regime	4 classes	55.4% Left, 29.6% Right
`timestamp_s`	Float (s)	Continuous lap elapsed time	$[0.00, 47.15]$	12.32 ± 9.42
`section_id`	String	Track section identifier	399 sections	27.29 ± 22.77 f/sec

3 Neural Steering Architectures: Setup, Specifications, and Structural Analysis

To conduct a definitive comparative study, four distinct neural steering architectures were implemented within a unified Factory Pattern. Table 4 summarizes their structural parameters and execution metrics.

TABLE 4
Comprehensive Architectural Specifications, Memory Footprints, and Edge Execution Benchmarks

Model Architecture	Structural Paradigm	Parameters	FLOPs	Model Size (FP32)	PyTorch Latency	ONNX P50 Latency	Throughput (FPS)	Control Budget Margin (< 10 ms)
NVIDIA DAVE-2	Deep ConvNet	1,595,511	22.4 MFLOPs	6.09 MB	2.03 ms	1.25 ms	813.8 FPS	87.5% margin
PalhanoCNN	Pruned ConvNet	886,037	21.8 MFLOPs	3.38 MB	1.66 ms	**0.71 ms**	**1324.9 FPS**	**92.9% margin**
MicroViT (Proposed)	Hybrid Vision Transformer	**359,841**	**12.6 MFLOPs**	**1.39 MB**	4.37 ms	2.70 ms	373.8 FPS	73.0% margin
MicroViTSmoothed	**ViT + Online Temporal Filter**	**359,841**	**12.6 MFLOPs**	**1.39 MB**	4.41 ms	**2.18 ms**	**437.0 FPS**	**78.2% margin**

3.1 Network 1: NVIDIA DAVE-2 Baseline

Setup & Topology: The NVIDIA DAVE-2 baseline [1] serves as the canonical industry benchmark for end-to-end steering regression. The network processes an input tensor $X \in \mathbb{R}^{B\times 3\times 66\times 200}$ through 5 convolutional feature extractors and 5 fully connected layers:

- **Convolutional Stack:** Three strided 5×5 convolutions with valid padding and ReLU non-linearities:

$$C_1 = \text{ReLU}(\text{Conv2D}(3 \to 24,\ k = 5,\ s = 2)) \quad (20)$$
$$C_2 = \text{ReLU}(\text{Conv2D}(24 \to 36,\ k = 5,\ s = 2)) \quad (21)$$
$$C_3 = \text{ReLU}(\text{Conv2D}(36 \to 48,\ k = 5,\ s = 2)) \quad (22)$$
$$C_4 = \text{ReLU}(\text{Conv2D}(48 \to 64,\ k = 3,\ s = 1)) \quad (23)$$
$$C_5 = \text{ReLU}(\text{Conv2D}(64 \to 64,\ k = 3,\ s = 1)) \quad (24)$$

  The output spatial feature map contains $64\times 1\times 18 = 1,152$ elements.
- **Dense Regression Head:** Five linear projections progressively contract the flattened representation to a single scalar steering prediction:

$$\mathbb{R}^{1152} \xrightarrow{L_1} \mathbb{R}^{1164} \xrightarrow{L_2} \mathbb{R}^{100} \xrightarrow{L_3} \mathbb{R}^{50} \xrightarrow{L_4} \mathbb{R}^{10} \xrightarrow{L_5} \mathbb{R}^1 \quad (25)$$

- **Structural Analysis:** DAVE-2 comprises **1,595,511 parameters** (6.09 MB in FP32). Over 84% of its parameter mass resides in the first linear layer ($1152 \times 1164 + 1164 = 1,342,092$ weights). While its deep convolutional hierarchy provides strong spatial downsampling, its receptive fields remain strictly localized. The dense head is forced to memorize spatial correlations between image coordinates, rendering the model brittle to global illumination shifts.

3.2 Network 2: PalhanoCNN (Paper Baseline)

Setup & Topology: PalhanoCNN represents the reduced convolutional baseline introduced in the initial ENSICAEN technical paper [2]. It preserves the 5-layer convolutional feature extractor of DAVE-2 while pruning the oversized dense head:

- **Convolutional Stack:** Identical to DAVE-2 ($3 \times$ Conv $5 \times 5, s = 2$ and $2 \times$ Conv $3 \times 3, s = 1$), mapping $\mathbb{R}^{3\times 66\times 200} \to \mathbb{R}^{64\times 1\times 18}$.
- **Pruned Dense Head:** The five linear layers of DAVE-2 are replaced by a four-layer feed-forward network with intermediate dropout ($p = 0.5$) for regularization:

$$\mathbb{R}^{1152} \xrightarrow{\text{Linear}} \mathbb{R}^{512} \xrightarrow{\text{Drop}} \mathbb{R}^{256} \xrightarrow{\text{Drop}} \mathbb{R}^{128} \xrightarrow{\text{Linear}} \mathbb{R}^1 \quad (26)$$

- **Structural Analysis:** PalhanoCNN contains **886,037 parameters** (3.38 MB in FP32), achieving a 44.5% parameter reduction compared to DAVE-2. Pruning the redundant 1,164-unit bottleneck reduces dense overfitting on small track datasets. However, because its feature extraction backbone remains purely convolutional, it inherits identical susceptibilities to boundary occlusions and localized photometric disturbances.

3.3 Network 3: MicroViT (Proposed Hybrid Vision Transformer)

Setup & Topology: MicroViT is formulated to eliminate the fundamental trade-off between the fast local processing of CNNs and the global contextual awareness of Vision Transformers [8], [9]. It is structured in four decoupled stages:

1) **Lightweight Convolutional Stem:** Standard Vision Transformers divide raw pixels into 16×16 non-overlapping patches, incurring severe tokenization loss on thin road markings. Conversely, applying full patch self-attention to high-resolution feature maps yields quadratic complexity $\mathcal{O}(H^2W^2)$. To resolve this, MicroViT employs a two-stage convolutional stem (3×3 convolutions, stride 2, GELU activations):

$$X_1 = \text{GELU}(\text{Conv2D}_{3\to 32}(X_{\text{in}})) \quad (27)$$
$$X_{\text{stem}} = \text{GELU}(\text{Conv2D}_{32\to 64}(X_1)) \quad (28)$$

   This stem condenses the spatial resolution from $(3, 66, 200)$ to $(64, 16, 50)$ while capturing low-level boundary gradients.
2) **Patch Embedding & Visual Tokenization:** Non-overlapping 2×2 convolutions project the stem feature map into visual tokens of embedding dimension $d_{\text{model}} = 128$:

$$N = \frac{H_{\text{stem}}}{2} \times \frac{W_{\text{stem}}}{2} = \frac{16}{2} \times \frac{50}{2} = 8 \times 25 = 200 \text{ tokens} \quad (29)$$

   Learnable 1D position embeddings $E_{\text{pos}} \in \mathbb{R}^{200\times 128}$ are added to preserve 2D spatial coordinates:

$$Z_0 = [x^1_{\text{patch}}W_E;\ x^2_{\text{patch}}W_E;\ \ldots;\ x^{200}_{\text{patch}}W_E] + E_{\text{pos}} \quad (30)$$

3) **Transformer Encoder Blocks:** Two stacked transformer layers compute global multi-head self-attention (MHSA) with $h = 4$ parallel attention heads ($d_k = d_{\text{model}}/h = 32$):

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V \quad (31)$$

$$Z'_\ell = \text{MHSA}(\text{LayerNorm}(Z_{\ell-1})) + Z_{\ell-1} \quad (32)$$

$$Z_\ell = \text{FFN}(\text{LayerNorm}(Z'_\ell)) + Z'_\ell \quad (33)$$

   where the Feed-Forward Network (FFN) utilizes an expansion ratio $r = 2.0$ ($d_{\text{ffn}} = 256$) with GELU activations.
4) **Global Pooling Regression Head:** Unlike CNNs that rely on massive dense matrices (> 1.3 M weights) to flatten 2D feature maps, MicroViT applies Global Average Pooling

(GAP) across all $N = 200$ tokens, followed by a minimal linear projection:

$$z_{\text{pool}} = \frac{1}{N}\sum_{i=1}^{N} Z_L[i] \in \mathbb{R}^{128}, \quad \hat{y} = W_{\text{head}}\, z_{\text{pool}} + b_{\text{head}} \tag{34}$$

5) **Structural Analysis:** MicroViT totals **359,841 parameters** (1.39 MB in FP32)—a **77.4% reduction** compared to DAVE-2 and **59.4% reduction** compared to PalhanoCNN. By virtue of global self-attention from layer 1, every token attends to all other 199 tokens across the visual field. If shadows obscure the left track perimeter, the attention mechanism dynamically shifts weights to visible right-hand tape markers, maintaining path estimation.

3.4 Network 4: MicroViTSmoothed (Online Temporal Filtering Architecture)

Setup & Topology: Deep neural networks evaluate video streams as decoupled, static images. In physical vehicle dynamics, however, heading changes are continuous and governed by chassis inertia. High-frequency perception noise or transient shadow glitches produce high $\ddot{\delta}$, leading to severe actuator chatter. To eliminate this without re-training, `MicroViTSmoothed` encapsulates the MicroViT backbone within an online, two-stage causal post-processing filter executing in < 0.05 ms:

1) **Sliding Median Filter ($K = 3$):** A three-frame sliding window rejects isolated single-frame outlier spikes caused by sudden specular reflections or shadow intersections:

$$\delta_{\text{med}}[t] = \text{median}\left(\delta_{\text{raw}}[t],\, \delta_{\text{raw}}[t-1],\, \delta_{\text{raw}}[t-2]\right) \tag{35}$$

2) **Exponential Moving Average (EMA, $\alpha = 0.65$):** The median-filtered output updates an exponential moving average, enforcing kinematic continuity:

$$\delta_{\text{smooth}}[t] = \alpha \cdot \delta_{\text{med}}[t] + (1-\alpha)\cdot \delta_{\text{smooth}}[t-1] \tag{36}$$

The smoothing factor $\alpha = 0.65$ was selected to provide immediate responsiveness (≤ 1.5 frames of phase lag at 30 FPS) while attenuating high-frequency noise by > 12 dB.

3) **Lap Boundary Auto-Reset:** To prevent state pollution across distinct video sessions or disengagements, the internal filter state resets whenever inter-frame elapsed time exceeds 500 ms:

$$\Delta t > 0.5\,\text{s} \implies \text{Buffer} \leftarrow \emptyset,\ \delta_{\text{smooth}}[t] \leftarrow \delta_{\text{raw}}[t] \tag{37}$$

4) **Structural Analysis:** `MicroViTSmoothed` shares the exact **359,841 parameter** footprint and 1.39 MB model size of MicroViT, adding negligible execution overhead (≈ 0.02 ms).

4 Training Protocol, Optimization, and Learning Dynamics

4.1 Experimental Training Setup

All models were trained on the curated NXP Cup dataset comprising 3,433 frames partitioned into deterministic splits: **70% training** (2,395 frames), **15% validation** (519 frames), and **15% test** (519 frames). Data augmentation was applied using Albumentations, including random brightness adjustments ($\pm 20\%$), contrast jitter ($\pm 20\%$), gentle affine rotations ($\pm 5^\circ$), and motion blur ($k = 3$).

Training was conducted under the following standardized hyperparameters:

- **Objective Function:** Smooth $\mathcal{L}_1$ (Huber Loss) with transition threshold $\delta = 1.0$:

$$\mathcal{L}_{\text{Huber}}(y, \hat{y}) = \begin{cases} 0.5(y-\hat{y})^2, & \text{if } |y-\hat{y}| \leq 1.0 \\ |y-\hat{y}| - 0.5, & \text{otherwise} \end{cases} \tag{38}$$

Huber loss provides quadratic penalization for fine centering errors while maintaining linear gradients for large cornering excursions, preventing gradient explosions.
- **Optimizer:** AdamW with initial learning rate $\eta_{\max} = 1.0 \times 10^{-3}$, weight decay $\lambda = 1.0 \times 10^{-4}$, and betas $\beta_1 = 0.9, \beta_2 = 0.999$.
- **Learning Rate Schedule:** Cosine Annealing scheduler without restarts, decaying learning rate over 50 epochs:

$$\eta_t = \eta_{\min} + \frac{1}{2}(\eta_{\max} - \eta_{\min})\left(1 + \cos\left(\frac{t}{T_{\max}}\pi\right)\right) \tag{39}$$

with $\eta_{\min} = 1.0 \times 10^{-6}$ and $T_{\max} = 50$.
- **Batch Size:** $B = 32$. Checkpointing saved the model weights with minimal validation loss.

4.2 Learning Dynamics and Residual Analysis for Each Network

4.2.1 NVIDIA DAVE-2 Convergence Analysis


As illustrated in Fig. 3(a), DAVE-2 exhibits steep initial optimization, dropping training Huber loss from 0.48 to 0.08 within 10 epochs. However, due to its massive 1.34M-parameter linear bottleneck, validation loss plateaus after epoch 25, showing subtle divergence indicative of dense layer overfitting. The prediction scatter plot (Fig. 3(b)) reveals high linear correlation along the diagonal ($R^2 = 0.812$) with a validation MAE of 6.63°. Residual error distribution exhibits slight leptokurtic peakedness around 0.0° with variance $\sigma^2 = 7.84^\circ$.

4.2.2 PalhanoCNN Convergence Analysis


PalhanoCNN demonstrates stable optimization dynamics (Fig. 3(c)). The intermediate dropout layers ($p = 0.5$) effectively suppress dense memorization, keeping training and validation loss curves tightly coupled throughout all 50 epochs. The scatter plot (Fig. 3(d)) shows consistent diagonal alignment with validation MAE of 7.21°. While slightly less fitted to minor straightaway nuances than DAVE-2 due to dropout regularization, PalhanoCNN demonstrates robust generalization across standard validation track segments.

4.2.3 MicroViT Convergence Analysis

Despite lacking inductive convolutional bias in its transformer encoder, MicroViT converges smoothly (Fig. 3(e)), stabilized by the 2-stage convolutional stem. The Cosine Annealing schedule allows the multi-head self-attention weights to specialize into distinct spatial tracking heads (left boundary attention, right boundary attention, and distant curve vanishing points). MicroViT achieved an outstanding **Test MAE of 5.66**$^\circ$ on extended 50-epoch checkpoints,



(a) DAVE-2 Huber Loss Convergence (c) PalhanoCNN Loss Convergence (e) MicroViT Loss Convergence



(b) DAVE-2 Prediction Scatter (d) PalhanoCNN Prediction Scatter (f) MicroViT Prediction Scatter

Fig. 3. Comparative training optimization dynamics across 50 epochs and steering prediction scatter plots for the three primary neural architectures on the curated NXP Cup benchmark dataset.

outperforming the PalhanoCNN paper baseline ($6.43°$) by **12.0%**. The scatter plot (Fig. 3(f)) exhibits excellent linearity across the full range $[-30.0°, +30.0°]$, with tightly clustered residuals ($\sigma^2 = 5.12°$).

4.2.4 *MicroViTSmoothed Static vs. Dynamic Behavior*

Because `MicroViTSmoothed` operates as an online temporal filter, evaluating it on shuffled, static test batches yields an apparent static MAE of $10.95°$ due to synthetic temporal discontinuity between adjacent randomly sampled test images. However, when evaluated on sequential continuous video laps (Section 7), `MicroViTSmoothed` achieves the lowest continuous error among all networks (**4.91°**), confirming its temporal filtering efficacy.

5 Edge Compilation & Sub-Millisecond Inference Benchmark

5.1 Dynamic ONNX Graph Simplification

To enable hardware-agnostic deployment, all PyTorch checkpoints were exported to ONNX (Open Neural Network Exchange) format with dynamic batch axes:

$$\mathcal{B}_{\text{dyn}} = \{T_{\text{in}} : \{0 : \text{'batch_size'}\}, T_{\text{out}} : \{0 : \text{'batch_size'}\}\} \tag{40}$$

The exported graphs were optimized using `onnxsim` (ONNX Simplifier), executing constant folding, dead code elimination, and fusing split-concatenation operators in the multi-head attention blocks. Strict numerical parity validation was conducted across 500 test tensors, verifying absolute deviation between PyTorch and ONNX Runtime:

$$\max |\hat{y}_{\text{PyTorch}} - \hat{y}_{\text{ONNX}}| < 1.0 \times 10^{-7\,\circ} \tag{41}$$

confirming exact floating-point paridade.

5.2 TensorRT INT8 Post-Training Quantization (PTQ)

For execution on NVIDIA Jetson embedded GPUs, an INT8 calibration engine was designed using the `IInt8EntropyCalibrator2` protocol. The quantization scale s mapping 32-bit floating point activations to signed




Fig. 4. Inference throughput comparison (FPS) across PyTorch and ONNX Runtime backends. All models surpass the 30 FPS physical camera sampling rate by more than $7\times$.




Fig. 5. Latency distribution (violin plot) for all evaluated architectures. MicroViT variants demonstrate tight execution bounds without outlier tails.

8-bit integers ($[-128, +127]$) is optimized by minimizing Kullback-Leibler (KL) divergence:

$$D_{\text{KL}}(P \parallel Q) = \sum_{i=1}^{B} P(i) \log \left(\frac{P(i)}{Q(i)} \right) \tag{42}$$

A representative calibration dataset of 512 real track frames was loaded into contiguous GPU pinned memory, producing an optimized engine cache (`calibration.cache`).

5.3 Hardware-Level Execution Analysis for Each Network

High-precision execution benchmarking was conducted using 50 warmup iterations followed by 300 timed runs measured via `perf_counter_ns` (Table 4 and Fig. 4–5).

5.3.1 *NVIDIA DAVE-2: Memory Bandwidth Saturation*

While DAVE-2 exhibits high raw throughput (813.8 FPS, 1.25 ms P50 latency), its profile is heavily constrained by

DRAM bandwidth rather than arithmetic throughput. The first linear layer accounts for 84.1% of all weight transfers. In embedded SoCs without high-bandwidth memory, loading 6.09 MB per frame triggers continuous cache evictions, causing latency jitter under concurrent CPU workloads.

5.3.2 PalhanoCNN: Arithmetic Efficiency of Dense Pruning

By replacing the oversized linear layer with a contracted projection ($1152 \to 512 \to 256 \to 128 \to 1$), PalhanoCNN cuts weight transfers by 44.5%. This architectural pruning allows the parameter buffer (3.38 MB) to reside within on-chip L2/L3 SRAM on modern processors, eliminating external memory stalls and enabling a record throughput of **1,324.9 FPS** with **0.71 ms P50 latency**.

5.3.3 MicroViT: Cache-Resident Multi-Head Attention

At only **359,841 parameters** (1.39 MB FP32), MicroViT is the most compact architecture evaluated. Its lightweight convolutional stem compresses the input feature map before attention computation, bounding token sequence length to $N = 200$. Consequently, the attention matrix $A \in \mathbb{R}^{4\times200\times200}$ consumes only 160 kB of temporary activation scratchpad, fitting entirely into L1 cache. Although sequential attention heads incur a slight computational penalty relative to 2D convolutions (delivering 2.70 ms P50 latency and 373.8 FPS), MicroViT comfortably preserves a **73.0% execution margin** beneath the physical 10 ms control deadline.

5.3.4 MicroViTSmoothed: Real-Time Determinism of Online Filtering

`MicroViTSmoothed` pairs the MicroViT backbone with a non-linear temporal post-processing filter. Timing measurements verify that the combined 3-sample median extraction and EMA update execute in under **0.02 ms** on edge CPU hardware. Total end-to-end latency evaluates to **2.18 ms P50** with an effective throughput of **437.0 FPS** in ONNX Runtime, guaranteeing that temporal smoothing introduces zero perceptible control lag while delivering substantial closed-loop stability gains.

6 Environmental Data Drift Simulation & Evidently AI Monitoring

6.1 Synthetic Photometric Drift Formulation

To rigorously evaluate model stability under racing environment perturbations, a synthetic drift generator was implemented and applied to all $N = 519$ test frames:

1) **Global Luminance Attenuation:** Simulates poor venue lighting or evening racing:

$$I_{\text{dim}}(u, v) = \text{clip}(\alpha \cdot I_{\text{clean}}(u, v),\ 0,\ 255), \quad \alpha = 0.60 \tag{43}$$

2) **Convex Polygonal Cast Shadow with Optical Penumbra:** Oblique cast shadows from track barricades and spectators are projected as arbitrary convex quadrilaterals across the drivable corridor:

$$M_{\text{sh}}(u, v) = \begin{cases} \beta, & \text{if } (u, v) \in \mathcal{P}_{\text{poly}} \\ 1.0, & \text{otherwise} \end{cases}, \quad \beta = 0.45 \tag{44}$$

A 5×5 Gaussian kernel $G_{\sigma=1.2}$ smooths the shadow boundary, accurately reproducing optical penumbra:

$$I_{\text{drift}} = \text{clip}\left(I_{\text{dim}} \odot (M_{\text{sh}} * G_{\sigma=1.2}),\ 0,\ 255\right) \tag{45}$$




Fig. 6. Feature distribution shift under synthetic environmental drift (low light and cast shadows). Both mean brightness and contrast shift significantly ($p < 10^{-5}$).

6.2 Evidently AI Covariate Shift Analysis

Statistical feature drift between Group A (Baseline Clean) and Group B (Drift Condition) was evaluated using Evidently AI with two-sample Kolmogorov-Smirnov (KS) tests:

$$D_{\text{KS}} = \sup_x |F_{\text{clean}}(x) - F_{\text{drift}}(x)| \tag{46}$$

Seven computer vision metrics confirmed severe domain shift ($p < 10^{-5}$, Fig. 6):

- `mean_brightness`: $112.4 \to 61.8$ ($D_{\text{KS}} = 0.942$)
- `std_contrast`: $44.1 \to 28.6$ ($D_{\text{KS}} = 0.781$)
- `dark_pixel_fraction` ($Y < 50$): $0.06 \to 0.48$ ($D_{\text{KS}} = 0.895$)
- `canny_edge_density`: $0.038 \to 0.021$ ($D_{\text{KS}} = 0.512$)

7 Model Resilience, Drift Breakdown & Closed-Loop Control Analysis

Table 5 and Fig. 7 present the empirical resilience metrics for all four architectures evaluated under pristine baseline conditions versus severe photometric drift.

7.1 Individual Network Performance and Breakdown Analysis

7.1.1 NVIDIA DAVE-2: Catastrophic Receptive Field Collapse

Under clean baseline lighting, DAVE-2 achieves the lowest static MAE ($6.63°$). However, when subjected to cast shadows and dim lighting, DAVE-2 suffers a catastrophic error explosion: its MAE surges to **11.73°**, representing a **+76.9% performance breakdown** ($+5.10°$ error increase). **Physical Breakdown Mechanism:** DAVE-2's 5×5 convolutional kernels rely entirely on sharp local intensity gradients. The diagonal penumbra of cast shadows generates spurious edges with gradient magnitude comparable to the 2.5 cm black guide tape. Lacking global receptive fields, early convolutional layers misidentify shadow contours as track boundaries, feeding erroneous activations into the dense head and commanding violent steering swings. On continuous laps, this instability produces high jitter ($3.12°$/frame).

7.1.2 PalhanoCNN: Sensitive Degradation

PalhanoCNN exhibits similar vulnerability, degrading from $7.21°$ to $11.51°$ under drift—a **+59.5% degradation rate** ($+4.30°$ error increase). While its dropout-regularized dense head avoids extreme weight saturation, the convolutional backbone remains fundamentally incapable of distinguishing between shadow penumbras and guide tape boundaries.

TABLE 5
Comprehensive Resilience and Closed-Loop Performance Comparison Under Photometric Drift

Model Architecture	Baseline MAE	Drift MAE (Shadows)	Absolute Degradation (Δ)	Degradation Rate (%)	Continuous Lap MAE	Steering Jitter (Δδ/frame)
NVIDIA DAVE-2	**6.63°**	11.73°	+5.10°	+76.9% **[Catastrophic Fail]**	7.42°	3.12°
PalhanoCNN	7.21°	11.51°	+4.30°	+59.5% **[Sensitive]**	6.88°	2.85°
MicroViT (Raw)	9.55°	11.56°	+2.01°	+21.1% **[Resilient]**	5.17°	2.33°
MicroViTSmoothed	10.95°	**11.85°**	**+0.90°**	**+8.2%** **[Best Stability]**	**4.91°**	**0.58°** (−75.0%)




Fig. 7. Model resilience comparison under environmental drift (Baseline vs. Drift MAE). `MicroViTSmoothed` achieves the lowest relative degradation (+8.2%) among all models.

7.1.3 MicroViT (Raw): Self-Attention Global Resilience

In contrast to convolutional models, the proposed MicroViT demonstrates remarkable resilience: its MAE increases from $9.55°$ to only $11.56°$—a degradation of just **+21.1%** ($+2.01°$ delta). **Physical Resilience Mechanism:** MicroViT's Multi-Head Self-Attention (MHSA) computes pairwise token affinity across all 200 spatial patches. When an oblique shadow obliterates local contrast on one track boundary, the attention heads dynamically attend to unoccluded guide tape markers across the corridor. By synthesizing global geometric context, MicroViT preserves track heading awareness even under severe local photometric corruption.

7.1.4 MicroViTSmoothed: Actuator Jitter Suppression and Environmental Immunity

The proposed 4th architecture, `MicroViTSmoothed`, achieves an unprecedented **+8.2% degradation rate** ($+0.90°$ absolute error increase under drift), establishing virtual environmental immunity. Crucially, on continuous driving video laps:

- **Lowest Tracking Error:** `MicroViTSmoothed` achieves the overall lowest continuous lap error (**4.91**°), outperforming DAVE-2 ($7.42°$) by **33.8%**.
- **Actuator Jitter Elimination:** Steering command jitter ($\Delta\delta$/frame) is suppressed by $-$**75.0%** ($2.33° \rightarrow 0.58°$/frame). By filtering out transient optical spikes, the Ackermann steering servo operates smoothly, preventing tire scrub and ensuring rock-solid chassis stability.

8 Edge MLOps, Clean Architecture, and Deployment Pipeline

To transition from academic prototyping to production deployment on scale autonomous vehicles, the complete software pipeline was structured under strict Clean Architecture principles and modern MLOps standards:

1) **Factory & Strategy Design Patterns:** Model instantiation is decoupled through a dynamic `ModelFactory`, while runtime execution is abstracted via an `InferenceStrategy` interface supporting transparent backend switching between PyTorch, ONNX Runtime, and TensorRT engines without modifying vehicle control code.
2) **Strict Static Typing and Automated Quality Gates:** The entire codebase adheres to strict type safety verified by `mypy` and linted via `ruff`. A comprehensive test suite comprising 31 unit tests (`pytest`) continuously verifies tensor shapes, numerical parities between frameworks ($< 10^{-7}$ tolerance), and data loader pipelines.
3) **Continuous Drift Monitoring Pipeline:** Integration with Evidently AI enables automated covariate shift detection. During real-world competition runs, incoming telemetry can be batched against calibration baselines, triggering real-time operator alerts if mean brightness, contrast, or edge densities diverge beyond acceptable statistical thresholds.
4) **Embedded Microservice Architecture:** The inference engine is exposed via an asynchronous high-performance FastAPI service providing a `POST /steer` endpoint. Packaged into a multi-stage Docker container optimized for ARM64 and CUDA, the system can be deployed directly onto NVIDIA Jetson Orin Nano, Xavier NX, or Raspberry Pi 5 onboard companion computers.

9 Conclusion

This comprehensive technical monograph delivered a complete, production-grade autonomy framework for scale autonomous racing:

1) **Continuous Ground-Truth and Deep Segmentation:** A dual-domain Canny and Black Top-Hat pipeline, accompanied by deep multi-scale segmenters (`NXPUNetDeep` and `NXPU2NetDeep`) and a Stanley/Pure Pursuit controller, synthesized 3,433 continuous steering targets ($\delta \in [-30.0°, +30.0°]$) with 0% background leakage.
2) **MicroViT Architecture:** By coupling a 2-stage convolutional stem with global Multi-Head Self-Attention, MicroViT reduces parameter count by 77.4% relative to NVIDIA DAVE-2 (359,841 parameters, 1.39 MB FP32).
3) **Sub-Millisecond Edge Engine:** Dynamic ONNX Runtime and TensorRT INT8 entropy quantization deliver P50 execution latencies of **0.71 ms to 2.18 ms (437 to 1324 FPS)**, reserving $> 73\%$ computational safety margins under the 10 ms control deadline.
4) **Photometric Resilience:** Evidently AI covariate monitoring proved that while CNN baselines suffer catastrophic failure under shadows (+76.9% degradation for DAVE-2), MicroViT restricts degradation to +21.1%.
5) **Production Excellence:** The 4th architecture (`MicroViTSmoothed`) achieved record-low drift degradation (**+8.2%**), the lowest continuous lap error (**4.91**°), and a $-$**75.0% reduction in servo jitter**. Full validation across 3,433 track frames and 31 passing unit

test suites establishes an authoritative standard for edge autonomous robotics.

REFERENCES

[1] M. Bojarski, D. Del Testa, D. Dworakowski, et al., "End to end learning for self-driving cars," *arXiv preprint arXiv:1604.07316*, 2016.

[2] I. B. Palhano, et al., "Autonomous scale kart navigation on standardized canvas tracks," *ENSICAEN Technical Report*, 2025–2026.

[3] M. Bertozzi and A. Broggi, "GOLD: a parallel real-time stereo vision system for generic obstacle and lane detection," *IEEE Transactions on Image Processing*, vol. 7, no. 1, pp. 62–81, 1998.

[4] J. Canny, "A computational approach to edge detection," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. PAMI-8, no. 6, pp. 679–698, 1986.

[5] X. Qin, Z. Zhang, C. Huang, et al., "U2-Net: Going deeper with nested U-structure for salient object detection," *Pattern Recognition*, vol. 106, p. 107404, 2020.

[6] L.-C. Chen, G. Papandreou, F. Schroff, and H. Adam, "Rethinking atrous convolution for semantic image segmentation," *arXiv preprint arXiv:1706.05587*, 2017.

[7] J. Hu, L. Shen, and G. Sun, "Squeeze-and-excitation networks," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2018, pp. 7132–7141.

[8] A. Dosovitskiy, L. Beyer, A. Kolesnikov, et al., "An image is worth 16x16 words: Transformers for image recognition at scale," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2021.

[9] Z. Liu, Y. Lin, Y. Cao, et al., "Swin Transformer: Hierarchical vision transformer using shifted windows," in *Proc. IEEE/CVF Int. Conf. Comput. Vis. (ICCV)*, 2021, pp. 10012–10022.

[10] Evidently AI Team, "Evidently: Open-source machine learning monitoring," *Evidently AI Documentation and Core Benchmarks*, 2024–2026.

[11] NVIDIA Corporation, "TensorRT: High-performance deep learning inference optimizer and runtime," *NVIDIA Developer SDK Documentation*, 2024.

[12] G. M. Hoffmann, C. J. Tomlin, M. Montemerlo, and S. Thrun, "Autonomous automobile trajectory tracking for off-road driving: Controller design, experimental validation and racing," in *Proc. Amer. Control Conf.*, 2007, pp. 2296–2301.

[13] R. C. Coulter, "Implementation of the pure pursuit path tracking algorithm," Carnegie Mellon Univ., Pittsburgh, PA, Tech. Rep. CMU-RI-TR-92-01, 1992.