





0000000000000000000 8(00000 Q1 PNZZZZA G € R6 1k 0000000 0000000000+ RR1 4.7k 0 0 0 0 0 0 0 0 8087 P3 RESET 000000000000000000 000000 74F00 U14 0000000000000000 U7 74F573 C3 0.1uF() O 0000000000 Ö **0**000000000000000 D1 1N4148 POWER_LED U4 **G ©** R7 10k SST39SF010A 00000000000 O SW1 00008 00000000000000 000000000 0000000000000 00 00 000000000 00 00 U15 000 00 00 00 00 00000 **0**000000000 00 00 U6 ASSCIANCE U11 74F245 U13 74F244 O O O O O O O O O 00 00 00 0 00 00 0000000000000000 00 00 00 80 **0**000000000 0000000000000 000 R3 47 0 0 0 0 R2 47 00000000000 000000000 000 U3 FE2010A 888 O O C16 0.1uF GPLv3 Micro 8088 - Version 1.2 U12 74F244 U12 10k SW2 CONFIG Copyright (C) 2017-2018 Sergey Kiselev 🖊 www.malinov.com Sheet: File: 8088-FE2010A-SBC.kicad_pcb Title: Size: USLetter | Date: 27 sep 2012 Rev: KiCad E.D.A. kicad 4.0.1-stable ld: 1/1