





0000000000000000000 8 000000000 000000 PN2222A **10**00 0000000 0000000000+ RR1 4.7k 0 0 0 0 0 0 0 0 8087 P3 RESET U8 74F573 000000000000000000 000000 74F00 U14 0000000000000000 U7 74F573 C3 0.1uF() O 0000000000 Ö U4 G R7 10k SST39SF010A D1 1N4148 POWER_LED U4 **G E** R7 10k 00000000000 O SW1 00008 00000000000000 000000000000 00 00 0000000000 00 00 U15 000 00 00 00 00 00000 **0**000000000 00 00 U11 74F245 U13 74F244 O O O O O O O O O U6 ASSCIANCE 00 00 00 0 00 00 0000000000000000 00 00 00 **0**000000000 000000000000 000 00000000000 000000000 000 888 O O C16 0.1uF Micro 8088 - Version 1.1 OSHW RR3 4.7k RR2 10k GPLv3 Copyright (C) 2017 Sergey Kiselev 0000000000 **□**□ 0 0 U12 74F244 SW2 CONFIG 🖊 www.malinov.com Sheet: File: 8088-FE2010A-SBC.kicad_pcb Title: Size: USLetter Date: 27 sep 2012 Rev: KiCad E.D.A. kicad 4.0.1-stable ld: 1/1