Geometric Tools Engine Update History

Last modified: November 27, 2023

Contents

1	Updates to Version 6.8	2
2	Updates to Version 6.7	8
3	Updates to Version 6.6	13
4	Updates to Version 6.5	15
5	Updates to Version 6.4	20
6	Updates to Version 6.3	24
7	Updates to Version 6.2	2 6
8	Updates to Version 6.1	30
9	Updates to Version 6.0	34
10	Version 6.0	40

The version release dates are listed here. Versions released before the current version may be obtained by email request.

- Version 6.8 posted August 9, 2023.
- Version 6.7 posted July 17, 2023.
- Version 6.6 posted May 8, 2023.
- Version 6.5 posted December 14, 2022.
- Version 6.4 posted June 8, 2022.
- Version 6.3 posted April 3, 2022.
- Version 6.2 posted March 7, 2022.
- Version 6.1 posted February 7, 2022.
- Version 6.0 posted January 3, 2022.

The updated files and related notes are provided for the versions in each of the ensuing sections. Each section has a list of changes that occurred to the version number mentioned in that section. Those changes were rolled up into the zip file that was posted for the next version. Modified files are colored gold, new files are colored green and deleted files are colored red. Source code is colored Violet.

1 Updates to Version 6.8

November 27, 2023. Reimplemented the query for distance between two circles in 3D. The previous version used only floating-point arithmetic. The rounding errors when computing derivatives of the degree-8 polynomial were causing extreme inaccuracy in the results. The new code now uses a mixture of floating-point arithmetic and rational arithmetic. The degree-8 polynomial and its derivatives are created using rational arithmetic. Bisection is performed using floating-point arithmetic, but with some initial rational arithmetic to determine sign changes in a polynomial at the endpoints of a potential root-bounding interval.

GTE/Mathematics/DistCircle3Circles.h

Added multithreading to the general-degree polynomial root estimator to improve the performance.

GTE/Mathematics/RootsGeneralPolynomial.h

November 26, 2023. Based on reader feedback for FastOrthogonalComplement.pdf, I reordered the vectors in the signatures of the functions listed in the pseudocode and in the actual code (in Vector3.h). This is the usual convention I have for writing code (inputs first, outputs last). I also modified the actual code function name to FastComputeOrthogonalComplement.

GTE/Mathematics/Vector3.h

November 21, 2023. After thinking harder about the new Vector3 function ComputeOrthogonalComplement, I was able to avoid the square root operation. Given a unit-length vector, you can compute the orthogonal complement with only arithmetic operations. A new PDF has been posted to the website: FastOrthogonalComplement.pdf.

```
GTE/Mathematics/Vector3.h
```

November 20, 2023. The RootsPolynomial<T>::Find function suffered from significant floating-point rounding errors in the computation of the coefficients of the polynomial derivatives. The class allows for type T to be rational, but the bisection effectively does not converge because the number of bits per rational number is excessively large. This class is now deprecated. The low-degree root finders are now in RootsLinear.h, RootsQuadratic.h, RootsCubic.h, and RootsQuartic.h. Three of these files are listed here because a comment mentioned using Cauchy's bound when in fact the code uses Lagrange's bound.

```
GTE/Mathematics/RootsQuadratic.h
GTE/Mathematics/RootsCubic.h
GTE/Mathematics/RootsQuartic.h
GTE/Mathematics/RootsPolynomial.h
```

The replacement for RootsPolynomial<T>::Find is RootsGeneralPolynomial<T>::Solve. The algorithm is effectively the same as the deprecated Find, but it uses a mixture of floating-point arithmetic and rational arithmetic. The coefficients of the polynomial derivatives are computed using rational arithmetic to avoid the rounding errors that plagued the deprecated code. When the bisection code consumes these polynomials, rational evaluation is used to determine sign information at the endpoints of an interval. If bisection must occur, the rational coefficients are converted to floating-point, and the resulting rounding errors are significantly smaller than that of the deprecated code. The floating-point-based bisection is fast, so the performance is reasonable in order to get increased accuracy of the root estimates.

```
\label{eq:GTE-GTM-athematics} $$GTE/GTM athematics. $\{v16,v17\}. \{vcxproj,vcxproj.filters\}$$GTE/Mathematics/RootsGeneralPolynomial.h
```

Added a new function ComputeOrthogonalComplement with a signature different from the other same-named function. The new function computes the basis by computing a unit-length quaternion for a rotation matrix whose last column is a user-specified unit-length vector. The other two columns are extracted from the rotation matrix.

```
GTE/Mathematics/Vector3.h
```

The Rotate function for a 4-tuple vector did not compile because it uses a Vector3-based Cross product function. The Vector3 quantities were replaced by Vector4 quantities, but the header file Vector3.h still needs to be included to access the cross product of two 4-tuple vectors.

```
GTE/Mathematics/Quaternion.h
```

Added a member accessor to get a const reference to the polynomial coefficients.

GTE/Mathematics/Polynomial1.h

Added an exception to the Insert function that detects whether the vertex ordering for two edges is opposite for the two triangles sharing the edge. If the ordering is not opposite, the mesh is not manifold. The test is exposed by default (mThrowOnNonmanifoldInsertion is initially true), but you can disable the test by setting the aforementioned Boolean to false.

GTE/Mathematics/ETManifoldMesh.h

The GetGradient function had a typecast of a float to a size_t and then assigned it to an int32_t. The typecast was changed to a int32_t. Fixed Ubuntu gcc compiler warnings/errors: missing typename when declaring topology, 3 loop variables were size_t but needed to be IndexType.

```
GTE/Mathematics/SurfaceExtractorMC.h
```

Fedora gcc complained about undefined int32_t (but Ubuntu gcc did not). Added an include of cstdint.h.

```
GTE/Mathematics/HermiteBiquintic.h
GTE/Mathematics/HermiteTricubic.h
GTE/Mathematics/HermiteTriquintic.h
```

The following warnings/errors occur using LVM - clang-cl in Microsoft Visual Studio 2022 version 17.8.0. After these modifications, the Intel C++ Compiler 2023 had no warnings/errors.

An include of Functions.h is required; otherwise, the block of functions starting with atandivpi become infinitely recursive. The definition of atandivpi whose input is IEEEBinary16 makes a call to atandivpi whose argument is typecast to float. This works as long as the definition of atandivpi in Functions.h is accessible. Without it, an implicit IEEEBinary16 constructor call is made from the float input, thus the infinite recursion. The constructor with input of type double has variable temp that is tagged as not initialized. It is on the next line, but I moved that code into the union initialization.

```
GTE/Mathematics/IEEEBinary16.h
```

Two declarations of Vector3 < T > delta occurred in the code, but the variables are unused. They have been removed.

```
GTE/Mathematics/DistLine3Circle3.h
```

Function ConstrainedTriangulate had a declaration of counter that was used for debugging. Even though it is incremented in the code, the value is not used anywhere else and is flagged as such. It has been removed.

```
GTE/Mathematics/TriangulateCDT.h
```

The operator() function declared and initialized numZero. Even though it is incremented in the code, the value is not used anywhere else and is flagged as such. They have been removed.

GTE/Mathematics/IntrHalfspace3Segment3.h GTE/Mathematics/IntrHalfspace3Triangle3.h

The LLVM compiler also generates warnings about Intel intrinsics files emmintrin.h and xmmintrin.h. The projects do not include these headers explicitly, so they must be exposed somewhere in Microsoft's header files.

October 21, 2023. Added a code to save binary STL files.

GTE/Mathematics/STLBinaryFile.h

October 20, 2023. Added a file loader for binary STL files.

GTE/Mathematics/STLBinaryFile.h

October 11, 2023. Reimplemented the Quaternion<T>::Rotate functions to use fewer arithmetic operations. Thanks to Robert Eisele for sending me a link to his webpage about the algorithm; the link is provided in the header file.

GTE/Mathematics/Quaternion.h

September 30, 2023. Toggling between double and BSRational UInteger AP32 required commenting and uncommenting some code. I added a preprocessor define so that you can toggle by exposing or hiding this define.

GTE/Samples/Geometrics/PolygonBooleanOperations/PolygonBooleanOperationsWindow2.{h,cpp}

September 28, 2023. Modified the sample application to use exact rational arithmetic if so desired. BSPPolygon2<T> already compiles when T is BSRational<UIntegerAP32>.

GTE/Samples/Geometrics/PolygonBooleanOperations/PolygonBooleanOperationsWindow2.{h,cpp}

Fixed a problem with segment-arc and ray-arc find-intersection queries that were caused by the line-circle find-intersection query setting only one of the result.parameter values when the line and circle are tangent. It is necessary to set both parameter values to the same number, effectively a degenerate interval that is used in interval-interval find-intersection queries used in segment-arc and ray-arc. Thanks to owai on github for reporting the problem, diagnosing it, and fixing it.

GTE/Mathematics/IntrLine2Circle2.h

Removed the deprecation comment about the Contains function without the epsilon argument. This function is still useful when you know the point is on the arc so that you do not need the epsilon value.

GTE/Mathematics/Arc2.h

September 25, 2023. The operator< comparison had an incorrect comparison in it, using origin instead of the correct normal.

```
GTE/Mathematics/Hyperplane.h
```

September 25, 2023. Yet more modifications to surface extraction. The index type for the indices array were hard-coded as int32_t. Some applications have different types for the indices. The MarchingCubes and SurfaceExtractionMC classes now have template parameters IndexType to allow the user to choose whatever type is natural to the application. I back-ported changes made to the GTL version of MarchingCubes; for example, int32_t index[8] is now std::array<IndexType, 8> index.

```
GTE/Mathematics/MarchingCubes.h
GTE/Mathematics/SurfaceExtractorMC.h
GTE/Samples/Physics/BouncingBall/DeformableBall.cpp
GTE/Samples/Imagics/SurfaceExtraction/SurfaceExtractionWindow3.h
```

September 24, 2023. In SurfaceExtractorMC.h, the test code used only a positive perturbation and the output is correct. When the perturbation is negative, the order of sign testing needed to be modified to ensure the output is correct. The BouncingBall physics sample uses SurfaceExtractorMC.h, so it needed a modification to add the perturbation parameter.

```
GTE/Mathematics/SurfaceExtractorMC.h
GTE/Samples/Physics/BouncingBall/DeformableBall.cpp
```

September 23, 2023. When the single-voxel Extract returns false, the full-image extraction was supposed to ignore the voxel. Instead it deleted the entire mesh, which is a disastrous bug. The unit tests verified only that the Marching Cubes 256 triangle-lookup table entries are correct, and none of these provided code coverage that would have found the bug. Also, floating-point rounding errors in mesh vertex construction led to small sets of vertices, each set containing vertices that are nearly the same (but should have been the same without the rounding errors). MakeUnique is unable to identify these as duplicates. I modified the single-voxel Extract function to generate the same vertex on an edge shared by multiple voxels, using a consistent ordering of the voxel corners to ensure that the all constructions of the vertex have the same rounding errors. Finally, the interfaces were modified to have a new parameter perturb that allows you to avoid the ignoring of voxels for which at least one corner of the voxel is exactly the input level value. Thanks to Scott Johnson for reporting these problems.

```
GTE/Mathematics/SurfaceExtractorMC.h
```

September 17, 2023. If the mesh is not orientable, GetBoundaryPolygons had an infinite loop when trying to traverse a triangle strip the connects two consecutive boundary edges. When not orientable, two adjacent triangles are repeatedly visited. I added a trap for this and throw an exception.

```
GTE/Mathematics/ETManifoldMesh.h
```

September 10, 2023. Added new file for distance queries between 2 circles in 2D.

```
GTE/GTMathematics.{v16,v17}.{vcxproj,vcxproj.filters}
GTE/Mathematics/DistCircle2Circle2.h
```

Added includes of C++ Standard Library headers to ensure they are always exposed to the file.

```
GTE/Mathematics/DistLine2Arc2.h
GTE/Mathematics/DistRay2Arc2.h
GTE/Mathematics/DistSegment2Arc2.h
```

August 28, 2023. Revised comments. Fixed bugs that were exposed when unit testing ray-arc and segment-arc distance queries. Feature request: Added new distance queries. Sorry for the delay. I struggle with 2-dimensional mathematics. I know I have problems with 3-dimensional mathematics because I get lost walking around my neighborhood. I seem to be most comfortable in 7-dimensional space.

```
GTE/Mathematics/DistLine2Circle2.h
GTE/Mathematics/DistRay2Circle2.h
GTE/Mathematics/DistSegment2Circle2.h
GTE/Mathematics/DistLine2Arc2.h
GTE/Mathematics/DistRay2Arc2.h
GTE/Mathematics/DistSegment2Arc2.h
```

August 27, 2023. The comments in these files indicate the direction vectors do not have to be unit length. This was not true in earlier versions of GTE; that is, the directions had to be unit length. I had modified the comments at one time because I was removing the unit-length constraint. Unfortunately, the code was not modified, so only unit-length vectors worked. My unit tests passed anyway because they all used unit-length directions. The constraint is now removed. The direction vectors do not have to be unit length, the code was corrected, and the unit tests were updated to handle non-unit-length vectors. The line-segment distance query in DistPointSegment.h is correct.

```
GTE/Mathematics/DistPointLine.h
GTE/Mathematics/DistPointRay.h
```

August 26, 2023. When the line intersects the circle in two distinct points, the parameter members of result must be increasingly ordered. They were not always, so a test-and-swap had to be added. I also fixed old comments about the Result struct.

```
GTE/Mathematics/Dist2Line2Circle2.h
```

Added a distance query for segment-circle in 2D.

```
GTE/GTM at hematics. \{v16, v17\}. \{vcxproj, vcxproj. filters\}\\ GTE/M at hematics/Dist2Segment2Circle2.h
```

August 24, 2023. The GTMathematicsGPU solutions and projects duplicated the GUID in MSVS 2019 and MSVS 2022. The MSVS 2019 GUID was modified. The GenerateMesh v17 projects were missing references to the GTMathematicsGPU projects (which did not affect the compilation).

```
GTE/BuildAll.v16.sln
GTE/BuildAllDX11.v16.sln
GTE/BuildAllGL45.v16.sln
GTE/GTMathematicsGPU.v16.sln
GTE/GTMathematicsGPU.v16.vcxproj
GTE/Samples/Geometrics/GenerateMeshUVs/GenerateMeshUVsDX11.v16.sln\\
GTE/Samples/Geometrics/GenerateMeshUVs/GenerateMeshUVsDX11.v16.vcxproj
GTE/Samples/Geometrics/GenerateMeshUVs/GenerateMeshUVsDX17.v16.sln
GTE/Samples/Geometrics/GenerateMeshUVs/GenerateMeshUVsGL45.v16.sln
GTE/Samples/Geometrics/GenerateMeshUVs/GenerateMeshUVsGL45.v16.vcxproj
GTE/Samples/Geometrics/GenerateMeshUVs/GenerateMeshUVsGL45.v17.sln
GTE/Samples/Physics/BlownGlass/BlownGlassDX11.v16.sln
GTE/Samples/Physics/BlownGlass/BlownGlassDX11.v16.vcxproj
GTE/Samples/Physics/BlownGlass/BlownGlassGL45.v16.sln
GTE/Samples/Physics/BlownGlass/BlownGlassGL45.v16.vcxproj
GTE/Samples/Physics/Fluids2D/Fluids2DDX11.v16.sln
GTE/Samples/Physics/Fluids2D/Fluids2DDX11.v16.vcxproj
GTE/Samples/Physics/Fluids2D/Fluids2DGL45.v16.sln
GTE/Samples/Physics/Fluids3D/Fluids3DDX11.v16.sln
GTE/Samples/Physics/Fluids3D/Fluids3DGL45.v16.sln
```

Removed MSVS 2022 warnings about uninitialized arrays (which clearly are initialized in the code).

```
GTE/Mathematics/Image2.h
GTE/Mathematics/Image3.h
```

August 20, 2023. This is a new file that accompanies the revised version of the document MovingAlongCurveSpecifiedSpeed.pdf. It contains an implementation of the algorithms described in the PDF.

```
\label{eq:GTE-def} \begin{split} & GTE/GTM athematics. \{v16, v17\}. \{vcxproj, vcxproj. filters\}\\ & GTE/M athematics/Reparameterize By Arclength. h \end{split}
```

2 Updates to Version 6.7

August 8, 2023. After refactoring Math.h, a significant number of GTE files no longer compiled. The files required headers from the C++ Standard Library, but some of those headers were accessed indirectly by including other GTE files. I fixed those, but then discovered that my instantiation tool had a significant number of source files that included ArbitraryPrecision.h in order to instantiate templates based on numeric types float, double, BSNumber, and BSRational. The arbitrary precision header itself exposes standard library files that allowed some of the float-based and double-based templates, but when the arbitrary precision header is hidden, several of these templates failed to compile.

To avoid this mess, I modified nearly every GTE mathematics header file to explicitly include standard library headers for symbols that the header file references. This should protect the distribution from major failure if I refactor headers in the future. I also modified the instantiation tool to allow me to compile with or without arbitrary precision headers. I had already done this in my GTL development track. The number of modified files is so large that I am not listing them here.

Because the number of modified files was so large, I also unified my top-level commenting style. General comments at the top of the header about the file now occur after the #pragma statement but before #include-s of the headers that the file requires. I had already done this in my GTL development track.

Items modified during the refactor with additional needs are listed below.

New files for computing distance between a line or ray and a circle. The other cases for segment-circle, line-arc, ray-arc, and segment-arc will be posted soon.

```
GTE/GTMathematics.{v16,v17}.{vcxproj,vcxproj.filters}
GTE/Mathematics/DistLine2Circle2.h
GTE/Mathematics/DistRay2Circle2.h
```

Added initialization of some local variables to avoid MSVS code analysis complaint.

```
GTE/Mathematics/BSplineSurfaceFit.h
GTE/Mathematics/BSplineVolume.h
GTE/Mathematics/ContEllipse2.h
GTE/Mathematics/ContEllipsoid3.h
GTE/Mathematics/Matrix.h
GTE/Mathematics/FPInterval.h
GTE/Mathematics/GMatrix.h
GTE/Mathematics/IntpThinPlateSpline2.h
GTE/Mathematics/IntpVectorField2.h
GTE/Mathematics/Matrix.h
GTE/Mathematics/NURBSVolume.h
GTE/Mathematics/RootsBisection1.h
GTE/Mathematics/SurfaceExtractorMC.h
GTE/Mathematics/SWInterval.h
```

Replaced a move operation by a copy operation to avoid MSVS code analysis complaint about the moved object now being invalid.

```
GTE/Mathematics/Polynomial1.h
```

The class Quaternion is a client of Chebyshev ratios. The interface for ChebyshevRatio changed, so the quaternion code needed updating.

```
GTE/Mathematics/Quaternion.h
```

Commented out debug preprocessor symbols. If you want any of these, expose them again or add them to your global preprocessor defines.

```
GTE/Mathematics/APInterval.h
GTE/Mathematics/ApprQuery.h
GTE/Mathematics/BitHacks.h
GTE/Mathematics/BSNumber.h
```

Deleted the GTE_NO_LOGGER macro, exposing the LogAssert statements. This were the only occurrences of the no-logger control.

```
GTE/Mathematics/ApprPolynomialSpecial2.h
GTE/Mathematics/ApprPolynomialSpecial3.h
GTE/Mathematics/ApprPolynomialSpecial4.h
```

Added pragma block for MSVS 2022 in the function Convert in the case of the rounding mode FE_TONEAREST. The pragma disables a code analysis warning. This code had been tested and analyzed previously and works fine. I do not understand the code analysis message, which I have added to the pragma block as a comment.

```
GTE/Mathematics/BSNumber.h
```

Moved the comparison operators from external scope to class scope to be consistent with the other primitives having class-scope operators.

```
GTE/Mathematics/CanonicalBox.h
```

The gcc compilers on Linux complained about a potential uninitialized array (MSVS 2022 did not). The complaint is correct. The GetVertices functions return false if the Delaunay dimension is not 2. The GetBarycentrics functions return false if the triangle index t is invalid or if the ComputeBarycentrics function fails. In all these cases, the output arrays are uninitialized. First, I removed the test for dimension 2 and added an exception in the constructor if the input Delaunay object is not 2-dimensional. Second, I added initialization of the arrays if failure occurs, setting the components all to zero and then returning false.

```
GTE/Mathematics/Delaunay2Mesh.h GTE/Mathematics/Delaunay3Mesh.h
```

Modified std::abs calls to std::fabs calls.

```
GTE/Mathematics/IntrAlignedBox3Cone3.h
```

Converted some loop counters from int32_t to size_t to avoid MSVS code analysis complaints about 32-bit arithmetic performed on index lookups possibly causing overflow (it does not).

```
GTE/Mathematics/NaturalCubicSpline.h
GTE/Mathematics/NaturalQuarticSpline.h
GTE/Mathematics/UIntegerAP32.h
```

Replace an auto statement by the explicit type for a std::function object to avoid a MSVS 2022 code analysis complaint about not being able to determine whether a copy or const reference is asked for.

```
GTE/Mathematics/RiemannianGeodesic.h
```

Replaced C-style arrays by std::array.

GTE/Mathematics/SurfaceExtractorMC.h

Added precision counter for fused-multiply-add.

```
GTE/Tools/PrecisionCalculator/PrecisionCalculator.cpp
```

August 3, 2023. Factored Math.h into Constants.h, Functions.h, and TypeTraits.h. The Math.h file has been removed from the distribution. The constants header contains a small number of commonly used constants. The functions header contains implementations for IEEE recommended functions for convenience. These are for float and double. The type traits header contains traits for has_division and is_arbitrary_precision. Some other traits were added, but they are currently only in use in the GTL version. They are useful for eliminating the verbose nature of std::enable_if for conditionally selecting implementations based on type (floatting-point or rational). The removal of Math.h led to many file modifications. Most of the clients of this header simply needed <cmath>.

```
GTE/GTMathematics.{v16,v17}.{vcxproj,vcxproj.filters}
GTE/Mathematics/Math.h
GTE/Mathematics/Constants.h
GTE/Mathematics/Functions.h
GTE/Mathematics/TypeTraits.h
```

I added support for std::remainder in Functions.h and in the rational arithmetic classes. As it turns out, the factoring of Math.h led to discovery of some bugs. BSNumber.h and BSRational.h implemented the arbitrary precision type trait, setting the value to true. These were both missing a leading underscore, so the compiler thought they were new primary templates rather than implementations of the primary templates defined in TypeTraits.h.

```
GTE/Mathematics/BSNumber.h
GTE/Mathematics/BSRational.h
```

The majority of Math.h consisted of special constants for the function estimators such as ACosEstimate.h among others. The constants were moved into the estimators files themselves in GTL together with a reduction in code. I back-ported the files from GTL to GTE. The interfaces have changed for the estimators. They were template classes but are now template functions. A couple of new files were added, one for computing SLERP and one for computing Chebyshev coefficients that occur in the SLERP formula, $\sin((1-t)\theta)/\sin(\theta)$ and $\sin(t\theta)/\sin(\theta)$.

```
GTE/Mathematics/ACosEstimate.h
GTE/Mathematics/ASinEstimate.h
GTE/Mathematics/ChebyshevRatio.h
GTE/Mathematics/ChebyshevRatioEstimate.h
GTE/Mathematics/CosEstimate.h
GTE/Mathematics/Exp2Estimate.h
GTE/Mathematics/ExpEstimate.h
GTE/Mathematics/InvSqrtEstimate.h
```

```
GTE/Mathematics/Log2Estimate.h
GTE/Mathematics/LogEstimate.h
GTE/Mathematics/RemezAlgorithm.h
GTE/Mathematics/RotationEstimate.h
GTE/Mathematics/SinEstimate.h
GTE/Mathematics/Slerp.h
GTE/Mathematics/SlerpEstimate.h
GTE/Mathematics/SqrtEstimate.h
GTE/Mathematics/TanEstimate.h
```

August 2, 2023. Added the ability to discard code for fused-multiply-add (std::fma) if you know your target machine does not have floating-point hardware support for that instruction. The default is to compile std::fma. To discard this and fall back to x*y+z using 2 floating-point operations, define the preprocessor symbol GTE_DISCARD_FMA. The mechanism is simply to provide a function gte::FMA whose body is controlled by the preprocessor symbol.

```
GTE/Mathematics/Math.h
GTE/Mathematics/BSNumber.h
GTE/Mathematics/BSRational.h
GTE/Mathematics/RootsQuadratic.h
GTE/Mathematics/RootsCubic.h
GTE/Mathematics/IntrEllipse2Ellipse2.h
```

July 29, 2023. The index i1 was compared to the upper-bound loop counter for contiguous-open segment meshes. It needed to be i0.

```
GTE/Mathematics/SegmentMesh.h
```

July 28, 2023. Modified the interfaces to allow selection between using bisection or using the closed-form equations for root estimation. Updated the unit tests for code coverage of either selection.

```
GTE/Mathematics/RootsQuadratic.h
GTE/Mathematics/RootsCubic.h
GTE/Mathematics/RootsQuartic.h
```

Minor changes to avoid Visual Studio 2022 code analysis warnings.

```
GTE/Mathematics/UIntegerAP32.h
```

This file is cursed. Last check-in, I merged a line from GTL to GTE. The query result is stored in a struct Output in GTL but the GTE query result is stored in a struct Result. I then failed to run my instantiation tools which would have trapped the error.

```
GTE/Mathematics/DistLine3Circle3.h
```

July 23, 2023. The code ported to GTL had a unit-test failure for Robust function in the case that the circle center was not the origin. The GTE unit tests did not contain such a case. One block of Robust code was missing the translation of the closest line point to the original coordinate system.

3 Updates to Version 6.6

July 17, 2023. Added new files for robust root estimation for polynomials of degree 1, 2, 3, and 4. These use exact rational arithmetic for theoretically correct root classification, just as RootsPolynomial does. Rather than call standard mathematics library functions for the closed-form root equations, bisection is used to avoid magnification of rounding errors inherent in power functions. The document LowDegreePolynomialRoots.pdf has a major revision to be more clear about the root estimation. This includes avoiding some of the logic tests mentioned at the Wikipedia page for quartic polynomials. The code has been unit tested for 100% coverage.

```
GTE/Mathematics/PolynomialRoots.h
GTE/Mathematics/RootsLinear.h
GTE/Mathematics/RootsQuadratic.h (re-release)
GTE/Mathematics/RootsCubic.h
GTE/Mathematics/RootsQuartic.h
```

July 10, 2023. Running a ConsoleApplication-derived object on a laptop with Intel Integrated Graphics (Iris Xe/UHD) and an NVIDIA GeForce RTX 3050, the Intel graphics is identified as the most powerful adapter because that adapter is associated with the primary display. It is not the most powerful. I discovered this when the Intel DLL igc64.dll threw two exceptions,

```
MONZA::DdiThreadingContext<MONZA::AdapterTraits_Gen12LP>::msg_end MONZA::IgcThreadingContext<MONZA::AdapterTraits_Gen12LP>::msg_end
```

during shutdown of the DX11 graphics. I had added code to WindowApplication-derived objects some time ago to choose a discrete adapter (if available) before choosing the Intel driver. That same code has now been added to the console-based application layer.

```
GTE/Applications/MSW/ConsoleSystem.cpp
GTE/Applications/MSW/WindowSystem.cpp
```

Fixed a bug. The clamping of the infinite-cylinder closest point to the finite-cylinder closest point used height h instead of h/2. The unit tests associated with these cases were also fixed.

```
GTE/Mathematics/DistPoint3Cylinder3.h
```

June 17, 2023. Fixed a bug in DoQueryOneZero where sMin was set incorrectly in the case tHat > +h/2.

```
GTE/Mathematics/IntrCanonicalBox 3 Cylinder 3.h
```

June 16, 2023. Modified the ellipse-ellipse find-intersection query code to be more robust when using floating-point arithmetic. The code still executes with rational arithmetic. Added a sample program for testing the code. The interface for FlQuery<T,Ellipse2<T>,Ellipse2<T> changed, so the area-of-intersection code had an obsolete interface removed. Added support for fused-multiply-add instructions.

```
GTE/BuildAll*.sln
GTE/Mathematics/Math.h
GTE/Mathematics/BSNumber.h
GTE/Mathematics/BSRational.h
GTE/Mathematics/IntrEllipse2Ellipse2.h
GTE/Mathematics/IntrAreaEllipse2Ellipse2.h
GTE/Samples/Intersection/CMakeLists.txt
GTE/Samples/Intersection/IntersectEllipses/*
```

Revised the implemention to be provide a better estimation of the roots.

```
GTE/Mathematics/RootsQuadratic.h
```

June 11, 2023. Modified the code to initial cone parameters when the caller requests initialization. The previous initialization was an implementation of an algorithm describe in the LeastSquaresFitting.pdf file, but the mathematics of the file was incorrect. Fixing the mathematics leads to having to compute roots of a degree 10 polynomial. Instead, a simpler method is provided that uses a line-fitting algorithm to determine the relationship between height h and radial distance r. The PDF itself has been modified.

```
GTE/Mathematics/ApprCone3.h
```

May 25, 2023. Added a new class RootsQuadratic for robust estimation of roots to quadratic polynomials. The robust versions for cubic and quartic polynomials use this; the work is in progress. The older code in RootsPolynomial will remain in GTE for now but will be deprecated in GTL.

```
GTE/Mathematics/RootsQuadratic.h
```

Added number.Negate() member functions to avoid the verbose number.SetSign(-number.GetSign()). BSRational.SetSign had an mValue block with GTL_BINARY_SCIENTIFIC_SHOW_DOUBLE instead of GTE_BINARY_SCIENTIFIC_SHOW_DOUBLE. This affected only the visualizer display of mValue; the rational number itself is correct.

```
 \begin{array}{l} {\rm GTE/Mathematics/BSNumber.h} \\ {\rm GTE/Mathematics/BSRational.h} \end{array}
```

May 22, 2023. The line-circle distance code had flawed logic for the case of a line not perpendicular to the plane of the circle and containing the origin. However, the block is entered when the line origin is on the normal line to the plane containing the circle center.

```
GTE/Mathematics/DistLine3Circle3.h
```

Two std::sqrt calls have arguments that are theoretically nonnegative, but floating-point rounding errors can lead to negative arguments. I added guards against this (clamp to nonnegative). The other std::sqrt calls already have the guard. The errant calls were in SolveDepressedQuartic. The problem was discovered during the line-circle distance query investigation.

GTE/Mathematics/RootsPolynomial.h

4 Updates to Version 6.5

May 6, 2023. Ethan Thornburg's modifications to allow disabling exceptions, calling std::terminate() instead.

```
GTE/Mathematics/Logger.h
```

Fedora 38 with gcc 13.1.1 compiler complained about std::move whose argument is a temporary object.

```
GTE/Mathematics/DisjointIntervals.h
```

Fedora 38 with gcc 13.1.1 compiler complained about potentially uninitialized variables. Add initialization even though in fact they are initialized before use (metaknowledge about the algorithm).

```
GTE/Mathematics/MinimalCycleBasis.h
```

Feature request for code to approximate continuous parametric curves with circular arcs. This includes a sample application. A PDF describing the algorithm is at the Geometric Tools website (ApproximateCurve-ByArcs.pdf).

```
GTE/BuildAll*.sln
GTE/GTMathematics.{v16,v17}.{vcxproj,vcxproj.filters}
GTE/Mathematics/ApprCurveByArcs.h
GTE/Samples/Mathematics/ApproximateBezierCurveByArcs/*
GTE/Samples/Mathematics/CMakeLists.txt
```

Rewrote the biquadratic implementation. The old code had a problem in one computation where subtractive cancellation caused many significant bits to be eliminated. This was the problem in the github issue about intersection of two ellipses, one rotated by $\pi/4 + \varepsilon$ for a small epsilon. An algebraic identity was used to avoid the subtractive cancellation, and the ellipse-ellipse intersection problem was eliminated. (The problem with ellipse-ellipse intersection for rotation ε still exists when you are using floating-point arithmetic. It does not occur with rational arithmetic, but I am rewriting that code to fix the floating-point problems).

```
GTE/Mathematics/RootsPolynomial.h
```

Factored out the area computations from IntrEllipse2Ellipse2.h for separation of concerns.

```
GTE/Mathematics/IntrEllipse2Ellipse2.h
GTE/Mathematics/IntrAreaEllipse2Ellipse2.h
```

The code for approximating and ellipse and points used the old OBB tree code. Modified it to use the new OBB tree code.

```
GTE/Mathematics/ApprCone3EllipseAndPoints.h
```

Added a recomputation of mValue (in debug builds) when using the functions frexp and ldexp specialized to BSRational. Without this, the value was incorrect.

GTE/Mathematics/BSRational.h

April 11, 2023. Redesigned the OBB tree of points, factoring out the tree construction to OBBTree.h. I also fixed an incorrect sizing of the nodes of the tree. A feature request was made of an OBB tree of triangles, which was easy to implement by derivation from OBBTree. The OBBTreeOfTriangles class has additional support for computing the intersection of linear component (line, ray, segment) with a triangle mesh. I also added code for computing an OBB of segments.

```
GTE/GTMathematics.{v16,v17}.{vcxproj,vcxproj.filters}
GTE/Mathematics/OBBTree.h
GTE/Mathematics/OBBTreeOfPoints.h
GTE/Mathematics/OBBTreeOfSegments.h
GTE/Mathematics/OBBTreeOfTriangles.h
```

March 27, 2023. Modified EnableTextures to bind UAVs in pixel shaders in a single call to OMSetRenderTargetsAndUnorderedAccessViews. I included a lengthy comment in EnableTextures about why the modification is necessary.

```
GTE/Graphics/DX11/DX11Engine.cpp
```

March 20, 2023. Fixed a regression when switching from <set> to <unordered_set>; the hash function and equality operator incorrectly included in these functions the ProcessedVertex location member. Also, when the input dataset has duplicated vertices, the InsertEdge function needs to replace the vertex indices by the equivalence-class representatives (via mDuplicates) before processing the edge. The sample application has another small test dataset, this one with a duplicated vertex.

```
GTE/Mathematics/Delaunay2.h
GTE/Mathematics/ConstrainedDelaunay2.h
GTE/Samples/Geometrics/Delaunay2D/Delaunay2DWindow.cpp
```

February 25, 2023. New file for sorting points in a circular manner about a center point. The website has a PDF describing the algorithm (SortPointsOnCircle.pdf).

```
GTE/Mathematics/SortPointsOnCircle.h
GTE/GTMathematics.{v16,v17}.{vcxproj,vcxproj.filters}
```

I have a template instantiation tool that was running debug (-g) builds. I added the ability to run release (-O2) builds. The Fedora gcc compiler warned about potentially uninitialized variables in the FastMarch* files. It also warned about an out-of-range index in the C++ std::sort code in the DistLine3Circle3 file for the line std::sort(candidates.begin(), candidates.begin() + numRoots). The numRoots is known not to exceed 4, but the compiler cannot determine this. I added the line numRoots = std::min(numRoots, static_cast<size_t>(4)) before the call to std::sort to avoid the warning.

```
GTE/Mathematics/FastMarch{2,3}.h
GTE/Mathematics/DistLine3Circle3.h
```

February 20, 2023. Eliminated the Fedora gcc12.{1,2}.1 release-build warnings about uninitialized members in std_function.h, probably due to incorrect optimization by the compiler. The warnings occurred in release builds of PVWUpdater.cpp where the member default constructors were called in the class constructors followed by a Set call to assign the members. I removed the Set calls and initialize the members directly in the constructor initializer list.

```
GTE/Graphics/PVWUpdater.cpp
```

February 2, 2023. Added the parent window handle to Window::Parameters for GTE on Microsoft Windows. That handle is passed to the CreateWindow functions.

```
GTE/Applications/MSW/Window.{h,cpp}
GTE/Applications/MSW/WindowSystem.cpp
```

Added the OnCopyData callback for GTE on Microsoft Windows. This allows passing data from one application to another application.

```
GTE/Applications/WindowApplication.{h,cpp}
```

Fixed linter complaint suggesting that .empty() be used instead of .size() == 0.

```
GTE/Graphics/CLODMeshCreator.h
GTE/Applications/MSW/WindowSystem.cpp
```

Added a missing pragma.

```
GTE/Mathematics/ContTetrahedron3.h
```

January 24, 2023. Added a new file for fitting a rectangle to a convex quadrilateral that is nearly a rectangle. The algorithm uses a least-squares formulation.

```
GTE/Mathematics/ApprConvexQuadByRect.h
GTE/GTMathematics.{v16,v17}.{vcxproj,vcxproj.filters}
```

January 17, 2023. Modified ETManifoldMesh.h to conform to commenting standards and choosing using instead of typedef. Added explicit initialization in the constructors of nested classes. Added braces to default constructor calls. The most important change is that during unit testing of the port of ETManifoldMesh from GTE to GTL, I created a small mesh for which GetBoundaryPolygons triggered an assertion (unexpected for a correct implementation of the algorithm). The idea of processing triangle strips at boundary vertices that are shared by 4 or more edge is correct. The code works for the strict definition of manifold mesh, where bow-tie configurations are not allowed. However, GTE has relaxed the constraint and allows bow-ties. For such meshes, the implementation of GetBoundaryPolygons is flawed and can lead to failure. Moreover, the approach I used in the implementation is too complicated. I re-implemented the algorithm to be simpler.

GTE/Mathematics/ETManifoldMesh.h

Modified VETManifoldMesh.h to conform to commenting standards and explicitly initializing nested class members in their constructors.

```
GTE/Mathematics/VETManifoldMesh.h
```

Modified TSManifoldMesh.h to conform to commenting standards and choosing using instead of typedef. Added explicit initialization in the constructors of nested classes. I renamed the T member to S in the nested class Triangle. The other mesh classes use T to stand for Triangle. Using T for Tetrahedron makes the code difficult to read at times. Switching to S (for Simplex) helps with readability. Finally, I added the keyword virtual to Insert and Remove to support a new class VTSManifoldMesh that adds vertex manipulation to the base class TSManifoldMesh.

```
GTE/Mathematics/TSManifoldMesh.h
GTE/Mathematics/Delaunay3.h
GTE/GTMathematics.{v16,v17}.{vcxproj,vcxproj.filters}
GTE/Mathematics/VTSManifoldMesh.h
```

The static 2-manifold class has a member function GetBoundaryPolygons, just as the dynamic class ETManifoldMesh does. This function has the same flawed implementation mentioned previously. It is now reimplemented using the same approach as in ETManifoldMesh.

```
GTE/Mathematics/StaticVETManifoldMesh2.h
```

Added a static 3-manifold class for tetrahedra meshes. This is significantly faster than the dynamic classes TSManifoldMesh and VTSManifoldMesh.

```
GTE/Mathematics/StaticVTSManifoldMesh3.h
```

Added newer static manifold mesh classes, MeshStaticManifold2 and MeshStaticManifold3, that perform better than StaticVETManifoldMesh2 and StaticVTSManifoldMesh3. The newer classes are also multithreaded. The older static classes will be deprecated for GTL in favor of the newer static classes.

```
GTE/Mathematics/MeshStaticManifold2.h
GTE/Mathematics/MeshStaticManifold3.h
```

Important Note. ETManifoldMesh, VETManifoldMesh and StaticVETManifoldMesh2 store adjacency pointers and indices according to the following design: Let the triangle have ordered vertices (V[0],V[1],V[2]). The triangle adjacent to edge (V[0],V[1]) is A[0]. The triangle adjacent to edge (V[1],V[2]) is A[1] and the triangle adjacent to edge (V[2],V[0]) is A[2]. The new class MeshStaticManifold2 uses a different design: The triangle adjacent to edge (V[1],V[2]) is A[0], the triangle adjacent to edge (V[2],V[0]) is A[1] and the triangle adjacent to edge (V[0],V[1]) is A[2]. That is, A[i] is the triangle adjacent to the edge opposite vertex V[i].

The design for the new 2-manifold triangle meshes is consistent with the design of the 3-manifold tetrahedra meshes TSManifoldMesh and VTSManifoldMesh. Let the tetrahedron have ordered vertices (V[0],V[1],V[2],V[3]). The triangle faces are counterclockwise ordered when viewed from outside the tetrahedron, T[0] = (V[1],V[2],V[3]), T[1] = (V[0],V[3],V[2]), T[2] = (V[0],V[1],V[3]) and T[3] = (V[0],V[2],V[1]). Each face is opposite the vertex that

is not listed in the face. The tetrahedron adjacent to face T[i] is A[i]. Unfortunately, I had not noticed previously that the primitive class Tetrahedron3 assigns the faces in the opposite order: T[0] = (V[0],V[2],V[1]), T[1] = (V[0],V[1],V[3]), T[2] = (V[0],V[3],V[2]) and T[3] = (V[1],V[2],V[3]).

The edge and face design in GTL will be consistent and uses the designs of MeshStaticManifold2 and MeshStaticManifold3.

The profiling results are listed next for the 2-manifold classes, running on an Intel i9-10900 CPU. The test triangle mesh has 1048576 vertices and 2097117 triangles.

class	numThreads	milliseconds
VETManifoldMesh	1	8471
StaticVETManifoldMesh2	1	1129
	2	904
	4	817
	8	761
	16	759
MeshStaticManifold2	1	816
	2	629
	4	526
	8	542
	16	551

The profiling results are listed next for the 3-manifold classes, running on an Intel i9-10900 CPU. The test tetrahedron mesh has 262144 vertices and 1765604 tetrahedra.

class	numThreads	milliseconds
VTSManifoldMesh	1	10706
StaticVTSManifoldMesh3	1	2035
	2	1512
	4	1256
	8	1160
	16	1092
MeshStaticManifold3	1	2202
	2	691
	4	507
	8	391
	16	362

January 11, 2023. The Error function and the comment in the file about the error formula were incorrect. They appear to have been copied-and-pasted from the ApprOrthogonalLine3.h implementation. The error code was introduced in the port from WM5 to GTE1. Thanks to Scott Johnson for informing me about the mistakes.

GTE/Mathematics/ApprOrthogonalPlane3.h

January 4, 2023. The posted file StaticVETManifoldMesh2.h was out of sync with the development version and was missing the initialization of the members of mAdjacents to *invalid* (-1). I also modified some comments and added some const modifiers where necessary.

```
GTE/Mathematics/Static VETManifold Mesh 2.h
```

January 1, 2023. New file that provides an additional speed-up to VETManifoldMeshNR for constructing static vertex-edge-triangle manifold meshes from collections of triangles.

```
\label{eq:gtmathematics} \begin{split} & GTE/GTM athematics. \{v16, v17\}. vcxproj^* \\ & GTE/Mathematics/StaticVETM anifold Mesh 2.h \end{split}
```

December 24, 2022. Feature request for polyline/polygon offset. The code and a sample application has been added.

```
GTE/GTMathematics.{v16,v17}.vcxproj*
GTE/Mathematics/PolylineOffset.h
GTE/BuildAll*.sln
GTE/Samples/Geometrics/CMakeLists.txt
GTE/Samples/Geometrics/PolylineOffset/*
```

5 Updates to Version 6.4

December 14, 2022. The following are modifications based on complaints from ClangCL for v143 MSVS tools regarding unused variables. The unused variables were actually used in the code (for watching during debugging), but the final values were never consumed by the functions.

```
GTE/Graphics/Shader.cpp (handle)
GTE/Graphics/GL45/GLSLShader.cpp (blockIndex)
GTE/Samples/Intersection/IntersectConvexPolyhedra/ConvexPolyhedron.h (numZero)
GTE/Samples/Graphics/MultipleRenderTargets/MultipleRenderTargetsWindow3.cpp (hr)
GTE/Samples/Physics/RoughPlaneParticle1/RoughPlaneParticle1Window2.h (mSize)
GTE/Samples/Physics/WrigglingSnake/WrigglingSnakeWindow3.cpp (t)
```

Added override to DrawScreenOverlay to resolve ClangCL complaint.

```
GTE/Samples/Geometrics/MinimumAreaBox2D/MinimumAreaBox2DWindow2.h
```

Added missing file to projects.

```
GTE/Samples/Intersection/IntersectConvexPolyhedra/IntersectConvexPolyhedra\{DX11,GL45\}. \{vexproj,vexproj.filters\} \} and the properties of the properties of
```

December 12, 2022. Added new code and sample application for 2D find-intersection queries between a linear component (line, ray, segment) and a segment mesh.

```
GTE/GTMathematics.*.*
GTE/Mathematics/IntrLine2SegmentMesh2.h
```

```
GTE/Mathematics/IntrRay2SegmentMesh2.h
GTE/Mathematics/IntrSegment2SegmentMesh2.h
GTE/BuildAll*.sln
GTE/Samples/Intersection/CMakeLists.txt
GTE/Samples/Intersection/IntersectRayPolygon/*
```

Fixed a comment.

```
GTE/Mathematics/IntrLine2Segment2.h
```

December 1, 2022. Added new 2D distance queries for point-circle and point-arc. Also fixed some missing header file references in the GTMathematics.v16 project.

```
GTE/Mathematics/DistPoint2Arc2.h
GTE/Mathematics/DistPoint2Circle2.h
GTE/GTMathematics.{v16,v17}.vcxproj
GTE/GTMathematics.{v16,v17}.vcxproj.filters
```

November 27, 2022. The CopyBackBuffer call mapped mBackBufferStaging but failed to unmap it after the copy.

```
GTE/Graphics/DX11/DX11Engine.cpp
```

November 11, 2022. Rolling back the changes from the 4 November 2002 update. The code is faster but the rounding errors cause misclassification of the number of points of intersection. Welcome to the trade-off of floating-point versus rational arithmetic. At some point I need to implement rational arithmetic classes using the GNU Multiprecision Library to take advantage of the better performance for arbitrary precision multiplication. At a later date, I can implement a similar speed-up for BSNumber and BSRational.

```
GTE/Mathematics/IntrEllipse2Ellipse2.h
```

November 4, 2022. When using BSRational < UIntegerAP32 > for template type T, the number of words used in the SolveQuartic root finder can be extremely large—on the order of 100000. This leads to poor performance. The root finder has numerical rounding errors whether T is a floating-point type or a rational type, so to avoid the poor performance, the rational-valued quartic coefficients are converted to double and then reconverted to T. This introduces a small amount of rounding error, but performance is significantly better.

```
{\rm GTE/Mathematics/IntrEllipse 2Ellipse 2.h}
```

November 2, 2022. Added a fuzzy containment that tests whether a point is on a circular arc. The non-fuzzy containment requires the point to be on the circle of the arc (or nearly on the circle within floating-point rounding errors).

```
GTE/Mathematics/Arc2.h
```

October 17, 2022. Back-ported QuadricSurface from GTL to GTE, both versions unit tested.

GTE/Mathematics/QuadricSurface.h

September 23, 2022. Fixed a bug in ComputeSqrDistance on line 247 (incorrect sign on s). Thanks to Tom Foster for reporting the bug.

GTE/Mathematics/IntrCanonicalBox 3 Cylinder 3.h

August 25, 2022. Reimplemented the TCB spline code based on the rewrite of the PDF document Kochanek-Bartels Cubic Splines (TCB Splines). I removed the tangent adjustments suggested by Kochanek and Bartels (based on discrete variables), replacing them with adjustments based on continuous variables. I added support for specifying the boundary tangents explicitly rather than duplicating the endpoints of the keyframes and computing the boundary tangents internally. Finally, I added a parameter (λ) per key frame position to control the speed at those positions and ensure continuity of speed.

GTE/Mathematics/TCBSplineCurve.h

August 23, 2022. Feature request for code to compute the minimum-area aligned box that contains a circular arc.

GTE/Mathematics/ContAlignedBox2Arc2.h

August 16, 2022. Reset some std::vector arrays for re-use of the operator() function. Added mConvexHull3 member and accessor (from Leopard20 at github). Modified the file version.

GTE/Mathematics/MinimumVolumeBox3.h

July 13, 2022. The managed library project compiles with the directory structure of GTE, but if folders are moved elsewhere, the managed library needed \$(GTE_PATH) for the header search path. GTE_PATH is an environment variable that stores the path to the top-level folder GeometricTools/GTE (see the installation and release notes).

GTE/Samples/CSharpCppManaged/ManagedLibrary/ManagedLibrary.*,vcxproj

July 12, 2022. Removed the file ManagedObject.h, consolidating the contents with the managed files MinimumVolumeBox.{h,cpp}. Updated the copyright date in the assembly file. Modified the comments in the program file.

GTE/Samples/CSharpCppManaged/CSharpCppManaged.*.sln

GTE/Samples/CSharpCppManaged/ManagedLibrary/ManagedLibrary.*

GTE/Samples/CSharpCppManaged/ManagedLibrary/MinimumVolumeBox.{h,cpp}

GTE/Samples/CSharpCppManaged/ManagedLibrary/ManagedObject.h

GTE/Samples/CSharpCppManaged/CSharpApplication/Properties/AssemblyInfo.cs

 ${\rm GTE/Samples/CSharpCppManaged/CSharpApplication/Program.cs}$

July 4, 2022. The Window2 class was implemented not to allow window resizing. I removed this constraint and added comments in the header file about the responsibilities of an application class derived from Window2. The 2D fluid simulation sample application was modified to illustrate the resizing.

```
GTE/Applications/Window2.{h,cpp}
GTE/Samples/Physics/Fluids2D/Fluids2DMain.cpp
GTE/Samples/Physics/Fluids2D/Fluids2DWindow2.{h,cpp}
```

Modified comments that referred to the old file names GteSOMEFILE.h, replacing them by SOMEFILE.h.

```
GTE/Applications/Window2.cpp
GTE/Graphics/DX11/DX11InputLayout.h
GTE/Mathematics/ApprCone3.h
GTE/Mathematics/ApprTorus3.h
GTE/Mathematics/BSNumber.h
GTE/Mathematics/BSplineReduction.h
GTE/Mathematics/Cone.h
GTE/Mathematics/Math.h
GTE/Mathematics/MinimumAreaCircle2.h
GTE/Mathematics/MinimumVolumeSphere3.h
GTE/Mathematics/Quaternion.h
GTE/Mathematics/SlerpEstimate.h
```

June 29, 2022. The IsOnSurface function is a copy-and-paste error from the implicit curve file. I modified the name to IsOnCurve. I also set the output curvature on early exit in order not to leave output uninitialized.

```
GTE/Mathematics/ImplicitCurve2.h
```

Greatly simplified the implementation based on a revision of the document PrincipleCurvature.pdf.

```
{\rm GTE/Mathematics/ImplicitSurface 3.h}
```

June 26, 2022. Added a new class VETManifoldMeshNR which represents a vertex-edge-triangle manifold mesh for which triangles are provided as a single batch and NO REMOVE operations are going to be performed on the mesh. VETManifoldMeshNR significantly outperforms VETManifoldMesh. VETManifoldMesh is general purpose, allowing triangle insertions and triangle removals. The underlying C++ container classes lead to significant memory allocation/deallocation costs and are also expensive for find operations. It turns out that the design of VETManifoldMeshNR automatically gives you vertex adjacency information, so there is no ETManifoldMeshNR implementation. It is a requirement that the input triangles form a manifold mesh with consistently ordered triangles. In most applications, this requirement is already satisfied.

```
GTE/Mathematics/VETManifoldMeshNR.h
```

The VETManifoldMeshNR class is designed to minimize the allocations. For example, using this class for a collection of 1131652 positions and 2242293 triangles, the CPU times on an Intel (R) Core (TM) i9-10900 are as follows.

	ETManifoldMesh	VETManifoldMeshNR
graph creation	2234 milliseconds	118 milliseconds
connected component labeling	2169 milliseconds	40 milliseconds
get boundary polygons	232 milliseconds	25 milliseconds

Added comments to indicate that VETManifoldMeshNR might be a better choice for your application if it meets the preconditions.

```
\label{eq:GTE-Mathematics} \begin{split} & \operatorname{GTE/Mathematics/ETManifoldMesh.h} \\ & \operatorname{GTE/Mathematics/VETManifoldMesh.h} \end{split}
```

6 Updates to Version 6.3

June 8, 2022. Added new files that contain an efficient implementation of natural cubic splines and natural quintic splines. The PDF documentation has been revised accordingly, https://www.geometrictools.com/Documentation/NaturalSplines.pdf. The class NaturalSplineCurve will be deprecated in favor of the new classes.

```
GTE/Mathematics/NaturalCubicSpline.h
GTE/Mathematics/NaturalQuinticSpline.h
```

Fixed gcc compiler warnings (signed/unsigned integer comparisons).

```
GTE/Mathematics/NaturalSplineCurve.h
```

Fixed gcc errors about the keyword template required before the dependent typenames involving the Degree* function calls. The errors occurred with gcc 12.1.1 on Fedora 36 but not with gcc 9.3.0 on Ubuntu or with Microsoft compilers.

```
GTE/Mathematics/ASinEstimate.h
GTE/Mathematics/ExpEstimate.h
GTE/Mathematics/LogEstimate.h
```

Fixed an error in the deprecated file for UniqueVerticesTriangles; the <array> header is not explicitly included. This occurred with gcc 12.1.1 on Fedora 36 even though my instantiation tool did not include explicit instantiation for that class. The error did not occur with gcc 9.3.0 on Ubuntu 20.04.1 LTS or Microsoft compilers when running the tool.

```
GTE/Mathematics/UniqueVerticesTriangles.h
```

Fixed bugs in a block of code that is not exercised by the ShaderReflection sample application. This problem was caught by gcc 12.1.1 on Fedora 36.

```
GTE/Graphics/GL45/GLSLReflection.cpp
```

Modified code to avoid a potentially uninitialized variable warning from gcc 12.1.1 on Fedora 36.

```
\label{lem:condition} GTE/Samples/Geometrics/IncrementalDelaunay2/IncrementalDelaunay2Window2.cpp GTE/Samples/Intersection/IntersectTriangles2D/IntersectTriangles2DWindow2.cpp GTE/Samples/Mathematics/Interpolation2DWindow3.cpp
```

Fedora 36 with gcc 12.1.1 complains about potential index-out-of-range because Evaluate references all possible elements, but the compiler is unaware that the logic of Evaluate is designed to assign only those elements that are valid. For now, I am passing in an array of 3-tuples knowing that only one will be filled in. Added arrays of N-tuples to avoid the warnings.

```
GTE/Mathematics/ParametricCurve.h
GTE/Mathematics/ParametricSurface.h
GTE/Samples/Mathematics/BSplineCurveReduction/BSplineCurveReductionWindow3.cpp
```

June 4, 2022. The constructor for free or closed splines allocated more than enough elements for mCoefficients and the GetNumPoints() function returned the number of points based on the size of mCoefficients. The constructor for clamped splines allocated exactly the correct number of elements for mCoefficients, but then GetNumPoints() returned the incorrect number of points. This caused too few points to be processed in clamped splines. This occurred when the optimization was added to minimize memory allocations and deallocations for free splines. The optimization code has been reworked and the same memory optimization was added for closed and clamped splines. The unit tests pass for all 3 flavors of splines.

GTE/Mathematics/NaturalSplineCurve.h

May 30, 2022. The IsPowerOfTwo(int32_t) function called itself (infinite recursion). Modified the static cast to use uint32_t as intended.

GTE/Mathematics/BitHacks.h

May 16, 2022. In the GTL development, fixed a bug in the Inverse function for Transform<T> objects. The unit tests were incomplete in that they tested the inverse directly using queries to the internal matrices of Transform<T> rather than verifying the correctness of the output of Inverse. The corrections were backported to GTE.

GTE/Mathematics/Transform.h

The RectangleManager code was copied, pasted and modified to produce the BoxManager code. The comments were part of this and the BoxManager code referred to rectangles rather than boxes. Also, non-const references in both classes were modified to const references.

GTE/Mathematics/BoxManager.h GTE/Mathematics/RectangleManager.h

7 Updates to Version 6.2

April 3, 2022. By user request, on Microsoft Windows I added virtual OnWindowsMessage to WindowApplication and called by WindowSystem::WindowProcedure. This allows the application to use a third-party UI package, processing windows messages intended for that package. A return value of true tells the window procedure not to pass the message to the application window.

```
GTE/Applications/WindowApplication.{h,cpp} GTE/Applications/MSW/WindowSystem.cpp
```

April 2, 2022. Ported the Wild Magic 5 graphics sample ShadowMaps to GTE6. This is the last of the Wild Magic code I had planned on porting.

```
GTE/BuildAll*.*
GTE/Samples/Graphics/CMakeLists.txt
GTE/Samples/Graphics/ShadowMaps/*
GTE/Samples/Data/Stone.png
```

March 29, 2022. Ported the Wild Magic 5 MeshSmoother class to GTE6.

```
GTE/Mathematics/MeshSmoother.h
```

March 28, 2022. I finally trapped the problem with Windows OpenGL (WGL) where the first-drawn frame is not correct. I added a swap-buffers call immediately after creating the WGLEngine object (in the application layer), which eliminated the problem.

```
GTE/Applications/MSW/WindowSystem.cpp
```

Ported the Wild Magic 5 skinning sample to GTE6.

```
GTE/BuildAll*.*
GTE/Samples/Graphics/CMakeLists.txt
GTE/Samples/Graphics/Skinning/*
```

Added new constructors to avoid the repeated pattern of default construction of MeshFactory followed by the SetVertexFormat call.

```
GTE/Graphics/MeshFactory. {h,cpp}
```

Ported the line-torus find-intersection query from Wild Magic 5 to GTE 6 (at user request). Added a sample application to show that the code is working correctly. Internal unit tests have also been added.

```
GTE/BuildAll*.*
GTE/GTMathematics*.*
GTE/Mathematics/IntrLine3Torus3.h
GTE/Samples/Intersection/CMakeLists.txt
GTE/Samples/Intersection/IntersectLine3Torus3/*
```

March 25, 2022. The current 2D segment-segment queries use the find-intersection query for two lines, but the segments are converted to center-direction-extent form. The two-point representation has endpoints p_0 and p_1 and the parameterization is $p_0 + t(p_1 - p_0)$ for $t \in [0, 1]$. The center-direction-extent form is c + sd for $|s| \le e$. The center is $c = (p_0 + p_1)/2$, the direction is $d = (p_1 - p_0)/|p_1 - p_0|$ and the extent is $e = |p_1 - p_0|/2$. The computation of d involves a normalization which generally cannot be computed exactly with rational arithmetic. The computation of e is also not exact. The segment parameters returned from the queries are relative to s, not to t. The old queries are operator() functions and still exist. To allow for exact rational computation, I added new queries named Exact which uses the two-point form for segments. [In GTL development, I have been eliminating the use of the segment center-direction-extent form.]

```
GTE/Mathematics/IntrSegment2Segment2.h
```

The code had a call Normalize(diff) that is not necessary because the sign tests dependent on diff are (theoretically) independent of the length of diff. Removing the normalize call now allows the code to produce theoretically correct results when type T is a rational type.

```
GTE/Mathematics/IntrLine2Line2.h
```

Replace parenthesized casts by static_casts.

```
GTE/Mathematics/IntrLine2Line2.h
GTE/Mathematics/IntrLine2Ray2.h
GTE/Mathematics/IntrLine2Segment2.h
GTE/Mathematics/IntrRay2Ray2.h
GTE/Mathematics/IntrRay2Segment2.h
GTE/Mathematics/IntrSegment2Segment2.h
```

March 23, 2022. The SetRow function was missing a return statement.

```
GTE/Mathematics/GMatrix.h
```

March 22, 2022. Added abstract base classes for implicit curves in 2D, class ImplicitCurve2, and implicit surface in 3D, class ImplicitSurface3. The latter is a port of ImplicitSurface from Wild Magic 5. These classes support computation of coordinate frames and curvature information. For parametric curves and surfaces, see FrenetFrame and DarbouxFrame.

```
GTE/GTMathematics.*
GTE/Mathematics/ImplicitCurve2.h
GTE/Mathematics/ImplicitSurface3.h
```

Ported the Wild Magic 5 graphics sample VolumeFog to GTE6.

```
GTE/BuildAll*
GTE/GTGraphics.*.*
GTE/Graphics/GTGraphics.h
GTE/Graphics/VolumeFogEffect.{h,cpp}
```

```
GTE/Samples/Graphics/CMakeLists.txt
GTE/Samples/Graphics/VolumeFog/*
GTE/Data/BlueSky.png
GTE/Data/Shaders/VolumeFogEffect.{vs,ps}.{hlsl,glsl}
```

Fixed the minor number in file versions. Looks like versioning is the bane of the month.

```
GTE/Graphics/BoundTree.h
GTE/Graphics/CollisionGroup.h
GTE/Graphics/CollisionMesh.{h,cpp}
GTE/Graphics/CollisionRecord.h
GTE/Graphics/PlanarShadowEffect.{h,cpp}
GTE/Graphics/PlanarShadowEffect.{h,cpp}
GTE/Mathematics/ApprCone3EllipseAndPoints.h
GTE/Samples/Mathematics/FitConeByEllipseAndPoints/FitConeByEllipseAndPoints*.{h,cpp}
GTE/Samples/Physics/CollisionsBoundTree/CollisionsBoundTree*.{h,cpp}
GTE/Samples/Physics/CollisionsMovingSpheres/CollisionsMovingSphereTriangle*.{h,cpp}
```

March 21, 2022. Ported the Wild Magic 5 sample CollisionsMovingSphereTriangle to GTE6.

```
GTE/BuildAll*
GTE/Samples/Physics/CMakeLists.txt
GTE/Samples/Physics/CollisionsMovingSphereTriangle/*
```

March 20, 2022. Ported the Wild Magic 5 sample CollisionsMovingSpheres to GTE6. The CollisionsBoundTree sample should have been in the Physics folder.

```
GTE/BuildAll*
GTE/Samples/SceneGraphs/CMakeLists.txt
GTE/Samples/Physics/CMakeLists.txt
GTE/Samples/Physics/CollisionsMovingSpheres/*
GTE/Samples/SceneGraphs/CollisionsBoundTree/*
GTE/Samples/Physics/CollisionsBoundTree/*
```

Ported the Wild Magic 5 collision detection code to GTE6: BoundTree, CollisionGroup and CollisionRecord. Added a wrapper class, CollisionMesh, that provides the interface to a Visual-based triangle mesh to be used at a template parameter for the collision detection code. Added test-intersection and find-intersection queries for moving triangles. Ported the WM5 sample CollisionsBoundTree to illustrate use of the collision detection.

```
GTE/GTGraphics.{v16,v16}.vexproj
GTE/GTGraphics.{v16,v16}.vexproj.filters
GTE/Graphics/GTGraphics.h
GTE/Graphics/CMakeLists.txt
GTE/Mathematics/IntrTriangle3Triangle3.h
GTE/Samples/CMakeLists.txt
GTE/Graphics/BoundTree.h
```

```
GTE/Graphics/CollisionGroup.h
GTE/Graphics/CollisionRecord.h
GTE/Graphics/CollisionMesh.{h,cpp}
GTE/Samples/SceneGraphs/CollisionsBoundTree/*
```

I forgot to update the minor version from 1 to 2 when I posted GTE6.2. Time to automate this step.

```
GTE/CMakeLists.txt
GTE/Samples/CMakeLists.txt
GTE/Samples/Distance/CMakeLists.txt
GTE/Samples/Geometrics/CMakeLists.txt
GTE/Samples/Graphics/CMakeLists.txt
GTE/Samples/Imagics/CMakeLists.txt
GTE/Samples/Intersection/CMakeLists.txt
GTE/Samples/Mathematics/CMakeLists.txt
GTE/Samples/Physics/CMakeLists.txt
GTE/Samples/Physics/CMakeLists.txt
```

March 18, 2022. Fixed a bug in ContainsPoint. Modified the internal unit tests to include the test that exposes the bug.

```
GTE/Mathematics/IntrTriangle3Triangle3.h
```

Removed the MSVS 2015 and MSVS 2017 versions of the C#/managed/C++ projects because I no longer support these compilers. The MSVS 2019 projects still exist. I added projects for MSVS 2022. Fixed the path problem in the MSVS 2019 version (modified environment variable from GTE4_PATH to GTE_PATH).

```
GTE/Samples/CSharpCppManaged/CSharpCppManaged.{v14,v15}.sln
GTE/Samples/CSharpCppManaged/CSharpApplication/CSharpApplication.{v14,v15}.csproj
GTE/Samples/CSharpCppManaged/CppLibrary/CppLibrary.{v14,v15}.*
GTE/Samples/CSharpCppManaged/ManagedLibrary/ManagedLibrary.{v14,v15}.*
GTE/Samples/CSharpCppManaged/CppLibrary/CppLibrary.v16.vcxproj
GTE/Samples/CSharpCppManaged/CSharpCppManaged.v16.sln
GTE/Samples/CSharpCppManaged/CSharpApplication/CSharpApplication.v16.csproj
GTE/Samples/CSharpCppManaged/CppLibrary/CppLibrary.v16.*
GTE/Samples/CSharpCppManaged/ManagedLibrary/ManagedLibrary.v16.*
```

March 13, 2022. The Math.h file generated compiler errors when I used one of the inline non-templated functions (needed <cstdint>). The UniqueVerticesTriangles.h file generated compiler errors when I tried to use it (needed <set>). This file is deprecated, but until it is removed it needs to compile. I updated my internal instantiation tool to handle these files appropriately.

```
GTE/Mathematics/Math.h
GTE/UniqueVerticesTriangles.h
```

8 Updates to Version 6.1

March 7, 2022. The planar reflection constructor had out-of-order initialization of members, and gcc on Linux complained about this. The Microsoft compilers (2019/2022) did not complain. I also removed a block of code in the constructor (unexposed in a conditional compilation block) that was moved to a class member function.

GTE/Graphics/PlanarReflectionEffect.cpp

The change to the interface for PlanarReflectionEffect required changes to the bouncing ball sample application.

GTE/Samples/Physics/BouncingBall/BouncingBallWindow3. {h,cpp}

The MinimumWidthPoints2 class is templated with class T. It contained a line using RotatingCalipers = typename RotatingCalipers<T> which Microsoft compilers allow. The gcc compilers complained about the typename, so I removed it. I removed two unused variables. There was a sign mismatch in a loop counter.

GTE/Mathematics/MinimumWidthPoints2.h

Removed unused lines of code (old iterator code that was replaced by range-based iteration) and fixeds a sign mismatch in a loop. Removed the declaration for static constexpr maxFloat = std::numeric_limits<float>::max(); and now use the max() value itself in the code. I must be missing something about declaring class-member constexpr values; the loader for gcc complained that maxFloat is undefined. The Microsoft compilers (2019/2022) never complain about such a declaration.

GTE/Graphics/CLODMeshCreator.h

An unreferenced variable for the camera position needed to be accessed in two lines of code rather than re-lookup the variable.

GTE/Samples/Physics/DLODNodes/DLODNodesWindow3.cpp

The gcc compiler complained about the compound Boolean expression in the GTE_ASSERT statement in SwitchNode::SetActiveChild. It wanted parentheses around the and expression.

GTE/Graphics/SwitchNode.cpp

The CMake list of source files needed to be updated for PlanarShadowEffect.cpp, SwitchNode.cpp, CLODMesh.cpp and DLODNode.cpp.

GTE/Graphics/CMakeLists.txt

March 6, 2022. I wrote a GTE6 sample application for planar shadows that is similar to the one for Wild Magic 5. I revised the planar reflections code so that the two effects have essentially the same design.

```
GTE/BuildAll*.sln
GTE/Graphics/PlanarShadowEffect.{h,cpp}
GTE/Graphics.h
GTE/Samples/Graphics/PlanarShadows/PlanarShadows*.vcxproj
GTE/Samples/Graphics/PlanarShadows/PlanarShadows*.vcxproj.filter
GTE/Samples/Graphics/PlanarShadows/PlanarShadowsMain.cpp
GTE/Samples/Graphics/PlanarShadows/PlanarShadowsWindow3.{h,cpp}
GTE/Samples/Graphics/PlanarShadows/PlanarShadows.code-workspace
GTE/Samples/Graphics/PlanarShadows/CMakeLists.txt
GTE/Samples/Graphics/PlanarShadows/CMakeSample.sh
GTE/Samples/Graphics/PlanarShadows/cmake-variants.json
GTE/Samples/Graphics/PlanarShadows/.vscode/launch.json
GTE/Samples/Graphics/PlanarShadows/.vscode/settings.json
GTE/Samples/Graphics/CMakeLists.txt
GTE/Graphics/PlanarReflectionEffect.{h,cpp}
GTE/Samples/Graphics/PlanarReflections/PlanarReflectionsMain.cpp
GTE/Samples/Graphics/PlanarReflections/PlanarReflectionsWindow3.{h,cpp}
```

March 4, 2022. I wrote a GTE6 sample application for planar reflections that is similar to the one for Wild Magic 5. The PlanarReflectionEffect drawing function had a bug. It needed to set the back-face stencil parameters in addition to the front-face stencil parameters. Without the back-face parameters, the reflection caster was drawn on both sides of the reflection plane.

```
GTE/BuildAll*.sln
GTE/Samples/Graphics/PlanarReflections/PlanarReflections*.vcxproj
GTE/Samples/Graphics/PlanarReflections/PlanarReflections*.vcxproj.filter
GTE/Samples/Graphics/PlanarReflections/PlanarReflectionsMain.cpp
GTE/Samples/Graphics/PlanarReflections/PlanarReflectionsWindow3.{h,cpp}
GTE/Samples/Graphics/PlanarReflections/PlanarReflections.code-workspace
GTE/Samples/Graphics/PlanarReflections/CMakeLists.txt
GTE/Samples/Graphics/PlanarReflections/CMakeSample.sh
GTE/Samples/Graphics/PlanarReflections/cmake-variants.json
GTE/Samples/Graphics/PlanarReflections/.vscode/launch.json
GTE/Samples/Graphics/PlanarReflections/.vscode/settings.json
GTE/Samples/Graphics/CMakeLists.txt
GTE/PlanarReflectionEffect.{h,cpp}
```

After looking at the requirements for the feature request, I modified the return value of MinimumWidth-Points2::operator() to be OrientedBox2<T> to be consistent with the minimum-area box code. The sample application now draws the minimum-area box and the minimum-width box for comparison.

```
\label{lem:gte} GTE/Mathematics/MinimumWidthPoints2.h \\ GTE/Samples/Geometrics/MinimumAreaBox2DWindow2.\{h,cpp\}
```

March 3, 2022. Added an implementation of the rotating calipers algorithm, class RotatingCalipers. The goal was to refactor MinimumAreaBox2 to pull out the rotating calipers. However, this does not work because the minimum-area algorithm uses a pair of rotating calipers that work together. Added a new class MinimumWidthPoints2 that uses the rotating calipers algorithm to compute the width of a 2D point set. For now I

have modified the MinimumAreaBox2D sample application to show also the results from computing the width of a point set. I also cleaned up the comments to use current formatting rules. And I added functions to allow passing std::vector inputs rather than raw pointers.

```
GTE/Mathematics/RotatingCalipers.h
GTE/Mathematics/MinimumWidthPoints2.h
GTE/Mathematics/MinimumAreaBox2.h
GTE/Mathematics/GTMathematics.*.vcxproj
GTE/Mathematics/GTMathematics.*.vcxproj.filters
GTE/Samples/Geometrics/MinimumAreaBox2DWindow2.{h,cpp}
```

The ConvexHull2 class was supposed to have switched from FPInterval to SWInterval, but I apparently overlooked this. The FPInterval class uses floating-point hardware operations to support interval arithmetic; however, the GCC compiles ignores the changes to the floating-point environment (it does not support modifying the rounding mode of the FPU). The SWInterval class implements interval arithmetic and rounds using software operations.

```
GTE/Mathematics/ConvexHull2.h
```

Two class members were not initialized by the constructor.

```
GTE/Graphics/DLODNode.cpp
```

February 25, 2022. Feature request to fit a cone to known elliptical cross sections and some additional points (ApprCone3EllipseAndPoints). If the cross sections are provided as point samples approximately on the ellipses, the new code also includes a class to extract points for each ellipse because the points might be stored in a file in some unknown order (ApprCone3ExtractEllipses). 3D ellipses are then fit to each subset of points in order to obtain the ellipse input to ApprCone3EllipseAndPoints. A PDF has been added to the documentation to describe the fitting algorithm, FitConeToEllipseAndPoints.pdf.

```
GTE/BuildAll*.sln
GTE/Mathematics/GTMathematics.*.vcxproj
GTE/Mathematics/GTMathematics.*.vcxproj.filters
GTE/Mathematics/ApprCone3EllipseAndPoints.h
GTE/Samples/Mathematics/FitConeByEllipseAndPoints/FitConeByEllipseAndPoints*.vcxproj
GTE/Samples/Mathematics/FitConeByEllipseAndPoints/FitConeByEllipseAndPoints*. vcxproj. filter and the property of the proper
GTE/Samples/Mathematics/FitConeByEllipseAndPoints/FitConeByEllipseAndPointsMain.cpp
GTE/Samples/Mathematics/FitConeByEllipseAndPoints/FitConeByEllipseAndPointsWindow3.{h,cpp}
GTE/Samples/Mathematics/FitConeByEllipseAndPoints/Data/CircleAndVertex.txt
GTE/Samples/Mathematics/FitConeByEllipseAndPoints/Data/OneCircleOneEllipse.txt
GTE/Samples/Mathematics/FitConeByEllipseAndPoints/Data/TwoEllipses.txt
{\tt GTE/Samples/Mathematics/FitConeByEllipseAndPoints/Data/TwoPartialEllipses.txt}
GTE/Samples/Mathematics/FitConeBvEllipseAndPoints/FitConeBvEllipseAndPoints.code-workspace
GTE/Samples/Mathematics/FitConeByEllipseAndPoints/CMakeLists.txt
{\tt GTE/Samples/Mathematics/FitConeByEllipseAndPoints/CMakeSample.sh} \\
GTE/Samples/Mathematics/FitConeByEllipseAndPoints/cmake-variants.json
GTE/Samples/Mathematics/FitConeByEllipseAndPoints/.vscode/launch.json
```

```
\label{lipseAndPoints/vscode/settings.json} GTE/Samples/Mathematics/FitConeByEllipseAndPoints/.vscode/settings.json\\ GTE/Samples/Mathematics/CMakeLists.txt
```

February 24, 2022. Ported the WM5 classes ClodMesh, CreateClodMesh and CollapseRecord to GTE6 classes CLODMesh, CLODMeshCreator and CLODCollapseRecord. Ported the WM5 sample ClodMeshes to the GTE6 sample CLODMeshes.

```
GTE/BuildAll*.sln
GTE/Graphics/GTGraphics.h
GTE/Graphics/GTGraphics.*.vcxproj
GTE/Graphics/GTGraphics.*.vcxproj.filters
GTE/Graphics/CLODMeshCreator.h
GTE/Graphics/CLODMesh.{h,cpp}
GTE/Graphics/CLODCollapseRecord.h
{\tt GTE/Samples/SceneGraphs/CLODMeshes/CLODMeshes*.vcxproj}
GTE/Samples/SceneGraphs/CLODMeshes/CLODMeshes*.vcxproj.filter
GTE/Samples/SceneGraphs/CLODMeshes/CLODMeshesMain.cpp
GTE/Samples/SceneGraphs/CLODMeshes/CLODMeshesWindow3.{h,cpp}
GTE/Samples/SceneGraphs/CLODMeshes/Data/FunctionX64Y64R8.png
GTE/Samples/SceneGraphs/CLODMeshes/CLODMeshes.code-workspace
GTE/Samples/SceneGraphs/CLODMeshes/CMakeLists.txt
{\rm GTE/Samples/Scene Graphs/CLODMeshes/CMake Sample.sh}
GTE/Samples/SceneGraphs/CLODMeshes/cmake-variants.json
GTE/Samples/SceneGraphs/CLODMeshes/.vscode/launch.json
GTE/Samples/SceneGraphs/CLODMeshes/.vscode/settings.json
GTE/Samples/SceneGraphs/CMakeLists.txt
```

February 11, 2022. Modified the GenerateProject tool to generate the Visual Studio Code workspace files for sample applications.

```
GTE/Tools/GenerateProject/GenerateProject.*
GTE/Tools/GenerateProject/ProjectTemplateVSCode.{h,cpp}
```

Added missing *.code-workspace files to the recently ported physics samples.

```
GTE/Samples/Physics/BouncingSpheres/BouncingSpheres.code-workspace GTE/Samples/Physics/BouncingTetrahedra/BouncingTetrahedra.code-workspace GTE/Samples/Physics/RoughPlaneFlatBoard/RoughPlaneFlatBoard.code-workspace GTE/Samples/Physics/RoughPlaneParticle1/RoughPlaneParticle1.code-workspace GTE/Samples/Physics/RoughPlaneParticle2/RoughPlaneParticle2.code-workspace GTE/Samples/Physics/RoughPlaneSolidBox/RoughPlaneSolidBox.code-workspace GTE/Samples/Physics/RoughPlaneThinRod1/RoughPlaneThinRod1.code-workspace GTE/Samples/Physics/RoughPlaneThinRod2/RoughPlaneThinRod2.code-workspace GTE/Samples/Physics/WaterDropFormation/WaterDropFormation.code-workspace GTE/Samples/Physics/WrigglingSnake/WrigglingSnake.code-workspace
```

Ported the SwitchNode class and SwitchNodes sample application from Wild Magic 5 to Geometric Tools Engine 6.

```
GTE/BuildAll*.sln
GTE/Graphics/GTGraphics.h
GTE/Graphics/GTGraphics.*.vcxproj
GTE/Graphics/GTGraphics.*.vcxproj.filters
GTE/Graphics/SwitchNode.{h,cpp}
GTE/Samples/SceneGraphs/SwitchNodes/SwitchNodes*.vcxproj
GTE/Samples/SceneGraphs/SwitchNodes/SwitchNodes*.vcxproj.filter
GTE/Samples/Scene Graphs/SwitchNodes/SwitchNodesMain.cpp\\
GTE/Samples/SceneGraphs/SwitchNodes/SwitchNodesWindow3. {h,cpp}
GTE/Samples/SceneGraphs/SwitchNodes/SwitchNodes.code-workspace
GTE/Samples/SceneGraphs/SwitchNodes/CMakeLists.txt
GTE/Samples/SceneGraphs/SwitchNodes/CMakeSample.sh
GTE/Samples/SceneGraphs/SwitchNodes/cmake-variants.json
GTE/Samples/SceneGraphs/SwitchNodes/.vscode/launch.json
GTE/Samples/SceneGraphs/SwitchNodes/.vscode/settings.json
{\rm GTE/Samples/Scene Graphs/CMakeLists.txt}
```

Ported the DLODNode (dynamic level of detail node) class and DLODNodes sample application from Wild Magic 5 to Geometric Tools Engine 6.

```
GTE/BuildAll*.sln
GTE/Graphics/GTGraphics.h
GTE/Graphics/GTGraphics.*.vcxproi
GTE/Graphics/GTGraphics.*.vcxproj.filters
GTE/Graphics/DLODNode.{h,cpp}
GTE/Samples/SceneGraphs/DLODNodes/DLODNodes*.vcxproj
GTE/Samples/SceneGraphs/DLODNodes/DLODNodes*.vcxproj.filter
GTE/Samples/SceneGraphs/DLODNodes/DLODNodesMain.cpp
GTE/Samples/SceneGraphs/DLODNodes/DLODNodesWindow3.{h.cpp}
GTE/Samples/SceneGraphs/DLODNodes/DLODNodes.code-workspace
GTE/Samples/SceneGraphs/DLODNodes/CMakeLists.txt
GTE/Samples/SceneGraphs/DLODNodes/CMakeSample.sh
GTE/Samples/SceneGraphs/DLODNodes/cmake-variants.json
GTE/Samples/SceneGraphs/DLODNodes/.vscode/launch.json
GTE/Samples/SceneGraphs/DLODNodes/.vscode/settings.json
GTE/Samples/SceneGraphs/CMakeLists.txt
```

9 Updates to Version 6.0

February 7, 2022. Fixed a compiler error on Linux for a mismatch in size_t and int32_t. Changed the type of mNumCtrlPoints and mDegree to size_t.

GTE/Samples/Physics/WrigglingSnake/WrigglingSnakeWindow3.h

February 6, 2022. Ported the Wild Magic 5 physics sample BouncingTetrahedra to GTE. The port of BouncingSpheres was modified so that the two samples have the same conceptual framework.

```
GTE/Samples/Physics/BouncingTetrahedra/BouncingTetrahedra*.vcxproj
GTE/Samples/Physics/BouncingTetrahedra/BouncingTetrahedra*.vcxproj.filter
GTE/Samples/Physics/BouncingTetrahedra/BouncingTetrahedraMain.cpp
GTE/Samples/Physics/BouncingTetrahedra/BouncingTetrahedraWindow3.{h,cpp}
GTE/Samples/Physics/BouncingTetrahedra/PhysicsModule.{h,cpp}
GTE/Samples/Physics/BouncingTetrahedra/RigidPlane.{h,cpp}
GTE/Samples/Physics/BouncingTetrahedra/RigidTetrahedron. {h,cpp}
GTE/Samples/Physics/BouncingTetrahedra/Initial.txt
GTE/Samples/Physics/BouncingSpheres/BouncingSpheres*.vcxproj
GTE/Samples/Physics/BouncingSpheres/BouncingSpheres*.vcxproj.filter
GTE/Samples/Physics/BouncingSpheres/BouncingSpheresMain.cpp
GTE/Samples/Physics/BouncingSpheres/BouncingSpheresWindow3.{h,cpp}
GTE/Samples/Physics/BouncingSpheres/PhysicsModule.{h,cpp}
GTE/Samples/Physics/BouncingSpheres/BouncingSpheresMain.cpp
GTE/Samples/Physics/BouncingSpheres/BouncingSpheresWindow3. {h,cpp}
GTE/Samples/Physics/BouncingSpheres/RigidPlane. {h,cpp}
GTE/Samples/Physics/BouncingSpheres/RigidSphere. {h,cpp}
GTE/Samples/Physics/BouncingSpheres/Initial.txt
```

I factored out the impulse computations from the physics samples and moved them to RigidBody. The code now can be shared by the applications.

```
GTE/Mathematics/RigidBody.h
```

The Tetrahedron3 class has additional framework to support computing normals at features (vertices, edges, faces). The DistPoint3Tetrahedron3 query was modified because of an interface change in Tetrahedron3.

```
GTE/Mathematics/Tetrahedron3.h
GTE/Mathematics/DistPoint3Tetrahedron3.h
```

The algorithm I implemented for distance between tetrahedra was not robust because of testing for containment of vertices of one tetrahedron in another. I modified it to test centroids instead.

```
GTE/Mathematics/DistTetrahedron3Tetrahedron3.h
```

Added a new file for the test-intersection query between tetrahedra using the method of separating axes. This allowed for better performance in BouncingTetrahedra compared to using distance between tetrahedra.

```
GTE/Mathematics/IntrTetrahedron3Tetrahedron3.h
```

Fixed comments in the file.

```
GTE/Mathematics/IntrOrientedBox3OrientedBox3.h
```

February 3, 2022. Added missing projects from the MSVS 2019 build-all solutions. Added new build-all solutions for MSVS 2022.

```
GTE/BuildAll.v16.sln
GTE/BuildAllDX11.v16.sln
GTE/BuildAllGL45.v16.sln
GTE/BuildAll.v17.sln
GTE/BuildAllDX11.v17.sln
GTE/BuildAllGL45.v17.sln
```

February 1, 2022. Added new file that implements tetrahedron-tetrahedron query. This is needed for the port of BouncingTetrahedra from Wild Magic 5 to Geometric Tools Engine.

```
GTE/Mathematics/DistTetrahedron3Tetrahedron3.h
```

Modified the interfaces for computing barycentric coordinates. The raw arrays bary[] were replaced by std::array objects.

```
GTE/Mathematics/Vector2.h
GTE/Mathematics/Vector3.h
GTE/Mathematics/Delaunay2Mesh.h
GTE/Mathematics/Delaunay3Mesh.h
GTE/Mathematics/DistPoint3Tetrahedron3.h
GTE/Mathematics/IntpQuadraticNonuniform2.h
GTE/Mathematics/PlanarMesh.h
GTE/Samples/Mathematics/Interpolation2D/Interpolation2DWindow3.cpp
```

Added a function for computing the centroid of a tetrahedron.

```
GTE/Mathematics/Tetrahedron3.h
```

Updated a comment to be consistent with other distance-query comments.

```
GTE/Mathematics/DistTriangle3Triangles.h
```

Updated project files that reference the newly added mathematics header files.

```
GTE/Mathematics/GTMathematics.*.{vcxproj,vcxproj.filters}
```

January 31, 2022. Added new file that implements point-in-tetrahedron query. This is needed for the port of BouncingTetrahedra from Wild Magic 5 to Geometric Tools Engine.

```
{\rm GTE/Mathematics/ContTetrahedron3.h}
```

January 30, 2022. The point-tetrahedron distance query code failed to compile because of a mismatch in index type. (Reorganization of my internal tools caused the template instantiation tool not to launch when Tetrahedron3 was modified.)

GTE/Mathematics/DistPoint3Tetrahedron3.h

January 26, 2022. I modified the sample application to allow the spheres to spin based on angular momentum, taking into account transfer of momentum during colliding contact. This required a different algorithm for impulsive function construction than what is in "Game Physics, 2nd edition" (Section 6.2.2). The algorithm details are in a new document at my website, ComputingImpulsiveForces.pdf. I also added friction to stop eventually the spheres from sliding and spinning when they are on the floor. Eliminated the texture seam by hacking it to a toroidal texture. Modified the RigidBody interface for simpler presentation of the Runge-Kutta solver steps and to make it clear the dependency between physics parameters and quantities derived from them (to support synchronizing the state).

```
GTE/Mathematics/RigidBody.h

GTE/Samples/Physics/BouncingSpheres/BouncingSpheresMain.cpp

GTE/Samples/Physics/BouncingSpheres/BouncingSpheresWindow3.{h,cpp}

GTE/Samples/Physics/BouncingSpheres/PhysicsModule.{h,cpp}

GTE/Samples/Physics/BouncingSpheres/Initial.txt

GTE/Samples/Data/BallTextureWrap.png
```

January 17, 2022. The function FitIndexed has tests for the components of mean being finite floating-point numbers. The test for mean[2] was missing.

```
GTE/ApprOrthogonalPlane3.h
```

Converted the GetFaceIndices function to static because the indices for the triangular faces are the same no matter which tetrahedron. Added also the static function GetAllFaceIndices to access the entire array of indices as a single object; this is useful for index buffers associated with tetrahedra.

```
GTE/Tetrahedron3.h
```

January 16, 2022. I replaced the hard-coded physics time steps by a physics clock that requires the simulation to run at 60 frames per second. I also added comments that the physics implementation is based on Section 6.6 of my Game Physics book (2nd edition).

```
GTE/Samples/Physics/BouncingSpheres/BouncingSpheresWindow3.{h,cpp}
```

January 14, 2022. I ported the Wild Magic 5 physics sample BouncingSpheres to GTE 5. The sample illustrates impulsed-based physics for a collection of spheres. I refactored the code so that the physics portion is isolated to the PhysicsModule.* files. Update the CMake list of projects for physics.

```
GTE/Samples/Physics/BouncingSpheres/BouncingSpheres*.*
GTE/Samples/Physics/BouncingSpheres/PhysicsModule.{h,cpp}
GTE/Samples/Physics/CMakeLists.txt
```

The function SetMass had type float instead of the template parameter Real.

```
GTE/Mathematics/RigidBody.h
```

January 12, 2022. I ported the Wild Magic 5 physics sample WaterDropFormation to GTE 6. Update the CMake list of projects for physics.

```
GTE/Samples/Physics/WaterDropFormation/WaterDropFormation*.* GTE/Samples/Physics/WaterDropFormation/RevolutionSurface.{h,cpp} GTE/Samples/Physics/CMakeLists.txt
```

Fixed the file versions to show 6.1 instead of 6.0 to be consistent with my versioning rules.

```
GTE/Samples/Physics/RoughPlaneParticle1/RoughPlaneParticle1*.*
GTE/Samples/Physics/RoughPlaneParticle1/PhysicsModule. {h,cpp}
GTE/Samples/Physics/RoughPlaneParticle2/RoughPlaneParticle2*.*
GTE/Samples/Physics/RoughPlaneParticle2/PhysicsModule. {h,cpp}
GTE/Samples/Physics/RoughPlaneThinRod1/RoughPlaneThinRod1*.*
GTE/Samples/Physics/RoughPlaneThinRod1/PhysicsModule. {h,cpp}
GTE/Samples/Physics/RoughPlaneThinRod2/RoughPlaneThinRod2*.*
GTE/Samples/Physics/RoughPlaneThinRod2/PhysicsModule. {h,cpp}
GTE/Samples/Physics/RoughPlaneFlatBoard/RoughPlaneFlatBoard*.*
GTE/Samples/Physics/RoughPlaneFlatBoard/PhysicsModule. {h,cpp}
GTE/Samples/Physics/RoughPlaneSolidBox/RoughPlaneSolidBox*.*
GTE/Samples/Physics/RoughPlaneSolidBox/PhysicsModule. {h,cpp}
GTE/Samples/Physics/RoughPlaneSolidBox/PhysicsModule. {h,cpp}
GTE/Samples/Physics/WrigglingSnake/WrigglingSnake*.*
GTE/Samples/Physics/WrigglingSnake/TubeSurface. {h,cpp}
```

Added hyperlinks to the website PDF that describes some simple friction-based algorithms.

```
GTE/Samples/Physics/RoughPlaneParticle1/RoughPlaneParticle1.h GTE/Samples/Physics/RoughPlaneParticle2/RoughPlaneParticle2.h GTE/Samples/Physics/RoughPlaneThinRod1/RoughPlaneThinRod1.h GTE/Samples/Physics/RoughPlaneThinRod2/RoughPlaneThinRod2.h GTE/Samples/Physics/RoughPlaneFlatBoard/RoughPlaneFlatBoard.h GTE/Samples/Physics/RoughPlaneSolidBox/RoughPlaneSolidBox.h
```

January 11, 2022. I ported the Wild Magic 5 physics sample WrigglingSnake to GTE 6. Updated the CMake list of projects for physics.

```
GTE/Samples/Physics/WrigglingSnake/WrigglingSnake*.*
GTE/Samples/Physics/WrigglingSnake/TubeSurface.{h,cpp}
GTE/Data/Snake.png
GTE/Samples/Physics/CMakeLists.txt
```

January 10, 2022. I ported the Wild Magic 5 physics samples to GTE 6, the ones involving friction.

```
GTE/Samples/Physics/RoughPlaneParticle1/RoughPlaneParticle1*.* GTE/Samples/Physics/RoughPlaneParticle1/PhysicsModule. {h,cpp} GTE/Samples/Physics/RoughPlaneParticle2/RoughPlaneParticle2*.*
```

```
GTE/Samples/Physics/RoughPlaneParticle2/PhysicsModule.{h,cpp} GTE/Samples/Physics/RoughPlaneThinRod1/RoughPlaneThinRod1*.* GTE/Samples/Physics/RoughPlaneThinRod1/PhysicsModule.{h,cpp} GTE/Samples/Physics/RoughPlaneThinRod2/RoughPlaneThinRod2*.* GTE/Samples/Physics/RoughPlaneThinRod2/PhysicsModule.{h,cpp} GTE/Samples/Physics/RoughPlaneFlatBoard/RoughPlaneFlatBoard*.* GTE/Samples/Physics/RoughPlaneFlatBoard/PhysicsModule.{h,cpp} GTE/Samples/Physics/RoughPlaneSolidBox/RoughPlaneSolidBox*.* GTE/Samples/Physics/RoughPlaneSolidBox/PhysicsModule.{h,cpp}
```

I removed the post-build copies of the executables to the folder GeometricTools/GTE/Executable. The tools are used infrequently enough that I now run them from their _Output folders. Naturally, you can manually copy the executables to where you want them.

```
GTE/Tools/BitmapFontCreator/BitmapFontCreator.*.vcxproj
GTE/Tools/GenerateProject/GenerateProject.*.vcxproj
```

January 9, 2022. I added projects and solutions for Microsoft Visual Studio 2022. I removed the Microsoft Visual Studio 2015 projects and solutions because that version of the IDE reached mainstream end date on October 13, 2020. Microsoft Visual Studio 2017 reaches its mainstream end date on April 12, 2022. However, I have also removed the Microsoft Visual Studio 2017 projects and solutions because I do not have enough time to maintain so many versions of the compiler. From now on, I will support two versions of MSVS, the current one (whatever that is) and the previous one.

The Tools folder has various projects that were expanded to include projects and solutions for MSVS 2022. The GenerateProject tool has been modified to generate only MSVS 2019 and MSVS 2022 projects and solutions.

```
GTE/Tools/BitmapFontCreator/BitmapFontCreator.v17.*
GTE/Tools/BitmapFontCreator/BitmapFontCreator.v16.vcxproj
GTE/Tools/ChangePlatformToolset.v17.*
GTE/Tools/ChangePlatformToolset/ChangePlatformToolset.v16.vcxproj
GTE/Tools/FiniteDifferences/FiniteDifferencesDX11.v17.*
GTE/Tools/FiniteDifferences/FiniteDifferencesGL45.v17.*
GTE/Tools/FiniteDifferences/FiniteDifferencesDX11.v16.vcxproj
GTE/Tools/FiniteDifferences/FiniteDifferencesGL45.v16.vcxproj
GTE/Tools/GenerateApproximations/GenerateApproximations.v17.*
GTE/Tools/GenerateApproximations/GenerateApproximations.v16.vcxproj
GTE/Tools/GenerateOpenGLWrapper/GenerateOpenGLWrapper.v17.*
GTE/Tools/GenerateOpenGLWrapper/GenerateOpenGLWrapper.v16.vcxproj
GTE/Tools/GenerateOpenGLWrapper/GenerateOpenGLWrapper.cpp
GTE/Tools/PrecisionCalculator/PrecisionCalculator.v17.*
GTE/Tools/PrecisionCalculator/PrecisionCalculator.v16.vcxproj
GTE/Tools/RotationApproximation/RotationApproximationDX11.v17.*
GTE/Tools/RotationApproximation/RotationApproximationGL45.v17.*
GTE/Tools/RotationApproximation/RotationApproximationDX11.v16.vcxproj
GTE/Tools/RotationApproximation/RotationApproximationGL45.v16.vcxproj
```

The GenerateProject tool now creates project, solutions, filter files and source files only for MSVS 2019 and MSVS 2022.

```
GTE/Tools/GenerateProject/GenerateProject.v17.*
GTE/Tools/GenerateProject/GenerateProject.v16.{vcxproj,vcxproj.filters}
GTE/Tools/GenerateProject/GenerateProject.cpp
GTE/Tools/GenerateProject/ProjectTemplate.{h,cpp}
GTE/Tools/GenerateProject/ProjectTemplate.v17.{h,cpp}
GTE/Tools/GenerateProject/ProjectTemplate.v16.{h,cpp}
GTE/Tools/GenerateProject/ProjectTemplate.v15.{h,cpp}
GTE/Tools/GenerateProject/ProjectTemplate.v14.{h,cpp}
```

10 Version 6.0

January 3, 2022. The major revision is based on running the code analysis tools for Microsoft Visual Studio 2019 16.11.8 and for ClangCL. The reported issues were addressed with the exception of some incorrect warnings from MSVS 2019. For now, the incorrect warnings are encapsulated by #pragma commands and will be removed in the GTL development track.

The MSVS code analysis tool is not robust. Sometimes warnings occur in both the Output and Error List windows. Sometimes they occur in only one or the other window (but not both). And sometimes they do not occur in either window, but the 3-dot markers show up in source files that are opened after which the warnings show up in the Error List window. As I discover source files where the warnings show up only when the source file is opened, I will fix the issues. I believe most of these will be warnings about potentially uninitialized variables, typically for class objects whose default constructors should be called but MSVS seems to believe the class members are not initialized. This is the case for the Vector classes, but in the code using these classes, the members are set soon after the declaration. I was hoping the tool would figure out that the member initialization was deferred. (If I were to allocate a std::vector of Vector with a very large number of elements, and the code fills them in by loading data from a file, it would be a shame to waste all that time having the constructor initialize the members only to fill them in again from the loaded data.)

Another tool issue occurred with SymmetricEigensolver.h, in the GetEigenvector function. I have comments in that file about why the tool report is incorrect. For a long time I have been able to ignore the warning because code using it compiles fine, even with treat warnings as errors. The warnings occurred as part of a regular source-code build. For the first time I ran the code analyzer explicitly from the MSVS IDE menu on a source file that contains only the include of the aforementioned header file. The report now includes more warnings that appear to be based on the same incorrect diagnosis. The original warning was about a potential out-of-range index, and the Error List window allows you to drop-down a list of steps and assumptions to support the diagnosis. The new warning is about the same issue but for some reason displays a list of line numbers that show up in the drop-down list. After these new warnings occurred, I can no longer successfully build code using the eigensolver. I had to add #pragma commands to prevent the warnings. After that, a couple of other files generated similar warnings that had to be disabled using #pragma commands.

I had also spent a lot of time eliminating the warning about preferring scoped enumerations over unscoped ones. The unscoped ones typically defined enumerants that were used as array indices (in the DX11 and GL45 engine code). This is not allowed with scoped enumerations. I replaced the unscoped enumerations with

nested struct, each structure containing constant expressions of the form static uint32_t constexpr someName = someValue;. MSVS 2019 and ClangCL provided with MSVS 2019 allowed this modification, but unfortunately gcc on my Linux boxes did not. Searching stackoverflow, it appears that C++ considers such structs to be incomplete. I actually got linker errors about the various constants referenced by the sample applications but not found in the libraries linked to the applications. I restored the unscoped enumerations and disabled the code analysis warning number in the project settings.

A couple of the sample applications use BSRational<UIntegerFP<N>> where N is large. These lead to code analysis warnings about /analyze:stacksize numKBs indicating that numKBs is larger than the maximum stack size and the you should consider moving data from the stack to the heap. The samples have run correctly without stack overflow errors, so it is not clear to me what the problem is. Regardless, I modified the project settings and specified numKBs large enough to avoid the warnings. When I switched to using ClangCL, the compiler complains it cannot find files and lists the name /analyze:stacksize. It appears that ClangCL does not understand this analysis tool option. Unfortunately, with treat warnings as errors, those sample applications will not compile. So I removed the setting of numKBs and then disabled the code analysis warning number in the project settings.