

# **MATERIAL SAFETY DATA SHEET**

Ferro Corporation Performance Pigments & Colors 251 West Wylie Ave. Washington, PA 15301 USA Emergency telephone number

CHEMTREC: 1-800-424-9300 CHEMTREC (outside U.S.): 1-703-527-3887

Phone Number: 1-724-223-5900

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Name: GSLA LMM-14 Aerosol Date of Preparation: 12/11/2012

CAS-No.: Mixture

Recommended use: Industrial Use Only

Product Code: 1320717

## 2. HAZARDS IDENTIFICATION

## **Emergency Overview**

Warning

Highly flammable liquid and vapor. Vapors may travel to a source and flash back. May cause respiratory tract, eye and skin irritation. May cause allergic skin or respiratory reaction. May be harmful by inhalation. Contains crystalline silica which causes silicosis and lung cancer. Cancer hazard from inhalation (Nickel compounds).

			HMIS	NFPA 704
Color:	Black	Health:	2*	2
Physical		Flammability:	4	4
state:	. =.90.0	Physical Hazard:	1	1
Odor:	Characteristic	PPE:	Χ	

#### **Potential Health Effects**

**Eye contact:** Contact with eyes may cause irritation.

Skin contact: Prolonged skin contact may cause skin irritation and/or dermatitis. May cause allergic skin

reaction.

**Inhalation:** Over-exposure by inhalation may cause respiratory irritation. May be harmful by inhalation.

May cause allergic respiratory reaction.

**Ingestion:** May irritate digestive tract.

Chronic toxicity: Chronic inhalation exposure can cause lung damage. Long term inhalation causes lung

damage (silicosis and cancer). Respirable crystalline silica has been classified as a Group I (sufficient evidence in humans for carcinogenicity) carcinogenic by IARC and is listed by NTP as a substance which may reasonably be anticipated to be a carcinogen. Inhalation of nickel

and nickel compounds is associated with nasal and lung damage and cancer.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Weight %
Molybdenum compounds		10 - 20%
Quartz silica	14808-60-7	1 - 5%
Nickel iron chromite, black, spinel	71631-15-7	1 - 5%
Mica	12001-26-2	1 - 5%

The specific chemical identities are being withheld as a trade secret (29CFR1910.1200).

## 4. FIRST AID MEASURES

\_\_\_\_

4. FIRST AID MEASURES

Rinse immediately with plenty of water, also under the eyelids. Get medical attention if irritation Eye contact:

develops.

Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing Skin contact:

before re-use. If symptoms persist, call a physician.

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.

Drink plenty of water. Do not induce vomiting. Consult a physician if necessary. Ingestion:

Notes to physician: Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

Flash point (°C): -104( -156°F) Method: Estimated

Use dry chemical, CO2, water spray or "alcohol" foam. Suitable extinguishing media:

Hazardous decomposition products Carbon oxides.

under fire conditions:

Special protective equipment for

firefighters:

As in any fire, wear self-contained breathing apparatus (pressure-demand, NIOSH approved or

equivalent) and full protective gear

Flammable. Vapors may form explosive mixture with air. Vapors are heavier than air and may **Unusual hazards:** 

spread along floors. Vapor may travel considerable distance to source of ignition and flash

back.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Remove all non-essential people from the affected area. Ensure adequate ventilation. In case

of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes

and clothing. Wear personal protective equipment.

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do **Environmental precautions:** 

not flush into surface water or sanitary sewer system. Do not allow material to contaminate

ground water system.

Methods for cleaning up: Wear personal protective equipment. Absorb spill with inert material (e.g. dry sand or earth),

then place in a chemical waste container. Clean contaminated surface thoroughly. Dispose of

promptly.

#### 7. HANDLING AND STORAGE

## Handling:

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Handle in accordance with good industrial hygiene and safety practice. Use only in area provided with appropriate exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not eat, drink, or smoke in areas of use or storage. Do not take internally. Wash thoroughly after handling.

Keep containers tightly closed in a cool, well-ventilated place. Keep product and empty container away from heat and sources of ignition.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure limits**

Minimize exposure in accordance with good hygiene practice.

Components	OSHA	ACGIH
Quartz silica	0.1 mg/m <sup>3</sup> TWA (respirable dust)	0.025 mg/m <sup>3</sup> TWA respirable fraction
Mica	20 mppcf TWA	3 mg/m <sup>3</sup> TWA respirable fraction

Engineering measures: Provide appropriate exhaust ventilation wherever dust, mist, vapors, or fumes can be

generated. Ensure that eyewash stations and safety showers are proximal to the work-station

location.

**Eye protection:** Safety glasses with side-shields.

Skin and body protection: Lightweight protective clothing. Remove and wash contaminated clothing before re-use. Keep

working clothes separately.

Hand protection: Impervious gloves. Follow the recommendations given by the manufacturer of protective

gloves.

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment. NIOSH-approved

respirators should be worn where engineering controls and work practices do not reduce exposure to or below the PEL. Seek professional advice prior to respirator selection and use.

**Hygiene measures:** Wash hands before breaks and at the end of workday.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Color: Black Physical state: Liquid

Odor:CharacteristicMolecular weight:No data availableBoiling point/range (°C):No data availablepH:No data availableMelting point/range (°C):No data availableSpecific gravity (Water =1):No data availableBulk density:13 lbs/gal.Vapor pressure :No data available

Water solubility: No information available VOC content (%) 43

## 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions

Polymerization None under normal processing

Hazardous decomposition products: Thermal decomposition can lead to release of irritating gases and vapors. Carbon oxides.

Materials to avoid: None known.

**Conditions to avoid** Avoid elevated temperatures. Heat, flames and sparks.

## 11. TOXICOLOGICAL INFORMATION

**Acute toxicity:** Information given is based on data on the components and the toxicology of similar products

Chronic Toxicity: Contains crystalline silica which causes silicosis and lung cancer.

Carcinogenic Effects: Respirable crystalline silica has been classified as a Group I (sufficient evidence in humans for

carcinogenicity) carcinogenic by IARC and is listed by NTP as a substance which may reasonably be anticipated to be a carcinogen. Crystalline silica is also a known cause of silicosis, a non-cancerous lung disease caused by excessive exposure to crystalline silica. IARC made the overall evaluation that "Nickel compounds are carcinogenic to humans (Group 1)" on the basis of the combined results of epidemiological studies, carcinogenicity studies in

experimental animals, and several types of other relevant data.

Target Organ Effects: Chromium compound (inorganic): Eyes, skin, respiratory system. Silica: Respiratory system.

Nickel compounds: Lungs, skin.

Component information, if any, is listed below

\_\_\_\_\_

Molybdenum compounds

LD50s and LC50s: Oral LD50 (Rat) = 2689 mg/kg

Dermal LD50 (Rat) = 2 g/kg

Inhalation LC50 (Rat) = 5840 mg/m<sup>3</sup>

Quartz silica

LD50s and LC50s: Oral LD50 (Rat) = 500 mg/kg

**OSHA - Select Carcinogens:** Present

NTP: Known Human Carcinogen

IARC - Group 1: Listed

Nickel iron chromite, black, spinel

**OSHA - Select Carcinogens:** Present

NTP: Known Human Carcinogen

IARC - Group 1: Listed

## 12. ECOLOGICAL INFORMATION

Aquatic toxicity: No data is available on the product itself. Information given is based on data on the

components and the ecotoxicology of similar products.

Persistence and degradability: Not determined

# 13. DISPOSAL CONSIDERATIONS

Waste from residues / unused

products:

Waste must be disposed of in accordance with federal, state and local environmental control

regulations. Where possible recycling is preferred to disposal or incineration.

# 14. TRANSPORT INFORMATION

DOT (U.S.)

UN/ID No: UN1950 Proper shipping name: Aerosols **Hazard Class:** 2.1 **ERG No:** 126

TDG (Canada)

UN-No UN1950 **Proper Shipping Name** Aerosols **Hazard Class** 2.1

**IMDG** 

UN1950 **UN-No Proper Shipping Name** Aerosols **Hazard Class** F-D, S-U Ems:

**IATA** 

UN1950 UN-No

Proper shipping name Aerosols, flammable

**Hazard Class** 2.1 **ERG Code** 10L

#### 15. REGULATORY INFORMATION

# **U.S. Regulations:**

TSCA: Not subject to TSCA 12(b) Export Notification

#### **SARA 313:**

Components	U.S CERCLA/SARA - Section 313 - Emission Reporting
Molybdenum compounds (10 - 20%)	1.0 % de minimis concentration
Nickel compounds (1 - 5%)	0.1 % de minimis concentration
Chromium (III) compounds (1 - 5%)	1.0 % de minimis concentration

#### **State Regulations**

This product or its ingredients have been evaluated for New Jersey, Pennsylvania, and California Prop 65 supplier notification requirements. Substances that are subject to notification requirements, if any, are listed below.

Components	PARTK:
Molybdenum compounds	Listed (PARTK)
Nickel compounds	Listed (PARTK)
Chromium (III) compounds	Listed (PARTK)

Components	NJRTK:
Silica, amorphous, fumed, crystfree	Listed (NJRTK)
Mica	Listed (NJRTK)
Molybdenum compounds	Listed (NJRTK)
Kaolin	Listed (NJRTK)
Quartz silica	Listed (NJRTK)
Nickel compounds	Listed (NJRTK)
Chromium (III) compounds	Listed (NJRTK)

## **Canadian WHMIS**

WHMIS hazard class: D2A Very toxic materials

# Canadian Ingredient Disclosure List (IDL):

#### **International Inventories**

TSCA 8(b): Listed or exempt.

Canadian DSL/NDSL list All ingredient(s) are listed on the DSL or NDSL

**EC-No.** Listed or exempt.

**Philippines (PICCS):** One or more ingredient(s) are not on the PICCS list.

Japan (ENCS): Listed or exempt.

Korea (KECL): Listed.
China (IECS): Listed.
Australia (AICS): Listed.
New Zealand (NZIoC): Listed.

## **16. OTHER INFORMATION**

## For Industrial Use Only

# Prepared by: Ferro Technical Center

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guaranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable federal or state laws.

# **End of Safety Data Sheet**