

Slider Code Display

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-
scale=1.0">
  <title>Document</title>
</head>

<body>
  <style>
    .slider-container {
      box-sizing: border-box;
      width: 300px;
      position: relative;
      overflow: hidden;
      height:400px;
    }

    .slider-container:hover .next,
    .slider-container:hover .prev {
      transform: translate(0, -50%);
    }

    .slider-container:hover .play {
      opacity: 1;
    }

    .slider-container .sliderimage {
      width: 100%;
      position: absolute;
      top: 0;
      left: 0;
```

```
        opacity: 0;
        transition: 0.4s;
    }

    .slider-container .fixed {
        position: static;
        /* unset */
        width: 100%;
        opacity: 0;
    }

    .slider-container .show {
        opacity: 1;
    }

    .sliderbutton {
        position: absolute;
        top: 50%;
        background-color: rgba(0, 0, 0, 0.3);
        color: white;
        font-size: 40px;
        font-weight: bold;
        padding: 16px 12px;
        transition: 0.4s;
        cursor: pointer;
        border: none;
        outline: none;
    }

    .sliderbutton:hover {
        background-color: rgba(0, 0, 0, 0.7);
    }

    .sliderbutton.next {
        right: 0;
        border-top-left-radius: 10px;
        border-bottom-left-radius: 10px;
        transform: translate(100%, -50%);
```

```

}

.sliderbutton.prev {
  left: 0;
  border-top-right-radius: 10px;
  border-bottom-right-radius: 10px;
  transform: translate(-100%, -50%);
}

.sliderbutton.play {
  left: 50%;
  border-radius: 10px;
  transform: translate(-50%, -50%);
  opacity: 0;
}
</style>
<div class="slider-container">
  <!-- 
  
  
  
  
   -->

  <button id="btnNext" class="sliderbutton next">&#10095;</button>
  <button id="btnPrev" class="sliderbutton prev">&#10094;</button>
  <button id="btnPlay" class="sliderbutton play">&#x23f8;</button>
  <!--
    //23F5 ▶ forward, next, play &#x23f5; -->
</div>
<style>
  .card{
    display:grid;
    height:400px;
    gap:16px;
    justify-content: center; /* possible in grid */
  }

```

```
    }
</style>
<script>
    //ensures that all images are loaded first
    window.addEventListener("load", function () {
        var allImages;
        var sliderAnim = null;
        var currentSlide = 0;
        function nextSlide() {
            currentSlide++;
            if (currentSlide >= allImages.length) {
                currentSlide = 0;
            }
            allImages.forEach(function (ele, idx) {
                ele.classList.remove("show");
                if (idx == currentSlide) {
                    ele.classList.add("show");
                }
            });
        }
        document.querySelector("#btnNext").addEventListener("click",
function () {
            nextSlide();
        });
        var playButton = document.querySelector("#btnPlay");
        function adjustState(playState = false) {
            if (playState == false) {
                clearInterval(sliderAnim);
                sliderAnim = null;
                playButton.innerHTML = "&#x23f5;";
            }
            else {
                sliderAnim = setInterval(nextSlide, 5000);
                playButton.innerHTML = "&#x23f8;";
            }
        }
        playButton.addEventListener("click", function () {
            if (sliderAnim) {
```

```
        adjustState(false);
    }
    else {
        adjustState(true);
    }
});

    async function fetchJSON() {
        const response = await fetch("https://
jsonplaceholder.typicode.com/users"); //fetch returns a promise

        if (!response.ok) {
            throw new Error("Request failed");
        }
        return response.json(); //convert the response so gotten
to json format.
    }
    async function loadData() {
        try {
            users = await fetchJSON();
            console.log(users);
        }
        catch (err) {
            console.error(err);
        }
    }

    var users = [];
    var sliderContainer = document.querySelector(".slider-
container");
    async function init(){
        await loadData();
        users.forEach(user =>{
            let card = document.createElement("div");
            card.classList.add("card");
            card.classList.add("sliderimage");
            card.innerHTML = `
```

```

    <h2 class="name">${user.name}</h2>
    <div class="address">
        <ul>
            <li>${user.address.suite}</li>
            <li>${user.address.street}</li>
            <li>${user.address.city}</li>
            <li>${user.address.zipcode}</li>
        </ul>
    </div>
    <p>${user.email}</p>
    `;
    sliderContainer.insertAdjacentElement("afterbegin",
card);

    });
    //add the class show to the first sliderimage
    sliderContainer.firstElementChild.classList.add("show");
    const cards = sliderContainer.querySelectorAll(".card");
    const lastCard = cards[cards.length -1];
    //innerHTML - copy
    const fixedClone = lastCard.cloneNode(true);
    fixedClone.classList.add("fixed");
    fixedClone.classList.remove("card");
    fixedClone.classList.remove("sliderimage");
    //fixedClone.className = "fixed" (1 line)
    sliderContainer.appendChild(fixedClone);

    allImages = document.querySelectorAll(".sliderimage");
    sliderAnim = setInterval(nextSlide, 5000);
  }
  init();
});

</script>
</body>

</html>

```