

Outstanding User Interfaces with Shiny

David Granjon

2020-05-06

Contents

Prerequisites	5
Disclaimer	5
Is this book for me?	5
Related content	5
1 Introduction	7
Survival Kit	11
2 HTML	13
2.1 HTML Basics	13
2.2 Tag attributes	14
2.3 HTML page: skeleton	14
2.4 About the DOM	15
2.5 Preliminary introduction to CSS and JavaScript	17
3 JavaScript	19
4 Shiny	21
htmltools	25
5 htmltools overview	27
5.1 HTML Tags	27

5.2	Notations	27
5.3	Adding new tags	27
5.4	Alternative way to write tags	28
5.5	Playing with tags	28
6	Dependency utilities	35
6.1	The dirty approach	35
6.2	The clean approach	37
6.3	Another example: Importing HTML dependencies from other packages	38
6.4	Suppress dependencies	41
7	Other tools	43
7.1	CSS	43
	Practice	47
8	Template selection	49
9	Define dependencies	51
10	Template skeleton	53
11	Develop custom input widgets	55
11.1	How does Shiny handle inputs?	55
11.2	How to add new input to Shiny?	55
12	Testing templates elements	57

Prerequisites

- Be familiar with Shiny
- Basic knowledge in HTML and JavaScript is a plus but not mandatory

Disclaimer

This book is not an HTML/Javascript/CSS course! Instead, it provides a *survival kit* to be able to customize Shiny. I am sure however that readers will want to explore more about these topics.

Is this book for me?

You should read this book if you answer yes to the following questions:

- Do you want to know how to develop outstanding shiny apps?
- Have you ever wondered how to develop new input widgets?

Related content

See the RStudio Cloud dedicated project.

```
library(shiny)
library(shinydashboard)
library(shiny.semantic)
library(cascadess)
library(htmltools)
library(purrr)
library(magrittr)
```


Chapter 1

Introduction

There are various Shiny focused resources introducing basic as well as advanced topics such as modules and Javascript/R interactions. However, handling advanced user interfaces was never an emphasis. Clients often desire custom designs, yet this generally exceeds core features of Shiny. We recognized that R App developers lacking a significant background in web development may have found this requirement to be overwhelming. Consequently, the aim of this book is to provide readers the necessary knowledge to extend Shiny's layout, input widgets and output elements. This book is organized into four parts. We first go through the basics of HTML, JavaScript and jQuery. In part 2, we dive into the `{htmltools}` package, providing functions to create and manipulate shiny tags as well as manage dependencies. Part 3 homes in on the development of a new template on top of Shiny by demonstrating examples from the `{bs4Dash}` and `{shinyMobile}` packages, part of the RinterRface project.

A callout

Survival Kit

This part will give you basis in HTML, JavaScript to get started...

Chapter 2

HTML

In the following, we will give a short introduction to the HTML language. First of all, let's do the following experience:

- Open your RStudio IDE
- Load shiny with `library(shiny)`
- Execute `p("Hello World")` and notice the output format
- This is an HTML tag!

2.1 HTML Basics

HTML (Hypertext Markup Language) is derived from the SGML (Standard Generalized markup Language). An HTML file contains tags that can be divided into 2 categories:

- paired-tags
- closing-tags

```
<!-- /* paired-tags */ -->
<p></p>
<div></div>

<!-- /* self-closing tags */ -->
<iframe/>
<img/>
<input/>
<br/>
```

2.2 Tag attributes

All tags above don't have any attributes. Yet HTML allows to set attributes inside each tag. There exist a large range of attributes and we will only see 2 of them for now:

- class: may be shared between multiple tags
- id: each must be unique

```
<div class="awesome-item" id="myitem"></div>
<!-- /* the class awesome-item may be applied to multiple tags */ -->
<span class="awesome-item"></span>
```

Both attributes are widely used by CSS and JavaScript (we will discover in the following chapter the jQuery selectors) to apply custom style to a web page. While class may apply to multiple elements, id is restricted to only one item.

2.3 HTML page: skeleton

An HTML page is a collection of tags which will be interpreted by the web browser step by step. The simplest HTML page may be defined as follows:

```
<!DOCTYPE HTML>
<html>
  <head>
    <!-- /* head content here */ -->
  </head>
  <body>
    <!-- /* body content here */ -->
  </body>
</html>
```

- <html> is the may wrapper
- <head> and <body> are the 2 main children

<head> contains dependencies like styles and JavaScript files (but not only), <body> contains the page content. We will see later that JavaScript files are often added just before the end of the <body>.

Let's write the famous Hello World in html:

```
<!DOCTYPE HTML>
<html>
  <head>
    <!-- head content here -->
  </head>
  <body>
    <p>Hello World</p>
  </body>
</html>
```

In order to preview this page in a web browser, you need to save the above snippet to a script `hello-world.html` and double-click on it. It will open with you default web browser.

2.4 About the DOM

The DOM stands for “Document Object Model”, is a convenient representation of the html document. There actually exists multiple DOM types, namely DOM-XML and DOM-HTML but we will only focus on the later (in the following DOM is DOM-HTML). If we consider the last example (Hello World), the associated DOM tree may be inspected in Figure 2.1.

2.4.1 Visualizing the DOM: the HTML inspector

Below, we introduce a tool that we is going to be a valuable ally during our ambitious quest to beautiful shiny user interfaces. In this chapter, we restrict the description to the first panel of the HTML inspector ¹. This feature is available in all web browser but we will only focus on Chrome.

- Open the `hello-world.html` example in a web browser (google chrome here)
- Right-click to open the HTML inspector (developer tools must be enabled if it is not the case)

The HTML inspector is a convenient tool to explore the structure of the current HTML page. On the left-hand side, the DOM tree is displayed and we clearly see that `<html>` is the parent of `<head>` and `<body>`. `<body>` has also 1 child, that is `<p>`. We didn't mention this yet but we can preview any style (CSS) associated to the selected element on the right panel as well as Event Listeners (JavaScript). We will discuss that in the next chapter.

¹As shown in Figure 2.1, the inspector also has tools to debug JavaScript code, inspect files, run performances audit, ... We will describe some of these later in the book.



Figure 2.1: Inspection of the DOM in the Hello World example

2.5 Preliminary introduction to CSS and JavaScript

CSS and JavaScript are tools to enhance an HTML page.

2.5.1 HTML and CSS

CSS (Cascading Style Sheets) changes the style of HTML tags by targeting specific classes or ids. For instance, if we want all p tags to have red color we will use:

```
p {  
  color: red;  
}
```

To include CSS in an HTML page, we use the `<style>` tag as follows:

```
<!DOCTYPE HTML>  
<html>  
  <head>  
    <style type="text/css">  
      p {  
        color: red;  
      }  
    </style>  
  </head>  
  <body>  
    <p>Hello World</p>  
  </body>  
</html>
```

You may update the hello-world.html script and run it in your web-browser to see the difference (this is not super impressive but a good start). There exist other ways to include CSS (see next chapters).

2.5.2 HTML and JavaScript

JavaScript is also going to be one of our best friend in this book. You will see how quickly/seamlessly you may add awesome feature to your shiny app.

Let's consider an example below:

```
<!DOCTYPE HTML>
<html>
  <head>
    <style type="text/css">
      p {
        color: red;
      }
    </style>
    <script language="javascript">
      // displays an alert
      alert('Click on the Hello World text!');
      // change text color
      function changeColor(color){
        document.getElementById('hello').style.color = "green";
      }
    </script>
  </head>
  <body>
    <!-- onclick attributes applies the JavaScript function changeColor define above -->
    <p id="hello" onclick="changeColor('green')">Hello World</p>
  </body>
</html>
```

In few lines of code, you can change the color of the text. Wonderful isn't it? Let's move to the next chapter to discover JavaScript!

Chapter 3

JavaScript

Chapter 4

Shiny

htmltools

While building a custom html template, you will need to know more about the wonderful `htmltools` developed by Winston Chang, member of the shiny core team. It has the same spirit as `devtools`, that is, making your web developer life easier. What follows does not have the pretention to be an exhaustive guide about this package. Yet, it will provide you with the main tools to be more efficient.

Chapter 5

htmltools overview

5.1 HTML Tags

htmltools contains tools to write HTML tags we saw in Chapter 2:

```
div()
```

If you had to gather multiple tags together, prefer `tagList()` as `list()`, although the HTML output is the same. The first has the `shiny.tag.list` class in addition to `list`. (The `Golem` package allows to test if a R object is a tag list, therefore using `list` would make the test fail).

5.2 Notations

Whether to use `tags$div` or `div` depends if the tag is exported by default. For instance, you could use `htmltools::div` but not `htmltools::nav` since `nav` does not have a dedicated function (only for `p`, `h1`, `h2`, `h3`, `h4`, `h5`, `h6`, `a`, `br`, `div`, `span`, `pre`, `code`, `img`, `strong`, `em`, `hr`). Rather use `htmltools::tags$nav`. Alternatively, there exists a function (in `shiny` and `htmltools`) called `withTags()`. Wrapping your code in this function enables you to use `withTags(nav(), ...)` instead of `tags$nav()`.

5.3 Adding new tags

The `tag` function allows to add extra HTML tags not already defined. You may use it as follows:

```

tag("test", list(class = "test", p("Custom Tag")))
# structure below
tag
  "test"
  list
    class = "test"
    p
      "Custom Tag"

```

5.4 Alternative way to write tags

htmltools comes with the `HTML()` function that you can feed with raw HTML:

```

HTML('<div>Blabla</div>')
# will render exactly like
div("Blabla")

# but there class is different
class(HTML('<div>Blabla</div>'))
class(div("Blabla"))

```

You will not be able to use tag related functions, as in the following parts. Therefore, I strongly recommend using R and not mixing HTML in R. Interestingly, if you want to convert HTML to R code, there is a Shiny App developed by Alan Dipert from RStudio, namely `html2R`. There are some issues, non standard attributes (like `data-toggle`) are not correctly processed but there are fixes. This will save you precious time!

5.5 Playing with tags

5.5.1 Tags structure

According to the `tag` function, a tag has:

- a name such as `span`, `div`, `h1` ... `tag$name`
- some attributes, which you can access with `tag$attribs`
- children, which you can access with `tag$children`
- a class, namely `"shiny.tag"`

For instance:

```
# create the tag
myTag <- div(
  class = "divclass",
  id = "first",
  h1("Here comes your baby"),
  span(class = "child", id = "baby", "Crying")
)
# access its name
myTag$name
# access its attributes (id and class)
myTag$attrs
# access children (returns a list of 2 elements)
myTag$children
# access its class
class(myTag)
```

How to modify the class of the second child, namely span?

```
second_children <- myTag$children[[2]]
second_children$attrs$class <- "adult"
myTag
# Hummm, this is not working ...
```

Why is this not working? By assigning `myTag$children[[2]]` to `second_children`, `second_children$attrs$class <- "adult"` modifies the class of the copy and not the original object. Thus we do:

```
myTag$children[[2]]$attrs$class <- "adult"
myTag
```

In the following section we explore helper functions, such as `tagAppendChild` from `htmltools`.

5.5.2 Useful functions for tags

`htmltools` and `Shiny` have powerful functions to easily add attributes to tags, check for existing attributes, get attributes and add other siblings to a list of tags.

5.5.2.1 Add attributes

- `tagAppendAttributes`: this function allow you to add a new attribute to the current tag.

For instance, assuming you created a div for which you forgot to add an id attribute:

```
mydiv <- div("Where is my brain")
mydiv <- tagAppendAttributes(mydiv, id = "here_it_is")
```

You can pass as many attributes as you want, including non standard attributes such as `data-toggle` (see Bootstrap 3 tabs for instance):

```
mydiv <- tagAppendAttributes(mydiv, `data-toggle` = "tabs")
# even though you could proceed as follows
mydiv$attribs[["aria-controls"]] <- "home"
```

5.5.2.2 Check if tag has specific attribute

- `tagHasAttribute`: to check if a tag has a specific attribute

```
# I want to know if div has a class
mydiv <- div(class = "myclass")
has_class <- tagHasAttribute(mydiv, "class")
has_class
# if you are familiar with %>%
has_class <- mydiv %>% tagHasAttribute("class")
has_class
```

5.5.2.3 Get all attributes

- `tagGetAttribute`: to get the value of the targeted attributes, if it exists, otherwise `NULL`.

```
mydiv <- div(class = "test")
# returns the class
tagGetAttribute(mydiv, "class")
# returns NULL
tagGetAttribute(mydiv, "id")
```

5.5.2.4 Set child/children

- `tagSetChildren` allows to create children for a given tag. For instance:

```
mydiv <- div(class = "parent", id = "mother", "Not the mama!!!")
# mydiv has 1 child "Not the mama!!!"
mydiv
children <- lapply(1:3, span)
mydiv <- tagSetChildren(mydiv, children)
# mydiv has 3 children, the first one was removed
mydiv
```

Notice that `tagSetChildren` removes all existing children. Below we see another set of functions to add children while conserving existing ones.

5.5.2.5 Add child or children

- `tagAppendChild` and `tagAppendChildren`: add other tags to an existing tag. Whereas `tagAppendChild` only takes one tag, you can pass a list of tags to `tagAppendChildren`.

```
mydiv <- div(class = "parent", id = "mother", "Not the mama!!!")
otherTag <- span("I am your child")
mydiv <- tagAppendChild(mydiv, otherTag)
```

You might wonder why there is no `tagRemoveChild` or `tagRemoveAttributes`. Let's look at the `tagAppendChild`

```
tagAppendChild <- function (tag, child) {
  tag$children[[length(tag$children) + 1]] <- child
  tag
}
```

Below we write the `tagRemoveChild`, where `tag` is the target and `n` is the position to remove in the list of children:

```
mydiv <- div(class = "parent", id = "mother", "Not the mama!!!", span("Hey!"))

# we create the tagRemoveChild function
tagRemoveChild <- function(tag, n) {
  # check if the list is empty
  if (length(tag$children) == 0) {
    stop(paste(tag$name, "does not have any children!"))
  }
  tag$children[n] <- NULL
  tag
}
```

```
mydiv <- tagRemoveChild(mydiv, 1)
mydiv
```

When defining the `tagRemoveChild`, we choose `[]` instead of `[[` to allow to select multiple list elements:

```
mydiv <- div(class = "parent", id = "mother", "Not the mama!!!", "Hey!")
# fails
`[[`(mydiv$children, c(1, 2))
# works
`[`(mydiv$children, c(1, 2))
```

Alternatively, we could also create a `tagRemoveChildren` function. Also notice that the function raises an error if the provided tag does not have children.

5.5.3 Other interesting functions

The Golem package written by thinkr contains neat functions to edit your tags. Particularly, the `tagRemoveAttributes`:

```
tagRemoveAttributes <- function(tag, ...) {
  attrs <- as.character(list(...))
  for (i in seq_along(attrs)) {
    tag$attribs[[ attrs[i] ]] <- NULL
  }
  tag
}
```

```
mydiv <- div(class = "test", id = "coucou", "Hello")
tagRemoveAttributes(mydiv, "class", "id")
```

5.5.4 Conditionally set attributes

Sometimes, you only want to set attributes under specific conditions.

```
my_button <- function(color = NULL) {
  tags$button(
    style = paste("color:", color),
    p("Hello")
  )
}

my_button()
```


This example will not fail but having `style="color: "` is not clean. We may use conditions:

```
my_button <- function(color = NULL) {
  tags$button(
    style = if (!is.null(color)) paste("color:", color),
    p("Hello")
  )
}

my_button("blue")
my_button()
```

In this example, style won't be available if color is not specified.

5.5.5 Using %>%

While doing a lot of manipulation for a tag, if you don't need to create intermediate objects, this is a good idea to use %>% from magrittr:

```
div(class = "cl", h1("Hello")) %>%
  tagAppendAttributes(id = "myid") %>%
  tagAppendChild(p("some extra text here!"))
```

5.5.6 Programmatically create children elements

Assume you want to create a tag with 3 children inside:

```
div(
  span(1),
  span(2),
  span(3),
  span(4),
  span(5)
)
```

The structure is correct but imagine if you had to create 1000 `span` or fancier tag. The previous approach is not consistent with DRY programming. `lapply` function will be useful here (or the purrr `map` family):

```
# base R
div(lapply(1:5, function(i) span(i)))
# purrr + %>%
map(1:5, function(i) span(i)) %>% div()
```


Chapter 6

Dependency utilities

When creating a new template, you sometimes need to import custom HTML dependencies that do not come along with shiny. No problem, `htmltools` is here for you (shiny also contains these functions).

6.1 The dirty approach

Let's consider the following example. I want to include a bootstrap 4 card in a shiny app. This example is taken from an interesting question [here](#). The naive approach would be to include the HTML code directly in the app code

```
# we create the card function before
my_card <- function(...) {
  withTags(
    div(
      class = "card border-success mb-3",
      div(class = "card-header bg-transparent border-success"),
      div(
        class = "card-body text-success",
        h3(class = "card-title", "title"),
        p(class = "card-text", ...)
      ),
      div(class = "card-footer bg-transparent border-success", "footer")
    )
  )
}

# we build our app
shinyApp(
```

```

ui = fluidPage(
  fluidRow(
    column(
      width = 6,
      align = "center",
      br(),
      my_card("blablabla. PouetPouet Pouet.")
    )
  ),
  server = function(input, output) {}
)

```

and desperately see that nothing is displayed. If you remember, this was expected since shiny does not contain bootstrap 4 dependencies and this card is unfortunately a bootstrap 4 object. Don't panic! We just need to tell shiny to load the css we need to display this card (if required, we could include the javascript as well). We could use either `includeCSS()`, `tags$head(tags$link(rel = "stylesheet", type = "text/css", href = "custom.css"))`. See more here.

```

shinyApp(
  ui = fluidPage(
    # load the css code
    includeCSS(path = "https://maxcdn.bootstrapcdn.com/bootstrap/4.0.0/css/bootstrap.m
  fluidRow(
    column(
      width = 6,
      align = "center",
      br(),
      my_card("blablabla. PouetPouet Pouet.")
    )
  ),
  server = function(input, output) {}
)

```

The card is ugly (which is another problem we will fix later) but at least displayed.

When I say this approach is dirty, it is because it will not be easily re-usable by others. Instead, we prefer a packaging approach, like in the next section.

6.2 The clean approach

We will use the `htmlDependency` and `attachDependencies` functions from `htmltools`. The `htmlDependency` takes several arguments:

- the name of your dependency
- the version (useful to remember on which version it is built upon)
- a path to the dependency (can be a CDN or a local folder)
- script and stylesheet to respectively pass css and scripts

```
# handle dependency
card_css <- "bootstrap.min.css"
bs4_card_dep <- function() {
  htmlDependency(
    name = "bs4_card",
    version = "1.0",
    src = c(href = "https://maxcdn.bootstrapcdn.com/bootstrap/4.0.0/css/"),
    stylesheet = card_css
  )
}
```

We create the card tag and give it the bootstrap 4 dependency through the `attachDependencies()` function. In recent version of `htmltools`, we may simply use `tagList(tag, deps)` instead.

```
# create the card
my_card <- function(...) {
  cardTag <- withTags(
    div(
      class = "card border-success mb-3",
      div(class = "card-header bg-transparent border-success"),
      div(
        class = "card-body text-success",
        h3(class = "card-title", "title"),
        p(class = "card-text", ...)
      ),
      div(class = "card-footer bg-transparent border-success", "footer")
    )
  )

  # attach dependencies (old way)
  # htmltools::attachDependencies(cardTag, bs4_card_dep())

  # simpler way
  tagList(cardTag, bs4_card_dep())
}
```

```
}
```

We finally run our app:

```
# run shiny app
ui <- fluidPage(
  title = "Hello Shiny!",
  fluidRow(
    column(
      width = 6,
      align = "center",
      br(),
      my_card("blablabla. PouetPouet Pouet.")
    )
  )
)

shinyApp(ui, server = function(input, output) { })
```

With this approach, you could develop a package of custom dependencies that people could use when they need to add custom elements in shiny.

6.3 Another example: Importing HTML dependencies from other packages

You may know shinydashboard, a package to design dashboards with shiny. In the following, we would like to integrate the box component in a classic Shiny App (without the dashboard layout). However, if you try to include the Shinydashboard box tag, you will notice that nothing is displayed since Shiny does not have shinydashboard dependencies. Fortunately htmltools contains a function, namely `findDependencies` that looks for all dependencies attached to a tag. How about extracting shinydashboard dependencies? Before going further, let's define the basic skeleton of a shinydashboard:

```
shinyApp(
  ui = dashboardPage(
    dashboardHeader(),
    dashboardSidebar(),
    dashboardBody(),
    title = "Dashboard example"
  ),
  server = function(input, output) { }
)
```

6.3. ANOTHER EXAMPLE: IMPORTING HTML DEPENDENCIES FROM OTHER PACKAGES 39

We don't need to understand shinydashboard details. However, if you are interested to dig in, help yourself. What is important here is the main wrapper function `dashboardPage`. (You should already be familiar with `fluidPage`, another wrapper function). We apply `findDependencies` on `dashboardPage`.

```
deps <- findDependencies(  
  dashboardPage(  
    header = dashboardHeader(),  
    sidebar = dashboardSidebar(),  
    body = dashboardBody()  
  )  
)  
deps
```

`deps` is a list containing 4 dependencies:

- Font Awesome handles icons
- Bootstrap is the main HTML/CSS/JS template. Importantly, please note the version 3.3.7, whereas the current is 4.3.1
- AdminLTE is the dependency containing HTML/CSS/JS related to the admin template. It is closely linked to Bootstrap 3.
- shinydashboard, the CSS and javascript necessary for shinydashboard to work properly. In practice, integrating custom HTML templates to shiny does not usually work out of the box for many reasons (Explain why!) and some modifications are necessary.

```
[[1]]  
List of 10  
 $ name      : chr "font-awesome"  
 $ version   : chr "5.3.1"  
 $ src       :List of 1  
 ..$ file: chr "www/shared/fontawesome"  
 $ meta      : NULL  
 $ script    : NULL  
 $ stylesheet: chr [1:2] "css/all.min.css" "css/v4-shims.min.css"  
 $ head      : NULL  
 $ attachment: NULL  
 $ package   : chr "shiny"  
 $ all_files : logi TRUE  
 - attr(*, "class")= chr "html_dependency"  
[[2]]  
List of 10  
 $ name      : chr "bootstrap"  
 $ version   : chr "3.3.7"  
 $ src       :List of 2
```

```

..$ href: chr "shared/bootstrap"
..$ file: chr "/Library/Frameworks/R.framework/Versions/3.5/Resources/library/shiny/www"
$ meta      :List of 1
..$ viewport: chr "width=device-width, initial-scale=1"
$ script    : chr [1:3] "js/bootstrap.min.js" "shim/html5shiv.min.js" "shim/respond.min.js"
$ stylesheet: chr "css/bootstrap.min.css"
$ head      : NULL
$ attachment: NULL
$ package   : NULL
$ all_files : logi TRUE
- attr(*, "class")= chr "html_dependency"
[[3]]
List of 10
$ name      : chr "AdminLTE"
$ version   : chr "2.0.6"
$ src       :List of 1
..$ file: chr "/Library/Frameworks/R.framework/Versions/3.5/Resources/library/shinydashboard"
$ meta      : NULL
$ script    : chr "app.min.js"
$ stylesheet: chr [1:2] "AdminLTE.min.css" "_all-skins.min.css"
$ head      : NULL
$ attachment: NULL
$ package   : NULL
$ all_files : logi TRUE
- attr(*, "class")= chr "html_dependency"
[[4]]
List of 10
$ name      : chr "shinydashboard"
$ version   : chr "0.7.1"
$ src       :List of 1
..$ file: chr "/Library/Frameworks/R.framework/Versions/3.5/Resources/library/shinydashboard"
$ meta      : NULL
$ script    : chr "shinydashboard.min.js"
$ stylesheet: chr "shinydashboard.css"
$ head      : NULL
$ attachment: NULL
$ package   : NULL
$ all_files : logi TRUE
- attr(*, "class")= chr "html_dependency"

```

Below, we attach the dependencies to the `box` with `tagList`, as shown above. Notice that our custom `box` does not contain all parameters from `shinydashboard` but this is not what matters in this example.


```
my_box <- function(title, status) {  
  tagList(box(title = title, status = status), deps)  
}  
ui <- fluidPage(  
  titlePanel("Shiny with a box"),  
  my_box(title = "My box", status = "danger"),  
)  
server <- function(input, output) {}  
shinyApp(ui, server)
```

Now, you may imagine the possibilities are almost unlimited! Interestingly, this is the approach we use in `shinyWidgets` for the `useBs4Dash` function and other related tools.

6.4 Suppress dependencies

In rare cases, you may need to remove an existing dependency (conflict). The `suppressDependencies` function allows to perform that task. For instance, `shiny.semantic` built on top of `semantic ui` is not compatible with Bootstrap. Below, we remove the `AdminLTE` dependency from a `shinydashboard` page and nothing is displayed (as expected):

```
shinyApp(  
  ui = dashboardPage(  
    dashboardHeader(),  
    dashboardSidebar(),  
    dashboardBody(suppressDependencies("AdminLTE")),  
    title = "Dashboard example"  
  ),  
  server = function(input, output) { }  
)
```


Chapter 7

Other tools

7.1 CSS

- See `cascadess` to customize the style of tags

```
ui <- list(  
  cascadess(),  
  h4(  
    .style %>%  
      font(case = "upper") %>%  
      border(bottom = "red"),  
    "Etiam vel tortor sodales tellus ultricies commodo."  
  )  
)
```


Practice

In this chapter, you will learn how to build your own html templates taken from the web and package them, so that they can be re-used at any time by anybody.

Chapter 8

Template selection

There exists tons of HTML templates over the web. However, only a few part will be suitable for shiny, mainly because of what follows:

- shiny is built on top of bootstrap 3 (HTML, CSS and Javascript framework), meaning that going for another framework might not be straightforward. However, shinymaterial and shiny.semantic are examples showing this can be possible.
- shiny relies on jQuery (currently v 1.12.4 for shiny, whereas the latest version is 3.3.1). Consequently, all templates based upon React, Vue and other Javascript framework will not be natively supported. Again, there exist some examples for React with shiny and more generally, the reactR package developed by Kent Russell and Alan Dipert from RStudio.

See the github repository for more details about all dependencies related to the shiny package.

Notes: As shiny depends on Bootstrap 3.3.7, we recommend the user who would like to experiment Bootstrap 4 features to be particularly careful about potential incompatibilities. See a working example here with bs4Dash.

A good source of **open source** HTML templates is Colorlib and Creative Tim. You might also buy your template, but forget about the packaging option, which would be illegal in this particular case.

Chapter 9

Define dependencies

Chapter 10

Template skeleton

Chapter 11

Develop custom input widgets

11.1 How does Shiny handle inputs?

11.2 How to add new input to Shiny?

Chapter 12

Testing templates elements