

Building custom FreeBSD images

Baptiste Daroussin
bapt@FreeBSD.org
bapt@gandi.net



Taipei
2017-11-10

- ▶ Domain names
- ▶ SSL Certificates
- ▶ Simple hosting
- ▶ IaaS

- ▶ Domain names
- ▶ SSL Certificates
- ▶ Simple hosting
- ▶ IaaS
- ▶ An office here in Taiwan
- ▶ Website in ZH-HANT and ZH-HANS
- ▶ Support in Chinese



- ▶ Clean room package building
- ▶ Used in the FreeBSD cluster
- ▶ System stress tool
- ▶ Consistently non pronounceable

- ▶ Always build inside jails
- ▶ No network access during build

- ▶ Always build inside jails
- ▶ No network access during build
- ▶ Massive parallelisation (by default 1 build of package per core, tunable)

- ▶ Always build inside jails
- ▶ No network access during build
- ▶ Massive parallelisation (by default 1 build of package per core, tunable)
- ▶ Multiple modes:
 - ▶ ZFS
 - ▶ UFS
 - ▶ TMPFS:
 - ▶ data
 - ▶ localbase
 - ▶ workdir
 - ▶ all

- ▶ Always build inside jails
- ▶ No network access during build
- ▶ Massive parallelisation (by default 1 build of package per core, tunable)
- ▶ Multiple modes:
 - ▶ ZFS
 - ▶ UFS
 - ▶ TMPFS:
 - ▶ data
 - ▶ localbase
 - ▶ workdir
 - ▶ all
- ▶ port tester (in depth testing)

- ▶ Always build inside jails
- ▶ No network access during build
- ▶ Massive parallelisation (by default 1 build of package per core, tunable)
- ▶ Multiple modes:
 - ▶ ZFS
 - ▶ UFS
 - ▶ TMPFS:
 - ▶ data
 - ▶ localbase
 - ▶ workdir
 - ▶ all
- ▶ port tester (in depth testing)
- ▶ extremely easy to use

- ▶ Custom ramdisks (for FreeBSD based filers)
 - ▶ custom patches on the source tree
 - ▶ custom packages
 - ▶ minimalistic images
 - ▶ custom configuration files

- ▶ Custom ramdisks (for FreeBSD based filers)
 - ▶ custom patches on the source tree
 - ▶ custom packages
 - ▶ minimalistic images
 - ▶ custom configuration files
- ▶ FreeBSD base VM images (for customers)
 - ▶ Vanilla FreeBSD
 - ▶ Few packages
 - ▶ Custom configuration files
 - ▶ Custom script to add to the base system
- ▶ Fast to regenerate (rebuilding is time consuming)

► NanoBSD


- ▶ NanoBSD
- ▶ Crochet


- ▶ NanoBSD
- ▶ Crochet
- ▶ FreeBSD wifi build


- ▶ NanoBSD
- ▶ Crochet
- ▶ FreeBSD wifi build
- ▶ release.sh

A light pink oval with a thin black border containing the word "initial" in a black sans-serif font.

initial







- ▶ below 500 LoC (in shell)

- ▶ below 500 LoC (in shell)
- ▶ many output formats: iso, rawdisk, memdisk, firmware, tar files

- ▶ below 500 LoC (in shell)
- ▶ many output formats: iso, rawdisk, memdisk, firmware, tar files
- ▶ UEFI/bios ready images

- ▶ below 500 LoC (in shell)
- ▶ many output formats: iso, rawdisk, memdisk, firmware, tar files
- ▶ UEFI/bios ready images
- ▶ regenerate from binaries

- ▶ below 500 LoC (in shell)
- ▶ many output formats: iso, rawdisk, memdisk, firmware, tar files
- ▶ UEFI/bios ready images
- ▶ regenerate from binaries
- ▶ overlay

- ▶ below 500 LoC (in shell)
- ▶ many output formats: iso, rawdisk, memdisk, firmware, tar files
- ▶ UEFI/bios ready images
- ▶ regenerate from binaries
- ▶ overlay
- ▶ early support for cross targets: arm (thanks manu@)

- ▶ below 500 LoC (in shell)
- ▶ many output formats: iso, rawdisk, memdisk, firmware, tar files
- ▶ UEFI/bios ready images
- ▶ regenerate from binaries
- ▶ overlay
- ▶ early support for cross targets: arm (thanks manu@)

Poudrière image: how it works

1. jail should be built with a -K so that it contains a kernel

1. jail should be built with a -K so that it contains a kernel
2. bulk packages

1. jail should be built with a -K so that it contains a kernel
2. bulk packages
3. grab jail files into a temporary directory

1. jail should be built with a -K so that it contains a kernel
2. bulk packages
3. grab jail files into a temporary directory
4. run make delete-old base on an extra src.conf

1. jail should be built with a -K so that it contains a kernel
2. bulk packages
3. grab jail files into a temporary directory
4. run make delete-old base on an extra src.conf
5. install packages

1. jail should be built with a -K so that it contains a kernel
2. bulk packages
3. grab jail files into a temporary directory
4. run make delete-old base on an extra src.conf
5. install packages
6. apply an overlay or top of the system

1. jail should be built with a -K so that it contains a kernel
2. bulk packages
3. grab jail files into a temporary directory
4. run make delete-old base on an extra src.conf
5. install packages
6. apply an overlay or top of the system
7. generate the final image
8. profit

- ▶ already there:
 - ▶ support custom source and ports tree
 - ▶ support extra for both ports and source tree
 - ▶ overlay (specific code/configuration) can be isolated
 - ▶ Use binaries (jail + packages) when assembling an image

- ▶ already there:
 - ▶ support custom source and ports tree
 - ▶ support extra for both ports and source tree
 - ▶ overlay (specific code/configuration) can be isolated
 - ▶ Use binaries (jail + packages) when assembling an image
- ▶ to come:
 - ▶ ports overlay to allow working with a vanilla ports tree

Poudrière image: TODO/which list

- ▶ support for vmdk/qcow/vhd

- ▶ support for vmdk/qcow/vhd
- ▶ improve makefs(1): inode exhaustion

- ▶ support for vmdk/qcow/vhd
- ▶ improve makefs(1): inode exhaustion
- ▶ extend makefs(1) to support zfs

- ▶ support for vmdk/qcow/vhd
- ▶ improve makefs(1): inode exhaustion
- ▶ extend makefs(1) to support zfs
- ▶ allow to add u-boot into embedded images

- ▶ support for vmdk/qcow/vhd
- ▶ improve makefs(1): inode exhaustion
- ▶ extend makefs(1) to support zfs
- ▶ allow to add u-boot into embedded images
- ▶ allow user to specify the disk layout

- ▶ support for vmdk/qcow/vhd
- ▶ improve makefs(1): inode exhaustion
- ▶ extend makefs(1) to support zfs
- ▶ allow to add u-boot into embedded images
- ▶ allow user to specify the disk layout
- ▶ add zfs snapshot output

Questions?

Thanks

