

Football Manager

Sprint 3

Generated by Doxygen 1.13.2

1 BSPQ26-E6	1
2 doxygen_mainpage	3
3 Namespace Index	5
3.1 Package List	5
4 Hierarchical Index	7
4.1 Class Hierarchy	7
5 Class Index	9
5.1 Class List	9
6 File Index	11
6.1 File List	11
7 Namespace Documentation	13
7.1 Package com.example.football_manager	13
7.2 Package com.example.football_manager.config	13
7.3 Package com.example.football_manager.controller	14
7.4 Package com.example.football_manager.dto	14
7.4.1 Function Documentation	15
7.4.1.1 MatchResultDTO()	15
7.5 Package com.example.football_manager.model	15
7.6 Package com.example.football_manager.repository	15
7.7 Package com.example.football_manager.service	15
8 Class Documentation	17
8.1 com.example.football_manager.controller.AdminCountryViewController Class Reference	17
8.1.1 Detailed Description	17
8.1.2 Constructor & Destructor Documentation	17
8.1.2.1 AdminCountryViewController()	17
8.1.3 Member Function Documentation	17
8.1.3.1 countriesPage()	17
8.1.3.2 createCountry()	18
8.1.3.3 deleteCountry()	18
8.2 com.example.football_manager.controller.AdminPlayerViewController Class Reference	18
8.2.1 Detailed Description	18
8.2.2 Constructor & Destructor Documentation	19
8.2.2.1 AdminPlayerViewController()	19
8.2.3 Member Function Documentation	19
8.2.3.1 createPlayer()	19
8.2.3.2 deletePlayer()	19
8.2.3.3 managePlayersLanding()	19
8.2.3.4 manageTeamPlayers()	20

8.2.3.5 showEditPlayerForm()	20
8.2.3.6 updatePlayer()	20
8.3 com.example.football_manager.config.AdminSecurityFilter Class Reference	21
8.3.1 Detailed Description	21
8.3.2 Member Function Documentation	21
8.3.2.1 doFilter()	21
8.4 com.example.football_manager.controller.AdminUserController Class Reference	21
8.4.1 Detailed Description	22
8.4.2 Constructor & Destructor Documentation	22
8.4.2.1 AdminUserController()	22
8.4.3 Member Function Documentation	22
8.4.3.1 createUser()	22
8.4.3.2 usersPage()	22
8.5 com.example.football_manager.controller.AdminViewController Class Reference	22
8.5.1 Detailed Description	23
8.5.2 Member Function Documentation	23
8.5.2.1 adminPanel()	23
8.5.2.2 manageTeams()	23
8.6 com.example.football_manager.controller.AuthController Class Reference	23
8.6.1 Detailed Description	23
8.6.2 Member Function Documentation	24
8.6.2.1 login()	24
8.6.2.2 register()	24
8.7 com.example.football_manager.dto.AuthResponseDTO Class Reference	24
8.7.1 Detailed Description	24
8.7.2 Constructor & Destructor Documentation	24
8.7.2.1 AuthResponseDTO()	24
8.7.3 Member Function Documentation	25
8.7.3.1 getEmail()	25
8.7.3.2 getId()	25
8.7.3.3 getIsAdmin()	25
8.7.3.4 getMessage()	25
8.7.3.5 getUsername()	25
8.8 com.example.football_manager.controller.AuthViewController Class Reference	25
8.8.1 Detailed Description	26
8.8.2 Member Function Documentation	26
8.8.2.1 index()	26
8.8.2.2 loginPage()	26
8.8.2.3 registerPage()	26
8.9 com.example.football_manager.model.Competition Class Reference	26
8.9.1 Detailed Description	26
8.10 com.example.football_manager.controller.CompetitionController Class Reference	27

8.10.1 Detailed Description	27
8.10.2 Constructor & Destructor Documentation	27
8.10.2.1 CompetitionController()	27
8.10.3 Member Function Documentation	27
8.10.3.1 createCompetition()	27
8.10.3.2 deleteCompetition()	27
8.10.3.3 getAllCompetitions()	28
8.10.3.4 getCompetitionById()	28
8.10.3.5 updateCompetition()	28
8.11 com.example.football_manager.repository.CompetitionRepository Interface Reference	28
8.11.1 Detailed Description	28
8.12 com.example.football_manager.dto.CompetitionRequestDTO Class Reference	29
8.12.1 Detailed Description	29
8.12.2 Constructor & Destructor Documentation	29
8.12.2.1 CompetitionRequestDTO() [1/2]	29
8.12.2.2 CompetitionRequestDTO() [2/2]	29
8.12.3 Member Function Documentation	29
8.12.3.1 getName()	29
8.12.3.2 setName()	29
8.13 com.example.football_manager.service.CompetitionService Class Reference	30
8.13.1 Detailed Description	30
8.13.2 Constructor & Destructor Documentation	30
8.13.2.1 CompetitionService()	30
8.13.3 Member Function Documentation	30
8.13.3.1 createCompetition()	30
8.13.3.2 deleteCompetition()	30
8.13.3.3 getAllCompetitions()	30
8.13.3.4 getCompetitionById()	31
8.13.3.5 updateCompetition()	31
8.14 com.example.football_manager.model.Country Class Reference	31
8.14.1 Detailed Description	31
8.15 com.example.football_manager.controller.CountryController Class Reference	31
8.15.1 Detailed Description	31
8.15.2 Constructor & Destructor Documentation	32
8.15.2.1 CountryController()	32
8.15.3 Member Function Documentation	32
8.15.3.1 createCountry()	32
8.15.3.2 deleteCountry()	32
8.15.3.3 getAllCountries()	32
8.16 com.example.football_manager.repository.CountryRepository Interface Reference	32
8.16.1 Detailed Description	33
8.17 com.example.football_manager.dto.CountryRequestDTO Class Reference	33

8.17.1 Detailed Description	33
8.17.2 Constructor & Destructor Documentation	33
8.17.2.1 CountryRequestDTO() [1/2]	33
8.17.2.2 CountryRequestDTO() [2/2]	33
8.17.3 Member Function Documentation	33
8.17.3.1 getName()	33
8.17.3.2 setName()	34
8.18 com.example.football_manager.service.CountryService Class Reference	34
8.18.1 Detailed Description	34
8.18.2 Constructor & Destructor Documentation	34
8.18.2.1 CountryService()	34
8.18.3 Member Function Documentation	34
8.18.3.1 createCountry()	34
8.18.3.2 deleteCountry()	35
8.18.3.3 getAllCountries()	35
8.19 com.example.football_manager.controller.FavouriteTeamController Class Reference	35
8.19.1 Detailed Description	35
8.19.2 Constructor & Destructor Documentation	35
8.19.2.1 FavouriteTeamController()	35
8.19.3 Member Function Documentation	35
8.19.3.1 addFavouriteTeam()	35
8.19.3.2 removeFavouriteTeam()	36
8.20 com.example.football_manager.FootballManagerApplication Class Reference	36
8.20.1 Detailed Description	36
8.20.2 Member Function Documentation	36
8.20.2.1 main()	36
8.21 com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO Class Reference	36
8.21.1 Detailed Description	37
8.21.2 Member Function Documentation	37
8.21.2.1 getMinute()	37
8.21.2.2 getStoppageMinute()	37
8.21.2.3 getTeamId()	37
8.21.2.4 setMinute()	37
8.21.2.5 setStoppageMinute()	37
8.21.2.6 setTeamId()	37
8.22 com.example.football_manager.config.LocaleConfig Class Reference	38
8.22.1 Detailed Description	38
8.22.2 Member Function Documentation	38
8.22.2.1 addInterceptors()	38
8.22.2.2 localeChangeInterceptor()	38
8.22.2.3 localeResolver()	38
8.23 com.example.football_manager.dto.LoginDTO Class Reference	39

Generated by Doxygen

8.29.2.7	getStatus()	46
8.29.2.8	getVenue()	46
8.29.2.9	setAwayScore()	46
8.29.2.10	setAwayTeamId()	47
8.29.2.11	setCompetitionId()	47
8.29.2.12	setHomeScore()	47
8.29.2.13	setHomeTeamId()	47
8.29.2.14	setKickoffTime()	47
8.29.2.15	setStatus()	47
8.29.2.16	setVenue()	47
8.30	com.example.football_manager.dto.MatchResultRequestDTO Class Reference	48
8.30.1	Detailed Description	48
8.30.2	Member Function Documentation	48
8.30.2.1	getGoals()	48
8.30.2.2	setGoals()	48
8.31	com.example.football_manager.service.MatchService Class Reference	49
8.31.1	Detailed Description	49
8.31.2	Constructor & Destructor Documentation	49
8.31.2.1	MatchService()	49
8.31.3	Member Function Documentation	49
8.31.3.1	createMatch()	49
8.31.3.2	deleteMatch()	50
8.31.3.3	getAllMatches()	50
8.31.3.4	getFinishedMatchResults()	50
8.31.3.5	getFutureMatchesByFavouriteTeamIds()	50
8.31.3.6	getFutureMatchesByTeamId()	50
8.31.3.7	getGoalsByMatchId()	50
8.31.3.8	getMatchById()	51
8.31.3.9	getMatches()	51
8.31.3.10	getMatchForEdit()	51
8.31.3.11	getRecentMatchesByTeamId()	51
8.31.3.12	registerResult()	51
8.31.3.13	updateMatch()	52
8.32	com.example.football_manager.dto.MatchRequestDTO.MatchStatus Enum Reference	52
8.32.1	Detailed Description	52
8.32.2	Member Data Documentation	52
8.32.2.1	CANCELLED	52
8.32.2.2	FINISHED	52
8.32.2.3	IN_PROGRESS	53
8.32.2.4	SCHEDULED	53
8.33	com.example.football_manager.controller.MatchViewController Class Reference	53
8.33.1	Detailed Description	53

8.33.2 Constructor & Destructor Documentation	53
8.33.2.1 MatchViewController()	53
8.33.3 Member Function Documentation	54
8.33.3.1 saveMatchResult()	54
8.33.3.2 showEditForm()	54
8.33.3.3 showMatchesPage()	54
8.33.3.4 showResultsPage()	54
8.33.3.5 showScheduleForm()	55
8.33.3.6 showScoreForm()	55
8.33.3.7 submitScoreForm()	55
8.33.3.8 updateMatch()	55
8.34 com.example.football_manager.config.OpenApiConfig Class Reference	56
8.34.1 Detailed Description	56
8.35 com.example.football_manager.model.Player Class Reference	56
8.35.1 Detailed Description	56
8.36 com.example.football_manager.controller.PlayerController Class Reference	56
8.36.1 Detailed Description	56
8.36.2 Constructor & Destructor Documentation	56
8.36.2.1 PlayerController()	56
8.36.3 Member Function Documentation	57
8.36.3.1 createPlayer()	57
8.36.3.2 deletePlayer()	57
8.36.3.3 getPlayersByTeamId()	57
8.36.3.4 updatePlayer()	57
8.37 com.example.football_manager.model.PlayerPosition Enum Reference	57
8.37.1 Detailed Description	58
8.37.2 Member Data Documentation	58
8.37.2.1 DEFENDER	58
8.37.2.2 FORWARD	58
8.37.2.3 GOALKEEPER	58
8.37.2.4 MIDFIELDER	58
8.38 com.example.football_manager.repository.PlayerRepository Interface Reference	58
8.38.1 Detailed Description	59
8.38.2 Member Function Documentation	59
8.38.2.1 existsByTeamIdAndNumber()	59
8.38.2.2 existsByTeamIdAndNumberAndIdNot()	59
8.38.2.3 findByIdAndTeamId()	59
8.38.2.4 findByTeamIdOrderByNumberAsc()	59
8.39 com.example.football_manager.dto.PlayerRequestDTO Class Reference	60
8.39.1 Detailed Description	60
8.39.2 Constructor & Destructor Documentation	60
8.39.2.1 PlayerRequestDTO() [1/2]	60

8.39.2.2 PlayerRequestDTO() [2/2]	60
8.39.3 Member Function Documentation	60
8.39.3.1 getName()	60
8.39.3.2 getNumber()	60
8.39.3.3 getPosition()	61
8.39.3.4 setName()	61
8.39.3.5 setNumber()	61
8.39.3.6 setPosition()	61
8.40 com.example.football_manager.service.PlayerService Class Reference	61
8.40.1 Detailed Description	61
8.40.2 Constructor & Destructor Documentation	62
8.40.2.1 PlayerService()	62
8.40.3 Member Function Documentation	62
8.40.3.1 createPlayer()	62
8.40.3.2 deletePlayer()	62
8.40.3.3 getPlayerByTeamId()	62
8.40.3.4 getPlayersByTeamId()	62
8.40.3.5 updatePlayer()	63
8.41 com.example.football_manager.dto.ProfileUpdateDTO Class Reference	63
8.41.1 Detailed Description	63
8.41.2 Member Function Documentation	63
8.41.2.1 isPasswordConfirmationValid()	63
8.42 com.example.football_manager.controller.ProfileViewController Class Reference	63
8.42.1 Detailed Description	64
8.42.2 Constructor & Destructor Documentation	64
8.42.2.1 ProfileViewController()	64
8.42.3 Member Function Documentation	64
8.42.3.1 profilePage()	64
8.42.3.2 updateProfile()	64
8.43 com.example.football_manager.dto.RegisterDTO Class Reference	65
8.43.1 Detailed Description	65
8.43.2 Member Function Documentation	65
8.43.2.1 getEmail()	65
8.43.2.2 getIsAdmin()	65
8.43.2.3 getPassword()	65
8.43.2.4 getUsername()	65
8.43.2.5 setEmail()	66
8.43.2.6 setIsAdmin()	66
8.43.2.7 setPassword()	66
8.43.2.8 setUsername()	66
8.44 com.example.football_manager.config.SecurityConfig Class Reference	66
8.44.1 Detailed Description	66

8.44.2 Member Function Documentation	67
8.44.2.1 filterChain()	67
8.44.2.2 passwordEncoder()	67
8.45 com.example.football_manager.model.Team Class Reference	67
8.45.1 Detailed Description	67
8.45.2 Constructor & Destructor Documentation	67
8.45.2.1 Team()	67
8.46 com.example.football_manager.controller.TeamController Class Reference	68
8.46.1 Detailed Description	68
8.46.2 Constructor & Destructor Documentation	68
8.46.2.1 TeamController()	68
8.46.3 Member Function Documentation	68
8.46.3.1 createTeam()	68
8.46.3.2 deleteTeam()	68
8.46.3.3 getAllTeams()	68
8.46.3.4 getTeamById()	69
8.46.3.5 getTeamsContainingName()	69
8.46.3.6 updateTeam()	69
8.47 com.example.football_manager.repository.TeamRepository Interface Reference	69
8.47.1 Detailed Description	69
8.47.2 Member Function Documentation	70
8.47.2.1 findByNameContainingIgnoreCase()	70
8.48 com.example.football_manager.dto.TeamRequestDTO Class Reference	70
8.48.1 Detailed Description	70
8.48.2 Constructor & Destructor Documentation	70
8.48.2.1 TeamRequestDTO() [1/2]	70
8.48.2.2 TeamRequestDTO() [2/2]	70
8.48.3 Member Function Documentation	71
8.48.3.1 getCountryId()	71
8.48.3.2 getLogoUrl()	71
8.48.3.3 getName()	71
8.48.3.4 setCountryId()	71
8.48.3.5 setLogoUrl()	71
8.48.3.6 setName()	71
8.49 com.example.football_manager.service.TeamService Class Reference	72
8.49.1 Detailed Description	72
8.49.2 Constructor & Destructor Documentation	72
8.49.2.1 TeamService()	72
8.49.3 Member Function Documentation	72
8.49.3.1 createTeam()	72
8.49.3.2 deleteTeam()	72
8.49.3.3 getAllTeams()	72

8.49.3.4 getTeamById()	73
8.49.3.5 getTeamsContainingName()	73
8.49.3.6 updateTeam()	73
8.50 com.example.football_manager.controller.TeamViewController Class Reference	73
8.50.1 Detailed Description	73
8.50.2 Member Function Documentation	74
8.50.2.1 createTeam()	74
8.50.2.2 deleteTeam()	74
8.50.2.3 showAddTeamForm()	74
8.50.2.4 showEditTeamForm()	74
8.50.2.5 teamDetailsPage()	75
8.50.2.6 teamsPage()	75
8.50.2.7 updateTeam()	75
8.51 com.example.football_manager.model.User Class Reference	75
8.51.1 Detailed Description	75
8.52 com.example.football_manager.repository.UserRepository Interface Reference	76
8.52.1 Detailed Description	76
8.52.2 Member Function Documentation	76
8.52.2.1 existsByEmail()	76
8.52.2.2 existsByEmailAndIdNot()	76
8.52.2.3 existsByUsername()	77
8.52.2.4 existsByUsernameAndIdNot()	77
8.52.2.5 findByEmail()	77
8.52.2.6 findByUsername()	77
8.52.2.7 findWithFavouriteTeamsById()	77
8.53 com.example.football_manager.service.UserService Class Reference	78
8.53.1 Detailed Description	78
8.53.2 Member Function Documentation	78
8.53.2.1 addFavouriteTeam()	78
8.53.2.2 getFavouriteTeamIdsByUserId()	78
8.53.2.3 getUserById()	78
8.53.2.4 getUserByUsername()	79
8.53.2.5 getUserProfile()	79
8.53.2.6 login()	79
8.53.2.7 registerUser()	79
8.53.2.8 removeFavouriteTeam()	79
8.53.2.9 updateProfile()	79
9 File Documentation	81
9.1 docs/doxygen_mainpage.md File Reference	81
9.2 Football_Manager/src/main/java/com/example/football_manager/config/AdminSecurityFilter.java File Reference	81
9.3 AdminSecurityFilter.java	82

9.4 Football_Manager/src/main/java/com/example/football_manager/config/LocaleConfig.java File Reference	82
9.5 LocaleConfig.java	83
9.6 Football_Manager/src/main/java/com/example/football_manager/config/OpenApiConfig.java File Reference	83
9.7 OpenApiConfig.java	84
9.8 Football_Manager/src/main/java/com/example/football_manager/config/SecurityConfig.java File Reference	84
9.9 SecurityConfig.java	84
9.10 Football_Manager/src/main/java/com/example/football_manager/controller/AdminCountryView↔Controller.java File Reference	85
9.11 AdminCountryViewController.java	85
9.12 Football_Manager/src/main/java/com/example/football_manager/controller/AdminPlayerView↔Controller.java File Reference	86
9.13 AdminPlayerViewController.java	86
9.14 Football_Manager/src/main/java/com/example/football_manager/controller/AdminUserView↔Controller.java File Reference	89
9.15 AdminUserViewController.java	89
9.16 Football_Manager/src/main/java/com/example/football_manager/controller/AdminViewController.java File Reference	89
9.17 AdminViewController.java	90
9.18 Football_Manager/src/main/java/com/example/football_manager/controller/AuthController.java File Reference	90
9.19 AuthController.java	91
9.20 Football_Manager/src/main/java/com/example/football_manager/controller/AuthViewController.java File Reference	92
9.21 AuthViewController.java	92
9.22 Football_Manager/src/main/java/com/example/football_manager/controller/CompetitionController.java File Reference	93
9.23 CompetitionController.java	93
9.24 Football_Manager/src/main/java/com/example/football_manager/controller/CountryController.java File Reference	95
9.25 CountryController.java	95
9.26 Football_Manager/src/main/java/com/example/football_manager/controller/FavouriteTeamController.java File Reference	96
9.27 FavouriteTeamController.java	97
9.28 Football_Manager/src/main/java/com/example/football_manager/controller/MatchController.java File Reference	98
9.29 MatchController.java	99
9.30 Football_Manager/src/main/java/com/example/football_manager/controller/MatchViewController.java File Reference	101
9.31 MatchViewController.java	101
9.32 Football_Manager/src/main/java/com/example/football_manager/controller/PlayerController.java File Reference	103
9.33 PlayerController.java	104

9.34 Football_Manager/src/main/java/com/example/football_manager/controller/ProfileViewController.java File Reference	105
9.35 ProfileViewController.java	106
9.36 Football_Manager/src/main/java/com/example/football_manager/controller/TeamController.java File Reference	107
9.37 TeamController.java	108
9.38 Football_Manager/src/main/java/com/example/football_manager/controller/TeamViewController.java File Reference	109
9.39 TeamViewController.java	110
9.40 Football_Manager/src/main/java/com/example/football_manager/dto/AuthResponseDTO.java File Reference	111
9.41 AuthResponseDTO.java	112
9.42 Football_Manager/src/main/java/com/example/football_manager/dto/CompetitionRequestDTO.java File Reference	112
9.43 CompetitionRequestDTO.java	113
9.44 Football_Manager/src/main/java/com/example/football_manager/dto/CountryRequestDTO.java File Reference	113
9.45 CountryRequestDTO.java	113
9.46 Football_Manager/src/main/java/com/example/football_manager/dto/LoginDTO.java File Reference .	114
9.47 LoginDTO.java	114
9.48 Football_Manager/src/main/java/com/example/football_manager/dto/MatchRequestDTO.java File Reference	115
9.49 MatchRequestDTO.java	115
9.50 Football_Manager/src/main/java/com/example/football_manager/dto/MatchResultDTO.java File Ref- erence	116
9.51 MatchResultDTO.java	116
9.52 Football_Manager/src/main/java/com/example/football_manager/dto/MatchResultRequestDTO.java File Reference	117
9.53 MatchResultRequestDTO.java	117
9.54 Football_Manager/src/main/java/com/example/football_manager/dto/PlayerRequestDTO.java File Reference	118
9.55 PlayerRequestDTO.java	118
9.56 Football_Manager/src/main/java/com/example/football_manager/dto/ProfileUpdateDTO.java File Reference	119
9.57 ProfileUpdateDTO.java	120
9.58 Football_Manager/src/main/java/com/example/football_manager/dto/RegisterDTO.java File Reference	120
9.59 RegisterDTO.java	121
9.60 Football_Manager/src/main/java/com/example/football_manager/dto/TeamRequestDTO.java File Reference	121
9.61 TeamRequestDTO.java	122
9.62 Football_Manager/src/main/java/com/example/football_manager/FootballManagerApplication.java File Reference	122
9.63 FootballManagerApplication.java	123
9.64 Football_Manager/src/main/java/com/example/football_manager/model/Competition.java File Refer- ence	123
9.65 Competition.java	123

9.66 Football_Manager/src/main/java/com/example/football_manager/model/Country.java File Reference	124
9.67 Country.java	124
9.68 Football_Manager/src/main/java/com/example/football_manager/model/Match.java File Reference	124
9.69 Match.java	125
9.70 Football_Manager/src/main/java/com/example/football_manager/model/MatchGoal.java File Reference	125
9.71 MatchGoal.java	126
9.72 Football_Manager/src/main/java/com/example/football_manager/model/Player.java File Reference	126
9.73 Player.java	127
9.74 Football_Manager/src/main/java/com/example/football_manager/model/PlayerPosition.java File Reference	127
9.75 PlayerPosition.java	127
9.76 Football_Manager/src/main/java/com/example/football_manager/model/Team.java File Reference	128
9.77 Team.java	128
9.78 Football_Manager/src/main/java/com/example/football_manager/model/User.java File Reference	129
9.79 User.java	129
9.80 Football_Manager/src/main/java/com/example/football_manager/repository/CompetitionRepository.java File Reference	130
9.81 CompetitionRepository.java	130
9.82 Football_Manager/src/main/java/com/example/football_manager/repository/CountryRepository.java File Reference	130
9.83 CountryRepository.java	131
9.84 Football_Manager/src/main/java/com/example/football_manager/repository/MatchGoalRepository.java File Reference	131
9.85 MatchGoalRepository.java	131
9.86 Football_Manager/src/main/java/com/example/football_manager/repository/MatchRepository.java File Reference	132
9.87 MatchRepository.java	132
9.88 Football_Manager/src/main/java/com/example/football_manager/repository/PlayerRepository.java File Reference	133
9.89 PlayerRepository.java	133
9.90 Football_Manager/src/main/java/com/example/football_manager/repository/TeamRepository.java File Reference	133
9.91 TeamRepository.java	134
9.92 Football_Manager/src/main/java/com/example/football_manager/repository/UserRepository.java File Reference	134
9.93 UserRepository.java	135
9.94 Football_Manager/src/main/java/com/example/football_manager/service/CompetitionService.java File Reference	135
9.95 CompetitionService.java	135
9.96 Football_Manager/src/main/java/com/example/football_manager/service/CountryService.java File Reference	136
9.97 CountryService.java	136
9.98 Football_Manager/src/main/java/com/example/football_manager/service/MatchService.java File Reference	137
9.99 MatchService.java	138

9.100	Football_Manager/src/main/java/com/example/football_manager/service/PlayerService.java	File Reference	142
9.101	PlayerService.java		143
9.102	Football_Manager/src/main/java/com/example/football_manager/service/TeamService.java	File Reference	145
9.103	TeamService.java		145
9.104	Football_Manager/src/main/java/com/example/football_manager/service/UserService.java	File Reference	146
9.105	UserService.java		147
9.106	README.md	File Reference	149
Index			151

Chapter 1

BSPQ26-E6

Repository for team BSPQ26-E6

Chapter 2

doxygen_mainpage

Football Manager Documentation

Overview

Football Manager is a Spring Boot web application developed for managing football teams, matches, results and standings.

The project includes:

- Team management
- Match management
- Match results
- Favourite teams
- User authentication
- Admin views
- REST API controllers
- Automated tests
- CI pipeline with Jenkins
- Code coverage with JaCoCo
- Performance testing with JUnitPerf

Main Packages

- `controller`: REST and web controllers.
- `service`: Business logic.
- `repository`: Data access layer.
- `model`: Entity classes.
- `dto`: Data transfer objects.
- `config`: Security and application configuration.

Sprint 3 Documentation

This documentation was generated automatically using Doxygen as part of Sprint 3.

Chapter 3

Namespace Index

3.1 Package List

Here are the packages with brief descriptions (if available):

com.example.football_manager	13
com.example.football_manager.config	13
com.example.football_manager.controller	14
com.example.football_manager.dto	14
com.example.football_manager.model	15
com.example.football_manager.repository	15
com.example.football_manager.service	15

Chapter 4

Hierarchical Index

4.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

com.example.football_manager.controller.AdminCountryViewController	17
com.example.football_manager.controller.AdminPlayerViewController	18
com.example.football_manager.controller.AdminUserViewController	21
com.example.football_manager.controller.AdminViewController	22
com.example.football_manager.controller.AuthController	23
com.example.football_manager.dto.AuthResponseDTO	24
com.example.football_manager.controller.AuthViewController	25
com.example.football_manager.model.Competition	26
com.example.football_manager.controller.CompetitionController	27
com.example.football_manager.dto.CompetitionRequestDTO	29
com.example.football_manager.service.CompetitionService	30
com.example.football_manager.model.Country	31
com.example.football_manager.controller.CountryController	31
com.example.football_manager.dto.CountryRequestDTO	33
com.example.football_manager.service.CountryService	34
com.example.football_manager.controller.FavouriteTeamController	35
Filter	
com.example.football_manager.config.AdminSecurityFilter	21
com.example.football_manager.FootballManagerApplication	36
com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO	36
JpaRepository	
com.example.football_manager.repository.CompetitionRepository	28
com.example.football_manager.repository.CountryRepository	32
com.example.football_manager.repository.MatchGoalRepository	42
com.example.football_manager.repository.MatchRepository	43
com.example.football_manager.repository.PlayerRepository	58
com.example.football_manager.repository.TeamRepository	69
com.example.football_manager.repository.UserRepository	76
com.example.football_manager.dto.LoginDTO	39
com.example.football_manager.model.Match	40
com.example.football_manager.controller.MatchController	40
com.example.football_manager.model.MatchGoal	42
com.example.football_manager.dto.MatchRequestDTO	44
com.example.football_manager.dto.MatchResultRequestDTO	48
com.example.football_manager.service.MatchService	49

com.example.football_manager.dto.MatchRequestDTO.MatchStatus	52
com.example.football_manager.controller.MatchViewController	53
com.example.football_manager.config.OpenApiConfig	56
com.example.football_manager.model.Player	56
com.example.football_manager.controller.PlayerController	56
com.example.football_manager.model.PlayerPosition	57
com.example.football_manager.dto.PlayerRequestDTO	60
com.example.football_manager.service.PlayerService	61
com.example.football_manager.dto.ProfileUpdateDTO	63
com.example.football_manager.controller.ProfileViewController	63
com.example.football_manager.dto.RegisterDTO	65
com.example.football_manager.config.SecurityConfig	66
com.example.football_manager.model.Team	67
com.example.football_manager.controller.TeamController	68
com.example.football_manager.dto.TeamRequestDTO	70
com.example.football_manager.service.TeamService	72
com.example.football_manager.controller.TeamViewController	73
com.example.football_manager.model.User	75
com.example.football_manager.service.UserService	78
WebMvcConfigurer	
com.example.football_manager.config.LocaleConfig	38

Chapter 5

Class Index

5.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

com.example.football_manager.controller.AdminCountryViewController	17
com.example.football_manager.controller.AdminPlayerViewController	18
com.example.football_manager.config.AdminSecurityFilter	21
com.example.football_manager.controller.AdminUserViewController	21
com.example.football_manager.controller.AdminViewController	22
com.example.football_manager.controller.AuthController	23
com.example.football_manager.dto.AuthResponseDTO	24
com.example.football_manager.controller.AuthViewController	25
com.example.football_manager.model.Competition	26
com.example.football_manager.controller.CompetitionController	27
com.example.football_manager.repository.CompetitionRepository	28
com.example.football_manager.dto.CompetitionRequestDTO	29
com.example.football_manager.service.CompetitionService	30
com.example.football_manager.model.Country	31
com.example.football_manager.controller.CountryController	31
com.example.football_manager.repository.CountryRepository	32
com.example.football_manager.dto.CountryRequestDTO	33
com.example.football_manager.service.CountryService	34
com.example.football_manager.controller.FavouriteTeamController	35
com.example.football_manager.FootballManagerApplication	36
com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO	36
com.example.football_manager.config.LocaleConfig	38
com.example.football_manager.dto.LoginDTO	39
com.example.football_manager.model.Match	40
com.example.football_manager.controller.MatchController	40
com.example.football_manager.model.MatchGoal	42
com.example.football_manager.repository.MatchGoalRepository	42
com.example.football_manager.repository.MatchRepository	43
com.example.football_manager.dto.MatchRequestDTO	44
com.example.football_manager.dto.MatchResultRequestDTO	48
com.example.football_manager.service.MatchService	49
com.example.football_manager.dto.MatchRequestDTO.MatchStatus	52
com.example.football_manager.controller.MatchViewController	53
com.example.football_manager.config.OpenApiConfig	56
com.example.football_manager.model.Player	56

com.example.football_manager.controller.PlayerController	56
com.example.football_manager.model.PlayerPosition	57
com.example.football_manager.repository.PlayerRepository	58
com.example.football_manager.dto.PlayerRequestDTO	60
com.example.football_manager.service.PlayerService	61
com.example.football_manager.dto.ProfileUpdateDTO	63
com.example.football_manager.controller.ProfileViewController	63
com.example.football_manager.dto.RegisterDTO	65
com.example.football_manager.config.SecurityConfig	66
com.example.football_manager.model.Team	67
com.example.football_manager.controller.TeamController	68
com.example.football_manager.repository.TeamRepository	69
com.example.football_manager.dto.TeamRequestDTO	70
com.example.football_manager.service.TeamService	72
com.example.football_manager.controller.TeamViewController	73
com.example.football_manager.model.User	75
com.example.football_manager.repository.UserRepository	76
com.example.football_manager.service.UserService	78

Chapter 6

File Index

6.1 File List

Here is a list of all files with brief descriptions:

Football_Manager/src/main/java/com/example/football_manager/FootballManagerApplication.java	122
Football_Manager/src/main/java/com/example/football_manager/config/AdminSecurityFilter.java	81
Football_Manager/src/main/java/com/example/football_manager/config/LocaleConfig.java	82
Football_Manager/src/main/java/com/example/football_manager/config/OpenApiConfig.java	83
Football_Manager/src/main/java/com/example/football_manager/config/SecurityConfig.java	84
Football_Manager/src/main/java/com/example/football_manager/controller/AdminCountryViewController.java	
85	
Football_Manager/src/main/java/com/example/football_manager/controller/AdminPlayerViewController.java	
86	
Football_Manager/src/main/java/com/example/football_manager/controller/AdminUserViewController.java	89
Football_Manager/src/main/java/com/example/football_manager/controller/AdminViewController.java . .	89
Football_Manager/src/main/java/com/example/football_manager/controller/AuthController.java	90
Football_Manager/src/main/java/com/example/football_manager/controller/AuthViewController.java . . .	92
Football_Manager/src/main/java/com/example/football_manager/controller/CompetitionController.java . .	93
Football_Manager/src/main/java/com/example/football_manager/controller/CountryController.java	95
Football_Manager/src/main/java/com/example/football_manager/controller/FavouriteTeamController.java	96
Football_Manager/src/main/java/com/example/football_manager/controller/MatchController.java	98
Football_Manager/src/main/java/com/example/football_manager/controller/MatchViewController.java . .	101
Football_Manager/src/main/java/com/example/football_manager/controller/PlayerController.java	103
Football_Manager/src/main/java/com/example/football_manager/controller/ProfileViewController.java . .	105
Football_Manager/src/main/java/com/example/football_manager/controller/TeamController.java	107
Football_Manager/src/main/java/com/example/football_manager/controller/TeamViewController.java . .	109
Football_Manager/src/main/java/com/example/football_manager/dto/AuthResponseDTO.java	111
Football_Manager/src/main/java/com/example/football_manager/dto/CompetitionRequestDTO.java . . .	112
Football_Manager/src/main/java/com/example/football_manager/dto/CountryRequestDTO.java	113
Football_Manager/src/main/java/com/example/football_manager/dto/LoginDTO.java	114
Football_Manager/src/main/java/com/example/football_manager/dto/MatchRequestDTO.java	115
Football_Manager/src/main/java/com/example/football_manager/dto/MatchResultDTO.java	116
Football_Manager/src/main/java/com/example/football_manager/dto/MatchResultRequestDTO.java . . .	117
Football_Manager/src/main/java/com/example/football_manager/dto/PlayerRequestDTO.java	118
Football_Manager/src/main/java/com/example/football_manager/dto/ProfileUpdateDTO.java	119
Football_Manager/src/main/java/com/example/football_manager/dto/RegisterDTO.java	120
Football_Manager/src/main/java/com/example/football_manager/dto/TeamRequestDTO.java	121
Football_Manager/src/main/java/com/example/football_manager/model/Competition.java	123
Football_Manager/src/main/java/com/example/football_manager/model/Country.java	124

Football_Manager/src/main/java/com/example/football_manager/model/Match.java	124
Football_Manager/src/main/java/com/example/football_manager/model/MatchGoal.java	125
Football_Manager/src/main/java/com/example/football_manager/model/Player.java	126
Football_Manager/src/main/java/com/example/football_manager/model/PlayerPosition.java	127
Football_Manager/src/main/java/com/example/football_manager/model/Team.java	128
Football_Manager/src/main/java/com/example/football_manager/model/User.java	129
Football_Manager/src/main/java/com/example/football_manager/repository/CompetitionRepository.java .	130
Football_Manager/src/main/java/com/example/football_manager/repository/CountryRepository.java . . .	130
Football_Manager/src/main/java/com/example/football_manager/repository/MatchGoalRepository.java .	131
Football_Manager/src/main/java/com/example/football_manager/repository/MatchRepository.java	132
Football_Manager/src/main/java/com/example/football_manager/repository/PlayerRepository.java	133
Football_Manager/src/main/java/com/example/football_manager/repository/TeamRepository.java	133
Football_Manager/src/main/java/com/example/football_manager/repository/UserRepository.java	134
Football_Manager/src/main/java/com/example/football_manager/service/CompetitionService.java	135
Football_Manager/src/main/java/com/example/football_manager/service/CountryService.java	136
Football_Manager/src/main/java/com/example/football_manager/service/MatchService.java	137
Football_Manager/src/main/java/com/example/football_manager/service/PlayerService.java	142
Football_Manager/src/main/java/com/example/football_manager/service/TeamService.java	145
Football_Manager/src/main/java/com/example/football_manager/service/UserService.java	146

Chapter 7

Namespace Documentation

7.1 Package com.example.football_manager

Packages

- package [config](#)
- package [controller](#)
- package [dto](#)
- package [model](#)
- package [repository](#)
- package [service](#)

Classes

- class [FootballManagerApplication](#)

7.2 Package com.example.football_manager.config

Classes

- class [AdminSecurityFilter](#)
- class [LocaleConfig](#)
- class [OpenApiConfig](#)
- class [SecurityConfig](#)

7.3 Package com.example.football_manager.controller

Classes

- class [AdminCountryViewController](#)
- class [AdminPlayerViewController](#)
- class [AdminUserViewController](#)
- class [AdminViewController](#)
- class [AuthController](#)
- class [AuthViewController](#)
- class [CompetitionController](#)
- class [CountryController](#)
- class [FavouriteTeamController](#)
- class [MatchController](#)
- class [MatchViewController](#)
- class [PlayerController](#)
- class [ProfileViewController](#)
- class [TeamController](#)
- class [TeamViewController](#)

7.4 Package com.example.football_manager.dto

Classes

- class [AuthResponseDTO](#)
- class [CompetitionRequestDTO](#)
- class [CountryRequestDTO](#)
- class [LoginDTO](#)
- class [MatchRequestDTO](#)
- class [MatchResultRequestDTO](#)
- class [PlayerRequestDTO](#)
- class [ProfileUpdateDTO](#)
- class [RegisterDTO](#)
- class [TeamRequestDTO](#)

Functions

- record [MatchResultDTO](#) (@Schema(description="Match identifier", example="220") Long matchId, @Schema(description="Home team name", example="Real Sociedad") String homeTeamName, @Schema(description="Away team name", example="Athletic Club") String awayTeamName, @Schema(description="Home team score", example="2") short homeScore, @Schema(description="Away team score", example="1") short awayScore, @Schema(description="Kickoff time (UTC)", example="2026-04-28T18:30:00Z") OffsetDateTime kickoffTime)

7.4.1 Function Documentation

7.4.1.1 MatchResultDTO()

```
record com.example.football_manager.dto.MatchResultDTO (  
    @Schema(description="Match identifier", example="220") Long matchId,  
    @Schema(description="Home team name", example="Real Sociedad") String homeTeam↵  
Name,  
    @Schema(description="Away team name", example="Athletic Club") String awayTeam↵  
Name,  
    @Schema(description="Home team score", example="2") short homeScore,  
    @Schema(description="Away team score", example="1") short awayScore,  
    @Schema(description="Kickoff time (UTC)", example="2026-04-28T18:30:00Z") Offset↵  
DateTime kickoffTime)
```

Definition at line 6 of file [MatchResultDTO.java](#).

7.5 Package com.example.football_manager.model

Classes

- class [Competition](#)
- class [Country](#)
- class [Match](#)
- class [MatchGoal](#)
- class [Player](#)
- enum [PlayerPosition](#)
- class [Team](#)
- class [User](#)

7.6 Package com.example.football_manager.repository

Classes

- interface [CompetitionRepository](#)
- interface [CountryRepository](#)
- interface [MatchGoalRepository](#)
- interface [MatchRepository](#)
- interface [PlayerRepository](#)
- interface [TeamRepository](#)
- interface [UserRepository](#)

7.7 Package com.example.football_manager.service

Classes

- class [CompetitionService](#)
- class [CountryService](#)
- class [MatchService](#)
- class [PlayerService](#)
- class [TeamService](#)
- class [UserService](#)

Chapter 8

Class Documentation

8.1 com.example.football_manager.controller.AdminCountryViewController Class Reference

Public Member Functions

- [AdminCountryViewController](#) ([CountryService](#) countryService)
- String [countriesPage](#) (Model model)
- String [createCountry](#) (@ModelAttribute [CountryRequestDTO](#) countryRequest)
- String [deleteCountry](#) (@PathVariable Long id)

8.1.1 Detailed Description

Definition at line 10 of file [AdminCountryViewController.java](#).

8.1.2 Constructor & Destructor Documentation

8.1.2.1 AdminCountryViewController()

```
com.example.football_manager.controller.AdminCountryViewController.AdminCountryViewController  
(  
    CountryService countryService)
```

Definition at line 14 of file [AdminCountryViewController.java](#).

8.1.3 Member Function Documentation

8.1.3.1 countriesPage()

```
String com.example.football_manager.controller.AdminCountryViewController.countriesPage (  
    Model model)
```

Definition at line 19 of file [AdminCountryViewController.java](#).

References [countriesPage\(\)](#).

Referenced by [countriesPage\(\)](#).

8.1.3.2 createCountry()

```
String com.example.football_manager.controller.AdminCountryViewController.createCountry (
    @ModelAttribute CountryRequestDTO countryRequest)
```

Definition at line 26 of file [AdminCountryViewController.java](#).

References [createCountry\(\)](#).

Referenced by [createCountry\(\)](#).

8.1.3.3 deleteCountry()

```
String com.example.football_manager.controller.AdminCountryViewController.deleteCountry (
    @PathVariable Long id)
```

Definition at line 32 of file [AdminCountryViewController.java](#).

References [deleteCountry\(\)](#).

Referenced by [deleteCountry\(\)](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/AdminCountryViewController.java](#)

8.2 com.example.football_manager.controller.AdminPlayerView↵ Controller Class Reference

Public Member Functions

- [AdminPlayerViewController](#) ([TeamService](#) teamService, [PlayerService](#) playerService)
- String [managePlayersLanding](#) (Model model)
- String [manageTeamPlayers](#) (@PathVariable Long teamId, Model model, RedirectAttributes redirectAttributes)
- String [createPlayer](#) (@PathVariable Long teamId, @Valid @ModelAttribute("playerRequest") [PlayerRequestDTO](#) playerRequest, BindingResult bindingResult, Model model, RedirectAttributes redirectAttributes)
- String [showEditPlayerForm](#) (@PathVariable Long teamId, @PathVariable Long playerId, Model model, RedirectAttributes redirectAttributes)
- String [updatePlayer](#) (@PathVariable Long teamId, @PathVariable Long playerId, @Valid @ModelAttribute("playerRequest") [PlayerRequestDTO](#) playerRequest, BindingResult bindingResult, Model model, RedirectAttributes redirectAttributes)
- String [deletePlayer](#) (@PathVariable Long teamId, @PathVariable Long playerId, RedirectAttributes redirect↵Attributes)

8.2.1 Detailed Description

Definition at line 20 of file [AdminPlayerViewController.java](#).

8.2.2 Constructor & Destructor Documentation

8.2.2.1 AdminPlayerViewController()

```
com.example.football_manager.controller.AdminPlayerViewController.AdminPlayerViewController (
    TeamService teamService,
    PlayerService playerService)
```

Definition at line 25 of file [AdminPlayerViewController.java](#).

8.2.3 Member Function Documentation

8.2.3.1 createPlayer()

```
String com.example.football_manager.controller.AdminPlayerViewController.createPlayer (
    @PathVariable Long teamId,
    @Valid @ModelAttribute("playerRequest") PlayerRequestDTO playerRequest,
    BindingResult bindingResult,
    Model model,
    RedirectAttributes redirectAttributes)
```

Definition at line 52 of file [AdminPlayerViewController.java](#).

References [createPlayer\(\)](#).

Referenced by [createPlayer\(\)](#).

8.2.3.2 deletePlayer()

```
String com.example.football_manager.controller.AdminPlayerViewController.deletePlayer (
    @PathVariable Long teamId,
    @PathVariable Long playerId,
    RedirectAttributes redirectAttributes)
```

Definition at line 151 of file [AdminPlayerViewController.java](#).

References [deletePlayer\(\)](#).

Referenced by [deletePlayer\(\)](#).

8.2.3.3 managePlayersLanding()

```
String com.example.football_manager.controller.AdminPlayerViewController.managePlayersLanding
(
    Model model)
```

Definition at line 31 of file [AdminPlayerViewController.java](#).

References [managePlayersLanding\(\)](#).

Referenced by [managePlayersLanding\(\)](#).

8.2.3.4 manageTeamPlayers()

```
String com.example.football_manager.controller.AdminPlayerViewController.manageTeamPlayers (
    @PathVariable Long teamId,
    Model model,
    RedirectAttributes redirectAttributes)
```

Definition at line 36 of file [AdminPlayerViewController.java](#).

References [manageTeamPlayers\(\)](#).

Referenced by [manageTeamPlayers\(\)](#).

8.2.3.5 showEditPlayerForm()

```
String com.example.football_manager.controller.AdminPlayerViewController.showEditPlayerForm (
    @PathVariable Long teamId,
    @PathVariable Long playerId,
    Model model,
    RedirectAttributes redirectAttributes)
```

Definition at line 82 of file [AdminPlayerViewController.java](#).

References [showEditPlayerForm\(\)](#).

Referenced by [showEditPlayerForm\(\)](#).

8.2.3.6 updatePlayer()

```
String com.example.football_manager.controller.AdminPlayerViewController.updatePlayer (
    @PathVariable Long teamId,
    @PathVariable Long playerId,
    @Valid @ModelAttribute("playerRequest") PlayerRequestDTO playerRequest,
    BindingResult bindingResult,
    Model model,
    RedirectAttributes redirectAttributes)
```

Definition at line 116 of file [AdminPlayerViewController.java](#).

References [updatePlayer\(\)](#).


Referenced by [updatePlayer\(\)](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/AdminPlayerViewController.java](#)

8.3 com.example.football_manager.config.AdminSecurityFilter Class Reference

Inheritance diagram for com.example.football_manager.config.AdminSecurityFilter:



Public Member Functions

- void [doFilter](#) (ServletRequest request, ServletResponse response, FilterChain chain) throws IOException, ServletException

8.3.1 Detailed Description

Definition at line 16 of file [AdminSecurityFilter.java](#).

8.3.2 Member Function Documentation

8.3.2.1 doFilter()

```
void com.example.football_manager.config.AdminSecurityFilter.doFilter (
    ServletRequest request,
    ServletResponse response,
    FilterChain chain) throws IOException, ServletException
```

Definition at line 19 of file [AdminSecurityFilter.java](#).

The documentation for this class was generated from the following file:

- Football_Manager/src/main/java/com/example/football_manager/config/[AdminSecurityFilter.java](#)

8.4 com.example.football_manager.controller.AdminUserController Class Reference

Public Member Functions

- [AdminUserController](#) ([UserService](#) userService)
- String [usersPage](#) ()
- String [createUser](#) (@RequestParam String username, @RequestParam String email, @RequestParam String password, @RequestParam(defaultValue="false") Boolean isAdmin)

8.4.1 Detailed Description

Definition at line 8 of file [AdminUserController.java](#).

8.4.2 Constructor & Destructor Documentation

8.4.2.1 AdminUserController()

```
com.example.football_manager.controller.AdminUserController.AdminUserController (
    UserService userService)
```

Definition at line 12 of file [AdminUserController.java](#).

8.4.3 Member Function Documentation

8.4.3.1 createUser()

```
String com.example.football_manager.controller.AdminUserController.createUser (
    @RequestParam String username,
    @RequestParam String email,
    @RequestParam String password,
    @RequestParam(defaultValue="false") Boolean isAdmin)
```

Definition at line 22 of file [AdminUserController.java](#).

References [createUser\(\)](#).

Referenced by [createUser\(\)](#).

8.4.3.2 usersPage()

```
String com.example.football_manager.controller.AdminUserController.usersPage ()
```

Definition at line 17 of file [AdminUserController.java](#).

References [usersPage\(\)](#).

Referenced by [usersPage\(\)](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/AdminUserController.java](#)

8.5 com.example.football_manager.controller.AdminViewController Class Reference

Public Member Functions

- String [adminPanel](#) ()
- String [manageTeams](#) (Model model)

8.5.1 Detailed Description

Definition at line 10 of file [AdminViewController.java](#).

8.5.2 Member Function Documentation

8.5.2.1 adminPanel()

```
String com.example.football_manager.controller.AdminViewController.adminPanel ()
```

Definition at line 16 of file [AdminViewController.java](#).

References [adminPanel\(\)](#).

Referenced by [adminPanel\(\)](#).

8.5.2.2 manageTeams()

```
String com.example.football_manager.controller.AdminViewController.manageTeams (  
    Model model)
```

Definition at line 21 of file [AdminViewController.java](#).

References [manageTeams\(\)](#).

Referenced by [manageTeams\(\)](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/AdminViewController.java](#)

8.6 com.example.football_manager.controller.AuthController Class Reference

Public Member Functions

- `ResponseEntity< AuthResponseDTO > register (@Valid @RequestBody RegisterDTO registerDTO)`
- `ResponseEntity< AuthResponseDTO > login (@Valid @RequestBody LoginDTO loginDTO, HttpSession session)`

8.6.1 Detailed Description

Definition at line 24 of file [AuthController.java](#).

8.6.2 Member Function Documentation

8.6.2.1 login()

```
ResponseEntity< AuthResponseDTO > com.example.football_manager.controller.AuthController.login  
(  
    @Valid @RequestBody LoginDTO loginDTO,  
    HttpSession session)
```

Definition at line 76 of file [AuthController.java](#).

8.6.2.2 register()

```
ResponseEntity< AuthResponseDTO > com.example.football_manager.controller.AuthController.  
register (  
    @Valid @RequestBody RegisterDTO registerDTO)
```

Definition at line 44 of file [AuthController.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/AuthController.java](#)

8.7 com.example.football_manager.dto.AuthResponseDTO Class Reference

Public Member Functions

- [AuthResponseDTO](#) (Long id, String username, String email, Boolean isAdmin, String message)
- Long [getId](#) ()
- String [getUsername](#) ()
- String [getEmail](#) ()
- Boolean [getIsAdmin](#) ()
- String [getMessage](#) ()

8.7.1 Detailed Description

Definition at line 5 of file [AuthResponseDTO.java](#).

8.7.2 Constructor & Destructor Documentation

8.7.2.1 AuthResponseDTO()

```
com.example.football_manager.dto.AuthResponseDTO.AuthResponseDTO (  
    Long id,  
    String username,  
    String email,  
    Boolean isAdmin,  
    String message)
```

Definition at line 18 of file [AuthResponseDTO.java](#).

8.7.3 Member Function Documentation

8.7.3.1 getEmail()

```
String com.example.football_manager.dto.AuthResponseDTO.getEmail ()
```

Definition at line 34 of file [AuthResponseDTO.java](#).

8.7.3.2 getId()

```
Long com.example.football_manager.dto.AuthResponseDTO.getId ()
```

Definition at line 26 of file [AuthResponseDTO.java](#).

8.7.3.3 getIsAdmin()

```
Boolean com.example.football_manager.dto.AuthResponseDTO.getIsAdmin ()
```

Definition at line 38 of file [AuthResponseDTO.java](#).

8.7.3.4 getMessage()

```
String com.example.football_manager.dto.AuthResponseDTO.getMessage ()
```

Definition at line 42 of file [AuthResponseDTO.java](#).

8.7.3.5 getUsername()

```
String com.example.football_manager.dto.AuthResponseDTO.getUsername ()
```

Definition at line 30 of file [AuthResponseDTO.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/dto/AuthResponseDTO.java](#)

8.8 com.example.football_manager.controller.AuthViewController Class Reference

Public Member Functions

- String [index](#) ()
- String [loginPage](#) ()
- String [registerPage](#) ()

8.8.1 Detailed Description

Definition at line 7 of file [AuthViewController.java](#).

8.8.2 Member Function Documentation

8.8.2.1 index()

```
String com.example.football_manager.controller.AuthViewController.index ()
```

Definition at line 11 of file [AuthViewController.java](#).

References [index\(\)](#).

Referenced by [index\(\)](#).

8.8.2.2 loginPage()

```
String com.example.football_manager.controller.AuthViewController.loginPage ()
```

Definition at line 16 of file [AuthViewController.java](#).

References [loginPage\(\)](#).

Referenced by [loginPage\(\)](#).

8.8.2.3 registerPage()

```
String com.example.football_manager.controller.AuthViewController.registerPage ()
```

Definition at line 21 of file [AuthViewController.java](#).

References [registerPage\(\)](#).

Referenced by [registerPage\(\)](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/AuthViewController.java](#)

8.9 com.example.football_manager.model.Competition Class Reference

8.9.1 Detailed Description

Definition at line 13 of file [Competition.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/model/Competition.java](#)

8.10 com.example.football_manager.controller.CompetitionController Class Reference

Public Member Functions

- [CompetitionController](#) ([CompetitionService](#) competitionService)
- [ResponseEntity](#)< [Competition](#) > [createCompetition](#) (@Valid @RequestBody [CompetitionRequestDTO](#) dto)
- [ResponseEntity](#)< [Competition](#) > [updateCompetition](#) (@PathVariable Long id, @Valid @RequestBody [CompetitionRequestDTO](#) dto)
- [ResponseEntity](#)< [Competition](#) > [getCompetitionById](#) (@PathVariable Long id)
- [ResponseEntity](#)< List< [Competition](#) > > [getAllCompetitions](#) ()
- [ResponseEntity](#)< Void > [deleteCompetition](#) (@PathVariable Long id)

8.10.1 Detailed Description

Definition at line 22 of file [CompetitionController.java](#).

8.10.2 Constructor & Destructor Documentation

8.10.2.1 CompetitionController()

```
com.example.football_manager.controller.CompetitionController.CompetitionController (  
    CompetitionService competitionService)
```

Definition at line 26 of file [CompetitionController.java](#).

8.10.3 Member Function Documentation

8.10.3.1 createCompetition()

```
ResponseEntity< Competition > com.example.football_manager.controller.CompetitionController.  
createCompetition (  
    @Valid @RequestBody CompetitionRequestDTO dto)
```

Definition at line 44 of file [CompetitionController.java](#).

8.10.3.2 deleteCompetition()

```
ResponseEntity< Void > com.example.football_manager.controller.CompetitionController.  
deleteCompetition (  
    @PathVariable Long id)
```

Definition at line 104 of file [CompetitionController.java](#).

8.10.3.3 getAllCompetitions()

```
ResponseEntity< List< Competition > > com.example.football_manager.controller.CompetitionController.  
Controller.getAllCompetitions ()
```

Definition at line 91 of file [CompetitionController.java](#).

8.10.3.4 getCompetitionById()

```
ResponseEntity< Competition > com.example.football_manager.controller.CompetitionController.  
getCompetitionById (  
    @PathVariable Long id)
```

Definition at line 79 of file [CompetitionController.java](#).

8.10.3.5 updateCompetition()

```
ResponseEntity< Competition > com.example.football_manager.controller.CompetitionController.  
updateCompetition (  
    @PathVariable Long id,  
    @Valid @RequestBody CompetitionRequestDTO dto)
```


Definition at line 64 of file [CompetitionController.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/CompetitionController.java](#)

8.11 com.example.football_manager.repository.CompetitionRepository Interface Reference

Inheritance diagram for com.example.football_manager.repository.CompetitionRepository:



8.11.1 Detailed Description

Definition at line 8 of file [CompetitionRepository.java](#).

The documentation for this interface was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/repository/CompetitionRepository.java](#)

8.12 com.example.football_manager.dto.CompetitionRequestDTO Class Reference

Public Member Functions

- [CompetitionRequestDTO](#) ()
- [CompetitionRequestDTO](#) (String name)
- String [getName](#) ()
- void [setName](#) (String name)

8.12.1 Detailed Description

Definition at line 7 of file [CompetitionRequestDTO.java](#).

8.12.2 Constructor & Destructor Documentation

8.12.2.1 CompetitionRequestDTO() [1/2]

```
com.example.football_manager.dto.CompetitionRequestDTO.CompetitionRequestDTO ()
```

Definition at line 14 of file [CompetitionRequestDTO.java](#).

8.12.2.2 CompetitionRequestDTO() [2/2]

```
com.example.football_manager.dto.CompetitionRequestDTO.CompetitionRequestDTO (  
    String name)
```

Definition at line 17 of file [CompetitionRequestDTO.java](#).

8.12.3 Member Function Documentation

8.12.3.1 getName()

```
String com.example.football_manager.dto.CompetitionRequestDTO.getName ()
```

Definition at line 21 of file [CompetitionRequestDTO.java](#).

8.12.3.2 setName()

```
void com.example.football_manager.dto.CompetitionRequestDTO.setName (  
    String name)
```

Definition at line 25 of file [CompetitionRequestDTO.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/dto/CompetitionRequestDTO.java](#)

8.13 com.example.football_manager.service.CompetitionService Class Reference

Public Member Functions

- [CompetitionService](#) ([CompetitionRepository](#) competitionRepository)
- [Competition](#) createCompetition ([CompetitionRequestDTO](#) dto)
- [Competition](#) updateCompetition (Long id, [CompetitionRequestDTO](#) dto)
- Optional< [Competition](#) > [getCompetitionById](#) (Long id)
- List< [Competition](#) > [getAllCompetitions](#) ()
- void [deleteCompetition](#) (Long id)

8.13.1 Detailed Description

Definition at line 12 of file [CompetitionService.java](#).

8.13.2 Constructor & Destructor Documentation

8.13.2.1 CompetitionService()

```
com.example.football_manager.service.CompetitionService.CompetitionService (  
    CompetitionRepository competitionRepository)
```

Definition at line 16 of file [CompetitionService.java](#).

8.13.3 Member Function Documentation

8.13.3.1 createCompetition()

```
Competition com.example.football_manager.service.CompetitionService.createCompetition (  
    CompetitionRequestDTO dto)
```

Definition at line 20 of file [CompetitionService.java](#).

8.13.3.2 deleteCompetition()

```
void com.example.football_manager.service.CompetitionService.deleteCompetition (  
    Long id)
```

Definition at line 42 of file [CompetitionService.java](#).

8.13.3.3 getAllCompetitions()

```
List< Competition > com.example.football_manager.service.CompetitionService.getAllCompetitions  
()
```

Definition at line 38 of file [CompetitionService.java](#).

8.13.3.4 getCompetitionById()

```
Optional< Competition > com.example.football_manager.service.CompetitionService.getCompetition↵  
ById (   
        Long id)
```

Definition at line 34 of file [CompetitionService.java](#).

8.13.3.5 updateCompetition()

```
Competition com.example.football_manager.service.CompetitionService.updateCompetition (   
        Long id,   
        CompetitionRequestDTO dto)
```

Definition at line 26 of file [CompetitionService.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/service/CompetitionService.java](#)

8.14 com.example.football_manager.model.Country Class Reference

8.14.1 Detailed Description

Definition at line 13 of file [Country.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/model/Country.java](#)

8.15 com.example.football_manager.controller.CountryController Class Reference

Public Member Functions

- [CountryController](#) ([CountryService](#) countryService)
- [ResponseEntity](#)< [Country](#) > [createCountry](#) (@Valid @RequestBody [CountryRequestDTO](#) dto)
- [ResponseEntity](#)< List< [Country](#) > > [getAllCountries](#) ()
- [ResponseEntity](#)< Void > [deleteCountry](#) (@PathVariable Long id)

8.15.1 Detailed Description

Definition at line 22 of file [CountryController.java](#).

8.15.2 Constructor & Destructor Documentation

8.15.2.1 CountryController()

```
com.example.football_manager.controller.CountryController.CountryController (
    CountryService countryService)
```

Definition at line 26 of file [CountryController.java](#).

8.15.3 Member Function Documentation

8.15.3.1 createCountry()

```
ResponseEntity< Country > com.example.football_manager.controller.CountryController.createCountry (
    @Valid @RequestBody CountryRequestDTO dto)
```

Definition at line 44 of file [CountryController.java](#).

8.15.3.2 deleteCountry()

```
ResponseEntity< Void > com.example.football_manager.controller.CountryController.deleteCountry (
    @PathVariable Long id)
```

Definition at line 71 of file [CountryController.java](#).

8.15.3.3 getAllCountries()

```
ResponseEntity< List< Country > > com.example.football_manager.controller.CountryController.getAllCountries ()
```


Definition at line 57 of file [CountryController.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/CountryController.java](#)

8.16 com.example.football_manager.repository.CountryRepository Interface Reference

Inheritance diagram for com.example.football_manager.repository.CountryRepository:



8.16.1 Detailed Description

Definition at line 8 of file [CountryRepository.java](#).

The documentation for this interface was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/repository/CountryRepository.java](#)

8.17 com.example.football_manager.dto.CountryRequestDTO Class Reference

Public Member Functions

- [CountryRequestDTO](#) ()
- [CountryRequestDTO](#) (String name)
- String [getName](#) ()
- void [setName](#) (String name)

8.17.1 Detailed Description

Definition at line 7 of file [CountryRequestDTO.java](#).

8.17.2 Constructor & Destructor Documentation

8.17.2.1 CountryRequestDTO() [1/2]

```
com.example.football_manager.dto.CountryRequestDTO.CountryRequestDTO ()
```

Definition at line 14 of file [CountryRequestDTO.java](#).

8.17.2.2 CountryRequestDTO() [2/2]

```
com.example.football_manager.dto.CountryRequestDTO.CountryRequestDTO (  
    String name)
```

Definition at line 17 of file [CountryRequestDTO.java](#).

8.17.3 Member Function Documentation

8.17.3.1 getName()

```
String com.example.football_manager.dto.CountryRequestDTO.getName ()
```

Definition at line 21 of file [CountryRequestDTO.java](#).

8.17.3.2 setName()

```
void com.example.football_manager.dto.CountryRequestDTO.setName (  
    String name)
```

Definition at line 25 of file [CountryRequestDTO.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/dto/CountryRequestDTO.java](#)

8.18 com.example.football_manager.service.CountryService Class Reference

Public Member Functions

- [CountryService](#) ([CountryRepository](#) countryRepository)
- [Country](#) createCountry ([CountryRequestDTO](#) dto)
- List< [Country](#) > [getAllCountries](#) ()
- void [deleteCountry](#) (Long id)

8.18.1 Detailed Description

Definition at line 11 of file [CountryService.java](#).

8.18.2 Constructor & Destructor Documentation

8.18.2.1 CountryService()

```
com.example.football_manager.service.CountryService.CountryService (  
    CountryRepository countryRepository)
```

Definition at line 15 of file [CountryService.java](#).

8.18.3 Member Function Documentation

8.18.3.1 createCountry()

```
Country com.example.football_manager.service.CountryService.createCountry (  
    CountryRequestDTO dto)
```

Definition at line 19 of file [CountryService.java](#).

8.18.3.2 deleteCountry()

```
void com.example.football_manager.service.CountryService.deleteCountry (
    Long id)
```

Definition at line 29 of file [CountryService.java](#).

8.18.3.3 getAllCountries()

```
List< Country > com.example.football_manager.service.CountryService.getAllCountries ()
```

Definition at line 25 of file [CountryService.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/service/CountryService.java](#)

8.19 com.example.football_manager.controller.FavouriteTeamController Class Reference

Public Member Functions

- [FavouriteTeamController](#) ([UserService](#) userService)
- [ResponseEntity< String > addFavouriteTeam](#) (@PathVariable Long teamId, HttpSession session)
- [ResponseEntity< String > removeFavouriteTeam](#) (@PathVariable Long teamId, HttpSession session)

8.19.1 Detailed Description

Definition at line 20 of file [FavouriteTeamController.java](#).

8.19.2 Constructor & Destructor Documentation

8.19.2.1 FavouriteTeamController()

```
com.example.football_manager.controller.FavouriteTeamController.FavouriteTeamController (
    UserService userService)
```

Definition at line 24 of file [FavouriteTeamController.java](#).

8.19.3 Member Function Documentation

8.19.3.1 addFavouriteTeam()

```
ResponseEntity< String > com.example.football_manager.controller.FavouriteTeamController.add↵
FavouriteTeam (
    @PathVariable Long teamId,
    HttpSession session)
```

Definition at line 39 of file [FavouriteTeamController.java](#).

8.19.3.2 removeFavouriteTeam()

```
ResponseEntity< String > com.example.football_manager.controller.FavouriteTeamController.removeFavouriteTeam (
    @PathVariable Long teamId,
    HttpSession session)
```

Definition at line 64 of file [FavouriteTeamController.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/FavouriteTeamController.java](#)

8.20 com.example.football_manager.FootballManagerApplication Class Reference

Static Public Member Functions

- static void [main](#) (String[] args)

8.20.1 Detailed Description

Definition at line 7 of file [FootballManagerApplication.java](#).

8.20.2 Member Function Documentation

8.20.2.1 main()

```
static void com.example.football_manager.FootballManagerApplication.main (
    String[] args) [static]
```

Definition at line 9 of file [FootballManagerApplication.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/FootballManagerApplication.java](#)

8.21 com.example.football_manager.dto.MatchResultRequestDTO.Goal DTO Class Reference

Public Member Functions

- Long [getTeamId](#) ()
- void [setTeamId](#) (Long teamId)
- Integer [getMinute](#) ()
- void [setMinute](#) (Integer minute)
- Integer [getStoppageMinute](#) ()
- void [setStoppageMinute](#) (Integer stoppageMinute)

8.21.1 Detailed Description

Definition at line 25 of file [MatchResultRequestDTO.java](#).

8.21.2 Member Function Documentation

8.21.2.1 getMinute()

```
Integer com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO.getMinute ()
```

Definition at line 50 of file [MatchResultRequestDTO.java](#).

8.21.2.2 getStoppageMinute()

```
Integer com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO.getStoppageMinute ()
```

Definition at line 58 of file [MatchResultRequestDTO.java](#).

8.21.2.3 getTeamId()

```
Long com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO.getTeamId ()
```

Definition at line 42 of file [MatchResultRequestDTO.java](#).

8.21.2.4 setMinute()

```
void com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO.setMinute (  
    Integer minute)
```

Definition at line 54 of file [MatchResultRequestDTO.java](#).

8.21.2.5 setStoppageMinute()

```
void com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO.setStoppageMinute (  
    Integer stoppageMinute)
```

Definition at line 62 of file [MatchResultRequestDTO.java](#).

8.21.2.6 setTeamId()

```
void com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO.setTeamId (  
    Long teamId)
```


Definition at line 46 of file [MatchResultRequestDTO.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/dto/MatchResultRequestDTO.java](#)

8.22 com.example.football_manager.config.LocaleConfig Class Reference

Inheritance diagram for com.example.football_manager.config.LocaleConfig:



Public Member Functions

- LocaleResolver [localeResolver](#) ()
- LocaleChangeInterceptor [localeChangeInterceptor](#) ()
- void [addInterceptors](#) (InterceptorRegistry registry)

8.22.1 Detailed Description

Definition at line 13 of file [LocaleConfig.java](#).

8.22.2 Member Function Documentation

8.22.2.1 addInterceptors()

```
void com.example.football_manager.config.LocaleConfig.addInterceptors (
    InterceptorRegistry registry)
```

Definition at line 30 of file [LocaleConfig.java](#).

References [localeChangeInterceptor\(\)](#).

8.22.2.2 localeChangeInterceptor()

```
LocaleChangeInterceptor com.example.football_manager.config.LocaleConfig.localeChangeInterceptor
()
```

Definition at line 23 of file [LocaleConfig.java](#).

Referenced by [addInterceptors\(\)](#).

8.22.2.3 localeResolver()

```
LocaleResolver com.example.football_manager.config.LocaleConfig.localeResolver ()
```

Definition at line 16 of file [LocaleConfig.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/config/LocaleConfig.java](#)

8.23 com.example.football_manager.dto.LoginDTO Class Reference

Public Member Functions

- String [getUsername](#) ()
- void [setUsername](#) (String username)
- String [getPassword](#) ()
- void [setPassword](#) (String password)

8.23.1 Detailed Description

Definition at line 6 of file [LoginDTO.java](#).

8.23.2 Member Function Documentation

8.23.2.1 getPassword()

```
String com.example.football_manager.dto.LoginDTO.getPassword ()
```

Definition at line 24 of file [LoginDTO.java](#).

8.23.2.2 getUsername()

```
String com.example.football_manager.dto.LoginDTO.getUsername ()
```

Definition at line 16 of file [LoginDTO.java](#).

8.23.2.3 setPassword()

```
void com.example.football_manager.dto.LoginDTO.setPassword (  
    String password)
```

Definition at line 28 of file [LoginDTO.java](#).

8.23.2.4 setUsername()

```
void com.example.football_manager.dto.LoginDTO.setUsername (  
    String username)
```

Definition at line 20 of file [LoginDTO.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/dto/LoginDTO.java](#)

8.24 com.example.football_manager.model.Match Class Reference

8.24.1 Detailed Description

Definition at line 12 of file [Match.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/model/Match.java](#)

8.25 com.example.football_manager.controller.MatchController Class Reference

Public Member Functions

- `ResponseEntity< List< Match > > getMatches ( @RequestParam(required=false) Long teamId, @RequestParam(required=false) MatchRequestDTO.MatchStatus status, @RequestParam(required=false) Long competitionId)`
- `ResponseEntity< String > createMatchFromJson (@Valid @RequestBody MatchRequestDTO matchDTO)`
- `ResponseEntity< String > createMatchFromForm (@Valid @ModelAttribute MatchRequestDTO matchDTO)`
- `ResponseEntity< List< MatchResultDTO > > getMatchResults ()`
- `ResponseEntity< String > updateMatch (@PathVariable Long id, @RequestBody MatchRequestDTO matchDTO)`
- `ResponseEntity< String > deleteMatch (@PathVariable Long id)`
- `ResponseEntity< String > registerResult ( @PathVariable Long id, @Valid @RequestBody MatchResultRequestDTO resultDTO)`

8.25.1 Detailed Description

Definition at line 27 of file [MatchController.java](#).

8.25.2 Member Function Documentation

8.25.2.1 createMatchFromForm()

```
ResponseEntity< String > com.example.football_manager.controller.MatchController.createMatchFromForm (
    @Valid @ModelAttribute MatchRequestDTO matchDTO)
```

Definition at line 84 of file [MatchController.java](#).

8.25.2.2 createMatchFromJson()

```
ResponseEntity< String > com.example.football_manager.controller.MatchController.createMatchFromJson (
    @Valid @RequestBody MatchRequestDTO matchDTO)
```

Definition at line 66 of file [MatchController.java](#).

8.25.2.3 deleteMatch()

```
ResponseEntity< String > com.example.football_manager.controller.MatchController.deleteMatch (
    @PathVariable Long id)
```

Definition at line 141 of file [MatchController.java](#).

8.25.2.4 getMatches()

```
ResponseEntity< List< Match > > com.example.football_manager.controller.MatchController.getMatches (
    @RequestParam(required=false) Long teamId,
    @RequestParam(required=false) MatchRequestDTO.MatchStatus status,
    @RequestParam(required=false) Long competitionId)
```

Definition at line 41 of file [MatchController.java](#).

8.25.2.5 getMatchResults()

```
ResponseEntity< List< MatchResultDTO > > com.example.football_manager.controller.MatchController.getMatchResults ()
```

Definition at line 105 of file [MatchController.java](#).

8.25.2.6 registerResult()

```
ResponseEntity< String > com.example.football_manager.controller.MatchController.registerResult (
    @PathVariable Long id,
    @Valid @RequestBody MatchResultRequestDTO resultDTO)
```

Definition at line 163 of file [MatchController.java](#).

8.25.2.7 updateMatch()

```
ResponseEntity< String > com.example.football_manager.controller.MatchController.updateMatch (
    @PathVariable Long id,
    @RequestBody MatchRequestDTO matchDTO)
```

Definition at line 124 of file [MatchController.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/MatchController.java](#)

8.26 com.example.football_manager.model.MatchGoal Class Reference

8.26.1 Detailed Description


Definition at line 13 of file [MatchGoal.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/model/MatchGoal.java](#)

8.27 com.example.football_manager.repository.MatchGoalRepository Interface Reference

Inheritance diagram for com.example.football_manager.repository.MatchGoalRepository:



Public Member Functions

- void [deleteByMatchId](#) (Long matchId)
- List< [MatchGoal](#) > [findByMatchIdOrderByMinuteAscStoppageMinuteAscIdAsc](#) (Long matchId)

8.27.1 Detailed Description

Definition at line 10 of file [MatchGoalRepository.java](#).

8.27.2 Member Function Documentation

8.27.2.1 deleteByMatchId()

```
void com.example.football_manager.repository.MatchGoalRepository.deleteByMatchId (
    Long matchId)
```

8.27.2.2 findByMatchIdOrderByMinuteAscStoppageMinuteAscIdAsc()


```
List< MatchGoal > com.example.football_manager.repository.MatchGoalRepository.findByMatchId↔
OrderByMinuteAscStoppageMinuteAscIdAsc (
    Long matchId)
```

The documentation for this interface was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/repository/MatchGoalRepository.java](#)

8.28 com.example.football_manager.repository.MatchRepository Interface Reference

Inheritance diagram for com.example.football_manager.repository.MatchRepository:



Public Member Functions

- List< [Match](#) > [findByFilters](#) (@Param("teamId") Long teamId, @Param("finished") Boolean finished, @Param("competitionId") Long competitionId)
- List< [Match](#) > [findByFinishedTrueOrderByDatetimeDesc](#) ()
- List< [Match](#) > [findByFinishedTrueAndLeftTeamIdOrFinishedTrueAndRightTeamIdOrderByDatetimeDesc](#) (Long leftTeamId, Long rightTeamId)
- List< [Match](#) > [findByFinishedFalseAndDatetimeAfterAndLeftTeamIdOrFinishedFalseAndDatetimeAfterAndRightTeamIdOrderByDatetimeAsc](#) (OffsetDateTime now1, Long leftTeamId, OffsetDateTime now2, Long rightTeamId)
- List< [Match](#) > [findByFinishedFalseAndDatetimeAfterAndLeftTeamIdInOrFinishedFalseAndDatetimeAfterAndRightTeamIdInOrderByDatetimeAsc](#) (OffsetDateTime now1, Collection< Long > leftTeamIds, OffsetDateTime now2, Collection< Long > rightTeamIds)

8.28.1 Detailed Description

Definition at line 14 of file [MatchRepository.java](#).

8.28.2 Member Function Documentation

8.28.2.1 findByFilters()

```
List< Match > com.example.football_manager.repository.MatchRepository.findByFilters (
    @Param("teamId") Long teamId,
    @Param("finished") Boolean finished,
    @Param("competitionId") Long competitionId)
```

References [findByFilters\(\)](#).

Referenced by [findByFilters\(\)](#).

8.28.2.2 findByFinishedFalseAndDatetimeAfterAndLeftTeamIdInOrFinishedFalseAndDatetimeAfterAndRightTeamIdInOrderByDatetimeAsc

```
List< Match > com.example.football_manager.repository.MatchRepository.findByFinishedFalseAnd←
DatetimeAfterAndLeftTeamIdInOrFinishedFalseAndDatetimeAfterAndRightTeamIdInOrderByDatetimeAsc
(
    OffsetDateTime now1,
    Collection< Long > leftTeamIds,
    OffsetDateTime now2,
    Collection< Long > rightTeamIds)
```

References [findByFinishedFalseAndDatetimeAfterAndLeftTeamIdInOrFinishedFalseAndDatetimeAfterAndRightTeamIdInOrderByDatetimeAsc](#).

Referenced by [findByFinishedFalseAndDatetimeAfterAndLeftTeamIdInOrFinishedFalseAndDatetimeAfterAndRightTeamIdInOrderByDatetimeAsc](#).

8.28.2.3 `findByFinishedFalseAndDatetimeAfterAndLeftTeamIdOrFinishedFalseAndDatetimeAfterAndRightTeamIdOrderByDatetimeAsc`

```
List< Match > com.example.football_manager.repository.MatchRepository.findByFinishedFalseAnd←
DatetimeAfterAndLeftTeamIdOrFinishedFalseAndDatetimeAfterAndRightTeamIdOrderByDatetimeAsc (
    OffsetDateTime now1,
    Long leftTeamId,
    OffsetDateTime now2,
    Long rightTeamId)
```

References [findByFinishedFalseAndDatetimeAfterAndLeftTeamIdOrFinishedFalseAndDatetimeAfterAndRightTeamIdOrderByDatetimeAsc](#)

Referenced by [findByFinishedFalseAndDatetimeAfterAndLeftTeamIdOrFinishedFalseAndDatetimeAfterAndRightTeamIdOrderByDatetimeAsc](#)

8.28.2.4 `findByFinishedTrueAndLeftTeamIdOrFinishedTrueAndRightTeamIdOrderByDatetimeDesc()`

```
List< Match > com.example.football_manager.repository.MatchRepository.findByFinishedTrueAnd←
LeftTeamIdOrFinishedTrueAndRightTeamIdOrderByDatetimeDesc (
    Long leftTeamId,
    Long rightTeamId)
```

References [findByFinishedTrueAndLeftTeamIdOrFinishedTrueAndRightTeamIdOrderByDatetimeDesc\(\)](#).

Referenced by [findByFinishedTrueAndLeftTeamIdOrFinishedTrueAndRightTeamIdOrderByDatetimeDesc\(\)](#).

8.28.2.5 `findByFinishedTrueOrderByDatetimeDesc()`

```
List< Match > com.example.football_manager.repository.MatchRepository.findByFinishedTrue←
OrderByDatetimeDesc ()
```

References [findByFinishedTrueOrderByDatetimeDesc\(\)](#).

Referenced by [findByFinishedTrueOrderByDatetimeDesc\(\)](#).

The documentation for this interface was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/repository/MatchRepository.java](#)

8.29 `com.example.football_manager.dto.MatchRequestDTO` Class Reference

Classes

- enum [MatchStatus](#)

Public Member Functions

- Long [getHomeTeamId](#) ()
- void [setHomeTeamId](#) (Long homeTeamId)
- Long [getAwayTeamId](#) ()
- void [setAwayTeamId](#) (Long awayTeamId)
- Long [getCompetitionId](#) ()
- void [setCompetitionId](#) (Long competitionId)
- LocalDateTime [getKickoffTime](#) ()
- void [setKickoffTime](#) (LocalDateTime kickoffTime)
- String [getVenue](#) ()
- void [setVenue](#) (String venue)
- [MatchStatus](#) [getStatus](#) ()
- void [setStatus](#) ([MatchStatus](#) status)
- Integer [getHomeScore](#) ()
- void [setHomeScore](#) (Integer homeScore)
- Integer [getAwayScore](#) ()
- void [setAwayScore](#) (Integer awayScore)

8.29.1 Detailed Description

Definition at line 9 of file [MatchRequestDTO.java](#).

8.29.2 Member Function Documentation

8.29.2.1 [getAwayScore\(\)](#)

```
Integer com.example.football_manager.dto.MatchRequestDTO.getAwayScore ()
```

Definition at line 59 of file [MatchRequestDTO.java](#).

Referenced by [com.example.football_manager.service.MatchService.createMatch\(\)](#), and [com.example.football_manager.service.Mat](#)

8.29.2.2 [getAwayTeamId\(\)](#)

```
Long com.example.football_manager.dto.MatchRequestDTO.getAwayTeamId ()
```

Definition at line 41 of file [MatchRequestDTO.java](#).

Referenced by [com.example.football_manager.service.MatchService.createMatch\(\)](#), and [com.example.football_manager.service.Mat](#)

8.29.2.3 [getCompetitionId\(\)](#)

```
Long com.example.football_manager.dto.MatchRequestDTO.getCompetitionId ()
```

Definition at line 44 of file [MatchRequestDTO.java](#).

Referenced by [com.example.football_manager.service.MatchService.createMatch\(\)](#).

8.29.2.4 getHomeScore()

```
Integer com.example.football_manager.dto.MatchRequestDTO.getHomeScore ()
```

Definition at line 56 of file [MatchRequestDTO.java](#).

Referenced by [com.example.football_manager.service.MatchService.createMatch\(\)](#), and [com.example.football_manager.service.Mat](#)

8.29.2.5 getHomeTeamId()

```
Long com.example.football_manager.dto.MatchRequestDTO.getHomeTeamId ()
```

Definition at line 38 of file [MatchRequestDTO.java](#).

References [getHomeTeamId\(\)](#).

Referenced by [com.example.football_manager.service.MatchService.createMatch\(\)](#), [getHomeTeamId\(\)](#), and [com.example.football_manager.service.MatchService.updateMatch\(\)](#).

8.29.2.6 getKickoffTime()

```
LocalDateTime com.example.football_manager.dto.MatchRequestDTO.getKickoffTime ()
```

Definition at line 47 of file [MatchRequestDTO.java](#).

Referenced by [com.example.football_manager.service.MatchService.createMatch\(\)](#), and [com.example.football_manager.service.Mat](#)

8.29.2.7 getStatus()

```
MatchStatus com.example.football_manager.dto.MatchRequestDTO.getStatus ()
```

Definition at line 53 of file [MatchRequestDTO.java](#).

Referenced by [com.example.football_manager.service.MatchService.createMatch\(\)](#), and [com.example.football_manager.service.Mat](#)

8.29.2.8 getVenue()

```
String com.example.football_manager.dto.MatchRequestDTO.getVenue ()
```

Definition at line 50 of file [MatchRequestDTO.java](#).

Referenced by [com.example.football_manager.service.MatchService.createMatch\(\)](#), and [com.example.football_manager.service.Mat](#)

8.29.2.9 setAwayScore()

```
void com.example.football_manager.dto.MatchRequestDTO.setAwayScore (  
    Integer awayScore)
```

Definition at line 60 of file [MatchRequestDTO.java](#).

8.29.2.10 setAwayTeamId()

```
void com.example.football_manager.dto.MatchRequestDTO.setAwayTeamId (  
    Long awayTeamId)
```

Definition at line 42 of file [MatchRequestDTO.java](#).

8.29.2.11 setCompetitionId()

```
void com.example.football_manager.dto.MatchRequestDTO.setCompetitionId (  
    Long competitionId)
```

Definition at line 45 of file [MatchRequestDTO.java](#).

8.29.2.12 setHomeScore()

```
void com.example.football_manager.dto.MatchRequestDTO.setHomeScore (  
    Integer homeScore)
```

Definition at line 57 of file [MatchRequestDTO.java](#).

8.29.2.13 setHomeTeamId()

```
void com.example.football_manager.dto.MatchRequestDTO.setHomeTeamId (  
    Long homeTeamId)
```

Definition at line 39 of file [MatchRequestDTO.java](#).

8.29.2.14 setKickoffTime()

```
void com.example.football_manager.dto.MatchRequestDTO.setKickoffTime (  
    LocalDateTime kickoffTime)
```

Definition at line 48 of file [MatchRequestDTO.java](#).

8.29.2.15 setStatus()

```
void com.example.football_manager.dto.MatchRequestDTO.setStatus (  
    MatchStatus status)
```

Definition at line 54 of file [MatchRequestDTO.java](#).

8.29.2.16 setVenue()

```
void com.example.football_manager.dto.MatchRequestDTO.setVenue (  
    String venue)
```

Definition at line 51 of file [MatchRequestDTO.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/dto/MatchRequestDTO.java](#)

8.30 com.example.football_manager.dto.MatchResultRequestDTO Class Reference

Classes

- class [GoalDTO](#)

Public Member Functions

- List< [GoalDTO](#) > [getGoals](#) ()
- void [setGoals](#) (List< [GoalDTO](#) > goals)

8.30.1 Detailed Description

Definition at line 11 of file [MatchResultRequestDTO.java](#).

8.30.2 Member Function Documentation

8.30.2.1 getGoals()

```
List< GoalDTO > com.example.football_manager.dto.MatchResultRequestDTO.getGoals ()
```

Definition at line 17 of file [MatchResultRequestDTO.java](#).

Referenced by [com.example.football_manager.service.MatchService.registerResult\(\)](#).

8.30.2.2 setGoals()

```
void com.example.football_manager.dto.MatchResultRequestDTO.setGoals (  
    List< GoalDTO > goals)
```

Definition at line 21 of file [MatchResultRequestDTO.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/dto/MatchResultRequestDTO.java](#)

8.31 com.example.football_manager.service.MatchService Class Reference

Public Member Functions

- [MatchService](#) ([MatchRepository](#) matchRepository, [MatchGoalRepository](#) matchGoalRepository, [TeamRepository](#) teamRepository, [CompetitionRepository](#) competitionRepository)
- String [createMatch](#) ([MatchRequestDTO](#) request)
- String [updateMatch](#) (Long id, [MatchRequestDTO](#) request)
- String [deleteMatch](#) (Long id)
- String [registerResult](#) (Long id, [MatchResultRequestDTO](#) request)
- List< [MatchResultDTO](#) > [getFinishedMatchResults](#) ()
- Optional< [MatchRequestDTO](#) > [getMatchForEdit](#) (Long id)
- List< [Match](#) > [getAllMatches](#) ()
- List< [Match](#) > [getMatches](#) (Long teamId, [MatchRequestDTO](#).MatchStatus status, Long competitionId)
- [Match](#) [getMatchById](#) (Long id)
- List< [MatchGoal](#) > [getGoalsByMatchId](#) (Long matchId)
- List< [Match](#) > [getRecentMatchesByTeamId](#) (Long teamId)
- List< [Match](#) > [getFutureMatchesByTeamId](#) (Long teamId)
- List< [Match](#) > [getFutureMatchesByFavouriteTeamIds](#) (Set< Long > favouriteTeamIds)

8.31.1 Detailed Description

Definition at line 27 of file [MatchService.java](#).

8.31.2 Constructor & Destructor Documentation

8.31.2.1 MatchService()

```
com.example.football_manager.service.MatchService.MatchService (
    MatchRepository matchRepository,
    MatchGoalRepository matchGoalRepository,
    TeamRepository teamRepository,
    CompetitionRepository competitionRepository)
```

Definition at line 35 of file [MatchService.java](#).

8.31.3 Member Function Documentation

8.31.3.1 createMatch()

```
String com.example.football_manager.service.MatchService.createMatch (
    MatchRequestDTO request)
```

Definition at line 48 of file [MatchService.java](#).

References [com.example.football_manager.dto.MatchRequestDTO.MatchStatus.FINISHED](#), [com.example.football_manager.dto.MatchRequestDTO.getAwayTeamId\(\)](#), [com.example.football_manager.dto.MatchRequestDTO.getHomeScore\(\)](#), [com.example.football_manager.dto.MatchRequestDTO.getKickoffTime\(\)](#), [com.example.football_manager.dto.MatchRequestDTO.getVenue\(\)](#) and [com.example.football_manager.dto.MatchRequestDTO.getVenue\(\)](#).

8.31.3.2 deleteMatch()

```
String com.example.football_manager.service.MatchService.deleteMatch (
    Long id)
```

Definition at line 141 of file [MatchService.java](#).

8.31.3.3 getAllMatches()

```
List< Match > com.example.football_manager.service.MatchService.getAllMatches ()
```

Definition at line 263 of file [MatchService.java](#).

Referenced by [getMatches\(\)](#).

8.31.3.4 getFinishedMatchResults()

```
List< MatchResultDTO > com.example.football_manager.service.MatchService.getFinishedMatch←
Results ()
```

Definition at line 192 of file [MatchService.java](#).

8.31.3.5 getFutureMatchesByFavouriteTeamIds()

```
List< Match > com.example.football_manager.service.MatchService.getFutureMatchesByFavourite←
TeamIds (
    Set< Long > favouriteTeamIds)
```

Definition at line 306 of file [MatchService.java](#).

8.31.3.6 getFutureMatchesByTeamId()

```
List< Match > com.example.football_manager.service.MatchService.getFutureMatchesByTeamId (
    Long teamId)
```

Definition at line 294 of file [MatchService.java](#).

8.31.3.7 getGoalsByMatchId()

```
List< MatchGoal > com.example.football_manager.service.MatchService.getGoalsByMatchId (
    Long matchId)
```

Definition at line 282 of file [MatchService.java](#).

8.31.3.8 getMatchById()

```
Match com.example.football_manager.service.MatchService.getMatchById (
    Long id)
```

Definition at line 277 of file [MatchService.java](#).

8.31.3.9 getMatches()

```
List< Match > com.example.football_manager.service.MatchService.getMatches (
    Long teamId,
    MatchRequestDTO.MatchStatus status,
    Long competitionId)
```

Definition at line 267 of file [MatchService.java](#).

References [getAllMatches\(\)](#).

8.31.3.10 getMatchForEdit()

```
Optional< MatchRequestDTO > com.example.football_manager.service.MatchService.getMatchForEdit
(
    Long id)
```

Definition at line 207 of file [MatchService.java](#).

References [com.example.football_manager.dto.MatchRequestDTO.MatchStatus.FINISHED](#), and [com.example.football_manager.dto.](#)

8.31.3.11 getRecentMatchesByTeamId()

```
List< Match > com.example.football_manager.service.MatchService.getRecentMatchesByTeamId (
    Long teamId)
```

Definition at line 286 of file [MatchService.java](#).

8.31.3.12 registerResult()

```
String com.example.football_manager.service.MatchService.registerResult (
    Long id,
    MatchResultRequestDTO request)
```

Definition at line 152 of file [MatchService.java](#).

References [com.example.football_manager.dto.MatchResultRequestDTO.getGoals\(\)](#).

8.31.3.13 updateMatch()

```
String com.example.football_manager.service.MatchService.updateMatch (
    Long id,
    MatchRequestDTO request)
```

Definition at line 102 of file [MatchService.java](#).

References [com.example.football_manager.dto.MatchRequestDTO.MatchStatus.FINISHED](#), [com.example.football_manager.dto.MatchRequestDTO.getAwayTeamId\(\)](#), [com.example.football_manager.dto.MatchRequestDTO.getHomeTeamId\(\)](#), [com.example.football_manager.dto.MatchRequestDTO.getStatus\(\)](#), and [com.example.football_manager.dto.MatchRequestDTO.getVenueId\(\)](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/service/MatchService.java](#)

8.32 com.example.football_manager.dto.MatchRequestDTO.MatchStatus Enum Reference

Public Attributes

- [SCHEDULED](#)
- [IN_PROGRESS](#)
- [FINISHED](#)
- [CANCELLED](#)

8.32.1 Detailed Description

Definition at line 11 of file [MatchRequestDTO.java](#).

8.32.2 Member Data Documentation

8.32.2.1 CANCELLED

```
com.example.football_manager.dto.MatchRequestDTO.MatchStatus.CANCELLED
```

Definition at line 15 of file [MatchRequestDTO.java](#).

8.32.2.2 FINISHED

```
com.example.football_manager.dto.MatchRequestDTO.MatchStatus.FINISHED
```

Definition at line 14 of file [MatchRequestDTO.java](#).

Referenced by [com.example.football_manager.service.MatchService.createMatch\(\)](#), [com.example.football_manager.service.MatchService.updateMatch\(\)](#), and [com.example.football_manager.service.MatchService.updateMatch\(\)](#).

8.32.2.3 IN_PROGRESS

com.example.football_manager.dto.MatchRequestDTO.MatchStatus.IN_PROGRESS

Definition at line 13 of file [MatchRequestDTO.java](#).

8.32.2.4 SCHEDULED

com.example.football_manager.dto.MatchRequestDTO.MatchStatus.SCHEDULED

Definition at line 12 of file [MatchRequestDTO.java](#).

Referenced by [com.example.football_manager.service.MatchService.getMatchForEdit\(\)](#).

The documentation for this enum was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/dto/MatchRequestDTO.java](#)

8.33 com.example.football_manager.controller.MatchViewController Class Reference

Public Member Functions

- [MatchViewController](#) ([MatchService](#) matchService, [TeamService](#) teamService)
- String [showMatchesPage](#) (@RequestParam(required=false) Long teamId, @RequestParam(required=false) MatchRequestDTO.MatchStatus status, @RequestParam(required=false) Long competitionId, Model model, HttpSession session)
- String [showScheduleForm](#) (Model model)
- String [showResultsPage](#) (Model model)
- String [showEditForm](#) (@PathVariable Long id, Model model)
- String [updateMatch](#) (@PathVariable Long id, @ModelAttribute("matchRequest") [MatchRequestDTO](#) matchRequest, Model model)
- String [showScoreForm](#) (@PathVariable Long id, Model model)
- String [submitScoreForm](#) (@PathVariable Long id, @ModelAttribute("resultRequest") [MatchResultRequestDTO](#) resultRequest, Model model, RedirectAttributes redirectAttributes)
- String [saveMatchResult](#) (@PathVariable Long id, @ModelAttribute [MatchResultRequestDTO](#) requestDTO)

8.33.1 Detailed Description

Definition at line 26 of file [MatchViewController.java](#).

8.33.2 Constructor & Destructor Documentation

8.33.2.1 MatchViewController()

```
com.example.football_manager.controller.MatchViewController.MatchViewController (
    MatchService matchService,
    TeamService teamService)
```

Definition at line 31 of file [MatchViewController.java](#).

8.33.3 Member Function Documentation

8.33.3.1 saveMatchResult()

```
String com.example.football_manager.controller.MatchViewController.saveMatchResult (
    @PathVariable Long id,
    @ModelAttribute MatchResultRequestDTO requestDTO)
```

Definition at line 144 of file [MatchViewController.java](#).

References [saveMatchResult\(\)](#).

Referenced by [saveMatchResult\(\)](#).

8.33.3.2 showEditForm()

```
String com.example.football_manager.controller.MatchViewController.showEditForm (
    @PathVariable Long id,
    Model model)
```

Definition at line 71 of file [MatchViewController.java](#).

References [showEditForm\(\)](#).

Referenced by [showEditForm\(\)](#).

8.33.3.3 showMatchesPage()

```
String com.example.football_manager.controller.MatchViewController.showMatchesPage (
    @RequestParam(required=false) Long teamId,
    @RequestParam(required=false) MatchRequestDTO.MatchStatus status,
    @RequestParam(required=false) Long competitionId,
    Model model,
    HttpSession session)
```

Definition at line 37 of file [MatchViewController.java](#).

References [showMatchesPage\(\)](#).

Referenced by [showMatchesPage\(\)](#).

8.33.3.4 showResultsPage()

```
String com.example.football_manager.controller.MatchViewController.showResultsPage (
    Model model)
```

Definition at line 65 of file [MatchViewController.java](#).

References [showResultsPage\(\)](#).

Referenced by [showResultsPage\(\)](#).

8.33.3.5 showScheduleForm()

```
String com.example.football_manager.controller.MatchViewController.showScheduleForm (  
    Model model)
```

Definition at line 58 of file [MatchViewController.java](#).

References [showScheduleForm\(\)](#).

Referenced by [showScheduleForm\(\)](#).

8.33.3.6 showScoreForm()

```
String com.example.football_manager.controller.MatchViewController.showScoreForm (  
    @PathVariable Long id,  
    Model model)
```

Definition at line 90 of file [MatchViewController.java](#).

References [showScoreForm\(\)](#).

Referenced by [showScoreForm\(\)](#).

8.33.3.7 submitScoreForm()

```
String com.example.football_manager.controller.MatchViewController.submitScoreForm (  
    @PathVariable Long id,  
    @ModelAttribute("resultRequest") MatchResultRequestDTO resultRequest,  
    Model model,  
    RedirectAttributes redirectAttributes)
```

Definition at line 102 of file [MatchViewController.java](#).

References [submitScoreForm\(\)](#).

Referenced by [submitScoreForm\(\)](#).

8.33.3.8 updateMatch()

```
String com.example.football_manager.controller.MatchViewController.updateMatch (  
    @PathVariable Long id,  
    @ModelAttribute("matchRequest") MatchRequestDTO matchDTO)
```

Definition at line 83 of file [MatchViewController.java](#).

References [updateMatch\(\)](#).

Referenced by [updateMatch\(\)](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/MatchViewController.java](#)

8.34 com.example.football_manager.config.OpenApiConfig Class Reference

8.34.1 Detailed Description

Definition at line 24 of file [OpenApiConfig.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/config/OpenApiConfig.java](#)

8.35 com.example.football_manager.model.Player Class Reference

8.35.1 Detailed Description

Definition at line 22 of file [Player.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/model/Player.java](#)

8.36 com.example.football_manager.controller.PlayerController Class Reference

Public Member Functions

- [PlayerController](#) ([PlayerService](#) playerService)
- [ResponseEntity<?>](#) [createPlayer](#) ([@PathVariable](#) Long teamId, [@Valid](#) [@RequestBody](#) [PlayerRequestDTO](#) dto)
- [ResponseEntity<?>](#) [getPlayersByTeamId](#) ([@PathVariable](#) Long teamId)
- [ResponseEntity<?>](#) [updatePlayer](#) ([@PathVariable](#) Long teamId, [@PathVariable](#) Long playerId, [@Valid](#) [@RequestBody](#) [PlayerRequestDTO](#) dto)
- [ResponseEntity<?>](#) [deletePlayer](#) ([@PathVariable](#) Long teamId, [@PathVariable](#) Long playerId)

8.36.1 Detailed Description

Definition at line 22 of file [PlayerController.java](#).

8.36.2 Constructor & Destructor Documentation

8.36.2.1 PlayerController()

```
com.example.football_manager.controller.PlayerController.PlayerController (
    PlayerService playerService)
```

Definition at line 26 of file [PlayerController.java](#).

8.36.3 Member Function Documentation

8.36.3.1 createPlayer()

```
ResponseEntity<?> com.example.football_manager.controller.PlayerController.createPlayer (
    @PathVariable Long teamId,
    @Valid @RequestBody PlayerRequestDTO dto)
```

Definition at line 39 of file [PlayerController.java](#).

8.36.3.2 deletePlayer()

```
ResponseEntity<?> com.example.football_manager.controller.PlayerController.deletePlayer (
    @PathVariable Long teamId,
    @PathVariable Long playerId)
```

Definition at line 98 of file [PlayerController.java](#).

8.36.3.3 getPlayersByTeamId()

```
ResponseEntity<?> com.example.football_manager.controller.PlayerController.getPlayersByTeamId
(
    @PathVariable Long teamId)
```

Definition at line 59 of file [PlayerController.java](#).

8.36.3.4 updatePlayer()

```
ResponseEntity<?> com.example.football_manager.controller.PlayerController.updatePlayer (
    @PathVariable Long teamId,
    @PathVariable Long playerId,
    @Valid @RequestBody PlayerRequestDTO dto)
```

Definition at line 77 of file [PlayerController.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/PlayerController.java](#)

8.37 com.example.football_manager.model.PlayerPosition Enum Reference

Public Attributes

- [GOALKEEPER](#)
- [DEFENDER](#)
- [MIDFIELDER](#)
- [FORWARD](#)

8.37.1 Detailed Description

Definition at line 3 of file [PlayerPosition.java](#).

8.37.2 Member Data Documentation

8.37.2.1 DEFENDER

```
com.example.football_manager.model.PlayerPosition.DEFENDER
```

Definition at line 5 of file [PlayerPosition.java](#).

8.37.2.2 FORWARD

```
com.example.football_manager.model.PlayerPosition.FORWARD
```

Definition at line 7 of file [PlayerPosition.java](#).

8.37.2.3 GOALKEEPER

```
com.example.football_manager.model.PlayerPosition.GOALKEEPER
```

Definition at line 4 of file [PlayerPosition.java](#).

8.37.2.4 MIDFIELDER

```
com.example.football_manager.model.PlayerPosition.MIDFIELDER
```


Definition at line 6 of file [PlayerPosition.java](#).

The documentation for this enum was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/model/PlayerPosition.java](#)

8.38 com.example.football_manager.repository.PlayerRepository Interface Reference

Inheritance diagram for com.example.football_manager.repository.PlayerRepository:



Public Member Functions

- boolean [existsByTeamIdAndNumber](#) (Long teamId, Integer number)
- boolean [existsByTeamIdAndNumberAndIdNot](#) (Long teamId, Integer number, Long id)
- List< [Player](#) > [findByTeamIdOrderByNumberAsc](#) (Long teamId)
- java.util.Optional< [Player](#) > [findByIdAndTeamId](#) (Long id, Long teamId)

8.38.1 Detailed Description

Definition at line 10 of file [PlayerRepository.java](#).

8.38.2 Member Function Documentation

8.38.2.1 existsByTeamIdAndNumber()

```
boolean com.example.football_manager.repository.PlayerRepository.existsByTeamIdAndNumber (
    Long teamId,
    Integer number)
```

8.38.2.2 existsByTeamIdAndNumberAndIdNot()

```
boolean com.example.football_manager.repository.PlayerRepository.existsByTeamIdAndNumberAnd↵
IdNot (
    Long teamId,
    Integer number,
    Long id)
```

8.38.2.3 findByIdAndTeamId()

```
java.util.Optional< Player > com.example.football_manager.repository.PlayerRepository.findBy↵
IdAndTeamId (
    Long id,
    Long teamId)
```

8.38.2.4 findByTeamIdOrderByNumberAsc()

```
List< Player > com.example.football_manager.repository.PlayerRepository.findByTeamIdOrder↵
NumberAsc (
    Long teamId)
```

The documentation for this interface was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/repository/PlayerRepository.java](#)

8.39 com.example.football_manager.dto.PlayerRequestDTO Class Reference

Public Member Functions

- [PlayerRequestDTO](#) ()
- [PlayerRequestDTO](#) (String name, Integer number, [PlayerPosition](#) position)
- String [getName](#) ()
- void [setName](#) (String name)
- Integer [getNumber](#) ()
- void [setNumber](#) (Integer number)
- [PlayerPosition](#) [getPosition](#) ()
- void [setPosition](#) ([PlayerPosition](#) position)

8.39.1 Detailed Description

Definition at line 10 of file [PlayerRequestDTO.java](#).

8.39.2 Constructor & Destructor Documentation

8.39.2.1 [PlayerRequestDTO\(\)](#) [1/2]

```
com.example.football_manager.dto.PlayerRequestDTO.PlayerRequestDTO ()
```

Definition at line 26 of file [PlayerRequestDTO.java](#).

8.39.2.2 [PlayerRequestDTO\(\)](#) [2/2]

```
com.example.football_manager.dto.PlayerRequestDTO.PlayerRequestDTO (  
    String name,  
    Integer number,  
    PlayerPosition position)
```

Definition at line 29 of file [PlayerRequestDTO.java](#).

8.39.3 Member Function Documentation

8.39.3.1 [getName\(\)](#)

```
String com.example.football_manager.dto.PlayerRequestDTO.getName ()
```

Definition at line 35 of file [PlayerRequestDTO.java](#).

8.39.3.2 [getNumber\(\)](#)

```
Integer com.example.football_manager.dto.PlayerRequestDTO.getNumber ()
```

Definition at line 43 of file [PlayerRequestDTO.java](#).

8.39.3.3 getPosition()

[PlayerPosition](#) com.example.football_manager.dto.PlayerRequestDTO.getPosition ()

Definition at line 51 of file [PlayerRequestDTO.java](#).

8.39.3.4 setName()

```
void com.example.football_manager.dto.PlayerRequestDTO.setName (  
    String name)
```

Definition at line 39 of file [PlayerRequestDTO.java](#).

8.39.3.5 setNumber()

```
void com.example.football_manager.dto.PlayerRequestDTO.setNumber (  
    Integer number)
```

Definition at line 47 of file [PlayerRequestDTO.java](#).

8.39.3.6 setPosition()

```
void com.example.football_manager.dto.PlayerRequestDTO.setPosition (  
    PlayerPosition position)
```

Definition at line 55 of file [PlayerRequestDTO.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/dto/PlayerRequestDTO.java](#)

8.40 com.example.football_manager.service.PlayerService Class Reference

Public Member Functions

- [PlayerService](#) ([PlayerRepository](#) playerRepository, [TeamRepository](#) teamRepository)
- [Player](#) createPlayer (Long teamId, [PlayerRequestDTO](#) dto)
- List< [Player](#) > [getPlayersByTeamId](#) (Long teamId)
- [Player](#) [getPlayerByTeamId](#) (Long teamId, Long playerId)
- [Player](#) [updatePlayer](#) (Long teamId, Long playerId, [PlayerRequestDTO](#) dto)
- void [deletePlayer](#) (Long teamId, Long playerId)

8.40.1 Detailed Description

Definition at line 13 of file [PlayerService.java](#).

8.40.2 Constructor & Destructor Documentation

8.40.2.1 `PlayerService()`

```
com.example.football_manager.service.PlayerService.PlayerService (
    PlayerRepository playerRepository,
    TeamRepository teamRepository)
```

Definition at line 18 of file [PlayerService.java](#).

8.40.3 Member Function Documentation

8.40.3.1 `createPlayer()`

```
Player com.example.football_manager.service.PlayerService.createPlayer (
    Long teamId,
    PlayerRequestDTO dto)
```

Definition at line 23 of file [PlayerService.java](#).

8.40.3.2 `deletePlayer()`

```
void com.example.football_manager.service.PlayerService.deletePlayer (
    Long teamId,
    Long playerId)
```

Definition at line 107 of file [PlayerService.java](#).

8.40.3.3 `getPlayerByTeamId()`

```
Player com.example.football_manager.service.PlayerService.getPlayerByTeamId (
    Long teamId,
    Long playerId)
```

Definition at line 59 of file [PlayerService.java](#).

8.40.3.4 `getPlayersByTeamId()`

```
List< Player > com.example.football_manager.service.PlayerService.getPlayersByTeamId (
    Long teamId)
```

Definition at line 47 of file [PlayerService.java](#).

8.40.3.5 updatePlayer()

```
Player com.example.football_manager.service.PlayerService.updatePlayer (
    Long teamId,
    Long playerId,
    PlayerRequestDTO dto)
```

Definition at line 78 of file [PlayerService.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/service/PlayerService.java](#)

8.41 com.example.football_manager.dto.ProfileUpdatedDTO Class Reference

Public Member Functions

- boolean [isPasswordConfirmationValid](#) ()

8.41.1 Detailed Description

Definition at line 16 of file [ProfileUpdateDTO.java](#).

8.41.2 Member Function Documentation

8.41.2.1 isPasswordConfirmationValid()

```
boolean com.example.football_manager.dto.ProfileUpdatedDTO.isPasswordConfirmationValid ()
```

Definition at line 39 of file [ProfileUpdateDTO.java](#).

References [isPasswordConfirmationValid\(\)](#).

Referenced by [isPasswordConfirmationValid\(\)](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/dto/ProfileUpdatedDTO.java](#)

8.42 com.example.football_manager.controller.ProfileViewController Class Reference

Public Member Functions

- [ProfileViewController](#) ([UserService](#) userService)
- String [profilePage](#) (Model model, HttpSession session)
- String [updateProfile](#) (@Valid @ModelAttribute("profileForm") [ProfileUpdatedDTO](#) profileForm, BindingResult bindingResult, Model model, HttpSession session)

8.42.1 Detailed Description

Definition at line 18 of file [ProfileViewController.java](#).

8.42.2 Constructor & Destructor Documentation

8.42.2.1 ProfileViewController()

```
com.example.football_manager.controller.ProfileViewController.ProfileViewController (
    UserService userService)
```

Definition at line 22 of file [ProfileViewController.java](#).

8.42.3 Member Function Documentation

8.42.3.1 profilePage()

```
String com.example.football_manager.controller.ProfileViewController.profilePage (
    Model model,
    HttpSession session)
```

Definition at line 27 of file [ProfileViewController.java](#).

References [profilePage\(\)](#).

Referenced by [profilePage\(\)](#).

8.42.3.2 updateProfile()

```
String com.example.football_manager.controller.ProfileViewController.updateProfile (
    @Valid @ModelAttribute("profileForm") ProfileUpdatedDTO profileForm,
    BindingResult bindingResult,
    Model model,
    HttpSession session)
```

Definition at line 46 of file [ProfileViewController.java](#).

References [updateProfile\(\)](#).

Referenced by [updateProfile\(\)](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/ProfileViewController.java](#)

8.43 com.example.football_manager.dto.RegisterDTO Class Reference

Public Member Functions

- String [getUsername](#) ()
- void [setUsername](#) (String username)
- String [getEmail](#) ()
- void [setEmail](#) (String email)
- String [getPassword](#) ()
- void [setPassword](#) (String password)
- Boolean [getIsAdmin](#) ()
- void [setIsAdmin](#) (Boolean isAdmin)

8.43.1 Detailed Description

Definition at line 8 of file [RegisterDTO.java](#).

8.43.2 Member Function Documentation

8.43.2.1 getEmail()

```
String com.example.football_manager.dto.RegisterDTO.getEmail ()
```

Definition at line 31 of file [RegisterDTO.java](#).

8.43.2.2 getIsAdmin()

```
Boolean com.example.football_manager.dto.RegisterDTO.getIsAdmin ()
```

Definition at line 37 of file [RegisterDTO.java](#).

8.43.2.3 getPassword()

```
String com.example.football_manager.dto.RegisterDTO.getPassword ()
```

Definition at line 34 of file [RegisterDTO.java](#).

8.43.2.4 getUsername()

```
String com.example.football_manager.dto.RegisterDTO.getUsername ()
```

Definition at line 28 of file [RegisterDTO.java](#).

8.43.2.5 setEmail()

```
void com.example.football_manager.dto.RegisterDTO.setEmail (  
    String email)
```

Definition at line 32 of file [RegisterDTO.java](#).

8.43.2.6 setIsAdmin()

```
void com.example.football_manager.dto.RegisterDTO.setIsAdmin (  
    Boolean isAdmin)
```

Definition at line 38 of file [RegisterDTO.java](#).

8.43.2.7 setPassword()

```
void com.example.football_manager.dto.RegisterDTO.setPassword (  
    String password)
```

Definition at line 35 of file [RegisterDTO.java](#).

8.43.2.8 setUsername()

```
void com.example.football_manager.dto.RegisterDTO.setUsername (  
    String username)
```

Definition at line 29 of file [RegisterDTO.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/dto/RegisterDTO.java](#)

8.44 com.example.football_manager.config.SecurityConfig Class Reference

Public Member Functions

- SecurityFilterChain [filterChain](#) (HttpSecurity http) throws Exception
- PasswordEncoder [passwordEncoder](#) ()

8.44.1 Detailed Description

Definition at line 11 of file [SecurityConfig.java](#).

8.44.2 Member Function Documentation

8.44.2.1 filterChain()

```
SecurityFilterChain com.example.football_manager.config.SecurityConfig.filterChain (
    HttpSecurity http) throws Exception
```

Definition at line 14 of file [SecurityConfig.java](#).

8.44.2.2 passwordEncoder()

```
PasswordEncoder com.example.football_manager.config.SecurityConfig.passwordEncoder ()
```

Definition at line 25 of file [SecurityConfig.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/config/SecurityConfig.java](#)

8.45 com.example.football_manager.model.Team Class Reference

Public Member Functions

- [Team](#) (Long id, String name, String logoUrl, [Country](#) country)

8.45.1 Detailed Description

Definition at line 19 of file [Team.java](#).

8.45.2 Constructor & Destructor Documentation

8.45.2.1 Team()

```
com.example.football_manager.model.Team.Team (
    Long id,
    String name,
    String logoUrl,
    Country country)
```

Definition at line 42 of file [Team.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/model/Team.java](#)

8.46 com.example.football_manager.controller.TeamController Class Reference

Public Member Functions

- [TeamController](#) ([TeamService](#) teamService)
- [ResponseEntity](#)< [Team](#) > [createTeam](#) (@Valid @RequestBody [TeamRequestDTO](#) dto)
- [ResponseEntity](#)< [Team](#) > [updateTeam](#) (@PathVariable Long id, @Valid @RequestBody [TeamRequestDTO](#) dto)
- [ResponseEntity](#)< Void > [deleteTeam](#) (@PathVariable Long id)
- [ResponseEntity](#)< [Team](#) > [getTeamById](#) (@PathVariable Long id)
- [ResponseEntity](#)< List< [Team](#) > > [getTeamsContainingName](#) (@RequestParam String name)
- [ResponseEntity](#)< List< [Team](#) > > [getAllTeams](#) ()

8.46.1 Detailed Description

Definition at line 23 of file [TeamController.java](#).

8.46.2 Constructor & Destructor Documentation

8.46.2.1 TeamController()

```
com.example.football_manager.controller.TeamController.TeamController (  
    TeamService teamService)
```

Definition at line 27 of file [TeamController.java](#).

8.46.3 Member Function Documentation

8.46.3.1 createTeam()

```
ResponseEntity< Team > com.example.football_manager.controller.TeamController.createTeam (  
    @Valid @RequestBody TeamRequestDTO dto)
```

Definition at line 45 of file [TeamController.java](#).

8.46.3.2 deleteTeam()

```
ResponseEntity< Void > com.example.football_manager.controller.TeamController.deleteTeam (  
    @PathVariable Long id)
```

Definition at line 80 of file [TeamController.java](#).

8.46.3.3 getAllTeams()

```
ResponseEntity< List< Team > > com.example.football_manager.controller.TeamController.get↔  
AllTeams ()
```

Definition at line 118 of file [TeamController.java](#).

8.46.3.4 getTeamById()

```
ResponseEntity< Team > com.example.football_manager.controller.TeamController.getTeamById (
    @PathVariable Long id)
```

Definition at line 94 of file [TeamController.java](#).

8.46.3.5 getTeamsContainingName()

```
ResponseEntity< List< Team > > com.example.football_manager.controller.TeamController.getTeamsContainingName (
    @RequestParam String name)
```

Definition at line 106 of file [TeamController.java](#).

8.46.3.6 updateTeam()

```
ResponseEntity< Team > com.example.football_manager.controller.TeamController.updateTeam (
    @PathVariable Long id,
    @Valid @RequestBody TeamRequestDTO dto)
```


Definition at line 65 of file [TeamController.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/TeamController.java](#)

8.47 com.example.football_manager.repository.TeamRepository Interface Reference

Inheritance diagram for com.example.football_manager.repository.TeamRepository:



Public Member Functions

- List< Team > [findByNameContainingIgnoreCase](#) (String name)

8.47.1 Detailed Description

Definition at line 10 of file [TeamRepository.java](#).

8.47.2 Member Function Documentation

8.47.2.1 `findByNameContainingIgnoreCase()`

```
List< Team > com.example.football_manager.repository.TeamRepository.findByNameContaining↔  
IgnoreCase (   
    String name)
```

The documentation for this interface was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/repository/TeamRepository.java](#)

8.48 `com.example.football_manager.dto.TeamRequestDTO` Class Reference

Public Member Functions

- [TeamRequestDTO](#) ()
- [TeamRequestDTO](#) (String name, String logoUrl, Long countryId)
- String [getName](#) ()
- void [setName](#) (String name)
- String [getLogoUrl](#) ()
- void [setLogoUrl](#) (String logoUrl)
- Long [getCountryId](#) ()
- void [setCountryId](#) (Long countryId)

8.48.1 Detailed Description

Definition at line 8 of file [TeamRequestDTO.java](#).

8.48.2 Constructor & Destructor Documentation

8.48.2.1 `TeamRequestDTO()` [1/2]

```
com.example.football_manager.dto.TeamRequestDTO.TeamRequestDTO ()
```

Definition at line 23 of file [TeamRequestDTO.java](#).

8.48.2.2 `TeamRequestDTO()` [2/2]

```
com.example.football_manager.dto.TeamRequestDTO.TeamRequestDTO (   
    String name,  
    String logoUrl,  
    Long countryId)
```

Definition at line 26 of file [TeamRequestDTO.java](#).

8.48.3 Member Function Documentation

8.48.3.1 getCountryId()

```
Long com.example.football_manager.dto.TeamRequestDTO.getCountryId ()
```

Definition at line 48 of file [TeamRequestDTO.java](#).

8.48.3.2 getLogoUrl()

```
String com.example.football_manager.dto.TeamRequestDTO.getLogoUrl ()
```

Definition at line 40 of file [TeamRequestDTO.java](#).

8.48.3.3 getName()

```
String com.example.football_manager.dto.TeamRequestDTO.getName ()
```

Definition at line 32 of file [TeamRequestDTO.java](#).

8.48.3.4 setCountryId()

```
void com.example.football_manager.dto.TeamRequestDTO.setCountryId (  
    Long countryId)
```

Definition at line 52 of file [TeamRequestDTO.java](#).

Referenced by [com.example.football_manager.controller.TeamViewController.showEditTeamForm\(\)](#).

8.48.3.5 setLogoUrl()

```
void com.example.football_manager.dto.TeamRequestDTO.setLogoUrl (  
    String logoUrl)
```

Definition at line 44 of file [TeamRequestDTO.java](#).

Referenced by [com.example.football_manager.controller.TeamViewController.showEditTeamForm\(\)](#).

8.48.3.6 setName()

```
void com.example.football_manager.dto.TeamRequestDTO.setName (  
    String name)
```

Definition at line 36 of file [TeamRequestDTO.java](#).

Referenced by [com.example.football_manager.controller.TeamViewController.showEditTeamForm\(\)](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/dto/TeamRequestDTO.java](#)

8.49 com.example.football_manager.service.TeamService Class Reference

Public Member Functions

- [TeamService](#) ([TeamRepository](#) teamRepository, [CountryRepository](#) countryRepository)
- [Team](#) [createTeam](#) ([TeamRequestDTO](#) dto)
- [Team](#) [updateTeam](#) (Long id, [TeamRequestDTO](#) dto)
- void [deleteTeam](#) (Long id)
- Optional< [Team](#) > [getTeamById](#) (Long id)
- List< [Team](#) > [getTeamsContainingName](#) (String name)
- List< [Team](#) > [getAllTeams](#) ()

8.49.1 Detailed Description

Definition at line 15 of file [TeamService.java](#).

8.49.2 Constructor & Destructor Documentation

8.49.2.1 TeamService()

```
com.example.football_manager.service.TeamService.TeamService (  
    TeamRepository teamRepository,  
    CountryRepository countryRepository)
```

Definition at line 20 of file [TeamService.java](#).

8.49.3 Member Function Documentation

8.49.3.1 createTeam()

```
Team com.example.football_manager.service.TeamService.createTeam (  
    TeamRequestDTO dto)
```

Definition at line 25 of file [TeamService.java](#).

8.49.3.2 deleteTeam()

```
void com.example.football_manager.service.TeamService.deleteTeam (  
    Long id)
```

Definition at line 51 of file [TeamService.java](#).

8.49.3.3 getAllTeams()

```
List< Team > com.example.football_manager.service.TeamService.getAllTeams ()
```

Definition at line 69 of file [TeamService.java](#).

8.49.3.4 getTeamById()

```
Optional< Team > com.example.football_manager.service.TeamService.getTeamById (
    Long id)
```

Definition at line 58 of file [TeamService.java](#).

8.49.3.5 getTeamsContainingName()

```
List< Team > com.example.football_manager.service.TeamService.getTeamsContainingName (
    String name)
```

Definition at line 62 of file [TeamService.java](#).

8.49.3.6 updateTeam()

```
Team com.example.football_manager.service.TeamService.updateTeam (
    Long id,
    TeamRequestDTO dto)
```

Definition at line 37 of file [TeamService.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/service/TeamService.java](#)

8.50 com.example.football_manager.controller.TeamViewController Class Reference

Public Member Functions

- String [teamsPage](#) (Model model, HttpSession session)
- String [teamDetailsPage](#) (@PathVariable Long id, Model model, HttpSession session)
- String [showAddTeamForm](#) (Model model)
- String [createTeam](#) (@ModelAttribute [TeamRequestDTO](#) teamDTO)
- String [showEditTeamForm](#) (@PathVariable Long id, Model model)
- String [updateTeam](#) (@PathVariable Long id, @ModelAttribute [TeamRequestDTO](#) teamDTO)
- String [deleteTeam](#) (@PathVariable Long id)

8.50.1 Detailed Description

Definition at line 22 of file [TeamViewController.java](#).

8.50.2 Member Function Documentation

8.50.2.1 createTeam()

```
String com.example.football_manager.controller.TeamViewController.createTeam (  
    @ModelAttribute TeamRequestDTO teamDTO)
```

Definition at line 84 of file [TeamViewController.java](#).

References [createTeam\(\)](#).

Referenced by [createTeam\(\)](#).

8.50.2.2 deleteTeam()

```
String com.example.football_manager.controller.TeamViewController.deleteTeam (  
    @PathVariable Long id)
```

Definition at line 118 of file [TeamViewController.java](#).

References [deleteTeam\(\)](#).

Referenced by [deleteTeam\(\)](#).

8.50.2.3 showAddTeamForm()

```
String com.example.football_manager.controller.TeamViewController.showAddTeamForm (  
    Model model)
```

Definition at line 76 of file [TeamViewController.java](#).

References [showAddTeamForm\(\)](#).

Referenced by [showAddTeamForm\(\)](#).

8.50.2.4 showEditTeamForm()

```
String com.example.football_manager.controller.TeamViewController.showEditTeamForm (  
    @PathVariable Long id,  
    Model model)
```

Definition at line 91 of file [TeamViewController.java](#).

References [com.example.football_manager.dto.TeamRequestDTO.setCountryId\(\)](#), [com.example.football_manager.dto.TeamRequestDTO.setName\(\)](#), and [showEditTeamForm\(\)](#).

Referenced by [showEditTeamForm\(\)](#).

8.50.2.5 teamDetailsPage()

```
String com.example.football_manager.controller.TeamViewController.teamDetailsPage (  
    @PathVariable Long id,  
    Model model,  
    HttpSession session)
```

Definition at line 60 of file [TeamViewController.java](#).

References [teamDetailsPage\(\)](#).

Referenced by [teamDetailsPage\(\)](#).

8.50.2.6 teamsPage()

```
String com.example.football_manager.controller.TeamViewController.teamsPage (  
    Model model,  
    HttpSession session)
```

Definition at line 40 of file [TeamViewController.java](#).

References [teamsPage\(\)](#).

Referenced by [teamsPage\(\)](#).

8.50.2.7 updateTeam()

```
String com.example.football_manager.controller.TeamViewController.updateTeam (  
    @PathVariable Long id,  
    @ModelAttribute TeamRequestDTO teamDTO)
```

Definition at line 111 of file [TeamViewController.java](#).

References [updateTeam\(\)](#).

Referenced by [updateTeam\(\)](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/controller/TeamViewController.java](#)

8.51 com.example.football_manager.model.User Class Reference

8.51.1 Detailed Description


Definition at line 15 of file [User.java](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/model/User.java](#)

8.52 com.example.football_manager.repository.UserRepository Interface Reference

Inheritance diagram for com.example.football_manager.repository.UserRepository:



Public Member Functions

- Optional< [User](#) > [findByUsername](#) (String username)
- Optional< [User](#) > [findByEmail](#) (String email)
- Optional< [User](#) > [findWithFavouriteTeamsById](#) (Long id)
- boolean [existsByUsername](#) (String username)
- boolean [existsByEmail](#) (String email)
- boolean [existsByUsernameAndIdNot](#) (String username, Long id)
- boolean [existsByEmailAndIdNot](#) (String email, Long id)

8.52.1 Detailed Description

Definition at line 11 of file [UserRepository.java](#).

8.52.2 Member Function Documentation

8.52.2.1 existsByEmail()

```
boolean com.example.football_manager.repository.UserRepository.existsByEmail (
    String email)
```

References [existsByEmail\(\)](#).

Referenced by [existsByEmail\(\)](#).

8.52.2.2 existsByEmailAndIdNot()

```
boolean com.example.football_manager.repository.UserRepository.existsByEmailAndIdNot (
    String email,
    Long id)
```

References [existsByEmailAndIdNot\(\)](#).

Referenced by [existsByEmailAndIdNot\(\)](#).

8.52.2.3 existsByUsername()

```
boolean com.example.football_manager.repository.UserRepository.existsByUsername (
    String username)
```

References [existsByUsername\(\)](#).

Referenced by [existsByUsername\(\)](#).

8.52.2.4 existsByUsernameAndIdNot()

```
boolean com.example.football_manager.repository.UserRepository.existsByUsernameAndIdNot (
    String username,
    Long id)
```

References [existsByUsernameAndIdNot\(\)](#).

Referenced by [existsByUsernameAndIdNot\(\)](#).

8.52.2.5 findByEmail()

```
Optional< User > com.example.football_manager.repository.UserRepository.findByEmail (
    String email)
```

8.52.2.6 findByUsername()

```
Optional< User > com.example.football_manager.repository.UserRepository.findByUsername (
    String username)
```

8.52.2.7 findWithFavouriteTeamsById()

```
Optional< User > com.example.football_manager.repository.UserRepository.findWithFavourite↵
TeamsById (
    Long id)
```

References [findWithFavouriteTeamsById\(\)](#).

Referenced by [findWithFavouriteTeamsById\(\)](#).

The documentation for this interface was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/repository/UserRepository.java](#)

8.53 com.example.football_manager.service.UserService Class Reference

Public Member Functions

- [User registerUser](#) (String username, String email, String rawPassword, Boolean isAdmin)
- [User login](#) (String username, String rawPassword)
- [User getUserById](#) (Long id)
- [User getUserByUsername](#) (String username)
- [User addFavouriteTeam](#) (Long userId, Long teamId)
- [User removeFavouriteTeam](#) (Long userId, Long teamId)
- Set< Long > [getFavouriteTeamIdsByUserId](#) (Long userId)
- [User getUserProfile](#) (Long userId)
- [User updateProfile](#) (Long userId, String username, String email, String currentPassword, String newPassword, String confirmNewPassword)

8.53.1 Detailed Description

Definition at line 18 of file [UserService.java](#).

8.53.2 Member Function Documentation

8.53.2.1 addFavouriteTeam()

```
User com.example.football_manager.service.UserService.addFavouriteTeam (
    Long userId,
    Long teamId)
```

Definition at line 68 of file [UserService.java](#).

References [getUserById\(\)](#).

8.53.2.2 getFavouriteTeamIdsByUserId()

```
Set< Long > com.example.football_manager.service.UserService.getFavouriteTeamIdsByUserId (
    Long userId)
```

Definition at line 106 of file [UserService.java](#).

References [getUserById\(\)](#).

8.53.2.3 getUserById()

```
User com.example.football_manager.service.UserService.getUserById (
    Long id)
```

Definition at line 58 of file [UserService.java](#).

Referenced by [addFavouriteTeam\(\)](#), [getFavouriteTeamIdsByUserId\(\)](#), [removeFavouriteTeam\(\)](#), and [updateProfile\(\)](#).

8.53.2.4 getUserByUsername()

```
User com.example.football_manager.service.UserService.getUserByUsername (
    String username)
```

Definition at line 63 of file [UserService.java](#).

8.53.2.5 getUserProfile()

```
User com.example.football_manager.service.UserService.getUserProfile (
    Long userId)
```

Definition at line 122 of file [UserService.java](#).

8.53.2.6 login()

```
User com.example.football_manager.service.UserService.login (
    String username,
    String rawPassword)
```

Definition at line 47 of file [UserService.java](#).

8.53.2.7 registerUser()

```
User com.example.football_manager.service.UserService.registerUser (
    String username,
    String email,
    String rawPassword,
    Boolean isAdmin)
```

Definition at line 29 of file [UserService.java](#).

8.53.2.8 removeFavouriteTeam()

```
User com.example.football_manager.service.UserService.removeFavouriteTeam (
    Long userId,
    Long teamId)
```

Definition at line 86 of file [UserService.java](#).

References [getUserById\(\)](#).

8.53.2.9 updateProfile()

```
User com.example.football_manager.service.UserService.updateProfile (
    Long userId,
    String username,
    String email,
    String currentPassword,
    String newPassword,
    String confirmNewPassword)
```

Definition at line 127 of file [UserService.java](#).

References [getUserById\(\)](#).

The documentation for this class was generated from the following file:

- [Football_Manager/src/main/java/com/example/football_manager/service/UserService.java](#)

Chapter 9

File Documentation

9.1 docs/doxygen_mainpage.md File Reference

9.2 Football_Manager/src/main/java/com/example/football_↵ manager/config/AdminSecurityFilter.java File Reference

```
import jakarta.servlet.Filter;  
import jakarta.servlet.FilterChain;  
import jakarta.servlet.ServletException;  
import jakarta.servlet.ServletRequest;  
import jakarta.servlet.ServletResponse;  
import jakarta.servlet.http.HttpServletRequest;  
import jakarta.servlet.http.HttpServletResponse;  
import jakarta.servlet.http.HttpSession;  
import org.springframework.stereotype.Component;  
import java.io.IOException;
```

Classes

- class [com.example.football_manager.config.AdminSecurityFilter](#)

Packages

- package [com.example.football_manager.config](#)

9.3 AdminSecurityFilter.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.config;
00002
00003 import jakarta.servlet.Filter;
00004 import jakarta.servlet.FilterChain;
00005 import jakarta.servlet.ServletException;
00006 import jakarta.servlet.HttpServletRequest;
00007 import jakarta.servlet.HttpServletResponse;
00008 import jakarta.servlet.http.HttpServletRequest;
00009 import jakarta.servlet.http.HttpServletResponse;
00010 import jakarta.servlet.http.HttpSession;
00011 import org.springframework.stereotype.Component;
00012
00013 import java.io.IOException;
00014
00015 @Component
00016 public class AdminSecurityFilter implements Filter {
00017
00018     @Override
00019     public void doFilter(ServletRequest request, ServletResponse response, FilterChain chain)
00020         throws IOException, ServletException {
00021
00022         HttpServletRequest req = (HttpServletRequest) request;
00023         HttpServletResponse res = (HttpServletResponse) response;
00024
00025         String uri = req.getRequestURI();
00026
00027         boolean isProtectedPath = uri.startsWith("/admin") ||
00028             uri.startsWith("/teams/add") ||
00029             uri.startsWith("/teams/edit") ||
00030             uri.startsWith("/teams/delete");
00031
00032         if (isProtectedPath) {
00033             HttpSession session = req.getSession(false);
00034
00035             Boolean isAdmin = (session != null) ? (Boolean) session.getAttribute("isAdmin") : null;
00036
00037             if (isAdmin == null || !isAdmin) {
00038                 res.sendRedirect("/teams");
00039                 return;
00040             }
00041         }
00042
00043         chain.doFilter(request, response);
00044     }
00045 }

```

9.4 Football_Manager/src/main/java/com/example/football_ manager/config/LocaleConfig.java File Reference

```

import java.util.Locale;
import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;
import org.springframework.web.servlet.LocaleResolver;
import org.springframework.web.servlet.config.annotation.InterceptorRegistry;
import org.springframework.web.servlet.config.annotation.WebMvcConfigurer;
import org.springframework.web.servlet.i18n.CookieLocaleResolver;
import org.springframework.web.servlet.i18n.LocaleChangeInterceptor;

```

Classes

- class [com.example.football_manager.config.LocaleConfig](#)

Packages

- package [com.example.football_manager.config](#)

9.5 LocaleConfig.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.config;
00002
00003 import java.util.Locale;
00004 import org.springframework.context.annotation.Bean;
00005 import org.springframework.context.annotation.Configuration;
00006 import org.springframework.web.servlet.LocaleResolver;
00007 import org.springframework.web.servlet.config.annotation.InterceptorRegistry;
00008 import org.springframework.web.servlet.config.annotation.WebMvcConfigurer;
00009 import org.springframework.web.servlet.i18n.CookieLocaleResolver;
00010 import org.springframework.web.servlet.i18n.LocaleChangeInterceptor;
00011
00012 @Configuration
00013 public class LocaleConfig implements WebMvcConfigurer {
00014
00015     @Bean
00016     public LocaleResolver localeResolver() {
00017         CookieLocaleResolver resolver = new CookieLocaleResolver();
00018         resolver.setDefaultLocale(new Locale("es"));
00019         return resolver;
00020     }
00021
00022     @Bean
00023     public LocaleChangeInterceptor localeChangeInterceptor() {
00024         LocaleChangeInterceptor interceptor = new LocaleChangeInterceptor();
00025         interceptor.setParamName("lang");
00026         return interceptor;
00027     }
00028
00029     @Override
00030     public void addInterceptors(InterceptorRegistry registry) {
00031         registry.addInterceptor(localeChangeInterceptor());
00032     }
00033 }

```

9.6 Football_Manager/src/main/java/com/example/football_↵ manager/config/OpenApiConfig.java File Reference

```

import io.swagger.v3.oas.annotations.OpenAPIDefinition;
import io.swagger.v3.oas.annotations.info.Info;
import io.swagger.v3.oas.annotations.tags.Tag;
import org.springframework.context.annotation.Configuration;

```

Classes

- class [com.example.football_manager.config.OpenApiConfig](#)

Packages

- package [com.example.football_manager.config](#)

9.7 OpenApiConfig.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.config;
00002
00003 import io.swagger.v3.oas.annotations.OpenAPIDefinition;
00004 import io.swagger.v3.oas.annotations.info.Info;
00005 import io.swagger.v3.oas.annotations.tags.Tag;
00006 import org.springframework.context.annotation.Configuration;
00007
00008 @OpenAPIDefinition(
00009     info = @Info(
00010         title = "Football Manager API",
00011         version = "v1",
00012         description = "REST API for managing teams, matches, competitions, countries, and user
authentication."
00013     ),
00014     tags = {
00015         @Tag(name = "Auth", description = "User registration and login"),
00016         @Tag(name = "Teams", description = "Create, update, search, and delete teams"),
00017         @Tag(name = "Matches", description = "Schedule matches and register results"),
00018         @Tag(name = "Competitions", description = "Manage competitions"),
00019         @Tag(name = "Countries", description = "Manage countries"),
00020         @Tag(name = "Favourites", description = "Manage the current user's favourite teams")
00021     }
00022 )
00023 @Configuration
00024 public class OpenApiConfig {
00025 }
00026

```

9.8 Football_Manager/src/main/java/com/example/football_manager/config/SecurityConfig.java File Reference

```

import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;
import org.springframework.security.config.annotation.web.builders.HttpSecurity;
import org.springframework.security.config.annotation.web.configurers.HttpSecurity;
import org.springframework.security.crypto.bcrypt.BCryptPasswordEncoder;
import org.springframework.security.crypto.password.PasswordEncoder;
import org.springframework.security.web.SecurityFilterChain;

```

Classes

- class [com.example.football_manager.config.SecurityConfig](#)

Packages

- package [com.example.football_manager.config](#)

9.9 SecurityConfig.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.config;
00002
00003 import org.springframework.context.annotation.Bean;
00004 import org.springframework.context.annotation.Configuration;
00005 import org.springframework.security.config.annotation.web.builders.HttpSecurity;
00006 import org.springframework.security.crypto.bcrypt.BCryptPasswordEncoder;

```

```

00007 import org.springframework.security.crypto.password.PasswordEncoder;
00008 import org.springframework.security.web.SecurityFilterChain;
00009
00010 @Configuration
00011 public class SecurityConfig {
00012
00013     @Bean
00014     public SecurityFilterChain filterChain(HttpSecurity http) throws Exception {
00015         http
00016             .csrf(csrf -> csrf.ignoringRequestMatchers("/auth/**", "/api/**"))
00017             .authorizeHttpRequests(auth -> auth
00018                 .anyRequest().permitAll()
00019             );
00020
00021         return http.build();
00022     }
00023
00024     @Bean
00025     public PasswordEncoder passwordEncoder() {
00026         return new BCryptPasswordEncoder();
00027     }
00028 }
00029

```

9.10 Football_Manager/src/main/java/com/example/football_manager/controller/AdminCountryViewController.java File Reference

```

import com.example.football_manager.dto.CountryRequestDTO;
import com.example.football_manager.service.CountryService;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.*;

```

Classes

- class [com.example.football_manager.controller.AdminCountryViewController](#)

Packages

- package [com.example.football_manager.controller](#)

9.11 AdminCountryViewController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.dto.CountryRequestDTO;
00004 import com.example.football_manager.service.CountryService;
00005 import org.springframework.stereotype.Controller;
00006 import org.springframework.ui.Model;
00007 import org.springframework.web.bind.annotation.*;
00008
00009 @Controller
00010 public class AdminCountryViewController {
00011
00012     private final CountryService countryService;
00013
00014     public AdminCountryViewController(CountryService countryService) {
00015         this.countryService = countryService;
00016     }

```

```

00017     @GetMapping("/admin/countries")
00018     public String countriesPage(Model model) {
00019         model.addAttribute("countries", countryService.getAllCountries());
00020         model.addAttribute("countryRequest", new CountryRequestDTO());
00021         return "admin-countries";
00022     }
00023
00024     @PostMapping("/admin/countries")
00025     public String createCountry(@ModelAttribute CountryRequestDTO countryRequest) {
00026         countryService.createCountry(countryRequest);
00027         return "redirect:/admin/countries";
00028     }
00029
00030     @PostMapping("/admin/countries/delete/{id}")
00031     public String deleteCountry(@PathVariable Long id) {
00032         countryService.deleteCountry(id);
00033         return "redirect:/admin/countries";
00034     }
00035 }
00036

```

9.12 Football_Manager/src/main/java/com/example/football_↵ manager/controller/AdminPlayerViewController.java File Reference

```

import com.example.football_manager.dto.PlayerRequestDTO;
import com.example.football_manager.model.Player;
import com.example.football_manager.model.PlayerPosition;
import com.example.football_manager.model.Team;
import com.example.football_manager.service.PlayerService;
import com.example.football_manager.service.TeamService;
import jakarta.validation.Valid;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.validation.BindingResult;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.PathVariable;
import org.springframework.web.bind.annotation.PostMapping;
import org.springframework.web.servlet.mvc.support.RedirectAttributes;

```

Classes

- class [com.example.football_manager.controller.AdminPlayerViewController](#)

Packages

- package [com.example.football_manager.controller](#)

9.13 AdminPlayerViewController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.dto.PlayerRequestDTO;
00004 import com.example.football_manager.model.Player;
00005 import com.example.football_manager.model.PlayerPosition;
00006 import com.example.football_manager.model.Team;

```

```

00007 import com.example.football_manager.service.PlayerService;
00008 import com.example.football_manager.service.TeamService;
00009 import jakarta.validation.Valid;
00010 import org.springframework.stereotype.Controller;
00011 import org.springframework.ui.Model;
00012 import org.springframework.validation.BindingResult;
00013 import org.springframework.web.bind.annotation.GetMapping;
00014 import org.springframework.web.bind.annotation.ModelAttribute;
00015 import org.springframework.web.bind.annotation.PathVariable;
00016 import org.springframework.web.bind.annotation.PostMapping;
00017 import org.springframework.web.servlet.mvc.support.RedirectAttributes;
00018
00019 @Controller
00020 public class AdminPlayerViewController {
00021
00022     private final TeamService teamService;
00023     private final PlayerService playerService;
00024
00025     public AdminPlayerViewController(TeamService teamService, PlayerService playerService) {
00026         this.teamService = teamService;
00027         this.playerService = playerService;
00028     }
00029
00030     @GetMapping("/admin/players")
00031     public String managePlayersLanding(Model model) {
00032         return "redirect:/admin/manage-teams";
00033     }
00034
00035     @GetMapping("/admin/teams/{teamId}/players")
00036     public String manageTeamPlayers(@PathVariable Long teamId, Model model, RedirectAttributes
redirectAttributes) {
00037         Team team = teamService.getTeamById(teamId).orElse(null);
00038         if (team == null) {
00039             redirectAttributes.addFlashAttribute("errorMessage", "Team not found.");
00040             return "redirect:/admin/manage-teams";
00041         }
00042
00043         if (!model.containsAttribute("playerRequest")) {
00044             model.addAttribute("playerRequest", new PlayerRequestDTO());
00045         }
00046
00047         populateTeamPlayersModel(model, team);
00048         return "admin-team-players";
00049     }
00050
00051     @PostMapping("/admin/teams/{teamId}/players")
00052     public String createPlayer(
00053         @PathVariable Long teamId,
00054         @Valid @ModelAttribute("playerRequest") PlayerRequestDTO playerRequest,
00055         BindingResult bindingResult,
00056         Model model,
00057         RedirectAttributes redirectAttributes) {
00058
00059         Team team = teamService.getTeamById(teamId).orElse(null);
00060         if (team == null) {
00061             redirectAttributes.addFlashAttribute("errorMessage", "Team not found.");
00062             return "redirect:/admin/manage-teams";
00063         }
00064
00065         if (bindingResult.hasErrors()) {
00066             populateTeamPlayersModel(model, team);
00067             return "admin-team-players";
00068         }
00069
00070         try {
00071             playerService.createPlayer(teamId, playerRequest);
00072             redirectAttributes.addFlashAttribute("successMessage", "Player created successfully.");
00073             return "redirect:/admin/teams/" + teamId + "/players";
00074         } catch (IllegalArgumentException ex) {
00075             model.addAttribute("errorMessage", ex.getMessage());
00076             populateTeamPlayersModel(model, team);
00077             return "admin-team-players";
00078         }
00079     }
00080
00081     @GetMapping("/admin/teams/{teamId}/players/edit/{playerId}")
00082     public String showEditPlayerForm(
00083         @PathVariable Long teamId,
00084         @PathVariable Long playerId,
00085         Model model,
00086         RedirectAttributes redirectAttributes) {
00087
00088         Team team = teamService.getTeamById(teamId).orElse(null);
00089         if (team == null) {
00090             redirectAttributes.addFlashAttribute("errorMessage", "Team not found.");
00091             return "redirect:/admin/manage-teams";
00092         }

```

```

00093
00094
00095         try {
00096             Player player = playerService.getPlayerByTeamId(teamId, playerId);
00097             if (!model.containsAttribute("playerRequest")) {
00098                 PlayerRequestDTO playerRequest = new PlayerRequestDTO(
00099                     player.getName(),
00100                     player.getNumber(),
00101                     player.getPosition()
00102                 );
00103                 model.addAttribute("playerRequest", playerRequest);
00104             }
00105             catch (IllegalArgumentException ex) {
00106                 redirectAttributes.addFlashAttribute("errorMessage", ex.getMessage());
00107                 return "redirect:/admin/teams/" + teamId + "/players";
00108             }
00109
00110             model.addAttribute("team", team);
00111             model.addAttribute("playerId", playerId);
00112             model.addAttribute("positions", PlayerPosition.values());
00113             return "edit-player";
00114         }
00115
00116 @PostMapping("/admin/teams/{teamId}/players/edit/{playerId}")
00117 public String updatePlayer(
00118     @PathVariable Long teamId,
00119     @PathVariable Long playerId,
00120     @Valid @ModelAttribute("playerRequest") PlayerRequestDTO playerRequest,
00121     BindingResult bindingResult,
00122     Model model,
00123     RedirectAttributes redirectAttributes) {
00124
00125     Team team = teamService.getTeamById(teamId).orElse(null);
00126     if (team == null) {
00127         redirectAttributes.addFlashAttribute("errorMessage", "Team not found.");
00128         return "redirect:/admin/manage-teams";
00129     }
00130
00131     if (bindingResult.hasErrors()) {
00132         model.addAttribute("team", team);
00133         model.addAttribute("playerId", playerId);
00134         model.addAttribute("positions", PlayerPosition.values());
00135         return "edit-player";
00136     }
00137
00138     try {
00139         playerService.updatePlayer(teamId, playerId, playerRequest);
00140         redirectAttributes.addFlashAttribute("successMessage", "Player updated successfully.");
00141         return "redirect:/admin/teams/" + teamId + "/players";
00142     } catch (IllegalArgumentException ex) {
00143         model.addAttribute("team", team);
00144         model.addAttribute("playerId", playerId);
00145         model.addAttribute("positions", PlayerPosition.values());
00146         model.addAttribute("errorMessage", ex.getMessage());
00147         return "edit-player";
00148     }
00149
00150 @PostMapping("/admin/teams/{teamId}/players/delete/{playerId}")
00151 public String deletePlayer(
00152     @PathVariable Long teamId,
00153     @PathVariable Long playerId,
00154     RedirectAttributes redirectAttributes) {
00155
00156     try {
00157         playerService.deletePlayer(teamId, playerId);
00158         redirectAttributes.addFlashAttribute("successMessage", "Player deleted successfully.");
00159     } catch (IllegalArgumentException ex) {
00160         redirectAttributes.addFlashAttribute("errorMessage", ex.getMessage());
00161     }
00162
00163     return "redirect:/admin/teams/" + teamId + "/players";
00164
00165 private void populateTeamPlayersModel(Model model, Team team) {
00166     model.addAttribute("team", team);
00167     model.addAttribute("players", playerService.getPlayersByTeamId(team.getId()));
00168     model.addAttribute("positions", PlayerPosition.values());
00169 }
00170 }

```


9.14 Football_Manager/src/main/java/com/example/football_manager/controller/AdminUserController.java File Reference

```
import com.example.football_manager.service.UserService;
import org.springframework.stereotype.Controller;
import org.springframework.web.bind.annotation.*;
```

Classes

- class [com.example.football_manager.controller.AdminUserController](#)

Packages

- package [com.example.football_manager.controller](#)

9.15 AdminUserController.java

[Go to the documentation of this file.](#)

```
00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.service.UserService;
00004 import org.springframework.stereotype.Controller;
00005 import org.springframework.web.bind.annotation.*;
00006
00007 @Controller
00008 public class AdminUserController {
00009     private final UserService userService;
00010
00011     public AdminUserController(UserService userService) {
00012         this.userService = userService;
00013     }
00014
00015     @GetMapping("/admin/users")
00016     public String usersPage() {
00017         return "admin-users";
00018     }
00019
00020     @PostMapping("/admin/users")
00021     public String createUser(@RequestParam String username,
00022                             @RequestParam String email,
00023                             @RequestParam String password,
00024                             @RequestParam(defaultValue = "false") Boolean isAdmin) {
00025         userService.registerUser(username, email, password, isAdmin);
00026         return "redirect:/admin/users";
00027     }
00028 }
00029 }
```

9.16 Football_Manager/src/main/java/com/example/football_manager/controller/AdminViewController.java File Reference

```
import com.example.football_manager.service.TeamService;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.GetMapping;
```

Classes

- class [com.example.football_manager.controller.AdminViewController](#)

Packages

- package [com.example.football_manager.controller](#)

9.17 AdminViewController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.service.TeamService;
00004 import org.springframework.beans.factory.annotation.Autowired;
00005 import org.springframework.stereotype.Controller;
00006 import org.springframework.ui.Model;
00007 import org.springframework.web.bind.annotation.GetMapping;
00008
00009 @Controller
00010 public class AdminViewController {
00011
00012     @Autowired
00013     private TeamService teamService;
00014
00015     @GetMapping("/admin")
00016     public String adminPanel() {
00017         return "admin-panel";
00018     }
00019
00020     @GetMapping("/admin/manage-teams")
00021     public String manageTeams(Model model) {
00022         model.addAttribute("teams", teamService.getAllTeams());
00023         return "admin-manage-teams";
00024     }
00025 }

```

9.18 Football_Manager/src/main/java/com/example/football_↵ manager/controller/AuthController.java File Reference

```

import com.example.football_manager.dto.AuthResponseDTO;
import com.example.football_manager.dto.LoginDTO;
import com.example.football_manager.dto.RegisterDTO;
import com.example.football_manager.model.User;
import com.example.football_manager.service.UserService;
import jakarta.servlet.http.HttpSession;
import jakarta.validation.Valid;
import io.swagger.v3.oas.annotations.Operation;
import io.swagger.v3.oas.annotations.media.Content;
import io.swagger.v3.oas.annotations.media.Schema;
import io.swagger.v3.oas.annotations.responses.ApiResponse;
import io.swagger.v3.oas.annotations.responses.ApiResponses;
import io.swagger.v3.oas.annotations.tags.Tag;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.http.HttpStatus;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.*;

```

Classes

- class `com.example.football_manager.controller.AuthController`

Packages

- package `com.example.football_manager.controller`

9.19 AuthController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.dto.AuthResponseDTO;
00004 import com.example.football_manager.dto.LoginDTO;
00005 import com.example.football_manager.dto.RegisterDTO;
00006 import com.example.football_manager.model.User;
00007 import com.example.football_manager.service.UserService;
00008 import jakarta.servlet.http.HttpSession;
00009 import jakarta.validation.Valid;
00010 import io.swagger.v3.oas.annotations.Operation;
00011 import io.swagger.v3.oas.annotations.media.Content;
00012 import io.swagger.v3.oas.annotations.media.Schema;
00013 import io.swagger.v3.oas.annotations.responses.ApiResponse;
00014 import io.swagger.v3.oas.annotations.responses.ApiResponses;
00015 import io.swagger.v3.oas.annotations.tags.Tag;
00016 import org.springframework.beans.factory.annotation.Autowired;
00017 import org.springframework.http.HttpStatus;
00018 import org.springframework.http.ResponseEntity;
00019 import org.springframework.web.bind.annotation.*;
00020
00021 @RestController
00022 @RequestMapping("/auth")
00023 @Tag(name = "Auth")
00024 public class AuthController {
00025
00026     @Autowired
00027     private UserService userService;
00028
00029     @PostMapping("/register")
00030     @Operation(
00031         summary = "Register a user",
00032         description = "Creates a new user account. Returns a message indicating success or
00033         conflict.",
00034         requestBody = @io.swagger.v3.oas.annotations.parameters.RequestBody(
00035             required = true,
00036             description = "Registration details",
00037             content = @Content(schema = @Schema(implementation = RegisterDTO.class))
00038         )
00039     )
00040     @ApiResponses({
00041         @ApiResponse(responseCode = "201", description = "User registered"),
00042         @ApiResponse(responseCode = "409", description = "Username or email already exists"),
00043         @ApiResponse(responseCode = "400", description = "Validation error")
00044     })
00045     public ResponseEntity<AuthResponseDTO> register(@Valid @RequestBody RegisterDTO registerDTO) {
00046         try {
00047             User user = userService.registerUser(
00048                 registerDTO.getUsername(),
00049                 registerDTO.getEmail(),
00050                 registerDTO.getPassword(),
00051                 registerDTO.getIsAdmin()
00052             );
00053             return ResponseEntity.status(HttpStatus.CREATED)
00054                 .body(new AuthResponseDTO(user.getId(), user.getUsername(), user.getEmail(),
00055                     user.getIsAdmin(), "User registered"));
00056         } catch (IllegalArgumentException ex) {
00057             return ResponseEntity.status(HttpStatus.CONFLICT)
00058                 .body(new AuthResponseDTO(null, null, null, null, ex.getMessage()));
00059         }
00060     }
00061
00062     @PostMapping("/login")
00063     @Operation(
00064         summary = "Login",

```

```

00064         description = "Authenticates the user and stores the session attributes for subsequent
requests.",
00065         requestBody = @io.swagger.v3.oas.annotations.parameters.RequestBody(
00066             required = true,
00067             description = "Login credentials",
00068             content = @Content(schema = @Schema(implementation = LoginDTO.class))
00069         )
00070     )
00071     @ApiResponses({
00072         @ApiResponse(responseCode = "200", description = "Login successful"),
00073         @ApiResponse(responseCode = "401", description = "Invalid credentials"),
00074         @ApiResponse(responseCode = "400", description = "Validation error")
00075     })
00076     public ResponseEntity<AuthResponseDTO> login(@Valid @RequestBody LoginDTO loginDTO, HttpSession
session) {
00077         try {
00078             User user = userService.login(loginDTO.getUsername(), loginDTO.getPassword());
00079
00080             session.setAttribute("userId", user.getId());
00081             session.setAttribute("isAdmin", user.getIsAdmin());
00082
00083             return ResponseEntity.ok(
00084                 new AuthResponseDTO(user.getId(), user.getUsername(), user.getEmail(),
user.getIsAdmin(), "Login successful")
00085             );
00086         } catch (IllegalArgumentException ex) {
00087             return ResponseEntity.status(HttpStatus.UNAUTHORIZED)
00088                 .body(new AuthResponseDTO(null, null, null, null, ex.getMessage()));
00089         }
00090     }
00091 }

```

9.20 Football_Manager/src/main/java/com/example/football_↵ manager/controller/AuthViewController.java File Reference

```

import org.springframework.stereotype.Controller;
import org.springframework.web.bind.annotation.GetMapping;

```

Classes

- class [com.example.football_manager.controller.AuthViewController](#)

Packages

- package [com.example.football_manager.controller](#)

9.21 AuthViewController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import org.springframework.stereotype.Controller;
00004 import org.springframework.web.bind.annotation.GetMapping;
00005
00006 @Controller
00007 public class AuthViewController {
00008
00009
00010     @GetMapping("/")
00011     public String index() {
00012         return "redirect:/login";
00013     }
00014
00015     @GetMapping("/login")

```

```
00016     public String loginPage() {
00017         return "login"; //
00018     }
00019
00020     @GetMapping("/register")
00021     public String registerPage() {
00022         return "register"; //
00023     }
00024 }
```

9.22 Football_Manager/src/main/java/com/example/football_manager/controller/CompetitionController.java File Reference

```
import com.example.football_manager.dto.CompetitionRequestDTO;
import com.example.football_manager.model.Competition;
import com.example.football_manager.service.CompetitionService;
import jakarta.validation.Valid;
import io.swagger.v3.oas.annotations.Operation;
import io.swagger.v3.oas.annotations.media.Content;
import io.swagger.v3.oas.annotations.media.Schema;
import io.swagger.v3.oas.annotations.responses.ApiResponse;
import io.swagger.v3.oas.annotations.responses.ApiResponses;
import io.swagger.v3.oas.annotations.tags.Tag;
import org.springframework.http.HttpStatus;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.*;
import java.util.List;
```

Classes

- class [com.example.football_manager.controller.CompetitionController](#)

Packages

- package [com.example.football_manager.controller](#)

9.23 CompetitionController.java

[Go to the documentation of this file.](#)

```
00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.dto.CompetitionRequestDTO;
00004 import com.example.football_manager.model.Competition;
00005 import com.example.football_manager.service.CompetitionService;
00006 import jakarta.validation.Valid;
00007 import io.swagger.v3.oas.annotations.Operation;
00008 import io.swagger.v3.oas.annotations.media.Content;
00009 import io.swagger.v3.oas.annotations.media.Schema;
00010 import io.swagger.v3.oas.annotations.responses.ApiResponse;
00011 import io.swagger.v3.oas.annotations.responses.ApiResponses;
00012 import io.swagger.v3.oas.annotations.tags.Tag;
00013 import org.springframework.http.HttpStatus;
00014 import org.springframework.http.ResponseEntity;
00015 import org.springframework.web.bind.annotation.*;
00016
00017 import java.util.List;
00018
00019 @RestController
```

```

00020 @RequestMapping("/api/competitions")
00021 @Tag(name = "Competitions")
00022 public class CompetitionController {
00023
00024     private final CompetitionService competitionService;
00025
00026     public CompetitionController(CompetitionService competitionService) {
00027         this.competitionService = competitionService;
00028     }
00029
00030     @PostMapping
00031     @Operation(
00032         summary = "Create a competition",
00033         description = "Creates a new competition entry.",
00034         requestBody = @io.swagger.v3.oas.annotations.parameters.RequestBody(
00035             required = true,
00036             description = "Competition details",
00037             content = @Content(schema = @Schema(implementation = CompetitionRequestDTO.class))
00038         )
00039     )
00040     @ApiResponses({
00041         @ApiResponse(responseCode = "201", description = "Competition created"),
00042         @ApiResponse(responseCode = "400", description = "Validation error")
00043     })
00044     public ResponseEntity<Competition> createCompetition(@Valid @RequestBody CompetitionRequestDTO
00045     dto) {
00046         Competition createdCompetition = competitionService.createCompetition(dto);
00047         return new ResponseEntity<>(createdCompetition, HttpStatus.CREATED);
00048     }
00049
00050     @PutMapping("/{id}")
00051     @Operation(
00052         summary = "Update a competition",
00053         description = "Updates the competition name.",
00054         requestBody = @io.swagger.v3.oas.annotations.parameters.RequestBody(
00055             required = true,
00056             description = "Updated competition details",
00057             content = @Content(schema = @Schema(implementation = CompetitionRequestDTO.class))
00058         )
00059     )
00060     @ApiResponses({
00061         @ApiResponse(responseCode = "200", description = "Competition updated"),
00062         @ApiResponse(responseCode = "400", description = "Validation error"),
00063         @ApiResponse(responseCode = "404", description = "Competition not found")
00064     })
00065     public ResponseEntity<Competition> updateCompetition(@PathVariable Long id,
00066     @Valid @RequestBody CompetitionRequestDTO
00067     dto) {
00068         Competition updatedCompetition = competitionService.updateCompetition(id, dto);
00069         return ResponseEntity.ok(updatedCompetition);
00070     }
00071
00072     @GetMapping("/{id}")
00073     @Operation(
00074         summary = "Get competition by id",
00075         description = "Returns competition details for the specified id."
00076     )
00077     @ApiResponses({
00078         @ApiResponse(responseCode = "200", description = "Competition found"),
00079         @ApiResponse(responseCode = "404", description = "Competition not found")
00080     })
00081     public ResponseEntity<Competition> getCompetitionById(@PathVariable Long id) {
00082         return ResponseEntity.of(competitionService.getCompetitionById(id));
00083     }
00084
00085     @GetMapping
00086     @Operation(
00087         summary = "List all competitions",
00088         description = "Returns every competition in the system."
00089     )
00090     @ApiResponses({
00091         @ApiResponse(responseCode = "200", description = "Competition list")
00092     })
00093     public ResponseEntity<List<Competition>> getAllCompetitions() {
00094         return ResponseEntity.ok(competitionService.getAllCompetitions());
00095     }
00096
00097     @DeleteMapping("/{id}")
00098     @Operation(
00099         summary = "Delete a competition",
00100         description = "Deletes a competition by its identifier."
00101     )
00102     @ApiResponses({
00103         @ApiResponse(responseCode = "204", description = "Competition deleted"),
00104         @ApiResponse(responseCode = "404", description = "Competition not found")
00105     })
00106     public ResponseEntity<Void> deleteCompetition(@PathVariable Long id) {

```

```

00105         competitionService.deleteCompetition(id);
00106         return ResponseEntity.noContent().build();
00107     }
00108 }

```

9.24 Football_Manager/src/main/java/com/example/football_manager/controller/CountryController.java File Reference

```

import com.example.football_manager.dto.CountryRequestDTO;
import com.example.football_manager.model.Country;
import com.example.football_manager.service.CountryService;
import jakarta.validation.Valid;
import io.swagger.v3.oas.annotations.Operation;
import io.swagger.v3.oas.annotations.media.Content;
import io.swagger.v3.oas.annotations.media.Schema;
import io.swagger.v3.oas.annotations.responses.ApiResponse;
import io.swagger.v3.oas.annotations.responses.ApiResponses;
import io.swagger.v3.oas.annotations.tags.Tag;
import org.springframework.http.HttpStatus;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.*;
import java.util.List;

```

Classes

- class [com.example.football_manager.controller.CountryController](#)

Packages

- package [com.example.football_manager.controller](#)

9.25 CountryController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.dto.CountryRequestDTO;
00004 import com.example.football_manager.model.Country;
00005 import com.example.football_manager.service.CountryService;
00006 import jakarta.validation.Valid;
00007 import io.swagger.v3.oas.annotations.Operation;
00008 import io.swagger.v3.oas.annotations.media.Content;
00009 import io.swagger.v3.oas.annotations.media.Schema;
00010 import io.swagger.v3.oas.annotations.responses.ApiResponse;
00011 import io.swagger.v3.oas.annotations.responses.ApiResponses;
00012 import io.swagger.v3.oas.annotations.tags.Tag;
00013 import org.springframework.http.HttpStatus;
00014 import org.springframework.http.ResponseEntity;
00015 import org.springframework.web.bind.annotation.*;
00016
00017 import java.util.List;
00018
00019 @RestController
00020 @RequestMapping("/api/countries")
00021 @Tag(name = "Countries")
00022 public class CountryController {
00023
00024     private final CountryService countryService;

```

```

00025
00026 public CountryController(CountryService countryService) {
00027     this.countryService = countryService;
00028 }
00029
00030 @PostMapping
00031 @Operation(
00032     summary = "Create a country",
00033     description = "Creates a new country entry.",
00034     requestBody = @io.swagger.v3.oas.annotations.parameters.RequestBody(
00035         required = true,
00036         description = "Country details",
00037         content = @Content(schema = @Schema(implementation = CountryRequestDTO.class))
00038     )
00039 )
00040 @ApiResponses({
00041     @ApiResponse(responseCode = "201", description = "Country created"),
00042     @ApiResponse(responseCode = "400", description = "Validation error")
00043 })
00044 public ResponseEntity<Country> createCountry(@Valid @RequestBody CountryRequestDTO dto) {
00045     Country createdCountry = countryService.createCountry(dto);
00046     return new ResponseEntity<>(createdCountry, HttpStatus.CREATED);
00047 }
00048
00049 @GetMapping
00050 @Operation(
00051     summary = "List all countries",
00052     description = "Returns every country currently in the system."
00053 )
00054 @ApiResponses({
00055     @ApiResponse(responseCode = "200", description = "Country list")
00056 })
00057 public ResponseEntity<List<Country>> getAllCountries() {
00058     List<Country> countries = countryService.getAllCountries();
00059     return ResponseEntity.ok(countries);
00060 }
00061
00062 @DeleteMapping("/{id}")
00063 @Operation(
00064     summary = "Delete a country",
00065     description = "Deletes a country by its identifier."
00066 )
00067 @ApiResponses({
00068     @ApiResponse(responseCode = "204", description = "Country deleted"),
00069     @ApiResponse(responseCode = "404", description = "Country not found")
00070 })
00071 public ResponseEntity<Void> deleteCountry(@PathVariable Long id) {
00072     countryService.deleteCountry(id);
00073     return ResponseEntity.noContent().build();
00074 }
00075 }

```

9.26 Football_Manager/src/main/java/com/example/football_↵ manager/controller/FavouriteTeamController.java File Reference

```

import com.example.football_manager.service.UserService;
import jakarta.servlet.http.HttpSession;
import io.swagger.v3.oas.annotations.Operation;
import io.swagger.v3.oas.annotations.responses.ApiResponse;
import io.swagger.v3.oas.annotations.responses.ApiResponses;
import io.swagger.v3.oas.annotations.tags.Tag;
import org.springframework.http.HttpStatus;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.DeleteMapping;
import org.springframework.web.bind.annotation.PathVariable;
import org.springframework.web.bind.annotation.PostMapping;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RestController;

```

Classes

- class [com.example.football_manager.controller.FavouriteTeamController](#)

Packages

- package `com.example.football_manager.controller`

9.27 FavouriteTeamController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.service.UserService;
00004 import jakarta.servlet.http.HttpSession;
00005 import io.swagger.v3.oas.annotations.Operation;
00006 import io.swagger.v3.oas.annotations.responses.ApiResponse;
00007 import io.swagger.v3.oas.annotations.responses.ApiResponses;
00008 import io.swagger.v3.oas.annotations.tags.Tag;
00009 import org.springframework.http.HttpStatus;
00010 import org.springframework.http.ResponseEntity;
00011 import org.springframework.web.bind.annotation.DeleteMapping;
00012 import org.springframework.web.bind.annotation.PathVariable;
00013 import org.springframework.web.bind.annotation.PostMapping;
00014 import org.springframework.web.bind.annotation.RequestMapping;
00015 import org.springframework.web.bind.annotation.RestController;
00016
00017 @RestController
00018 @RequestMapping("/api/users/me/favourites/teams")
00019 @Tag(name = "Favourites")
00020 public class FavouriteTeamController {
00021
00022     private final UserService userService;
00023
00024     public FavouriteTeamController(UserService userService) {
00025         this.userService = userService;
00026     }
00027
00028     @PostMapping("/{teamId}")
00029     @Operation(
00030         summary = "Add favourite team",
00031         description = "Adds the team to the current user's favourites. Requires a logged-in
session."
00032     )
00033     @ApiResponses({
00034         @ApiResponse(responseCode = "201", description = "Team added to favourites"),
00035         @ApiResponse(responseCode = "401", description = "User not logged in"),
00036         @ApiResponse(responseCode = "404", description = "User or team not found"),
00037         @ApiResponse(responseCode = "409", description = "Team already in favourites")
00038     })
00039     public ResponseEntity<String> addFavouriteTeam(@PathVariable Long teamId, HttpSession session) {
00040         Long userId = (Long) session.getAttribute("userId");
00041         if (userId == null) {
00042             return ResponseEntity.status(HttpStatus.UNAUTHORIZED).body("You must be logged in");
00043         }
00044
00045         try {
00046             userService.addFavouriteTeam(userId, teamId);
00047             return ResponseEntity.status(HttpStatus.CREATED).body("Team added to favourites");
00048         } catch (IllegalArgumentException ex) {
00049             return mapError(ex.getMessage());
00050         }
00051     }
00052
00053     @DeleteMapping("/{teamId}")
00054     @Operation(
00055         summary = "Remove favourite team",
00056         description = "Removes the team from the current user's favourites. Requires a logged-in
session."
00057     )
00058     @ApiResponses({
00059         @ApiResponse(responseCode = "200", description = "Team removed from favourites"),
00060         @ApiResponse(responseCode = "401", description = "User not logged in"),
00061         @ApiResponse(responseCode = "404", description = "User or team not found"),
00062         @ApiResponse(responseCode = "409", description = "Team not in favourites")
00063     })
00064     public ResponseEntity<String> removeFavouriteTeam(@PathVariable Long teamId, HttpSession session)
00065     {
00066         Long userId = (Long) session.getAttribute("userId");
00067         if (userId == null) {
00068             return ResponseEntity.status(HttpStatus.UNAUTHORIZED).body("You must be logged in");
00069         }
00070         try {

```

```

00071         userService.removeFavouriteTeam(userId, teamId);
00072         return ResponseEntity.ok("Team removed from favourites");
00073     } catch (IllegalArgumentException ex) {
00074         return mapError(ex.getMessage());
00075     }
00076 }
00077
00078 private ResponseEntity<String> mapError(String message) {
00079     if ("User not found".equals(message) || "Team not found".equals(message)) {
00080         return ResponseEntity.status(HttpStatus.NOT_FOUND).body(message);
00081     }
00082
00083     if ("Team already in favourites".equals(message) || "Team not in favourites".equals(message))
00084     {
00085         return ResponseEntity.status(HttpStatus.CONFLICT).body(message);
00086     }
00087     return ResponseEntity.badRequest().body(message);
00088 }
00089 }
00090

```

9.28 Football_Manager/src/main/java/com/example/football_ manager/controller/MatchController.java File Reference ↩

```

import com.example.football_manager.dto.MatchRequestDTO;
import com.example.football_manager.dto.MatchResultDTO;
import com.example.football_manager.dto.MatchResultRequestDTO;
import com.example.football_manager.model.Match;
import com.example.football_manager.service.MatchService;
import jakarta.validation.Valid;
import io.swagger.v3.oas.annotations.Operation;
import io.swagger.v3.oas.annotations.media.Content;
import io.swagger.v3.oas.annotations.media.Schema;
import io.swagger.v3.oas.annotations.responses.ApiResponse;
import io.swagger.v3.oas.annotations.responses.ApiResponses;
import io.swagger.v3.oas.annotations.tags.Tag;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.http.HttpStatus;
import org.springframework.http.MediaType;
import org.springframework.http.ResponseEntity;
import org.springframework.web.server.ResponseStatusException;
import org.springframework.web.bind.annotation.*;
import java.util.List;

```

Classes

- class [com.example.football_manager.controller.MatchController](#)

Packages

- package [com.example.football_manager.controller](#)

9.29 MatchController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.dto.MatchRequestDTO;
00004 import com.example.football_manager.dto.MatchResultDTO;
00005 import com.example.football_manager.dto.MatchResultRequestDTO;
00006 import com.example.football_manager.model.Match;
00007 import com.example.football_manager.service.MatchService;
00008 import jakarta.validation.Valid;
00009 import io.swagger.v3.oas.annotations.Operation;
00010 import io.swagger.v3.oas.annotations.media.Content;
00011 import io.swagger.v3.oas.annotations.media.Schema;
00012 import io.swagger.v3.oas.annotations.responses.ApiResponse;
00013 import io.swagger.v3.oas.annotations.responses.ApiResponses;
00014 import io.swagger.v3.oas.annotations.tags.Tag;
00015 import org.springframework.beans.factory.annotation.Autowired;
00016 import org.springframework.http.HttpStatus;
00017 import org.springframework.http.MediaType;
00018 import org.springframework.http.ResponseEntity;
00019 import org.springframework.web.server.ResponseStatusException;
00020 import org.springframework.web.bind.annotation.*;
00021
00022 import java.util.List;
00023
00024 @RestController
00025 @RequestMapping("/api/matches")
00026 @Tag(name = "Matches")
00027 public class MatchController {
00028
00029     @Autowired
00030     private MatchService matchService;
00031
00032     @GetMapping
00033     @Operation(
00034         summary = "List matches",
00035         description = "Returns matches, optionally filtered by team, status, or competition."
00036     )
00037     @ApiResponses({
00038         @ApiResponse(responseCode = "200", description = "Match list"),
00039         @ApiResponse(responseCode = "400", description = "Unsupported filter value")
00040     })
00041     public ResponseEntity<List<Match>> getMatches(
00042         @RequestParam(required = false) Long teamId,
00043         @RequestParam(required = false) MatchRequestDTO.MatchStatus status,
00044         @RequestParam(required = false) Long competitionId) {
00045         try {
00046             return ResponseEntity.ok(matchService.getMatches(teamId, status, competitionId));
00047         } catch (IllegalArgumentException e) {
00048             throw new ResponseStatusException(HttpStatus.BAD_REQUEST, e.getMessage(), e);
00049         }
00050     }
00051
00052     @PostMapping(consumes = MediaType.APPLICATION_JSON_VALUE)
00053     @Operation(
00054         summary = "Create a match (JSON)",
00055         description = "Creates a match using a JSON body. Use this for API clients.",
00056         requestBody = @io.swagger.v3.oas.annotations.parameters.RequestBody(
00057             required = true,
00058             description = "Match details",
00059             content = @Content(schema = @Schema(implementation = MatchRequestDTO.class))
00060         )
00061     )
00062     @ApiResponses({
00063         @ApiResponse(responseCode = "201", description = "Match created"),
00064         @ApiResponse(responseCode = "400", description = "Validation or business rule error")
00065     })
00066     public ResponseEntity<String> createMatchFromJson(@Valid @RequestBody MatchRequestDTO matchDTO) {
00067         return createMatchResponse(matchDTO);
00068     }
00069
00070     @PostMapping(consumes = MediaType.APPLICATION_FORM_URLENCODED_VALUE)
00071     @Operation(
00072         summary = "Create a match (form)",
00073         description = "Creates a match using form-encoded fields. Useful for HTML form submissions.",
00074         requestBody = @io.swagger.v3.oas.annotations.parameters.RequestBody(
00075             required = true,
00076             description = "Match form fields",
00077             content = @Content(schema = @Schema(implementation = MatchRequestDTO.class))
00078         )
00079     )
00080     @ApiResponses({
00081         @ApiResponse(responseCode = "201", description = "Match created"),

```

```

00082         @ApiResponse(responseCode = "400", description = "Validation or business rule error")
00083     })
00084     public ResponseEntity<String> createMatchFromForm(@Valid @ModelAttribute MatchRequestDTO matchDTO)
00085     {
00086         return createMatchResponse(matchDTO);
00087     }
00088     private ResponseEntity<String> createMatchResponse(MatchRequestDTO matchDTO) {
00089         try {
00090             String response = matchService.createMatch(matchDTO);
00091             return new ResponseEntity<>(response, HttpStatus.CREATED);
00092         } catch (IllegalArgumentException e) {
00093             return new ResponseEntity<>(e.getMessage(), HttpStatus.BAD_REQUEST);
00094         }
00095     }
00096
00097     @GetMapping("/results")
00098     @Operation(
00099         summary = "List finished match results",
00100         description = "Returns results for matches with registered scores."
00101     )
00102     @ApiResponses({
00103         @ApiResponse(responseCode = "200", description = "Match results")
00104     })
00105     public ResponseEntity<List<MatchResultDTO>> getMatchResults() {
00106         return ResponseEntity.ok(matchService.getFinishedMatchResults());
00107     }
00108
00109     // Edit match details
00110     @PostMapping("/{id}")
00111     @Operation(
00112         summary = "Update match details",
00113         description = "Edits match details such as kickoff time, venue, or participants.",
00114         requestBody = @io.swagger.v3.oas.annotations.parameters.RequestBody(
00115             required = true,
00116             description = "Match updates",
00117             content = @Content(schema = @Schema(implementation = MatchRequestDTO.class))
00118         )
00119     )
00120     @ApiResponses({
00121         @ApiResponse(responseCode = "200", description = "Match updated"),
00122         @ApiResponse(responseCode = "400", description = "Validation or business rule error")
00123     })
00124     public ResponseEntity<String> updateMatch(@PathVariable Long id, @RequestBody MatchRequestDTO
matchDTO) {
00125         try {
00126             return ResponseEntity.ok(matchService.updateMatch(id, matchDTO));
00127         } catch (IllegalArgumentException e) {
00128             return new ResponseEntity<>(e.getMessage(), HttpStatus.BAD_REQUEST);
00129         }
00130     }
00131
00132     @DeleteMapping("/{id}")
00133     @Operation(
00134         summary = "Delete a match",
00135         description = "Removes a match by its identifier."
00136     )
00137     @ApiResponses({
00138         @ApiResponse(responseCode = "200", description = "Match deleted"),
00139         @ApiResponse(responseCode = "400", description = "Match not found or cannot be deleted")
00140     })
00141     public ResponseEntity<String> deleteMatch(@PathVariable Long id) {
00142         try {
00143             return ResponseEntity.ok(matchService.deleteMatch(id));
00144         } catch (IllegalArgumentException e) {
00145             return new ResponseEntity<>(e.getMessage(), HttpStatus.BAD_REQUEST);
00146         }
00147     }
00148
00149     @PatchMapping("/{id}/result")
00150     @Operation(
00151         summary = "Register match result",
00152         description = "Registers goals and final score for a match.",
00153         requestBody = @io.swagger.v3.oas.annotations.parameters.RequestBody(
00154             required = true,
00155             description = "List of goals to register",
00156             content = @Content(schema = @Schema(implementation = MatchResultRequestDTO.class))
00157         )
00158     )
00159     @ApiResponses({
00160         @ApiResponse(responseCode = "200", description = "Result registered"),
00161         @ApiResponse(responseCode = "400", description = "Validation or business rule error")
00162     })
00163     public ResponseEntity<String> registerResult(
00164         @PathVariable Long id,
00165         @Valid @RequestBody MatchResultRequestDTO resultDTO) {
00166         try {

```

```

00167         return ResponseEntity.ok(matchService.registerResult(id, resultDTO));
00168     } catch (IllegalArgumentException e) {
00169         return new ResponseEntity<>(e.getMessage(), HttpStatus.BAD_REQUEST);
00170     }
00171 }
00172 }

```

9.30 Football_Manager/src/main/java/com/example/football_manager/controller/MatchViewController.java File Reference

```

import com.example.football_manager.dto.MatchRequestDTO;
import com.example.football_manager.dto.MatchResultRequestDTO;
import com.example.football_manager.model.Match;
import com.example.football_manager.model.MatchGoal;
import com.example.football_manager.service.MatchService;
import com.example.football_manager.service.TeamService;
import jakarta.servlet.http.HttpSession;
import org.springframework.http.HttpStatus;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.PathVariable;
import org.springframework.web.bind.annotation.PostMapping;
import org.springframework.web.bind.annotation.RequestParam;
import org.springframework.web.server.ResponseStatusException;
import org.springframework.web.servlet.mvc.support.RedirectAttributes;
import java.util.ArrayList;
import java.util.List;

```

Classes

- class [com.example.football_manager.controller.MatchViewController](#)

Packages

- package [com.example.football_manager.controller](#)

9.31 MatchViewController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.dto.MatchRequestDTO;
00004 import com.example.football_manager.dto.MatchResultRequestDTO;
00005 import com.example.football_manager.model.Match;
00006 import com.example.football_manager.model.MatchGoal;
00007 import com.example.football_manager.service.MatchService;
00008 import com.example.football_manager.service.TeamService;
00009
00010 import jakarta.servlet.http.HttpSession;
00011 import org.springframework.http.HttpStatus;
00012 import org.springframework.stereotype.Controller;
00013 import org.springframework.ui.Model;
00014 import org.springframework.web.bind.annotation.GetMapping;

```

```

00015 import org.springframework.web.bind.annotation.ModelAttribute;
00016 import org.springframework.web.bind.annotation.PathVariable;
00017 import org.springframework.web.bind.annotation.PostMapping;
00018 import org.springframework.web.bind.annotation.RequestParam;
00019 import org.springframework.web.server.ResponseStatusException;
00020 import org.springframework.web.servlet.mvc.support.RedirectAttributes;
00021
00022 import java.util.ArrayList;
00023 import java.util.List;
00024
00025 @Controller
00026 public class MatchViewController {
00027
00028     private final MatchService matchService;
00029     private final TeamService teamService;
00030
00031     public MatchViewController(MatchService matchService, TeamService teamService) {
00032         this.matchService = matchService;
00033         this.teamService = teamService;
00034     }
00035
00036     @GetMapping("/matches")
00037     public String showMatchesPage(
00038         @RequestParam(required = false) Long teamId,
00039         @RequestParam(required = false) MatchRequestDTO.MatchStatus status,
00040         @RequestParam(required = false) Long competitionId,
00041         Model model,
00042         HttpSession session) {
00043         Boolean isAdmin = (Boolean) session.getAttribute("isAdmin");
00044
00045         model.addAttribute("isAdmin", isAdmin != null && isAdmin);
00046         try {
00047             model.addAttribute("matches", matchService.getMatches(teamId, status, competitionId));
00048         } catch (IllegalArgumentException e) {
00049             throw new ResponseStatusException(HttpStatus.BAD_REQUEST, e.getMessage(), e);
00050         }
00051         model.addAttribute("teams", teamService.getAllTeams());
00052         model.addAttribute("selectedTeamId", teamId);
00053
00054         return "matches";
00055     }
00056
00057     @GetMapping("/matches/schedule")
00058     public String showScheduleForm(Model model) {
00059         model.addAttribute("matchRequest", new MatchRequestDTO());
00060         model.addAttribute("teams", teamService.getAllTeams());
00061         return "schedule-match";
00062     }
00063
00064     @GetMapping("/matches/results")
00065     public String showResultsPage(Model model) {
00066         model.addAttribute("results", matchService.getFinishedMatchResults());
00067         return "match-results";
00068     }
00069
00070     @GetMapping("/matches/edit/{id}")
00071     public String showEditForm(@PathVariable Long id, Model model) {
00072         MatchRequestDTO matchRequestDTO = matchService.getMatchForEdit(id)
00073             .orElseThrow(() -> new IllegalArgumentException("Match not found."));
00074
00075         model.addAttribute("matchRequest", matchRequestDTO);
00076         model.addAttribute("matchId", id);
00077         // PASAR LA LISTA DE EQUIPOS PARA LOS DESPLEGABLES
00078         model.addAttribute("teams", teamService.getAllTeams());
00079         return "edit-match";
00080     }
00081
00082     @PostMapping("/matches/edit/{id}")
00083     public String updateMatch(@PathVariable Long id, @ModelAttribute("matchRequest") MatchRequestDTO
matchDTO) {
00084         matchService.updateMatch(id, matchDTO);
00085         return "redirect:/matches/results";
00086     }
00087
00088     @GetMapping("/matches/{id}/score")
00089     public String showScoreForm(@PathVariable Long id, Model model) {
00090         Match match = matchService.getMatchById(id);
00091
00092         if (!model.containsAttribute("resultRequest")) {
00093             model.addAttribute("resultRequest", toResultRequest(matchService.getGoalsByMatchId(id)));
00094         }
00095
00096         model.addAttribute("match", match);
00097         return "enter-match-score";
00098     }
00099 }
00100

```

```

00101     @PostMapping("/matches/{id}/score")
00102     public String submitScoreForm(
00103         @PathVariable Long id,
00104         @ModelAttribute("resultRequest") MatchResultRequestDTO resultRequest,
00105         Model model,
00106         RedirectAttributes redirectAttributes) {
00107
00108         Match match = matchService.getMatchById(id);
00109         model.addAttribute("match", match);
00110
00111         if (resultRequest.getGoals() == null) {
00112             resultRequest.setGoals(new ArrayList<>());
00113         }
00114
00115         try {
00116             matchService.registerResult(id, resultRequest);
00117             redirectAttributes.addFlashAttribute("successMessage", "Result saved successfully.");
00118             return "redirect:/matches/" + id + "/score";
00119         } catch (IllegalArgumentException e) {
00120             model.addAttribute("errorMessage", e.getMessage());
00121             return "enter-match-score";
00122         }
00123     }
00124
00125     private MatchResultRequestDTO toResultRequest(List<MatchGoal> goals) {
00126         MatchResultRequestDTO resultRequest = new MatchResultRequestDTO();
00127         List<MatchResultRequestDTO.GoalDTO> goalDTOs = new ArrayList<>();
00128
00129         for (MatchGoal goal : goals) {
00130             MatchResultRequestDTO.GoalDTO goalDTO = new MatchResultRequestDTO.GoalDTO();
00131             goalDTO.setTeamId(goal.getTeam().getId());
00132             goalDTO.setMinute((int) goal.getMinute());
00133             goalDTO.setStoppageMinute(
00134                 goal.getStoppageMinute() == null ? null : (int) goal.getStoppageMinute()
00135             );
00136             goalDTOs.add(goalDTO);
00137         }
00138
00139         resultRequest.setGoals(goalDTOs);
00140         return resultRequest;
00141     }
00142
00143     @PostMapping("/matches/{id}/results")
00144     public String saveMatchResult(@PathVariable Long id, @ModelAttribute MatchResultRequestDTO
00145         requestDTO) {
00146         try {
00147             matchService.registerResult(id, requestDTO);
00148
00149             return "redirect:/admin/matches";
00150         } catch (IllegalArgumentException e) {
00151             return "redirect:/matches/" + id + "/results?error=true";
00152         }
00153     }

```

9.32 Football_Manager/src/main/java/com/example/football_manager/controller/PlayerController.java File Reference

```

import com.example.football_manager.dto.PlayerRequestDTO;
import com.example.football_manager.model.Player;
import com.example.football_manager.service.PlayerService;
import io.swagger.v3.oas.annotations.Operation;
import io.swagger.v3.oas.annotations.media.Content;
import io.swagger.v3.oas.annotations.media.Schema;
import io.swagger.v3.oas.annotations.responses.ApiResponse;
import io.swagger.v3.oas.annotations.responses.ApiResponses;
import io.swagger.v3.oas.annotations.tags.Tag;
import jakarta.validation.Valid;
import org.springframework.http.HttpStatus;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.*;
import java.util.List;

```

Classes

- class [com.example.football_manager.controller.PlayerController](#)

Packages

- package [com.example.football_manager.controller](#)

9.33 PlayerController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.dto.PlayerRequestDTO;
00004 import com.example.football_manager.model.Player;
00005 import com.example.football_manager.service.PlayerService;
00006 import io.swagger.v3.oas.annotations.Operation;
00007 import io.swagger.v3.oas.annotations.media.Content;
00008 import io.swagger.v3.oas.annotations.media.Schema;
00009 import io.swagger.v3.oas.annotations.responses.ApiResponse;
00010 import io.swagger.v3.oas.annotations.responses.ApiResponses;
00011 import io.swagger.v3.oas.annotations.tags.Tag;
00012 import jakarta.validation.Valid;
00013 import org.springframework.http.HttpStatus;
00014 import org.springframework.http.ResponseEntity;
00015 import org.springframework.web.bind.annotation.*;
00016
00017 import java.util.List;
00018
00019 @RestController
00020 @RequestMapping("/api/teams/{teamId}/players")
00021 @Tag(name = "Players")
00022 public class PlayerController {
00023
00024     private final PlayerService playerService;
00025
00026     public PlayerController(PlayerService playerService) {
00027         this.playerService = playerService;
00028     }
00029
00030     @PostMapping
00031     @Operation(
00032         summary = "Create a player for a team",
00033         description = "Adds a new player to the given team squad."
00034     )
00035     @ApiResponses({
00036         @ApiResponse(responseCode = "201", description = "Player created"),
00037         @ApiResponse(responseCode = "400", description = "Validation or business rule error")
00038     })
00039     public ResponseEntity<?> createPlayer(
00040         @PathVariable Long teamId,
00041         @Valid @RequestBody PlayerRequestDTO dto) {
00042         try {
00043             Player createdPlayer = playerService.createPlayer(teamId, dto);
00044             return new ResponseEntity<>(createdPlayer, HttpStatus.CREATED);
00045         } catch (IllegalArgumentException ex) {
00046             return ResponseEntity.badRequest().body(ex.getMessage());
00047         }
00048     }
00049
00050     @GetMapping
00051     @Operation(
00052         summary = "List players of a team",
00053         description = "Returns the squad players for the given team ordered by number."
00054     )
00055     @ApiResponses({
00056         @ApiResponse(responseCode = "200", description = "Player list"),
00057         @ApiResponse(responseCode = "400", description = "Validation or business rule error")
00058     })
00059     public ResponseEntity<?> getPlayersByTeamId(@PathVariable Long teamId) {
00060         try {
00061             List<Player> players = playerService.getPlayersByTeamId(teamId);
00062             return ResponseEntity.ok(players);
00063         } catch (IllegalArgumentException ex) {
00064             return ResponseEntity.badRequest().body(ex.getMessage());
00065         }
00066     }

```



```
00066     }
00067
00068     @PutMapping("/{playerId}")
00069     @Operation(
00070         summary = "Update a player of a team",
00071         description = "Updates the details of a player that belongs to the given team."
00072     )
00073     @ApiResponses({
00074         @ApiResponse(responseCode = "200", description = "Player updated"),
00075         @ApiResponse(responseCode = "400", description = "Validation or business rule error")
00076     })
00077     public ResponseEntity<?> updatePlayer(
00078         @PathVariable Long teamId,
00079         @PathVariable Long playerId,
00080         @Valid @RequestBody PlayerRequestDTO dto) {
00081         try {
00082             Player updatedPlayer = playerService.updatePlayer(teamId, playerId, dto);
00083             return ResponseEntity.ok(updatedPlayer);
00084         } catch (IllegalArgumentException ex) {
00085             return ResponseEntity.badRequest().body(ex.getMessage());
00086         }
00087     }
00088
00089     @DeleteMapping("/{playerId}")
00090     @Operation(
00091         summary = "Delete a player from a team",
00092         description = "Deletes a player that belongs to the given team."
00093     )
00094     @ApiResponses({
00095         @ApiResponse(responseCode = "204", description = "Player deleted"),
00096         @ApiResponse(responseCode = "400", description = "Validation or business rule error")
00097     })
00098     public ResponseEntity<?> deletePlayer(@PathVariable Long teamId, @PathVariable Long playerId) {
00099         try {
00100             playerService.deletePlayer(teamId, playerId);
00101             return ResponseEntity.noContent().build();
00102         } catch (IllegalArgumentException ex) {
00103             return ResponseEntity.badRequest().body(ex.getMessage());
00104         }
00105     }
00106 }
```

9.34 Football_Manager/src/main/java/com/example/football_manager/controller/ProfileViewController.java File Reference

```
import com.example.football_manager.dto.ProfileUpdatedDTO;
import com.example.football_manager.model.User;
import com.example.football_manager.service.UserService;
import jakarta.servlet.http.HttpSession;
import jakarta.validation.Valid;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.validation.BindingResult;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.PostMapping;
import java.util.Set;
```

Classes

- class [com.example.football_manager.controller.ProfileViewController](#)

Packages

- package [com.example.football_manager.controller](#)

9.35 ProfileViewController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.dto.ProfileUpdateDTO;
00004 import com.example.football_manager.model.User;
00005 import com.example.football_manager.service.UserService;
00006 import jakarta.servlet.http.HttpSession;
00007 import jakarta.validation.Valid;
00008 import org.springframework.stereotype.Controller;
00009 import org.springframework.ui.Model;
00010 import org.springframework.validation.BindingResult;
00011 import org.springframework.web.bind.annotation.GetMapping;
00012 import org.springframework.web.bind.annotation.ModelAttribute;
00013 import org.springframework.web.bind.annotation.PostMapping;
00014
00015 import java.util.Set;
00016
00017 @Controller
00018 public class ProfileViewController {
00019
00020     private final UserService userService;
00021
00022     public ProfileViewController(UserService userService) {
00023         this.userService = userService;
00024     }
00025
00026     @GetMapping("/profile")
00027     public String profilePage(Model model, HttpSession session) {
00028         Long userId = (Long) session.getAttribute("userId");
00029         if (userId == null) {
00030             return "redirect:/login";
00031         }
00032
00033         User user;
00034         try {
00035             user = userService.getUserProfile(userId);
00036         } catch (IllegalArgumentException ex) {
00037             session.invalidate();
00038             return "redirect:/login";
00039         }
00040
00041         populateProfileModel(model, user);
00042         return "profile";
00043     }
00044
00045     @PostMapping("/profile")
00046     public String updateProfile(@Valid @ModelAttribute("profileForm") ProfileUpdateDTO profileForm,
00047                                BindingResult bindingResult,
00048                                Model model,
00049                                HttpSession session) {
00050         Long userId = (Long) session.getAttribute("userId");
00051         if (userId == null) {
00052             return "redirect:/login";
00053         }
00054
00055         User currentUser;
00056         try {
00057             currentUser = userService.getUserProfile(userId);
00058         } catch (IllegalArgumentException ex) {
00059             session.invalidate();
00060             return "redirect:/login";
00061         }
00062
00063         if (bindingResult.hasErrors()) {
00064             populateProfileModel(model, currentUser);
00065             return "profile";
00066         }
00067
00068         try {
00069             User updatedUser = userService.updateProfile(
00070                 userId,
00071                 profileForm.getUsername(),
00072                 profileForm.getEmail(),
00073                 profileForm.getCurrentPassword(),
00074                 profileForm.getNewPassword(),
00075                 profileForm.getConfirmNewPassword()
00076             );
00077
00078             ProfileUpdateDTO refreshedForm = new ProfileUpdateDTO();
00079             refreshedForm.setUsername(updatedUser.getUsername());
00080             refreshedForm.setEmail(updatedUser.getEmail());
00081             model.addAttribute("profileForm", refreshedForm);

```

```

00082         model.addAttribute("favouriteTeams", updatedUser.getFavouriteTeams() != null ?
updatedUser.getFavouriteTeams() : Set.of());
00083         model.addAttribute("successMessage", "Profile updated successfully");
00084         return "profile";
00085     } catch (IllegalArgumentException ex) {
00086         populateProfileModel(model, currentUser);
00087         model.addAttribute("errorMessage", ex.getMessage());
00088         return "profile";
00089     }
00090 }
00091
00092 private void populateProfileModel(Model model, User user) {
00093     if (!model.containsAttribute("profileForm")) {
00094         ProfileUpdateDTO profileForm = new ProfileUpdateDTO();
00095         profileForm.setUsername(user.getUsername());
00096         profileForm.setEmail(user.getEmail());
00097         model.addAttribute("profileForm", profileForm);
00098     }
00099
00100     model.addAttribute("favouriteTeams", user.getFavouriteTeams() != null ?
user.getFavouriteTeams() : Set.of());
00101 }
00102 }
00103
00104
00105
00106
00107
00108

```

9.36 Football_Manager/src/main/java/com/example/football_manager/controller/TeamController.java File Reference

```

import com.example.football_manager.dto.TeamRequestDTO;
import com.example.football_manager.model.Team;
import com.example.football_manager.service.TeamService;
import jakarta.validation.Valid;
import java.util.List;
import io.swagger.v3.oas.annotations.Operation;
import io.swagger.v3.oas.annotations.media.Content;
import io.swagger.v3.oas.annotations.media.Schema;
import io.swagger.v3.oas.annotations.responses.ApiResponse;
import io.swagger.v3.oas.annotations.responses.ApiResponses;
import io.swagger.v3.oas.annotations.tags.Tag;
import org.springframework.http.HttpStatus;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.*;

```

Classes

- class [com.example.football_manager.controller.TeamController](#)

Packages

- package [com.example.football_manager.controller](#)

9.37 TeamController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.dto.TeamRequestDTO;
00004 import com.example.football_manager.model.Team;
00005 import com.example.football_manager.service.TeamService;
00006 import jakarta.validation.Valid;
00007
00008 import java.util.List;
00009
00010 import io.swagger.v3.oas.annotations.Operation;
00011 import io.swagger.v3.oas.annotations.media.Content;
00012 import io.swagger.v3.oas.annotations.media.Schema;
00013 import io.swagger.v3.oas.annotations.responses.ApiResponse;
00014 import io.swagger.v3.oas.annotations.responses.ApiResponses;
00015 import io.swagger.v3.oas.annotations.tags.Tag;
00016 import org.springframework.http.HttpStatus;
00017 import org.springframework.http.ResponseEntity;
00018 import org.springframework.web.bind.annotation.*;
00019
00020 @RestController
00021 @RequestMapping("/api/teams")
00022 @Tag(name = "Teams")
00023 public class TeamController {
00024
00025     private final TeamService teamService;
00026
00027     public TeamController(TeamService teamService) {
00028         this.teamService = teamService;
00029     }
00030
00031     @PostMapping
00032     @Operation(
00033         summary = "Create a team",
00034         description = "Creates a new team linked to a country.",
00035         requestBody = @io.swagger.v3.oas.annotations.parameters.RequestBody(
00036             required = true,
00037             description = "Team details",
00038             content = @Content(schema = @Schema(implementation = TeamRequestDTO.class))
00039         )
00040     )
00041     @ApiResponses({
00042         @ApiResponse(responseCode = "201", description = "Team created"),
00043         @ApiResponse(responseCode = "400", description = "Validation error")
00044     })
00045     public ResponseEntity<Team> createTeam(@Valid @RequestBody TeamRequestDTO dto) {
00046         Team createdTeam = teamService.createTeam(dto);
00047         return new ResponseEntity<>(createdTeam, HttpStatus.CREATED);
00048     }
00049
00050     @PutMapping("/{id}")
00051     @Operation(
00052         summary = "Update a team",
00053         description = "Updates the name, logo, or country of an existing team.",
00054         requestBody = @io.swagger.v3.oas.annotations.parameters.RequestBody(
00055             required = true,
00056             description = "Updated team details",
00057             content = @Content(schema = @Schema(implementation = TeamRequestDTO.class))
00058         )
00059     )
00060     @ApiResponses({
00061         @ApiResponse(responseCode = "200", description = "Team updated"),
00062         @ApiResponse(responseCode = "400", description = "Validation error"),
00063         @ApiResponse(responseCode = "404", description = "Team not found")
00064     })
00065     public ResponseEntity<Team> updateTeam(@PathVariable Long id,
00066         @Valid @RequestBody TeamRequestDTO dto) {
00067         Team updatedTeam = teamService.updateTeam(id, dto);
00068         return ResponseEntity.ok(updatedTeam);
00069     }
00070
00071     @DeleteMapping("/{id}")
00072     @Operation(
00073         summary = "Delete a team",
00074         description = "Deletes a team by its identifier."
00075     )
00076     @ApiResponses({
00077         @ApiResponse(responseCode = "204", description = "Team deleted"),
00078         @ApiResponse(responseCode = "404", description = "Team not found")
00079     })
00080     public ResponseEntity<Void> deleteTeam(@PathVariable Long id) {
00081         teamService.deleteTeam(id);
00082         return ResponseEntity.noContent().build();

```

```
00083     }
00084
00085     @GetMapping("/{id}")
00086     @Operation(
00087         summary = "Get team by id",
00088         description = "Returns a team with its persisted details."
00089     )
00090     @ApiResponses({
00091         @ApiResponse(responseCode = "200", description = "Team found"),
00092         @ApiResponse(responseCode = "404", description = "Team not found")
00093     })
00094     public ResponseEntity<Team> getTeamById(@PathVariable Long id) {
00095         return ResponseEntity.of(teamService.getTeamById(id));
00096     }
00097
00098     @GetMapping("/search")
00099     @Operation(
00100         summary = "Search teams by name",
00101         description = "Returns teams whose name contains the provided text (case-insensitive)."
00102     )
00103     @ApiResponses({
00104         @ApiResponse(responseCode = "200", description = "Teams matching query")
00105     })
00106     public ResponseEntity<List<Team>> getTeamsContainingName(@RequestParam String name) {
00107         return ResponseEntity.ok(teamService.getTeamsContainingName(name));
00108     }
00109
00110     @GetMapping
00111     @Operation(
00112         summary = "List all teams",
00113         description = "Returns all teams currently registered in the system."
00114     )
00115     @ApiResponses({
00116         @ApiResponse(responseCode = "200", description = "Team list")
00117     })
00118     public ResponseEntity<List<Team>> getAllTeams() {
00119         List<Team> teams = teamService.getAllTeams();
00120         return ResponseEntity.ok(teams);
00121     }
00122 }
```

9.38 Football_Manager/src/main/java/com/example/football_manager/controller/TeamViewController.java File Reference

```
import com.example.football_manager.dto.TeamRequestDTO;
import com.example.football_manager.model.Team;
import com.example.football_manager.service.CountryService;
import com.example.football_manager.service.MatchService;
import com.example.football_manager.service.PlayerService;
import com.example.football_manager.service.TeamService;
import com.example.football_manager.service.UserService;
import jakarta.servlet.http.HttpSession;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.PathVariable;
import org.springframework.web.bind.annotation.PostMapping;
import java.util.Set;
```

Classes

- class [com.example.football_manager.controller.TeamViewController](#)

Packages

- package [com.example.football_manager.controller](#)

9.39 TeamViewController.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.controller;
00002
00003 import com.example.football_manager.dto.TeamRequestDTO;
00004 import com.example.football_manager.model.Team;
00005 import com.example.football_manager.service.CountryService;
00006 import com.example.football_manager.service.MatchService;
00007 import com.example.football_manager.service.PlayerService;
00008 import com.example.football_manager.service.TeamService;
00009 import com.example.football_manager.service.UserService;
00010 import jakarta.servlet.http.HttpSession;
00011 import org.springframework.beans.factory.annotation.Autowired;
00012 import org.springframework.stereotype.Controller;
00013 import org.springframework.ui.Model;
00014 import org.springframework.web.bind.annotation.GetMapping;
00015 import org.springframework.web.bind.annotation.ModelAttribute;
00016 import org.springframework.web.bind.annotation.PathVariable;
00017 import org.springframework.web.bind.annotation.PostMapping;
00018
00019 import java.util.Set;
00020
00021 @Controller
00022 public class TeamViewController {
00023
00024     @Autowired
00025     private TeamService teamService;
00026
00027     @Autowired
00028     private CountryService countryService;
00029
00030     @Autowired
00031     private UserService userService;
00032
00033     @Autowired
00034     private MatchService matchService;
00035
00036     @Autowired
00037     private PlayerService playerService;
00038
00039     @GetMapping("/teams")
00040     public String teamsPage(Model model, HttpSession session) {
00041         Boolean isAdmin = (Boolean) session.getAttribute("isAdmin");
00042         Long userId = (Long) session.getAttribute("userId");
00043
00044         Set<Long> favouriteTeamIds = Set.of();
00045
00046         try {
00047             favouriteTeamIds = userService.getFavouriteTeamIdsByUserId(userId);
00048         } catch (IllegalArgumentException ignored) {
00049         }
00050
00051         model.addAttribute("isAdmin", isAdmin != null && isAdmin);
00052         model.addAttribute("teams", teamService.getAllTeams());
00053         model.addAttribute("favouriteTeamIds", favouriteTeamIds);
00054         model.addAttribute("favouriteUpcomingMatches",
00055             matchService.getFutureMatchesByFavouriteTeamIds(favouriteTeamIds));
00056
00057         return "teams";
00058     }
00059
00060     @GetMapping("/teams/{id}")
00061     public String teamDetailsPage(@PathVariable Long id, Model model, HttpSession session) {
00062         Boolean isAdmin = (Boolean) session.getAttribute("isAdmin");
00063
00064         Team team = teamService.getTeamById(id)
00065             .orElseThrow(() -> new RuntimeException("Team not found"));
00066
00067         model.addAttribute("isAdmin", isAdmin != null && isAdmin);
00068         model.addAttribute("team", team);
00069         model.addAttribute("players", playerService.getPlayersByTeamId(id));
00070         model.addAttribute("recentMatches", matchService.getRecentMatchesByTeamId(id));
00071         model.addAttribute("futureMatches", matchService.getFutureMatchesByTeamId(id));
00072
00073         return "team-details";
00074     }
00075 }

```

```

00073     }
00074
00075     @GetMapping("/teams/add")
00076     public String showAddTeamForm(Model model) {
00077         model.addAttribute("teamRequest", new TeamRequestDTO());
00078         model.addAttribute("countries", countryService.getAllCountries());
00079
00080         return "add-team";
00081     }
00082
00083     @PostMapping("/teams/add")
00084     public String createTeam(@ModelAttribute TeamRequestDTO teamDTO) {
00085         teamService.createTeam(teamDTO);
00086
00087         return "redirect:/teams";
00088     }
00089
00090     @GetMapping("/teams/edit/{id}")
00091     public String showEditTeamForm(@PathVariable Long id, Model model) {
00092         Team existingTeam = teamService.getTeamById(id)
00093             .orElseThrow(() -> new RuntimeException("Team not found"));
00094
00095         TeamRequestDTO teamDTO = new TeamRequestDTO();
00096         teamDTO.setName(existingTeam.getName());
00097         teamDTO.setLogoUrl(existingTeam.getLogoUrl());
00098
00099         if (existingTeam.getCountry() != null) {
00100             teamDTO.setCountryId(existingTeam.getCountry().getId());
00101         }
00102
00103         model.addAttribute("teamRequest", teamDTO);
00104         model.addAttribute("teamId", id);
00105         model.addAttribute("countries", countryService.getAllCountries());
00106
00107         return "edit-team";
00108     }
00109
00110     @PostMapping("/teams/edit/{id}")
00111     public String updateTeam(@PathVariable Long id, @ModelAttribute TeamRequestDTO teamDTO) {
00112         teamService.updateTeam(id, teamDTO);
00113
00114         return "redirect:/teams";
00115     }
00116
00117     @PostMapping("/teams/delete/{id}")
00118     public String deleteTeam(@PathVariable Long id) {
00119         teamService.deleteTeam(id);
00120
00121         return "redirect:/teams";
00122     }
00123 }

```

9.40 Football_Manager/src/main/java/com/example/football_manager/dto/AuthResponseDTO.java File Reference

```
import io.swagger.v3.oas.annotations.media.Schema;
```

Classes

- class [com.example.football_manager.dto.AuthResponseDTO](#)

Packages

- package [com.example.football_manager.dto](#)

9.41 AuthResponseDTO.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.dto;
00002
00003 import io.swagger.v3.oas.annotations.media.Schema;
00004
00005 public class AuthResponseDTO {
00006
00007     @Schema(description = "User identifier", example = "101")
00008     private Long id;
00009     @Schema(description = "Username", example = "user123")
00010     private String username;
00011     @Schema(description = "Email address", example = "user123@example.com")
00012     private String email;
00013     @Schema(description = "Whether the user is an administrator", example = "false")
00014     private Boolean isAdmin;
00015     @Schema(description = "Status message")
00016     private String message;
00017
00018     public AuthResponseDTO(Long id, String username, String email, Boolean isAdmin, String message) {
00019         this.id = id;
00020         this.username = username;
00021         this.email = email;
00022         this.isAdmin = isAdmin;
00023         this.message = message;
00024     }
00025
00026     public Long getId() {
00027         return id;
00028     }
00029
00030     public String getUsername() {
00031         return username;
00032     }
00033
00034     public String getEmail() {
00035         return email;
00036     }
00037
00038     public Boolean getIsAdmin() {
00039         return isAdmin;
00040     }
00041
00042     public String getMessage() {
00043         return message;
00044     }
00045 }
00046

```

9.42 Football_Manager/src/main/java/com/example/football_manager/dto/CompetitionRequestDTO.java File Reference

```

import jakarta.validation.constraints.NotBlank;
import jakarta.validation.constraints.Size;
import io.swagger.v3.oas.annotations.media.Schema;

```

Classes

- class [com.example.football_manager.dto.CompetitionRequestDTO](#)

Packages

- package [com.example.football_manager.dto](#)

9.43 CompetitionRequestDTO.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.dto;
00002
00003 import jakarta.validation.constraints.NotBlank;
00004 import jakarta.validation.constraints.Size;
00005 import io.swagger.v3.oas.annotations.media.Schema;
00006
00007 public class CompetitionRequestDTO {
00008
00009     @NotBlank(message = "Competition name is required")
00010     @Size(max = 50, message = "Competition name must be at most 50 characters")
00011     @Schema(description = "Competition name", example = "LaLiga")
00012     private String name;
00013
00014     public CompetitionRequestDTO() {
00015     }
00016
00017     public CompetitionRequestDTO(String name) {
00018         this.name = name;
00019     }
00020
00021     public String getName() {
00022         return name;
00023     }
00024
00025     public void setName(String name) {
00026         this.name = name;
00027     }
00028 }

```

9.44 Football_Manager/src/main/java/com/example/football_manager/dto/CountryRequestDTO.java File Reference

```

import jakarta.validation.constraints.NotBlank;
import jakarta.validation.constraints.Size;
import io.swagger.v3.oas.annotations.media.Schema;

```

Classes

- class [com.example.football_manager.dto.CountryRequestDTO](#)

Packages

- package [com.example.football_manager.dto](#)

9.45 CountryRequestDTO.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.dto;
00002
00003 import jakarta.validation.constraints.NotBlank;
00004 import jakarta.validation.constraints.Size;
00005 import io.swagger.v3.oas.annotations.media.Schema;
00006
00007 public class CountryRequestDTO {
00008
00009     @NotBlank(message = "Country name is required")
00010     @Size(max = 100, message = "Country name must be at most 100 characters")
00011     @Schema(description = "Country name", example = "Spain")

```

```

00012     private String name;
00013
00014     public CountryRequestDTO() {
00015     }
00016
00017     public CountryRequestDTO(String name) {
00018         this.name = name;
00019     }
00020
00021     public String getName() {
00022         return name;
00023     }
00024
00025     public void setName(String name) {
00026         this.name = name;
00027     }
00028 }

```

9.46 Football_Manager/src/main/java/com/example/football_manager/dto/LoginDTO.java File Reference ↩

```

import jakarta.validation.constraints.NotBlank;
import io.swagger.v3.oas.annotations.media.Schema;

```

Classes

- class [com.example.football_manager.dto.LoginDTO](#)

Packages

- package [com.example.football_manager.dto](#)

9.47 LoginDTO.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.dto;
00002
00003 import jakarta.validation.constraints.NotBlank;
00004 import io.swagger.v3.oas.annotations.media.Schema;
00005
00006 public class LoginDTO {
00007
00008     @NotBlank(message = "Username is required")
00009     @Schema(description = "Username", example = "user123")
00010     private String username;
00011
00012     @NotBlank(message = "Password is required")
00013     @Schema(description = "User password", example = "P@ssw0rd123")
00014     private String password;
00015
00016     public String getUsername() {
00017         return username;
00018     }
00019
00020     public void setUsername(String username) {
00021         this.username = username;
00022     }
00023
00024     public String getPassword() {
00025         return password;
00026     }
00027
00028     public void setPassword(String password) {
00029         this.password = password;
00030     }
00031 }
00032

```

9.48 Football_Manager/src/main/java/com/example/football_manager/dto/MatchRequestDTO.java File Reference

```
import java.time.LocalDateTime;
import jakarta.validation.constraints.Min;
import jakarta.validation.constraints.NotBlank;
import jakarta.validation.constraints.NotNull;
import io.swagger.v3.oas.annotations.media.Schema;
```

Classes

- class [com.example.football_manager.dto.MatchRequestDTO](#)
- enum [com.example.football_manager.dto.MatchRequestDTO.MatchStatus](#)

Packages

- package [com.example.football_manager.dto](#)

9.49 MatchRequestDTO.java

[Go to the documentation of this file.](#)

```
00001 package com.example.football_manager.dto;
00002
00003 import java.time.LocalDateTime;
00004 import jakarta.validation.constraints.Min;
00005 import jakarta.validation.constraints.NotBlank;
00006 import jakarta.validation.constraints.NotNull;
00007 import io.swagger.v3.oas.annotations.media.Schema;
00008
00009 public class MatchRequestDTO {
00010
00011     public enum MatchStatus {
00012         SCHEDULED,
00013         IN_PROGRESS,
00014         FINISHED,
00015         CANCELLED
00016     }
00017
00018     @Schema(description = "Home team identifier", example = "12")
00019     private Long homeTeamId;
00020     @Schema(description = "Away team identifier", example = "45")
00021     private Long awayTeamId;
00022     @Schema(description = "Competition identifier", example = "3")
00023     private Long competitionId;
00024     @Schema(description = "Kickoff time (local server time)", example = "2026-04-28T18:30:00")
00025     private LocalDateTime kickoffTime;
00026     @Schema(description = "Match venue or stadium name", example = "Anoeta Stadium")
00027     private String venue;
00028
00029     @Schema(description = "Match status", example = "SCHEDULED")
00030     private MatchStatus status;
00031
00032     @Schema(description = "Home team score", example = "2")
00033     private Integer homeScore;
00034     @Schema(description = "Away team score", example = "1")
00035     private Integer awayScore;
00036
00037
00038     public Long getHomeTeamId() { return homeTeamId; }
00039     public void setHomeTeamId(Long homeTeamId) { this.homeTeamId = homeTeamId; }
00040
00041     public Long getAwayTeamId() { return awayTeamId; }
00042     public void setAwayTeamId(Long awayTeamId) { this.awayTeamId = awayTeamId; }
00043
00044     public Long getCompetitionId() { return competitionId; }
```

```

00045     public void setCompetitionId(Long competitionId) { this.competitionId = competitionId; }
00046
00047     public LocalDateTime getKickoffTime() { return kickoffTime; }
00048     public void setKickoffTime(LocalDateTime kickoffTime) { this.kickoffTime = kickoffTime; }
00049
00050     public String getVenue() { return venue; }
00051     public void setVenue(String venue) { this.venue = venue; }
00052
00053     public MatchStatus getStatus() { return status; }
00054     public void setStatus(MatchStatus status) { this.status = status; }
00055
00056     public Integer getHomeScore() { return homeScore; }
00057     public void setHomeScore(Integer homeScore) { this.homeScore = homeScore; }
00058
00059     public Integer getAwayScore() { return awayScore; }
00060     public void setAwayScore(Integer awayScore) { this.awayScore = awayScore; }
00061 }

```

9.50 Football_Manager/src/main/java/com/example/football_manager/dto/MatchResultDTO.java File Reference

```

import java.time.OffsetDateTime;
import io.swagger.v3.oas.annotations.media.Schema;

```

Packages

- package [com.example.football_manager.dto](#)

Functions

- record [com.example.football_manager.dto.MatchResultDTO](#) (@Schema(description="Match identifier", example="220") Long matchId, @Schema(description="Home team name", example="Real Sociedad") String homeTeamName, @Schema(description="Away team name", example="Athletic Club") String awayTeamName, @Schema(description="Home team score", example="2") short homeScore, @Schema(description="Away team score", example="1") short awayScore, @Schema(description="Kickoff time (UTC)", example="2026-04-28T18:30:00Z") OffsetDateTime kickoffTime)

9.51 MatchResultDTO.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.dto;
00002
00003 import java.time.OffsetDateTime;
00004 import io.swagger.v3.oas.annotations.media.Schema;
00005
00006 public record MatchResultDTO(
00007     @Schema(description = "Match identifier", example = "220") Long matchId,
00008     @Schema(description = "Home team name", example = "Real Sociedad") String homeTeamName,
00009     @Schema(description = "Away team name", example = "Athletic Club") String awayTeamName,
00010     @Schema(description = "Home team score", example = "2") short homeScore,
00011     @Schema(description = "Away team score", example = "1") short awayScore,
00012     @Schema(description = "Kickoff time (UTC)", example = "2026-04-28T18:30:00Z") OffsetDateTime
    kickoffTime
00013 ) {
00014 }

```

9.52 Football_Manager/src/main/java/com/example/football_manager/dto/MatchResultRequestDTO.java File Reference

```
import jakarta.validation.Valid;
import jakarta.validation.constraints.Max;
import jakarta.validation.constraints.Min;
import jakarta.validation.constraints.NotNull;
import io.swagger.v3.oas.annotations.media.Schema;
import java.util.List;
```

Classes

- class [com.example.football_manager.dto.MatchResultRequestDTO](#)
- class [com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO](#)

Packages

- package [com.example.football_manager.dto](#)

9.53 MatchResultRequestDTO.java

[Go to the documentation of this file.](#)

```
00001 package com.example.football_manager.dto;
00002
00003 import jakarta.validation.Valid;
00004 import jakarta.validation.constraints.Max;
00005 import jakarta.validation.constraints.Min;
00006 import jakarta.validation.constraints.NotNull;
00007 import io.swagger.v3.oas.annotations.media.Schema;
00008
00009 import java.util.List;
00010
00011 public class MatchResultRequestDTO {
00012
00013     @NotNull
00014     @Schema(description = "List of goals scored during the match")
00015     private List<@Valid GoalDTO> goals;
00016
00017     public List<GoalDTO> getGoals() {
00018         return goals;
00019     }
00020
00021     public void setGoals(List<GoalDTO> goals) {
00022         this.goals = goals;
00023     }
00024
00025     public static class GoalDTO {
00026
00027         @NotNull
00028         @Schema(description = "Identifier of the scoring team", example = "12")
00029         private Long teamId;
00030
00031         @NotNull
00032         @Min(1)
00033         @Max(120)
00034         @Schema(description = "Minute of the goal (1-120)", example = "67")
00035         private Integer minute;
00036
00037         @Min(0)
00038         @Max(30)
00039         @Schema(description = "Stoppage minute (optional)", example = "2")
00040         private Integer stoppageMinute;
00041
00042         public Long getTeamId() {
00043             return teamId;
```

```

00044     }
00045
00046     public void setTeamId(Long teamId) {
00047         this.teamId = teamId;
00048     }
00049
00050     public Integer getMinute() {
00051         return minute;
00052     }
00053
00054     public void setMinute(Integer minute) {
00055         this.minute = minute;
00056     }
00057
00058     public Integer getStoppageMinute() {
00059         return stoppageMinute;
00060     }
00061
00062     public void setStoppageMinute(Integer stoppageMinute) {
00063         this.stoppageMinute = stoppageMinute;
00064     }
00065 }
00066 }

```

9.54 Football_Manager/src/main/java/com/example/football_manager/dto/PlayerRequestDTO.java File Reference

```

import com.example.football_manager.model.PlayerPosition;
import io.swagger.v3.oas.annotations.media.Schema;
import jakarta.validation.constraints.Min;
import jakarta.validation.constraints.NotBlank;
import jakarta.validation.constraints.NotNull;
import jakarta.validation.constraints.Size;

```

Classes

- class [com.example.football_manager.dto.PlayerRequestDTO](#)

Packages

- package [com.example.football_manager.dto](#)

9.55 PlayerRequestDTO.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.dto;
00002
00003 import com.example.football_manager.model.PlayerPosition;
00004 import io.swagger.v3.oas.annotations.media.Schema;
00005 import jakarta.validation.constraints.Min;
00006 import jakarta.validation.constraints.NotBlank;
00007 import jakarta.validation.constraints.NotNull;
00008 import jakarta.validation.constraints.Size;
00009
00010 public class PlayerRequestDTO {
00011
00012     @NotBlank(message = "Player name is required")
00013     @Size(max = 30, message = "Player name must be at most 30 characters")
00014     @Schema(description = "Player name", example = "Mikel Oyarzabal")
00015     private String name;
00016
00017     @NotNull(message = "Player number is required")

```

```

00018     @Min(value = 1, message = "Player number must be greater than 0")
00019     @Schema(description = "Squad number", example = "10")
00020     private Integer number;
00021
00022     @NotNull(message = "Player position is required")
00023     @Schema(description = "Player position", example = "FORWARD")
00024     private PlayerPosition position;
00025
00026     public PlayerRequestDTO() {
00027     }
00028
00029     public PlayerRequestDTO(String name, Integer number, PlayerPosition position) {
00030         this.name = name;
00031         this.number = number;
00032         this.position = position;
00033     }
00034
00035     public String getName() {
00036         return name;
00037     }
00038
00039     public void setName(String name) {
00040         this.name = name;
00041     }
00042
00043     public Integer getNumber() {
00044         return number;
00045     }
00046
00047     public void setNumber(Integer number) {
00048         this.number = number;
00049     }
00050
00051     public PlayerPosition getPosition() {
00052         return position;
00053     }
00054
00055     public void setPosition(PlayerPosition position) {
00056         this.position = position;
00057     }
00058 }

```

9.56 Football_Manager/src/main/java/com/example/football_manager/dto/ProfileUpdateDTO.java File Reference

```

import jakarta.validation.constraints.Email;
import jakarta.validation.constraints.AssertTrue;
import jakarta.validation.constraints.NotBlank;
import jakarta.validation.constraints.Pattern;
import jakarta.validation.constraints.Size;
import io.swagger.v3.oas.annotations.media.Schema;
import lombok.AllArgsConstructor;
import lombok.Data;
import lombok.NoArgsConstructor;

```

Classes

- class [com.example.football_manager.dto.ProfileUpdateDTO](#)

Packages

- package [com.example.football_manager.dto](#)

9.57 ProfileUpdateDTO.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.dto;
00002
00003 import jakarta.validation.constraints.Email;
00004 import jakarta.validation.constraints.AssertTrue;
00005 import jakarta.validation.constraints.NotBlank;
00006 import jakarta.validation.constraints.Pattern;
00007 import jakarta.validation.constraints.Size;
00008 import io.swagger.v3.oas.annotations.media.Schema;
00009 import lombok.AllArgsConstructor;
00010 import lombok.Data;
00011 import lombok.NoArgsConstructor;
00012
00013 @Data
00014 @NoArgsConstructor
00015 @AllArgsConstructor
00016 public class ProfileUpdateDTO {
00017
00018     @NotBlank(message = "Username is required")
00019     @Size(max = 30, message = "Username must be at most 30 characters")
00020     @Schema(description = "New username", example = "john_doe")
00021     private String username;
00022
00023     @NotBlank(message = "Email is required")
00024     @Email(message = "Email must be valid")
00025     @Schema(description = "New email address", example = "john_doe@example.com")
00026     private String email;
00027
00028     @Schema(description = "Current password (required when changing password)", example =
"OldP@ssw0rd")
00029     private String currentPassword;
00030
00031     @Pattern(regexp = "^[a-zA-Z0-9]{8,}$", message = "New password must be at least 8 characters")
00032     @Schema(description = "New password (min 8 characters)", example = "NewP@ssw0rd123")
00033     private String newPassword;
00034
00035     @Schema(description = "Confirmation of new password", example = "NewP@ssw0rd123")
00036     private String confirmNewPassword;
00037
00038     @AssertTrue(message = "New passwords do not match")
00039     public boolean isPasswordConfirmationValid() {
00040         if ((newPassword == null || newPassword.isBlank()) && (confirmNewPassword == null ||
confirmNewPassword.isBlank())) {
00041             return true;
00042         }
00043
00044         if (newPassword == null || confirmNewPassword == null) {
00045             return false;
00046         }
00047
00048         return newPassword.equals(confirmNewPassword);
00049     }
00050 }
00051
00052
00053
00054

```

9.58 Football_Manager/src/main/java/com/example/football_← manager/dto/RegisterDTO.java File Reference

```

import jakarta.validation.constraints.Email;
import jakarta.validation.constraints.NotBlank;
import jakarta.validation.constraints.Size;
import io.swagger.v3.oas.annotations.media.Schema;

```

Classes

- class [com.example.football_manager.dto.RegisterDTO](#)

Packages

- package [com.example.football_manager.dto](#)

9.59 RegisterDTO.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.dto;
00002
00003 import jakarta.validation.constraints.Email;
00004 import jakarta.validation.constraints.NotBlank;
00005 import jakarta.validation.constraints.Size;
00006 import io.swagger.v3.oas.annotations.media.Schema;
00007
00008 public class RegisterDTO {
00009
00010     @NotBlank(message = "Username is required")
00011     @Size(max = 30, message = "Username must be at most 30 characters")
00012     @Schema(description = "Username", example = "user123")
00013     private String username;
00014
00015     @NotBlank(message = "Email is required")
00016     @Email(message = "Invalid email format")
00017     @Schema(description = "Email address", example = "user123@example.com")
00018     private String email;
00019
00020     @NotBlank(message = "Password is required")
00021     @Size(min = 8, message = "Password must be at least 8 characters")
00022     @Schema(description = "Password (min 8 characters)", example = "P@ssw0rd123")
00023     private String password;
00024
00025     @Schema(description = "Whether the user should be registered as admin", example = "false")
00026     private Boolean isAdmin;
00027
00028     public String getUsername() { return username; }
00029     public void setUsername(String username) { this.username = username; }
00030
00031     public String getEmail() { return email; }
00032     public void setEmail(String email) { this.email = email; }
00033
00034     public String getPassword() { return password; }
00035     public void setPassword(String password) { this.password = password; }
00036
00037     public Boolean getIsAdmin() { return isAdmin; }
00038     public void setIsAdmin(Boolean isAdmin) { this.isAdmin = isAdmin; }
00039 }

```

9.60 Football_Manager/src/main/java/com/example/football_manager/dto/TeamRequestDTO.java File Reference

```

import jakarta.validation.constraints.NotBlank;
import jakarta.validation.constraints.NotNull;
import jakarta.validation.constraints.Size;
import io.swagger.v3.oas.annotations.media.Schema;

```

Classes

- class [com.example.football_manager.dto.TeamRequestDTO](#)

Packages

- package [com.example.football_manager.dto](#)

9.61 TeamRequestDTO.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.dto;
00002
00003 import jakarta.validation.constraints.NotBlank;
00004 import jakarta.validation.constraints.NotNull;
00005 import jakarta.validation.constraints.Size;
00006 import io.swagger.v3.oas.annotations.media.Schema;
00007
00008 public class TeamRequestDTO {
00009
00010     @NotBlank(message = "Team name is required")
00011     @Size(max = 30, message = "Team name must be at most 30 characters")
00012     @Schema(description = "Team name", example = "Real Sociedad")
00013     private String name;
00014
00015     @NotBlank(message = "Logo URL is required")
00016     @Schema(description = "Public logo URL", example =
00017         "https://cdn.example.com/logos/real-sociedad.png")
00018     private String logoUrl;
00019
00020     @NotNull(message = "Country ID is required")
00021     @Schema(description = "Identifier of the country the team belongs to", example = "34")
00022     private Long countryId;
00023
00024     public TeamRequestDTO() {
00025
00026     }
00027
00028     public TeamRequestDTO(String name, String logoUrl, Long countryId) {
00029         this.name = name;
00030         this.logoUrl = logoUrl;
00031         this.countryId = countryId;
00032     }
00033
00034     public String getName() {
00035         return name;
00036     }
00037
00038     public void setName(String name) {
00039         this.name = name;
00040     }
00041
00042     public String getLogoUrl() {
00043         return logoUrl;
00044     }
00045
00046     public void setLogoUrl(String logoUrl) {
00047         this.logoUrl = logoUrl;
00048     }
00049
00050     public Long getCountryId() {
00051         return countryId;
00052     }
00053
00054     public void setCountryId(Long countryId) {
00055         this.countryId = countryId;
00056     }
00057
00058 }

```

9.62 Football_Manager/src/main/java/com/example/football_manager/ FootballManagerApplication.java File Reference

```

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

```

Classes

- class [com.example.football_manager.FootballManagerApplication](#)

Packages

- package [com.example.football_manager](#)

9.63 FootballManagerApplication.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager;
00002
00003 import org.springframework.boot.SpringApplication;
00004 import org.springframework.boot.autoconfigure.SpringBootApplication;
00005
00006 @SpringBootApplication
00007 public class FootballManagerApplication {
00008
00009     public static void main(String[] args) {
00010         SpringApplication.run(FootballManagerApplication.class, args);
00011     }
00012
00013 }

```

9.64 Football_Manager/src/main/java/com/example/football_manager/model/Competition.java File Reference

```

import jakarta.persistence.*;
import lombok.AllArgsConstructor;
import lombok.Data;
import lombok.NoArgsConstructor;

```

Classes

- class [com.example.football_manager.model.Competition](#)

Packages

- package [com.example.football_manager.model](#)

9.65 Competition.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.model;
00002
00003 import jakarta.persistence.*;
00004 import lombok.AllArgsConstructor;
00005 import lombok.Data;
00006 import lombok.NoArgsConstructor;
00007
00008 @Entity
00009 @Table(name = "competition")
00010 @Data
00011 @NoArgsConstructor
00012 @AllArgsConstructor
00013 public class Competition {
00014
00015     @Id
00016     @GeneratedValue(strategy = GenerationType.IDENTITY)
00017     private Long id;
00018
00019     @Column(nullable = false, length = 50)
00020     private String name;
00021 }
00022

```

9.66 Football_Manager/src/main/java/com/example/football_manager/model/Country.java File Reference

```
import jakarta.persistence.*;
import lombok.AllArgsConstructor;
import lombok.Data;
import lombok.NoArgsConstructor;
```

Classes

- class [com.example.football_manager.model.Country](#)

Packages

- package [com.example.football_manager.model](#)

9.67 Country.java

[Go to the documentation of this file.](#)

```
00001 package com.example.football_manager.model;
00002
00003 import jakarta.persistence.*;
00004 import lombok.AllArgsConstructor;
00005 import lombok.Data;
00006 import lombok.NoArgsConstructor;
00007
00008 @Entity
00009 @Table(name = "country")
00010 @Data
00011 @NoArgsConstructor
00012 @AllArgsConstructor
00013 public class Country {
00014
00015     @Id
00016     @GeneratedValue(strategy = GenerationType.IDENTITY)
00017     private Long id;
00018
00019     @Column(nullable = false, length = 50)
00020     private String name;
00021 }
00022
```

9.68 Football_Manager/src/main/java/com/example/football_manager/model/Match.java File Reference

```
import jakarta.persistence.*;
import lombok.*;
import java.time.OffsetDateTime;
```

Classes

- class [com.example.football_manager.model.Match](#)

Packages

- package [com.example.football_manager.model](#)

9.69 Match.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.model;
00002
00003 import jakarta.persistence.*;
00004 import lombok.*;
00005 import java.time.OffsetDateTime;
00006
00007 @Entity
00008 @Table(name = "match")
00009 @Data
00010 @NoArgsConstructor
00011 @AllArgsConstructor
00012 public class Match {
00013
00014     @Id
00015     @GeneratedValue(strategy = GenerationType.IDENTITY)
00016     private Long id;
00017
00018     @ManyToOne
00019     @JoinColumn(name = "fk_left_team_id", nullable = false)
00020     private Team leftTeam;
00021
00022     @ManyToOne
00023     @JoinColumn(name = "fk_right_team_id", nullable = false)
00024     private Team rightTeam;
00025
00026     @ManyToOne
00027     @JoinColumn(name = "fk_league_id", nullable = false)
00028     private Competition competition;
00029
00030     @Column(nullable = false)
00031     private OffsetDateTime datetime;
00032
00033     @Column(nullable = false, length = 100)
00034     private String venue;
00035
00036     @Column(name = "left_score", nullable = false)
00037     private short leftScore;
00038
00039     @Column(name = "right_score", nullable = false)
00040     private short rightScore;
00041
00042     @Column(nullable = false)
00043     private boolean finished;
00044 }

```

**9.70 Football_Manager/src/main/java/com/example/football_↵
manager/model/MatchGoal.java File Reference**

```

import jakarta.persistence.*;
import lombok.AllArgsConstructor;
import lombok.Data;
import lombok.NoArgsConstructor;

```

Classes

- class [com.example.football_manager.model.MatchGoal](#)

Packages

- package [com.example.football_manager.model](#)

9.71 MatchGoal.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.model;
00002
00003 import jakarta.persistence.*;
00004 import lombok.AllArgsConstructor;
00005 import lombok.Data;
00006 import lombok.NoArgsConstructor;
00007
00008 @Entity
00009 @Table(name = "match_goal")
00010 @Data
00011 @NoArgsConstructor
00012 @AllArgsConstructor
00013 public class MatchGoal {
00014
00015     @Id
00016     @GeneratedValue(strategy = GenerationType.IDENTITY)
00017     private Long id;
00018
00019     @ManyToOne
00020     @JoinColumn(name = "fk_match_id", nullable = false)
00021     private Match match;
00022
00023     @ManyToOne
00024     @JoinColumn(name = "fk_team_id", nullable = false)
00025     private Team team;
00026
00027     @Column(name = "goal_minute", nullable = false)
00028     private short minute;
00029
00030     @Column(name = "stoppage_minute")
00031     private Short stoppageMinute;
00032 }

```

9.72 Football_Manager/src/main/java/com/example/football_↵ manager/model/Player.java File Reference

```

import com.fasterxml.jackson.annotation.JsonBackReference;
import jakarta.persistence.*;
import lombok.AllArgsConstructor;
import lombok.Data;
import lombok.EqualsAndHashCode;
import lombok.NoArgsConstructor;
import lombok.ToString;

```

Classes

- class [com.example.football_manager.model.Player](#)

Packages

- package [com.example.football_manager.model](#)

9.73 Player.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.model;
00002
00003 import com.fasterxml.jackson.annotation.JsonBackReference;
00004 import jakarta.persistence.*;
00005 import lombok.AllArgsConstructor;
00006 import lombok.Data;
00007 import lombok.EqualsAndHashCode;
00008 import lombok.NoArgsConstructor;
00009 import lombok.ToString;
00010
00011 @Entity
00012 @Table(
00013     name = "player",
00014     uniqueConstraints = @UniqueConstraint(
00015         name = "uk_player_team_number",
00016         columnNames = {"fk_team_id", "number"}
00017     )
00018 )
00019 @Data
00020 @NoArgsConstructor
00021 @AllArgsConstructor
00022 public class Player {
00023
00024     @Id
00025     @GeneratedValue(strategy = GenerationType.IDENTITY)
00026     private Long id;
00027
00028     @Column(nullable = false, length = 30)
00029     private String name;
00030
00031     @Column(nullable = false)
00032     private Integer number;
00033
00034     @Enumerated(EnumType.STRING)
00035     @Column(nullable = false, length = 30)
00036     private PlayerPosition position;
00037
00038     @ManyToOne(fetch = FetchType.LAZY)
00039     @JoinColumn(name = "fk_team_id", nullable = false)
00040     @JsonBackReference
00041     @ToString.Exclude
00042     @EqualsAndHashCode.Exclude
00043     private Team team;
00044 }
00045

```

9.74 Football_Manager/src/main/java/com/example/football_↵ manager/model/PlayerPosition.java File Reference

Classes

- enum [com.example.football_manager.model.PlayerPosition](#)

Packages

- package [com.example.football_manager.model](#)

9.75 PlayerPosition.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.model;
00002
00003 public enum PlayerPosition {
00004     GOALKEEPER,
00005     DEFENDER,
00006     MIDFIELDER,
00007     FORWARD
00008 }

```

9.76 Football_Manager/src/main/java/com/example/football_↵ manager/model/Team.java File Reference

```
import com.fasterxml.jackson.annotation.JsonManagedReference;
import jakarta.persistence.*;
import lombok.AllArgsConstructor;
import lombok.Data;
import lombok.EqualsAndHashCode;
import lombok.NoArgsConstructor;
import lombok.ToString;
import java.util.ArrayList;
import java.util.List;
```

Classes

- class [com.example.football_manager.model.Team](#)

Packages

- package [com.example.football_manager.model](#)

9.77 Team.java

[Go to the documentation of this file.](#)

```
00001 package com.example.football_manager.model;
00002
00003 import com.fasterxml.jackson.annotation.JsonManagedReference;
00004 import jakarta.persistence.*;
00005 import lombok.AllArgsConstructor;
00006 import lombok.Data;
00007 import lombok.EqualsAndHashCode;
00008 import lombok.NoArgsConstructor;
00009 import lombok.ToString;
00010
00011 import java.util.ArrayList;
00012 import java.util.List;
00013
00014 @Entity
00015 @Table(name = "team")
00016 @Data
00017 @NoArgsConstructor
00018 @AllArgsConstructor
00019 public class Team {
00020
00021     @Id
00022     @GeneratedValue(strategy = GenerationType.IDENTITY)
00023     private Long id;
00024
00025     @Column(nullable = false, length = 30)
00026     private String name;
00027
00028     @Column(name = "logo_url", nullable = false, columnDefinition = "TEXT")
00029     private String logoUrl;
00030
00031     @ManyToOne
00032     @JoinColumn(name = "fk_country_id", nullable = false)
00033     private Country country;
00034
00035     @OneToMany(mappedBy = "team", cascade = CascadeType.ALL, orphanRemoval = true)
00036     @OrderBy("number ASC")
00037     @JsonManagedReference
00038     @ToString.Exclude
00039     @EqualsAndHashCode.Exclude
00040     private List<Player> players = new ArrayList<>();
```



```

00041
00042     public Team(Long id, String name, String logoUrl, Country country) {
00043         this.id = id;
00044         this.name = name;
00045         this.logoUrl = logoUrl;
00046         this.country = country;
00047     }
00048 }
00049

```

9.78 Football_Manager/src/main/java/com/example/football_manager/model/User.java File Reference ↩

```

import jakarta.persistence.*;
import lombok.AllArgsConstructor;
import lombok.Data;
import lombok.NoArgsConstructor;
import java.util.Set;

```

Classes

- class [com.example.football_manager.model.User](#)

Packages

- package [com.example.football_manager.model](#)

9.79 User.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.model;
00002
00003 import jakarta.persistence.*;
00004 import lombok.AllArgsConstructor;
00005 import lombok.Data;
00006 import lombok.NoArgsConstructor;
00007
00008 import java.util.Set;
00009
00010 @Entity
00011 @Table(name = "\"user\"")
00012 @Data
00013 @NoArgsConstructor
00014 @AllArgsConstructor
00015 public class User {
00016
00017     @Id
00018     @GeneratedValue(strategy = GenerationType.IDENTITY)
00019     private Long id;
00020
00021     @Column(nullable = false, length = 30)
00022     private String username;
00023
00024     @Column(nullable = false, columnDefinition = "TEXT")
00025     private String email;
00026
00027     @Column(name = "hashed_password", nullable = false, columnDefinition = "TEXT")
00028     private String hashedPassword;
00029
00030     @Column(name = "is_admin", nullable = false)
00031     private Boolean isAdmin = false;
00032
00033     @ManyToMany
00034     @JoinTable(
00035         name = "favourite_team",
00036         joinColumns = @JoinColumn(name = "fk_user_id"),
00037         inverseJoinColumns = @JoinColumn(name = "fk_team_id")
00038     )
00039     private Set<Team> favouriteTeams;
00040 }

```

9.80 Football_Manager/src/main/java/com/example/football_↵ manager/repository/CompetitionRepository.java File Reference

```
import com.example.football_manager.model.Competition;
import org.springframework.data.jpa.repository.JpaRepository;
import org.springframework.stereotype.Repository;
```

Classes

- interface [com.example.football_manager.repository.CompetitionRepository](#)

Packages

- package [com.example.football_manager.repository](#)

9.81 CompetitionRepository.java

[Go to the documentation of this file.](#)

```
00001 package com.example.football_manager.repository;
00002
00003 import com.example.football_manager.model.Competition;
00004 import org.springframework.data.jpa.repository.JpaRepository;
00005 import org.springframework.stereotype.Repository;
00006
00007 @Repository
00008 public interface CompetitionRepository extends JpaRepository<Competition, Long> {}
```

9.82 Football_Manager/src/main/java/com/example/football_↵ manager/repository/CountryRepository.java File Reference

```
import com.example.football_manager.model.Country;
import org.springframework.data.jpa.repository.JpaRepository;
import org.springframework.stereotype.Repository;
```

Classes

- interface [com.example.football_manager.repository.CountryRepository](#)

Packages

- package [com.example.football_manager.repository](#)

9.83 CountryRepository.java

[Go to the documentation of this file.](#)

```
00001 package com.example.football_manager.repository;
00002
00003 import com.example.football_manager.model.Country;
00004 import org.springframework.data.jpa.repository.JpaRepository;
00005 import org.springframework.stereotype.Repository;
00006
00007 @Repository
00008 public interface CountryRepository extends JpaRepository<Country, Long> {
00009 }
00010
```

9.84 Football_Manager/src/main/java/com/example/football_↵ manager/repository/MatchGoalRepository.java File Reference

```
import com.example.football_manager.model.MatchGoal;
import org.springframework.data.jpa.repository.JpaRepository;
import org.springframework.stereotype.Repository;
import java.util.List;
```

Classes

- interface [com.example.football_manager.repository.MatchGoalRepository](#)

Packages

- package [com.example.football_manager.repository](#)

9.85 MatchGoalRepository.java

[Go to the documentation of this file.](#)

```
00001 package com.example.football_manager.repository;
00002
00003 import com.example.football_manager.model.MatchGoal;
00004 import org.springframework.data.jpa.repository.JpaRepository;
00005 import org.springframework.stereotype.Repository;
00006
00007 import java.util.List;
00008
00009 @Repository
00010 public interface MatchGoalRepository extends JpaRepository<MatchGoal, Long> {
00011
00012     void deleteByMatchId(Long matchId);
00013
00014     List<MatchGoal> findByMatchIdOrderByMinuteAscStoppageMinuteAscIdAsc(Long matchId);
00015 }
```

9.86 Football_Manager/src/main/java/com/example/football_↵ manager/repository/MatchRepository.java File Reference

```
import com.example.football_manager.model.Match;
import org.springframework.data.jpa.repository.JpaRepository;
import org.springframework.data.jpa.repository.Query;
import org.springframework.data.repository.query.Param;
import org.springframework.stereotype.Repository;
import java.time.OffsetDateTime;
import java.util.Collection;
import java.util.List;
```

Classes

- interface [com.example.football_manager.repository.MatchRepository](#)

Packages

- package [com.example.football_manager.repository](#)

9.87 MatchRepository.java

[Go to the documentation of this file.](#)

```
00001 package com.example.football_manager.repository;
00002
00003 import com.example.football_manager.model.Match;
00004 import org.springframework.data.jpa.repository.JpaRepository;
00005 import org.springframework.data.jpa.repository.Query;
00006 import org.springframework.data.repository.query.Param;
00007 import org.springframework.stereotype.Repository;
00008
00009 import java.time.OffsetDateTime;
00010 import java.util.Collection;
00011 import java.util.List;
00012
00013 @Repository
00014 public interface MatchRepository extends JpaRepository<Match, Long> {
00015
00016     @Query("""
00017         SELECT m FROM Match m
00018         WHERE (:teamId IS NULL OR m.leftTeam.id = :teamId OR m.rightTeam.id = :teamId)
00019             AND (:finished IS NULL OR m.finished = :finished)
00020             AND (:competitionId IS NULL OR m.competition.id = :competitionId)
00021         """)
00022     List<Match> findByFilters(
00023         @Param("teamId") Long teamId,
00024         @Param("finished") Boolean finished,
00025         @Param("competitionId") Long competitionId
00026     );
00027
00028     List<Match> findByFinishedTrueOrderByDatetimeDesc();
00029
00030     List<Match> findByFinishedTrueAndLeftTeamIdOrFinishedTrueAndRightTeamIdOrderByDatetimeDesc (
00031         Long leftTeamId,
00032         Long rightTeamId
00033     );
00034
00035     List<Match>
00036         findByFinishedFalseAndDatetimeAfterAndLeftTeamIdOrFinishedFalseAndDatetimeAfterAndRightTeamIdOrderByDatetimeAsc (
00037         OffsetDateTime now1,
00038         Long leftTeamId,
00039         OffsetDateTime now2,
00040         Long rightTeamId
00041     );
```

```

00042         List<Match>
00043             findByFinishedFalseAndDatetimeAfterAndLeftTeamIdInOrFinishedFalseAndDatetimeAfterAndRightTeamIdInOrderByDatetimeAsc(
00044                 OffsetDateTime now1,
00045                 Collection<Long> leftTeamIds,
00046                 OffsetDateTime now2,
00047                 Collection<Long> rightTeamIds
00048             );

```

9.88 Football_Manager/src/main/java/com/example/football_manager/repository/PlayerRepository.java File Reference

```

import com.example.football_manager.model.Player;
import org.springframework.data.jpa.repository.JpaRepository;
import org.springframework.stereotype.Repository;
import java.util.List;

```

Classes

- interface [com.example.football_manager.repository.PlayerRepository](#)

Packages

- package [com.example.football_manager.repository](#)

9.89 PlayerRepository.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.repository;
00002
00003 import com.example.football_manager.model.Player;
00004 import org.springframework.data.jpa.repository.JpaRepository;
00005 import org.springframework.stereotype.Repository;
00006
00007 import java.util.List;
00008
00009 @Repository
00010 public interface PlayerRepository extends JpaRepository<Player, Long> {
00011     boolean existsByTeamIdAndNumber(Long teamId, Integer number);
00012
00013     boolean existsByTeamIdAndNumberAndIdNot(Long teamId, Integer number, Long id);
00014
00015     List<Player> findByTeamIdOrderByNumberAsc(Long teamId);
00016
00017     java.util.Optional<Player> findByIdAndTeamId(Long id, Long teamId);
00018 }
00019

```

9.90 Football_Manager/src/main/java/com/example/football_manager/repository/TeamRepository.java File Reference

```

import com.example.football_manager.model.Team;
import org.springframework.data.jpa.repository.JpaRepository;
import org.springframework.stereotype.Repository;
import java.util.List;

```

Classes

- interface [com.example.football_manager.repository.TeamRepository](#)

Packages

- package [com.example.football_manager.repository](#)

9.91 TeamRepository.java

[Go to the documentation of this file.](#)

```
00001 package com.example.football_manager.repository;
00002
00003 import com.example.football_manager.model.Team;
00004 import org.springframework.data.jpa.repository.JpaRepository;
00005 import org.springframework.stereotype.Repository;
00006
00007 import java.util.List;
00008
00009 @Repository
00010 public interface TeamRepository extends JpaRepository<Team, Long> {
00011     List<Team> findByNameContainingIgnoreCase(String name);
00012 }
00013
```

9.92 Football_Manager/src/main/java/com/example/football_↵ manager/repository/UserRepository.java File Reference

```
import com.example.football_manager.model.User;
import org.springframework.data.jpa.repository.EntityGraph;
import org.springframework.data.jpa.repository.JpaRepository;
import org.springframework.stereotype.Repository;
import java.util.Optional;
```

Classes

- interface [com.example.football_manager.repository.UserRepository](#)

Packages

- package [com.example.football_manager.repository](#)

9.93 UserRepository.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.repository;
00002
00003 import com.example.football_manager.model.User;
00004 import org.springframework.data.jpa.repository.EntityGraph;
00005 import org.springframework.data.jpa.repository.JpaRepository;
00006 import org.springframework.stereotype.Repository;
00007
00008 import java.util.Optional;
00009
00010 @Repository
00011 public interface UserRepository extends JpaRepository<User, Long> {
00012     Optional<User> findByUsername(String username);
00013     Optional<User> findByEmail(String email);
00014     @EntityGraph(attributePaths = "favouriteTeams")
00015     Optional<User> findWithFavouriteTeamsById(Long id);
00016     boolean existsByUsername(String username);
00017     boolean existsByEmail(String email);
00018     boolean existsByUsernameAndIdNot(String username, Long id);
00019     boolean existsByEmailAndIdNot(String email, Long id);
00020 }

```

9.94 Football_Manager/src/main/java/com/example/football_↵ manager/service/CompetitionService.java File Reference

```

import com.example.football_manager.dto.CompetitionRequestDTO;
import com.example.football_manager.model.Competition;
import com.example.football_manager.repository.CompetitionRepository;
import org.springframework.stereotype.Service;
import java.util.List;
import java.util.Optional;

```

Classes

- class [com.example.football_manager.service.CompetitionService](#)

Packages

- package [com.example.football_manager.service](#)

9.95 CompetitionService.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.service;
00002
00003 import com.example.football_manager.dto.CompetitionRequestDTO;
00004 import com.example.football_manager.model.Competition;
00005 import com.example.football_manager.repository.CompetitionRepository;
00006 import org.springframework.stereotype.Service;
00007
00008 import java.util.List;
00009 import java.util.Optional;
00010
00011 @Service
00012 public class CompetitionService {
00013
00014     private final CompetitionRepository competitionRepository;

```

```

00015
00016     public CompetitionService(CompetitionRepository competitionRepository) {
00017         this.competitionRepository = competitionRepository;
00018     }
00019
00020     public Competition createCompetition(CompetitionRequestDTO dto) {
00021         Competition competition = new Competition();
00022         competition.setName(dto.getName().trim());
00023         return competitionRepository.save(competition);
00024     }
00025
00026     public Competition updateCompetition(Long id, CompetitionRequestDTO dto) {
00027         Competition competition = competitionRepository.findById(id)
00028             .orElseThrow(() -> new RuntimeException("Competition not found with id: " + id));
00029
00030         competition.setName(dto.getName().trim());
00031         return competitionRepository.save(competition);
00032     }
00033
00034     public Optional<Competition> getCompetitionById(Long id) {
00035         return competitionRepository.findById(id);
00036     }
00037
00038     public List<Competition> getAllCompetitions() {
00039         return competitionRepository.findAll();
00040     }
00041
00042     public void deleteCompetition(Long id) {
00043         Competition competition = competitionRepository.findById(id)
00044             .orElseThrow(() -> new RuntimeException("Competition not found with id: " + id));
00045
00046         competitionRepository.delete(competition);
00047     }
00048 }

```

9.96 Football_Manager/src/main/java/com/example/football_↵ manager/service/CountryService.java File Reference

```

import com.example.football_manager.dto.CountryRequestDTO;
import com.example.football_manager.model.Country;
import com.example.football_manager.repository.CountryRepository;
import org.springframework.stereotype.Service;
import java.util.List;

```

Classes

- class [com.example.football_manager.service.CountryService](#)

Packages

- package [com.example.football_manager.service](#)

9.97 CountryService.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.service;
00002
00003 import com.example.football_manager.dto.CountryRequestDTO;
00004 import com.example.football_manager.model.Country;
00005 import com.example.football_manager.repository.CountryRepository;
00006 import org.springframework.stereotype.Service;
00007

```



```

00008 import java.util.List;
00009
00010 @Service
00011 public class CountryService {
00012
00013     private final CountryRepository countryRepository;
00014
00015     public CountryService(CountryRepository countryRepository) {
00016         this.countryRepository = countryRepository;
00017     }
00018
00019     public Country createCountry(CountryRequestDTO dto) {
00020         Country country = new Country();
00021         country.setName(dto.getName().trim());
00022         return countryRepository.save(country);
00023     }
00024
00025     public List<Country> getAllCountries() {
00026         return countryRepository.findAll();
00027     }
00028
00029     public void deleteCountry(Long id) {
00030         Country country = countryRepository.findById(id)
00031             .orElseThrow(() -> new RuntimeException("Country not found with id: " + id));
00032
00033         countryRepository.delete(country);
00034     }
00035 }

```

9.98 Football_Manager/src/main/java/com/example/football_manager/service/MatchService.java File Reference

```

import com.example.football_manager.dto.MatchRequestDTO;
import com.example.football_manager.dto.MatchResultDTO;
import com.example.football_manager.dto.MatchResultRequestDTO;
import com.example.football_manager.model.Competition;
import com.example.football_manager.model.Match;
import com.example.football_manager.model.MatchGoal;
import com.example.football_manager.model.Team;
import com.example.football_manager.repository.CompetitionRepository;
import com.example.football_manager.repository.MatchGoalRepository;
import com.example.football_manager.repository.MatchRepository;
import com.example.football_manager.repository.TeamRepository;
import org.springframework.stereotype.Service;
import org.springframework.transaction.annotation.Transactional;
import java.time.OffsetDateTime;
import java.time.ZoneId;
import java.util.ArrayList;
import java.util.List;
import java.util.Objects;
import java.util.Optional;
import java.util.Set;

```

Classes

- class [com.example.football_manager.service.MatchService](#)

Packages

- package [com.example.football_manager.service](#)

9.99 MatchService.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.service;
00002
00003 import com.example.football_manager.dto.MatchRequestDTO;
00004 import com.example.football_manager.dto.MatchResultDTO;
00005 import com.example.football_manager.dto.MatchResultRequestDTO;
00006 import com.example.football_manager.model.Competition;
00007 import com.example.football_manager.model.Match;
00008 import com.example.football_manager.model.MatchGoal;
00009 import com.example.football_manager.model.Team;
00010 import com.example.football_manager.repository.CompetitionRepository;
00011 import com.example.football_manager.repository.MatchGoalRepository;
00012 import com.example.football_manager.repository.MatchRepository;
00013 import com.example.football_manager.repository.TeamRepository;
00014
00015 import org.springframework.stereotype.Service;
00016 import org.springframework.transaction.annotation.Transactional;
00017
00018 import java.time.OffsetDateTime;
00019 import java.time.ZoneId;
00020 import java.util.ArrayList;
00021 import java.util.List;
00022 import java.util.Objects;
00023 import java.util.Optional;
00024 import java.util.Set;
00025
00026 @Service
00027 public class MatchService {
00028
00029     private final MatchRepository matchRepository;
00030     private final MatchGoalRepository matchGoalRepository;
00031     private final TeamRepository teamRepository;
00032     private final CompetitionRepository competitionRepository;
00033
00034     public MatchService(
00035         MatchRepository matchRepository,
00036         MatchGoalRepository matchGoalRepository,
00037         TeamRepository teamRepository,
00038         CompetitionRepository competitionRepository
00039     ) {
00040         this.matchRepository = matchRepository;
00041         this.matchGoalRepository = matchGoalRepository;
00042         this.teamRepository = teamRepository;
00043         this.competitionRepository = competitionRepository;
00044     }
00045
00046     @Transactional
00047     public String createMatch(MatchRequestDTO request) {
00048         validateMatchRequest(request, true);
00049
00050         Team homeTeam = teamRepository.findById(request.getHomeTeamId())
00051             .orElseThrow(() -> new IllegalArgumentException("Home team not found with id: " +
00052                 request.getHomeTeamId()));
00053
00054         Team awayTeam = teamRepository.findById(request.getAwayTeamId())
00055             .orElseThrow(() -> new IllegalArgumentException("Away team not found with id: " +
00056                 request.getAwayTeamId()));
00057
00058         Competition competition = competitionRepository.findById(request.getCompetitionId())
00059             .orElseThrow(() -> new IllegalArgumentException("Competition not found with id: " +
00060                 request.getCompetitionId()));
00061
00062         Match match = new Match();
00063         match.setLeftTeam(homeTeam);
00064         match.setRightTeam(awayTeam);
00065         match.setCompetition(competition);
00066         match.setDatetime(request.getKickoffTime().atZone(ZoneId.systemDefault()).toOffsetDateTime());
00067         match.setVenue(request.getVenue().trim());
00068         match.setLeftScore(toShortScore(request.getHomeScore()));
00069         match.setRightScore(toShortScore(request.getAwayScore()));
00070         match.setFinished(request.getStatus() == MatchRequestDTO.MatchStatus.FINISHED);
00071
00072         matchRepository.save(match);
00073
00074         return "Match scheduled successfully.";
00075     }
00076
00077     private void validateMatchRequest(MatchRequestDTO request, boolean competitionRequired) {
00078         if (request == null) {
00079             throw new IllegalArgumentException("Validation Error: Match data is required.");
00080         }
00081     }
00082
00083     private ShortScore toShortScore(int score) {
00084         return score > 9 ? ShortScore.MAX : ShortScore.of(score);
00085     }
00086
00087     private MatchStatus toMatchStatus(MatchRequestDTO.MatchStatus status) {
00088         return MatchStatus.valueOf(status.name());
00089     }
00090
00091     private MatchStatus toMatchStatus(MatchStatus status) {
00092         return status;
00093     }
00094
00095     private MatchStatus toMatchStatus(MatchStatus status) {
00096         return status;
00097     }
00098
00099     private MatchStatus toMatchStatus(MatchStatus status) {
00100         return status;
00101     }
00102
00103     private MatchStatus toMatchStatus(MatchStatus status) {
00104         return status;
00105     }
00106
00107     private MatchStatus toMatchStatus(MatchStatus status) {
00108         return status;
00109     }
00110
00111     private MatchStatus toMatchStatus(MatchStatus status) {
00112         return status;
00113     }
00114
00115     private MatchStatus toMatchStatus(MatchStatus status) {
00116         return status;
00117     }
00118
00119     private MatchStatus toMatchStatus(MatchStatus status) {
00120         return status;
00121     }
00122
00123     private MatchStatus toMatchStatus(MatchStatus status) {
00124         return status;
00125     }
00126
00127     private MatchStatus toMatchStatus(MatchStatus status) {
00128         return status;
00129     }
00130
00131     private MatchStatus toMatchStatus(MatchStatus status) {
00132         return status;
00133     }
00134
00135     private MatchStatus toMatchStatus(MatchStatus status) {
00136         return status;
00137     }
00138
00139     private MatchStatus toMatchStatus(MatchStatus status) {
00140         return status;
00141     }
00142
00143     private MatchStatus toMatchStatus(MatchStatus status) {
00144         return status;
00145     }
00146
00147     private MatchStatus toMatchStatus(MatchStatus status) {
00148         return status;
00149     }
00150
00151     private MatchStatus toMatchStatus(MatchStatus status) {
00152         return status;
00153     }
00154
00155     private MatchStatus toMatchStatus(MatchStatus status) {
00156         return status;
00157     }
00158
00159     private MatchStatus toMatchStatus(MatchStatus status) {
00160         return status;
00161     }
00162
00163     private MatchStatus toMatchStatus(MatchStatus status) {
00164         return status;
00165     }
00166
00167     private MatchStatus toMatchStatus(MatchStatus status) {
00168         return status;
00169     }
00170
00171     private MatchStatus toMatchStatus(MatchStatus status) {
00172         return status;
00173     }
00174
00175     private MatchStatus toMatchStatus(MatchStatus status) {
00176         return status;
00177     }
00178
00179     private MatchStatus toMatchStatus(MatchStatus status) {
00180         return status;
00181     }
00182
00183     private MatchStatus toMatchStatus(MatchStatus status) {
00184         return status;
00185     }
00186
00187     private MatchStatus toMatchStatus(MatchStatus status) {
00188         return status;
00189     }
00190
00191     private MatchStatus toMatchStatus(MatchStatus status) {
00192         return status;
00193     }
00194
00195     private MatchStatus toMatchStatus(MatchStatus status) {
00196         return status;
00197     }
00198
00199     private MatchStatus toMatchStatus(MatchStatus status) {
00200         return status;
00201     }
00202
00203     private MatchStatus toMatchStatus(MatchStatus status) {
00204         return status;
00205     }
00206
00207     private MatchStatus toMatchStatus(MatchStatus status) {
00208         return status;
00209     }
00210
00211     private MatchStatus toMatchStatus(MatchStatus status) {
00212         return status;
00213     }
00214
00215     private MatchStatus toMatchStatus(MatchStatus status) {
00216         return status;
00217     }
00218
00219     private MatchStatus toMatchStatus(MatchStatus status) {
00220         return status;
00221     }
00222
00223     private MatchStatus toMatchStatus(MatchStatus status) {
00224         return status;
00225     }
00226
00227     private MatchStatus toMatchStatus(MatchStatus status) {
00228         return status;
00229     }
00230
00231     private MatchStatus toMatchStatus(MatchStatus status) {
00232         return status;
00233     }
00234
00235     private MatchStatus toMatchStatus(MatchStatus status) {
00236         return status;
00237     }
00238
00239     private MatchStatus toMatchStatus(MatchStatus status) {
00240         return status;
00241     }
00242
00243     private MatchStatus toMatchStatus(MatchStatus status) {
00244         return status;
00245     }
00246
00247     private MatchStatus toMatchStatus(MatchStatus status) {
00248         return status;
00249     }
00250
00251     private MatchStatus toMatchStatus(MatchStatus status) {
00252         return status;
00253     }
00254
00255     private MatchStatus toMatchStatus(MatchStatus status) {
00256         return status;
00257     }
00258
00259     private MatchStatus toMatchStatus(MatchStatus status) {
00260         return status;
00261     }
00262
00263     private MatchStatus toMatchStatus(MatchStatus status) {
00264         return status;
00265     }
00266
00267     private MatchStatus toMatchStatus(MatchStatus status) {
00268         return status;
00269     }
00270
00271     private MatchStatus toMatchStatus(MatchStatus status) {
00272         return status;
00273     }
00274
00275     private MatchStatus toMatchStatus(MatchStatus status) {
00276         return status;
00277     }
00278
00279     private MatchStatus toMatchStatus(MatchStatus status) {
00280         return status;
00281     }
00282
00283     private MatchStatus toMatchStatus(MatchStatus status) {
00284         return status;
00285     }
00286
00287     private MatchStatus toMatchStatus(MatchStatus status) {
00288         return status;
00289     }
00290
00291     private MatchStatus toMatchStatus(MatchStatus status) {
00292         return status;
00293     }
00294
00295     private MatchStatus toMatchStatus(MatchStatus status) {
00296         return status;
00297     }
00298
00299     private MatchStatus toMatchStatus(MatchStatus status) {
00300         return status;
00301     }
00302
00303     private MatchStatus toMatchStatus(MatchStatus status) {
00304         return status;
00305     }
00306
00307     private MatchStatus toMatchStatus(MatchStatus status) {
00308         return status;
00309     }
00310
00311     private MatchStatus toMatchStatus(MatchStatus status) {
00312         return status;
00313     }
00314
00315     private MatchStatus toMatchStatus(MatchStatus status) {
00316         return status;
00317     }
00318
00319     private MatchStatus toMatchStatus(MatchStatus status) {
00320         return status;
00321     }
00322
00323     private MatchStatus toMatchStatus(MatchStatus status) {
00324         return status;
00325     }
00326
00327     private MatchStatus toMatchStatus(MatchStatus status) {
00328         return status;
00329     }
00330
00331     private MatchStatus toMatchStatus(MatchStatus status) {
00332         return status;
00333     }
00334
00335     private MatchStatus toMatchStatus(MatchStatus status) {
00336         return status;
00337     }
00338
00339     private MatchStatus toMatchStatus(MatchStatus status) {
00340         return status;
00341     }
00342
00343     private MatchStatus toMatchStatus(MatchStatus status) {
00344         return status;
00345     }
00346
00347     private MatchStatus toMatchStatus(MatchStatus status) {
00348         return status;
00349     }
00350
00351     private MatchStatus toMatchStatus(MatchStatus status) {
00352         return status;
00353     }
00354
00355     private MatchStatus toMatchStatus(MatchStatus status) {
00356         return status;
00357     }
00358
00359     private MatchStatus toMatchStatus(MatchStatus status) {
00360         return status;
00361     }
00362
00363     private MatchStatus toMatchStatus(MatchStatus status) {
00364         return status;
00365     }
00366
00367     private MatchStatus toMatchStatus(MatchStatus status) {
00368         return status;
00369     }
00370
00371     private MatchStatus toMatchStatus(MatchStatus status) {
00372         return status;
00373     }
00374
00375     private MatchStatus toMatchStatus(MatchStatus status) {
00376         return status;
00377     }
00378
00379     private MatchStatus toMatchStatus(MatchStatus status) {
00380         return status;
00381     }
00382
00383     private MatchStatus toMatchStatus(MatchStatus status) {
00384         return status;
00385     }
00386
00387     private MatchStatus toMatchStatus(MatchStatus status) {
00388         return status;
00389     }
00390
00391     private MatchStatus toMatchStatus(MatchStatus status) {
00392         return status;
00393     }
00394
00395     private MatchStatus toMatchStatus(MatchStatus status) {
00396         return status;
00397     }
00398
00399     private MatchStatus toMatchStatus(MatchStatus status) {
00400         return status;
00401     }
00402
00403     private MatchStatus toMatchStatus(MatchStatus status) {
00404         return status;
00405     }
00406
00407     private MatchStatus toMatchStatus(MatchStatus status) {
00408         return status;
00409     }
00410
00411     private MatchStatus toMatchStatus(MatchStatus status) {
00412         return status;
00413     }
00414
00415     private MatchStatus toMatchStatus(MatchStatus status) {
00416         return status;
00417     }
00418
00419     private MatchStatus toMatchStatus(MatchStatus status) {
00420         return status;
00421     }
00422
00423     private MatchStatus toMatchStatus(MatchStatus status) {
00424         return status;
00425     }
00426
00427     private MatchStatus toMatchStatus(MatchStatus status) {
00428         return status;
00429     }
00430
00431     private MatchStatus toMatchStatus(MatchStatus status) {
00432         return status;
00433     }
00434
00435     private MatchStatus toMatchStatus(MatchStatus status) {
00436         return status;
00437     }
00438
00439     private MatchStatus toMatchStatus(MatchStatus status) {
00440         return status;
00441     }
00442
00443     private MatchStatus toMatchStatus(MatchStatus status) {
00444         return status;
00445     }
00446
00447     private MatchStatus toMatchStatus(MatchStatus status) {
00448         return status;
00449     }
00450
00451     private MatchStatus toMatchStatus(MatchStatus status) {
00452         return status;
00453     }
00454
00455     private MatchStatus toMatchStatus(MatchStatus status) {
00456         return status;
00457     }
00458
00459     private MatchStatus toMatchStatus(MatchStatus status) {
00460         return status;
00461     }
00462
00463     private MatchStatus toMatchStatus(MatchStatus status) {
00464         return status;
00465     }
00466
00467     private MatchStatus toMatchStatus(MatchStatus status) {
00468         return status;
00469     }
00470
00471     private MatchStatus toMatchStatus(MatchStatus status) {
00472         return status;
00473     }
00474
00475     private MatchStatus toMatchStatus(MatchStatus status) {
00476         return status;
00477     }
00478
00479     private MatchStatus toMatchStatus(MatchStatus status) {
00480         return status;
00481     }
00482
00483     private MatchStatus toMatchStatus(MatchStatus status) {
00484         return status;
00485     }
00486
00487     private MatchStatus toMatchStatus(MatchStatus status) {
00488         return status;
00489     }
00490
00491     private MatchStatus toMatchStatus(MatchStatus status) {
00492         return status;
00493     }
00494
00495     private MatchStatus toMatchStatus(MatchStatus status) {
00496         return status;
00497     }
00498
00499     private MatchStatus toMatchStatus(MatchStatus status) {
00500         return status;
00501     }
00502
00503     private MatchStatus toMatchStatus(MatchStatus status) {
00504         return status;
00505     }
00506
00507     private MatchStatus toMatchStatus(MatchStatus status) {
00508         return status;
00509     }
00510
00511     private MatchStatus toMatchStatus(MatchStatus status) {
00512         return status;
00513     }
00514
00515     private MatchStatus toMatchStatus(MatchStatus status) {
00516         return status;
00517     }
00518
00519     private MatchStatus toMatchStatus(MatchStatus status) {
00520         return status;
00521     }
00522
00523     private MatchStatus toMatchStatus(MatchStatus status) {
00524         return status;
00525     }
00526
00527     private MatchStatus toMatchStatus(MatchStatus status) {
00528         return status;
00529     }
00530
00531     private MatchStatus toMatchStatus(MatchStatus status) {
00532         return status;
00533     }
00534
00535     private MatchStatus toMatchStatus(MatchStatus status) {
00536         return status;
00537     }
00538
00539     private MatchStatus toMatchStatus(MatchStatus status) {
00540         return status;
00541     }
00542
00543     private MatchStatus toMatchStatus(MatchStatus status) {
00544         return status;
00545     }
00546
00547     private MatchStatus toMatchStatus(MatchStatus status) {
00548         return status;
00549     }
00550
00551     private MatchStatus toMatchStatus(MatchStatus status) {
00552         return status;
00553     }
00554
00555     private MatchStatus toMatchStatus(MatchStatus status) {
00556         return status;
00557     }
00558
00559     private MatchStatus toMatchStatus(MatchStatus status) {
00560         return status;
00561     }
00562
00563     private MatchStatus toMatchStatus(MatchStatus status) {
00564         return status;
00565     }
00566
00567     private MatchStatus toMatchStatus(MatchStatus status) {
00568         return status;
00569     }
00570
00571     private MatchStatus toMatchStatus(MatchStatus status) {
00572         return status;
00573     }
00574
00575     private MatchStatus toMatchStatus(MatchStatus status) {
00576         return status;
00577     }
00578
00579     private MatchStatus toMatchStatus(MatchStatus status) {
00580         return status;
00581     }
00582
00583     private MatchStatus toMatchStatus(MatchStatus status) {
00584         return status;
00585     }
00586
00587     private MatchStatus toMatchStatus(MatchStatus status) {
00588         return status;
00589     }
00590
00591     private MatchStatus toMatchStatus(MatchStatus status) {
00592         return status;
00593     }
00594
00595     private MatchStatus toMatchStatus(MatchStatus status) {
00596         return status;
00597     }
00598
00599     private MatchStatus toMatchStatus(MatchStatus status) {
00600         return status;
00601     }
00602
00603     private MatchStatus toMatchStatus(MatchStatus status) {
00604         return status;
00605     }
00606
00607     private MatchStatus toMatchStatus(MatchStatus status) {
00608         return status;
00609     }
00610
00611     private MatchStatus toMatchStatus(MatchStatus status) {
00612         return status;
00613     }
00614
00615     private MatchStatus toMatchStatus(MatchStatus status) {
00616         return status;
00617     }
00618
00619     private MatchStatus toMatchStatus(MatchStatus status) {
00620         return status;
00621     }
00622
00623     private MatchStatus toMatchStatus(MatchStatus status) {
00624         return status;
00625     }
00626
00627     private MatchStatus toMatchStatus(MatchStatus status) {
00628         return status;
00629     }
00630
00631     private MatchStatus toMatchStatus(MatchStatus status) {
00632         return status;
00633     }
00634
00635     private MatchStatus toMatchStatus(MatchStatus status) {
00636         return status;
00637     }
00638
00639     private MatchStatus toMatchStatus(MatchStatus status) {
00640         return status;
00641     }
00642
00643     private MatchStatus toMatchStatus(MatchStatus status) {
00644         return status;
00645     }
00646
00647     private MatchStatus toMatchStatus(MatchStatus status) {
00648         return status;
00649     }
00650
00651     private MatchStatus toMatchStatus(MatchStatus status) {
00652         return status;
00653     }
00654
00655     private MatchStatus toMatchStatus(MatchStatus status) {
00656         return status;
00657     }
00658
00659     private MatchStatus toMatchStatus(MatchStatus status) {
00660         return status;
00661     }
00662
00663     private MatchStatus toMatchStatus(MatchStatus status) {
00664         return status;
00665     }
00666
00667     private MatchStatus toMatchStatus(MatchStatus status) {
00668         return status;
00669     }
00670
00671     private MatchStatus toMatchStatus(MatchStatus status) {
00672         return status;
00673     }
00674
00675     private MatchStatus toMatchStatus(MatchStatus status) {
00676         return status;
00677     }
00678
00679     private MatchStatus toMatchStatus(MatchStatus status) {
00680         return status;
00681     }
00682
00683     private MatchStatus toMatchStatus(MatchStatus status) {
00684         return status;
00685     }
00686
00687     private MatchStatus toMatchStatus(MatchStatus status) {
00688         return status;
00689     }
00689

```

```

00080         if (request.getHomeTeamId() == null || request.getAwayTeamId() == null) {
00081             throw new IllegalArgumentException("Validation Error: Both Home and Away team IDs are
required.");
00082         }
00083
00084         if (competitionRequired && request.getCompetitionId() == null) {
00085             throw new IllegalArgumentException("Validation Error: Competition ID is required.");
00086         }
00087
00088         if (request.getKickoffTime() == null || request.getVenue() == null) {
00089             throw new IllegalArgumentException("Validation Error: Kickoff time and Venue are
required.");
00090         }
00091
00092         if (request.getHomeTeamId().equals(request.getAwayTeamId())) {
00093             throw new IllegalArgumentException("Validation Error: Home and Away teams must be
different.");
00094         }
00095
00096         if (request.getStatus() == null) {
00097             request.setStatus(MatchRequestDTO.MatchStatus.SCHEDULED);
00098         }
00099     }
00100
00101     @Transactional
00102     public String updateMatch(Long id, MatchRequestDTO request) {
00103         validateMatchUpdate(request);
00104
00105         Match match = matchRepository.findById(id)
00106             .orElseThrow(() -> new IllegalArgumentException("Match not found"));
00107
00108         Team homeTeam = teamRepository.findById(request.getHomeTeamId())
00109             .orElseThrow(() -> new IllegalArgumentException("Home team not found"));
00110         Team awayTeam = teamRepository.findById(request.getAwayTeamId())
00111             .orElseThrow(() -> new IllegalArgumentException("Away team not found"));
00112
00113         match.setLeftTeam(homeTeam);
00114         match.setRightTeam(awayTeam);
00115
00116         // Actualizamos la fecha usando la zona horaria del sistema de tu compañero
00117         if (request.getKickoffTime() != null) {
00118             match.setDatetime(request.getKickoffTime().atZone(ZoneId.systemDefault()).toOffsetDateTime());
00119         }
00120
00121         // Actualizamos la sede (venue)
00122         if (request.getVenue() != null && !request.getVenue().isBlank()) {
00123             match.setVenue(request.getVenue().trim());
00124         }
00125
00126         match.setFinished(request.getStatus() == MatchRequestDTO.MatchStatus.FINISHED);
00127
00128         if (request.getHomeScore() != null) {
00129             match.setLeftScore(request.getHomeScore().shortValue());
00130         }
00131         if (request.getAwayScore() != null) {
00132             match.setRightScore(request.getAwayScore().shortValue());
00133         }
00134
00135         matchRepository.save(match);
00136
00137         return "Match with ID " + id + " has been updated.";
00138     }
00139
00140     @Transactional
00141     public String deleteMatch(Long id) {
00142         Match match = matchRepository.findById(id)
00143             .orElseThrow(() -> new IllegalArgumentException("Match not found with id: " + id));
00144
00145         matchGoalRepository.deleteByMatchId(id);
00146         matchRepository.delete(match);
00147
00148         return "Match with ID " + id + " has been deleted.";
00149     }
00150
00151     @Transactional
00152     public String registerResult(Long id, MatchResultRequestDTO request) {
00153         if (request == null || request.getGoals() == null) {
00154             throw new IllegalArgumentException("Validation Error: Goals are required.");
00155         }
00156
00157         Match match = matchRepository.findById(id)
00158             .orElseThrow(() -> new IllegalArgumentException("Match not found with id: " + id));
00159
00160         List<MatchGoal> goals = new ArrayList<>();
00161         int leftScore = 0;
00162         int rightScore = 0;

```

```

00163
00164     for (MatchResultRequestDTO.GoalDTO goalDTO : request.getGoals()) {
00165         Team scoringTeam = resolveScoringTeam(match, goalDTO);
00166
00167         if (Objects.equals(scoringTeam.getId(), match.getLeftTeam().getId())) {
00168             leftScore++;
00169         } else {
00170             rightScore++;
00171         }
00172
00173         MatchGoal goal = new MatchGoal();
00174         goal.setMatch(match);
00175         goal.setTeam(scoringTeam);
00176         goal.setMinute(goalDTO.getMinute().shortValue());
00177         goal.setStoppageMinute(toShort(goalDTO.getStoppageMinute()));
00178         goals.add(goal);
00179     }
00180
00181     matchGoalRepository.deleteByMatchId(id);
00182     matchGoalRepository.saveAll(goals);
00183
00184     match.setLeftScore((short) leftScore);
00185     match.setRightScore((short) rightScore);
00186     match.setFinished(true);
00187     matchRepository.save(match);
00188
00189     return "Result registered for match " + id + ": " + leftScore + " - " + rightScore;
00190 }
00191
00192 public List<MatchResultDTO> getFinishedMatchResults() {
00193     List<Match> matches = matchRepository.findByFinishedTrueOrderByDatetimeDesc();
00194
00195     return matches.stream()
00196         .map(match -> new MatchResultDTO(
00197             match.getId(),
00198             match.getLeftTeam().getName(),
00199             match.getRightTeam().getName(),
00200             match.getLeftScore(),
00201             match.getRightScore(),
00202             match.getDatetime()
00203         ))
00204         .toList();
00205 }
00206
00207 public Optional<MatchRequestDTO> getMatchForEdit(Long id) {
00208     if (matchRepository == null) {
00209         return Optional.empty();
00210     }
00211
00212     return matchRepository.findById(id).map(match -> {
00213         MatchRequestDTO dto = new MatchRequestDTO();
00214         dto.setHomeTeamId(match.getLeftTeam().getId());
00215         dto.setAwayTeamId(match.getRightTeam().getId());
00216         dto.setKickoffTime(match.getDatetime().toLocalDateTime());
00217         dto.setVenue(match.getVenue()); // Carga el venue real, no "TBD"
00218         dto.setStatus(match.isFinished()
00219             ? MatchRequestDTO.MatchStatus.FINISHED
00220             : MatchRequestDTO.MatchStatus.SCHEDULED);
00221         dto.setHomeScore((int) match.getLeftScore());
00222         dto.setAwayScore((int) match.getRightScore());
00223         return dto;
00224     });
00225 }
00226
00227 private void validateMatchUpdate(MatchRequestDTO request) {
00228     if (request.getHomeTeamId() == null || request.getAwayTeamId() == null) {
00229         throw new IllegalArgumentException("Validation Error: Both Home and Away team IDs are
00230 required.");
00231     }
00232
00233     if (request.getKickoffTime() == null || request.getVenue() == null ||
00234 request.getVenue().isBlank()) {
00235         throw new IllegalArgumentException("Validation Error: Kickoff time and Venue are
00236 required.");
00237     }
00238
00239     if (request.getStatus() == null) {
00240         throw new IllegalArgumentException("Validation Error: Match status is required.");
00241     }
00242
00243     if (request.getHomeTeamId().equals(request.getAwayTeamId())) {
00244         throw new IllegalArgumentException("Validation Error: Home and Away teams must be
00245 different.");
00246     }
00247
00248     if (request.getHomeScore() != null && request.getAwayScore() == null) {
00249         throw new IllegalArgumentException("Validation Error: Away score is required when home

```

```

        score is provided.");
00246     }
00247
00248     if (request.getAwayScore() != null && request.getHomeScore() == null) {
00249         throw new IllegalArgumentException("Validation Error: Home score is required when away
score is provided.");
00250     }
00251
00252     if (request.getStatus() == MatchRequestDTO.MatchStatus.FINISHED
&& (request.getHomeScore() == null || request.getAwayScore() == null)) {
00253         throw new IllegalArgumentException("Validation Error: Both scores are required when status
is FINISHED.");
00254     }
00255
00256     if (request.getStatus() != MatchRequestDTO.MatchStatus.FINISHED
&& (request.getHomeScore() != null || request.getAwayScore() != null)) {
00257         throw new IllegalArgumentException("Validation Error: Scores can only be submitted when
status is FINISHED.");
00258     }
00259
00260 } // <-- ESTA ES LA LLAVE QUE FALTABA
00261
00262 public List<Match> getAllMatches() {
00263     return matchRepository.findAll();
00264 }
00265
00266 public List<Match> getMatches(Long teamId, MatchRequestDTO.MatchStatus status, Long competitionId)
{
00267     Boolean finished = toFinishedFilter(status);
00268
00269     if (teamId == null && finished == null && competitionId == null) {
00270         return getAllMatches();
00271     }
00272
00273     return matchRepository.findByFilters(teamId, finished, competitionId);
00274 }
00275
00276 public Match getMatchById(Long id) {
00277     return matchRepository.findById(id)
00278         .orElseThrow(() -> new IllegalArgumentException("Match not found with id: " + id));
00279 }
00280
00281 public List<MatchGoal> getGoalsByMatchId(Long matchId) {
00282     return matchGoalRepository.findByMatchIdOrderByMinuteAscStoppageMinuteAscIdAsc(matchId);
00283 }
00284
00285 public List<Match> getRecentMatchesByTeamId(Long teamId) {
00286     return matchRepository
00287         .findByFinishedTrueAndLeftTeamIdOrFinishedTrueAndRightTeamIdOrderByDatetimeDesc(
00288             teamId,
00289             teamId
00290         );
00291 }
00292
00293 public List<Match> getFutureMatchesByTeamId(Long teamId) {
00294     OffsetDateTime now = OffsetDateTime.now();
00295
00296     return matchRepository
00297         .findByFinishedFalseAndDatetimeAfterAndLeftTeamIdOrFinishedFalseAndDatetimeAfterAndRightTeamIdOrderByDatetimeAsc(
00298             now,
00299             teamId,
00300             now,
00301             teamId
00302         );
00303 }
00304
00305 public List<Match> getFutureMatchesByFavouriteTeamIds(Set<Long> favouriteTeamIds) {
00306     if (favouriteTeamIds == null || favouriteTeamIds.isEmpty()) {
00307         return List.of();
00308     }
00309
00310     OffsetDateTime now = OffsetDateTime.now();
00311
00312     return matchRepository
00313         .findByFinishedFalseAndDatetimeAfterAndLeftTeamIdInOrFinishedFalseAndDatetimeAfterAndRightTeamIdInOrderByDatetimeAsc(
00314             now,
00315             favouriteTeamIds,
00316             now,
00317             favouriteTeamIds
00318         );
00319 }
00320
00321 private Team resolveScoringTeam(Match match, MatchResultRequestDTO.GoalDTO goalDTO) {
00322     if (goalDTO == null || goalDTO.getTeamId() == null || goalDTO.getMinute() == null) {
00323         throw new IllegalArgumentException("Validation Error: Every goal must include team ID and
minute.");
00324     }

```

```

00325     }
00326
00327     if (goalDTO.getMinute() < 1 || goalDTO.getMinute() > 120) {
00328         throw new IllegalArgumentException("Validation Error: Goal minute must be between 1 and
120.");
00329     }
00330
00331     if (goalDTO.getStoppageMinute() != null
00332         && (goalDTO.getStoppageMinute() < 0 || goalDTO.getStoppageMinute() > 30)) {
00333         throw new IllegalArgumentException("Validation Error: Stoppage minute must be between 0
and 30.");
00334     }
00335
00336     if (Objects.equals(goalDTO.getTeamId(), match.getLeftTeam().getId())) {
00337         return match.getLeftTeam();
00338     }
00339
00340     if (Objects.equals(goalDTO.getTeamId(), match.getRightTeam().getId())) {
00341         return match.getRightTeam();
00342     }
00343
00344     throw new IllegalArgumentException("Validation Error: Scoring team must belong to the
match.");
00345 }
00346
00347 private Short toShort(Integer value) {
00348     return value == null ? null : value.shortValue();
00349 }
00350
00351 private short toShortScore(Integer score) {
00352     if (score == null) {
00353         return 0;
00354     }
00355
00356     if (score < 0 || score > Short.MAX_VALUE) {
00357         throw new IllegalArgumentException("Validation Error: Score must be a positive number.");
00358     }
00359
00360     return score.shortValue();
00361 }
00362
00363 private Boolean toFinishedFilter(MatchRequestDTO.MatchStatus status) {
00364     if (status == null) {
00365         return null;
00366     }
00367
00368     return switch (status) {
00369         case FINISHED -> true;
00370         case SCHEDULED -> false;
00371         default -> throw new IllegalArgumentException("Validation Error: Match status filter must
be FINISHED or SCHEDULED.");
00372     };
00373 }
00374 }

```

9.100 Football_Manager/src/main/java/com/example/football_↵ manager/service/PlayerService.java File Reference

```

import com.example.football_manager.dto.PlayerRequestDTO;
import com.example.football_manager.model.Player;
import com.example.football_manager.model.Team;
import com.example.football_manager.repository.PlayerRepository;
import com.example.football_manager.repository.TeamRepository;
import org.springframework.stereotype.Service;
import java.util.List;

```

Classes

- class [com.example.football_manager.service.PlayerService](#)

Packages

- package [com.example.football_manager.service](#)

9.101 PlayerService.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.service;
00002
00003 import com.example.football_manager.dto.PlayerRequestDTO;
00004 import com.example.football_manager.model.Player;
00005 import com.example.football_manager.model.Team;
00006 import com.example.football_manager.repository.PlayerRepository;
00007 import com.example.football_manager.repository.TeamRepository;
00008 import org.springframework.stereotype.Service;
00009
00010 import java.util.List;
00011
00012 @Service
00013 public class PlayerService {
00014
00015     private final PlayerRepository playerRepository;
00016     private final TeamRepository teamRepository;
00017
00018     public PlayerService(PlayerRepository playerRepository, TeamRepository teamRepository) {
00019         this.playerRepository = playerRepository;
00020         this.teamRepository = teamRepository;
00021     }
00022
00023     public Player createPlayer(Long teamId, PlayerRequestDTO dto) {
00024         validatePlayerRequest(teamId, dto);
00025
00026         Team team = teamRepository.findById(teamId)
00027             .orElseThrow(() -> new IllegalArgumentException("Team not found with id: " + teamId));
00028
00029         if (playerRepository.existsByTeamIdAndNumber(teamId, dto.getNumber())) {
00030             throw new IllegalArgumentException(
00031                 "Validation Error: Team already has a player with number " + dto.getNumber() + "."
00032             );
00033         }
00034
00035         Player player = new Player();
00036         player.setName(dto.getName().trim());
00037         player.setNumber(dto.getNumber());
00038         player.setPosition(dto.getPosition());
00039         player.setTeam(team);
00040
00041         Player savedPlayer = playerRepository.save(player);
00042         team.getPlayers().add(savedPlayer);
00043
00044         return savedPlayer;
00045     }
00046
00047     public List<Player> getPlayersByTeamId(Long teamId) {
00048         if (teamId == null) {
00049             throw new IllegalArgumentException("Validation Error: Team ID is required.");
00050         }
00051
00052         if (!teamRepository.existsById(teamId)) {
00053             throw new IllegalArgumentException("Team not found with id: " + teamId);
00054         }
00055
00056         return playerRepository.findByTeamIdOrderByNumberAsc(teamId);
00057     }
00058
00059     public Player getPlayerByTeamId(Long teamId, Long playerId) {
00060         if (teamId == null) {
00061             throw new IllegalArgumentException("Validation Error: Team ID is required.");
00062         }
00063
00064         if (playerId == null) {
00065             throw new IllegalArgumentException("Validation Error: Player ID is required.");
00066         }
00067
00068         if (!teamRepository.existsById(teamId)) {
00069             throw new IllegalArgumentException("Team not found with id: " + teamId);
00070         }
00071
00072         return playerRepository.findByIdAndTeamId(playerId, teamId)
00073             .orElseThrow(() -> new IllegalArgumentException(

```

```

00074         "Player not found with id: " + playerId + " for team id: " + teamId
00075     );
00076 }
00077
00078 public Player updatePlayer(Long teamId, Long playerId, PlayerRequestDTO dto) {
00079     validatePlayerRequest(teamId, dto);
00080
00081     if (playerId == null) {
00082         throw new IllegalArgumentException("Validation Error: Player ID is required.");
00083     }
00084
00085     Team team = teamRepository.findById(teamId)
00086         .orElseThrow(() -> new IllegalArgumentException("Team not found with id: " + teamId));
00087
00088     Player player = playerRepository.findByIdAndTeamId(playerId, teamId)
00089         .orElseThrow(() -> new IllegalArgumentException(
00090             "Player not found with id: " + playerId + " for team id: " + teamId
00091         ));
00092
00093     if (playerRepository.existsByTeamIdAndNumberAndIdNot(teamId, dto.getNumber(), playerId)) {
00094         throw new IllegalArgumentException(
00095             "Validation Error: Team already has a player with number " + dto.getNumber() + "."
00096         );
00097     }
00098
00099     player.setName(dto.getName().trim());
00100     player.setNumber(dto.getNumber());
00101     player.setPosition(dto.getPosition());
00102     player.setTeam(team);
00103
00104     return playerRepository.save(player);
00105 }
00106
00107 public void deletePlayer(Long teamId, Long playerId) {
00108     if (teamId == null) {
00109         throw new IllegalArgumentException("Validation Error: Team ID is required.");
00110     }
00111
00112     if (playerId == null) {
00113         throw new IllegalArgumentException("Validation Error: Player ID is required.");
00114     }
00115
00116     Team team = teamRepository.findById(teamId)
00117         .orElseThrow(() -> new IllegalArgumentException("Team not found with id: " + teamId));
00118
00119     Player player = playerRepository.findByIdAndTeamId(playerId, teamId)
00120         .orElseThrow(() -> new IllegalArgumentException(
00121             "Player not found with id: " + playerId + " for team id: " + teamId
00122         ));
00123
00124     team.getPlayers().remove(player);
00125     playerRepository.delete(player);
00126 }
00127
00128 private void validatePlayerRequest(Long teamId, PlayerRequestDTO dto) {
00129     if (teamId == null) {
00130         throw new IllegalArgumentException("Validation Error: Team ID is required.");
00131     }
00132
00133     if (dto == null) {
00134         throw new IllegalArgumentException("Validation Error: Player data is required.");
00135     }
00136
00137     if (dto.getName() == null || dto.getName().trim().isEmpty()) {
00138         throw new IllegalArgumentException("Validation Error: Player name is required.");
00139     }
00140
00141     if (dto.getName().trim().length() > 30) {
00142         throw new IllegalArgumentException("Validation Error: Player name must be at most 30
00143 characters.");
00144     }
00145
00146     if (dto.getNumber() == null) {
00147         throw new IllegalArgumentException("Validation Error: Player number is required.");
00148     }
00149
00150     if (dto.getNumber() <= 0) {
00151         throw new IllegalArgumentException("Validation Error: Player number must be greater than
00152 0.");
00153     }
00154
00155     if (dto.getPosition() == null) {
00156         throw new IllegalArgumentException("Validation Error: Player position is required.");
00157     }

```


9.102 Football_Manager/src/main/java/com/example/football_manager/service/TeamService.java File Reference

```
import com.example.football_manager.dto.TeamRequestDTO;
import com.example.football_manager.model.Country;
import com.example.football_manager.model.Team;
import com.example.football_manager.repository.CountryRepository;
import com.example.football_manager.repository.TeamRepository;
import java.util.List;
import java.util.Optional;
import org.springframework.stereotype.Service;
```

Classes

- class [com.example.football_manager.service.TeamService](#)

Packages

- package [com.example.football_manager.service](#)

9.103 TeamService.java

[Go to the documentation of this file.](#)

```
00001 package com.example.football_manager.service;
00002
00003 import com.example.football_manager.dto.TeamRequestDTO;
00004 import com.example.football_manager.model.Country;
00005 import com.example.football_manager.model.Team;
00006 import com.example.football_manager.repository.CountryRepository;
00007 import com.example.football_manager.repository.TeamRepository;
00008
00009 import java.util.List;
00010 import java.util.Optional;
00011
00012 import org.springframework.stereotype.Service;
00013
00014 @Service
00015 public class TeamService {
00016
00017     private final TeamRepository teamRepository;
00018     private final CountryRepository countryRepository;
00019
00020     public TeamService(TeamRepository teamRepository, CountryRepository countryRepository) {
00021         this.teamRepository = teamRepository;
00022         this.countryRepository = countryRepository;
00023     }
00024
00025     public Team createTeam(TeamRequestDTO dto) {
00026         Country country = countryRepository.findById(dto.getCountryId())
00027             .orElseThrow(() -> new RuntimeException("Country not found with id: " +
00028                 dto.getCountryId()));
00029         Team team = new Team();
00030         team.setName(dto.getName().trim());
00031         team.setLogoUrl(dto.getLogoUrl().trim());
00032         team.setCountry(country);
00033
00034         return teamRepository.save(team);
00035     }
00036
00037     public Team updateTeam(Long id, TeamRequestDTO dto) {
00038         Team existingTeam = teamRepository.findById(id)
00039             .orElseThrow(() -> new RuntimeException("Team not found with id: " + id));
00040
00041         Country country = countryRepository.findById(dto.getCountryId())
```

```

00042         .orElseThrow(() -> new RuntimeException("Country not found with id: " +
00043         dto.getCountryId()));
00044         existingTeam.setName(dto.getName().trim());
00045         existingTeam.setLogoUrl(dto.getLogoUrl().trim());
00046         existingTeam.setCountry(country);
00047
00048         return teamRepository.save(existingTeam);
00049     }
00050
00051     public void deleteTeam(Long id) {
00052         Team existingTeam = teamRepository.findById(id)
00053             .orElseThrow(() -> new RuntimeException("Team not found with id: " + id));
00054
00055         teamRepository.delete(existingTeam);
00056     }
00057
00058     public Optional<Team> getTeamById(Long id) {
00059         return teamRepository.findById(id);
00060     }
00061
00062     public List<Team> getTeamsContainingName(String name) {
00063         if (name == null || name.trim().isEmpty()) {
00064             return List.of();
00065         }
00066         return teamRepository.findByNameContainingIgnoreCase(name.trim());
00067     }
00068
00069     public List<Team> getAllTeams() {
00070         return teamRepository.findAll();
00071     }
00072 }

```

9.104 Football_Manager/src/main/java/com/example/football_↵ manager/service/UserService.java File Reference

```

import com.example.football_manager.model.Team;
import com.example.football_manager.model.User;
import com.example.football_manager.repository.TeamRepository;
import com.example.football_manager.repository.UserRepository;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.security.crypto.password.PasswordEncoder;
import org.springframework.stereotype.Service;
import java.util.Collections;
import java.util.HashSet;
import java.util.Objects;
import java.util.Set;
import java.util.stream.Collectors;

```

Classes

- class [com.example.football_manager.service.UserService](#)

Packages

- package [com.example.football_manager.service](#)

9.105 UserService.java

[Go to the documentation of this file.](#)

```

00001 package com.example.football_manager.service;
00002
00003 import com.example.football_manager.model.Team;
00004 import com.example.football_manager.model.User;
00005 import com.example.football_manager.repository.TeamRepository;
00006 import com.example.football_manager.repository.UserRepository;
00007 import org.springframework.beans.factory.annotation.Autowired;
00008 import org.springframework.security.crypto.password.PasswordEncoder;
00009 import org.springframework.stereotype.Service;
00010
00011 import java.util.Collections;
00012 import java.util.HashSet;
00013 import java.util.Objects;
00014 import java.util.Set;
00015 import java.util.stream.Collectors;
00016
00017 @Service
00018 public class UserService {
00019
00020     @Autowired
00021     private UserRepository userRepository;
00022
00023     @Autowired
00024     private TeamRepository teamRepository;
00025
00026     @Autowired
00027     private PasswordEncoder passwordEncoder;
00028
00029     public User registerUser(String username, String email, String rawPassword, Boolean isAdmin) {
00030         if (userRepository.existsByUsername(username)) {
00031             throw new IllegalArgumentException("Username already in use");
00032         }
00033
00034         if (userRepository.existsByEmail(email)) {
00035             throw new IllegalArgumentException("Email already in use");
00036         }
00037
00038         User user = new User();
00039         user.setUsername(username);
00040         user.setEmail(email);
00041         user.setHashedPassword(passwordEncoder.encode(rawPassword));
00042         user.setIsAdmin(Boolean.TRUE.equals(isAdmin));
00043
00044         return userRepository.save(user);
00045     }
00046
00047     public User login(String username, String rawPassword) {
00048         User user = userRepository.findById(username)
00049             .orElseThrow(() -> new IllegalArgumentException("Invalid credentials"));
00050
00051         if (!passwordEncoder.matches(rawPassword, user.getHashedPassword())) {
00052             throw new IllegalArgumentException("Invalid credentials");
00053         }
00054
00055         return user;
00056     }
00057
00058     public User getUserById(Long id) {
00059         return userRepository.findById(id)
00060             .orElseThrow(() -> new IllegalArgumentException("User not found"));
00061     }
00062
00063     public User getUserByUsername(String username) {
00064         return userRepository.findByUsername(username)
00065             .orElseThrow(() -> new IllegalArgumentException("User not found"));
00066     }
00067
00068     public User addFavouriteTeam(Long userId, Long teamId) {
00069         User user = getUserById(userId);
00070         Team team = teamRepository.findById(teamId)
00071             .orElseThrow(() -> new IllegalArgumentException("Team not found"));
00072
00073         Set<Team> favouriteTeams = user.getFavouriteTeams();
00074         if (favouriteTeams == null) {
00075             favouriteTeams = new HashSet<>();
00076             user.setFavouriteTeams(favouriteTeams);
00077         }
00078
00079         if (!favouriteTeams.add(team)) {
00080             throw new IllegalArgumentException("Team already in favourites");
00081         }
00082     }

```

```

00083         return userRepository.save(user);
00084     }
00085
00086     public User removeFavouriteTeam(Long userId, Long teamId) {
00087         User user = getUserById(userId);
00088
00089         if (!userRepository.existsById(teamId)) {
00090             throw new IllegalArgumentException("Team not found");
00091         }
00092
00093         Set<Team> favouriteTeams = user.getFavouriteTeams();
00094         if (favouriteTeams == null || favouriteTeams.isEmpty()) {
00095             throw new IllegalArgumentException("Team not in favourites");
00096         }
00097
00098         boolean removed = favouriteTeams.removeIf(team -> teamId.equals(team.getId()));
00099         if (!removed) {
00100             throw new IllegalArgumentException("Team not in favourites");
00101         }
00102
00103         return userRepository.save(user);
00104     }
00105
00106     public Set<Long> getFavouriteTeamIdsByUserId(Long userId) {
00107         if (userId == null) {
00108             return Collections.emptySet();
00109         }
00110
00111         User user = getUserById(userId);
00112         Set<Team> favouriteTeams = user.getFavouriteTeams();
00113         if (favouriteTeams == null || favouriteTeams.isEmpty()) {
00114             return Collections.emptySet();
00115         }
00116
00117         return favouriteTeams.stream()
00118             .map(Team::getId)
00119             .collect(Collectors.toSet());
00120     }
00121
00122     public User getUserProfile(Long userId) {
00123         return userRepository.findWithFavouriteTeamsById(userId)
00124             .orElseThrow(() -> new IllegalArgumentException("User not found"));
00125     }
00126
00127     public User updateProfile(Long userId,
00128                             String username,
00129                             String email,
00130                             String currentPassword,
00131                             String newPassword,
00132                             String confirmNewPassword) {
00133         User user = getUserById(userId);
00134
00135         String normalizedUsername = normalizeField(username, "Username is required");
00136         String normalizedEmail = normalizeField(email, "Email is required");
00137
00138         if (userRepository.existsByUsernameAndIdNot(normalizedUsername, userId)) {
00139             throw new IllegalArgumentException("Username already in use");
00140         }
00141
00142         if (userRepository.existsByEmailAndIdNot(normalizedEmail, userId)) {
00143             throw new IllegalArgumentException("Email already in use");
00144         }
00145
00146         if (!Objects.equals(user.getUsername(), normalizedUsername)) {
00147             user.setUsername(normalizedUsername);
00148         }
00149
00150         if (!Objects.equals(user.getEmail(), normalizedEmail)) {
00151             user.setEmail(normalizedEmail);
00152         }
00153
00154         if (isPasswordChangeRequested(currentPassword, newPassword, confirmNewPassword)) {
00155             if (isBlank(currentPassword)) {
00156                 throw new IllegalArgumentException("Current password is required");
00157             }
00158             if (isBlank(newPassword) || isBlank(confirmNewPassword)) {
00159                 throw new IllegalArgumentException("New password and confirmation are required");
00160             }
00161             if (!newPassword.equals(confirmNewPassword)) {
00162                 throw new IllegalArgumentException("New passwords do not match");
00163             }
00164             if (newPassword.length() < 8) {
00165                 throw new IllegalArgumentException("New password must be at least 8 characters");
00166             }
00167             if (!passwordEncoder.matches(currentPassword, user.getHashedPassword())) {
00168                 throw new IllegalArgumentException("Current password is incorrect");
00169             }

```

```
00170
00171         user.setHashedPassword(passwordEncoder.encode(newPassword));
00172     }
00173
00174     return userRepository.save(user);
00175 }
00176
00177 private boolean isPasswordChangeRequested(String currentPassword, String newPassword, String
confirmNewPassword) {
00178     return !isBlank(currentPassword) || !isBlank(newPassword) || !isBlank(confirmNewPassword);
00179 }
00180
00181 private boolean isBlank(String value) {
00182     return value == null || value.isBlank();
00183 }
00184
00185 private String normalizeField(String value, String message) {
00186     if (value == null || value.trim().isEmpty()) {
00187         throw new IllegalArgumentException(message);
00188     }
00189     return value.trim();
00190 }
00191 }
```

9.106 README.md File Reference

Index

addFavouriteTeam
 com.example.football_manager.controller.FavouriteTeamController, [18](#)
 com.example.football_manager.service.UserService, [78](#)

addInterceptors
 com.example.football_manager.config.LocaleConfig, [38](#)

AdminCountryViewController
 com.example.football_manager.controller.AdminCountryViewController, [17](#)

adminPanel
 com.example.football_manager.controller.AdminViewController, [23](#)

AdminPlayerViewController
 com.example.football_manager.controller.AdminPlayerViewController, [19](#)

AdminUserViewController
 com.example.football_manager.controller.AdminUserViewController, [22](#)

AuthResponseDTO
 com.example.football_manager.dto.AuthResponseDTO, [24](#)

BSPQ26-E6, [1](#)

CANCELLED
 com.example.football_manager.dto.MatchRequestDTO.MatchStatus, [52](#)

com.example.football_manager, [13](#)

com.example.football_manager.config, [13](#)

com.example.football_manager.config.AdminSecurityFilter, [21](#)

 doFilter, [21](#)

com.example.football_manager.config.LocaleConfig, [38](#)

 addInterceptors, [38](#)

 localeChangeInterceptor, [38](#)

 localeResolver, [38](#)

com.example.football_manager.config.OpenApiConfig, [56](#)

com.example.football_manager.config.SecurityConfig, [66](#)

 filterChain, [67](#)

 passwordEncoder, [67](#)

com.example.football_manager.controller, [14](#)

com.example.football_manager.controller.AdminCountryViewController, [17](#)

 AdminCountryViewController, [17](#)

 countriesPage, [17](#)

 createCountry, [17](#)

 deleteCountry, [18](#)

 updateCountry, [18](#)

com.example.football_manager.controller.AdminPlayerViewController, [19](#)

 createPlayer, [19](#)

 deletePlayer, [19](#)

 managePlayersLanding, [19](#)

 manageTeamPlayers, [19](#)

 showEditPlayerForm, [20](#)

com.example.football_manager.controller.AdminUserViewController, [22](#)

 createUser, [22](#)

 usersPage, [22](#)

com.example.football_manager.controller.AdminViewController, [22](#)

 adminPanel, [23](#)

 manageTeams, [23](#)

com.example.football_manager.controller.AuthController, [23](#)

 login, [24](#)

 register, [24](#)

com.example.football_manager.controller.AuthViewController, [25](#)

 index, [26](#)

 loginPage, [26](#)

 registerPage, [26](#)

com.example.football_manager.controller.CompetitionController, [27](#)

 CompetitionController, [27](#)

 createCompetition, [27](#)

 deleteCompetition, [27](#)

 getAllCompetitions, [27](#)

 getCompetitionById, [28](#)

 updateCompetition, [28](#)

com.example.football_manager.controller.CountryController, [31](#)

 CountryController, [32](#)

 createCountry, [32](#)

 deleteCountry, [32](#)

 getAllCountries, [32](#)

com.example.football_manager.controller.FavouriteTeamController, [35](#)

 addFavouriteTeam, [35](#)

 FavouriteTeamController, [35](#)

 removeFavouriteTeam, [35](#)

com.example.football_manager.controller.MatchController, [40](#)

- createMatchFromForm, 40
- createMatchFromJson, 40
- deleteMatch, 40
- getMatches, 41
- getMatchResults, 41
- registerResult, 41
- updateMatch, 41
- com.example.football_manager.controller.MatchViewController, CountryRequestDTO, 33
 - 53
 - MatchViewController, 53
 - saveMatchResult, 54
 - showEditForm, 54
 - showMatchesPage, 54
 - showResultsPage, 54
 - showScheduleForm, 54
 - showScoreForm, 55
 - submitScoreForm, 55
 - updateMatch, 55
- com.example.football_manager.controller.PlayerController, 56
 - createPlayer, 57
 - deletePlayer, 57
 - getPlayersByTeamId, 57
 - PlayerController, 56
 - updatePlayer, 57
- com.example.football_manager.controller.ProfileViewController, 63
 - profilePage, 64
 - ProfileViewController, 64
 - updateProfile, 64
- com.example.football_manager.controller.TeamController, 68
 - createTeam, 68
 - deleteTeam, 68
 - getAllTeams, 68
 - getTeamById, 68
 - getTeamsContainingName, 69
 - TeamController, 68
 - updateTeam, 69
- com.example.football_manager.controller.TeamViewController, 73
 - createTeam, 74
 - deleteTeam, 74
 - showAddTeamForm, 74
 - showEditTeamForm, 74
 - teamDetailsPage, 74
 - teamsPage, 75
 - updateTeam, 75
- com.example.football_manager.dto, 14
 - MatchResultDTO, 15
- com.example.football_manager.dto.AuthResponseDTO, 24
 - AuthResponseDTO, 24
 - getEmail, 25
 - getId, 25
 - getIsAdmin, 25
 - getMessage, 25
 - getUsername, 25
- com.example.football_manager.dto.CompetitionRequestDTO, 29
 - CompetitionRequestDTO, 29
 - getName, 29
 - setName, 29
- com.example.football_manager.dto.CountryRequestDTO, 33
 - 33
 - getName, 33
 - setName, 33
- com.example.football_manager.dto.LoginDTO, 39
 - getPassword, 39
 - getUsername, 39
 - setPassword, 39
 - setUsername, 39
- com.example.football_manager.dto.MatchRequestDTO, 44
 - 44
 - getAwayScore, 45
 - getAwayTeamId, 45
 - getCompetitionId, 45
 - getHomeScore, 45
 - getHomeTeamId, 46
 - getKickoffTime, 46
 - getStatus, 46
 - getVenue, 46
 - setAwayScore, 46
 - setAwayTeamId, 46
 - setCompetitionId, 47
 - setHomeScore, 47
 - setHomeTeamId, 47
 - setKickoffTime, 47
 - setStatus, 47
 - setVenue, 47
- com.example.football_manager.dto.MatchRequestDTO.MatchStatus, 52
 - 52
 - CANCELLED, 52
 - FINISHED, 52
 - IN_PROGRESS, 52
 - SCHEDULED, 53
- com.example.football_manager.dto.MatchResultRequestDTO, 48
 - 48
 - getGoals, 48
 - setGoals, 48
- com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO, 36
 - 36
 - getMinute, 37
 - getStoppageMinute, 37
 - getTeamId, 37
 - setMinute, 37
 - setStoppageMinute, 37
 - setTeamId, 37
- com.example.football_manager.dto.PlayerRequestDTO, 60
 - 60
 - getName, 60
 - getNumber, 60
 - getPosition, 60
 - PlayerRequestDTO, 60
 - setName, 61

- setNumber, [61](#)
- setPosition, [61](#)
- com.example.football_manager.dto.ProfileUpdateDTO, [63](#)
- isPasswordConfirmationValid, [63](#)
- com.example.football_manager.dto.RegisterDTO, [65](#)
- getEmail, [65](#)
- getIsAdmin, [65](#)
- getPassword, [65](#)
- getUsername, [65](#)
- setEmail, [65](#)
- setIsAdmin, [66](#)
- setPassword, [66](#)
- setUsername, [66](#)
- com.example.football_manager.dto.TeamRequestDTO, [70](#)
- getCountryId, [71](#)
- getLogoUrl, [71](#)
- getName, [71](#)
- setCountryId, [71](#)
- setLogoUrl, [71](#)
- setName, [71](#)
- TeamRequestDTO, [70](#)
- com.example.football_manager.FootballManagerApplication, [36](#)
- main, [36](#)
- com.example.football_manager.model, [15](#)
- com.example.football_manager.model.Competition, [26](#)
- com.example.football_manager.model.Country, [31](#)
- com.example.football_manager.model.Match, [40](#)
- com.example.football_manager.model.MatchGoal, [42](#)
- com.example.football_manager.model.Player, [56](#)
- com.example.football_manager.model.PlayerPosition, [57](#)
- DEFENDER, [58](#)
- FORWARD, [58](#)
- GOALKEEPER, [58](#)
- MIDFIELDER, [58](#)
- com.example.football_manager.model.Team, [67](#)
- Team, [67](#)
- com.example.football_manager.model.User, [75](#)
- com.example.football_manager.repository, [15](#)
- com.example.football_manager.repository.CompetitionRepository, [28](#)
- com.example.football_manager.repository.CountryRepository, [32](#)
- com.example.football_manager.repository.MatchGoalRepository, [42](#)
- deleteByMatchId, [42](#)
- findByMatchIdOrderByMinuteAscStoppageMinuteAsc, [42](#)
- com.example.football_manager.repository.MatchRepository, [43](#)
- findByFilters, [43](#)
- findByFinishedFalseAndDatetimeAfterAndLeftTeamIdInOrFinishedFalseAndDatetimeAfterAndRightTeamIdOrderByDatetimeAsc, [43](#)
- findByFinishedFalseAndDatetimeAfterAndLeftTeamIdOrFinishedFalseAndDatetimeAfterAndRightTeamIdOrderByDatetimeAsc, [43](#)
- findByFinishedTrueAndLeftTeamIdOrFinishedTrueAndRightTeamIdOrderByDatetimeDesc, [44](#)
- findByFinishedTrueOrderByDatetimeDesc, [44](#)
- com.example.football_manager.repository.PlayerRepository, [58](#)
- existsByTeamIdAndNumber, [59](#)
- existsByTeamIdAndNumberAndIdNot, [59](#)
- findByIdAndTeamId, [59](#)
- findByTeamIdOrderByNumberAsc, [59](#)
- com.example.football_manager.repository.TeamRepository, [69](#)
- findByNameContainingIgnoreCase, [70](#)
- com.example.football_manager.repository.UserRepository, [76](#)
- existsByEmail, [76](#)
- existsByEmailAndIdNot, [76](#)
- existsByUsername, [76](#)
- existsByUsernameAndIdNot, [77](#)
- findByEmail, [77](#)
- findByUsername, [77](#)
- findWithFavouriteTeamsById, [77](#)
- com.example.football_manager.service, [15](#)
- com.example.football_manager.service.CompetitionService, [30](#)
- CompetitionService, [30](#)
- createCompetition, [30](#)
- deleteCompetition, [30](#)
- getAllCompetitions, [30](#)
- getCompetitionById, [30](#)
- updateCompetition, [31](#)
- com.example.football_manager.service.CountryService, [34](#)
- CountryService, [34](#)
- createCountry, [34](#)
- deleteCountry, [34](#)
- getAllCountries, [35](#)
- com.example.football_manager.service.MatchService, [49](#)
- createMatch, [49](#)
- deleteMatch, [49](#)
- getAllMatches, [50](#)
- getFinishedMatchResults, [50](#)
- getFutureMatchesByFavouriteTeamIds, [50](#)
- getFutureMatchesByTeamId, [50](#)
- getGoalsByMatchId, [50](#)
- getMatchById, [50](#)
- getMatches, [51](#)
- getMatchForEdit, [51](#)
- getRecentMatchesByTeamId, [51](#)
- MatchService, [49](#)
- registerResult, [51](#)
- updateMatch, [51](#)
- com.example.football_manager.service.PlayerService, [61](#)
- createPlayer, [62](#)

deletePlayer, [62](#)
 getPlayerByTeamId, [62](#)
 getPlayersByTeamId, [62](#)
 PlayerService, [62](#)
 updatePlayer, [62](#)
 com.example.football_manager.service.TeamService, [72](#)
 createTeam, [72](#)
 deleteTeam, [72](#)
 getAllTeams, [72](#)
 getTeamById, [72](#)
 getTeamsContainingName, [73](#)
 TeamService, [72](#)
 updateTeam, [73](#)
 com.example.football_manager.service.UserService, [78](#)
 addFavouriteTeam, [78](#)
 getFavouriteTeamIdsByUserId, [78](#)
 getUserById, [78](#)
 getUserByUsername, [78](#)
 getUserProfile, [79](#)
 login, [79](#)
 registerUser, [79](#)
 removeFavouriteTeam, [79](#)
 updateProfile, [79](#)
 CompetitionController
 com.example.football_manager.controller.CompetitionController, [27](#)
 CompetitionRequestDTO
 com.example.football_manager.dto.CompetitionRequestDTO, [29](#)
 CompetitionService
 com.example.football_manager.service.CompetitionService, [30](#)
 countriesPage
 com.example.football_manager.controller.AdminCountryViewController, [17](#)
 CountryController
 com.example.football_manager.controller.CountryController, [32](#)
 CountryRequestDTO
 com.example.football_manager.dto.CountryRequestDTO, [33](#)
 CountryService
 com.example.football_manager.service.CountryService, [34](#)
 createCompetition
 com.example.football_manager.controller.CompetitionController, [27](#)
 com.example.football_manager.service.CompetitionService, [30](#)
 createCountry
 com.example.football_manager.controller.AdminCountryViewController, [17](#)
 com.example.football_manager.controller.CountryController, [32](#)
 com.example.football_manager.service.CountryService, [34](#)
 createMatch
 com.example.football_manager.service.MatchService, [49](#)
 createMatchFromForm
 com.example.football_manager.controller.MatchController, [40](#)
 createMatchFromJson
 com.example.football_manager.controller.MatchController, [40](#)
 createPlayer
 com.example.football_manager.controller.AdminPlayerViewController, [19](#)
 com.example.football_manager.controller.PlayerController, [57](#)
 com.example.football_manager.service.PlayerService, [62](#)
 createTeam
 com.example.football_manager.controller.TeamController, [68](#)
 com.example.football_manager.controller.TeamViewController, [74](#)
 com.example.football_manager.service.TeamService, [72](#)
 createUser
 com.example.football_manager.controller.AdminUserViewController, [22](#)
 DEFENDER
 com.example.football_manager.model.PlayerPosition, [58](#)
 deleteByMatchId
 com.example.football_manager.repository.MatchGoalRepository, [42](#)
 deleteCompetition
 com.example.football_manager.controller.CompetitionController, [27](#)
 com.example.football_manager.service.CompetitionService, [30](#)
 deleteCountry
 com.example.football_manager.controller.AdminCountryViewController, [18](#)
 com.example.football_manager.controller.CountryController, [32](#)
 com.example.football_manager.service.CountryService, [34](#)
 deleteMatch
 com.example.football_manager.controller.MatchController, [40](#)
 com.example.football_manager.service.MatchService, [49](#)
 deletePlayer
 com.example.football_manager.controller.AdminPlayerViewController, [19](#)
 com.example.football_manager.controller.PlayerController, [57](#)
 com.example.football_manager.service.PlayerService, [62](#)
 deleteTeam
 com.example.football_manager.controller.TeamController, [68](#)

com.example.football_manager.controller.TeamViewController, 74
 com.example.football_manager.service.TeamService, 72
 docs/doxygen_mainpage.md, 81
 doFilter
 com.example.football_manager.config.AdminSecurityFilter, 21
 doxygen_mainpage, 3
 existsByEmail
 com.example.football_manager.repository.UserRepository, 76
 existsByEmailAndIdNot
 com.example.football_manager.repository.UserRepository, 76
 existsByTeamIdAndNumber
 com.example.football_manager.repository.PlayerRepository, 59
 existsByTeamIdAndNumberAndIdNot
 com.example.football_manager.repository.PlayerRepository, 59
 existsByUsername
 com.example.football_manager.repository.UserRepository, 76
 existsByUsernameAndIdNot
 com.example.football_manager.repository.UserRepository, 77
 FavouriteTeamController
 com.example.football_manager.controller.FavouriteTeamController, 35
 filterChain
 com.example.football_manager.config.SecurityConfig, 67
 findByEmail
 com.example.football_manager.repository.UserRepository, 77
 findByFilters
 com.example.football_manager.repository.MatchRepository, 43
 findByFinishedFalseAndDatetimeAfterAndLeftTeamIdInOrFinishedFalseAndDatetimeAfterAndRightTeamIdInOrderByDatetimeAsc
 com.example.football_manager.repository.MatchRepository, 43
 findByFinishedFalseAndDatetimeAfterAndLeftTeamIdOrFinishedFalseAndDatetimeAfterAndRightTeamIdOrderByDatetimeAsc
 com.example.football_manager.repository.MatchRepository, 43
 findByFinishedTrueAndLeftTeamIdOrFinishedTrueAndRightTeamIdOrderByDatetimeDesc
 com.example.football_manager.repository.MatchRepository, 44
 findByFinishedTrueOrderByDatetimeDesc
 com.example.football_manager.repository.MatchRepository, 44
 findByIdAndTeamId
 com.example.football_manager.repository.PlayerRepository, 59
 findByMatchIdOrderByMinuteAscStoppageMinuteAscIdAsc
 com.example.football_manager.repository.MatchGoalRepository, 42

com.example.football_manager.service.MatchService, 50
 getGoals com.example.football_manager.dto.MatchResultRequestDTO, 48
 getGoalsByMatchId com.example.football_manager.service.MatchService, 50
 getHomeScore com.example.football_manager.dto.MatchRequestDTO, 45
 getHomeTeamId com.example.football_manager.dto.MatchRequestDTO, 46
 getId com.example.football_manager.dto.AuthResponseDTO, 25
 getIsAdmin com.example.football_manager.dto.AuthResponseDTO, 25
 com.example.football_manager.dto.RegisterDTO, 65
 getKickoffTime com.example.football_manager.dto.MatchRequestDTO, 46
 getLogoUrl com.example.football_manager.dto.TeamRequestDTO, 71
 getMatchById com.example.football_manager.service.MatchService, 50
 getMatches com.example.football_manager.controller.MatchController, 41
 com.example.football_manager.service.MatchService, 51
 getMatchForEdit com.example.football_manager.service.MatchService, 51
 getMatchResults com.example.football_manager.controller.MatchController, 41
 getMessage com.example.football_manager.dto.AuthResponseDTO, 25
 getMinute com.example.football_manager.dto.MatchResultRequestDTO, 37
 getName com.example.football_manager.dto.CompetitionRequestDTO, 29
 com.example.football_manager.dto.CountryRequestDTO, 33
 com.example.football_manager.dto.PlayerRequestDTO, 60
 com.example.football_manager.dto.TeamRequestDTO, 71
 getNumber com.example.football_manager.dto.PlayerRequestDTO, 60
 getPassword com.example.football_manager.dto.LoginDTO, 39
 com.example.football_manager.dto.RegisterDTO, 65
 getPlayerByTeamId com.example.football_manager.service.PlayerService, 62
 getPlayersByTeamId com.example.football_manager.controller.PlayerController, 57
 com.example.football_manager.service.PlayerService, 62
 getPosition com.example.football_manager.dto.PlayerRequestDTO, 60
 getRecentMatchesByTeamId com.example.football_manager.service.MatchService, 51
 getStatus com.example.football_manager.dto.MatchRequestDTO, 46
 getStoppageMinute com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO, 37
 getTeamById com.example.football_manager.controller.TeamController, 68
 com.example.football_manager.service.TeamService, 72
 getTeamId com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO, 37
 getTeamsContainingName com.example.football_manager.controller.TeamController, 69
 com.example.football_manager.service.TeamService, 73
 getUserById com.example.football_manager.service.UserService, 78
 getUserByUsername com.example.football_manager.service.UserService, 78
 getUsername com.example.football_manager.dto.AuthResponseDTO, 25
 com.example.football_manager.dto.LoginDTO, 39
 com.example.football_manager.dto.RegisterDTO, 65
 com.example.football_manager.service.UserService, 79
 getVenue com.example.football_manager.dto.MatchRequestDTO, 46
 GOALKEEPER

[com.example.football_manager.dto.MatchRequestDTO](#), [47](#)
[setHomeTeamId](#), [20](#)
[com.example.football_manager.dto.MatchRequestDTO](#), [47](#)
[setIsAdmin](#), [74](#)
[com.example.football_manager.dto.RegisterDTO](#), [66](#)
[setKickoffTime](#), [54](#)
[com.example.football_manager.dto.MatchRequestDTO](#), [47](#)
[setLogoUrl](#), [54](#)
[com.example.football_manager.dto.TeamRequestDTO](#), [71](#)
[setMinute](#), [54](#)
[com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO](#), [37](#)
[setName](#), [55](#)
[com.example.football_manager.dto.CompetitionRequestDTO](#), [29](#)
[com.example.football_manager.dto.CountryRequestDTO](#), [33](#)
[com.example.football_manager.dto.PlayerRequestDTO](#), [61](#)
[com.example.football_manager.dto.TeamRequestDTO](#), [71](#)
[setNumber](#), [68](#)
[com.example.football_manager.dto.PlayerRequestDTO](#), [61](#)
[setPassword](#), [74](#)
[com.example.football_manager.dto.LoginDTO](#), [39](#)
[com.example.football_manager.dto.RegisterDTO](#), [66](#)
[setPosition](#), [72](#)
[com.example.football_manager.dto.PlayerRequestDTO](#), [61](#)
[setStatus](#), [75](#)
[com.example.football_manager.dto.MatchRequestDTO](#), [47](#)
[setStoppageMinute](#), [75](#)
[com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO](#), [37](#)
[setTeamId](#), [28](#)
[com.example.football_manager.dto.MatchResultRequestDTO.GoalDTO](#), [37](#)
[setUsername](#), [31](#)
[com.example.football_manager.dto.LoginDTO](#), [39](#)
[com.example.football_manager.dto.RegisterDTO](#), [66](#)
[setVenue](#), [55](#)
[com.example.football_manager.dto.MatchRequestDTO](#), [47](#)
[showAddTeamForm](#), [51](#)
[com.example.football_manager.controller.TeamViewController](#), [74](#)
[showEditForm](#), [20](#)
[com.example.football_manager.controller.MatchViewController](#), [54](#)
[com.example.football_manager.controller.MatchRequestDTO](#), [47](#)
[com.example.football_manager.controller.AdminPlayerViewController](#), [20](#)
[com.example.football_manager.controller.TeamViewController](#), [74](#)
[com.example.football_manager.controller.MatchViewController](#), [54](#)
[com.example.football_manager.controller.MatchViewController](#), [54](#)
[com.example.football_manager.controller.MatchViewController](#), [54](#)
[com.example.football_manager.controller.MatchViewController](#), [55](#)
[com.example.football_manager.controller.MatchViewController](#), [55](#)
[com.example.football_manager.model.Team](#), [67](#)
[com.example.football_manager.controller.TeamController](#), [68](#)
[com.example.football_manager.controller.TeamViewController](#), [74](#)
[com.example.football_manager.dto.TeamRequestDTO](#), [70](#)
[com.example.football_manager.service.TeamService](#), [72](#)
[com.example.football_manager.controller.TeamViewController](#), [75](#)
[com.example.football_manager.controller.CompetitionController](#), [28](#)
[com.example.football_manager.service.CompetitionService](#), [31](#)
[com.example.football_manager.controller.MatchController](#), [41](#)
[com.example.football_manager.controller.MatchViewController](#), [55](#)
[com.example.football_manager.service.MatchService](#), [51](#)
[com.example.football_manager.controller.AdminPlayerViewController](#), [20](#)
[com.example.football_manager.controller.PlayerController](#), [57](#)
[com.example.football_manager.service.PlayerService](#), [62](#)

updateProfile

com.example.football_manager.controller.ProfileViewController,
[64](#)
com.example.football_manager.service.UserService,
[79](#)

updateTeam

com.example.football_manager.controller.TeamController,
[69](#)
com.example.football_manager.controller.TeamViewController,
[75](#)
com.example.football_manager.service.TeamService,
[73](#)

usersPage

com.example.football_manager.controller.AdminUserController,
[22](#)