

Berner Fachhochschule - Technik und Informatik

Object-Oriented Programming 2

Topic 2: Collections

Prof. Rolf Haenni & Prof. Annett Laube

FS 2016

Outline

The Collection Framework

Lists

Queues and Deques

Sets and Sorted Sets

Maps and Sorted Maps

Iterators

The Minimax Algorithm

Outline

The Collection Framework

Lists

Queues and Deques

Sets and Sorted Sets

Maps and Sorted Maps


Iterators

The Minimax Algorithm

The Collection Framework

- ▶ A **collection** represents an iterable group of elements
- ▶ There are various types of collections, depending on how the elements are stored and on how manipulations work
 - Some allow duplicate elements, others do not
 - Some are ordered, others are unordered
 - Some have a fixed (or maximal) size, others have a variable size
 - Some can be modified, others are immutable
- ▶ The generic interface `Collection<E>` is the root of the **Java Collections Framework** (JCF)
- ▶ The JCF exists since Java 1.2 (generic types added in Java 5)
- ▶ The interfaces `Map<K,V>` and `SortedMap<K,V>` do not inherit from `Collection<E>`, but are still members of the JCF


Interfaces of the Collection Framework



The Collection Interface

- ▶ The interface `Collection` defines a number of methods that perform basic operations
 - `boolean isEmpty()`: Returns true if the collection is empty
 - `int size()`: Returns the collection's number of elements
 - `boolean add(E e)`: Ensures that the collection contains `e`
 - `boolean remove(Object e)`: Removes `e` from the collection
 - `boolean contains(Object e)`: Returns true if the collection contains `e`
 - `void clear()`: Removes all elements from the collection
 - `Object[] toArray()`: Returns an array containing all of the elements from the collection
- ▶ An additional method is inherited from `Iterable<E>`
 - `Iterator<E> iterator()`: Returns an iterator over all elements

Classes of the Collection Framework



Classes of the Collection Framework

- ▶ A class that implements `Collection<E>` is supposed to provide at least two constructors for constructing ...
 - an empty collection
 - a collection containing all elements of another collection
- ▶ Examples:
 - `ArrayList()`, `ArrayList(Collection<? extends E> c)`
 - `LinkedList()`, `LinkedList(Collection<? extends E> c)`
 - `HashSet()`, `HashSet(Collection<? extends E> c)`
 - etc.

Example of Using Collections I

```
public class CollectionTester {  
  
    public static void main(String[] args) {  
  
        Collection<String> c1 = new ArrayList<>();  
        c1.add("Hello");  
        c1.add("World");  
        c1.size(); // returns 2  
        System.out.println(c1); // prints "[Hello, World]"  
  
        Collection<String> c2 = new LinkedList<>(c1);  
        c2.add("!");  
        c2.add("!");  
        c2.size(); // returns 4  
        c2.remove("World");  
        c2.size(); // returns 3  
        System.out.println(c2); // prints "[Hello, !, !]"  
    }  
}
```

Example of Using Collections II

```
Collection<String> c3 = new HashSet(c2);  
c3.add("World");  
c3.add("World");  
c3.size(); // returns 3  
System.out.println(c3); // prints "[!, Hello, World]"  
}  
  
}
```

Outline

The Collection Framework

Lists

Queues and Deques

Sets and Sorted Sets


Maps and Sorted Maps

Iterators

The Minimax Algorithm

Lists

- ▶ The interfaces `List`, `Queue`, and `Deque` extend the interface `Collection` by introducing ...
 - an ordering of the elements stored in the collection
 - additional access methods
- ▶ A `list` offers **positional access**, i.e., manipulations of elements are based on their numerical position (index) in the list



The List Interface

- ▶ `E get(int i)`: Returns the element at the specified index `i`
- ▶ `E set(int index, E element)`: Replaces the element at the specified index `i` with `e`
- ▶ `void add(int i, E e)`: Inserts `e` at the specified index `i`
- ▶ `E remove(int i)`: Removes the element at the specified index `i`
- ▶ `int indexOf(Object e)`: Returns the index of the first occurrence of `e`
- ▶ `int lastIndexOf(Object e)`: Returns the index of the last occurrence of `e`

ArrayList vs. LinkedList

- ▶ The main difference between the classes `ArrayList` and `LinkedList` is their internal way of storing the elements
 - `ArrayList` uses internally an array (which needs to be replaced by a bigger one if it gets full)
 - `LinkedList` uses internally a doubly linked chain of nodes, which carry the elements
- ▶ This has implications on the running times of some methods
 - `ArrayList` allows for fast random access, but adding or removing elements may require existing elements to be shifted
 - `LinkedList` allows for constant-time insertions or removals, but only sequential access
- ▶ Recommendation: use `ArrayList` except in cases where insertions or removals are the dominant operations

Example of Using Sets I

```
public class ListTester {  
  
    public static int ROUNDS = 500000;  
  
    public static void main(String[] args) {  
  
        List<String> l1 = new ArrayList<>();  
        System.out.println("ArrayList: start...");  
        for (int i = 1; i <= ROUNDS; i++) {  
            l1.add(0, "Hello");  
        }  
        System.out.println("done");  
  
        List<String> l2 = new LinkedList<>();  
        System.out.println("LinkedList: start...");  
        for (int i = 1; i <= ROUNDS; i++) {  
            l2.add(0, "World");  
        }  
    }  
}
```

Example of Using Sets II

```
    }  
    System.out.println("done");  
}  
  
}
```


Outline

The Collection Framework

Lists

Queues and Deques

Sets and Sorted Sets

Maps and Sorted Maps

Iterators


The Minimax Algorithm

Queues and Deques (and Stacks)

- ▶ A **queue** offers **first-in-first-out access** (FIFO) to its elements
 - Elements are added to the back of the queue
 - Elements are removed from the front of the queue
- ▶ A **deque** (short form for “double ended queue”, pronounced as “deck”) offers access to both of its extremities
 - Elements are added to the front or the back of the deque
 - Elements are removed from the front or the back of the deque
- ▶ A deque also includes typical methods of a **stack**, which offers **last-in-first-out access** (LIFO)
 - Elements are added to the front (push)
 - Elements are removed from the front (pop)

The Queue Interface


- ▶ `E element()`, `E peek()`: Retrieves, but does not remove, the first element of the queue
- ▶ `boolean add(E e)`, `boolean offer(E e)`: Inserts `e` into the queue if it is possible
- ▶ `E remove()`, `E poll()`: Retrieves and removes the first element of the queue



The Deque Interface

- ▶ `E getFirst()`, `E peekFirst()`: Retrieves, but does not remove, the first element of the deque
- ▶ `E getLast()`, `E peekLast()`: Retrieves, but does not remove, the last element of the deque
- ▶ `void addFirst(E e)`, `void offerFirst(E e)`, `void push(E e)`: Inserts `e` at the front of the deque
- ▶ `void addLast(E e)`, `void offerLast(E e)`: Inserts `e` at the end of the deque
- ▶ `E removeFirst()`, `E pollFirst()`, `E pop()`: Retrieves and removes the first element of the deque
- ▶ `E removeLast()`, `E pollLast()`: Retrieves and removes the last element of the deque

The Deque Interface



ArrayDeque vs. PriorityQueue

- ▶ In a `ArrayDeque`, the order of the elements is determined by the sequence of insertion operations
- ▶ In a `PriorityQueue`, the order of the elements is determined by their natural order or by specifying a comparator
 - `PriorityQueue()`
 - `PriorityQueue(Comparator<? super E> comparator)`
- ▶ Another difference is their internal way of storing the elements
 - `ArrayDeque` uses internally an array (similar to `ArrayList`)
 - `PriorityQueue` uses internally a **heap**
- ▶ All critical operations are efficient: average $O(1)$ for `ArrayDeque`, worst-case $O(\log n)$ for `PriorityQueue`

Example of Using Queues I

```
public class QueueTester {  
  
    public static void main(String[] args) {  
  
        Queue<String> p1 = new ArrayDeque<>(); // Insertion order  
        p1.add("Peter");  
        p1.add("John");  
        p1.add("Tom");  
        p1.add("Andrew");  
        while (!p1.isEmpty()) {  
            System.out.println(p1.remove());  
        } // Loop prints "Peter", "John", "Tom", "Andrew"  
  
        Queue<String> p2 = new PriorityQueue<>(); // Natural order  
        p2.add("Peter");  
        p2.add("John");  
        p2.add("Tom");  
    }  
}
```

Example of Using Queues II

```
p2.add("Andrew");  
while (!p2.isEmpty()) {  
    System.out.println(p2.remove());  
} // Loop prints "Andrew", "John", "Peter", "Tom"  
  
// String length comparator  
Comparator<String> c = new Comparator<String>() {  
    @Override  
    public int compare(String s1, String s2) {  
        if (s1.length() < s2.length()) {  
            return -1;  
        }  
        if (s1.length() > s2.length()) {  
            return 1;  
        }  
        return 0;  
    }  
};
```


Example of Using Queues III

```
Queue<String> p3 = new PriorityQueue<>(c);
p3.add("Peter");
p3.add("John");
p3.add("Tom");
p3.add("Andrew");
while (!p3.isEmpty()) {
    System.out.println(p3.remove());
} // Loop prints "Tom", "John", "Peter", "Andrew"
}
```

Outline

The Collection Framework

Lists

Queues and Deques

Sets and Sorted Sets

Maps and Sorted Maps

Iterators

The Minimax Algorithm

Sets

- ▶ A `set` in Java is a collection that contains no duplicates
- ▶ Duplicates are elements `e1` and `e2` such that `e1.equals(e2)`
- ▶ Compared to a list, there are two important differences:
 - A list may contain duplicates
 - Elements in a list are ordered (positional access)
- ▶ Java sets correspond to sets in mathematics, except that Java sets can be modified
 - `boolean contains(Object x)`: tests if $x \in X$
 - `boolean containsAll(Collection<?> y)`: tests if $Y \subseteq X$
 - `boolean addAll(Collection<? extends E> y)`: computes $X \cup Y$
 - `boolean retainAll(Collection<?> y)`: computes $X \cap Y$
 - `boolean removeAll(Collection<?> y)`: computes $X \setminus Y$

Sorted Sets

- ▶ A **sorted set** in Java is a set that provides a total order on its elements, which is determined by their natural order or by specifying a comparator
- ▶ The interface `SortedSet` provides some additional methods that exploit the existence of an order
 - `E first()`: Returns the minimal element currently in this set
 - `E last()`: Returns the maximal element currently in this set
 - `SortedSet<E> tailSet(E e)`: Returns elements that are greater than or equal to `e`
 - `SortedSet<E> headSet(E e)`: Returns elements that are strictly less than `e`
 - `SortedSet<E> subSet(E e1, E e2)`: Returns the elements that range from `e1` (inclusive) to `e2` (exclusive)

HashSet vs. TreeSet

- ▶ In a HashSet, the order of the elements is unspecified
- ▶ In a TreeSet, the order is determined by their natural order or by specifying a comparator (similar to PriorityQueue)
 - `TreeSet()`
 - `TreeSet(Comparator<? super E> comparator)`
- ▶ Another difference is their internal way of storing the elements
 - HashSet uses internally a **hash table** (array)
 - TreeSet uses internally a **red-black tree**
- ▶ All critical operations are efficient: average $O(1)$ for HashSet, worst-case $O(\log n)$ for TreeSet

Example of Using Sets I

```
public class SetTester {  
  
    public static void main(String[] args) {  
  
        Set<Integer> s1 = new HashSet<>(Arrays.asList(new Integer  
            []{1,2,3,4}));  
        Set<Integer> s2 = new HashSet<>(Arrays.asList(new Integer  
            []{3,4,5}));  
        Set<Integer> s3 = new HashSet<>(Arrays.asList(new Integer  
            []{2,5,6}));  
  
        s2.addAll(s3);  
        System.out.println(s2); // s2 = s2 cup s3 = {2,3,4,5,6}  
  
        s2.retainAll(s1); // s2 = s2 cap s1 = {2,3,4}  
        System.out.println(s2); // s2 = s2 cap s1 = {2,3,4}
```

Example of Using Sets II

```
s2.removeAll(s3);  
System.out.println(s2); // s2 = s2 minus s3 = {3,4}  
  
s2.add(3);  
s2.add(5);  
s2.add(5);  
System.out.println(s2); // s2 = s2 cup {3,5,5} = {3,4,5}  
  
SortedSet<Integer> s = new TreeSet<>(Arrays.asList(new  
    Integer[]{1,3,7,2,5,4,7}));  
System.out.println(s.headSet(5)); // {1,2,3,4}  
System.out.println(s.tailSet(5)); // {5,7}  
System.out.println(s.subSet(2,5)); // {2,3,4}  
}  
}
```

The Equals Method

- ▶ Duplicates in sets and sorted sets are defined differently:
 - Sets: `e1.equals(e2)`
 - Sorted sets:
`e1.compareTo(e2) == 0` or `c.compareTo(e1,e2) == 0`
- ▶ The method `equals(Object obj)` as defined in `Object` only performs an identity check `e1 == e2`
- ▶ **Important:** If you need a `Set<MyClass>`, you must override `equals(Object obj)` in your class `MyClass`
 - `e.equals(null) == false`
 - `e.equals(e) == true` (Reflexivity)
 - `e1.equals(e2) == e2.equals(e1)` (Symmetry)
 - `e1.equals(e2) && e2.equals(e3) == e1.equals(e3)` (Transitivity)

Auto-Generated Equals Method I

```
public class MyClass {  
  
    private int x;  
    private String y;  
  
    @Override  
    public boolean equals(Object obj) {  
        if (obj == null) {  
            return false;  
        }  
        if (this == obj) {  
            return true;  
        }  
        if (getClass() != obj.getClass()) {  
            return false;  
        }  
        MyClass other = (MyClass) obj;
```

Auto-Generated Equals Method II

```
if (this.x != other.x) {  
    return false;  
}  
if (this.y == null) {  
    if (other.y != null) {  
        return false;  
    }  
} else if (!this.y.equals(other.y)) {  
    return false;  
}  
return true;  
}
```

The hashCode Method

- ▶ A set implemented based on hash tables (e.g. HashSet) requires a **hash function** that is compatible with equals
- ▶ The method `hashCode()` as defined in `Object` only transforms the memory address of the object into an integer
- ▶ **Important:** If you need a `HashSet<MyClass>`, you must override `hashCode()` in your class `MyClass`
 - If `e1.equals(e2)`, then `e1.hashCode() == e2.hashCode()`
 - Otherwise, `e1.hashCode() != e2.hashCode()` with high probability
- ▶ General recommendation: Always override `hashCode()` when you override `equals(Object obj)`

Auto-Generated hashCode Method

- ▶ Let h_1, \dots, h_n be the hash codes of the n fields of an object x , then a good practice is to define $h_0 = 1$ and compute

$$\text{hashCode}(x) = \sum_{i=0}^n h_i \cdot 31^{n-i}$$

- ▶ Example: Let $n = 2$, then $\text{hashCode}(x) = 31^2 + 31h_1 + h_2$

```
@Override
public int hashCode() {
    final int prime = 31;
    int result = 1;
    result = prime * result + x;
    result = prime * result + ((y == null) ? 0 : y.hashCode());
    return result;
}
```

Outline

The Collection Framework

Lists

Queues and Deques

Sets and Sorted Sets

Maps and Sorted Maps

Iterators

The Minimax Algorithm

Maps and Sorted Maps

- ▶ A **map** in Java is an object that maps **keys** to **values** (similar to a function $f : \{k_1, \dots, k_n\} \rightarrow V$ in mathematics)

$$k_1 \mapsto v_1 = f(k_1)$$

$$\vdots$$

$$k_n \mapsto v_n = f(k_n)$$

- ▶ A map cannot contain duplicate keys (each key maps to at most one value), but different keys can map to the same value
- ▶ The goal of a map is to provide a **key-based access** to the values stored in the map
- ▶ A **sorted map** is a map that provides a total ordering on its keys (similar to SortedSet)

The Map Interface

- ▶ Since `Map<K,V>` does not inherit from `Collection<E>`, it defines its own methods `isEmpty()`, `size()`, and `clear()`
 - `boolean containsKey(Object key)`: Returns true if the map contains a mapping with the given value
 - `boolean containsValue(Object key)`: Returns true if the map contains a mapping for the given key
 - `V get(Object key)`: Returns the value of the mapping for the given key (or null if the key does not exist)
 - `V put(K key, V value)`: Adds a new mapping or replaces the value of an existing mapping
 - `V remove(Object key)`: Removes the mapping if the given key exists
 - `V replace(K key, V value)`: Replaces the value in the mapping if the given key exists
 - `Collection<V> values()`: Returns a collection of all values
 - `Set<K> keySet()`: Returns a set of all keys

HashMap vs. TreeMap

- ▶ In a HashMap, the order of the keys is unspecified
- ▶ In a TreeMap, the order is determined by their natural order or by specifying a comparator (similar to TreeSet)
 - `TreeMap()`
 - `TreeMap(Comparator<? super E> comparator)`
- ▶ Another difference is their internal way of storing the elements
 - HashMap uses internally a **hash table** (array)
 - TreeMap uses internally a **red-black tree**
- ▶ All critical operations are efficient: average $O(1)$ for HashMap, worst-case $O(\log n)$ for TreeMap

Example of Using Maps I

```
public class MapTester {  
  
    public static void main(String[] args) {  
  
        Map<Integer,String> map = new HashMap<>();  
        map.put(1, "Hello");  
        map.put(5, "World");  
        map.put(7, "Hello");  
        map.put(10, "Hello World");  
        map.put(10, "Hello World!"); // replaces previous value  
  
        System.out.println(map.keySet()); // prints [1, 5, 7, 10]  
        System.out.println(map.values()); // prints [Hello, World,  
            Hello, Hello World!]  
  
        String str1 = map.get(1);  
        if (str1 != null) {
```

Example of Using Maps II

```
    System.out.println(str1); // prints "Hello"
}
String str2 = map.get(2);
if (str2 != null) {
    System.out.println(str2); // nothing is printed
}

// the following code is less efficient
int key = 1;
if (map.containsKey(key)) {
    System.out.println(map.get(key)); // prints "Hello"
}
}
```

Outline

The Collection Framework

Lists

Queues and Deques

Sets and Sorted Sets

Maps and Sorted Maps

Iterators

The Minimax Algorithm



Iterators

- ▶ An **iterator** in Java is an object that helps iterating through all elements in a collection
- ▶ The interface `Iterator<E>` defines the following methods:
 - `boolean hasNext()`: Returns true if the iteration has more elements
 - `E next()`: Returns the next element in the iteration
- ▶ Note that an iterator only allows a single iteration
- ▶ The following is a typical example of usage:

```
Iterator<String> iterator = ...;  
while(iterator.hasNext()) {  
    System.out.println(iterator.next());  
}
```

Array Iterator I

```
public class ArrayIterator<E> implements Iterator<E> {  
  
    private E[] array;  
    private int currentIndex;  
  
    public ArrayIterator(E[] array) {  
        this.array = array;  
        this.currentIndex = 0;  
    }  
  
    @Override  
    public boolean hasNext() {  
        return this.currentIndex < this.array.length;  
    }  
  
    @Override  
    public E next() {
```

Array Iterator II

```
if (!this.hasNext()){  
    throw new NoSuchElementException();  
}  
return this.array[this.currentIndex++];  
}  
  
}
```

Reverse Array Iterator I

```
public class ReverseArrayIterator<E> implements Iterator<E> {  
  
    private E[] array;  
    private int currentIndex;  
  
    public ReverseArrayIterator(E[] array) {  
        this.array = array;  
        this.currentIndex = array.length - 1;  
    }  
  
    @Override  
    public boolean hasNext() {  
        return this.currentIndex >= 0;  
    }  
  
    @Override  
    public E next() {
```

Reverse Array Iterator II

```
if (!this.hasNext()) {  
    throw new NoSuchElementException();  
}  
return this.array[this.currentIndex--];  
}  
  
}
```


Iterator Tester I

```
public class IteratorTester {  
  
    public static void main(String[] args) {  
  
        Integer[] values = new Integer[] { 1, 3, 3, 5, 6, 9 };  
  
        Iterator<Integer> i1 = new ArrayIterator<>(values);  
        while (i1.hasNext()) {  
            System.out.print(i1.next() + " ");  
        }  
        System.out.println();  
        // prints 1 3 3 5 6 9  
  
        Iterator<Integer> i2 = new ReverseArrayIterator<>(values);  
        while (i2.hasNext()) {  
            System.out.print(i2.next() + " ");  
        }  
    }  
}
```

Iterator Tester II

```
System.out.println();  
// prints 9 6 5 3 3 1  
}  
  
}
```

List Iterators

- ▶ The `ListIterator<E>` interface extends `Iterator<E>` with methods for traversing a list backwards
 - `boolean hasPrevious()`: Returns true if a backward iteration has more elements
 - `E previous()`: Returns the previous element in a backward iteration
- ▶ It also provides methods for adding, removing, or replacing element in the list
 - `void add(E e)`: Inserts an element into the list
 - `void remove()`: Removes the current element from the list
 - `void set(E e)`: Replaces the current element in the list

Obtaining Iterators from Collections

- ▶ An iterator can be obtained from a collection using a method inherited from `Iterable<E>`
 - `Iterator<E> iterator()`: Returns an iterator over all elements in the collection (the order is unspecified)
- ▶ Similarly, a list iterator can be obtained from a list
 - `ListIterator<E> listIterator()`: Returns a list iterator over all elements in the list
- ▶ Note that the Java for-each loop work for any class that implements the `Iterable<E>` interface

```
Iterable<Integer> values =Arrays.asList(new Integer
    []{1,3,3,5,7,9});
int sum = 0;
for (Integer value: values) {
    sum = sum + value;
}
```

Outline

The Collection Framework

Lists

Queues and Deques

Sets and Sorted Sets

Maps and Sorted Maps

Iterators

The Minimax Algorithm

The Minimax-Algorithm


- ▶ The **minimax algorithm** is an optimal game playing algorithm for two player games such as tic-tac-toe, chess, go, uril, ...
- ▶ Let A and B be the two players and S the finite set of possible **game states**, where ...
 - $s_0 \in S$ is the **initial state**
 - $S^* \subseteq S$ are **final states**, in which the game ends
- ▶ For all final states $s^* \in S^*$, the winner of the game is defined by a function $E : S^* \rightarrow [-1, 1]$, where

$$E(s^*) = \begin{cases} 1, & \text{if } A \text{ wins} \\ 0, & \text{if the game ends as draw} \\ -1, & \text{if } B \text{ wins} \end{cases}$$

Example: Subtraction Game

- ▶ In a (k, n) -subtraction game, A and B take turns in removing up to k objects from a pile with initially n objects
 - A begins
 - Whoever removes the last object from the pile wins
- ▶ Example: $(2, 5)$ -subtraction game
 - States: $S = \{(5, A), (3, A), \dots, (0, A), (4, B), \dots, (0, B)\}$
 - Initial state: $s_0 = (5, A)$
 - Final states: $S^* = \{(0, A), (0, B)\}$
 - $$E(s^*) = \begin{cases} 1, & \text{for } s^* = (0, B) \\ -1, & \text{for } s^* = (0, A) \end{cases}$$

Example: Subtraction Game



Minimax Algorithm: General Idea

- ▶ Let $next(s) \subseteq S$ be the reachable states from $s \in S$
- ▶ Example: $(2, 5)$ -subtraction game
 - $next((5, A)) = \{(4, B), (3, B)\}$
 - $next((4, B)) = \{(3, A), (2, A)\}$
 - \vdots
 - $next((0, A)) = next(0, B) = \{\}$
- ▶ The minimax algorithm extends E from $E : S^* \rightarrow [-1, 1]$ to $F : S \rightarrow [-1, 1]$ by computing $F(s)$ recursively by for all $s \in S$

$$F(s) = \begin{cases} E(s), & \text{if } s \in S^* \\ \max\{F(s') : s' \in next(s)\}, & \text{if it is } A\text{'s turn} \\ \min\{F(s') : s' \in next(s)\}, & \text{if it is } B\text{'s turn} \end{cases}$$

Minimax Algorithm: Pseudocode

Algorithm: Minimax(s, d)

if $s \in S^*$ **then** // game ends
 | **return** $E(s)$

if $d \bmod 2 = 0$ **then** // A's turn

 | $m \leftarrow -1$
 | **for** $s' \in next(s)$ **do**
 | $m \leftarrow \max(m, \text{Minimax}(s', d + 1))$

else // B's turn


 | $m \leftarrow 1$
 | **for** $s' \in next(s)$ **do**
 | $m \leftarrow \min(m, \text{Minimax}(s', d + 1))$

return m

Example: Subtraction Game

Initial call: $\text{Minimax}((5, A), 0)$

Return value: $F((5, A)) = 1$, i.e. A wins by removing 2 objects



Minimax Algorithm: Performance

- ▶ The **branching factor** b of a game is the average number legal moves (children in the game tree)
- ▶ Examples:
 - (k, n) -subtraction game: $b \leq k, h \leq n$
 - Chess: $b \approx 35, h \approx 80$
 - Go: $b \approx 250$
- ▶ The minimax algorithm runs in $O(b^h)$ time, where h denotes the height (maximal depth) of the game tree
- ▶ In other words, exploring the full game tree is impossible for most non-trivial games

Pruned Minimax Algorithm

- ▶ To apply the minimax algorithm to non-trivial games, the game tree exploration must be pruned
- ▶ The simplest pruning method is to stop the recursion when a **maximal depth** d_{\max} is reached
- ▶ When the recursion stops at state $s \in S$, then a **evaluation function** $\tilde{E} : S \rightarrow [-1, 1]$ is applied to s
 - For $s \in S^*$, let $\tilde{E}(s) = E(s)$
 - Otherwise, let $\tilde{E}(s)$ be an estimate of the **advantage** of state s relative to A and B , such that $\tilde{E}(s) = 1$ means maximal advantage for A and $\tilde{E}(s) = -1$ maximal advantage for B
- ▶ The quality of the estimate $\tilde{E}(s)$ and d_{\max} determine the quality and accuracy of the final minimax return value

Pruned Minimax Algorithm: Pseudocode

```

Algorithm: Minimax( $s, d, d_{\max}$ )

if  $s \in S^*$  or  $d = d_{\max}$  then                                // game ends
  | return  $\tilde{E}(s)$ 
if  $d \bmod 2 = 0$  then                                           // A's turn
  |  $m \leftarrow -1$ 
  | for  $s' \in \text{next}(s)$  do
  | |  $m \leftarrow \max(m, \text{Minimax}(s', d + 1, d_{\max}))$ 
else                                                           // B's turn
  |  $m \leftarrow 1$ 
  | for  $s' \in \text{next}(s)$  do
  | |  $m \leftarrow \min(m, \text{Minimax}(s', d + 1, d_{\max}))$ 
return  $m$ 
  
```

Defining the Evaluation Function

- ▶ One popular strategy for constructing an evaluation function $\tilde{E} : S \rightarrow [-1, 1]$ is as a **weighted sum**

$$\tilde{E}(s) = \frac{1}{W} \sum_{i=1}^k w_i \cdot \tilde{E}_i(s)$$


of k individual evaluation criteria

- ▶ The value $w_i \in [0, 1]$ denotes the **weight** of criterion i and $W = \sum_{i=1}^k w_i$ denotes the total weight of all criteria
- ▶ $\tilde{E}_i : S \rightarrow [-1, 1]$ defines the evaluation function of criterion i
- ▶ Example from chess:

$$\tilde{E}(s) = 9 \cdot (Q - Q') + 5 \cdot \frac{R - R'}{2} + 3 \cdot \frac{B - B'}{2} + 3 \cdot \frac{N - N'}{2} + \frac{P - P'}{8} + \dots$$

Alpha-Beta Pruning

- ▶ There are many ways of optimizing the minimax algorithm
- ▶ The general idea is to prune branches of the game tree that will not influence the final minimax return value
- ▶ The simplest optimization is known as **alpha-beta pruning**



- ▶ The following version of the minimax algorithm is initially called with $\text{Minimax}(s_0, 0, d_{\max}, -1, 1)$

Alpha-Beta Pruning: Pseudocode I

```

Algorithm: Minimax( $s, d, d_{\max}, \alpha, \beta$ )
if  $s \in S^*$  or  $d = d_{\max}$  then                                // game ends
  | return  $\tilde{E}(s)$ 
if  $d \bmod 2 = 0$  then                                           // A's turn
  |  $m \leftarrow -1$ 
  | for  $s' \in \text{next}(s)$  do
  | |  $m \leftarrow \max(m, \text{Minimax}(s', d + 1, d_{\max}, \alpha, \beta))$ 
  | |  $\alpha \leftarrow \max(\alpha, m)$ 
  | | if  $\alpha \geq \beta$  then
  | | | return  $m$                                               //  $\beta$  cutoff
  |

```

Alpha-Beta Pruning: Pseudocode II

```
else // B's turn
   $m \leftarrow 1$ 
  for  $s' \in next(s)$  do
     $m \leftarrow \min(m, \text{Minimax}(s', d + 1, , d_{\max}, \alpha, \beta))$ 
     $\beta \leftarrow \min(\beta, m)$ 
    if  $\alpha \geq \beta$  then
      return  $m$  //  $\alpha$  cutoff
  return  $m$ 
```