

Berner Fachhochschule - Technik und Informatik

Object-Oriented Programming 2

Topic 2: Generic Programming

Prof. Rolf Haenni & Prof. Annett Laube

FS 2017

Outline

Generic Types

Generic Classes and Interfaces

Bounded Type Parameters

Raw Types and Wildcards

Generic Methods

Limitations of Generics

Outline

Generic Types

Generic Classes and Interfaces

Bounded Type Parameters

Raw Types and Wildcards

Generic Methods

Limitations of Generics

Motivation

- ▶ The goal of **generic programming** is to help implementing ...
 - algorithms (e.g. sort)
 - data types (e.g. ArrayList)
 - libraries (e.g. Collection)

independently of concrete data types

- ▶ Advantages of generic programming:
 - Increased code reusability, reduced code redundancy
 - Stronger type checks at compile time
 - Less runtime errors
 - Elimination of casts
 - Improved code readability

Non-Generic Array Lists

- ▶ Java support **generic types** since Java 5 (2004)
- ▶ Before Java 5, using an array list looked as follows:

```
ArrayList list = new ArrayList();  
list.add("HelloWorld");  
  
String s = (String) list.get(0);  
  
Integer i = (Integer) list.get(0); // Runtime error
```

- ▶ The main problem was a lack of **type safety**: a non-generic array list stores elements of type Object

Generic Array Lists

- ▶ Since Java 5, using an array list looks as follows:

```
ArrayList<String> list = new ArrayList<String>();  
list.add("HelloWorld");  
  
String s = list.get(0);  
  
Integer i = list.get(0); // Compilation error
```

- ▶ Java 7 introduced the **diamond operator** to simplify object creation

```
ArrayList<String> list = new ArrayList<>();
```

Type Parameters

- Generic classes and generic interfaces have one or multiple type parameters

```
public class ArrayList<E> implements List<E> {  
    public ArrayList() { ... }  
    public E get(int index) { ... }  
    public void add(E element) { ... }  
    :  
}  
  
public interface List<E> extends Collection<E> {  
    public E get(int index);  
    public void add(E element);  
    :  
}
```

Naming Conventions

- ▶ The convention for type parameters is to use single capital letters
 - T general generic type
 - N for numbers
 - E for elements in a collection
 - K for key in a map
 - V for values in a map
 - S, U, W for additional generic types

Outline

Generic Types

Generic Classes and Interfaces

Bounded Type Parameters

Raw Types and Wildcards

Generic Methods

Limitations of Generics

Non-Generic Example 1: StringBox I

```
public class StringBox {  
  
    private String content;  
  
    public StringBox(String content) {  
        this.content = content;  
    }  
  
    public void setContent(String content) {  
        this.content = content;  
    }  
  
    public String getContent() {  
        return this.content;  
    }  
}
```

Non-Generic Example 1: StringBox II

```
public static void main(String[] args) {  
  
    StringBox stringBox = new StringBox("HelloWorld");  
    String str = stringBox.getContent();  
  
}  
}
```

Example 1: StringBox.java

Non-Generic Example: IntegerBox I

```
public class IntegerBox {  
  
    private Integer content;  
  
    public IntegerBox(Integer content) {  
        this.content = content;  
    }  
  
    public void setContent(Integer content) {  
        this.content = content;  
    }  
  
    public Integer getContent() {  
        return this.content;  
    }  
}
```

Non-Generic Example: IntegerBox II

```
public static void main(String[] args) {  
  
    IntegerBox integerBox = new IntegerBox(100);  
    int i = integerBox.getContent();  
  
}  
}
```

Example 2: IntegerBox.java

Example: One Generic Type Parameter I

```
public class Box<T> {  
  
    private T content;  
  
    public Box(T content) {  
        this.content = content;  
    }  
  
    public void setContent(T content) {  
        this.content = content;  
    }  
  
    public T getContent() {  
        return this.content;  
    }  
}
```

Example: One Generic Type Parameter II

```
public static void main(String[] args) {  
  
    Box<String> stringBox = new Box<>("HelloWorld");  
    String s = stringBox.getContent();  
  
    Box<Integer> integerBox = new Box<>(100);  
    int i = integerBox.getContent();  
  
    Box<Box<Integer>> doubleIntegerBox = new Box<>(  
        integerBox);  
    int j = doubleIntegerBox.getContent().getContent();  
}  
}
```

Example 3: Box.java

Example: Two Generic Type Parameters I

```
public class Pair<S, T> {  
  
    private S first;  
    private T second;  
  
    public Pair(S first, T second) {  
        this.first = first;  
        this.second = second;  
    }  
  
    public S getFirst() {  
        return this.first;  
    }  
  
    public T getSecond() {
```


Example: Two Generic Type Parameters II

```
        return this.second;
    }

    public void setFirst(S first) {
        this.first = first;
    }

    public void setSecond(T second) {
        this.second = second;
    }

    public static void main(String[] args) {

        Pair<String, Integer> pair1 = new Pair<>("HelloWorld", 100);
        String s1 = pair1.getFirst();
        int i1 = pair1.getSecond();
    }
}
```

Example: Two Generic Type Parameters III

```
Pair<Integer, String> pair2 = new Pair<>(100, "
    HelloWorld");
int i2 = pair2.getFirst();
String s2 = pair2.getSecond();
}
```

Example 4: Pair.java

Example: Inheritance of Type Parameters I

```
public class Couple<T> extends Pair<T, T> {  
  
    public Couple(T first, T second) {  
        super(first, second);  
    }  
  
    public void swap() {  
        T tmp = this.getFirst();  
        this.setFirst(this.getSecond());  
        this.setSecond(tmp);  
    }  
  
    public List<T> toList() {  
        List<T> list = new ArrayList<>();  
        list.add(this.getFirst());  
    }  
}
```

Example: Inheritance of Type Parameters II

```
list.add(this.getSecond());  
return list;  
}  
  
public static void main(String[] args) {  
  
    Couple<Integer> couple = new Couple<>(100, 200);  
    int i1 = couple.getFirst();  
    int i2 = couple.getSecond();  
    List<Integer> list = couple.toList();  
}  
}
```

Example 5: Couple.java

Example: Nested Type Parameters I

```
public class PairOfBoxes<S, T> extends Pair<Box<S>, Box<T>> {  
  
    public PairOfBoxes(Box<S> first, Box<T> second) {  
        super(first, second);  
    }  
  
    public PairOfBoxes(S firstContent, T secondContent) {  
        super(new Box<S>(firstContent), new Box<T>(secondContent));  
    }  
  
    public S getFirstContent() {  
        return this.getFirst().getContent();  
    }  
}
```

Example: Nested Type Parameters II

```
public T getSecondContent() {  
    return this.getSecond().getContent();  
}  
  
public void setFirstContent(S content) {  
    this.getFirst().setContent(content);  
}  
  
public void setSecondContent(T content) {  
    this.getSecond().setContent(content);  
}  
  
public static void main(String[] args) {  
  
    PairOfBoxes<String, Integer> pairOfBoxes = new  
        PairOfBoxes<>("HelloWorld", 200);  
}
```

Example: Nested Type Parameters III

```
Box<String> box1 = pairOfBoxes.getFirst();  
Box<Integer> box2 = pairOfBoxes.getSecond();  
  
String s = pairOfBoxes.getFirstContent();  
Integer i = pairOfBoxes.getSecondContent();  
}  
}
```

Example 6: PairOfBoxes.java

Outline

Generic Types

Generic Classes and Interfaces

Bounded Type Parameters

Raw Types and Wildcards

Generic Methods

Limitations of Generics

Bounded Type Parameters

- ▶ In the examples before, the type parameters were **unbounded**
 - No restrictions on the types used in instantiations
 - No access to specific methods
- ▶ Note that the class declaration **class** Box<T> is a shortcut for **class** Box<T **extends** Object>
- ▶ Example of **bounded type parameters**:

```
public interface Country {  
    public String getLanguage();  
}  
public class Germany implements Country { ... }  
public class France implements Country { ... }
```

Example: Bounded Type Parameters I

```
public class Passport<T extends Country> {  
  
    private T country;  
  
    public Passport(T country) {  
        this.country = country;  
    }  
  
    public T getCountry() {  
        return this.country;  
    }  
  
    public String getLanguage() {  
        return this.country.getLanguage();  
    }  
}
```

Example: Bounded Type Parameters II

```
public static void main(String[] args) {  
    France france = new France();  
    Passport<France> passport = new Passport<>(france);  
    France country = passport.getCountry();  
  
    // the following line produces a compilation error  
    Passport<String> pp = new Passport<>("France");  
}  
}
```

Example 7: Passport.java

Bounded Type Parameters: Remarks

- ▶ When applied to type parameters, the keyword `extends` actually means “`extends` or `implements`”, i.e., the bounds can be either classes or interfaces
- ▶ Occasionally, two or more type bounds are necessary, for example `<T extends Comparable & Cloneable>`
- ▶ If multiple type bounds are specified, and one of them is a class, then the class must be specified first

```
public class A { ... }  
public interface B { ... }  
public interface C { ... }  
  
public class D <T extends A & B & C> { ... } // OK  
public class E <T extends B & A & C> { ... } // Not OK
```

Subtype Rules

- ▶ When type parameters are instantiated, the following **subtype rules** apply:
 - `List<String>` is a subtype of `Object`
 - `List<String>` is a subtype of `List`
 - `ArrayList<String>` is a subtype of `List<String>`
 - `Couple<String>` is a subtype of `Pair<String, String>`
- ▶ Counter-examples:
 - `List` is not a subtype of `List<String>`
 - `List<Integer>` is not a subtype of `List<String>`
 - `List<Number>` is not a subtype of `List<Integer>`
 - `List<Integer>` is not a subtype of `List<Number>`
 - `Passport<France>` is not a subtype of `Passport<Country>`
- ▶ The last two examples are surprising and often lead to misunderstanding

Outline

Generic Types

Generic Classes and Interfaces

Bounded Type Parameters

Raw Types and Wildcards

Generic Methods

Limitations of Generics



Raw Types

- ▶ A **raw type** is the name of a generic class or interface with an unspecified type parameter, for example `Box`
- ▶ Raw types are supported for compatibility reasons with Java 1.4 or less (using raw types is not recommended)
- ▶ Note that `Box` is not exactly the same as `Box<Object>`

```
Box rawBox;  
rawBox = new Box("HelloWorld"); // OK  
rawBox = new Box<String>("HelloWorld"); // OK  
rawBox.setContent(10); // OK  
  
Box<Object> objectBox;  
objectBox = new Box<>("HelloWorld"); // OK  
objectBox = new Box<String>("HelloWorld"); // Not OK  
objectBox.setContent(10); // OK
```

Wildcard Types

- ▶ In generic programs, the **wildcard** `?` represents an unknown type, for example `Box<?>`
- ▶ Note that `Box<?>` (unknown type) and `Box` (unspecified type) are not the same, because `Box<?>` guarantees type safety

```
Box rawBox;  
rawBox = new Box("HelloWorld"); // OK  
rawBox = new Box<String>("HelloWorld"); // OK  
rawBox.setContent(10); // OK  
  
Box<?> wildcardBox;  
wildcardBox = new Box<>("HelloWorld"); // OK  
wildcardBox = new Box<String>("HelloWorld"); // OK  
wildcardBox.setContent(10); // Not OK
```


Wildcard Types

- ▶ Wildcards can be used in declaration of ...
 - local variables
 - instance variables
 - static variables
 - method parameters
 - return values
- ▶ Using wildcards in return types is not recommended
- ▶ Wildcards are often used to bypass the restrictions of the strict subtype rules (while avoiding raw types)
- ▶ Note that wildcards cannot be used in the definition of generic classes or when invoking their constructors

Bounded Wildcard Types

- ▶ Note that `Box<?>` is a shortcut for `Box<? extends Object>`
- ▶ Wildcards can be **bounded** in two different ways:
 - Upper-bounded: `Box<? extends Number>`
 $\Leftrightarrow \{\text{Number, Byte, Double, Integer, Long, BigInteger, ...}\}$
 - Lower-bound: `Box<? super Integer>`
 $\Leftrightarrow \{\text{Integer, Number, Object}\}$
- ▶ The following subtype rules apply:
 - `List<Integer>` is a subtype of `List<?>`
 - `ArrayList<Integer>` is a subtype of `List<?>`
 - `List<Integer>` is a subtype of `List<? extends Integer>`
 - `List<Integer>` is a subtype of `List<? extends Number>`
 - `List<Number>` is a subtype of `List<? super Integer>`
 - `List<Number>` is a subtype of `List<? super Number>`

Using Unbounded Wildcards

- Unbounded wildcards are used when some code does not depend on the concrete type

```
public static void printList1(List<Object> list) {  
    for (Object e : list)  
        System.out.println(e + " ");  
}  
  
public static void printList2(List<?> list) {  
    for (Object e : list)  
        System.out.println(e + " ");  
}  
  
List<Integer> list = Arrays.asList(1, 2, 3);  
printList1(list); // Not OK  
printList2(list); // OK
```

Using Upper-Bounded Wildcards

- ▶ Upper-bounded wildcards are used when some code depends on the methods available for a certain type

```
public static double sum(List<? extends Number> list) {  
    double sum = 0.0;  
    for (Number number : list)  
        sum += number.doubleValue();  
    return sum;  
}
```

```
List<Integer> list1 = Arrays.asList(1, 2, 3);  
System.out.println("sum = " + sum(list1)); // OK
```

```
List<Double> list2 = Arrays.asList(1.2, 2.3, 3.5);  
System.out.println("sum = " + sum(list2)); // OK
```

Using Lower-Bounded Wildcards

- ▶ Lower-bounded wildcards are occasionally used when a variable holds data for use elsewhere

```
public static void addInts(List<? super Integer> list) {  
    for (int i = 1; i <= 10; i++)  
        list.add(i);  
}
```

```
List<Integer> list1 = new ArrayList<>();  
addInts(list1); // OK
```

```
List<Object> list2 = new ArrayList<>();  
addInts(list2); // OK
```

Outline

Generic Types

Generic Classes and Interfaces

Bounded Type Parameters

Raw Types and Wildcards

Generic Methods

Limitations of Generics



Generic Methods

- ▶ Generic methods are methods that specify their own type parameters (independently of any generic types of the class)
 - They can be defined in generic or non-generic classes and interfaces
 - Static and non-static generic methods are allowed, as well as generic constructors
- ▶ In a generic method, the type parameter's scope is limited to the method
- ▶ The type parameter of a generic method must appear before the method's return type
- ▶ The main purpose of generic methods is to ensure type safety between arguments and return values

Example: BoxUtil I

```
public class BoxUtil {  
  
    // non-generic method using wildcards  
    public static boolean compare1(Box<?> b1, Box<?> b2) {  
        return b1.getContent().equals(b2.getContent());  
    }  
  
    // generic method  
    public static <T> boolean compare2(Box<T> b1, Box<T> b2) {  
        return b1.getContent().equals(b2.getContent());  
    }  
  
    // generic method  
    public static <T> Couple<T> couple(Box<T> b1, Box<T> b2) {  
        return new Couple<T>(b1.getContent(), b2.getContent());  
    }  
}
```


Example: BoxUtil II

```
public static void main(String[] args) {  
    Box<String> box1 = new Box<>("Hello");  
    Box<String> box2 = new Box<>("World");  
    Box<Integer> box3 = new Box<>(10);  
  
    BoxUtil.compare1(box1, box2); // OK  
    BoxUtil.compare1(box1, box3); // OK  
  
    BoxUtil.compare2(box1, box2); // OK  
    BoxUtil.compare2(box1, box3); // Not OK  
  
    Couple<String> c1 = BoxUtil.couple(box1, box2); // OK  
    Couple<String> c2 = BoxUtil.couple(box1, box3); // Not OK  
}  
}
```

Example 8: BoxUtil.java

Outline

Generic Types

Generic Classes and Interfaces

Bounded Type Parameters

Raw Types and Wildcards

Generic Methods

Limitations of Generics

Type Erasure

- ▶ The Java compiler fully **erases** generic type parameters:
 - Generic types are replaced with their type bounds
 - Unbounded types are replaced by `Object`
 - Type casts are inserted if necessary
 - Bridge methods are generated to preserve polymorphism (they may appear in a stack trace)
- ▶ The produced bytecode, therefore, contains only ordinary classes, interfaces, and methods
- ▶ As a consequence, generics does not create new classes and implies no computational overhead at runtime
- ▶ Knowing about type erasure types helps understanding the limitations of Java generics

Creating Instances of Type Parameters

- ▶ It is impossible to create instances of type parameters
- ▶ The problem in the following example is that `new T()` is replaced by `new Object()`

```
public static <T> void fill(T[] array) {  
    for (int i = 0; i < array.length; i++)  
        array[i] = new T(); // Not OK  
}  
  
public static <T> void fillWithDefaults(T[] array, T  
    defaultValue) {  
    for (int i = 0; i < array.length; i++)  
        array[i] = defaultValue; // OK  
}
```

Creating Arrays of Type Parameters

- ▶ It is impossible to create arrays of type parameters
- ▶ The problem is that, for compatibility reasons, creating arrays in Java requires knowledge about its type
- ▶ Read detailed explanation [here](#)

```
public class ArrayList<E> implements List<E> {  
  
    private E[] elements; // OK  
  
    public ArrayList() {  
        this.elements = new E[10]; // Not OK  
        this.elements = (E[]) new Object[10]; // OK  
    }  
}
```

Declaring Static Variables of a Generic Type

- ▶ Static variables of type parameters are not allowed, because they are shared by all instances of that class
- ▶ What would be the type of the variable `defaultContent` in the following example?

```
public class Box<T> {  
  
    private static T defaultContent; // Not OK  
    private T content;  
  
    public Box() {  
        this.content = defaultContent;  
    }  
}
```

Method Overloading

- ▶ A class cannot have two overloaded methods that will have the same signature after type erasure

```
public interface ListPrinter {  
    public void print(List<String> strList);  
    public void print(List<Integer> intList); // Not OK  
    public void print(List<Double> intList); // Not OK  
}
```