

Object-Oriented Programming 2

Rolf Haenni & Andres Scheidegger

Exercises 2

1. Series of Values

Consider the following two generic functional interfaces `Function` and `Predicate`:

```
1 public interface Function<V> {  
2     public V apply(V value);  
3 }  
4  
5 public interface Predicate<V> {  
6     public boolean test(V value);  
7 }
```

Write a generic class `Series<V>`, which allows to generate finite series of values for different types. The class must provide the following methods:

- `boolean hasNext()`: checks if the series contains at least one additional value
- `V next()`: returns the next value in the series (if one exists)
- `void reset()`: resets the series to its initial state
- `List<V> toList()`: returns a list that contains all the values of the series

A series can be specified in two different ways:

1. Initial value, update function, condition

Example: $0, f(x) = x + 1, x \leq 10$ for $\langle 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 \rangle$

2. Initial value, update function, final value

Example: $0, f(x) = x + 2, 10$ for $\langle 0, 2, 4, 6, 8, 10 \rangle$

Write a generic class `PairSeries<S,T>`, which inherits from `Series<V>`. Its purpose is to produce a series of pairs of type `Pair<S,T>`. Write a constructor, which takes two series—one of type `S` and one of type `T`—as input and produces a corresponding series of pairs (its length corresponds to the shorter of the two input series).

Here is a test program:

```

1 public class PairSeriesTester {
2
3     public static void main(String[] args) {
4
5         Series<Integer> s1 = new Series<>(0, x -> x + 2, x -> x <= 10);
6         Series<String> s2 = new Series<>(" ", s -> s + "*", s -> s.
            length() <= 10);
7
8         PairSeries<Integer, String> s12 = new PairSeries<>(s1, s2);
9         System.out.println(s12.toList());
10    }
11 }

```

This is the output generated by the test program:

```
[[0,], [2,*], [4,**], [6,***], [8,****], [10,*****]]
```

3. The Comparable Interface

The generic Java interface `Comparable<T>` is used in methods such as `Collections.sort` or `Arrays.sort` to determine the *natural order* of the elements to be sorted. The classes `String`, `Integer`, `BigInteger`, etc. all implement this interface, for example `String` implements `Comparable<String>`.

- a) Define a new class `ComparablePair`, which inherits from `Pair` and implements the `Comparable` interface. Make sure that both generic types of your class also implement the `Comparable` interface. This allows you to define the natural order of a pair based on the natural order of its values by assuming that the order of the first value “dominates” the order of the second value. Examples: $(3, 4) < (6, 2)$, $(3, 4) > (1, 2)$, $(3, 4) < (3, 6)$, $(3, 4) > (3, 2)$, etc.

Test your solutions by calling `Collections.sort` for a list of comparable pairs.

- b) Write two generic static methods `getMin` and `getMax`, which expect two comparable pairs as inputs and return the minimum respectively maximum of the two (relative to their natural order).

Here is a test program:

```

1     public static void main(String[] args) {
2         ComparablePair<Integer,String> p1 = new ComparablePair<>(3, "
            Hello");
3         ComparablePair<Integer,String> p2 = new ComparablePair<>(3, "
            World");

```

```
4     ComparablePair<Integer,String> p3 = new ComparablePair<>(2, "
      Hello");
5     ComparablePair<Integer,String> p4 = new ComparablePair<>(2, "
      World");
6     ComparablePair<Integer,String> p5 = new ComparablePair<>(4, "
      Hello");
7     ComparablePair<Integer,String> p6 = new ComparablePair<>(4, "
      World");
8
9     System.out.println(ComparablePair.getMin(p1, p2));
10    System.out.println(ComparablePair.getMax(p1, p2));
11
12    List<ComparablePair<Integer,String>> list = new ArrayList<>();
13    list.add(p1);
14    list.add(p2);
15    list.add(p3);
16    list.add(p4);
17    list.add(p5);
18    list.add(p6);
19    Collections.sort(list);
20    System.out.println(list);
21 }
```

This is the output generated by the test program:

```
[3,Hello]
[3,World]
[[2,Hello], [2,World], [3,Hello], [3,World], [4,Hello], [4,World]]
```