


CEN 571 – Data Mining

Assignment 7: RDD



PREPARED:

Baftjar TABAKU

07.06.2020


Epoka University Tirana, ALBANIA ACCEPTED:

Prof.Dr. Arben Asllani

Tasks to complete

In this assignment, we work with 'csv' files named 'covid_19_us_data' and 'covid_19_us_hospital_beds'

 Download the files in your computer, study the structure of the file, and upload both of them in the HDFS subdirectory RDD/Ex4. Start the Spark shell.



2. Create an RDD named 'casesRDD' that captures the data from the 'covid19_us_data.csv' file. Display the first few records and the total number of records in this RDD.

```
Using Scala version 2.11.12 (OpenJDK 64-Bit Server VM, Java 1.8.0_252)
Type in expressions to have them evaluated.
Type in expressions to have the evaluated.
Type in expressions to have them evaluated.
Type in expressions to have the evaluated to expressions.
Type in expressions to express
```

 Create an RDD named 'hospitalsRDD' that captures the data from the covid19_us_hospital_beds.csv file. Display the first few records and the total number of records in this RDD.

```
scala> val hospitalsRDD= sc.textFile("RDD/Ex4/covid 19 hospital beds.csv")
hospitalsRDD: org.apache.spark.rdd.RDD[String] = RDD/Ex4/covid_19_hospital_beds.csv MapPartitionsRDD[3] at textFile at <console>:24

scala> val hospitalsFirstCases: array[String] = RDD/Ex4/covid_19_hospital_beds.csv MapPartitionsRDD[3] at textFile at <console>:24

scala> val hospitalsFirstCases: array[String] = Array(ORM:ExtDL) Hospital, INME, Hospital_TYPE, HQ_ADDRESS, HQ_ADDRESS1, HQ_CITY, HQ_STATE, HQ_ZIP_CODE, COUNTY_NAME, STATE_NAME, STATE_FIPS, CNTY_FIPS, FIPS, NTM_LICENSED_BEDS, NUM_STAFFED_BEDS, NUM_CID_REDS_NDUIL ICU_BEDS_PEDI_ICU_BEDS_BED_UTILIZATION, Potential_Increase_In_Bed_Capac, AVG_VENTILATOR_USAGE, latitude, longitude, = 6001.W
estern Regional Medical Facility = John Montford Unit, Short Term Acute Care Hospital, 4802 Peach Ave, Lubbock, TX, 79404, Lubbock, Texas, 48, 303, 48303, 550, 550, 96, 96, ., 0, 33.584
611, -101.7793662, 6003, Mildwood Lifestyle Center, Short Term Acute Care Hospital, 435 Life ...
scala> val topHospitalsList = hospitalsRDD.first
topHospitalsList: String = OBJECTID, HOSPITAL_NAME, HOSPITAL_TYPE, HQ_ADDRESS, HQ_ADDRESS, HQ_CITY, HQ_STATE_HQ_ZIP_CODE, COUNTY_NAME, STATE_NAME, STATE_NAME, STATE_NAME, STATE_FIPS, CNTY_FIPS, FIPS, NUM_LICENSED_BEDS, NUM_STAFFED_BEDS, NUM_STAFFED_BEDS, NUM_STAFFED_BEDS, NUM_CITY, HQ_STATE, HQ_ZIP_CODE, COUNTY_NAME, STATE_FIPS, CNTY_FIPS, FIPS, NUM_LICENSED_BEDS, NUM_STAFFED_BEDS, NUM_STA
```

4. Execute a query to display two select 'state', 'cases' and 'deaths' from the 'casesRDD' and store it into finalCasesRDD. Show the first few records and provide a screenshot of the result.

```
scala> import org.apache.spark.sql._
scala> import org.apache.spark.sql.types._
import org.apache.spark.sql.types._
scala> import org.apache.spark.sql.types._
scala> import org.apache.spark.sql.types._
scala> import org.apache.spark.sql.types._
scala> import org.apache.spark.sql.Row
import org.apache.spark.sql.Row
scala> val states cases deaths RDD = casesRDD.filter(line=>line!=topcaseslist).map(line=>line.split(",")).map(values=>Row(values(1), values(3).toLong, values(4).toLong))
scala> val state deaths = states_cases_deaths_RDD.take(10)
scala> val state_deaths = states_cases_deaths_RDD.take(10)
state_deaths.tarey(org.apache.spark.sql.Row) = MapPartitionsRDD[6] at map at <console>:34
scala> val state_deaths = states_cases_deaths_RDD.take(10)
state_deaths.tarey(org.apache.spark.sql.Row) = Arrayy([Washington,1,0], [Washington,1,0], [Washington,1,0], [California,1,0], [California,1,0
```

Execute a query to display two select 'STATE_NAME', 'HOSPITAL_NAME' and
 'HOSPITAL_TYPE' from the 'hospitalsRDD' and store it into finalHospitalsRDD. Show the
 first few records and provide a screenshot of the result.

```
scala> val hospitalsRddSelect = hospitalsRDD.filter(line=>line=copHospitalsList).map(line=>line.split(*,*)).map(values=>Row(values(3), values(1), values(2)))
hospitalsRddSelect: org.apache.spark.rdd.RDD[org.apache.spark.sql.Row] = MapPartitionsRDD[3] at map at <console>:34
scala> val state_deaths = hospitalsRddSelect.take(6)
state_deaths: Array(org.apache.spark.aql.Row] = Array([New York, Western New York Childrens Psychiatric Center, Psychiatric Hospital], [Texas, Western Regional Medical Facility = 3
ohn Montford Unit, Short Term Acute Care Hospital], [Georgia, Wildwood Lifestyle Center, Short Term Acute Care Hospital], [Alabama, EastPointe Hospital, Psychiatric Hospital], [New 3
exsey, Al Rashid Health and Wellness Center, Short Term Acute Care Hospital]
[Reas, Western Regional Medical Facility = John Montford Onit, Short Term Acute Care Hospital]
[Georgia, Wildwood Lifestyle Center, Short Term Acute Care Hospital]
[Reas AgastPointe Hospital, Psychiatric Hospital]
[Reas AgastPoi
```

Create a DataFrame named 'casesDF' and transform the data from 'finalCasesRDD' to this
DataFrame. Display the schema and the first few records of the 'casesDF'. Provide a
screenshot of the results.

7. Create a DataFrame named 'hospitalsDF' and transform the data from 'finalHospitalsRDD' to this DataFrame. Display the schema and the first few records of the 'hospitalsDF'. Provide a screenshot of the results.

```
scala val schema of hospitals = StructType (Array (StructField("state", StringType), StructField("hospital", StringType), StructField("hospital_type", StructField(hospital_type, StructField(hospital), StructField(hospital_type, StructField(hospital), StructField(hospital_type, StructField(hospital), StructField(hospital_type, StructField(hospital), StructField(hospital_type, StructField(hospital), StructField(hospital_type, StructField(hospital, StructField(hos
```

8. Execute another query that results in the 'casesDF' with just 'state' and 'cases' and only includes states with more than 1000 cases. Provide a screenshot of the result.

9. Create a new DataFrame that joins the two original DataFrames: 'casesDF' and 'hospitalsDF' by the state. Display the first 10 records. Provide a screenshot of the result.

```
scala> val joinedDataFrame = custom_casesDF.join(hospitalDF,custom_casesDF("state")====hospitalDF("state"))
joinedDataFrame: org.apache.spark.sql.DataFrame = [state: string, totcases: bigint ... 3 more fields]
scala> joinedDataFrame.show(10)
state|totcases|state|
                                 hospital
                                                  hospital_type|
         54643| Utah| Center for Change|Psychiatric Hospital|
 Utahl
         54643| Utah|Copper Hills Yout...|Psychiatric Hospital|
 Utahl
 Utahl
         54643| Utah|Northern Utah Reh...|Rehabilitation Ho...
 Utah|
         54643| Utah|
                          Layton Hospital|Short Term Acute ...
 Utah |
                        ViewPoint Center|Short Term Acute ...|
         54643| Utah|Kane County Hospital|Critical Access H...|
         54643| Utah|Utah Valley Speci...|Long Term Acute C...
 Utah|
         54643| Utah| Utah State Hospital|Psychiatric Hospital|
         54643| Utah|South Davis Commu...|Long Term Acute C...|
 Utah|
         54643| Utah|Marian Center at ...|Psychiatric Hospital|
 Utah|
only showing top 10 rows
scala>
```

10. Transform the last DataFrame into an RDD. Display the first 10 elements of the RDD.

```
scala> val transformedRdd = joinedDataFrame.rdd
transformedRdd: org.apache.spark.rdd.RDD[org.apache.spark.sql.Row] = MapPartitionsRDD[53] at rdd at <console>:32
scala> transformedRdd.take(5).foreach(println)
[Utah, 54643,Utah,Center for Change,Psychiatric Hospital]
[Utah,54643,Utah,Copper Hills Youth Center,Psychiatric Hospital]
[Utah,54643,Utah,Northern Utah Rehabilitation Hospital,Rehabilitation Hospital]
[Utah,54643,Utah,Layton Hospital,Short Term Acute Care Hospital]
[Utah,54643,Utah,ViewPoint Center,Short Term Acute Care Hospital]
scala>
```

11. Save the data from the RDD in the above step onto the cluster. Open another terminal and verify that results are stored in the cluster. Provide a screenshot of the result.