Quiz 3 (Version 2)

CS 320: Concepts of Programming Languages

October 28, 2026

Name:

BUID:

- ▷ You will have approximately 35 minutes to complete this quiz. Make sure to read every question; some are easier than others.
- ▷ Make it very clear what your final solution for each problem is (e.g., by surrounding it in a box). We reserve the right to mark off points if we cannot tell what your final solution is.
- ▷ You must show your work on all problems unless otherwise specified. A solution without work will be considered incorrect (and will be investigated for potential academic misconduct).

1 OCaml Programming

(10 points) Implement the function

```
val map2_opt : ('a -> 'b -> 'c) -> 'a list -> 'b list -> 'c list option
```

so that `map2_opt f l r` is `Some` of the list of results of applying `f` to the corresponding elements of `l` and `r`, in order. If `l` and `r` have different lengths, then the result is `None`.

```
let _ = assert(map2_opt (+) [1;2;3] [4;5;6] = Some [5;7;9])
let _ = assert(map2_opt (+) [1;2;3] [4;5] = None)
let _ = assert(map2_opt (+) [] [1] = None)
let _ = assert(map2_opt (+) [] [] = Some [])
```

2 Formal Grammar

Consider the following BNF grammar.

```
<e>  ::= fun <v> -> <e> | <e> <e2> | <e2>
<e2> ::= <v> | (<e>)
<v>  ::= x | y | z
```

A. (10 points) Demonstrate that the sentence `(fun x -> x) (y z)` is recognized by the above grammar by providing a parse tree for it.

The grammar from the previous part is reproduced for convenience.

```
<e>  ::= fun <v> -> <e> | <e> <e2> | <e2>
<e2> ::= <v> | (<e>)
<v>  ::= x | y | z
```

B. (10 points) Demonstrate that the above grammar is ambiguous by determining a sentence with multiple parse trees. Include both parse trees in your answer.