

Parser Generators

Concepts of Programming Languages
Lecture 13

Outline

- » Extend our BNF syntax to be a bit more convenient
- » Introduce **parser generators**
- » Discuss **lexical analysis**
- » Demo **Menhir**, the parser generator for this course

Recap

Recall: Example

<expr>	::=	<op1>	<expr>
	 	<op2>	<expr> <expr>
	 	<var>	
<op1>	::=	not	
<op2>	::=	and	 or
<var>	::=	x	 y z

Recall: Example

<expr> ::= **<op1>** **<expr>**
 | **<op2>** **<expr>** **<expr>**
 | **<var>**


<op1> ::= **not**

<op2> ::= **and** | **or**


<var> ::= **x** | **y** | **z**

tokens (terminal symbols)

Recall: Example



Recall: Example




Recall: Parse Trees

<expr>	::=	<op1>	<expr>
			<op2> <expr> <expr>
			<var>
<op1>	::=	not	
<op2>	::=	and	or
<var>	::=	x	y z

Recall: Parse Trees



<expr>	::=	<op1>	<expr>
		<op2>	<expr> <expr>
		<var>	
<op1>	::=	not	
<op2>	::=	and or	
<var>	::=	x y z	

<expr>





Recall: Parse Trees

<expr>	::=	<op1>	<expr>
		<op2>	<expr> <expr>
		<var>	
<op1>	::=	not	
<op2>	::=	and	 or
<var>	::=	x	 y z



Recall: Parse Trees


<expr>	::=	<op1>	<expr>
		<op2>	<expr> <expr>
		<var>	
<op1>	::=	not	
<op2>	::=	and or	
<var>	::=	x y z	



Recall: Parse Trees

<expr>	::=	<op1>	<expr>
		<op2>	<expr> <expr>
		<var>	
<op1>	::=	not	
<op2>	::=	and	or
<var>	::=	x	y z


<expr>
<op2> **<expr>** **<expr>**
and **<expr>** **<expr>**
and **<op1>** **<expr>** **<expr>**



Recall: Parse Trees

<expr>	::=	<op1>	<expr>
		<op2>	<expr> <expr>
		<var>	
<op1>	::=	not	
<op2>	::=	and	or
<var>	::=	x	y z


<expr>
<op2> **<expr>** **<expr>**
and **<expr>** **<expr>**
and **<op1>** **<expr>** **<expr>**
and **not** **<expr>** **<expr>**



Recall: Parse Trees

<expr>	::=	<op1>	<expr>
		<op2>	<expr> <expr>
		<var>	
<op1>	::=	not	
<op2>	::=	and	or
<var>	::=	x	y z


<expr>
<op2> **<expr>** **<expr>**
and **<expr>** **<expr>**
and **<op1>** **<expr>** **<expr>**
and **not** **<expr>** **<expr>**
and **not** **<var>** **<expr>**



Recall: Parse Trees

<expr>	::=	<op1>	<expr>
		<op2>	<expr> <expr>
		<var>	
<op1>	::=	not	
<op2>	::=	and or	
<var>	::=	x y z	


<expr>
<op2> **<expr>** **<expr>**
and **<expr>** **<expr>**
and **<op1>** **<expr>** **<expr>**
and **not** **<expr>** **<expr>**
and **not** **<var>** **<expr>**
and **not** **x** **<expr>**



Recall: Parse Trees

<expr>	::=	<op1>	<expr>
		<op2>	<expr> <expr>
		<var>	
<op1>	::=	not	
<op2>	::=	and	or
<var>	::=	x	y z


<expr>
<op2> **<expr>** **<expr>**
and **<expr>** **<expr>**
and **<op1>** **<expr>** **<expr>**
and not **<expr>** **<expr>**
and not **<var>** **<expr>**
and not **x** **<expr>**
and not **x** **<var>**



Recall: Parse Trees

<expr>	::=	<op1>	<expr>	
		 	<op2>	<expr> <expr>
		 	<var>	
<op1>	::=	not		
<op2>	::=	and	 	or
<var>	::=	x	 	y z


<expr>
<op2> <expr> <expr>
and <expr> <expr>
and <op1> <expr> <expr>
and not <expr> <expr>
and not <var> <expr>
and not x <expr>
and not x <var>
and not x y



Recall: Parse Trees

<expr>	::=	<op1>	<expr>
		<op2>	<expr> <expr>
		<var>	
<op1>	::=	not	
<op2>	::=	and or	
<var>	::=	x y z	

<expr>
<op2> **<expr>** **<expr>**
and **<expr>** **<expr>**
and **<op1>** **<expr>** **<expr>**
and **not** **<expr>** **<expr>**
and **not** **<var>** **<expr>**
and **not** **x** **<expr>**
and **not** **x** **<var>**
and **not** **x** **y**



Recall: Ambiguity in Formal Grammar

Recall: Ambiguity in Formal Grammar

Definition. A BNF grammar is **ambiguous** if there is a sentence with multiple parse trees/leftmost derivations.

Recall: Ambiguity in Formal Grammar

Definition. A BNF grammar is **ambiguous** if there is a sentence with multiple parse trees/
leftmost derivations.

```
<expr> ::= <expr> <op> <expr>
          | <var>
<op>    ::= +
<var>   ::= x | y | z
```

Recall: Ambiguity in Formal Grammar

Definition. A BNF grammar is **ambiguous** if there is a sentence with multiple parse trees/
leftmost derivations.

```
<expr> ::= <expr> <op> <expr>
          | <var>
<op>    ::= +
<var>   ::= x | y | z
```


x + y + z can be derived as

Recall: Ambiguity in Formal Grammar

Definition. A BNF grammar is **ambiguous** if there is a sentence with multiple parse trees/leftmost derivations.

```
<expr> ::= <expr> <op> <expr>
          | <var>
<op>    ::= +
<var>   ::= x | y | z
```

x + y + z can be derived as





Recall: Ambiguity in Formal Grammar

Definition. A BNF grammar is **ambiguous** if there is a sentence with multiple parse trees/leftmost derivations.

```
<expr> ::= <expr> <op> <expr>
          | <var>
<op>    ::= +
<var>   ::= x | y | z
```

x + y + z can be derived as






Practice Problem

```
<expr> ::= fun <var> -> <expr>
          | <expr> <expr>
          | <var>
<var>   ::= x
```

Demonstrate that the above grammar is ambiguous

$\langle \text{expr} \rangle ::= \text{fun } \langle \text{var} \rangle \rightarrow \langle \text{expr} \rangle$
$\quad \quad \quad \quad \langle \text{expr} \rangle \langle \text{expr} \rangle$
$\quad \quad \quad \quad \langle \text{var} \rangle$
$\langle \text{var} \rangle ::= x$

Solution



Handwritten box containing $x \ x \ x$.


Motivation

A Note on "History"


Lexical analysis and parsing are typically associated with *compiler design*

Compiler design was once a fundamental requirement in CS programs. *This is not really the case anymore*

Also, we have *parser generators*



Parser Generators



Parser generators are programs which, given a representation of a language (e.g., as an ***EBNF grammar***), build a parser for you


(So there was a point to learning (E)BNF for the "real-world")

Aside: Domain-Specific Languages

Domain-specific languages (DSLs) are simple programming languages for domain-specific tasks, e.g.

- » Emacs Lisp
- » SQL

*We need **parsers** for these languages if we want to use them...*



Extended BNF

Extended BNF

```
<expr> ::= <only-mul-div> { (+ | -) <only-mul-div> }  
<only-mul-div> ::= <var-or-parens> { (* | /) <var-or-parens> }  
<var-or-parens> ::= x | ( <expr> )
```


Extended BNF

```
<expr> ::= <only-mul-div> { (+ | -) <only-mul-div> }  
<only-mul-div> ::= <var-or-parens> { (* | /) <var-or-parens> }  
<var-or-parens> ::= x | ( <expr> )
```

Extended BNF is essentially syntactic sugar. It let's us express BNF grammars in more compact way

Extended BNF

```
<expr> ::= <only-mul-div> { (+ | -) <only-mul-div> }  
<only-mul-div> ::= <var-or-parens> { (* | /) <var-or-parens> }  
<var-or-parens> ::= x | ( <expr> )
```

Extended BNF is essentially syntactic sugar. It let's us express BNF grammars in more compact way

EBNF is not more expressive than BNF

Extended BNF

```
<expr> ::= <only-mul-div> { (+ | -) <only-mul-div> }  
<only-mul-div> ::= <var-or-parens> { (* | /) <var-or-parens> }  
<var-or-parens> ::= x | ( <expr> )
```

Extended BNF is essentially syntactic sugar. It let's us express BNF grammars in more compact way

EBNF is not more expressive than BNF

But it allows us to specify:

Extended BNF

```
<expr> ::= <only-mul-div> { (+ | -) <only-mul-div> }  
<only-mul-div> ::= <var-or-parens> { (* | /) <var-or-parens> }  
<var-or-parens> ::= x | ( <expr> )
```

Extended BNF is essentially syntactic sugar. It let's us express BNF grammars in more compact way

EBNF is not more expressive than BNF

But it allows us to specify:

» Optional parts of production rule

Extended BNF

<code><expr></code>	<code>::=</code>	<code><only-mul-div></code>	<code>{</code>	<code>(+ -)</code>	<code><only-mul-div></code>	<code>}</code>
<code><only-mul-div></code>	<code>::=</code>	<code><var-or-parens></code>	<code>{</code>	<code>(* /)</code>	<code><var-or-parens></code>	<code>}</code>
<code><var-or-parens></code>	<code>::=</code>	<code>x (<expr>)</code>				

Extended BNF is essentially syntactic sugar. It let's us express BNF grammars in more compact way

EBNF is not more expressive than BNF

But it allows us to specify:

- » Optional parts of production rule
- » Repeated parts of a production rule

Extended BNF

<code><expr></code>	<code>::=</code>	<code><only-mul-div></code>	<code>{</code>	<code>(+ -)</code>	<code><only-mul-div></code>	<code>}</code>
<code><only-mul-div></code>	<code>::=</code>	<code><var-or-parens></code>	<code>{</code>	<code>(* /)</code>	<code><var-or-parens></code>	<code>}</code>
<code><var-or-parens></code>	<code>::=</code>	<code>x (<expr>)</code>				

Extended BNF is essentially syntactic sugar. It let's us express BNF grammars in more compact way

EBNF is not more expressive than BNF

But it allows us to specify:

- » Optional parts of production rule
- » Repeated parts of a production rule

Note: EBNF means different things to different people

Optional Syntax

BNF:

```
<expr> ::= if <expr> then <expr>  
          | if <expr> then <expr> else <else>  
<else> ::= else <expr>
```

EBNF:

```
<expr> ::= if <expr> then <expr> [ else <expr> ]
```

Menhir:

```
expr =  
  | IF; e1 = expr; THEN; e2 = expr; e3_opt = else?  
    { match e3_opt with  
      | None -> It (e1, e2)  
      | Some e3 -> Ite (e1, e2, e3)  
    }  
else =  
  | ELSE; e = expr { e }
```

Repetition Syntax

BNF: `<word> ::= <letter> | <letter> <word>`

EBNF: `<word> ::= <letter> { <letter> }`

Menhir:

```
word =  
  | l = letter; ls = letter*  
  { String.of_list (l :: ls) }
```


Interlude: Regular Expressions

Regular Grammars

~~$\langle a \rangle ::= b \langle c \rangle d$~~
 ~~$\langle a \rangle ::= \langle b \rangle c$~~

$\langle \text{nonterminal} \rangle ::= \text{terminal}$

$\langle \text{nonterminal} \rangle ::= \text{terminal} \langle \text{nonterminal} \rangle$

$\langle \text{nonterminal} \rangle ::= \epsilon$ (the empty string)

A **regular grammar** is a BNF grammar with the above kinds of rules

Regular grammars are easier to parse

Example

$\langle s \rangle$

$a \langle s \rangle$

$a a \langle s \rangle$

$a a a \langle \epsilon \rangle$

$a a a b \langle a \rangle$

$a a a b c \langle a \rangle$

$a a a b c c \langle a \rangle$

$a a a b c c$

$\langle s \rangle ::= a \langle s \rangle$

$\langle s \rangle ::= b \langle a \rangle$

$\langle a \rangle ::= \epsilon$

$\langle a \rangle ::= c \langle a \rangle$

Regular Expressions (Formally)

Regular Expressions (Formally)

Regular expressions (Regex) provide a compact way of describing regular grammars:

Regular Expressions (Formally)

Regular expressions (Regex) provide a compact way of describing regular grammars:

» A **terminal symbols** is a regex

Regular Expressions (Formally)

Regular expressions (Regex) provide a compact way of describing regular grammars:

» A **terminal symbols** is a regex

» **[t1 ... tk]** is a regex describing an **any one of** the symbols **t1, t2, ..., tk**

Regular Expressions (Formally)

Regular expressions (Regex) provide a compact way of describing regular grammars:

» A **terminal symbols** is a regex

» [**t1 ... tk**] is a regex describing an **any one of** the symbols **t1, t2, ..., tk**

» (**e1 | ... | ek**) is a regex describing any one of the ~~expressions~~ ^{regex} **e1, e2, ..., ek**

Regular Expressions (Formally)

Regular expressions (Regex) provide a compact way of describing regular grammars:

- » A **terminal symbols** is a regex
- » **[t1 ... tk]** is a regex describing an **any one of** the symbols **t1, t2, ..., tk**
- » **(e1 | ... | ek)** is a regex describing any one of the expressions **e1, e2, ..., ek**
- » **exp*** is a regex describing **zero or more occurrences** of **exp**

Regular Expressions (Formally)

Regular expressions (Regex) provide a compact way of describing regular grammars:

- » A **terminal symbols** is a regex
- » **[t1 ... tk]** is a regex describing an **any one of** the symbols **t1, t2, ..., tk**
- » **(e1 | ... | ek)** is a regex describing any one of the expressions **e1, e2, ..., ek**
- » **exp*** is a regex describing **zero or more occurrences** of **exp**
- » **exp+** is a regex describing **one or more occurrences** of **exp**

Regular Expressions (Formally)

Regular expressions (Regex) provide a compact way of describing regular grammars:

- » A **terminal symbols** is a regex
- » **[t1 ... tk]** is a regex describing an **any one of** the symbols **t1, t2, ..., tk**
- » **(e1 | ... | ek)** is a regex describing any one of the expressions **e1, e2, ..., ek**
- » **exp*** is a regex describing **zero or more occurrences** of **exp**
- » **exp+** is a regex describing **one or more occurrences** of **exp**
- » **exp?** is a regex describing **zero or one occurrences** of **exp**

Example

$\langle s \rangle ::= a \langle s \rangle$

$\langle s \rangle ::= b \langle a \rangle$

$\langle a \rangle ::= \epsilon$

$\langle a \rangle ::= c \langle a \rangle$

is equivalent to

$a^* b c^*$

or

$'a' * 'b' 'c' *$

in ocamllex syntax

Example: Numbers and Variables

$-?[0-9]^+$

option (pointing to $-?$)

numbers (pointing to $[0-9]^+$)

1 or more (pointing to $^+$)

- 103

123

9967

$[a-z][a-zA-Z_']^*$

lowercase letter (pointing to $[a-z]$)

1 or more (pointing to *)

variables (pointing to $[a-zA-Z_']$)

x

x y z _ z y x '

a _ _ ' _ _ _

We'll leave it there, take CS332
if you want more, or read the
Wikipedia page...

Lexical Analysis

The "Lexing" Problem

"let" \approx ['l', 'e', 't'] \mapsto *LET*

"fun" \approx ['f', 'u', 'n'] \mapsto *FUN*

The "Lexing" Problem

"let" \approx ['l', 'e', 't'] \mapsto *LET*

"fun" \approx ['f', 'u', 'n'] \mapsto *FUN*

The Goal. Convert a stream of characters into a stream of tokens

The "Lexing" Problem

"let" \approx ['l', 'e', 't'] \mapsto *LET*

"fun" \approx ['f', 'u', 'n'] \mapsto *FUN*

***The Goal.** Convert a stream of characters into a stream of tokens*

» Characters are **grouped** so together so they correspond to the *smallest units* at the level of the language

The "Lexing" Problem

"let" \approx ['l', 'e', 't'] \mapsto *LET*

"fun" \approx ['f', 'u', 'n'] \mapsto *FUN*

The Goal. *Convert a stream of characters into a stream of tokens*

- » Characters are **grouped** so together so they correspond to the *smallest units* at the level of the language
- » Whitespace and comments are *ignored*

The "Lexing" Problem

"let" \approx ['l', 'e', 't'] \mapsto *LET*

"fun" \approx ['f', 'u', 'n'] \mapsto *FUN*

The Goal. *Convert a stream of characters into a stream of tokens*

- » Characters are **grouped** so together so they correspond to the *smallest units* at the level of the language
- » Whitespace and comments are *ignored*
- » **Syntax errors** are caught, when possible

Lexing vs. Parsing

Lexing vs. Parsing

Lexical Analysis is about *small-scale* language constructs

Lexing vs. Parsing

Lexical Analysis is about *small-scale* language constructs

» keywords, names, literals

Lexing vs. Parsing

Lexical Analysis is about *small-scale* language constructs

» keywords, names, literals

Syntactic Analysis (Parsing) is about *large-scale* language constructs

Lexing vs. Parsing

Lexical Analysis is about *small-scale* language constructs

- » keywords, names, literals

Syntactic Analysis (Parsing) is about *large-scale* language constructs

- » expressions, statements, modules

Why separate them?

Why separate them?

*Good question...*for simple implementations, we don't

But there are benefits for larger projects:

Why separate them?

Good question... for simple implementations, we don't

But there are benefits for larger projects:

» **Simplicity.** It's *easier to think about* parsing if we don't need to worry about whitespace, characters, etc.

Why separate them?

Good question... for simple implementations, we don't

But there are benefits for larger projects:

» **Simplicity.** It's *easier to think about* parsing if we don't need to worry about whitespace, characters, etc.

» **Portability.** Files are finicky things, handled differently across different operating systems.

Abstracting this away for parsing is just good software engineering

Lexemes and Tokens

<u>input program:</u>	fun	⌊	->	⌊	++	[100]
<u>lexemes:</u>	"fun"	"⌊"	"->"	"⌊"	"++"	"["	"100"	"]"
<u>tokens:</u>	FUN	(ID "⌊")	ARR	(ID "⌊")	(OP "++")	LBRAK	(INT 100)	RBRAK

Lexemes and Tokens

<u>input program:</u>	fun	⌊	->	⌊	++	[100]
<u>lexemes:</u>	"fun"	"⌊"	"->"	"⌊"	"++"	"["	"100"	"]"
<u>tokens:</u>	FUN	(ID "⌊")	ARR	(ID "⌊")	(OP "++")	LBRAK	(INT 100)	RBRAK

A **lexeme** is a **sequence of characters** associated a syntactic unit in a language

Lexemes and Tokens

<u>input program:</u>	fun	l	->	l	++	[100]
<u>lexemes:</u>	"fun"	"l"	"->"	"l"	"++"	"["	"100"	"]"
<u>tokens:</u>	FUN	(ID "l")	ARR	(ID "l")	(OP "++")	LBRAK	(INT 100)	RBRAK

A **lexeme** is a **sequence of characters** associated a syntactic unit in a language

A **token** is a lexeme together with information about **what kind of unit it is**

Lexemes and Tokens

<u>input program:</u>	fun	l	->	l	++	[100]
<u>lexemes:</u>	"fun"	"l"	"->"	"l"	"++"	"["	"100"	"]"
<u>tokens:</u>	FUN	(ID "l")	ARR	(ID "l")	(OP "++")	LBRAK	(INT 100)	RBRAK

A **lexeme** is a **sequence of characters** associated a syntactic unit in a language

A **token** is a lexeme together with information about **what kind of unit it is**

» "12" and "234" are both INT_LITS, whereas "let" is a KEYWORD.

Lexemes and Tokens

<u>input program:</u>	fun	l	->	l	++	[100]
<u>lexemes:</u>	"fun"	"l"	"->"	"l"	"++"	"["	"100"	"]"
<u>tokens:</u>	FUN	(ID "l")	ARR	(ID "l")	(OP "++")	LBRAK	(INT 100)	RBRAK

A **lexeme** is a **sequence of characters** associated a syntactic unit in a language

A **token** is a lexeme together with information about **what kind of unit it is**

» "12" and "234" are both INT_LITS, whereas "let" is a KEYWORD.

We typically represent tokens as an ADT

Aside: One Token at a time

" **let**@#_)(\$#@_J_@0#GKJ" ^{next_token} → (LET, "@#_)(\$#@_J_@0#GKJ")

"le x = 2" ^{next_token} → **FAILURE**

Aside: One Token at a time

" let@#_) (\$#@_J_@0#GKJ" ^{next_token} → (LET, "@#_) (\$#@_J_@0#GKJ")

"le x = 2" ^{next_token} → **FAILURE**

The approach:

Aside: One Token at a time

" **let**@#_)(\$#@_J_@0#GKJ" ^{next_token}  (LET, "@#_)(\$#@_J_@0#GKJ")

"le x = 2" ^{next_token}  **FAILURE**

The approach:

- » Given a stream of characters, determine if there is a valid lexeme at the *beginning*

Aside: One Token at a time

" **let**@#_)(\$#@_J_@0#GKJ" ^{next_token} → (LET, "@#_)(\$#@_J_@0#GKJ")

"le x = 2" ^{next_token} → **FAILURE**

The approach:

- » Given a stream of characters, determine if there is a valid lexeme at the *beginning*
- » If there is, return its corresponding token and the *remainder of the stream*

Parsing with Menhir

General Parsing

General Parsing

***In Theory.** Determine if a given sentence is recognized by a given grammar*

General Parsing

In Theory. Determine if a given sentence is recognized by a given grammar

In Practice. Given a grammar, write a program which converts a string recognized by that grammar into an ADT

Today

```
<prog> ::= <expr>

<expr> ::= let <var> = <expr> in <expr>
        | <expr1>

<bop>   ::= + | - | * | /

<expr1> ::= <expr1> <bop> <expr1>
        | <num>
        | <var>
        | ( <expr> )

<num>   ::= 0 ; DUMMY VALUE
<var>   ::= x ; DUMMY VALUE

; In lex.mll:
;
; let num = '-'? ['0'-'9']+
; let var = ['a'-'z' '_' ] ['a'-'z' 'A'-'Z' '0'-'9' '_' '\''']*
```

Operators in order of increasing precedence:

Operator	Associativity
+, -	left
*, /	left

We'll be building a parser for the this grammar

A Rough Sketch

1. Specify the tokens (i.e., terminal symbols) of the grammar
2. Specify the rules of the grammar (using a BNF-like syntax)
3. Specify the rules of the lexer (i.e., which strings go to which tokens)