

# Parser Generators

**Concepts of Programming Languages**  
**Lecture 13**

# Outline

- » Extend our BNF syntax to be a bit more convenient
- » Introduce **parser generators**
- » Discuss **lexical analysis**
- » Demo **Menhir**, the parser generator for this course

# Recap

# Recall: Example

<b>&lt;expr&gt;</b>	<b>::=</b>	<b>&lt;op1&gt;</b>	<b>&lt;expr&gt;</b>
	<b> </b>	<b>&lt;op2&gt;</b>	<b>&lt;expr&gt; &lt;expr&gt;</b>
	<b> </b>	<b>&lt;var&gt;</b>	
<b>&lt;op1&gt;</b>	<b>::=</b>	<b>not</b>	
<b>&lt;op2&gt;</b>	<b>::=</b>	<b>and</b>	<b>  or</b>
<b>&lt;var&gt;</b>	<b>::=</b>	<b>x</b>	<b>  y   z</b>

# Recall: Example

**<expr>** ::= **<op1>** **<expr>**  
          | **<op2>** **<expr>** **<expr>**  
          | **<var>**


**<op1>** ::= **not**

**<op2>** ::= **and** | **or**


**<var>** ::= **x** | **y** | **z**

tokens (terminal symbols)

# Recall: Example



# Recall: Example



# Recall: Parse Trees


<expr>	::=	<op1>	<expr>
			<op2> <expr> <expr>
			<var>
<op1>	::=	not	
<op2>	::=	and	or
<var>	::=	x	y   z



# Recall: Parse Trees



<b>&lt;expr&gt;</b>	<b>::=</b>	<b>&lt;op1&gt;</b>	<b>&lt;expr&gt;</b>
			<b>&lt;op2&gt;</b> <b>&lt;expr&gt;</b> <b>&lt;expr&gt;</b>
			<b>&lt;var&gt;</b>
<b>&lt;op1&gt;</b>	<b>::=</b>	<b>not</b>	
<b>&lt;op2&gt;</b>	<b>::=</b>	<b>and</b>	<b>or</b>
<b>&lt;var&gt;</b>	<b>::=</b>	<b>x</b>	<b>y</b>   <b>z</b>

**<expr>**





# Recall: Parse Trees

<b>&lt;expr&gt;</b>	<b>::=</b>	<b>&lt;op1&gt;</b>	<b>&lt;expr&gt;</b>
		<b>&lt;op2&gt;</b>	<b>&lt;expr&gt; &lt;expr&gt;</b>
		<b>&lt;var&gt;</b>	
<b>&lt;op1&gt;</b>	<b>::=</b>	<b>not</b>	
<b>&lt;op2&gt;</b>	<b>::=</b>	<b>and</b>	<b>  or</b>
<b>&lt;var&gt;</b>	<b>::=</b>	<b>x</b>	<b>  y   z</b>



# Recall: Parse Trees


<b>&lt;expr&gt;</b>	<b>::=</b>	<b>&lt;op1&gt;</b>	<b>&lt;expr&gt;</b>
		<b>&lt;op2&gt;</b>	<b>&lt;expr&gt;</b> <b>&lt;expr&gt;</b>
		<b>&lt;var&gt;</b>	
<b>&lt;op1&gt;</b>	<b>::=</b>	<b>not</b>	
<b>&lt;op2&gt;</b>	<b>::=</b>	<b>and</b>   <b>or</b>	
<b>&lt;var&gt;</b>	<b>::=</b>	<b>x</b>   <b>y</b>   <b>z</b>	



# Recall: Parse Trees

<b>&lt;expr&gt;</b>	<b>::=</b>	<b>&lt;op1&gt;</b>	<b>&lt;expr&gt;</b>
		<b>&lt;op2&gt;</b>	<b>&lt;expr&gt;</b> <b>&lt;expr&gt;</b>
		<b>&lt;var&gt;</b>	
<b>&lt;op1&gt;</b>	<b>::=</b>	<b>not</b>	
<b>&lt;op2&gt;</b>	<b>::=</b>	<b>and</b>	<b>or</b>
<b>&lt;var&gt;</b>	<b>::=</b>	<b>x</b>	<b>y</b> <b>z</b>


**<expr>**  
**<op2>** **<expr>** **<expr>**  
**and** **<expr>** **<expr>**  
**and** **<op1>** **<expr>** **<expr>**



# Recall: Parse Trees

<b>&lt;expr&gt;</b>	<b>::=</b>	<b>&lt;op1&gt;</b>	<b>&lt;expr&gt;</b>
		<b>&lt;op2&gt;</b>	<b>&lt;expr&gt;</b> <b>&lt;expr&gt;</b>
		<b>&lt;var&gt;</b>	
<b>&lt;op1&gt;</b>	<b>::=</b>	<b>not</b>	
<b>&lt;op2&gt;</b>	<b>::=</b>	<b>and</b>	<b>or</b>
<b>&lt;var&gt;</b>	<b>::=</b>	<b>x</b>	<b>y</b> <b>z</b>


**<expr>**  
**<op2>** **<expr>** **<expr>**  
**and** **<expr>** **<expr>**  
**and** **<op1>** **<expr>** **<expr>**  
**and** **not** **<expr>** **<expr>**



# Recall: Parse Trees

<b>&lt;expr&gt;</b>	<b>::=</b>	<b>&lt;op1&gt;</b>	<b>&lt;expr&gt;</b>	
		<b> </b>	<b>&lt;op2&gt;</b>	<b>&lt;expr&gt; &lt;expr&gt;</b>
		<b> </b>	<b>&lt;var&gt;</b>	
<b>&lt;op1&gt;</b>	<b>::=</b>	<b>not</b>		
<b>&lt;op2&gt;</b>	<b>::=</b>	<b>and</b>	<b>  or</b>	
<b>&lt;var&gt;</b>	<b>::=</b>	<b>x</b>	<b>  y</b>	<b>  z</b>


<expr>  
<op2> <expr> <expr>  
and <expr> <expr>  
and <op1> <expr> <expr>  
and not <expr> <expr>  
and not <var> <expr>



# Recall: Parse Trees

<b>&lt;expr&gt;</b>	<b>::=</b>	<b>&lt;op1&gt;</b>	<b>&lt;expr&gt;</b>
		<b>&lt;op2&gt;</b>	<b>&lt;expr&gt;</b> <b>&lt;expr&gt;</b>
		<b>&lt;var&gt;</b>	
<b>&lt;op1&gt;</b>	<b>::=</b>	<b>not</b>	
<b>&lt;op2&gt;</b>	<b>::=</b>	<b>and</b>   <b>or</b>	
<b>&lt;var&gt;</b>	<b>::=</b>	<b>x</b>   <b>y</b>   <b>z</b>	


**<expr>**  
**<op2>** **<expr>** **<expr>**  
**and** **<expr>** **<expr>**  
**and** **<op1>** **<expr>** **<expr>**  
**and** **not** **<expr>** **<expr>**  
**and** **not** **<var>** **<expr>**  
**and** **not** **x** **<expr>**



# Recall: Parse Trees

<b>&lt;expr&gt;</b>	<b>::=</b>	<b>&lt;op1&gt;</b>	<b>&lt;expr&gt;</b>
		<b>&lt;op2&gt;</b>	<b>&lt;expr&gt;</b> <b>&lt;expr&gt;</b>
		<b>&lt;var&gt;</b>	
<b>&lt;op1&gt;</b>	<b>::=</b>	<b>not</b>	
<b>&lt;op2&gt;</b>	<b>::=</b>	<b>and</b>	<b>or</b>
<b>&lt;var&gt;</b>	<b>::=</b>	<b>x</b>	<b>y</b> <b>z</b>

**<expr>**  
**<op2>** **<expr>** **<expr>**  
**and** **<expr>** **<expr>**  
**and** **<op1>** **<expr>** **<expr>**  
**and not** **<expr>** **<expr>**  
**and not** **<var>** **<expr>**  
**and not** **x** **<expr>**  
**and not** **x** **<var>**






# Recall: Parse Trees

<b>&lt;expr&gt;</b>	<b>::=</b>	<b>&lt;op1&gt;</b>	<b>&lt;expr&gt;</b>
		<b>&lt;op2&gt;</b>	<b>&lt;expr&gt;</b> <b>&lt;expr&gt;</b>
		<b>&lt;var&gt;</b>	
<b>&lt;op1&gt;</b>	<b>::=</b>	<b>not</b>	
<b>&lt;op2&gt;</b>	<b>::=</b>	<b>and</b>	<b>or</b>
<b>&lt;var&gt;</b>	<b>::=</b>	<b>x</b>	<b>y</b> <b>z</b>


**<expr>**  
**<op2>** **<expr>** **<expr>**  
**and** **<expr>** **<expr>**  
**and** **<op1>** **<expr>** **<expr>**  
**and not** **<expr>** **<expr>**  
**and not** **<var>** **<expr>**  
**and not** **x** **<expr>**  
**and not** **x** **<var>**  
**and not** **x** **y**



# Recall: Parse Trees

<b>&lt;expr&gt;</b>	<b>::=</b>	<b>&lt;op1&gt;</b>	<b>&lt;expr&gt;</b>	
			<b>&lt;op2&gt;</b>	<b>&lt;expr&gt;</b> <b>&lt;expr&gt;</b>
			<b>&lt;var&gt;</b>	
<b>&lt;op1&gt;</b>	<b>::=</b>	<b>not</b>		
<b>&lt;op2&gt;</b>	<b>::=</b>	<b>and</b>		<b>or</b>
<b>&lt;var&gt;</b>	<b>::=</b>	<b>x</b>		<b>y</b>   <b>z</b>

<expr>  
<op2> <expr> <expr>  
and <expr> <expr>  
and <op1> <expr> <expr>  
and not <expr> <expr>  
and not <var> <expr>  
and not x <expr>  
and not x <var>  
and not x y



# **Recall: Ambiguity in Formal Grammar**

# Recall: Ambiguity in Formal Grammar

**Definition.** A BNF grammar is **ambiguous** if there is a sentence with multiple parse trees/leftmost derivations.

# Recall: Ambiguity in Formal Grammar

**Definition.** A BNF grammar is **ambiguous** if there is a sentence with multiple parse trees/  
leftmost derivations.

```
<expr> ::= <expr> <op> <expr>
          | <var>
<op>    ::= +
<var>   ::= x | y | z
```

# Recall: Ambiguity in Formal Grammar

**Definition.** A BNF grammar is **ambiguous** if there is a sentence with multiple parse trees/  
leftmost derivations.

```
<expr> ::= <expr> <op> <expr>
          | <var>
<op>    ::= +
<var>   ::= x | y | z
```


**x + y + z** can be derived as

# Recall: Ambiguity in Formal Grammar

**Definition.** A BNF grammar is **ambiguous** if there is a sentence with multiple parse trees/leftmost derivations.

```
<expr> ::= <expr> <op> <expr>
          | <var>
<op>    ::= +
<var>   ::= x | y | z
```

**x + y + z** can be derived as





# Recall: Ambiguity in Formal Grammar

**Definition.** A BNF grammar is **ambiguous** if there is a sentence with multiple parse trees/leftmost derivations.

```
<expr> ::= <expr> <op> <expr>
          | <var>
<op>    ::= +
<var>   ::= x | y | z
```

**x + y + z** can be derived as





# Practice Problem


```
<expr> ::= fun <var> -> <expr>
          | <expr> <expr>
          | <var>
<var>    ::= x
```

*Demonstrate that the above grammar is ambiguous*


# Solution

*fun x → x; x*

*fun x → (x x)*



$\langle \text{expr} \rangle$	$::=$	<b>fun</b>	$\langle \text{var} \rangle$	$\rightarrow$	$\langle \text{expr} \rangle$
					$\langle \text{expr} \rangle \langle \text{expr} \rangle$
					$\langle \text{var} \rangle$
$\langle \text{var} \rangle$	$::=$	<b>x</b>			



*(x x) x*


# Motivation

# A Note on "History"

Lexical analysis and parsing are typically associated with *compiler design*


Compiler design was once a fundamental requirement in CS programs. *This is not really the case anymore*

Also, we have *parser generators*





# Parser Generators



***Parser generators*** are programs which, given a representation of a language (e.g., as an ***EBNF grammar***), build a parser for you


(So there was a point to learning (E)BNF for the "real-world")

# Aside: Domain-Specific Languages

*Domain-specific languages* (DSLs) are simple programming languages for domain-specific tasks, e.g.

- » Emacs Lisp
- » SQL

*We need **parsers** for these languages if we want to use them...*



# Extended BNF

# Extended BNF

```
<expr> ::= <only-mul-div> { (+ | -) <only-mul-div> }  
<only-mul-div> ::= <var-or-parens> { (* | /) <var-or-parens> }  
<var-or-parens> ::= x | ( <expr> )
```



# Extended BNF

```
<expr> ::= <only-mul-div> { (+ | -) <only-mul-div> }  
<only-mul-div> ::= <var-or-parens> { (* | /) <var-or-parens> }  
<var-or-parens> ::= x | ( <expr> )
```

Extended BNF is essentially syntactic sugar. It let's us express BNF grammars in more compact way

# Extended BNF

<code>&lt;expr&gt;</code>	<code>::=</code>	<code>&lt;only-mul-div&gt;</code>	<code>{</code>	<code>(+   -)</code>	<code>&lt;only-mul-div&gt;</code>	<code>}</code>
<code>&lt;only-mul-div&gt;</code>	<code>::=</code>	<code>&lt;var-or-parens&gt;</code>	<code>{</code>	<code>(*   /)</code>	<code>&lt;var-or-parens&gt;</code>	<code>}</code>
<code>&lt;var-or-parens&gt;</code>	<code>::=</code>	<code>x   ( &lt;expr&gt; )</code>				

Extended BNF is essentially syntactic sugar. It let's us express BNF grammars in more compact way

**EBNF is not more expressive than BNF**

# Extended BNF

```
<expr> ::= <only-mul-div> { (+ | -) <only-mul-div> }  
<only-mul-div> ::= <var-or-parens> { (* | /) <var-or-parens> }  
<var-or-parens> ::= x | ( <expr> )
```

Extended BNF is essentially syntactic sugar. It let's us express BNF grammars in more compact way

**EBNF is not more expressive than BNF**

But it allows us to specify:

# Extended BNF

```
<expr> ::= <only-mul-div> { (+ | -) <only-mul-div> }  
<only-mul-div> ::= <var-or-parens> { (* | /) <var-or-parens> }  
<var-or-parens> ::= x | ( <expr> )
```

Extended BNF is essentially syntactic sugar. It let's us express BNF grammars in more compact way

**EBNF is not more expressive than BNF**

But it allows us to specify:

» Optional parts of production rule

# Extended BNF

<code>&lt;expr&gt;</code>	<code>::=</code>	<code>&lt;only-mul-div&gt;</code>	<code>{</code>	<code>(+   -)</code>	<code>&lt;only-mul-div&gt;</code>	<code>}</code>
<code>&lt;only-mul-div&gt;</code>	<code>::=</code>	<code>&lt;var-or-parens&gt;</code>	<code>{</code>	<code>(*   /)</code>	<code>&lt;var-or-parens&gt;</code>	<code>}</code>
<code>&lt;var-or-parens&gt;</code>	<code>::=</code>	<code>x   ( &lt;expr&gt; )</code>				

Extended BNF is essentially syntactic sugar. It let's us express BNF grammars in more compact way

**EBNF is not more expressive than BNF**

But it allows us to specify:

- » Optional parts of production rule
- » Repeated parts of a production rule

# Extended BNF

<code>&lt;expr&gt;</code>	<code>::=</code>	<code>&lt;only-mul-div&gt;</code>	<code>{</code>	<code>(+   -)</code>	<code>&lt;only-mul-div&gt;</code>	<code>}</code>
<code>&lt;only-mul-div&gt;</code>	<code>::=</code>	<code>&lt;var-or-parens&gt;</code>	<code>{</code>	<code>(*   /)</code>	<code>&lt;var-or-parens&gt;</code>	<code>}</code>
<code>&lt;var-or-parens&gt;</code>	<code>::=</code>	<code>x   ( &lt;expr&gt; )</code>				

Extended BNF is essentially syntactic sugar. It let's us express BNF grammars in more compact way

**EBNF is not more expressive than BNF**

But it allows us to specify:

- » Optional parts of production rule
- » Repeated parts of a production rule

**Note: EBNF means different things to different people**

# Optional Syntax

**BNF:**

```
<expr> ::= if <expr> then <expr>
          | if <expr> then <expr> <else>
<else> ::= else <expr>
```

**EBNF:** `<expr> ::= if <expr> then <expr> [ else <expr> ]`

**Menhir:**

```
expr =
  | IF; e1 = expr; THEN; e2 = expr; e3_opt = else?
    { match e3_opt with
      | None -> It (e1, e2)
      | Some e3 -> Ite (e1, e2, e3)
    }
else =
  | ELSE; e = expr { e }
```

# Repetition Syntax

**BNF:** `<word> ::= <letter> | <letter> <word>`

**EBNF:** `<word> ::= <letter> { <letter> }`

**Menhir:**

```
word =  
  | l = letter; ls = letter*  
  { String.of_list (l :: ls) }
```



# **Interlude: Regular Expressions**

# Regular Grammars

`<nonterminal> ::= terminal`

`<nonterminal> ::= terminal <nonterminal>`

`<nonterminal> ::=  $\epsilon$  (the empty string)`

A **regular grammar** is a BNF grammar with the above kinds of rules

*Regular grammars are easier to parse*

# Example

$\langle s \rangle$	$::=$	$a$	$\langle s \rangle$
$\langle s \rangle$	$::=$	$b$	$\langle a \rangle$
$\langle a \rangle$	$::=$	$\epsilon$	
$\langle a \rangle$	$::=$	$c$	$\langle a \rangle$

$a^n b c^m$

$\langle s \rangle$

$a \langle s \rangle$

$a a \langle s \rangle$

$a a a \langle s \rangle$

$a a a a \langle s \rangle$

$a a a a b \langle a \rangle$

$a a a a b c \langle a \rangle$

$a a a a b c c \langle a \rangle$

$a a a a b c c$

# Regular Expressions (Formally)

# Regular Expressions (Formally)

**Regular expressions (Regex)** provide a compact way of describing regular grammars:

# Regular Expressions (Formally)

**Regular expressions (Regex)** provide a compact way of describing regular grammars:

» A **terminal symbols** is a regex

# Regular Expressions (Formally)

**Regular expressions (Regex)** provide a compact way of describing regular grammars:

» A **terminal symbols** is a regex

» **[ t1 ... tk ]** is a regex describing an **any one of** the symbols **t1, t2, ..., tk**

# Regular Expressions (Formally)

**Regular expressions (Regex)** provide a compact way of describing regular grammars:

- » A **terminal symbols** is a regex
- » **[ t1 ... tk ]** is a regex describing an **any one of** the symbols **t1, t2, ..., tk**
- » **( e1 | ... | ek )** is a regex describing any one of the expressions **e1, e2, ..., ek**



# Regular Expressions (Formally)

**Regular expressions (Regex)** provide a compact way of describing regular grammars:

- » A **terminal symbols** is a regex
- » **[ t1 ... tk ]** is a regex describing an **any one of** the symbols **t1, t2, ..., tk**
- » **( e1 | ... | ek )** is a regex describing any one of the expressions **e1, e2, ..., ek**
- » **exp\*** is a regex describing **zero or more occurrences** of **exp**

# Regular Expressions (Formally)

**Regular expressions (Regex)** provide a compact way of describing regular grammars:

- » A **terminal symbols** is a regex
- » **[ t1 ... tk ]** is a regex describing an **any one of** the symbols **t1, t2, ..., tk**
- » **( e1 | ... | ek )** is a regex describing any one of the expressions **e1, e2, ..., ek**
- » **exp\*** is a regex describing **zero or more occurrences** of **exp**
- » **exp+** is a regex describing **one or more occurrences** of **exp**

# Regular Expressions (Formally)

$0^* 1^*$

**Regular expressions (Regex)** provide a compact way of describing regular grammars:

✓

» A **terminal symbols** is a regex

»  $[ t_1 \dots t_k ]$  is a regex describing an **any one of** the symbols  $t_1, t_2, \dots, t_k$

»  $( e_1 \mid \dots \mid e_k )$  is a regex describing any one of the expressions  $e_1, e_2, \dots, e_k$

✓

»  $\text{exp}^*$  is a regex describing **zero or more occurrences** of  $\text{exp}$

»  $\text{exp}^+$  is a regex describing **one or more occurrences** of  $\text{exp}$

»  $\text{exp}^?$  is a regex describing **zero or one occurrences** of  $\text{exp}$

$e_1, \dots, e_k$  is a regex

# Example

$\langle s \rangle ::= a \langle s \rangle$

$\langle s \rangle ::= b \langle a \rangle$

$\langle a \rangle ::= \epsilon$

$\langle a \rangle ::= c \langle a \rangle$

*is equivalent to*

*0 or more*  
 $a^* b c^*$   
*0 or more*  
*or*

$'a' * 'b' 'c' *$

*in ocamllex syntax*

# Example: Numbers and Variables

*optional*  
 $-?[0-9]^+$   
*numbers*  
*digits*

-13

144

99

-000

*lower case*

$[a-z][a-zA-Z0-9_']^*$   
*variables*

x

x4z

x\_x\_z

a\_ \_ \_

We'll leave it there, take CS332  
if you want more, or read the  
Wikipedia page...

# Lexical Analysis

# The "Lexing" Problem

"let"  $\approx$  ['l', 'e', 't']  $\mapsto$  *LET*

"fun"  $\approx$  ['f', 'u', 'n']  $\mapsto$  *FUN*



# The "Lexing" Problem

"let"  $\approx$  ['l', 'e', 't']  $\mapsto$  *LET*

"fun"  $\approx$  ['f', 'u', 'n']  $\mapsto$  *FUN*

*The Goal. Convert a stream of characters into a stream of tokens*

# The "Lexing" Problem

"let"  $\approx$  ['l', 'e', 't']  $\mapsto$  *LET*

"fun"  $\approx$  ['f', 'u', 'n']  $\mapsto$  *FUN*

***The Goal.** Convert a stream of characters into a stream of tokens*

» Characters are **grouped** so together so they correspond to the *smallest units* at the level of the language

# The "Lexing" Problem

"let"  $\approx$  ['l', 'e', 't']  $\mapsto$  *LET*

"fun"  $\approx$  ['f', 'u', 'n']  $\mapsto$  *FUN*

**The Goal.** *Convert a stream of characters into a stream of tokens*

- » Characters are **grouped** so together so they correspond to the *smallest units* at the level of the language
- » Whitespace and comments are *ignored*

# The "Lexing" Problem

"let"  $\approx$  ['l', 'e', 't']  $\mapsto$  *LET*

"fun"  $\approx$  ['f', 'u', 'n']  $\mapsto$  *FUN*

**The Goal.** *Convert a stream of characters into a stream of tokens*

- » Characters are **grouped** so together so they correspond to the *smallest units* at the level of the language
- » Whitespace and comments are *ignored*
- » **Syntax errors** are caught, when possible

# Lexing vs. Parsing

# Lexing vs. Parsing

**Lexical Analysis** is about *small-scale* language constructs

# Lexing vs. Parsing

**Lexical Analysis** is about *small-scale* language constructs

» keywords, names, literals

# Lexing vs. Parsing

**Lexical Analysis** is about *small-scale* language constructs

» keywords, names, literals

**Syntactic Analysis (Parsing)** is about *large-scale* language constructs



# Lexing vs. Parsing

**Lexical Analysis** is about *small-scale* language constructs

- » keywords, names, literals

**Syntactic Analysis (Parsing)** is about *large-scale* language constructs

- » expressions, statements, modules

# **Why separate them?**

# Why separate them?

*Good question...*for simple implementations, we don't

But there are benefits for larger projects:

# Why separate them?

*Good question...* for simple implementations, we don't

But there are benefits for larger projects:

» **Simplicity.** It's *easier to think about* parsing if we don't need to worry about whitespace, characters, etc.

# Why separate them?

*Good question...* for simple implementations, we don't

But there are benefits for larger projects:

» **Simplicity.** It's *easier to think about* parsing if we don't need to worry about whitespace, characters, etc.

» **Portability.** Files are finicky things, handled differently across different operating systems.

*Abstracting this away* for parsing is just good software engineering

# Lexemes and Tokens

<u>input program:</u>	fun	⌊	->	⌊	++	[	100	]
<u>lexemes:</u>	"fun"	"⌊"	"->"	"⌊"	"++"	"["	"100"	"]"
<u>tokens:</u>	FUN	(ID "⌊")	ARR	(ID "⌊")	(OP "++")	LBRAK	(INT 100)	RBRAK

# Lexemes and Tokens

<u>input program:</u>	fun	⌊	->	⌊	++	[	100	]
<u>lexemes:</u>	"fun"	"⌊"	"->"	"⌊"	"++"	"["	"100"	"]"
<u>tokens:</u>	FUN	(ID "⌊")	ARR	(ID "⌊")	(OP "++")	LBRAK	(INT 100)	RBRAK

A **lexeme** is a **sequence of characters** associated a syntactic unit in a language

# Lexemes and Tokens

<u>input program:</u>	fun	l	->	l	++	[	100	]
<u>lexemes:</u>	"fun"	"l"	"->"	"l"	"++"	"["	"100"	"]"
<u>tokens:</u>	FUN	(ID "l")	ARR	(ID "l")	(OP "++")	LBRAK	(INT 100)	RBRAK

A **lexeme** is a **sequence of characters** associated a syntactic unit in a language

A **token** is a lexeme together with information about **what kind of unit it is**



# Lexemes and Tokens

<u>input program:</u>	fun	␣	->	␣	++	[	100	]
<u>lexemes:</u>	"fun"	"␣"	"->"	"␣"	"++"	"["	"100"	"]"
<u>tokens:</u>	FUN	(ID "␣")	ARR	(ID "␣")	(OP "++")	LBRAK	(INT 100)	RBRAK

A **lexeme** is a **sequence of characters** associated a syntactic unit in a language

A **token** is a lexeme together with information about **what kind of unit it is**

» "12" and "234" are both INT\_LITS, whereas "let" is a KEYWORD.

# Lexemes and Tokens

<u>input program:</u>	fun	l	->	l	++	[	100	]
<u>lexemes:</u>	"fun"	"l"	"->"	"l"	"++"	"["	"100"	"]"
<u>tokens:</u>	FUN	(ID "l")	ARR	(ID "l")	(OP "++")	LBRAK	(INT 100)	RBRAK

A **lexeme** is a **sequence of characters** associated a syntactic unit in a language

A **token** is a lexeme together with information about **what kind of unit it is**

» "12" and "234" are both INT\_LITS, whereas "let" is a KEYWORD.

*We typically represent tokens as an ADT*

# Aside: One Token at a time

" **let**@#\_)( \$#@\_J\_@0#GKJ" <sup>next\_token</sup> → (LET, "@#\_)( \$#@\_J\_@0#GKJ")

"le x = 2" <sup>next\_token</sup> → **FAILURE**

# Aside: One Token at a time

" **let**@#\_)( \$#@\_J\_@0#GKJ" <sup>next\_token</sup> → (LET, "@#\_)( \$#@\_J\_@0#GKJ")

"le x = 2" <sup>next\_token</sup> → **FAILURE**

The approach:

# Aside: One Token at a time

" **let**@#\_)( \$#@\_J\_@0#GKJ" <sup>next\_token</sup>  (LET, "@#\_)( \$#@\_J\_@0#GKJ")

"le x = 2" <sup>next\_token</sup>  **FAILURE**

## The approach:

» Given a stream of characters, determine if there is a valid lexeme at the *beginning*

# Aside: One Token at a time

" **let**@#\_)( \$#@\_J\_@0#GKJ" <sup>next\_token</sup> → (LET, "@#\_)( \$#@\_J\_@0#GKJ")

"le x = 2" <sup>next\_token</sup> → **FAILURE**

## The approach:

- » Given a stream of characters, determine if there is a valid lexeme at the *beginning*
- » If there is, return its corresponding token and the *remainder of the stream*

# Parsing with Menhir

# General Parsing



# General Parsing

***In Theory.** Determine if a given sentence is recognized by a given grammar*

# General Parsing

***In Theory.*** Determine if a given sentence is recognized by a given grammar

***In Practice.*** Given a grammar, write a program which converts a string recognized by that grammar into an ADT

# Today

```
<prog> ::= <expr>

<expr> ::= let <var> = <expr> in <expr>
        | <expr1>

<bop>   ::= + | - | * | /

<expr1> ::= <expr1> <bop> <expr1>
        | <num>
        | <var>
        | ( <expr> )

<num>   ::= 0 ; DUMMY VALUE
<var>   ::= x ; DUMMY VALUE

; In lex.mll:
;
; let num = '-'? ['0'-'9']+
; let var = ['a'-'z' '_' ] ['a'-'z' 'A'-'Z' '0'-'9' '_' '\''']*
```

Operators in order of increasing precedence:

Operator	Associativity
+, -	left
*, /	left

We'll be building a parser for the this grammar

# A Rough Sketch

1. Specify the tokens (i.e., terminal symbols) of the grammar
2. Specify the rules of the grammar (using a BNF-like syntax)
3. Specify the rules of the lexer (i.e., which strings go to which tokens)