



Session 1.2 - Linux environment review

Sarai Varona

BU-ISCIII

Unidades Comunes Científico Técnicas - SGSAFI-ISCIII

28-02 Junio-Julio 2021, 3ª Edición Programa Formación Continua, ISCIII





Index

<u>Linux environment review:</u>

- Linux OS
- Linux file system
- Linux users and privileges
- Basic commands
- Command line syntax





Index

<u>Linux environment review:</u>

- Linux OS
- Linux file system
- Linux users and privileges
- Basic commands
- Command line syntax






Linux OS - Introduction

Linux is:

- Operative system
- Open source
- Multi-task
- Multi-user








Linux OS - Introduction

Linux is:

- Operative system
- Open source
- Multi-task
- Multi-user








Operative System (OS):












Operative System (OS):



Windows










Operative System (OS):

 Software that manages computer hardware and software resources and provides common services for computer programs








Operative System (OS):

 Software that manages computer hardware and software resources and provides common services for computer programs


Functions:

- Program execution control and oversee
- Administrate peripherals
- User and permission management
- Error and security management













Shell

Program that provides the traditional, text-only user interface.





Shell

Program that provides the traditional, text-only user interface.

Command line

Graphical user interface







Shell

Program that provides the traditional, text-only user interface.

File system

It controls how data is stored, manipulated and retrieved.





Shell

Program that provides the traditional, text-only user interface.

File system

It controls how data is stored, manipulated and retrieved.

Kernel

It is the foundational layer of an operating system (OS).

It functions at a basic level, communicating with

hardware and managing resources.






Linux OS - Introduction

Linux is:

- Operative system
- Open source
- Multi-task
- Multi-user







Linux OS - Open source I

The distribution terms of open-source software must comply with the following criteria:

- Free Redistribution
- Source Code
- Derived Works
- Integrity of the Author's Source Code
- No Discrimination Against Persons or Groups
- No Discrimination Against Fields of Endeavour
- Distribution of license
- License Must Not Be Specific to a Product
- License Must not Restrict Other Software
- License Must Be Technology-Neutral





Linux OS - Open source II

Linux Distributions

- A distro is a Linux kernel based operating system made from a software collection and sometimes a package management system.
- There are distros for a wide variety of platforms.
- A typical Linux distro comprises a Linux kernel, GNU tools and libraries, additional software, documentation, a window system, a window manager, and a desktop environment.
- Most of the included software is free and open-source software made available both as compiled binaries and in source code form, allowing modifications to the original software. Usually, Linux distributions optionally include some proprietary software that may not be available in source code form, such as binary blobs required for some device drivers.





Linux OS - Open source II

Linux Distributions







Linux OS - Open source II

Linux Distributions





Ubuntu 20.04 LTS






Linux OS - Introduction

Linux is:

- Operative system
- Open source
- Multi-task
- Multi-user








Linux OS - Multi-task

A multi-task operative systems allows a user to perform more than one computer task (such as the operation of an application program) at a time.

The operating system is able to keep track of where you are in these tasks and go from one to the other without losing information.








Linux OS - Introduction

Linux is:

- Operative system
- Open source
- Multi-task
- Multi-user







Linux OS - Multi-user I

- Multi-user software is software that allows access by multiple users of a computer.
- An example is a Unix server where multiple remote users have access (such as via a serial port or Secure Shell) to the Unix shell prompt at the same time.








Linux OS - Multi-user II

Virtualisation:

the act of creating a virtual (rather than actual) version of something, including virtual computer hardware platforms, storage devices, and computer network resources.



Traditional Architecture



Virtual Architecture






Index

<u>Linux environment review:</u>

- Linux OS
- Linux file system
- Linux users and privileges
- Basic commands
- Command line syntax












Linux File System - Key Features

- Everything is a File
- Specifying Paths
- Case-Sensitive
- File Extensions and Hidden Files
- Permissions
- Root directory (/)






Linux File System - Structure







Linux File System - Structure








Linux File System - Comparison

- Everything "hangs" from root
- Files are classified by type / role instead of unit location
- Files locations in disks are invisible for users








- PATH:
 - Absolute path:
 - Location of a file or directory from the root directory (/).
 - Static.
 - Ej: /home/alumno1/dir1/book.txt
 - Relative path:
 - Path related to the present working directory (pwd).
 - Variable
 - Actual pwd = "."
 - Parent directory = ".."
 - Ej:
 - from /home: alumno1/dir1/book.txt or
 ./alumno1/dir1/book.txt
 - from /home/alumno1: dir1/book.txt or dir1/book.txt
 - from /home/alumno1/dir1: book.txt ./book.txt






- Example
 - ../../ To go home from Dir1 or Dir2
 - ../../alumno2 To go alumno2 from Dir1 o Dir2.
 - ../Dir2 To go from Dir1 to Dir2.




























No matter were we are

Absolute path /home/alumno1/Dir1/Libro.txt








Linux File System - Paths

Important pwd or "."

Relative path ./Dir1/Libro.txt







Index

<u>Linux environment review:</u>

- Linux OS
- Linux file system
- Linux users and privileges
- Basic commands
- Command line syntax





Linux Users and Privileges - Users

- Users can be linked to a person or computer process
- Every user may belong to one ore more groups
- Every user may has a home folder inside /home
- Users own the files they create, directly or indirectly
- Users can change permissions on files they own
- Users also own processes they execute
- Root rules over them all
- Root home folder is in /root






Permissions are the "rights" to act on a file or directory. The are only 3 basic permissions:

- Read (r) allows the contents of the file to be viewed.
 A read permission on a directory allows you to list the contents of a directory.
- Write (w) allows you to modify the contents of that file. For a directory, the write permission allows you to edit the contents of a directory.
- Execute (x) for a file, the executable permission allows you to run the file and execute a program or script. For a directory, the execute permission allows you to change to a different directory and make it your current working directory (pwd or ".").





- A file's rights can only be modified by the owner of the file, the group owning the file and the root
- The system stores this right information in a 9 bits sequence.
- This sequence has a sequence of 3 elements for each 3 groups:








- Examples:
 - Example 1: /opt directory





Linux File System - Structure







- Examples:
 - Example 1: /opt directory
 - drwxr-xr-x root root opt
 - Owner (root) can read, write and execute
 - Group (root) and rest can only read and execute





- Examples:
 - Example 1: /opt directory
 - drwxr-xr-x root root opt
 - Owner (root) can read, write and execute
 - Group (root) and rest can only read and execute
 - Example 2: personal directory
 - drwx----- alumno clase alumno
 - Owner can read, modify and access the directory
 - Group and others can't do anything





- Examples:
 - Example 1: /opt directory
 - drwxr-xr-x root root opt
 - Owner (root) can read, write and execute
 - Group (root) and rest can only read and execute
 - Example 2: personal directory
 - drwx----- alumno clase alumno
 - Owner can read, modify and access the directory
 - Group and others can't do anything
 - Example 3: tmp
 - drwxrwxrwx root root tmp
 - Everybody has permissions for everything





To view file permissions and ownership on files and directories, use the **ls -al** command. For example:

drwxr-xr-x 2 user user 4096 Jan 9 10:11 documents

- `drwxr-xr-x` are the permissions
- `2` is the number of files or directories
- `user` is the owner
- `user` is the group
- `4096` is the size
- `Jan 9 10:11` is the date/time of last access
- `documents` is the directory





Following previous example:

drwxrw-r-- 2 user user 4096 Jan 9 10:11 documents

Permissions are listed in the first 10 characters-dash section.

5555





Following previous example:

drwxrw-r-- 2 user user 4096 Jan 9 10:11 documents

Permissions are listed in the first 10 characters-dash section. The section can be read as follows:

- `d` is a directory (`-` for files)
- `rwx` the user has read, write, and execute permissions
- `rw-` the group has read and write permissions
- `r--` all others have read only permissions





Index

Linux environment review:

- Linux OS
- Linux file system
- Linux users and privileges
- Basic commands
- Command line syntax





Linux OS - Operating System III

Shell

Program that provides the traditional, text-only user interface.

Command line

```
Various Common Unit Interface

1 on the Common Unit Interface

2 on the Common Unit Interface

3 on the Common Unit Interface

4 on the Common Unit Interface
```

Graphical user interface








Basic Commands - Shell's prompt

- Shell waits for the user to write commands in a line called prompt.
- Prompt line gives some important information that can be easily understood:



 This example prompt gives the information that the user is profesor, which has no admin privileges, which is connected to VM-NGS01 machine, and whose directory where the user is located is the folder Documentos.






- `pwd` display your present working directory
- `ls` list contents
- `cd` change directory
- `mkdir` make directory
- `rm` remove file
- `rmdir` remove directory
- `less` display contents of file
- `nano` text editor on the terminal
- `man` displays the manual of a command







































REMEMBER:

TAB is your friend!

Hit it to autocomplete a command, file, path or get suggestion to do it





Index

Linux environment review:

- Linux OS
- Linux file system
- Linux users and privileges
- Basic commands
- Command line syntax





Command Line Syntax

Linux command line follows a simple syntax common to every command and program you can execute on it:

Command [option(s)] [parameter(s)]

- Options or flags are characters or words preceded by a dash (`ls -la`). They change the way a program works by default.
- Parameters are other attributes that the program may need to run. The most common ones usually are the input files.
- REMEMBER: most programs have a -h or --help option which displays a short description and usage guide.





Thanks for your attention!

