

Research: Previous Team's Model

Jeremy Bui (Spring 2025)

Models Used

1. all-MiniLM-L6-v2 Embedding Model

- Strengths:
 - Efficient, small, and optimized for fast semantic search.
 - 384-dimensional vector space keeps embeddings lightweight.
 - Good performance for metadata-based retrieval.
- Trade-offs:
 - Slightly lower embedding quality than larger models (e.g., all-MiniLM-L12-v2).
 - May struggle with more complex semantic relationships.
 - Works best in high-speed and resource-limited environments, but sacrifices some accuracy.

2. Pinecone Vector Store

- Strengths:
 - Managed service, removes infrastructure concerns.
 - Handles large-scale vector searches efficiently.
 - Works well with real-time query retrieval.
- Trade-offs:
 - High costs at scale (limited free tier, expensive for large datasets).

3. GPT-4o-mini for Response Generation

- Strengths:
 - Produces coherent, natural responses based on retrieved documents.
 - Cheaper than full GPT-4o while maintaining strong performance.
- Trade-offs:
 - Still expensive for heavy usage compared to open-source LLMs.
 - Does not fine-tune on BPL-specific data, relying on retrieval quality.

Challenges with the Current Model?

- Speed:
 - Query response times range from 25-70s, largely due to retrieval and reranking overhead.
 - Fetching full metadata from the Digital Commonwealth API slows down response time.
 - Pinecone indexing is fast, but metadata fetch adds extra latency.
- Cost Concerns:

- Pinecone & OpenAI API costs scale up quickly, especially with frequent queries.
 - Reducing dataset size helped lower expenses but limited search scope.
- Query Alignment Issues:
 - No automatic query segmentation to prioritize title vs. date vs. abstract.

Potential Next Steps?

1. Embedding Optimization
 - Consider a larger model (e.g., all-MiniLM-L12-v2) for better semantic understanding.
 - Experiment with re-ranking before embedding to reduce unnecessary vector searches.
2. Vector Store Adjustments
 - Move from Pinecone to FAISS (self-hosted) to reduce costs.
 - Use hybrid retrieval (BM25 + vector search) instead of relying purely on embeddings.
3. Query Segmentation & Weighting
 - Preprocess queries to identify titles, dates, and abstract content separately.
 - Apply weighted BM25 ranking before passing to the vector store.
4. Alternative LLMs for Cost Reduction
 - Experiment with LLama 2 for price difference (maybe)?

Resources

- [Alternatives to Pinecone? \(Vector databases\) \[D\] : r/MachineLearning](#)
- [Pricing | Pinecone](#)
- [sentence-transformers/all-MiniLM-L6-v2 · Hugging Face](#)