



CSE 215: Database

Department of CSE
Bangladesh University of Engineering & Technology

Relational Model

Instructor Relation



<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>	attributes (or columns)
10101	Srinivasan	Comp. Sci.	65000	tuples (or rows)
12121	Wu	Finance	90000	
15151	Mozart	Music	40000	
22222	Einstein	Physics	95000	
32343	El Said	History	60000	
33456	Gold	Physics	87000	
45565	Katz	Comp. Sci.	75000	
58583	Califieri	History	62000	
76543	Singh	Finance	80000	
76766	Crick	Biology	72000	
83821	Brandt	Comp. Sci.	92000	
98345	Kim	Elec. Eng.	80000	

Relation Schema and Instance



- A_1, A_2, \dots, A_n are *attributes*
- $R = (A_1, A_2, \dots, A_n)$ is a *relation schema*

Example:

instructor = (*ID*, *name*, *dept_name*, *salary*)

- A relation instance r defined over schema R is denoted by $r(R)$
- The current values a relation are specified by a table
- An element t of relation r is called a *tuple* and is represented by a *row* in a table



Attributes

- The set of allowed values for each attribute is called the domain of the attribute
- Attribute values are (normally) required to be atomic; that is, indivisible
- The special value null is a member of every domain. Indicated that the value is “unknown”
- The null value causes complications in the definition of many operations

Relations are Unordered



- Order of tuples is irrelevant (tuples may be stored in an arbitrary order)
- Example: instructor relation with unordered tuples

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
22222	Einstein	Physics	95000
12121	Wu	Finance	90000
32343	El Said	History	60000
45565	Katz	Comp. Sci.	75000
98345	Kim	Elec. Eng.	80000
76766	Crick	Biology	72000
10101	Srinivasan	Comp. Sci.	65000
58583	Califieri	History	62000
83821	Brandt	Comp. Sci.	92000
15151	Mozart	Music	40000
33456	Gold	Physics	87000
76543	Singh	Finance	80000

Relational Model

Database Schema



- Database schema -- is the logical structure of the database.
- Database instance -- is a snapshot of the data in the database at a given instant in time.
- schema: instructor (ID, name, dept_name, salary)

- Instance:

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
22222	Einstein	Physics	95000
12121	Wu	Finance	90000
32343	El Said	History	60000
45565	Katz	Comp. Sci.	75000
98345	Kim	Elec. Eng.	80000
76766	Crick	Biology	72000
10101	Srinivasan	Comp. Sci.	65000
58583	Califieri	History	62000
83821	Brandt	Comp. Sci.	92000
15151	Mozart	Music	40000
33456	Gold	Physics	87000
76543	Singh	Finance	80000




Keys

- Let $K \subseteq R$
- K is a **superkey** of R if values for K are sufficient to identify a unique tuple of each possible relation $r(R)$
 - Example: $\{ID\}$ and $\{ID, name\}$ are both superkeys of *instructor*
- Superkey K is a **candidate key** if K is minimal
Example: $\{ID\}$ is a candidate key for *Instructor*
- One of the candidate keys is selected to be the **primary key**
- **Foreign key** constraint: Value in one relation must appear in another
 - **Referencing** relation, **Referenced** relation
 - Example: *dept_name* in *instructor* is a foreign key from *instructor* referencing *department*

Relational Model

Schema Diagram



Relational Algebra



- A procedural language consisting of a set of operations that take one or two relations as input and produce a new relation as their result
- Six basic operators
 - select: σ
 - project: Π
 - union: \cup
 - set difference: $-$
 - Cartesian product: \times
 - rename: ρ



Select Operation

- The **select** operation selects tuples that satisfy a given predicate
- Notation: $\sigma_p(r)$
- p is called the **selection predicate**
- Example: select those tuples of the *instructor* relation where the instructor is in the “Physics” department

– Query

$\sigma_{dept_name = \text{“Physics”}}(instructor)$

– Result

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
22222	Einstein	Physics	95000
33456	Gold	Physics	87000



Select Operation

- We allow comparisons using $=$, \neq , $>$, \geq , $<$, \leq in the selection predicate
- We can combine several predicates into a larger predicate by using the connectives:

\wedge (**and**), \vee (**or**), \neg (**not**)

- Example: Find the instructors in Physics with a salary greater \$90,000, we write:

$\sigma_{dept_name = \text{"Physics"} \wedge salary > 90,000} (instructor)$

- The select predicate may include comparisons between two attributes.
 - Example, find all departments whose name is the same as their building name:

– $\sigma_{dept_name = building} (department)$



Project Operation

- A unary operation that returns its argument relation, with certain attributes left out
- Notation:

$$\Pi_{A_1, A_2, A_3 \dots A_k} (r)$$

where A_1, A_2, \dots, A_k are attribute names and r is a relation name

- The result is defined as the relation of k columns obtained by erasing the columns that are not listed
- Duplicate rows removed from result, since relations are sets



Project Operation

- Example: eliminate the *dept_name* attribute of *instructor*
- Query:

$\Pi_{ID, name, salary}(instructor)$

- Result:

<i>ID</i>	<i>name</i>	<i>salary</i>
10101	Srinivasan	65000
12121	Wu	90000
15151	Mozart	40000
22222	Einstein	95000
32343	El Said	60000
33456	Gold	87000
45565	Katz	75000
58583	Califieri	62000
76543	Singh	80000
76766	Crick	72000
83821	Brandt	92000
98345	Kim	80000

Composition of Relational Operations

- The result of a relational-algebra operation is relation and therefore of relational-algebra operations can be composed together into a **relational-algebra expression**
- Consider the query -- Find the names of all instructors in the Physics department

$$\Pi_{name}(\sigma_{dept_name = "Physics"}(instructor))$$

- Instead of giving the name of a relation as the argument of the projection operation, we give an expression that evaluates to a relation

Cartesian-Product Operation



- The Cartesian-product operation (denoted by \times) allows us to combine information from any two relations
- Example: the Cartesian product of the relations *instructor* and *teaches* is written as:

instructor \times *teaches*

- We construct a tuple of the result out of each possible pair of tuples: one from the *instructor* relation and one from the *teaches* relation
- Since the instructor *ID* appears in both relations we distinguish between these attribute by attaching to the attribute the name of the relation from which the attribute originally came
 - *instructor.ID*
 - *teaches.ID*

Relational Algebra

The *instructor X teaches* table

<i>instructor.ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>	<i>teaches.ID</i>	<i>course_id</i>	<i>sec_id</i>	<i>semester</i>	<i>year</i>
10101	Srinivasan	Comp. Sci.	65000	10101	CS-101	1	Fall	2017
10101	Srinivasan	Comp. Sci.	65000	10101	CS-315	1	Spring	2018
10101	Srinivasan	Comp. Sci.	65000	10101	CS-347	1	Fall	2017
10101	Srinivasan	Comp. Sci.	65000	12121	FIN-201	1	Spring	2018
10101	Srinivasan	Comp. Sci.	65000	15151	MU-199	1	Spring	2018
10101	Srinivasan	Comp. Sci.	65000	22222	PHY-101	1	Fall	2017
...
...
12121	Wu	Finance	90000	10101	CS-101	1	Fall	2017
12121	Wu	Finance	90000	10101	CS-315	1	Spring	2018
12121	Wu	Finance	90000	10101	CS-347	1	Fall	2017
12121	Wu	Finance	90000	12121	FIN-201	1	Spring	2018
12121	Wu	Finance	90000	15151	MU-199	1	Spring	2018
12121	Wu	Finance	90000	22222	PHY-101	1	Fall	2017
...
...
15151	Mozart	Music	40000	10101	CS-101	1	Fall	2017
15151	Mozart	Music	40000	10101	CS-315	1	Spring	2018
15151	Mozart	Music	40000	10101	CS-347	1	Fall	2017
15151	Mozart	Music	40000	12121	FIN-201	1	Spring	2018
15151	Mozart	Music	40000	15151	MU-199	1	Spring	2018
15151	Mozart	Music	40000	22222	PHY-101	1	Fall	2017
...
...
22222	Einstein	Physics	95000	10101	CS-101	1	Fall	2017
22222	Einstein	Physics	95000	10101	CS-315	1	Spring	2018
22222	Einstein	Physics	95000	10101	CS-347	1	Fall	2017
22222	Einstein	Physics	95000	12121	FIN-201	1	Spring	2018
22222	Einstein	Physics	95000	15151	MU-199	1	Spring	2018
22222	Einstein	Physics	95000	22222	PHY-101	1	Fall	2017
...
...



Join Operation

- The Cartesian-Product

instructor X teaches

associates every tuple of *instructor* with every tuple of *teaches*

- Most of the resulting rows have information about instructors who did NOT teach a particular course

- To get only those tuples of “*instructor X teaches*” that pertain to instructors and the courses that they taught, we write:

$\sigma_{instructor.id = teaches.id} (instructor \times teaches)$

- The result of this expression, shown in the next slide

Relational Algebra

Join Operation



- The table corresponding to:

$$\sigma_{instructor.id = teaches.id}(instructor \times teaches)$$

<i>instructor.ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>	<i>teaches.ID</i>	<i>course_id</i>	<i>sec_id</i>	<i>semester</i>	<i>year</i>
10101	Srinivasan	Comp. Sci.	65000	10101	CS-101	1	Fall	2017
10101	Srinivasan	Comp. Sci.	65000	10101	CS-315	1	Spring	2018
10101	Srinivasan	Comp. Sci.	65000	10101	CS-347	1	Fall	2017
12121	Wu	Finance	90000	12121	FIN-201	1	Spring	2018
15151	Mozart	Music	40000	15151	MU-199	1	Spring	2018
22222	Einstein	Physics	95000	22222	PHY-101	1	Fall	2017
32343	El Said	History	60000	32343	HIS-351	1	Spring	2018
45565	Katz	Comp. Sci.	75000	45565	CS-101	1	Spring	2018
45565	Katz	Comp. Sci.	75000	45565	CS-319	1	Spring	2018
76766	Crick	Biology	72000	76766	BIO-101	1	Summer	2017
76766	Crick	Biology	72000	76766	BIO-301	1	Summer	2018
83821	Brandt	Comp. Sci.	92000	83821	CS-190	1	Spring	2017
83821	Brandt	Comp. Sci.	92000	83821	CS-190	2	Spring	2017
83821	Brandt	Comp. Sci.	92000	83821	CS-319	2	Spring	2018
98345	Kim	Elec. Eng.	80000	98345	EE-181	1	Spring	2017



Join Operation

- The **join** operation allows us to combine a select operation and a Cartesian-Product operation into a single operation
- Consider relations $r (R)$ and $s (S)$
- Let “theta” be a predicate on attributes in the schema R “union” S. The join operation $r \bowtie_{\theta} s$ is defined as follows:

$$r \bowtie_{\theta} s = \sigma_{\theta} (r \times s)$$

- Thus

$$\sigma_{instructor.id = teaches.id} (instructor \times teaches)$$

- Can equivalently be written as

$$instructor \bowtie_{Instructor.id = teaches.id} teaches.$$



Union Operation

- The union operation allows us to combine two relations
- Notation: $r \cup s$
- For $r \cup s$ to be valid:
 1. r, s must have the **same arity** (same number of attributes)
 2. The attribute domains must be **compatible** (example: 2nd column of r deals with the same type of values as does the 2nd column of s)
- Example: to find all courses taught in the Fall 2017 semester, or in the Spring 2018 semester, or in both

$$\Pi_{course_id} (\sigma_{semester="Fall" \wedge year=2017}(section)) \cup \Pi_{course_id} (\sigma_{semester="Spring" \wedge year=2018}(section))$$



Union Operation

- Result of:

$$\Pi_{course_id} (\sigma_{semester="Fall" \wedge year=2017} (section)) \cup \\ \Pi_{course_id} (\sigma_{semester="Spring" \wedge year=2018} (section))$$

<i>course_id</i>
CS-101
CS-315
CS-319
CS-347
FIN-201
HIS-351
MU-199
PHY-101

Set-Intersection Operation



- The set-intersection operation allows us to find tuples that are in both the input relations
- Notation: $r \cap s$
- Assume:
 - r, s have the *same arity*
 - attributes of r and s are compatible
- Example: Find the set of all courses taught in both the Fall 2017 and the Spring 2018 semesters

$$\Pi_{course_id} (\sigma_{semester="Fall" \wedge year=2017} (section)) \cap \Pi_{course_id} (\sigma_{semester="Spring" \wedge year=2018} (section))$$

<i>course_id</i>
CS-101



Set Difference Operation

- The set-difference operation allows us to find tuples that are in one relation but are not in another
- Notation $r - s$
- Set differences must be taken between **compatible** relations
 - r and s must have the **same** arity
 - attribute domains of r and s must be compatible
- Example: to find all courses taught in the Fall 2017 semester, but not in the Spring 2018 semester

$$\Pi_{course_id} (\sigma_{semester="Fall" \wedge year=2017}(section)) - \Pi_{course_id} (\sigma_{semester="Spring" \wedge year=2018}(section))$$

course_id
CS-347
PHY-101



The Assignment Operation

- It is convenient at times to write a relational-algebra expression by assigning parts of it to temporary relation variables
- The assignment operation is denoted by \leftarrow and works like assignment in a programming language
- Example: Find all instructor in the “Physics” and Music department

$Physics \leftarrow \sigma_{dept_name = \text{“Physics”}}(instructor)$

$Music \leftarrow \sigma_{dept_name = \text{“Music”}}(instructor)$

$Physics \cup Music$

- With the assignment operation, a query can be written as a sequential program consisting of a series of assignments followed by an expression whose value is displayed as the result of the query



The Rename Operation

- The results of relational-algebra expressions do not have a name that we can use to refer to them. The rename operator, ρ , is provided for that purpose
- The expression:

$$\rho_x(E)$$

returns the result of expression E under the name x

- Another form of the rename operation:

$$\rho_{x(A1,A2, \dots, An)}(E)$$



Equivalent Queries

- There is more than one way to write a query in relational algebra
- Example: Find information about courses taught by instructors in the Physics department with salary greater than 90,000
- Query 1

$$\sigma_{dept_name = \text{"Physics"} \wedge salary > 90,000} (instructor)$$

- Query 2

$$\sigma_{dept_name = \text{"Physics"}} (\sigma_{salary > 90,000} (instructor))$$

- The two queries are not identical; they are, however, equivalent -- they give the same result on any database



Equivalent Queries

- There is more than one way to write a query in relational algebra.
- Example: Find information about courses taught by instructors in the Physics department

- Query 1

$$\sigma_{dept_name = \text{"Physics"}}(instructor \bowtie_{instructor.ID = teaches.ID} teaches)$$

- Query 2

$$(\sigma_{dept_name = \text{"Physics"}}(instructor)) \bowtie_{instructor.ID = teaches.ID} teaches$$

- The two queries are not identical; they are, however, equivalent -- they give the same result on any database



Acknowledgement

- Some slides and figures are collected from
 - <https://www.db-book.com/>