



Scalable Compositional Static Taint Analysis for Industrial Microservices

Zexin Zhong, Jiangchao Liu, Diyu Wu, Peng Di, Yulei Sui and Alex X. Liu

In 44th International Conference on Software Engineering: Software Engineering in Practice (ICSE-SEIP'22)



Outline

- Background & Motivation
- Challenges
- Approach
- Evaluation



Background



Increasing Cost of Data Breach in Industry

Measured in US\$ millions



**Average total cost of a data breach
(IBM Security, 2021)**



Increasing Cost of Data Breach in Industry

Measured in US\$ millions




**Average total cost of a data breach
(IBM Security, 2021)**

- **10% Increase**
- **Largest margin in seven years**



Increasing Demand for Tracking Sensitive Data


- Security: data leak detection





Increasing Demand for Tracking Sensitive Data

```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject("LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}
```






Increasing Demand for Tracking Sensitive Data

```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject("LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}

public Transaction generateTransaction(Order order, Payment payment, User user){
    Transaction transaction = new Transaction();
    ....
    // Desensitize sensitive data
    String secretData = desensitizeData(user.getName());
    // User combine the secret data to generate the description
    String description = secretData + payment.getType() + order.getID();
    transaction.setDescription(description);
    ....

    return Transaction;
}
```





Increasing Demand for Tracking Sensitive Data


```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject("LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}
```

```
public Transaction generateTransaction(Order order, Payment payment, User user){
    Transaction transaction = new Transaction();
    ....
    // Desensitize sensitive data
    String secretData = desensitizeData(user.getName()...);
    // User combine the secret data to generate the description
    String description = secretData + payment.getType() + order.getID();
    transaction.setDescription(description);
    ....
}
```

```
return Transaction;
```

```
public void handleTransaction(int UID, Order order, Payment payment){
    ....


    User user = loadUserDetail(UID);
    Transaction transaction = generateTransaction(order, payment, user);
    // Insert the generated transaction to the database
    getSqlMapClientTemplate().insert("INSERT-NEW-TRANSACTION-RECORD", transaction);
    ....
}
```





Increasing Demand for Tracking Sensitive Data


1. Where will the user information be loaded in the microservices applications?





Increasing Demand for Tracking Sensitive Data


1. Where will the user information be loaded in the microservices applications?
2. How will the user information be used in the microservices applications ?





Increasing Demand for Tracking Sensitive Data

1. Where will the user information be loaded in the microservices applications?
2. How will the user information be used in the microservices applications ?
3. How to identify the propagation paths of the user information in the microservices applications?





Taint Analysis

◆ What is taint analysis?

- ◆ Information/data flow tracking analysis
- ◆ Aims to reason about the control and data dependence from a source to sink



Taint Analysis

◆ What is taint analysis?

- ◆ Information/data flow tracking analysis
- ◆ Aims to reason about the control and data dependence from a source to sink

◆ What can taint analysis do?

- ◆ Detect sensitive data leak



Taint Analysis

◆ What is taint analysis?

- ◆ Information/data flow tracking analysis
- ◆ Aims to reason about the control and data dependence from a source to sink

◆ What can taint analysis do?

- ◆ Detect sensitive data leak
- ◆ Detect code vulnerability



Taint Analysis

◆ What is taint analysis?

- ◆ Information/data flow tracking analysis
- ◆ Aims to reason about the control and data dependence from a source to sink

◆ What can taint analysis do?

- ◆ Detect sensitive data leak
- ◆ Detect code vulnerability
- ◆ Use for change governance



Taint Analysis

◆ What is taint analysis?

- ◆ Information/data flow tracking analysis
- ◆ Aims to reason about the control and data dependence from a source to sink

◆ What can taint analysis do?

- ◆ Detect sensitive data leak
- ◆ Detect code vulnerability
- ◆ Use for change governance

- FlowDroid
- ANTaint
- F4F
- DroidInfer

Challenges

A blue circle containing the word 'Recall' in white text. A vertical blue line extends upwards from the top of the circle.

Recall

A blue circle containing the word 'Scalability' in white text. A vertical blue line extends upwards from the top of the circle.

Scalability

A blue circle containing the word 'Precision' in white text. A vertical blue line extends upwards from the top of the circle.

Precision



Challenges

A large blue circle containing the word "Recall" in white text, positioned in the upper left area of the slide.

Recall



Challenges

A large blue circle with the word "Recall" written in white text in the center.

Recall

Challenge 1: Low Recall Rate

Unsound call-graph due to framework behaviours



Challenge1: Recall

```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject(
"LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}

public void handleTransaction(int UID, Order order, Payment payment){
    ....

    User user = loadUserDetail(UID);
    lambdaExample(user);
    Transaction transaction = generateTransaction(order, payment, user);
    // Insert the generated transaction to the database
    getSqlMapClientTemplate().insert("INSERT-NEW-TRANSACTION-RECORD"
, transaction);
    ....
}

public void lambdaExample(User user){
    ....
    //Lambda expression which print out the uid and password
    OperationInterl expose = (int uid, String password) -> System.out.println(
"UserID:"+uid+"password:"+password);
    ....
}
```



Code Fragment




Challenge1: Recall

```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject(
        "LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}

public void handleTransaction(int UID, Order order, Payment payment){
    ....
    User user = loadUserDetail(UID);
    lambdaExample(user);
    Transaction transaction = generateTransaction(order, payment, user);
    // Insert the generated transaction to the database
    getSqlMapClientTemplate().insert("INSERT-NEW-TRANSACTION-RECORD"
        , transaction);
    ....
}

public void lambdaExample(User user){
    ....
    //lambda expression which print out the uid and password
    OperationInterl expose = (int uid, String password) -> System.out.println(
        "UserID:"+uid+"password:"+password);
    ....
}
```

Code Fragment



Call Graph




Challenge1: Recall

```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject(
        "LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}


public void handleTransaction(int UID, Order order, Payment payment){
    ....
    User user = loadUserDetail(UID);
    lambdaExample(user);
    Transaction transaction = generateTransaction(order, payment, user);
    // Insert the generated transaction to the database
    getSqlMapClientTemplate().insert("INSERT-NEW-TRANSACTION-RECORD",
        transaction);
    ....
}

public void lambdaExample(User user){
    ....
    //lambda expression which print out the uid and password
    OperationInterl expose = (int uid, String password) -> System.out.println(
        "UserID:"+uid+"password:"+password);
    ....
}
```

Code Fragment



Call Graph



Data Flow Graph




Challenge1: Recall

```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject(
        "LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}


public void handleTransaction(int UID, Order order, Payment payment){
    ....
    User user = loadUserDetail(UID);
    lambdaExample(user);
    Transaction transaction = generateTransaction(order, payment, user);
    // Insert the generated transaction to the database
    getSqlMapClientTemplate().insert("INSERT-NEW-TRANSACTION-RECORD",
        transaction);
    ....
}

public void lambdaExample(User user){
    ....
    //lambda expression which print out the uid and password
    OperationInterl expose = (int uid, String password) -> System.out.println(
        "UserID:"+uid+"password:"+password);
    ....
}
```

Code Fragment



Call Graph



Control Flow Graph

Unsound call graph due to complex framework behaviors



Challenge1: Recall


```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject(
"LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}

public void handleTranscation(int UID, Order order, Payment payment){
    ....

    User user = loadUserDetail(UID);
    lambdaExample(user);

    // Insert the generated transaction to the database
    getSqlMapClientTemplate().insert("INSERT-NEW-TRANSACTION-RECORD"
, transaction);
    ....
}

public void lambdaExample(User user){
    ....
    //lambda expression which print out the uid and password
    OperationInter1 expose = (int uid, String password) -> System.out.println(
"UserID:"+uid+"password:"+password);
    ....
}
```





Challenge1: Recall

```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject(
"LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}


public void handleTranscation(int UID, Order order, Payment payment){
    ....

    User user = loadUserDetail(UID);
    lambdaExample(user);

    // Insert the generated transaction to the database
    getSqlMapClientTemplate().insert("INSERT-NEW-TRANSACTION-RECORD"
, transaction);

    ....
}

public void lambdaExample(User user){
    ....
    //lambda expression which print out the uid and password
    OperationInter1 expose = (int uid, String password) -> System.out.println(
"UserID:"+uid+"password:"+password);
    ....
}
```





Challenge1: Recall

```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject(
"LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}

public void handleTransection(int UID, Order order, Payment payment){
    ....


    User user = loadUserDetail(UID);
    lambdaExample(user);

    // Insert the generated transaction to the database
    getSqlMapClientTemplate().insert("INSERT-NEW-TRANSACTION-RECORD"
, transaction);

    ....
}

public void lambdaExample(User user){
    ....
    //lambda expression which print out the uid and password
    OperationInter1 expose = (int uid, String password) -> System.out.println(
"UserID:"+uid+"password:"+password);
    ....
}
```

Need manually
modeling to supplement
the call-graph





Challenge1: Recall

```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject(
"LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}

public void handleTransection(int UID, Order order, Payment payment){
    ....


    User user = loadUserDetail(UID);
    lambdaExample(user);

    // Insert the generated transaction to the database
    getSqlMapClientTemplate().insert("INSERT-NEW-TRANSACTION-RECORD"
, transaction);

    ....
}

public void lambdaExample(User user){
    ....
    //lambda expression which print out the uid and password
    OperationInter1 expose = (int uid, String password) -> System.out.println(
"UserID:"+uid+"password:"+password);
    ....
}
```

Need manually
modeling to supplement
the call-graph



- Incomplete call-graph caused the lack of trace



Challenges



Recall

Challenge 1: Low Recall Rate

Unsound call-graph due to
framework behaviours




Scalability

Challenge 2: Unscalable

Costly in both memory usage
and time consumption




Challenge2: Scalability






Challenge2: Scalability



- Classes: dozens of thousands




Challenge2: Scalability



- Classes: dozens of thousands
- Jar Package: 100 MB+




Challenge2: Scalability



- Classes: dozens of thousands
- Jar Package: 100 MB+
- Services Methods: a few hundreds




Challenge2: Scalability



- Classes: dozens of thousands
- Jar Package: 100 MB+
- Services Methods: a few hundreds
- Interested Fields: dozens of thousands



Challenge2: Scalability




- Classes: dozens of thousands
- Jar Package: 100 MB+
- Services Methods: a few hundreds
- Interested Fields: dozens of thousands

- Massive amount of context information need to maintenance



Challenge2: Scalability




- Classes: dozens of thousands
- Jar Package: 100 MB+
- Services Methods: a few hundreds
- Interested Fields: dozens of thousands

- Massive amount of context information need to maintenance
- Functions invoked under different contexts must be (re)analyzed



Challenge2: Scalability



- Classes: dozens of thousands
- Jar Package: 100 MB+
- Services Methods: a few hundreds
- Interested Fields: dozens of thousands

- Massive amount of context information need to maintenance
- Functions invoked under different contexts must be (re)analyzed

Existing tools run too long and use too much memory



Challenges



Recall

Challenge 1: Low Recall Rate

Unsound call-graph due to
framework behaviours



Scalability

Challenge 2: Unscalable

Costly in both memory usage
and time consumption



Precision


Challenge 3: Inaccuracy

Over-tainted due to inaccurate
taint trace in container



Challenge3: Precision


- A simple model introduces false positives





Challenge3: Precision

- A simple model introduces false positives



ele.name is regarded as tainted





Approach




Overview of TaintFuzz

Byte Code / Jar Package
<ul style="list-style-type: none">- App Jar package- Libraries Jar package (Dependencies)




Overview of TaintFuzz





Overview of TaintFuzz






Preprocessing Module

Code Transformation and Modeling Module

Database Operation Modeling Module






Preprocessing Module

Code Transformation and Modeling Module

- Framework code (e.g. RPC)

Database Operation Modeling Module






Preprocessing Module

Code Transformation and Modeling Module

- Framework code (e.g. RPC)
- Hidden code of the AOP invoke

Database Operation Modeling Module






Preprocessing Module

Code Transformation and Modeling Module

- Framework code (e.g. RPC)
- Hidden code of the AOP invoke
- Operation of the container code (e.g. map.put(), list.add(), JSON.format(), etc.)

Database Operation Modeling Module






Preprocessing Module

Code Transformation and Modeling Module

- Framework code (e.g. RPC)
- Hidden code of the AOP invoke
- Operation of the container code (e.g. map.put(), list.add(), JSON.format(), etc.)

Database Operation Modeling Module

- Extract and analysis all SQL statement from the targeted code






Preprocessing Module

Code Transformation and Modeling Module

- Framework code (e.g. RPC)
- Hidden code of the AOP invoke
- Operation of the container code (e.g. map.put(), list.add(), JSON.format(), etc.)


Database Operation Modeling Module

- Extract and analysis all SQL statement from the targeted code
- Generate the relationship between variable and database column





Overview of TaintFuzz





Recall: File-based Static Taint Analysis



Recall: Filed-based Static Taint Analysis


```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject(
"LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}

public void handleTranscation(int UID, Order order, Payment payment){
    ....

    User user = loadUserDetail(UID);
    lambdaExample(user);
    Transaction transaction = generateTranscation(order, payment, user);
    // Insert the generated transaction to the database
    getSqlMapClientTemplate().insert("INSERT-NEW-TRANSACTION-RECORD"
, transaction);

    ....
}

public void lambdaExample(User user){
    ....
    //lambda expression which print out the uid and password
    OperationInter1 expose = (int uid, String password) -> System.out.println(
"UserID:"+uid+"password:"+password);
    ....
}
```



- All propagation of the same field are related

Scalability: Function Summary Construction

Algorithm 1: Inter-Procedure Taint Analysis

Input : application A
Output: G

```

1  $G = \emptyset, S = \emptyset$ 
2 foreach  $m \in M$  do
3    $S_m = \text{BuildSummary}(m, G, S)$ 
4    $S = S \cup \{S_m\}$ 
5 return  $G$ 
6 Function  $\text{BuildSummary}(m, G, S)$ :
7    $T_p = \emptyset, R_f = \emptyset, R_p = \emptyset, MID = \emptyset$ 
8    $S_m = \{T_p, R_f, R_p\}$ 
9   foreach  $statement \in m$  do
10    if  $statement : v \leftarrow v'$  then
11      if  $v$  is local then
12         $MID = MID \cup \{\langle v, v' \rangle\}$ 
13      else if  $v : \_ . f$  then
14        foreach  $p_i \in \text{find}(v', MID)$  do
15           $T_p = T_p \cup \{\langle p_i, f \rangle\}$ 
16        foreach  $\_ . f' \in \text{find}(v', MID)$  do
17           $G = G \cup \{\langle f', f \rangle\}$ 
18      else if  $statement : \text{return } v$  then
19        foreach  $p_i \in \text{find}(v, MID)$  do
20           $R_p = R_p \cup \{p_i\}$ 
21        foreach  $\_ . f \in \text{find}(v, MID)$  do
22           $R_f = R_f \cup \{f\}$ 
23      else if  $statement : v = m'(v')$  then
24         $S_{m'} = \text{generate}(m', S)$ 
25        foreach  $p_i \in \text{find}(v', MID)$  do
26          foreach  $\langle p'_i, f \rangle \in T'_p$  do
27             $T_p = T_p \cup \{\langle p_i, f \rangle\}$ 
28        foreach  $\_ . f' \in \text{find}(v', MID)$  do
29          foreach  $\langle p'_i, f \rangle \in T'_p$  do
30             $G = G \cup \{\langle f', f \rangle\}$ 
31         $MID = MID \cup \{\langle v, src \rangle \mid src \in R'_f \parallel src \in R'_p\}$ 
32 return  $S_m$ 

```

Scalability: Function Summary Construction

- Start the analysis from any function randomly

Algorithm 1: Inter-Procedure Taint Analysis

```
Input : application  $A$ 
Output:  $G$ 
1  $G = \emptyset, S = \emptyset$ 
2 foreach  $m \in M$  do
3    $S_m = \text{BuildSummary}(m, G, S)$ 
4    $S = S \cup \{S_m\}$ 
5 return  $G$ 
6 Function  $\text{BuildSummary}(m, G, S)$ :
7    $T_p = \emptyset, R_f = \emptyset, R_p = \emptyset, MID = \emptyset$ 
8    $S_m = \{T_p, R_f, R_p\}$ 
9   foreach  $statement \in m$  do
10    if  $statement : v \leftarrow v'$  then
11      if  $v$  is local then
12         $MID = MID \cup \{\langle v, v' \rangle\}$ 
13      else if  $v : \_ . f$  then
14        foreach  $p_i \in \text{find}(v', MID)$  do
15           $T_p = T_p \cup \{\langle p_i, f \rangle\}$ 
16        foreach  $\_ . f' \in \text{find}(v', MID)$  do
17           $G = G \cup \{\langle f', f \rangle\}$ 
18      else if  $statement : \text{return } v$  then
19        foreach  $p_i \in \text{find}(v, MID)$  do
20           $R_p = R_p \cup \{p_i\}$ 
21        foreach  $\_ . f \in \text{find}(v, MID)$  do
22           $R_f = R_f \cup \{f\}$ 
23      else if  $statement : v = m'(v')$  then
24         $S_{m'} = \text{generate}(m', S)$ 
25        foreach  $p_i \in \text{find}(v', MID)$  do
26          foreach  $\langle p'_i, f \rangle \in T'_p$  do
27             $T_p = T_p \cup \{\langle p_i, f \rangle\}$ 
28        foreach  $\_ . f' \in \text{find}(v', MID)$  do
29          foreach  $\langle p'_i, f \rangle \in T'_p$  do
30             $G = G \cup \{\langle f', f \rangle\}$ 
31         $MID = MID \cup \{\langle v, src \rangle \mid src \in R'_f \parallel src \in R'_p\}$ 
32 return  $S_m$ 
```

Scalability: Function Summary Construction

- Start the analysis from any function randomly
- Generate a data propagation summary for each function

Algorithm 1: Inter-Procedure Taint Analysis

Input : application A
Output: G

```

1  $G = \emptyset, S = \emptyset$ 
2 foreach  $m \in M$  do
3    $S_m = \text{BuildSummary}(m, G, S)$ 
4    $S = S \cup \{S_m\}$ 
5 return  $G$ 
6 Function  $\text{BuildSummary}(m, G, S)$ :
7    $T_p = \emptyset, R_f = \emptyset, R_p = \emptyset, MID = \emptyset$ 
8    $S_m = \{T_p, R_f, R_p\}$ 
9   foreach  $statement \in m$  do
10    if  $statement : v \leftarrow v'$  then
11      if  $v$  is local then
12         $MID = MID \cup \{\langle v, v' \rangle\}$ 
13      else if  $v : \_ . f$  then
14        foreach  $p_i \in \text{find}(v', MID)$  do
15           $T_p = T_p \cup \{\langle p_i, f \rangle\}$ 
16        foreach  $\_ . f' \in \text{find}(v', MID)$  do
17           $G = G \cup \{\langle f', f \rangle\}$ 
18      else if  $statement : \text{return } v$  then
19        foreach  $p_i \in \text{find}(v, MID)$  do
20           $R_p = R_f \cup \{p_i\}$ 
21        foreach  $\_ . f \in \text{find}(v, MID)$  do
22           $R_f = R_f \cup \{f\}$ 
23      else if  $statement : v = m'(v')$  then
24         $S_{m'} = \text{generate}(m', S)$ 
25        foreach  $p_i \in \text{find}(v', MID)$  do
26          foreach  $\langle p'_i, f \rangle \in T'_p$  do
27             $T_p = T_p \cup \{\langle p_i, f \rangle\}$ 
28        foreach  $\_ . f' \in \text{find}(v', MID)$  do
29          foreach  $\langle p'_i, f \rangle \in T'_p$  do
30             $G = G \cup \{\langle f', f \rangle\}$ 
31         $MID = MID \cup \{\langle v, src \rangle \mid src \in R'_f \parallel src \in R'_p\}$ 
32 return  $S_m$ 

```

Scalability: Function Summary Construction

- Start the analysis from any function randomly
- Generate a data propagation summary for each function
 - Only maintenance the context information of the current function
 - On demand call analysis with the function summary

Algorithm 1: Inter-Procedure Taint Analysis

```

Input : application  $A$ 
Output:  $G$ 
1  $G = \emptyset, S = \emptyset$ 
2 foreach  $m \in M$  do
3    $S_m = \text{BuildSummary}(m, G, S)$ 
4    $S = S \cup \{S_m\}$ 
5 return  $G$ 
6 Function  $\text{BuildSummary}(m, G, S)$ :
7    $T_p = \emptyset, R_f = \emptyset, R_p = \emptyset, MID = \emptyset$ 
8    $S_m = \{T_p, R_f, R_p\}$ 
9   foreach  $statement \in m$  do
10    if  $statement : v \leftarrow v'$  then
11      if  $v$  is local then
12         $MID = MID \cup \{\langle v, v' \rangle\}$ 
13      else if  $v : \_ . f$  then
14        foreach  $p_i \in \text{find}(v', MID)$  do
15           $T_p = T_p \cup \{\langle p_i, f \rangle\}$ 
16        foreach  $\_ . f' \in \text{find}(v', MID)$  do
17           $G = G \cup \{\langle f', f \rangle\}$ 
18      else if  $statement : \text{return } v$  then
19        foreach  $p_i \in \text{find}(v, MID)$  do
20           $R_p = R_f \cup \{p_i\}$ 
21        foreach  $\_ . f \in \text{find}(v, MID)$  do
22           $R_f = R_f \cup \{f\}$ 
23      else if  $statement : v = m'(v')$  then
24         $S_{m'} = \text{generate}(m', S)$ 
25        foreach  $p_i \in \text{find}(v', MID)$  do
26          foreach  $\langle p'_i, f \rangle \in T'_p$  do
27             $T_p = T_p \cup \{\langle p_i, f \rangle\}$ 
28        foreach  $\_ . f' \in \text{find}(v', MID)$  do
29          foreach  $\langle p'_i, f \rangle \in T'_p$  do
30             $G = G \cup \{\langle f', f \rangle\}$ 
31         $MID = MID \cup \{\langle v, src \rangle \mid src \in R'_f \parallel src \in R'_p\}$ 
32 return  $S_m$ 

```



```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject("LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}

public String generateTransaction(int UID, Order order, Payment payment){
    ....
    User user = loadUserDetail(UID);
    String secretData = user.getPassword() + user.getUID() + user.getName();
    String transactionMessage = order.getID() + secretData();
    ....

    return transactionMessage;
}
```



```
public User loadUserDetail(int UID){  
    ....  
    // Query user information from database by ID  
    User user = getSqlMapClientTemplate().queryForObject("LOAD-ALL-USER-INFO-BY-UID", UID);  
    return user;  
}
```

```
public String generateTransaction(int UID, Order order, Payment payment){  
    ....  
    User user = loadUserDetail(UID);  
    String secretData = user.getPassword() + user.getUID() + user.getName();  
    String transactionMessage = order.getID() + secretData();  
    ....  
    return transactionMessage;  
}
```

Existed: pass **UID** as context information.
No Exist: generate the summarization



```
public User loadUserDetail(int UID){
    ....
    // Query user information from database by ID
    User user = getSqlMapClientTemplate().queryForObject("LOAD-ALL-USER-INFO-BY-UID", UID);
    return user;
}


public String generateTransaction(int UID, Order order, Payment payment){
    ....
    User user = loadUserDetail(UID);
    String secretData = user.getPassword() + user.getUID() + user.getName();
    String transactionMessage = order.getID() + secretData();
    ....

    return transactionMessage;
}
```

{ [SQL:LOAD-ALL-USER -> returnObject] -> user
-> secretData -> transactionMessage -> returnObj}




Overview of TaintFuzz





Overview of TaintFuzz





Evaluation



Datasets

- Open-source Micro-benchmark
- Production-benchmark



Datasets

- Open-source Micro-benchmark
 - ◆ Provides by Wang et al. (2020) on GitHub
 - ◆ Contributed by the industry experts
 - ◆ Including 27 cases that developers are concerned with in the industry scenario
- Production-benchmark



Datasets

- **Open-source Micro-benchmark**
 - ◆ Provides by Wang et al. (2020) on GitHub
 - ◆ Contributed by the industry experts
 - ◆ Including 27 cases that developers are concerned with in the industry scenario
- **Production-benchmark**
 - ◆ Contains more than 500 core production microservices applications of the industry partner
 - ◆ Written in SOFA architecture



Research Questions

- *RQ1:* What is the performance of our approach when it is applied on real world industrial cases ?



Research Questions

- *RQ1:* What is the performance of our approach when it is applied on real world industrial cases ?
- *RQ2:* How well does our approach in terms of precision and recall for sensitive data tracing on industrial microservices applications?



Research Questions

- *RQ1:* What is the performance of our approach when it is applied on real world industrial cases ?
- *RQ2:* How well does our approach in terms of precision and recall for sensitive data tracing on industrial microservices applications?
- *RQ3:* How TaintFuzz is compared to existing tools, such as ANTaint?



Evaluation: Performance

RQ1: What is the performance of our approach when it is applied on real world industrial cases ?

- Evaluate on the Open-source Micro-benchmark

Evaluation: Performance

RQ1: What is the performance of our approach when it is applied on real world industrial cases ?

- Evaluate on the Open-source Micro-benchmark
 - Pass **93% (25 out of 27 cases)** of the test scenarios
 - With the **precision of 100%**

		ANTaint			TaintFuzz		
Micro-benchmark	Exp	Exa	FN	FP	Exa	FN	FP
queryForPageTaint	5	5	0	0	5	0	0
resolveFromReference	10	10	0	0	0	10	0
updateRidAll	18	18	0	0	18	0	0
queryAllTaint	15	15	0	0	15	0	0
allResolve	20	20	0	0	20	0	0
saveAndQuery	15	15	0	0	15	0	0
updateRidByName	10	10	0	0	10	0	0
queryByNameTaint	5	5	0	0	5	0	0
queryByName2Taint	4	4	0	0	4	0	0
saveSampleByResult	10	10	0	0	10	0	0
batchResolve	10	10	0	0	10	0	0
resolveSampleResult	10	10	0	0	0	10	0
queryByCallback1	1	1	0	0	1	0	0
queryByCallbacks34	2	2	0	0	2	0	0
queryByCallbacks56	2	2	0	0	2	0	0
queryByCallbacks12	2	2	0	0	2	0	0
queryByCallbacks13	2	2	0	0	2	0	0
queryByCallbacks15	2	2	0	0	2	0	0
testMultiplePaths4	1	1	0	0	1	0	0
testList2	1	1	0	0	1	0	0
testList3	1	1	0	0	1	0	0
testList4	1	1	0	0	1	0	0
testDeepCopy	2	2	0	0	2	0	0
testDeepCopy2	2	2	0	0	2	0	0
Total						20	0

Evaluation: Performance

RQ1: What is the performance of our approach when it is applied on real world industrial cases ?

- Evaluate on the Open-source Micro-benchmark
 - Pass **93% (25 out of 27 cases)** of the test scenarios
 - With the **precision of 100%**

Two cases are failed to find any taint propagation paths because of **using a super-class object as a source for the analysis**

		ANTaint			TaintFuzz		
Micro-benchmark	Exp	Exa	FN	FP	Exa	FN	FP
queryForPageTaint	5	5	0	0	5	0	0
resolveFromReference	10	10	0	0	0	10	0
updateRidAll	18	18	0	0	18	0	0
queryAllTaint	15	15	0	0	15	0	0
allResolve	20	20	0	0	20	0	0
saveAndQuery	15	15	0	0	15	0	0
updateRidByName	10	10	0	0	10	0	0
queryByNameTaint	5	5	0	0	5	0	0
queryByName2Taint	4	4	0	0	4	0	0
saveSampleByResult	10	10	0	0	10	0	0
batchResolve	10	10	0	0	10	0	0
resolveSampleResult	10	10	0	0	0	10	0
queryByCallback1	1	1	0	0	1	0	0
queryByCallbacks34	2	2	0	0	2	0	0
queryByCallbacks56	2	2	0	0	2	0	0
queryByCallbacks12	2	2	0	0	2	0	0
queryByCallbacks13	2	2	0	0	2	0	0
queryByCallbacks15	2	2	0	0	2	0	0
testMultiplePaths4	1	1	0	0	1	0	0
testList2	1	1	0	0	1	0	0
testList3	1	1	0	0	1	0	0
testList4	1	1	0	0	1	0	0
testDeepCopy	2	2	0	0	2	0	0
testDeepCopy2	2	2	0	0	2	0	0
Total						20	0



Evaluation: Precision & Recall

RQ2: How well does our approach in terms of precision and recall for sensitive data tracing on industrial microservices applications?

- Production benchmark: more than 500 microservices applications



Metric Criteria

- True/Correct Path (**TP**) : Correct taint paths that are identified



Metric Criteria

- True/Correct Path (**TP**) : Correct taint paths that are identified
- False-Negative Path (**FN**) : Correct taint paths that are not identified



Metric Criteria

- True/Correct Path (**TP**) : Correct taint paths that are identified
- False-Negative Path (**FN**) : Correct taint paths that are not identified
- False-Positive Path (**FP**) : Incorrect taint paths that are identified



Metric Criteria

- True/Correct Path (**TP**) : Correct taint paths that are identified
- False-Negative Path (**FN**) : Correct taint paths that are not identified
- False-Positive Path (**FP**) : Incorrect taint paths that are identified
- Recall of our approach: $Recall = \frac{TP}{TP+FN}$



Metric Criteria

- True/Correct Path (**TP**) : Correct taint paths that are identified
- False-Negative Path (**FN**) : Correct taint paths that are not identified
- False-Positive Path (**FP**) : Incorrect taint paths that are identified
- Recall of our approach: $Recall = \frac{TP}{TP+FN}$
- Precision (**P**) of our approach: $P = \frac{TP}{TP + FP}$



Metric Criteria

- True/Correct Path (**TP**) : Correct taint paths that are identified
- False-Negative Path (**FN**) : Correct taint paths that are not identified
- False-Positive Path (**FP**) : Incorrect taint paths that are identified
- Recall (**R**) of our approach: $R = \frac{TP}{TP+FN}$
- Precision (**P**) of our approach: $P = \frac{TP}{TP + FP}$
- Overall time consumption



Evaluation: Precision & Recall

RQ2: How well does our approach in terms of precision and recall for sensitive data tracing on industrial microservices applications?

- Production benchmark: more than 500 microservices applications

Average Precision of 94% and Recall of 98%

	Code Size		ANTaint						TaintFuzz					
App	app(MB)	lib(MB)	TP	FN	FP	Time(s)	Recall(%)	P(%)	TP	FN	FP	Time(s)	Recall(%)	P(%)
M1	40.9	85.5	9	2	3	2260	81.82%	75%	11	0	0	167.41	100%	100%
M2	4.7	78	5	2	1	906	71.43%	83%	7	0	0	67.97	100%	100%
M3	20.4	173.3	3	5	6	4423	37.50%	33%	8	1	2	369	88.89%	80%
M4	19.3	80.6	8	0	4	2517	100%	67%	8	0	1	180.8	100%	89%
M5	3.4	68.2	6	1	2	1124	85.71%	75%	7	0	0	166.89	100%	100%
M6	2.3	193.9	5	3	1	51.7	62.50%	83%	8	0	0	14	100%	100%
Avg	12%	88%	55%	19.70%	25.76%	1880.3	73.16%	68%	92.45%	1.89%	5.67%	161.0	98%	94%
Note: TP = Correct/True Paths, FN = False-negative, FP = False-positive, P = Precision														



Evaluation: Precision & Recall

RQ2: How well does our approach in terms of precision and recall for sensitive data tracing on industrial microservices applications?

- Production benchmark: more than 500 microservices applications

Average Precision of 94% and **Recall of 98%**

Worst Precision of 80% and **Recall of 88.98%**

	Code Size		ANTaint						TaintFuzz					
App	app(MB)	lib(MB)	TP	FN	FP	Time(s)	Recall(%)	P(%)	TP	FN	FP	Time(s)	Recall(%)	P(%)
M1	40.9	85.5	9	2	3	2260	81.82%	75%	11	0	0	167.41	100%	100%
M2	4.7	78	5	2	1	906	71.43%	83%	7	0	0	67.97	100%	100%
M3	20.4	173.3	3	5	6	4423	37.50%	33%	8	1	2	369	88.89%	80%
M4	19.3	80.6	8	0	4	2517	100%	67%	8	0	1	180.8	100%	89%
M5	3.4	68.2	6	1	2	1124	85.71%	75%	7	0	0	166.89	100%	100%
M6	2.3	193.9	5	3	1	51.7	62.50%	83%	8	0	0	14	100%	100%
Avg	12%	88%	55%	19.70%	25.76%	1880.3	73.16%	68%	92.45%	1.89%	5.67%	161.0	98%	94%

Note: TP = Correct/True Paths, FN = False-negative, FP = False-positive, P = Precision



Evaluation: Precision & Recall

RQ2: How well does our approach in terms of precision and recall for sensitive data tracing on industrial microservices applications?

- Production benchmark: more than 500 microservices applications

	Code Size		ANTaint						TaintFuzz					
App	app(MB)	lib(MB)	TP	FN	FP	Time(s)	Recall(%)	P(%)	TP	FN	FP	Time(s)	Recall(%)	P(%)
M1	40.9	85.5	9	2	3	2260	81.82%	75%	11	0	0	167.41	100%	100%
M2	4.7	78	5	2	1	906	71.43%	83%	7	0	0	67.97	100%	100%
M3	20.4	173.3	3	5	6	4423	37.50%	33%	8	1	2	369	88.89%	80%
M4	19.3	80.6	8	0	4	2517	100%	67%	8	0	1	180.8	100%	89%
M5	3.4	68.2	6	1	2	1124	85.71%	75%	7	0	0	166.89	100%	100%
M6	2.3	193.9	5	3	1	51.7	62.50%	83%	8	0	0	14	100%	100%
Avg	12%	88%	55%	19.70%	25.76%	1880.3	73.16%	68%	92.45%	1.89%	5.67%	161.0	98%	94%
Note: TP = Correct/True Paths, FN = False-negative, FP = False-positive, P = Precision														



Evaluation: Precision & Recall

RQ2: How well does our approach in terms of precision and recall for sensitive data tracing on industrial microservices applications?

- Production benchmark: more than 500 microservices applications

1 FN Results: caused by the usage of a vague object as the taint source

3 FP Results: caused by the propagation between container with a non-constant key

	Code Size		ANTaint						TaintFuzz					
App	app(MB)	lib(MB)	TP	FN	FP	Time(s)	Recall(%)	P(%)	TP	FN	FP	Time(s)	Recall(%)	P(%)
M1	40.9	85.5	9	2	3	2260	81.82%	75%	11	0	0	167.41	100%	100%
M2	4.7	78	5	2	1	906	71.43%	83%	7	0	0	67.97	100%	100%
M3	20.4	173.3	3	5	6	4423	37.50%	33%	8	1	2	369	88.89%	80%
M4	19.3	80.6	8	0	4	2517	100%	67%	8	0	1	180.8	100%	89%
M5	3.4	68.2	6	1	2	1124	85.71%	75%	7	0	0	166.89	100%	100%
M6	2.3	193.9	5	3	1	51.7	62.50%	83%	8	0	0	14	100%	100%
Avg	12%	88%	55%	19.70%	25.76%	1880.3	73.16%	68%	92.45%	1.89%	5.67%	161.0	98%	94%
Note: TP = Correct/True Paths, FN = False-negative, FP = False-positive, P = Precision														



Evaluation: Comparison with ANTaint

RQ3: How TaintFuzz is compared to existing tools, such as ANTaint?

	Code Size		ANTaint						TaintFuzz					
App	app(MB)	lib(MB)	TP	FN	FP	Time(s)	Recall(%)	P(%)	TP	FN	FP	Time(s)	Recall(%)	P(%)
M1	40.9	85.5	9	2	3	2260	81.82%	75%	11	0	0	167.41	100%	100%
M2	4.7	78	5	2	1	906	71.43%	83%	7	0	0	67.97	100%	100%
M3	20.4	173.3	3	5	6	4423	37.50%	33%	8	1	2	369	88.89%	80%
M4	19.3	80.6	8	0	4	2517	100%	67%	8	0	1	180.8	100%	89%
M5	3.4	68.2	6	1	2	1124	85.71%	75%	7	0	0	166.89	100%	100%
M6	2.3	193.9	5	3	1	51.7	62.50%	83%	8	0	0	14	100%	100%
Avg	12%	88%	55%	19.70%	25.76%	1880.3	73.16%	68%	92.45%	1.89%	5.67%	161.0	98%	94%

Note: TP = Correct/True Paths, FN = False-negative, FP = False-positive, P = Precision



Evaluation: Comparison with ANTaint

RQ3: How TaintFuzz is compared to existing tools, such as ANTaint?

Precision: **68%**(ANTaint) V.S. **94%**(TaintFuzz) → **25% increase**

	Code Size		ANTaint						TaintFuzz					
App	app(MB)	lib(MB)	TP	FN	FP	Time(s)	Recall(%)	P(%)	TP	FN	FP	Time(s)	Recall(%)	P(%)
M1	40.9	85.5	9	2	3	2260	81.82%	75%	11	0	0	167.41	100%	100%
M2	4.7	78	5	2	1	906	71.43%	83%	7	0	0	67.97	100%	100%
M3	20.4	173.3	3	5	6	4423	37.50%	33%	8	1	2	369	88.89%	80%
M4	19.3	80.6	8	0	4	2517	100%	67%	8	0	1	180.8	100%	89%
M5	3.4	68.2	6	1	2	1124	85.71%	75%	7	0	0	166.89	100%	100%
M6	2.3	193.9	5	3	1	51.7	62.50%	83%	8	0	0	14	100%	100%
Avg	12%	88%	55%	19.70%	25.76%	1880.3	73.16%	68%	92.45%	1.89%	5.67%	161.0	98%	94%
Note: TP = Correct/True Paths, FN = False-negative, FP = False-positive, P = Precision														



Evaluation: Comparison with ANTaint

RQ3: How TaintFuzz is compared to existing tools, such as ANTaint?

Precision: **68%(ANTaint) V.S. 94%(TaintFuzz) → 25% increase**

Recall: **73.16%(ANTaint) V.S. 98%(TaintFuzz) → 24.84% increase**

	Code Size		ANTaint						TaintFuzz					
App	app(MB)	lib(MB)	TP	FN	FP	Time(s)	Recall(%)	P(%)	TP	FN	FP	Time(s)	Recall(%)	P(%)
M1	40.9	85.5	9	2	3	2260	81.82%	75%	11	0	0	167.41	100%	100%
M2	4.7	78	5	2	1	906	71.43%	83%	7	0	0	67.97	100%	100%
M3	20.4	173.3	3	5	6	4423	37.50%	33%	8	1	2	369	88.89%	80%
M4	19.3	80.6	8	0	4	2517	100%	67%	8	0	1	180.8	100%	89%
M5	3.4	68.2	6	1	2	1124	85.71%	75%	7	0	0	166.89	100%	100%
M6	2.3	193.9	5	3	1	51.7	62.50%	83%	8	0	0	14	100%	100%
Avg	12%	88%	55%	19.70%	25.76%	1880.3	73.16%	68%	92.45%	1.89%	5.67%	161.0	98%	94%
Note: TP = Correct/True Paths, FN = False-negative, FP = False-positive, P = Precision														



Evaluation: Comparison with ANTaint

RQ3: How TaintFuzz is compared to existing tools, such as ANTaint?

Precision: **68%(ANTaint) V.S. 94%(TaintFuzz) → 25% increase**

Recall: **73.16%(ANTaint) V.S. 98%(TaintFuzz) → 24.84% increase**

Time: **31mins(ANTaint) V.S. 2.67mins(TaintFuzz) → 91% off & 10 times faster**

	Code Size		ANTaint						TaintFuzz					
App	app(MB)	lib(MB)	TP	FN	FP	Time(s)	Recall(%)	P(%)	TP	FN	FP	Time(s)	Recall(%)	P(%)
M1	40.9	85.5	9	2	3	2260	81.82%	75%	11	0	0	167.41	100%	100%
M2	4.7	78	5	2	1	906	71.43%	83%	7	0	0	67.97	100%	100%
M3	20.4	173.3	3	5	6	4423	37.50%	33%	8	1	2	369	88.89%	80%
M4	19.3	80.6	8	0	4	2517	100%	67%	8	0	1	180.8	100%	89%
M5	3.4	68.2	6	1	2	1124	85.71%	75%	7	0	0	166.89	100%	100%
M6	2.3	193.9	5	3	1	51.7	62.50%	83%	8	0	0	14	100%	100%
Avg	12%	88%	55%	19.70%	25.76%	1880.3	73.16%	68%	92.45%	1.89%	5.67%	161.0	98%	94%
Note: TP = Correct/True Paths, FN = False-negative, FP = False-positive, P = Precision														



Conclusion



In Conclusion

- Features
 - ✓ A compositional taint analysis approach



In Conclusion

- Features
 - ✓ A compositional taint analysis approach
 - ✓ Used the function summary strategy for more scalable analysis



In Conclusion

- Features
 - ✓ A compositional taint analysis approach
 - ✓ Used the function summary strategy for scalable analysis
 - ✓ Used the field-based algorithm to provide more sound analysis



In Conclusion

- Features
 - ✓ A compositional taint analysis approach
 - ✓ Used the function summary strategy for scalable analysis
 - ✓ Used the field-based algorithm to provide more sound analysis
 - ✓ Used the white-box fuzzing to verify the massive amount of taint analysis results



In Conclusion

- Features
 - ✓ A compositional taint analysis approach
 - ✓ Used the function summary strategy for scalable analysis
 - ✓ Used the field-based algorithm to provide more sound analysis
 - ✓ Used the white-box fuzzing to verify the massive amount of taint analysis results
 - ✓ 25% higher than ANTaint in terms of precision and recall



In Conclusion

- Features
 - ✓ A compositional taint analysis approach
 - ✓ Used the function summary strategy for scalable analysis
 - ✓ Used the field-based algorithm to provide more sound analysis
 - ✓ Used the white-box fuzzing to verify the massive amount of taint analysis results
 - ✓ 25% higher than ANTaint in terms of precision and recall
 - ✓ 10 times faster than ANTaint



In Conclusion

- Features
 - ✓ A compositional taint analysis approach
 - ✓ Used the function summary strategy for scalable analysis
 - ✓ Used the field-based algorithm to provide more sound analysis
 - ✓ Used the white-box fuzzing to verify the massive amount of taint analysis results
 - ✓ 25% higher than ANTaint in terms of precision and recall
 - ✓ 10 times faster than ANTaint



In Conclusion

- Features
 - ✓ A compositional taint analysis approach
 - ✓ Used the function summary strategy for scalable analysis
 - ✓ Used the field-based algorithm to provide more sound analysis
 - ✓ Used the white-box fuzzing to verify the massive amount of taint analysis results
 - ✓ 25% higher than ANTaint in terms of precision and recall
 - ✓ 10 times faster than ANTaint
- Limitations



In Conclusion

- Features

- ✓ A compositional taint analysis approach
- ✓ Used the function summary strategy for scalable analysis
- ✓ Used the field-based algorithm to provide more sound analysis
- ✓ Used the white-box fuzzing to verify the massive amount of taint analysis results
- ✓ 25% higher than ANTaint in terms of precision and recall
- ✓ 10 times faster than ANTaint

- Limitations

- ✓ Unable to tracking taint propagation with non-constant key data in container



In Conclusion

- Features

- ✓ A compositional taint analysis approach
- ✓ Used the function summary strategy for scalable analysis
- ✓ Used the field-based algorithm to provide more sound analysis
- ✓ Used the white-box fuzzing to verify the massive amount of taint analysis results
- ✓ 25% higher than ANTaint in terms of precision and recall
- ✓ 10 times faster than ANTaint

- Limitations

- ✓ Unable to tracking taint propagation with non-constant key data in container
- ✓ Unable to tracking taint propagation of a source of an superclass object



Questions ?