



*ManfredSteyer*



# I18N mit Angular

Manfred Steyer

**SOFTWARE***architekt.at*

# Inhalt

- Angular Compiler
- ngx-translate


# Angular Compiler



# Angular Compiler

XML Localisation Interchange File Format (XLIFF, version 1.2)

XML Message Bundle (XMB)



# Angular Compiler

Great  
Performance

One Build per  
Language

Cannot Change  
Language at  
Runtime!

Cannot Read  
Translations in  
Code

# Texte markieren

```
<th i18n>From</th>  
<th i18n="Beschreibung">To</th>  
<th i18n="Bedeutung | Beschreibung">Passengers</th>
```

# Texte extrahieren (Angular CLI)

```
ng xi18n
```

# Übersetzungen und AOT (Angular CLI)


```
ng build --i18nFile=src/i18n/messages.de.xlf  
        --locale=de  
        --i18nFormat=xlf
```




# Übersetzungen und JIT

```
providers: [  
  {provide: TRANSLATIONS, useValue: require('./i18n/messages.de.xlf')},  
  {provide: TRANSLATIONS_FORMAT, useValue: 'xlf'},  
  {provide: LOCALE_ID, useValue: 'de'}  
]
```

ngx-translate



# ngx-translate



Data format and way of loading are adaptable

# ngx-translate

One Build

Change  
Language at  
Runtime!

Read  
Translations in  
Code

Data Binding  
Influences  
Performance

# Import

```
export function createLoader(http: HttpClient) {  
  return new TranslateStaticLoader(http, './i18n', '.json');  
}
```

# Import

```
export function createLoader(http: HttpClient) {  
  return new TranslateStaticLoader(http, './i18n', '.json');  
}
```

```
@NgModule({  
  imports: [  
    TranslateModule.forRoot({  
      provide: TranslateLoader,  
      useFactory: createLoader,  
      deps: [HttpClient]  
    })  
  ],  
  [...]  
})  
export class AppModule {  
}
```

# Initialize

```
this.translate.addLangs(['en', 'de']);  
this.translate.setDefaultLang('de');  
this.translate.use('de');
```

# Resource File

```
{  
  "FLIGHTS": {  
    "from": "From",  
    "to": "to",  
    "search": "Search",  
    "found": "{{count}} flights found."  
  }  
}
```



# Translation

```
<th>{{'FLIGHTS.from' | translate}}</th>
```

```
<th>{{'FLIGHTS.found' | translate:{count: 7} }}</th>
```

# DEMO



Local Formats

---

# Pipes and local Formats

```
{{ flight.date | date:'long' }}
```

# Import format information

```
import { registerLocaleData } from '@angular/common';  
import localeDe from '@angular/common/locales/de';  
import localeDeAt from '@angular/common/locales/de-AT';  
import localeEs from '@angular/common/locales/es';
```

```
registerLocaleData(localeDe);    // de-DE  
registerLocaleData(localeDeAt);  // de-AT  
registerLocaleData(localeEs);    // es-ES
```

# Define default locale

```
providers: [  
  [...]  
  { provide: LOCALE_ID, useValue: 'de' },  
]
```

# Use Formats

```
<p>Datum (Default=de): {{ item.date | date:'long' }}</p>
```

```
<p>Datum (de-AT): {{ item.date | date:'long':'': 'de-AT' }}</p>
```

```
<p>Datum (es): {{ item.date | date:'long':'': 'es' }}</p>
```



# I18N and Inputs?

- Pipes are just for outputs
- Use component lib (like Angular Material)
- General concept: `ControlValueAccessor`