

Disaster Recovery Plan (DRP) Template

Technology recovery plan — completed per client environment

Document ID: BVT-IRP-049

Version: 1.0

Issued: July 02, 2026

Effective Date: _____

Client: _____

Plan Owner: _____

Last Updated: _____

Last Tested: _____

Objectives and Definitions

This plan restores IT services after a disaster (site loss, hardware failure, ransomware, extended outage). RTO = maximum tolerable time to restore a service. RPO = maximum tolerable data loss measured in time. Targets below are set with the client and drive backup frequency and recovery architecture.

System Recovery Tiers

Tier	Systems (fill in)	RTO	RPO	Recovery Method
Tier 1 — Critical (business stops)	e.g., M365/email, LOB app, file services	≤ 8 hrs	≤ 4 hrs	Cloud-native resilience + image restore / failover
Tier 2 — Important	e.g., accounting, print, secondary apps	≤ 24 hrs	≤ 24 hrs	Image or file-level restore
Tier 3 — Deferrable	Archives, reference systems	≤ 5 days	≤ 24 hrs	File-level restore after Tier 1–2

Disaster Scenarios and Strategies

Scenario	Primary Strategy
Single server failure	Restore image backup to replacement/loaner hardware or virtualize from backup
Site loss (fire/flood/storm)	Cloud restore of Tier 1 workloads; staff work remote on M365; replacement site per BCP
Ransomware	Execute Ransomware Playbook (BVT-IRP-046); restore from immutable/offsite backups after eradication
Extended internet outage	LTE/5G failover if equipped; relocate critical staff; vendor escalation via LOA (BVT-OPS-030)
Cloud tenant outage	Vendor status monitoring; execute manual workarounds in BCP; communicate ETA to staff

Declaration and Activation

- 1 Any authorized contact or BVTech may recommend declaration; Client's designated officer declares a disaster; BVTech activates this plan and assigns a Recovery Lead.
- 2 Establish the incident bridge (phone/Teams) and use the BCP communication tree.
- 3 Assess damage; select the scenario strategy; confirm target recovery point BEFORE restoring (avoid restoring compromised data).
- 4 Recover Tier 1 → validate with business owners → Tier 2 → Tier 3.
- 5 Document all actions and deviations for the post-recovery review.

Recovery Resources

Resource	Detail
Backup platform & credentials location	iDrive — credentials in vault (Restricted)
Backup encryption key location	Vault — WITHOUT THIS, RESTORES ARE IMPOSSIBLE
Hardware sources (loaner/vendor/warranty)	
ISP / DNS / registrar contacts	See Network Documentation (BVT-OPS-026)
Key vendor support numbers	

Testing

Minimum: quarterly file-restore test; semi-annual full-server or Tier 1 application recovery test; annual DR tabletop with the client. Record results, timing vs. RTO, and gaps; update the plan after every test and material environment change.