

Remote Access Policy

Secure remote work and remote administration (PR.AA, PR.IR)

Document ID: BVT-POL-037

Version: 1.0

Issued: July 02, 2026

Effective Date: _____

Purpose, Scope, and Authority

This policy is part of the BVTech Written Information Security Program, aligned to the NIST Cybersecurity Framework (CSF) 2.0. It applies to all BVTech LLC personnel, contractors, systems, and, where adopted by a client, the client's covered environment. The Managing Partner (or designated security officer) owns this policy, reviews it at least annually, and approves exceptions in writing. Violations may result in disciplinary action up to termination of employment or contract.

Exception process: submit written request describing the business need, compensating controls, and duration. Exceptions expire after 12 months unless renewed. NIST CSF 2.0 references shown per section (GV, ID, PR, DE, RS, RC).

Approved Methods

- Remote administration of client systems occurs only through the approved RMM platform or client-approved VPN with MFA — never via exposed RDP.
- RDP, SSH, and management interfaces must not be exposed directly to the internet; access is via VPN or vendor-secured gateway only.
- Staff remote work requires company-managed, encrypted, EDR-protected devices; public-computer access to business systems is prohibited.
- Remote sessions to client endpoints require user consent prompts where the tool supports it, except for unattended servers and after-hours maintenance authorized by contract.

Session Standards

- All remote sessions are logged (who, what device, when) via RMM audit trails.
- Idle timeout of 15 minutes on privileged consoles; automatic lock on staff devices at 10 minutes.
- Home/travel networks: VPN required on untrusted WiFi; hotspot preferred over open public WiFi.
- Third parties receive time-limited, scoped, named-account access only, with monitoring.

Prohibited

- Split-purpose personal use of remote admin tools; installing remote tools not on the approved list; storing client data locally beyond active-work needs; port-forwarding management ports on client firewalls.