

iDrive Backup — Deployment & Recovery Runbook

Backup deployment, monitoring, and restore procedures

Document ID: BVT-RUN-056

Version: 1.0

Issued: July 02, 2026

Effective Date: _____

Deployment Standard

- 1 Provision the client account/sub-account under the BVTech team console; document account, plan size, and renewal date in the PSA.
- 2 ENCRYPTION DECISION FIRST: enable private-key encryption at first setup (cannot be changed later without re-provisioning). Generate a strong key, store it in the vault as Restricted — iDrive cannot recover data without it.
- 3 Install the agent on covered servers/workstations via RMM; configure backup sets to the coverage standard in the Backup Policy (BVT-IRP-051): image-level for servers where contracted; user-data paths for workstations; application-aware settings for databases (VSS).
- 4 Schedule: nightly with continuous data protection for active file sets where appropriate; bandwidth throttling during business hours.
- 5 Enable local backup copy (iDrive local/hybrid) where hardware allows, satisfying the '2 media' leg of 3-2-1.
- 6 Verify the FIRST FULL BACKUP completes and perform a test restore of a sample file before marking onboarding complete.
- 7 Enable email alerts to the service desk alias; set retention/versioning per policy (30 versions default; deleted-file retention ON).

Monitoring

- Daily: review backup status dashboard/alert digest; ticket every failure; one business day to resolution, two consecutive failures escalate.
- Common failure causes to check in order: agent service stopped → VSS writer errors (restart writers/reboot window) → destination quota full → changed credentials → path no longer exists (data moved!) — a 'success' backing up the wrong path is still a failure; verify paths after any migration.
- Monthly: quota utilization review (alert at 80%); restore test per policy; confirm versioning/retention unchanged.

Restore Procedures

Scenario	Procedure
Single file / folder	Console or agent restore → restore to alternate path first → verify with user → move into place. Check version history for the correct point in time.
Deleted by user (past retention?)	Check deleted-file retention window; if outside, check secondary copies (local/image) before declaring unrecoverable
Full server (bare metal)	Prepare target hardware/VM → boot recovery media / install agent → image restore → driver injection if dissimilar hardware → verify services, test app, re-point DNS if IP changed → re-enable backups on restored server

Scenario	Procedure
Ransomware recovery	ONLY after eradication per BVT-IRP-046: choose restore point pre-dating dwell time; restore to isolated network first; scan before reconnecting
Physical shipment (large restores)	For multi-TB restores, request iDrive Express physical media shipment to beat bandwidth constraints; track chain of custody

Offboarding

Per BVT-OPS-025: offer final export or transfer of the account to the client/successor; document the agreed retention window for BVTech-held backup data (default 30 days post-termination), then delete and record destruction. Never delete backup data early during a billing dispute without written management approval.