

Name: Brian Sampson

Date: 10/30/2022

Pledge: I pledge my honor that I have abided by the Stevens Honor System.

- 1) Consider an array containing the following 40 integers:

5 2 4 4 0 1 6 7 3 1 1 0 5 1 5 4 4 5 7 0 6 1 0 7 5 2 7 6 5 3 7 0 5 5 7 1 1 2 6 5

How many counters does CountingSort need to sort this array: 7

Give the value of each counter after the array of counters has been fully initialized:

Counter 0: 5

Counter 1: 7

Counter 2: 3

Counter 3: 2

Counter 4: 4

Counter 5: 9

Counter 6: 4

Counter 7: 6

- 2) Consider an array containing the following 32 bit integers (written as hexadecimal values to save space):

4EC1EEA9

520B6E78

1E90D74E

52DB6E42

5F05EF13

74284442

794E8117

55526E42

Imagine you are using a version of RadixSort that sorts on one byte at a time (so two hexadecimal digits) using a stable version of CountingSort. Write the content of the array after each of the four runs of CountingSort:

5F05EF13, 794E8117, 55526E42, 52DB6E42, 74284442, 1E90D74E, 520B6E78, 4EC1EEA9  
 74284442, 52DB6E42, 55526E42, 520B6E78, 794E8117, 1E90D74E, 4EC1EEA9, 5F05EF13  
 5F05EF13, 520B6E78, 74284442, 794E8117, 55526E42, 1E90D74E, 4EC1EEA9, 52DB6E42  
 1E90D74E, 4EC1EEA9, 520B6E78, 52DB6E42, 55526E42, 5F05EF13, 74284442, 794E8117

