

Brigham Young University AUVSI Capstone Team (Team 45)

Autopilot Subsystem Summary

ID	Rev.	Date	Description	Author	Checked By
CT-004	0.1	02-27-	Initial concep-	John Akagi	Brady Moon
		2019	tion		
CT-004	0.2	02-27-	Section on	Brady Moon	John Akagi
		2019	path planning		



1 Introduction

This document summarizes the performance of the autopilot. Full test procedures and results are included later in the design review packet.

2 Autopilot Tuning

The underlying control algorithms being used involve a combination of PID, PI, and PD algorithms. Each of these require gains to be set so that the system is stable but also able to respond quickly to changes in the commanded attitude of the airplane. Additional gains are also needed to control the behavior of the airplane as it attempts to follow a defined path.

The gains were initially based on the gains from last year's plane and then tuned through in-flight testing. For tuning the longitudinal autopilot, the plane was initially commanded to fly straight. Varying altitudes and airspeeds were then commanded, and the longitudinal gains were adjusted so the transitions were smooth and controlled. The lateral gains were tuned by commanding the airplane to hold varying roll attitudes and making the transition smooth. Finally, the path follower gains were tuned by changing the desired course heading and adjusting the gains for smooth transitions.

3 Autopilot Testing

For testing the autopilot, sensor information was gathered using GPS and an inertial measurement unit. A heading and altitude were commanded and the airplane response was recorded. Overall, the airplane was able to stay within an acceptable bound of the commanded attitude.

Some problems were noted during testing with the altitude estimation. We are only using GPS data for that, so the values can jump around considerably since GPS is less accurate for altitude than it is for position. If the airplane receives an incorrect altitude estimation it could cause a catastrophic crash. In order to obtain better altitude estimates, we plan to integrate additional sensors such as a barometer.



4 Path Planning Testing

We tested the path planning algorithms for robustness and efficacy. This was done in simulation with 5 different random maps. Each map had 5 waypoints and 10 obstacles which were placed randomly. A path was planned to hit all waypoints and then a simulated plane, based on our actual design, attempted to fly the path. The closest approach to each waypoint and obstacle were calculated. After running all the simulations, we evaluated the success of the mission based on our key success measures. There were some mistakes in the simulations, but overall the results fall in the excellent category as defined by the key success measures. We will be analyzing the reasons for the failures in the tests, and then fix them in the refinement process.

5 Conclusion

We have been able to test and verify the autopilot gains and the path planning algorithm. Additional work is still required in order to obtain a better altitude estimation and to make the path planning algorithm more consistent.