



AIAA Design/Build/Fly Competition
2020-2021 Aircraft Design Report

Brigham Young University Aeronautics Club
2021 AIAA Design Build Fly Competition Design Report

Contents

1	Executive Summary	3
2	Management Summary	4
2.1	Team Organization	4
2.2	Schedule	4
3	Conceptual Design	5
3.1	Mission Requirements	5
3.2	Sub-system Design Requirements	5
3.3	Scoring Sensitivity Analysis	6
3.4	Concept Review, Weighting, and Selection Process	7
4	Preliminary Design	11
4.1	Methodology	11
4.2	Trade Studies	13
4.3	Estimated Aircraft Performance	15
5	Detail Design	17
5.1	Dimensional Parameters	17
5.2	Structural Characteristics and Capabilities	17
5.3	Systems and Sub-system Selection, Integration, and Architecture	17
5.4	Weights and Balance	18
5.5	Flight Performance Parameters	18
5.6	Mission Performance	19
5.7	Drawing Package	19
6	Manufacturing Plan	24
6.1	Process Investigation and Selection	24
6.2	Manufacturing Milestones	28
7	Testing Plan	28
7.1	Completed Testing	28
7.2	Planned Testing	32
7.3	Test and Flight Checklists	32
8	Performance Results	32
8.1	Key Subsystem Demonstrated Performance Comparison	32
8.2	Complete Aircraft Demonstrated Performance Comparison	32
8.3	Complete Aircraft Improvements After Flight Testing	32



I Executive Summary

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



II Management Summary

II.A Team Organization

Figure 1 depicts the overall organization of our team structure. Each of the teams is lead by an individual who answers to the Engineering Lead and Project Manager. The skills required for each position/team are as follows.

Engineering Lead As with the team leads, the Engineering Lead primarily requires good decision making and leadership skills, qualities the BYU Aero Club seeks to develop in all of its members. In addition the Engineering Lead has a well rounded understanding of the various systems and both design and testing expertise.

Project Manager The Project Manager has excellent organizational skills and oversees the logistical side of the project: heading up report writing, budgeting tasks, scheduling, etc.

Aerodynamics The Aerodynamics team members have expertise in aerodynamic analysis and testing, including skills in hand calculations, computational analysis tools, wind tunnel and glide testing.

Structures The Structures team members focus on skills in structural analysis and testing, employing hand calculations, computational tools, and various structural testing methods.

Propulsion The Propulsion team focuses on analyzing and testing the propulsion system effectiveness and efficiency, but also has skills in electronics related to the propulsion system.

Systems The Systems team works very closely with the Engineering Lead, as they oversee all systems interfacing, avionics, etc. There is a sub-group of the Systems team that is assigned to work on the mission specific payload and related components, as well as related testing.

Manufacturing The Manufacturing team oversees the manufacturing of all prototypes and testing apparatus.

Graphics The Graphics team has skills in CAD design as well as graphical marketing for the team.

II.B Schedule




Figure 2 This milestone chart reveals our original plan for major elements of our design process compared to the actual timing of these events. Note that we submitted the proposal on time, as well as this report. We anticipate remaining on schedule for the future elements of this chart.

Figure 2 depicts our planned vs. actual timeline for the year. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

III Conceptual Design

III.A Mission Requirements

The mission requirements for this year's competition are as follows:

III.A.1 Airframe and Operational Constraints:

- Safety Requirements:
 - [THIS YEAR'S REQUIREMENT(S).]
- Airframe Requirements:
 - [THIS YEAR'S REQUIREMENT(S).]
- Payload Requirements:
 - [THIS YEAR'S REQUIREMENT(S).]
- [THIS YEAR'S SPECIAL REQUIREMENT(S)]:
 - [THIS YEAR'S REQUIREMENT(S).]

III.A.2 Flight Mission Scoring:

Flight Mission 1:

Flight Mission 2:

Flight Mission 3:

III.A.3 Total Score Summary:

$$TS = M_1 + M_2 + M_3 + GM + DR$$

where TS is total score, M_i is the score associated with the mission number subscript, GM is the ground mission score, and DR is the design report score.




Figure 3 This plot breaks down the estimated lengths of the course based on the scale drawing from the mission requirements.

III.B Sub-system Design Requirements

We have organized our sub-system requirements into aerodynamics, structure, propulsion, and specialty requirements explained below.



III.B.1 Aerodynamics Requirements

Some of the major requirements for the aerodynamics sub-system are: Maximize aerodynamic efficiency in order to use less energy to overcome drag for all flight missions. Design wing loading to be able to take off and fly with design max payload weight. Keep the wingspan within the maximum of [MAX SPAN CONSTRAINT THIS YEAR]. Choose airfoil(s) and configuration that will make take off feasible in the [THIS YEAR'S TAKE-OFF REQUIREMENT]

III.B.2 Structural Requirements

The breakdown of mission requirements for the structures sub-system include: Minimize the structural weight while maintaining sufficient rigidity to keep the aerodynamics as designed, especially when full payload weight is in use. Make sure the structure is sufficiently rigid to avoid aerodynamic flutter within the flight envelope. [OTHER MISC. STRUCTURES REQUIREMENTS THIS YEAR (E.G. FOLDING WINGS.)]

III.B.3 Propulsion Requirements

The propulsion sub-system requirements are to: Have sufficient system efficiency and battery capacity to enable completion of the flight missions and maximizing speed with sufficient endurance while also providing sufficient thrust for [THIS YEAR'S TAKE-OFF REQUIREMENT]

III.B.4 Specialty Requirements

[REQUIREMENTS FOR THIS YEAR'S SPECIAL STUFF.] Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

III.C Scoring Sensitivity Analysis




Figure 4 This plot shows the effects of those design parameters that directly affect the increase/decrease in mission scoring beyond simple completion.

For our sensitivity study, we first differentiated between design variables that could increase/decrease our score and those that were only related to the minimum constraints. Furthermore, some aspects of the score are insensitive by design parameters, such as the design report score, the ground mission score, and the Flight Mission 1 score. Our total, design-sensitive score is simply the sum of scores from Flight Mission 2 and 3.



[BREAKDOWN OF THE MATHS USED TO PERFORM THE SENSITIVITY STUDY.]

In order to normalize the scores as they are in the competition, we ran the analysis first without normalization, from which we saved the maximum scores like they are in competition. We then used those maxima as the normalization factors and re-ran the analysis. This way we could simulate the competition normalizations for the scoring and one mission would not dominate another unrealistically.

In our analysis (results shown in figure 4), we found that the wing area and parasitic drag coefficient induced negative sensitivities, thus we want to minimize drag and maximize wing loading (while still being able to take off). The available power was also important, and can be affected by increasing battery capacity, discharge rate, or voltage, or increasing propulsive efficiency. [TAKE AWAYS FROM PAYLOAD STUFF]. We should also note that the aircraft weight had the lowest effect on the overall sensitivity, but is incredibly important to meeting the fixed constraints of the competition.

III.D Concept Review, Weighting, and Selection Process

Informed by our sensitivity study, table 1 shows our general figures of merit for our conceptual design choices. In addition to the primary mission sensitive parameters, we added some practical figures of merit as well. In addition, rather than having multiple figures of the same value, we chose to make each figure a distinct value, thereby requiring a true prioritization and less change of ambiguity during the selection process.

We chose weight as the most important factor because it not only relates to the mission objectives, but also concerns the take-off/landing constraints. Drag was our next highest factor, as speed is important for maximizing flight mission scores. We placed simplicity next, as we must be able to actually produce our chosen design with our current and realistic potential abilities. We found stability to be important as well, since our aircraft needs to be controllable if we are to compete, but stability is relatively easy to achieve for most designs, so it was given a relatively lower value to match. Finally [TALK ABOUT THE YEAR SPECIFIC METRIC IF THERE IS ONE.] Each of the decision matrices has additional figures of merit associated with sub-system specific requirements. Note also, that parameters associated with available power were not included in the general list of figures of merit, but are included in propulsion specific decision matrices.

Table 1 Figures of Merit

Factor	Scale (1-5)
Weight	10
Drag	8
Simplicity	6
Stability	4
[YEAR SPECIFIC ITEM]	2

III.D.1 Wing Configuration Selection

For our wing configuration, we needed to take overall potential lift into account, due to the take-off/landing requirements. Table 2 shows our scoring for single wing, tandem wing, and bi/tri-wing configurations. Note that we eliminated flying wing/blended wing body configurations up front based on our previous experience with that concept.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



Table 2 Weighted decision matrix for wing configuration.

Factor	Scale	Single Wing	Tandem Wing	Bi/Tri-wing
Weight	10	3	2	1
Drag	8	3	2	1
Simplicity	6	3	1	2
Lift	5	2	2	3
Stability	4	3	2	3
[YEAR SPECIFIC ITEM]	2			
Totals				

III.D.2 Wing Placement Selection

For the wing placement, we compared high, mid, and low wing placement. An addition figure of merit here is the accessibility, that is, the accessibility of the payload and electronics. This is important not only for the ground mission, but also for setting up the aircraft for flight.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Table 3 Weighted decision matrix for wing placement.

Factor	Scale	High Wing	Mid Wing	Low Wing
Weight	10	3	2	3
Drag	8	2	3	2
Simplicity	6	3	1	2
Accessibility	5	1	2	3
Stability	4	3	2	1
[YEAR SPECIFIC ITEM]	2			
Totals				

III.D.3 Empennage Configuration Selection

For the tail configuration selection, we did not see the need for any further figures of merit. We compared three families of configuration: T-tail family, including conventional, cruciform, and T-tail designs; V-tail family, including V- and inverted V-tail designs; and H-tail family, including U-, H-, and inverted U-tail designs.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Table 4 Weighted decision matrix for tail configuration.

Factor	Scale	T-Tail Variations		V-Tail Variations		H-Tail Variations	
Weight	10	2	3			1	
Drag	8	2	3			2	
Simplicity	6	3	2			1	
Stability	4	2	1			3	
[YEAR SPECIFIC ITEM]	2						
Totals							

III.D.4 Propulsion Configuration Selection

For the propulsion configuration, drag did not make sense as a figure of merit, since the system is in direct opposition to drag. Therefore we exchanged drag for efficiency, since efficiency directly affects available power (which we found to be important in section 3.3). We also included lift as a figure of merit for the propulsion system, because blown wing configurations can experience increased lift (due to higher induced velocities over the wing).

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Table 5 Weighted decision matrix for propulsion configuration.

Factor	Scale	Single Prop		Dual Prop		Distributed Prop	
Weight	10	3	2	2	1		
Propulsive Efficiency	8	1	2	2	3		
Lift	7	1	2	2	3		
Simplicity	6	3	2	2	1		
Stability	4	3	2	2	3		
[YEAR SPECIFIC ITEM]	2						
Totals							



III.D.5 Propulsion Placement Selection

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Table 6 Weighted decision matrix for propulsion placement.

Factor	Scale	Pull Variations	Push Variations	Combinations
Weight	10	3	3	3
Lift	4	3	1	2
Simplicity	6	3	2	1
Propulsive Efficiency	4	3	1	2
[YEAR SPECIFIC ITEM]	2			
Totals				

III.D.6 Payload

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Table 7 Weighted decision matrix for [SPECIFY THIS YEAR'S PAYLOAD DESIGN].

Factor	Scale	[OPTION]	[OPTION]	[OPTION]
		<i>Figure Placeholder</i> Aspect ratio = 4:3	<i>Figure Placeholder</i> Aspect ratio = 4:3	<i>Figure Placeholder</i> Aspect ratio = 4:3
Weight	10			
Strength	8			
Simplicity	6			
Durability	4			
[YEAR SPECIFIC ITEM]	2			
Totals				

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant



morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

III.D.7 Final Concept

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.




Figure 5 Drawings and rendering of our conceptual aircraft design.

IV Preliminary Design

IV.A Methodology

IV.A.1 Quantify Basic Constraints

The sensitivity study presented in section 3.3 did not include any constraints, but rather simple sensitivities that informed our conceptual design choices. To begin a preliminary design, we first needed to translate the given constraints (listed in section 3.2) into mathematical formulas for rapid comparison and trade studies. Aside from the obvious constraints (such as the wing span constraint), we determined the following to be important expressions.



Figure Placeholder

Aspect ratio = 4:3

Figure 6 Preliminary design process flow chart.

Stall Speed

$$V_{\text{stall}} = \left[\frac{2W}{\rho S_{\text{ref}} C_{L_{\max}}} \right]^{1/2}$$

Where V_{stall} is the stall speed, W is the total aircraft weight, ρ is the ambient air density, S_{ref} is the reference wing area, and $C_{L_{\max}}$ is the maximum aircraft lift coefficient.

Take-off Distance

$$d_{LO} = \frac{W^{5/2}}{(\rho S_{\text{ref}} C_{L_{\max}})^{3/2} P_{\text{net}}}$$

Where d_{LO} is the distance to lift-off, P_{net} is the net power, that is, the power accounting for both thrust and drag, and the other variables are as defined previously.

Maximum Speed

$$V_{\max} = \left[\frac{\frac{T_a}{S_{\text{ref}}} + \frac{W}{S_{\text{ref}}} \sqrt{\left(\frac{T_a}{W} \right)^2 - 4C_{D_0}K}}{\rho C_{D_0}} \right]^{1/2}$$

Where V_{\max} is the maximum velocity, T_a is the available thrust, C_{D_0} is the zero-lift drag coefficient of the aircraft, and K is an empirical constant assumed here to be 0.38.

Maximum Range

$$R = \frac{e_b}{g} \eta \frac{L}{D} \frac{m_b}{m_{\text{tot}}}$$

Where R is the total range; e_b is the battery energy per unit mass; g is the gravitational constant; η is the combination of efficiency factors from the battery, motor, and propeller ($\eta = \eta_b \eta_m \eta_p$); L/D is the aircraft lift to drag ratio, and m_b/m_{tot} is ratio of the battery mass to total aircraft mass.

C_L for Maximum Efficiency (and Range)

$$C_{L_{\max \text{ L/D}}} = [C_{D_p} \pi S_{\text{ref}} Re]^{1/2}$$

Where C_{D_p} is the parasitic drag coefficient for the aircraft, Re is the Reynolds number, and other variables are defined previously.

Climb Rate

$$v_z = \frac{V_{\infty} (T - D)}{W}$$

Where v_z is the vertical climb rate, V_{∞} is the flight velocity of the aircraft, T is the thrust force magnitude, and D is the drag force magnitude.



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



Coordinated Turn Radius

$$r_{\text{turn}} = \frac{V^2}{g \tan \phi}$$

Where r_{turn} is the turn radius, V is the aircraft speed, and ϕ is the bank angle of the aircraft.

Coordinated Turn Load Factor

$$n = \frac{1}{\cos \phi}$$

Where n is the load factor.

IV.A.2 Analysis Models

Weight Estimation

Propulsion Model

Vortex Lattice Method (XFLR5, AVL, or VLM.jl)

Structures Stuff (Beams, composites, etc.)

Code

IV.B Trade Studies

maximize : $M2 + M3$

with respect to : $W, S_{\text{ref}}, C_{D_0}, [\text{PAYLOAD STUFF}], P_a$ (1)

subject to : $V_{\text{stall}}, V_{\text{maneuver}}, d_{LO}, R, r_{\text{turn}}$

where V_{maneuver} is the maximum velocity boundary associated with structural failure due to maneuver acceleration.

IV.B.1 Wing/Tail Design




Figure 7 Airfoil geometry comparison.

Airfoil(s)

Sizing

IV.B.2 Propulsion

IV.B.3 Fuselage

IV.B.4 Payload

IV.B.5 [OTHER TRADE STUDIES TO FIND THE ANSWER TO THE OPTIMIZATION PROBLEM.]



Figure Placeholder

Aspect ratio = 4:3

Figure Placeholder

Aspect ratio = 4:3

a) c_{ℓ} vs α

b) c_{ℓ} vs c_d

Figure 8 Airfoil Polar comparison.

Table 8 Preliminary wing and tail sizes.

Parameter	Wing	Vertical Tail	Horizontal Tail
Span (ft)			
Root Chord (ft)			
Tip Chord (ft)			
Wing Area (ft^2)			
Aspect Ratio			

Figure Placeholder

Aspect ratio = 2:1

Figure 9 Lift distribution at cruise for each mission.

Table 9 Preliminary propulsion system comparison.

Motor	Kv	Battery	Current (Amps)	Propeller	Static Thrust (lbs)	Total Weight (lbs)



Figure Placeholder

Aspect ratio = 4:3

Figure 10 Efficiency curves for the motor and propeller selection.

IV.C Estimated Aircraft Performance

IV.C.1 Performance Prediction Methodologies and Uncertainties

IV.C.2 Lift and Drag

Table 10 Estimated total lift and drag values.

Parameter	Mission 1	Mission 2	Mission 3
$C_{L_{\max}}$			
$C_{L_{\text{avg}}}$			
C_{D_0}			
L/D_{cruise}			
Efficiency Factor (e)			

Lift Analysis

Figure Placeholder

Aspect ratio = 2:1

Figure 11 Drag breakdown for each mission

Drag Analysis

IV.C.3 Stability



Figure Placeholder

Aspect ratio = 2:1

Figure 12 Moment coefficient vs α

Table 11 Stability derivatives for Flight Mission 1.

	Angle of Attack	V_{TO}/V_C	Side Slip Angle	V_{TO}/V_C	Roll Rate	V_{TO}/V_C	Pitch Rate	V_{TO}/V_C	Yaw rate	V_{TO}/V_C
Lift Force	$C_{L\alpha}$	0.0000/0.0000	$C_{L\beta}$	0.0000/0.0000	C_{Lp}	0.0000/0.0000	C_{Lq}	0.0000/0.0000	C_{Lr}	0.0000/0.0000
Drag Force	$C_{D\alpha}$	0.0000/0.0000	$C_{D\beta}$	0.0000/0.0000	C_{Dp}	0.0000/0.0000	C_{Dq}	0.0000/0.0000	C_{Dr}	0.0000/0.0000
Lateral Force	$C_{Y\alpha}$	0.0000/0.0000	$C_{Y\beta}$	0.0000/0.0000	C_{Yp}	0.0000/0.0000	C_{Yq}	0.0000/0.0000	C_{Yr}	0.0000/0.0000
Rolling Moment	$C_{\ell\alpha}$	0.0000/0.0000	$C_{\ell\beta}$	0.0000/0.0000	$C_{\ell p}$	0.0000/0.0000	$C_{\ell q}$	0.0000/0.0000	$C_{\ell r}$	0.0000/0.0000
Pitching Moment	$C_{m\alpha}$	0.0000/0.0000	$C_{m\beta}$	0.0000/0.0000	C_{mp}	0.0000/0.0000	C_{mq}	0.0000/0.0000	C_{mr}	0.0000/0.0000
Yawing Moment	$C_{n\alpha}$	0.0000/0.0000	$C_{n\beta}$	0.0000/0.0000	C_{np}	0.0000/0.0000	C_{nq}	0.0000/0.0000	C_{nr}	0.0000/0.0000

Table 12 Stability derivatives for Flight Mission 2.

	Angle of Attack	V_{TO}/V_C	Side Slip Angle	V_{TO}/V_C	Roll Rate	V_{TO}/V_C	Pitch Rate	V_{TO}/V_C	Yaw rate	V_{TO}/V_C
Lift Force	$C_{L\alpha}$	0.0000/0.0000	$C_{L\beta}$	0.0000/0.0000	C_{Lp}	0.0000/0.0000	C_{Lq}	0.0000/0.0000	C_{Lr}	0.0000/0.0000
Drag Force	$C_{D\alpha}$	0.0000/0.0000	$C_{D\beta}$	0.0000/0.0000	C_{Dp}	0.0000/0.0000	C_{Dq}	0.0000/0.0000	C_{Dr}	0.0000/0.0000
Lateral Force	$C_{Y\alpha}$	0.0000/0.0000	$C_{Y\beta}$	0.0000/0.0000	C_{Yp}	0.0000/0.0000	C_{Yq}	0.0000/0.0000	C_{Yr}	0.0000/0.0000
Rolling Moment	$C_{\ell\alpha}$	0.0000/0.0000	$C_{\ell\beta}$	0.0000/0.0000	$C_{\ell p}$	0.0000/0.0000	$C_{\ell q}$	0.0000/0.0000	$C_{\ell r}$	0.0000/0.0000
Pitching Moment	$C_{m\alpha}$	0.0000/0.0000	$C_{m\beta}$	0.0000/0.0000	C_{mp}	0.0000/0.0000	C_{mq}	0.0000/0.0000	C_{mr}	0.0000/0.0000
Yawing Moment	$C_{n\alpha}$	0.0000/0.0000	$C_{n\beta}$	0.0000/0.0000	C_{np}	0.0000/0.0000	C_{nq}	0.0000/0.0000	C_{nr}	0.0000/0.0000



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



Table 13 Stability derivatives for Flight Mission 3.

	Angle of Attack	V_{TO}/V_C	Side Slip Angle	V_{TO}/V_C	Roll Rate	V_{TO}/V_C	Pitch Rate	V_{TO}/V_C	Yaw rate	V_{TO}/V_C
Lift Force	C_{L_α}	0.0000/0.0000	C_{L_β}	0.0000/0.0000	C_{L_p}	0.0000/0.0000	C_{L_q}	0.0000/0.0000	C_{L_r}	0.0000/0.0000
Drag Force	C_{D_α}	0.0000/0.0000	C_{D_β}	0.0000/0.0000	C_{D_p}	0.0000/0.0000	C_{D_q}	0.0000/0.0000	C_{D_r}	0.0000/0.0000
Lateral Force	C_{Y_α}	0.0000/0.0000	C_{Y_β}	0.0000/0.0000	C_{Y_p}	0.0000/0.0000	C_{Y_q}	0.0000/0.0000	C_{Y_r}	0.0000/0.0000
Rolling Moment	C_{ℓ_α}	0.0000/0.0000	C_{ℓ_β}	0.0000/0.0000	C_{ℓ_p}	0.0000/0.0000	C_{ℓ_q}	0.0000/0.0000	C_{ℓ_r}	0.0000/0.0000
Pitching Moment	C_{m_α}	0.0000/0.0000	C_{m_β}	0.0000/0.0000	C_{m_p}	0.0000/0.0000	C_{m_q}	0.0000/0.0000	C_{m_r}	0.0000/0.0000
Yawing Moment	C_{n_α}	0.0000/0.0000	C_{n_β}	0.0000/0.0000	C_{n_p}	0.0000/0.0000	C_{n_q}	0.0000/0.0000	C_{n_r}	0.0000/0.0000

Table 14 Dynamic stability characteristics.

Lon. Modes	Mode	Eigenvalue			Damping Ratio			Undamped Frequency (Hz)		
		M1	M2	M3	M1	M2	M3	M1	M2	M3
	Short Period (I)	-0.0 ± 0.0 <i>i</i>	-0.0 ± 0.0 <i>i</i>	-0.0 ± 0.0 <i>i</i>	0.0	0.0	0.0	0.0	0.0	0.0
	Phugoid (II)	-0.0 ± 0.0 <i>i</i>	-0.0 ± 0.0 <i>i</i>	-0.0 ± 0.0 <i>i</i>	0.0	0.0	0.0	0.0	0.0	0.0
Lat. Modes	Dutch Roll (III)	-0.0 ± 0.0 <i>i</i>	-0.0 ± 0.0 <i>i</i>	-0.0 ± 0.0 <i>i</i>	0.0	0.0	0.0	0.0	0.0	0.0
	Roll (IV)	-0.0 ± 0.0 <i>i</i>	-0.0 ± 0.0 <i>i</i>	-0.0 ± 0.0 <i>i</i>	0.0	0.0	0.0	0.0	0.0	0.0
	Spiral (V)	-0.0 ± 0.0 <i>i</i>	-0.0 ± 0.0 <i>i</i>	-0.0 ± 0.0 <i>i</i>	0.0	0.0	0.0	0.0	0.0	0.0

IV.C.4 Mission Performance

Table 15 Estimated Mission Performance.

Parameter	Mission 1	Mission 2	Mission 3
Total Weight (lbs)			
Wing Loading (lbs/ft ²)			
V_C (ft/s)			
V_{TO} (ft/s)			
Payload			
[YEAR SPECIFIC ITEM]			
Raw Mission Score			

V Detail Design

V.A Dimensional Parameters

V.B Structural Characteristics and Capabilities

V.C Systems and Sub-system Selection, Integration, and Architecture



Figure Placeholder

Aspect ratio = 4:3

Figure 13 Root-locus plot for stability modes.

Table 16 Dimensional Parameters.

(a) Main Wing		(b) Horizontal Tail		(c) Vertical Tail	
Parameter	Value (units)	Parameter	Value (units)	Parameter	Value (units)
Airfoils	abc	Airfoil	abc	Airfoil	abc
Span	0.0 (ft)	Span	0.0 (ft)	Span	0.0 (ft)
Root Chord	0.0 (ft)	Root Chord	0.0 (ft)	Root Chord	0.0 (ft)
Tip Chord	0.0 (ft)	Tip Chord	0.0 (ft)	Tip Chord	0.0 (ft)
Aspect Ratio	0.0	Aspect Ratio	0.0	Aspect Ratio	0.0
Dihedral	0.0 (°)	Volume Ratio	0.0	Volume Ratio	0.0
Incidence Angle	0.0 (°)	Incidence Angle	0.0 (°)	Rudder Chord	0.0 (ft)
Flap Chord	0.0 (ft)	Elevator Chord	0.0 (ft)	Rudder Span	0.0 (ft)
Flap Span	0.0 (ft)	Elevator Span	0.0 (ft)		
Aileron Chord	0.0 (ft)				
Aileron Span	0.0 (ft)				
(d) Fuselage		(e) Propulsion		(f) Controls	
Parameter	Value (units)	Parameter	Value (units)	Parameter	Value (units)
Total Length	0.0 (ft)	Motor	abc	Transmitter	abc
Nose Length	0.0 (ft)	Kv	0.0 (RPM/V)	Receiver	abc
Tail Length	0.0 (ft)	Power Rating	0.0 (W)	Servos	abc
Width	0.0 (ft)	No-Load Current	0.0 (A)	Flight Controller	abc
Height	0.0 (ft)	Internal Resistance	0.0 (Ω)		
		Propeller	abc 0×0		

V.D Weights and Balance

V.E Flight Performance Parameters



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



V.F Mission Performance

V.G Drawing Package

The following are drawings including a 3-View drawing with dimensions of all configurations, a structural arrangement drawing, a systems layout/location drawing, and payload accommodation drawings.

Figure Placeholder

Figure Placeholder

Figure Placeholder

Figure Placeholder



Figure Placeholder

Figure 14 V-n diagram for our aircraft design.

Figure Placeholder

Figure 15 Schematic of electrical/avionics systems.

VI Manufacturing Plan

VIA Process Investigation and Selection

Table 20 shows our figures of merit for our manufacturing technique decision matrices. Note that we prioritized in a similar fashion to our design figures with some changes to more applicable figures. First, again, is weight. The lower the aircraft weight, the more points can be had through [YEAR SPECIFIC ITEM]. After weight, we prioritized strength, as our structures need to be able to carry the loads required. Third is simplicity; we need to be able to actually manufacture something with a given technique. Note that simplicity is relative to our team's expertise at the time of our decisions and feasible future abilities within the time frame of the competition. We next chose to include durability. It is not very high on our list since we would hope to be able to design an aircraft that has no unscheduled landings, however, one cannot predict the future enough to know whether or not durability will be required, and experience shows that it most likely will. Finally, [TALK ABOUT THE YEAR SPECIFIC METRIC IF THERE IS ONE.] Because many of these factors depend on intelligent design (e.g. a built-up balsa wing could be heavier than a foam core wing, depending on how it is designed), as well as manufacturer skill, we did some prototyping and testing of representative models before completing our decision factor calculations.



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



Table 17 Weight and Balance table including empty aircraft and each possible configuration. Note that the datum point of the aircraft is the center of the leading edge of the main wing.

		C.G. Location (ft)			
	Component	Weight (lbs)	X	Y	Z
Empty Airframe	Fuselage	0.0	0.0	0.0	0.0
	Wing	0.0	0.0	0.0	0.0
	H. Tail	0.0	0.0	0.0	0.0
	V. Tail	0.0	0.0	0.0	0.0
	Landing Gear	0.0	0.0	0.0	0.0
	Motor	0.0	0.0	0.0	0.0
	Total	0.0	0.0	0.0	0.0
Mission 1 Additions	Component	0.0	0.0	0.0	0.0
	Component	0.0	0.0	0.0	0.0
	Component	0.0	0.0	0.0	0.0
	Total	0.0	0.0	0.0	0.0
Mission 2 Additions	Component	0.0	0.0	0.0	0.0
	Component	0.0	0.0	0.0	0.0
	Component	0.0	0.0	0.0	0.0
	Total	0.0	0.0	0.0	0.0
Mission 3 Additions	Component	0.0	0.0	0.0	0.0
	Component	0.0	0.0	0.0	0.0
	Total	0.0	0.0	0.0	0.0

Table 18 Expected Flight Performance parameters for each mission.

Parameter	Mission 1	Mission 2	Mission 3
$C_{L_{\max}}$			
$C_{L_{\text{avg}}}$			
C_{D_0}			
L/D_{cruise}			
efficiency factor (e)			
V_{TO}			
V_C			
Total Weight (lbs)			
Wing Loading (lbs/ft ²)			
Takeoff Length (ft)			
Climb Rate (ft/s)			
Max Range (ft)			
Max Endurance (minutes)			

Table 19 Expected Mission Performance.

Parameter	Mission 1	Mission 2	Mission 3
Payload			
[YEAR SPECIFIC ITEM]			
Raw Mission Score			



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



Table 20 Figures of Merit

Factor	Relative Importance (1-5)
Weight	10
Strength	8
Simplicity	6
Durability	4
[YEAR SPECIFIC ITEM]	2

VI.A.1 Wing Manufacturing Process Selection

Table 21 Weighted decision matrix for wing manufacturing technique. Factors here come from our initial testing of balsa and fiber reinforced polymer (FRP) techniques.

Factor	Foam Core FRP	Hollow Core FRP	Built-up/Balsa
	Scale		
Weight	10		
Strength	8		
Simplicity	6		
Durability	4		
[YEAR SPECIFIC ITEM]	2		
Totals			

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

VI.A.2 Empennage Manufacturing Process Selection

Table 22 Weighted decision matrix for tail manufacturing technique.

Factor	Foam Core FRP	Hollow Core FRP	Built-up/Balsa
	Scale		
Weight	10		
Strength	8		
Simplicity	6		
Durability	4		
[YEAR SPECIFIC ITEM]	2		
Totals			



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

VI.A.3 Fuselage Manufacturing Process Selection

Table 23 Weighted decision matrix for fuselage manufacturing technique.

Factor	Scale	3D Printing	Hollow Core FRP	Built-up/Balsa
Weight	10			
Strength	8			
Simplicity	6			
Durability	4			
[YEAR SPECIFIC ITEM]	2			
Totals				

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

VI.A.4 Payload Manufacturing Process Selection

Table 24 Weighted decision matrix for [SPECIFY THIS YEAR'S PAYLOAD DESIGN].

Factor	Scale	[OPTION]	[OPTION]	[OPTION]
Weight	10	<i>Figure Placeholder</i> Aspect ratio = 4:3	<i>Figure Placeholder</i> Aspect ratio = 4:3	<i>Figure Placeholder</i> Aspect ratio = 4:3
Strength	8			
Simplicity	6			
Durability	4			
[YEAR SPECIFIC ITEM]	2			
Totals				

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

VI.B Manufacturing Milestones




Figure 16 This milestone chart reveals our original plan for major elements of our manufacturing process compared to the actual timing of these events for our detailed prototype, we hope to hold to a similar planned schedule for our competition build.

VII Testing Plan




Figure 17 This milestone chart reveals our original plan for major elements of our testing process compared to the actual timing of these events. We anticipate remaining on schedule for the future elements of this chart.

VII.A Completed Testing

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus



vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

VII.A.1 Ground Testing

Aerodynamic Testing

Structural Testing

Propulsion Testing

Systems Testing Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur. Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim




Figure 18 example figure. will need several throughout the testing section

elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetuer at, consectetuer sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetuer a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetuer. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus.

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetur odio sem sed wisi.



VII.A.2 Flight Testing

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis duí, et vehicula libero duí cursus duí. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas duí, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut duí. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc duí lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetur at, consectetur sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst.



Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetur a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetur. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus.

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetur odio sem sed wisi.

VII.B Planned Testing

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

VII.C Test and Flight Checklists

VIII Performance Results

VIII.A Key Subsystem Demonstrated Performance Comparison

VIII.A.1 Subsystem Improvements After Testing

VIII.B Complete Aircraft Demonstrated Performance Comparison

VIII.C Complete Aircraft Improvements After Flight Testing



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



Table 25 Pre-flight Inspection Checklist

Component	Task
Propulsion	<input type="checkbox"/> Propeller is balanced and free of visible damage
	<input type="checkbox"/> Propeller is securely fastened to motor shaft
	<input type="checkbox"/> Motor is free of visible damage and rotates smoothly
	<input type="checkbox"/> Motor is securely fastened to airframe
	<input type="checkbox"/> Wired connections are undamaged, unexposed, and fit securely
	<input type="checkbox"/> Safety fuse/arm switch are undamaged, secured, and fully functional
	<input type="checkbox"/> ESC is functional and properly connected
	<input type="checkbox"/> Battery is fully charged and properly shaped (not puffy)
Fuselage	<input type="checkbox"/> Internal components are secure and fuselage is free of debris
	<input type="checkbox"/> Landing gear is securely attached and functional
	<input type="checkbox"/> Fuselage is free of damage at all attachment locations
	<input type="checkbox"/> All component wiring/connections are correct and secure
Wing & Tail	<input type="checkbox"/> Wing and tail surfaces are damage free
	<input type="checkbox"/> Control linkages are secure with minimal play
	<input type="checkbox"/> Control surfaces are secure and move smoothly and freely
	<input type="checkbox"/> Wing and tail are securely mounted to fuselage
	<input type="checkbox"/> Wing and tail attachment points are without damage
Controls	<input type="checkbox"/> Transmitter arm/disarm switches are functional
	<input type="checkbox"/> Receiver and flight controller are connected, secured, and functioning
	<input type="checkbox"/> Control surfaces appropriately respond to control inputs
	<input type="checkbox"/> Pilot is aware of control mixes and levels
	<input type="checkbox"/> Throttle appropriately responds based on arm/disarm settings

Table 26 Final Flight Test Checklist

Stage	Task
Pre-flight	<input type="checkbox"/> Task
	<input type="checkbox"/> Task
Mid-flight	<input type="checkbox"/> Task
	<input type="checkbox"/> Task
Post-flight	<input type="checkbox"/> Task
	<input type="checkbox"/> Task



Brigham Young University Aeronautics Club

2021 AIAA Design Build Fly Competition Design Report



Table 27 Example subsystem performance table.

Parameter	Mission 1		Mission 2		Mission 3	
	Expected	Measured	Expected	Measured	Expected	Measured
Parameter						
Parameter						
Parameter						
Parameter						

Table 28 Expected Flight Performance parameters for each mission.

Parameter	Mission 1		Mission 2		Mission 3	
	Expected	Measured	Expected	Measured	Expected	Measured
$C_{L_{\max}}$						
$C_{L_{avg}}$						
C_{D_0}						
L/D_{cruise}						
efficiency factor (ϵ)						
V_{TO}						
V_C						
Total Weight (lbs)						
Wing Loading (lbs/ft ²)						
Takeoff Length (ft)						
Climb Rate (ft/s)						
Max Range (ft)						
Max Endurance (minutes)						
Payload						
Score						