

## Week-1

### Session-1

a) Log into the system

**Sol:** \$ login: <user name>

\$ password: \*\*\*\*\*

b) Use vi editor to create a file called myfile.txt which contains some text.

**Sol:** \$ vi myfile.txt

**[Press i to go in insert mode]**

~ Unix is Case Sensitive

~ Never leave the Computer without logging out when you are working in a time sharing or network environments.

Press <Esc>

: wq <ENTER>

c) correct typing errors during creation.

**Sol:** \$ vi myfile.txt

**[Press i to go in insert mode]**

~ unix is Case Sensitive

Press<Esc>

: wq <ENTER>

d) Save the file

Press<Esc>

: wq <ENTER>

e) logout of the system

**Sol:** \$exit

## Session 2

a) Log into the system

**Sol:** \$ login: <user name>

\$ password: \*\*\*\*\*

b) open the file created in session 1

**Sol:** \$ vi myfile

~ Unix is Case Sensitive

~ Never leave the Computer without logging out.

~ Shell Programming

c) Add some text

**Sol:** \$ vi myfile

~ Unix is Case Sensitive

~ Never leave the Computer without logging out when you are working in a time sharing or network environments.

~ Shell Programming

d) Change some text

**Sol:** \$ vi myfile

~ Unix is Case Sensitive

~ Shell Programming

e) Delete some text

**Sol:** \$ vi myfile

~ Unix is Case Sensitive

~ Shell Programming

f) Save the Changes

**Sol:** press [Esc]

: wq

g) Logout of the system

**Sol:** \$exit

## Week-2

a) Log into the system

**Sol:** \$ login: <user name>

\$ password: \*\*\*\*\*

b) Use the cat command to create a file containing the following data. Call it mytable use tabs to separate the fields.

1425 Ravi 15.65

4320 Ramu 26.27

6830 Sita 36.15

1450 Raju 21.86

**Sol:** \$ cat > mytable

1425 <tab> Ravi <tab> 15.65 <tab>

4320 <tab> ramu <tab> 26.27 <tab>

6830 <tab> sita <tab> 36.15 <tab>

1450 <tab> Raju <tab> 21.86 <tab>

Press Ctrl+D to quit enter

c) Use the cat command to display the file, mytable.

**Sol:** \$ cat mytable

1425 Ravi 15.65

4320 ramu 26.27

6830 sita 36.15

1450 Raju 21.86

d) Use the vi command to correct any errors in the file, mytable.

**\$ vi mytable**

```
1425  Ravi kumar    15.65
4320  ramu Singh     26.27
6830  sita kumara    36.15
1450  Raju singh     21.86
```

**press [Esc]**

**: wq [Enter]**

e) Use the sort command to sort the file mytable according to the first field. Call the sorted file mytable

**\$ sort -k 1n mytable**

```
1425  Ravi kumar    15.65
1450  Raju singh     21.86
4320  ramu Singh     26.27
6830  sita kumara    36.15
```

f) Print the file mytable

**Sol: \$ lpr mytable**

g) Use the cut and paste commands to swap fields 2 and 3 of mytable. Call it mytable

**\$ cut -f1 mytable > temp1**

**\$ cut -f2 mytable > temp2**

**\$ cut -f3 mytable > temp3**

**\$ paste temp1 temp3 temp2 > mytable**

h) Print the new file mytable

**Sol: \$ lpr mytable**

i) Logout of the system.

**Sol: \$exit**

**Result: Week-2 questions are demonstrated with suitable examples successfully.**

### **Week-3**

1) a) Login to the system

**Sol: \$ login: <user name>**

**\$ password: \*\*\*\*\***

b) Use the appropriate command to determine your login shell

**Sol: \$echo "the login shell is \$SHELL"**

c) Use the /etc/passwd file to verify the result of step b.

**Sol: \$cat /etc/passwd**

d) Use the who command and redirect the result to a file called myfile1. Use the more command to see the contents of myfile1.

```
Soln: $who > myfile1
      $more myfile1
```

e) Use the date and who commands in sequence (in one line) such that the output of date will display on the screen and the output of who will be redirected to a file called myfile2. Use the more command to check the contents of myfile2.

```
$date; who>myfile2
$more myfile2
```

2) a) Write a sed command that deletes the first character in each line in a file.

```
Sol: $cat > sample
     my name is Ramu
     I am studying B.Tech III year I am learning UNIX
     ^Z(press ctrl+Z)
     $sed "s/./" sample
```

1. Write a sed command that deletes the character before the last character in each line in a file.

```
Sol: $sed "s/.\(.\)$/\1/" sample
```

2. Write a sed command that swaps the first and second words in each line in a file.

```
sed -e "s/\([^ ]*\) \([^ ]*\)/\2 \1 /g" sample
```

#### Week-4

**1. Pipe your /etc/passwd file to awk, and print out the home directory of each user.**

```
cat /etc/passwd | awk '{ print $6}'
```

**2. Develop an interactive grep script that asks for a word and a file name and then tells how many lines contain that word.**

```
Cat>filename
Day by day week by end
Week by week month by end
Month by month year by end
But friendship is never end
```

```
$ vi grep.sh
echo "Enter the pattern to be searched: "
read pattern
echo "Enter the file to be used: "
read filename
echo "Searching for $pattern from file $filename"
```

```
echo "The selected records are: " grep "$pattern" $filename
echo "The no.of lines contains the word( $pattern ) : "
grep -c "$pattern" $filename
```

Output :

```
$ sh grep.sh
Enter the pattern to be searched: by
Enter the file to be used: filename
Searching for by from filename
The selected records are:
Day by day week by end
Week by week month by end
Month by month year by end
The no. of lines contains the words ( by ) :3
```

## WEEK 5

- a) Write a shell script that takes a command –line argument and reports on whether it is directory, a file, or something else.
- b) Write a shell script that accepts one or more file name as arguments and converts all of them to uppercase, provided they exist in the current directory.
- c) Write a shell script that determines the period for which a specified user is working on the system.

- a) Write a shell script that takes a command –line argument and reports on whether it is directory, a file, or something else.

```
echo " enter file"
read str
if test -f $str
then echo "file exists and it is an ordinary file"
elif test -d $str
then echo "directory file"
else echo "not exists"
fi
```

- b) Write a shell script that accepts one or more file name as arguments and converts all of them to uppercase, provided they exist in the current directory.

```
vi week5B.sh
echo -n "Enter file name"
read filename
if [ ! -f $filename ]
then
    echo "filename $filename does not exist"
```

```
exit 1
fi
tr '[:lower:]' '[:upper:]' < filename
```

- c) a shell script that determines the period for which a specified user is working on the system.

```
echo "Enter the USER NAME : "
read user
last $user
```

**NOTE:**

**Last command:** The last command reads listing of last logged in users from the system file called /var/log/wtmp

**Week-6**

- a) Write a shell script that accepts a file name starting and ending line numbers as arguments and displays all the lines between the given line numbers.
- b) Write a shell script that deletes all lines containing a specified word in one or more files supplied as arguments to it.

- a) echo "enter the filename"

```
read fname

echo "enter the starting line number"

read s

echo "enter the ending line number"

read n

sed -n $s,$n\p $fname | cat > newline

cat newline
```

- b) Write a shell script that deletes all lines containing a specified word in one or more files supplied as arguments to it.

```
echo "enter file name"
read file
echo "enter word"
```

```

read word
echo "file before removing $word:"
cat $file
grep -v -i $word $file > test
mv test $file
echo "file after removing $word:"
cat $file

```

## Week-7

- a) Write a shell script that computes the gross salary of an employee according to the following rules:
- i) If basic salary is < 1500 then HRA = 10% of the basic and DA = 90% of the basic.
  - ii) If basic salary is >= 1500 then HRA = Rs500 and DA = 98% of the basic.

```

$ vi gsalary.sh
echo "enter basic salary"
read bsal
if [ $bsal -lt 1500 ]
then
gsal=$((bsal+((bsal/100)*10)+(bsal/100)*90))
echo "The gross salary is $gsal"
fi
if [ $bsal -ge 1500 ]
then
gsal=$((bsal+500+((bsal/100)*98)))
echo "The gross salary is $gsal"
fi

```

- b) Write a shell script that accepts two integers as its arguments and computes the value of first number raised to the power of the second number.

```

vi pow.sh
echo "Enter the integer value :"
read int1
echo "Enter the power of that integer:"
read int2
pv=$int1
i=1
while [ $i -lt $int2 ]
do
    pv=`expr $pv \* $int1`
    i=`expr $i + 1 `
done
echo "The value of first number to the power of the second number :"

```

```
echo "$pv"
```

## Week 8

- a) **Write an interactive file-handling shell program. Let it offer the user the choice of copying, removing, renaming, or linking files. Once the user has made a choice, have the program ask the user for the necessary information, such as the file name, new name and so on.**

### **vi Krishna.txt**

No one is waste, No one is greate  
Without work nothing is possible  
With hard work nothing is impossible  
So do your work perfectly

### **vi Vivekananda.txt**

Be a Hero.  
Always Say, 'I have no fear'.

### **vi week8a.sh**

```
while true
do
echo "*****MENU*****"
echo
" 1. List of files.
  2. Copying files.
  3. Removing files.
  4. Renaming files.
  5. Linking files.
press [CTRL+C] TO EXIT"
echo "enter your choice "
read ch
case "$ch" in

1 ) echo "The list of file names."
ls -l || echo "These are file";;

2) echo "Enter the old filename."
read ofile
echo "Enter the new file name."
read nfile
cp $ofile $nfile && echo "Copied sucessfully." || echo "Copied is not possible." ;;

3 ) echo "Enter the file name to remove."
read rfile
rm -f $rfile && echo "Successfully removed." ;;

4 ) echo "Enter the old file name."
```



```

    read ofile
    echo "Enter the new file name."
    read nfile
    mv $ofile $nfile && echo "The file $ofile name renamed to $nfile." || echo "You cann't
    Rename the file.".;;
5 ) echo "Enter the original filename."
    read ofile
    echo "Enter the new filename to link a file."
    read lfile
    ln $ofile $lfile && echo "Creat the linking file Sccessfully." || echo "You cann't Linking
    the file.";; * )

    echo "Invalid option."
    Echo " Enter correct choice."
    esac
done

```

**b. Write shell script that takes a login name as command – line argument and reports when that person logs in**

```

vi week8b.sh
echo "Enter the user name:"
read user
last $user && echo "these are the datails of user $user"

```

**c) Write a shell script which receives two file names as arguments. It should check whether the two file contents are same or not. If they are same then second file should be deleted.**

```

vi week8c.sh
echo "enter the first file name"
read file1
echo "enter the second file name"
read file2
cmp $file1 $file2 && rm $file2
if [ -e $file1 ]
then
if [ ! -e $file2 ]
then
echo " the two files contents are same. so $file2 is deleted"
else
echo " the two file contents are not same and $file2 not deleted"
fi
else
echo "$file1 is not existed"
fi

```

## Week-9

a) Write a shell script that displays a list of all the files in the current directory to which the user has read, write and execute permissions.

```
echo "The list of file names in the current directory:"
for file in *
do
if [ -f $file ]
then
if [ -r $file -a -w $file -a -x $file ]
then
ls -l $file
fi
fi
done
```

b) Develop an interactive script that ask for a word and a file name and then tells how many times, that word occurred in the file.

```
Cat>sample.txt
Day by day week by end
Week by week month by end
Month by month year by end
But friendship is never end
```

## Press Ctrl+d

```
$ vi grep.sh
echo "Enter the pattern to be searched: "
read pattern
echo "Enter the file to be used: "
read filename
echo "Searching for $pattern from file $filename"
echo "The selected records are: " grep "$pattern" $filename
echo "The no.of lines contains the word( $pattern ) : "
grep -c "$pattern" $filename
```

## Output :

```
$ sh grep.sh
Enter the pattern to be searched: by
Enter the file to be used: sample.txt
Searching for by from sample.txt
The selected records are:
Day by day week by end
Week by week month by end
```

Month by month year by end  
The no. of lines contains the words ( by ) :3

### **Week-10**

**Write a shell script to perform the following string operations:**

**i) To extract a sub-string from a given string.**

```
echo "Enter the string"
read str
strlen=${#str}
echo "the length of the given string is:$strlen"
echo "Enter the position of substring in main string"
read s1
echo "Enter the ending position of substring in main string"
read f1
echo $str|cut -c$s1-$f1
```

**ii) To find the length of a given string**

```
str="Hare Ram Singh"
strlen=${#str}
echo "length of $str is:$strlen"
```