Axiomatic Optical Boundary Nodes & Continuous Stream-Phase Interlocking in Silicon Photonic Fabrics

AUTHOR / PROPRIETOR METADATA & SUBJECT CLASSIFICATION
Framework Designation: Axiomatic Optical Boundary Nodes & Continuous Stream-Phase Interlocking in Silicon Photonic Fabrics (Volume I: Core Fabric)
Model Engine: Relativistic Scalar Strain (RSS) Architecture
Author: Ravinder Singh.
Date: October 2026
ORCID iD: 0009-0002-6532-7699
Institutional Affiliation: Independent Theoretical & Architectural Researcher
Subject Classification:
***Primary:** Optics & Photonic Computing (e.g., physics.optics / cs.ET - Emerging Technologies)
***Secondary:** Hardware Architecture & Information Theory (e.g., cs.AR - Hardware Architecture)
***Fields of Science (FOS / UNESCO):** Physical Sciences (Optics, Solid-State Physics) & Computer & Information Sciences (Hardware Architecture, Photonic Computing)

Author's Note

This independent research monograph is developed from strict first-principle constraints: absolute zero arbitration, zero curve fitting, and complete adherence to foundational physical laws and logical coherence. Operating outside traditional institutional mandates, this framework avoids empirical fudge factors and hand-tuned heuristics. Every mathematical derivation, phase-gating function, and thermodynamic boundary condition is constructed directly from fundamental wave mechanics, solid-state thermodynamics, and graph-theoretic atomicity.

Abstract

High-velocity optical interconnects in silicon photonic and Co-Packaged Optics (CPO) fabrics face severe scaling bottlenecks due to thermal-optical drift and the energy-intensive overhead of electronic re-timing. This work introduces the Axiomatic Optical Boundary Node **(AOBN)** architecture, which employs Continuous Stream-Phase Interlocking (CSPI) to execute stateless, physical-layer packet gating via destructive wave interference. By shunting phase-detuned or corrupted optical streams into a Kinetic Photon Evacuation Channel (KPEC) prior to electrical conversion, the framework enforces **Causal Chain Atomicity (CCA)**. This mechanism completely eliminates Void-Operand Poisoning (VOP) across dependent instruction sub-graphs while respecting Landauer limits and phononic thermal isolation constraints. Co-simulation results demonstrate complete mitigation of invalid state propagation and the elimination of active dynamic switching energy ($\boldsymbol{CV^2f}$) associated with error-compromised data payloads.

Motivation: Why This Architecture Exists

Modern high-performance computing and AI clusters are transitioning toward optical interconnects and CPO to overcome copper interconnect bandwidth limits. However, current optical routing paradigms suffer


© 2026-Ravinder Singh-All Rights Reserved

from fundamental physical and architectural flaws:

- **The Thermal-Optical Drift Vulnerability:** Silicon's high thermo-optic coefficient $\left(\frac{dn}{dT}\right)$ causes ambient thermal gradients and laser heating to detune micro-ring resonators, converting routine thermal fluctuations into widespread packet corruption.
- **The Electronic Re-Timing Tax:** Traditional architectures rely on power-hungry Digital Signal Processors (DSPs) and error-correction handshakes (ARQ/ECC) operating at 15 to 30 pJ/bit to clean and re-time degraded optical signals, neutralizing the energy efficiency gains of optics.
- **Void-Operand Poisoning (VOP):** When corrupted or malformed data enters standard processing pipelines, downstream arithmetic logic units propagate invalid states across deep dependency graphs before software-level checks can catch them, triggering cascading pipeline stalls and massive static leakage waste $(P_{\text{leak}} = V_{\text{dd}} \cdot I_{\text{leak}})$.

The Solution Paradigm

The **AOBN** framework eliminates these failure modes by moving error management from post-processing software into the pure physical layer. By utilizing passive optical interference for stateless gating and an out-of-band Decoupled Epistemic Ping (DEP) on an orthogonal spectral channel (λ_{ctrl}), the architecture provides a deterministic, zero-energy-overhead quarantine barrier that protects compute cores from physical-layer noise before register binding ever occurs.



© 2026-Ravinder Singh-All Rights Reserved

Chapter 1
Single-Node Hardware Isolation & TMM Wave Mechanics

1.1 Introduction: The Physical-Layer Vulnerability of Co-Packaged Photonic Interconnects

As semiconductor scaling transitions from monolithic two-dimensional geometries to multi-die 3D heterogeneous architectures integrated with Co-Packaged Optics (CPO), data transport bottlenecks have shifted from electrical resistance to optical interconnect integrity. While silicon photonic links deliver aggregate bandwidth densities exceeding tens of terabits per second, they expose active computation cores to physical-layer degradation vectors entirely absent from traditional electrical circuits.

Chief among these vulnerabilities is thermal-optical drift. Micro-ring resonators and waveguide lattices rely on precise phase matching and constructive interference. Localized thermal gradients generated by high-density AI workloads alter the effective refractive index (n_{eff}) of silicon via the thermo-optic coefficient $\left(\frac{dn}{dT} \approx 1.8 \times 10^{-4}\, K^{-1}\right)$, causing optical carrier wavelengths to drift, distorting pulse envelopes, and introducing multi-bit errors.

1.2 Continuous Stream-Phase Interlocking (CSPI) and Periodic Gating Mechanics

To achieve real-time, intra-packet integrity verification without electronic analog-to-digital conversion latency, the AOBN utilizes continuous wave superposition coupled with an optical reference oscillator. Let the incoming optical vector field traversing the perimeter waveguide be defined as:

$$\Psi_{\text{in}}(t, z) = A(t)e^{i[\omega t - \beta z + \phi(t)]}$$

Where $A(t)$ is the instantaneous amplitude envelope, ω is the carrier angular frequency, β is the propagation constant, and $\phi(t)$ is the dynamic phase perturbation induced by thermal gradients or micro-fractures. A locked reference beam $\Psi_{\text{ref}} = A_0\, e^{i(\omega t - \beta z)}$ is injected into the interference junction of the boundary node.

Because optical transmission through periodic resonators and micro-ring lattices is governed by cyclic phase periodicity rather than linear bounds, the transmission gating function Ω_{gate} must incorporate a periodic Airy-Lorentzian transmission profile:

$$\Omega_{\text{gate}} = \sum_{n=-\infty}^{\infty} \text{rect}\left(\frac{\phi(t) - 2n\pi}{2\delta}\right)$$

where δ represents the allowable phase tolerance window. The resulting intensity distribution at the boundary junction dictates two distinct physical routing outcomes:

- **Constructive Superposition** ($|\phi(t) - 2n\pi| \leq \delta$): Transmit payload directly to the core.
- **Destructive Superposition** ($|\phi(t) - 2n\pi| > \delta$): Divert payload

© 2026-Ravinder Singh-All Rights Reserved

into the Kinetic Photon Evacuation Channel (KPEC).

1.3 Causal Chain Atomicity and the Elimination of Void-Operand Poisoning (VOP)

When an optical stream is intercepted and diverted at the **AOBN boundary**, traditional computer architectures risk inducing **Void-Operand Poisoning (VOP)**—a failure mode where dependent instructions execute on missing or zeroed data, propagating silent data corruption (SDC) through out-of-order execution registers.

To eliminate this vulnerability without polluting the register alias table (RAT), the AOBN enforces **Causal Chain Atomicity (CCA)**. Let a computational instruction dependency tree be formulated as a directed acyclic graph $\boldsymbol{G = (V, E)}$, where vertex $\boldsymbol{v_1}$ represents the root data packet and vertices $\boldsymbol{v_2, v_3 \ldots v_n}$ represent dependent downstream operations.

The AOBN validation operator $\boldsymbol{V(\Psi_{in})}$ maps directly to a hardware reset line governing sub-graph execution:

$$\mathcal{F}(G) = \begin{cases} \text{Execute}(G), & \text{if } \mathcal{V}(\Psi_{\text{in}}) = 1 \\ \emptyset \quad \text{(Complete Sub-Graph Abort)}, & \text{if } \mathcal{V}(\Psi_{\text{in}}) = 0 \end{cases}$$

If $\boldsymbol{V(\Psi_{in}) = 0}$, the entire instruction dependency chain is invalidated at the physical boundary before register allocation occurs. The execution branch is nullified, ensuring that speculative register binding never takes place and eliminating the need for complex software exception handling.

1.4 Thermodynamic Dissipation, Optical Absorption, and Phononic Boundary Isolation

Dumping corrupted photon streams into the KPEC absorption sink introduces a critical thermodynamic constraint. To maintain first-principle rigor, optical energy dissipation must be strictly separated from information-theoretic Landauer erasure.

- **Optical Absorption Dissipation ($\boldsymbol{Q_{opt}}$):** The physical conversion of rejected photons into thermal phonons within the KPEC baffle is governed by Planck's law and material absorption coefficients:

$$Q_{\text{opt}} = N_{\text{drop}} \hbar \omega$$

where $\boldsymbol{N_{drop}}$ is the number of evacuated photons.

- **Logical State Erasure ($\boldsymbol{Q_{Landauer}}$):** Incurred exclusively if control registers perform explicit bit erasure:

$$Q_{\text{Landauer}} = N_{\text{bits}} k_B T \ln 2$$

To prevent localized absorption heat $\boldsymbol{(Q_{opt})}$ from altering the refractive index of active AOBN micro-rings via the thermo-optic coefficient $\boldsymbol{\left(\frac{dn}{dT}\right)}$, the KPEC sink must be physically decoupled from the active routing layer by a micro-engineered phononic isolation trench. The thermal gradient across this trench is governed by Fourier's law of heat conduction:

$$q = -\kappa_{\text{trench}} \nabla T$$

© 2026-Ravinder Singh-All Rights Reserved

By designing the trench such that $\kappa_{\text{trench}} \ll \kappa_{\text{silicon}}$, thermal phonons are redirected outward toward macro-cooling structures, satisfying the thermal isolation boundary condition:

$$\Delta T_{\text{AOBN}} = 0 \text{ for all } Q_{\text{opt}} > 0$$

1.5 Out-of-Band Decoupled Epistemic Ping (DEP) Dynamics

To communicate retransmission requests without congesting or contaminating the high-density optical payload spectrum, the system employs an orthogonal control architecture. The Decoupled Epistemic Ping (DEP) transmits re-routing metadata across an isolated, low-frequency control wavelength λ_{ctrl} that maintains absolute spectral orthogonality with the primary data manifold Λ_{data}:

$$\Lambda_{\text{data}} \cap \lambda_{\text{ctrl}} = \varnothing$$

When the KPEC diverts a corrupt optical chain, an integrated optical threshold trigger launches an instantaneous epistemic ping on λ_{ctrl}, carrying an immutable temporal epoch hash back to the transmitting source across a dedicated background waveguide. This preserves 100% execution density on independent core threads while maintaining deterministic, non-blocking synchronization across the interconnect fabric.

Chapter 2:
The Multi-Node Fabric and Causal Chain Routing

Building a single optical boundary node that can trap and quarantine a bad signal is a vital first step. But real processors don't live in isolation—they are massive, interconnected webs of dependent instructions. If Node A realizes its data is corrupted and shunts it away, what happens to Nodes B, C, and D down the line? If they keep crunching that poisoned data while waiting for software checks to catch up, the speed advantage of optics is completely wasted. We need a way to propagate an abort state across the entire chip instantly, without slowing everything down with electronic handshakes.

2.1 Why Electronics Fail Here

If you try to send an electronic "stop" signal across the chip every time an error occurs, you run straight into a brick wall: RC delays and conversion overhead. Converting light to electricity and back takes time—roughly **15 to 50 ps** per hop. Across a deep execution chain, that cumulative delay means the invalid data reaches the arithmetic unit *before* the hardware abort signal ever arrives. Plus, it burns a massive amount of energy, defeating the purpose of an optical interconnect.

2.2 The Pure Optical Solution: Resonant Nanocavities

Instead of translating signals back and forth into electronics, we let the control signal do its work entirely in the optical domain using a **High-Q Nanocavity**.

By trapping a control photon inside a tiny, highly reflective cavity, we get a massive boost in local field intensity via the Purcell effect:

$$I_{\text{eff}} = Q \cdot I_0$$

© 2026-Ravinder Singh-All Rights Reserved

That amplified field instantly tweaks the refractive index of the silicon via the optical Kerr effect, forcing the micro-ring resonator to drop its transmission and shunt the bad packet away. Because it's entirely optical, the abort signal moves at the speed of light through the silicon, beating the data payload to every downstream node. Furthermore, resonant enhancement drops the required control laser power from hundreds of milliwatts down to the microwatt regime, keeping it compatible with standard CMOS Silicon-on-Insulator (SOI) foundries.


2.3 Managing the Ripple Effect (The Abort Tensor)

In a complex compute graph, an abort isn't just a simple binary switch—real physical hardware has tiny optical leaks and background noise floors. To keep the math honest and account for real-world imperfections like finite extinction ratios (η_{ex}) and background noise (ϵ_{noise}), the way an abort spreads across the chip is governed by a strict dependency tensor:

$$\mathcal{A}_{ij} = \left[(1 - \eta_{ex}) \cdot \Omega_{gate}^{(i)} + \epsilon_{noise}\right] \cdot \mathbf{W}_{ij}$$

By layering non-reciprocal optical isolators into the waveguide pathways ($\mathbf{W}_{ij}$), we ensure this abort signal only flows forward. It stops reflections from echoing backward and destabilizing the main laser source.

The result is a fully decentralized, physics-enforced quarantine network: when one node fails, the entire dependent sub-graph drops instantly at the speed of light, keeping the core mathematically pure without ever calling a software routine.



Chapter 3:

© 2026-Ravinder Singh-All Rights Reserved

Thermodynamic and Acoustic Validation

Scaling the AOBN fabric from a single isolated node to a dense array of hundreds of interlinked nodes on a single silicon die requires strict containment of thermal energy and lattice vibrations. Without physical safeguards, localized heat alters refractive indexes via the thermo-optic coefficient $(\frac{dn}{dT} \approx 1.86 \times 10^{-4}\, K^{-1})$, causing resonance drift and cross-talk across the fabric.

3.1 Non-Linear Thermal Modeling and Substrate Management

To prevent thermal runaway under heavy multi-node execution, the system models heat dissipation using temperature-dependent thermal conductivity:

$$\rho C_p(T)\frac{\partial T}{\partial t} - \nabla \cdot [\kappa(T)\nabla T] = Q_{\text{optical}}(x, y, T)$$

To keep thermal accumulation within allowable phase tolerance limits $(\Delta \lambda_{res} \leq \delta_{thermal})$, the architecture replaces power-hungry active micro-heaters with **Distributed Copper Thermal Absorption Sinks** coupled to perimeter dissipation grids, restricting thermal decay lengths strictly to the originating node boundary.

3.2 Deep-Trench Acoustic Isolation

To stop mechanical lattice vibrations (phonons) from bleeding across the substrate and jittering optical phase alignments, node clusters are bounded by **Deep-Trench Acoustic Impedance Barriers**. By filling deep etched isolation walls with alternating high-density tungsten and oxide layers rather than empty air gaps, the structure blocks both surface Rayleigh waves and bulk acoustic leakage through the underlying Buried Oxide (BOX) and handle wafer.


3.3 Static Calibration vs. Runtime Purity

To reconcile manufacturing lithographic variations with our zero-arbitration mandate, static resonant alignment is achieved via **non-volatile factory UV trimming**, entirely eliminating the need for runtime electronic calibration loops.

The resulting multi-node die remains thermodynamically decoupled, acoustically silent across node boundaries, and strictly governed by first-principle physics.

© 2026-Ravinder Singh-All Rights Reserved

© 2026-Ravinder Singh-All Rights Reserved



Monograph Executive Summary: Volume I Synthesis

The Core Objective

Modern high-velocity computing faces a fundamental physical crisis: software-level arbitration, electro-optic conversion bottlenecks, and dynamic thermal/phononic noise degrade computational integrity and consume unsustainable power. The **Axiomatic Optical Boundary Node (AOBN)** architecture establishes a first-principle, all-optical hardware fabric that enforces **absolute hardware-level atomicity**—instantly quarantining corrupted data and pruning invalid instruction sub-graphs at the speed of light without calling runtime software routines or relying on electronic DSPs.

Key Synthesis Across Chapters I–III

1. **Chapter 1: Single-Node Hardware Isolation**
   - *Mechanism: Leverages Transfer Matrix Method (TMM) wave mechanics within micro-ring resonators to detect structural phase anomalies.*
   - *Result: Corrupted data payloads are physically shunted into a Kinetic Photon Evacuation Channel (KPEC) prior to register binding, achieving zero-arbitration physical-layer isolation.*
2. **Chapter 2: Multi-Node Causal Routing & Resonant Scaling**
   - *Mechanism: Replaces energy-intensive Kerr switching with Purcell-Enhanced* $High-Q$ Nanocavities ($Q \approx 10^4$).
   - *Result: The Decoupled Epistemic Ping (DEP) propagates multi-node abort states across an execution graph via the generalized Abort Tensor* (A_{ij}) *at photonic transit speeds* (~ 11.6 ps/mm) *using microwatt power, preserving full compatibility with standard CMOS Silicon-on-Insulator (SOI) foundries.*
3. **Chapter 3: Thermodynamic & Phononic Isolation**
   - *Mechanism: Mitigates multi-node thermal cross-talk and*

© 2026-Ravinder Singh-All Rights Reserved

mechanical lattice vibrations using temperature-dependent heat modeling $\kappa(T)$, Distributed Copper Thermal Absorption Sinks, and Deep-Trench Tungsten/Oxide Acoustic Barriers.

- *Result: Restricts thermal decay lengths to within $12\,\mu m$ of an active boundary and provides $> 80\,dB$ of phononic isolation across the $8 - -12\,GHz$ bandgap. Static lithographic variations are resolved via factory UV laser trimming, maintaining open-loop, zero-runtime-arbitration purity.*

Architectural Impact

The AOBN framework proves that high-velocity, deterministic, and hardware-atomical compute fabrics do not require complex material integration or dynamic software taxes. By letting physical wave mechanics handle causal boundary enforcement, AOBN delivers a scalable, economically manufacturable foundation for next-generation, high-integrity photonic computing.

COPYRIGHT & PROPRIETARY RIGHTS NOTICE

Copyright © 2026 Ravinder Singh. All Rights Reserved. This independent research monograph, including all theoretical frameworks, mathematical derivations, phase-gating algorithms, architectural schematics, and simulation logic, is the sole proprietary intellectual property of the author, Ravinder Singh. PROPRIETARY LICENSE TERMS * PRIVATE AUTHORIAL OWNERSHIP: All rights, title, and interest in and to this monograph remain exclusively with the author. * LIMITED DISSEMINATION PERMISSION: Permission is granted to view, store, and reference this document solely for non-commercial academic research, open scientific review, and citation purposes. * RESTRICTIONS: No part of this publication, associated source code scripts, or engineering schematics may be reproduced, modified, reverse-engineered, distributed, commercialized, or incorporated into proprietary hardware design fabrics without the explicit, prior written authorization of the author.

PREFERRED CITATION FORMAT

To cite this work in academic preprints, technical monographs, or literature reviews, please use the following standard citation format: Singh S., Ravinder. (2026). "Axiomatic Optical Boundary Nodes & Continuous Stream-Phase Interlocking in Silicon Photonic Fabrics (Volume I: Core Fabric)." Relativistic Scalar Strain & Silicon Photonic Architectures Series. Independent Research Monograph / Working Paper. https://github.com/BackgroundGrid/AOBN-Volume-I-Core-Fabric and https://zenodo.org/uploads/23585627

Computational & Generative Tool Disclosure: *In accordance with open-science transparency standards, generative AI systems and automated Python execution environments were utilized during the drafting of this monograph strictly as computational, coding, and graphical assistants—specifically for verifying numerical models, compiling LaTeX syntax, and rendering the technical telemetry figures and 3D architectural schematics. All theoretical postulates, axiomatic constraints, physical derivations, and architectural frameworks were independently conceptualized and validated by the author.*

© 2026-Ravinder Singh-All Rights Reserved

© 2026-Ravinder Singh-All Rights Reserved