



CYBOP UDP-Kommunikation



Gliederung

- Idee: UDP-Echo-Server
- CYBOL
 - service
 - namespace
 - address
 - send
 - channel
 - language
 - receiver
- Beispiel
 - Sender
 - Empfänger



UDP-Echo-Server

- Idee:

- CYBOI 1 wartet in Endlosschleife auf eingehende Daten
→ UDP/IP-Kommunikation
- CYBOI 1 sendet empfangene Daten 1:1 wieder an den Sender zurück
- CYBOI 2 sendet an CYBOI 1 via Netzwerk bspw. „Hello CYBOI“



UDP-Echo-Server

→ Szenario in CYBOL abbilden und eventuell auftretende Probleme/Fehler dokumentieren



CYBOL > service

Startup

This operation starts up the given service.

Example

```
<part name="startup_wui" channel="inline" abstraction="operation" model="startup">  
  <property name="service" channel="inline" abstraction="character" model="www"/>  
  <property name="namespace" channel="inline" abstraction="character" model="inet"/>  
  <property name="style" channel="inline" abstraction="character" model="stream"/>  
  <property name="address" channel="inline" abstraction="character" model="any"/>  
</part>
```



CYBOL > service

Startup

This operation starts up the given service.

Example

```
<part name="startup_wui" channel="inline" abstraction="operation" model="startup">  
  <property name="service" channel="inline" abstraction="character" model="www"/>  
  <property name="namespace" channel="inline" abstraction="character" model="inet"/>  
  <property name="style" channel="inline" abstraction="character" model="stream"/>  
  <property name="address" channel="inline" abstraction="character" model="any"/>  
</part>
```




CYBOL > service

Service Property

This is the service to be started up.

required

```
name      = 'service'
abstraction = 'character'
model     = 'signal' | 'shell' | 'standard output' |
            'gnu_linux_console' | 'x_window_system' |
            'www' | 'cyboi'
```



CYBOL > service

Service Property

This is the service to be started up.

required

```
name      = 'service'
abstraction = 'character'
model      = 'signal' | 'shell' | 'standard output' |
              'gnu_linux_console' | 'x_window_system' |
              'www' | 'cyboi' | 'network'
```




CYBOL > service

Startup

This operation starts up the given service.

Example

```
<part name="startup_wui" channel="inline" abstraction="operation" model="startup">  
  <property name="service" channel="inline" abstraction="character" model="www"/>  
  <property name="namespace" channel="inline" abstraction="character" model="inet"/>  
  <property name="style" channel="inline" abstraction="character" model="stream"/>  
  <property name="address" channel="inline" abstraction="character" model="any"/>  
</part>
```



CYBOL > service

Namespace Property

The namespace of the socket.

optional, only if service is www or cyboi

```
name          = 'namespace'  
abstraction   = 'character'  
model         = 'local' | 'inet' | 'inet6' | 'ns' | 'iso' |  
               'ccitt' | 'implink' | 'route'
```



CYBOL > service

Namespace Property

The namespace of the socket.

optional, only if service is www or cyboi

```
name          = 'namespace'
abstraction    = 'character'
model         = 'local' | 'inet' | 'inet6' | 'ns' | 'iso' |
                'ccitt' | 'implink' | 'route'
```



CYBOL > service

Startup

This operation starts up the given service.

Example

```
<part name="startup_wui" channel="inline" abstraction="operation" model="startup">  
  <property name="service" channel="inline" abstraction="character" model="www"/>  
  <property name="namespace" channel="inline" abstraction="character" model="inet"/>  
  <property name="style" channel="inline" abstraction="character" model="stream"/>  
  <property name="address" channel="inline" abstraction="character" model="any"/>  
</part>
```



CYBOL > service

Address Property

This is the address of hosts communicating with this system via socket.

optional, only if service is www or cyboi

```
name          = 'address'
abstraction    = 'character'
model         = 'loopback' | 'any'
```



CYBOL > service

Address Property






CYBOL > send

Send

This operation is able to send a message via textual, graphical or web user interface, or to the file system or also as shell output directly.

Example

```
<part name="send_menu" channel="inline" abstraction="operation" model="send">  
  <property name="channel" channel="inline" abstraction="character"  
    model="gnu_linux_console"/>  
  <property name="language" channel="inline" abstraction="character" model="tui"/>  
  <property name="message" channel="inline" abstraction="knowledge" model=".app.tui"/>  
  <property name="area" channel="inline" abstraction="knowledge" model=".app.tui.menu"/>  
  <property name="clean" channel="inline" abstraction="boolean" model="true"/>  
</part>
```



CYBOL > send

Send

This operation is able to send a message via textual, graphical or web user interface, or to the file system or also as shell output directly.

Example

```
<part name="send_menu" channel="inline" abstraction="operation" model="send">  
  <property name="channel" channel="inline" abstraction="character"  
    model="gnu_linux_console"/>  
  <property name="language" channel="inline" abstraction="character" model="tui"/>  
  <property name="message" channel="inline" abstraction="knowledge" model=".app.tui"/>  
  <property name="area" channel="inline" abstraction="knowledge" model=".app.tui.menu"/>  
  <property name="clean" channel="inline" abstraction="boolean" model="true"/>  
</part>
```




CYBOL > send

Channel Property

The channel via which to send the message.

required

```
name          = 'channel'
abstraction    = 'character'
model         = 'inline' | 'file' | 'standard_output' |
                'gnu_linux_console' | 'x_window_system' |
                'http'
```



CYBOL > send

Channel Property

The channel via which to send the message.

required

```
name          = 'channel'
abstraction    = 'character'
model         = 'inline' | 'file' | 'standard_output' |
                'gnu_linux_console' | 'x_window_system' |
                'http' | 'cyboi' | 'network'
```



CYBOL > send

Send

This operation is able to send a message via textual, graphical or web user interface, or to the file system or also as shell output directly.

Example

```
<part name="send_menu" channel="inline" abstraction="operation" model="send">
  <property name="channel" channel="inline" abstraction="character"
    model="gnu_linux_console"/>
  <property name="language" channel="inline" abstraction="character" model="tui"/>
  <property name="message" channel="inline" abstraction="knowledge" model=".app.tui"/>
  <property name="area" channel="inline" abstraction="knowledge" model=".app.tui.menu"/>
  <property name="clean" channel="inline" abstraction="boolean" model="true"/>
</part>
```



CYBOL > send

Language Property

The language into which to encode the message before sending it.

required

```
name          = 'language'  
abstraction   = 'character'  
model         = 'tui' | 'gui' | 'wui'
```



CYBOL > send

Language Property

```
trunk/examples$ grep -R "language" * | grep -v svn
addition/run.cybol: <property name="language" channel="inline" abstraction="text/plain" model="integer"/>
[...]
addition_static_model/run.cybol: <property name="language" channel="inline" abstraction="text/plain"
model="text/cybol"/>
[...]
counter/run.cybol: <property name="language" channel="inline" abstraction="text/plain" model="text/model-
diagram"/>
[...]
helloworld/startup.cybol: <property name="language" channel="inline" abstraction="text/plain"
model="text/plain"/>
http_communication/logic/send_wui_index.cybol: <property name="language" channel="inline"
abstraction="text/plain" model="text/html"/>
[...]
http_communication/logic/handler/handle_www_service.cybol: <property name="language" channel="inline"
abstraction="text/plain" model="message/http-request"/>
```



CYBOL > send

Receiver Property

The name of the system receiving the message.

required


```
name          = 'receiver'  
abstraction   = 'character'  
model         = name of receiving system
```

?



Beispiel > service

```
<part name="startup_udp" channel="inline" abstraction="operation/plain" model="startup">  
  
  <property name="service" channel="inline" abstraction="text/plain" model="cyboi"/>  
  
  <property name="namespace" channel="inline" abstraction="text/plain" model="ipv4"/>  
  
  <property name="style" channel="inline" abstraction="text/plain" model="datagram"/>  
  
  <property name="address" channel="inline" abstraction="text/plain" model="any"/>  
  
</part>
```



Beispiel > service

```
root@chaos:examples# nmap -sU -p 1970-1975 localhost
```


```
Starting Nmap 5.21 ( http://nmap.org ) at 2011-04-26 17:00 CEST
```

```
Nmap scan report for localhost (127.0.0.1)
```

```
Host is up (0.000025s latency).
```

PORT	STATE	SERVICE
1970/udp	closed	unknown
1971/udp	open filtered	unknown
1972/udp	closed	unknown
1973/udp	closed	unknown
1974/udp	closed	unknown
1975/udp	closed	unknown

```
Nmap done: 1 IP address (1 host up) scanned in 1.35 seconds
```

Beispiel > receive

```
<part name="read" channel="inline" abstraction="operation/plain" model="receive">
```

```
  <property name="channel" channel="inline" abstraction="text/plain" model="cyboi"/>
```

```
  <property name="language" channel="inline" abstraction="text/plain"  
    model="text/plain"/>
```

```
  <property name="model" channel="inline" abstraction="path/knowledge"  
    model=".udp_communication.msg"/>
```

```
  <property name="mode" channel="inline" abstraction="text/plain" model="server">
```

```
  <property name="style" channel="inline" abstraction="text/plain" model="datagram"/>
```

```
</part>
```



Beispiel > receive

...

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

TEST ps: 0

...

kein Empfang



Beispiel > send

```
<part name="write" channel="inline" abstraction="operation/plain" model="send">
```

```
  <property name="channel" channel="inline" abstraction="text/plain" model="cyboi"/>
```

```
  <property name="language" channel="inline" abstraction="text/plain"
    model="text/plain"/>
```

```
  <property name="namespace" channel="inline" abstraction="text/plain" model="ipv4"/>
```

```
  <property name="style" channel="inline" abstraction="text/plain" model="datagram"/>
```

```
  <property name="mode" channel="inline" abstraction="text/plain" model="client"/>
```

```
  <property name="message" channel="inline" abstraction="path/knowledge"
    model=".udp_communication.send_msg"/>
```

```
</part>
```



Beispiel > send

```
examples$ ../bin/cyboi --knowledge udp_sender/run.cybol  
TEST: startup socket bind s: 3  
TEST: send socket sn: 2  
TEST: send socket an: 2  
TEST: send socket st: 2  
Speicherzugriffsfehler
```