

Fuzzy Classification of Web Reports with Linguistic Text Mining

Jan Dědek^{1,2} Peter Vojtáš^{1,2}

¹Department of Software Engineering, Faculty of Mathematics and Physics,
Charles University in Prague, Czech Republic

²Institute of Computer Science, Academy of Sciences of the Czech Republic

Soft approaches to information access on the Web,
Web Intelligence 2009, 15 – 18 September 2009
Università degli Studi di Milano Bicocca, Milano, Italy


Outline

- 1 **Introduction**
 - Our Information Extraction System
 - Fuzzy ILP
- 2 **Our Experiment**
 - Experiment Description
- 3 **Fuzzy ILP / GAP Implementation**
 - Monotonization
- 4 **Evaluation and Conclusion**
 - Learning Results
 - Evaluation
 - Conclusion

Our work

- Extraction of semantic information from **texts**.
 - In Czech language.
 - Coming from web pages.
- Using of Semantic Web **ontologies**.
 - RDF, OWL
- Exploiting of linguistic tools.
 - Mainly from the **Prague Dependency Treebank** project.
 - Experiments with the Czech WordNet.
- **Rule based** extraction method.
 - Extraction rules \approx **tree queries**
 - ILP learning of extraction rules
- **In this presentation**
 - Experiment with **Fuzzy ILP**
 - Accident seriousness classification
 - Exploitation of extracted information

Schema of the whole system



- 1 Web Crawling
- 2 Information Extraction and User Evaluation
- 3 Logic representation
 - Construction of **background knowledge**
 - Construction of **learning examples**
- 4 ILP Learning
 - Crisp
 - Fuzzy
- 5 Comparison of results

Example of processed web page




Ministerstvo vnitra
[home](#) [navigace](#) [vyhledávání](#) [změna vzhledu](#)

Zpravodajství
Informace z resortu o tom, co se stalo, co se děje i co se připravuje

[skrýt menu](#)

■ HZS Jihomoravského kraje

Zubatého 1, 614 00 Brno, telefon 950 630 111,
<http://www.firebrno.cz>
Zpravodajství v roce 2006



15.05.2007

V trabantu zemřeli dva lidé

K tragické nehodě dnes odpoledne hasiči vyjžděli na silnici z obce Česká do Kuřimi na Brněnsku.

Nehoda byla operačnímu středisku HZS ohlášena ve 13.13 hodin a na místě zasahovala jednotka profesionálních hasičů ze stanice v Třišnově. Jednalo se o čelní srážku autobusu Karosa s vozidlem Trabant 501. Podle dostupných informací trabant jedoucí ve z Brna do Kuřimi zřejmě vyjel do protisměru, kde narazil do linkového autobusu dopravní společnosti ze Žďáru nad Sázavou. Ve zdemolovaném trabantu na místě zemřeli dva muži – 82letý senior a další muž, jehož totožnost zjišťují policisté.

Hasiči udělali na vozidle protipožární opatření a po vyšetření a zadokumentování nehody dopravní policii vrak trabantu zaklesnutý pod autobusem pomocí lana odtrhli. Po odstranění střechy trabantu pak z kabiny vyprostili těla obou mužů. Obě vozidla – trabant i autobus, pak postupně odstranili na kraj vozovky a uvolnili tak jeden jízdní pruh. Únik provozních kapalin nebyl zjištěn. Po 16. hodině pomohli vrak trabantu naložit k odhahu a asistovali při odtažení autobusu. Po úklidu vozovky krátce před 16.30 hod. místo nehody předali policistům a ukončili zásah.






Odkazy

Hasiči

- Generální ředitelství
- hl. m. Praha
- Jihočeský kraj
- Jihomoravský kraj
- Karlovarský kraj
- Královéhradecký kraj
- Liberecký kraj
- Moravskoslezský kraj
- Olomoucký kraj
- Pardubický kraj
- Píseňský kraj
- Středočeský kraj
- Ústecký kraj
- kraj Vysočina
- Zlínský kraj



V této rubrice Zpravodajství

- Aktualizace stránek
- Archiv zpravodajství
- Bleskové zpravodajství
- RSS
- Boj proti korupci
- Digitální televize
- Hasiči
- Hlavní zprávy
- Ministerstvo
- Od dopisovatelů (neoficiální)
- Policie
- Regiony
- Servis nejen pro novináře
- Schengenská spolupráce
- WebEditorial

Na našem serveru v jiných rubrikách

- Aktuality Národního archivu

● Fire and car accidents reports

Example of processed text


Diagram illustrating information extraction from a Czech text snippet. The text is: "Požár byl operace na střední ŽS ohlášen dnes ve 2.13 hodin, na místo vyjeli profesionální hasiči ze stanice v Židlochovicích a dobrovolní hasiči z Židlochovic, Žabčic a Přísnotic, Oheň, finished at 4:03 troinstalaci u chladicího boxu, hasiči dostali pod kontrolu ve 2.32 hodin a uhasili tři minuty po třetí hodině. Příčinou vzniku požáru byla technická závada, škodu vyšetřovatel předběžně vyčíslil na osm tisíc korun. damage 8 000 CZK id_47443".

Extracted information (highlighted in green):

- fire
- 3 amateur units
- started at
- 2.13
- Židlochovic
- Žabčic
- Přísnotic
- Oheň
- finished at 4:03
- troinstalaci u chladicího boxu
- 2.32
- tři minuty po třetí hodině
- technická závada
- škodu vyšetřovatel předběžně vyčíslil na osm tisíc korun
- damage 8 000 CZK
- id_47443

- Information to be extracted is decorated.
- See the last sentence on the next slide.

Example of a linguistic tree



..., škodu vyšetřovatel předběžně vyčísil na osm tisíc korun.

..., investigating officer preliminarily reckoned the damage to be 8 000 CZK.

- Our IE method uses **tree queries** (tree patterns)

Accident attributes

attribute name	distinct values	missing values	monotonic
size (of file)	49	0	yes
type (of accident)	3	0	no
damage	18	30	yes
dur_minutes	30	17	yes
fatalities	4	0	yes
injuries	5	0	yes
cars	5	0	yes
amateur_units	7	1	yes
profesional_units	6	1	yes
pipes	7	8	yes
lather	3	2	yes
aqualung	3	3	yes
fan	3	2	yes
ranking	14	0	yes

- Information that we can/could extract from a report.
- Not everything is always mentioned.

Classical ILP and Fuzzy ILP principles

- Learning examples $E = P \cup N$ (Positive and Negative)
- Background knowledge B
- ILP task – to find hypothesis H such that:

$$(\forall e \in P)(B \cup H \models e) \ \& \ (\forall n \in N)(B \cup H \not\models n).$$

- Fuzzy learning examples $\mathcal{E} : E \longrightarrow [0, 1]$
- Fuzzy background knowledge $\mathcal{B} : B \longrightarrow [0, 1]$
- Fuzzy ILP task – to find hyp. $\mathcal{H} : H \longrightarrow [0, 1]$ such that:

$$(\forall e_1, e_2 \in E)(\forall \mathcal{M})(\mathcal{M} \models_f B \cup \mathcal{H}) : \mathcal{E}(e_1) > \mathcal{E}(e_2) \Rightarrow \|e_1\|_{\mathcal{M}} \geq \|e_2\|_{\mathcal{M}}$$

Generalized Annotated Programs

- Induction of Generalized Annotated Programs is equivalent¹ to Fuzzy ILP


¹See in S. Krajci, R. Lencses and P. Vojtas: “A comparison of fuzzy and annotated logic programming”, Fuzzy Sets and Systems, vol.144, pp.173–192, 2004.

Accident attributes

attribute name	distinct values	missing values	monotonic
size (of file)	49	0	yes
type (of accident)	3	0	no
damage	18	30	yes
dur_minutes	30	17	yes
fatalities	4	0	yes
injuries	5	0	yes
cars	5	0	yes
amateur_units	7	1	yes
profesional_units	6	1	yes
pipes	7	8	yes
lather	3	2	yes
aqualung	3	3	yes
fan	3	2	yes
ranking	14	0	yes

- Almost all attributes are **numeric**.
 - So **monotonic**
 - This will be used for “fuzzyfication”
- Artificial target attribute **seriousness ranking**.

Histogram of the seriousness ranking attribute



- 14 different values, range 0.5 – 8
- Divided into four approximately **equipotent** groups.

Essential difference between learning examples

Crisp learning examples

```
serious_2(id_47443). %positive
```

```
serious_0(id_47443). %negative
```

```
serious_1(id_47443). %negative
```

```
serious_3(id_47443). %negative
```

Monotonized learning examples

```
serious_atl_0(id_47443). %positive
```

```
serious_atl_1(id_47443). %positive
```

```
serious_atl_2(id_47443). %positive
```

```
serious_atl_3(id_47443). %negative
```

For one evidence
(occurrence):

- Crisp:
Always **one** positive
and **three** negative
learning examples
- Monotonized:
**Up to the observed
degree** positive,
the rest negative.

Monotonization of attributes

damage → damage_atl

```
damage_atl(ID,N) :- %unknown values
                    damage(ID,N), not(integer(N)).
damage_atl(ID,N) :- %numeric values
                    damage(ID,N2), integer(N2),
                    damage(N), integer(N), N2>=N.
```

- We infer all lower values as sufficient.
- Treatment of unknown values.
- Negation as failure.

serious_0(A):-dur_minutes(A,8).
 serious_0(A):-type(A,fire),pipes(A,0).
 serious_0(A):-fatalities(A,0),pipes(A,1),lather(A,0).
 serious_1(A):-amateur_units(A,1).
 serious_1(A):-amateur_units(A,0),pipes(A,2),aqualung(A,1).
 serious_1(A):-damage(A,300000).
 serious_1(A):-damage(A,unknown),type(A,fire),prof_units(A,1).
 serious_1(A):-dur_minutes(A,unknown),fatalities(A,0),cars(A,1).
 serious_2(A):-lather(A,unknown).
 serious_2(A):-lather(A,0),aqualung(A,1),fan(A,0).
 serious_2(A):-amateur_units(A,2),prof_units(A,2).
 serious_2(A):-dur_minutes(A,unknown),injuries(A,2).
 serious_3(A):-fatalities(A,1).
 serious_3(A):-fatalities(A,2).
 serious_3(A):-injuries(A,2),cars(A,2).
 serious_3(A):-pipes(A,4).

serious_atl_0(A).
 serious_atl_1(A):-injuries_atl(A,1).
 serious_atl_1(A):-lather_atl(A,1).
 serious_atl_1(A):-pipes_atl(A,3).
 serious_atl_1(A):-dur_minutes_atl(A,unknown).
 serious_atl_1(A):-size_atl(A,764),pipes_atl(A,1).
 serious_atl_1(A):-damage_atl(A,8000),amateur_units_atl(A,3).
 serious_atl_1(A):-type(A,car_accident).
 serious_atl_1(A):-pipes_atl(A,unknown),randomized_order_atl(A,35).
 serious_atl_2(A):-pipes_atl(A,3),aqualung_atl(A,1).
 serious_atl_2(A):-type(A,car_accident),cars_atl(A,2),prof_units_atl(A,2).
 serious_atl_2(A):-injuries_atl(A,1),prof_units_atl(A,3),fan_atl(A,0).
 serious_atl_2(A):-type(A,other),aqualung_atl(A,1).
 serious_atl_2(A):-dur_minutes_atl(A,59),pipes_atl(A,3).
 serious_atl_2(A):-injuries_atl(A,2),cars_atl(A,2).
 serious_atl_2(A):-fatalities_atl(A,1).
 serious_atl_3(A):-fatalities_atl(A,1).
 serious_atl_3(A):-dur_minutes_atl(A,unknown),pipes_atl(A,3).

- Crisp hypothesis
- Monotonized hypothesis

Evaluation and Comparison of Results

		Raw ILP	Monot. ILP
Monot. test set	TP:	42	57
	positive: 64	FP: 7	6
	negative: 36	Precision: 0,857	0,905
	sum: 100	Recall: 0,656	0,891
		F-measure: 0,743	0,898
Crisp test set	TP:	12	15
	positive: 25	FP: 13	10
	negative: 75	Precision: 0,480	0,600
	sum: 100	Recall: 0,480	0,600
		F-measure: 0,480	0,600

- Rules evaluated on both testing sets.
 - By use of conversion predicates (next slide)
- Monotonized rules **better in both cases.**

Conversion of Results

crisp \rightarrow monotone

```
serious_2(ID) :- serious_atl_2(ID),  
                not(serious_atl_3(ID)).
```

monotone \rightarrow crisp

```
serious_atl_0(ID) :- serious_2(ID).  
serious_atl_1(ID) :- serious_2(ID).  
serious_atl_2(ID) :- serious_2(ID).
```

Conclusion

- We used Fuzzy/GAP ILP in an **experiment** closely connect with WIE.
- Showed basic **principles and implementation** of Fuzzy/GAP ILP.
- Compared results of Fuzzy/GAP ILP and Classical ILP.
- Observed much better results in the Fuzzy case.