

Information Extraction using PDT Tools and Inductive Logic Programming

Jan Dědek

Department of Software Engineering, Faculty of Mathematics and Physics,
Charles University in Prague, Czech Republic

Aplikace NLP, 31. 3. 2011, MFF UK, Praha

Outline

1 Information Extraction Problem

- Information Extraction
- Example Tasks

2 Tools

- PDT
- GATE
- PDT in GATE

3 Our Solution

- Basic Idea
- Manually Created Rules
- Learning of Rules
 - Inductive Logic Programming
 - Integration of the extraction process
- Evaluation
- Conclusion

4 IE & the Semantic Web

Information Extraction Task

- The Task of Information Extraction
 - Automatically **find** the information you're looking for.
 - Pick out the **most useful bits**.
 - **Present** it in preferred manner, at the right level of detail.

“Axis” of Information Extraction

- Information depth

- “Document labeling”

The event started at half pas six.
 ↖time_expression

- Uniform representation (“Semantic interpretation”)

The event started at half pas six.
 ↖time_expression=18:30

- Task complexity

- Entity recognition

J. Dědek is a PhD student at the Charles Univ.
 ↖Person ↖Organization

- Relation extraction

J. Dědek is a PhD student at the Charles Univ.
 ↖Person →has_affiliation→ ↖Organization

1 Information Extraction Problem

- Information Extraction
- Example Tasks

2 Tools

- PDT
- GATE
- PDT in GATE

3 Our Solution

- Basic Idea
- Manually Created Rules
- Learning of Rules
 - Inductive Logic Programming
 - Integration of the extraction process
- Evaluation
- Conclusion

4 IE & the Semantic Web

Example Tasks

Example of the web-page with a report of a fire department




Ministerstvo vnitra
Zpravodajství
Informace z resortu o tom, co se stalo, co se děje i co se připravuje

[home](#)
[navigace](#)
[vyhledávání](#)
[změna vzhledu](#)

[HZS Jihomoravského kraje](#)
Zubatého 1, 614 00 Brno, telefon 950 630 111,
<http://www.firebrno.cz>
Zpravodajství v roce 2006



15.05.2007
V trabantu zemřeli dva lidé
K tragické nehodě dnes odpoledne hasiči vyjžděli na silnici z obce Česká do Kuřimi na Brněnsku.

Nehoda byla operačním střediskem HZS ohlášena ve 13.13 hodin a na místě zasahovala jednotka profesionálních hasičů ze stanice v Tišnově. Jednalo se o čelní srážku autobusu Karosa s vozidlem Trabant 601. Podle dostupných informací trabant jedoucí ve z Brna do Kuřimi zřejmě vyjel do protisměru, kde narazil do linkového autobusu dopravní společnosti ze Žďáru nad Sázavou. Ve zdemolovaném trabantu na místě zemřeli dva muži – 82letý senior a další muž, jehož totožnost zjišťují policisté.

Hasiči udělali na vozidle protipožární opatření a po vyšetření a zadokumentování nehody dopravní policií vrak trabantu zaklesnutý pod autobusem pomocí lana odtrhli. Po odstranění střechy trabantu pak z kabiny vyprostili těla obou mužů. Obě vozidla – trabant i autobus, pak postupně odstranili na kraj vozovky a uvolnili tak jeden jízdní pruh. Únik provozních kapalin nebyl zjištěn. Po 16. hodině pomohli vrak trabantu naložit k odtahu a asistovali při odtažení autobusu. Po úklidu vozovky krátce před 16.30 hod. místo nehody předali policistům a ukončili zásah.



Odkazy

[skrz menu](#)

Hasiči

- Generální ředitelství
- hl. m. Praha
- Jihočeský kraj
- Jihomoravský kraj
- Karlovarský kraj
- Královéhradecký kraj
- Liberecký kraj
- Moravskoslezský kraj
- Olomoucký kraj
- Pardubický kraj
- Píseňský kraj
- Středočeský kraj
- Ústecký kraj
- kraj Vysočina
- Zlínský kraj



V této rubrice Zpravodajství

- Aktualizace stránek
- Archiv zpravodajství
- Bleskové zpravodajství
- RSS
- Boj proti korupci
- Digitalní televize
- Hasiči
- Hlavní zprávy
- Ministerstvo
- Od dopisovatelů (neoficiální)
- Policie
- Regiony
- Servis nejen pro novináře
- Schengenská spolupráce
- WebEditorial

Na našem serveru v jiných rubrikách

- Aktuality Národního archivu

Text of an Accident Report and Contained Information

The diagram shows a text snippet from an accident report with several pieces of information highlighted in green boxes and connected to labels by arrows. The text is in Czech. The labels and their corresponding text are:

- fire** points to **Požár**.
- 3 amateur units** points to **3 amatérské jednotky**.
- started at** points to **2.13**.
- finished at 4:03** points to **4:03**.
- damage 8 000 CZK** points to **8 000 Kč**.

The text of the report is as follows:

Požár byl operace a střežící ZS ohlášen dnes ve 2.13 hodin, na místo vyjeli profesionální hasiči ze stanice v Židlochovicích a dobrovolní hasiči z Židlochovic, Žabčic a Přisnotic. Oheň, která vznikla při troinstalaci u chladicího boxu, hasiči dostali pod kontrolu ve 2.32 hodin a uhasili tři minuty po třetí hodině. Příčinou vzniku požáru byla technická závada, škodu vyšetřovatel předběžně vyčíslil na osm tisíc korun.

id_47443

- Information to be extracted is decorated.

Acquisitions Corpus

- Corporate Acquisition Events
- Acquisitions v1.1 version¹

<p>FIRST WISCONSIN <FWB> TO BUY MINNESOTA BANK MILWAUKEE, Wis., March 26 - First Wisconsin Corp said it plans to acquire Shelard Bancshares Inc for about 25 mln dlrs in cash, its first acquisition of a Minnesota-based bank.</p> <p>First Wisconsin said Shelard is the holding company for two banks with total assets of 168 mln dlrs.</p> <p>First Wisconsin, which had assets at yearend of 7.1 billion dlrs, said the Shelard purchase price is about 12 times the 1986 earnings of the bank.</p> <p>It said the two Shelard banks have a total of five offices in the Minneapolis-St. Paul area.</p> <p>Reuter</p>	<p>Key</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> acqabr <input checked="" type="checkbox"/> acqbus <input checked="" type="checkbox"/> acqloc <input checked="" type="checkbox"/> acquired <input checked="" type="checkbox"/> dlramt <input type="checkbox"/> doc <input checked="" type="checkbox"/> purchabr <input checked="" type="checkbox"/> purchaser <input checked="" type="checkbox"/> purchcode
--	--

¹from the Dot.kom project's resources:

1 Information Extraction Problem

- Information Extraction
- Example Tasks

2 Tools


- PDT
- GATE
- PDT in GATE

3 Our Solution

- Basic Idea
- Manually Created Rules
- Learning of Rules
 - Inductive Logic Programming
 - Integration of the extraction process
- Evaluation
- Conclusion

4 IE & the Semantic Web

Layers of linguistic annotation in PDT



- Tectogrammatical layer
- Analytical layer
- Morphological layer
- PDT 2.0 on-line:

<http://ufal.mff.cuni.cz/pdt2.0/>

Sentence:


Byl by šel dolesa.

He-was would went toforest.

Tools for machine linguistic annotation

- ① Segmentation and tokenization
 - ② Morphological analysis
 - ③ Morphological tagging
 - ④ McDonald's Maximum Spanning Tree parser
 - Czech adaptation
 - ⑤ Analytical function assignment
 - ⑥ Tectogrammatical analysis
 - Developed by Václav Klimeš
- Available within the **TectoMT²** project

²<http://ufal.mff.cuni.cz/tectomt/>



- Lemmas
- Functors
- Semantic parts of speech

Sentence:

Ve zdemolovaném trabantu na místě zemřeli dva muži – 82letý senior a další muž, jehož totožnost zjišťují policisté.

Two men died on the spot in demolished trabant – ...

Netgraph

- <http://quest.ms.mff.cuni.cz/netgraph/>
- PML Tree Query
- Query Engine and Query Language for TreeBanks
- <http://ufal.mff.cuni.cz/~pajas/pmltq/>

GATE info



- General Architecture for Text Engineering
- University of Sheffield, UK
- Natural Language Processing (NLP)
- Information Extraction (IE)
- Text Annotation
- Developed in **Java**
- `http://gate.ac.uk/`

GATE features

- Document and annotation management
- Language and processing utility resources
 - Taggers, Parsers, Coreference-processors, Named entity recognizers, Alignment tools, WordNet, Yahoo search, etc
- JAPE grammar rules
- Performance evaluation tools
- Machine learning facilities
- Ontology support

GATE screen shot

File Options Tools Help

ATE

Applications

rename-FAO-anno...

Language Resources

S0FNTC~

S01121~

Processing Resources

BeanShell

Data stores

file:/home/dian...

Messages

rename-FAO-anno...

Annotation Sets Annotations List Co-reference Editor OAT Text

This species reaches a maximum size of 445 cm total length and about 540 kg weight. The size range of fish taken by the commercial swordfish longliners is 120 to 190 cm body length in the northwestern Pacific; the average weight in the Mediterranean Sea ranges from 115 to 160 kg. Usually females are larger than males, and most swordfish over 140 kg are females. Adults grow over 230 kg (rarely) in the Mediterranean, up to 320 kg in the western Atlantic, and up to 537 kg in the southeast. The all-tackle-angling record for this species is a 536 kg fish caught off Iquique, Chile in 1953. There is little biological minimum size and age and some of the

Key

Location

Original markups

Type	Set	Start	End	Id	Features
Location	Key	3067	3084	850	{kind=water}

1 Annotations (1 selected) Select: [] New


Document Editor Initialisation Parameters

Views built!

Integration of PDT in GATE

- Implemented **Batch TectoMT Language Analyzer**
 - Transformation of PDT annotations to GATE
- **Netgraph** used as a tree viewer
 - Works also for Stanford Dependencies
- `http://czsem.berlios.de/`

Netgraph Tree Viewer in GATE (for Stanford Dependencies)



Sentence: Users also said it is in the strongest financial position in its 24-year history.

1 Information Extraction Problem

- Information Extraction
- Example Tasks

2 Tools

- PDT
- GATE
- PDT in GATE

3 Our Solution

- Basic Idea
- Manually Created Rules
- Learning of Rules
 - Inductive Logic Programming
 - Integration of the extraction process
- Evaluation
- Conclusion

4 IE & the Semantic Web


How to extract the information about the damage of the accident?

Diagram illustrating information extraction from a text snippet. The text is in Czech and describes a fire incident. Key entities and values are highlighted in green boxes, and callouts point to them:

- fire
- 3 amateur units
- started at
- 2.13
- finished at 4:03
- trůinstalaci u chladícího boxu, hasiči dostali pod kontrolu ve 2.32 hodin a uhasili tři
- minuty po třetí hodině
- osm tisíc
- korun
- damage 8 000 CZK
- id_47443

- How to extract the information about the damage of the accident?
- See the last sentence on the **next slide**.

Corresponding linguistic tree



..., škodu vyšetřovatel předběžně vyčíslil na osm tisíc korun.


..., investigating officer preliminarily reckoned the damage to be 8 000 CZK.

- Basic Idea: use **tree queries** (tree patterns) to extract the information.

Introduction of Our Solution

- Extraction of semantic information from texts.
- Exploiting of linguistic tools.
 - Mainly “from” the **Prague Dependency Treebank** project.
 - Related tools – language analyzers (TectoMT), Netgraph, etc.
 - Experiments with the Czech WordNet.
- **Rule based** extraction method.
 - Extraction rules \approx **tree queries**
 - ILP **learning** of extraction rules

Schema of the extraction process



- 1 Extraction of text
 - Using **RSS feed** to download pages.
 - **Regular expression** to extract text.
- 2 Linguistic annotation
 - Using **chain** of 6 linguistic tools (see on next slides).
- 3 Data extraction
 - Exploitation of linguistic trees.
 - Using **extraction rules**.
- 4 Semantic representation of data
 - Ontology needed.
 - Semantic interpretation of rules.
 - Far from finished in current state.

1 Information Extraction Problem

- Information Extraction
- Example Tasks

2 Tools


- PDT
- GATE
- PDT in GATE

3 Our Solution

- Basic Idea
- **Manually Created Rules**
- Learning of Rules
 - Inductive Logic Programming
 - Integration of the extraction process
- Evaluation
- Conclusion

4 IE & the Semantic Web

Extraction rules – Netgraph queries



- Tree patterns on **shape** and **nodes** (on node attributes).
- Evaluation gives **actual matches** of particular nodes.
- **Names** of nodes allow use of references.

Manually Created Rules

Raw data extraction output

```


<QueryMatches>
  <Match root_id="T-vysocina63466.txt-001-pls4" match_string="2:0,7:3,8:4,11:2">
    <Sentence>
      Při požáru byla jedna osoba lehce zraněna - jednalo se
      o majitele domu, který si vykloubil rameno.
    </Sentence>
    <Data>
      <Value variable_name="action_type" attribute_name="t_lemma">zranit</Value>
      <Value variable_name="injury_manner" attribute_name="t_lemma">lehký</Value>
      <Value variable_name="participant" attribute_name="t_lemma">osoba</Value>
      <Value variable_name="quantity" attribute_name="t_lemma">jeden</Value>
    </Data>
  </Match>
  <Match root_id="T-jihomoravsky49640.txt-001-pls4" match_string="1:0,13:3,14:4">
    <Sentence>
      Ve zdemolovaném trabantu na místě zemřeli dva muži - 82letý senior
      a další muž, jehož totožnost zjišťují policisté.
    </Sentence>
    <Data>
      <Value variable_name="action_type" attribute_name="t_lemma">zemřít</Value>
      <Value variable_name="participant" attribute_name="t_lemma">muž</Value>
      <Value variable_name="quantity" attribute_name="t_lemma">dva</Value>
    </Data>
  </Match>
  <Match root_id="T-jihomoravsky49736.txt-001-p4s3" match_string="1:0,3:3,7:1">
    <Sentence>Ctyřiatřicetiletý řidič nebyl zraněn.</Sentence>
    <Data>
      <Value variable_name="action_type" attribute_name="t_lemma">zranit</Value>
      <Value variable_name="a-negation" attribute_name="m/tag">VpYS---XRⓃA---
      </Value>
      <Value variable_name="participant" attribute_name="t_lemma">řidič</Value>
    </Data>
  </Match>
</QueryMatches>

```



SELECT **action_type.t_lemma**, **a-negation.mtag**, **injury_manner.t_lemma**,
participant.t_lemma, **quantity.t_lemma** FROM ****extraction rule****

Extraction rules – Environment Protection Use Case




Manually Created Rules

Matching Tree

"Due to the clash the throat of fuel tank tore off and 800 litres of oil (diesel) has run out to a stream."

"Nárazem se utrhlo hrdlo palivové nádrže a do potoka postupně vyteklo na 800 litrů nafty."



Raw data extraction output

```

<QueryMatches>
  <Match root_id="jihmor56559.txt-001-pls3" match_string="15:0,16:4,22:1,23:2,27:3">
    <Sentence>Nárazem se utrhhl hrdlo palivové nádrže a do potoka postupně vyteklo na
800 litrů nafty.</Sentence>
    <Data>
      <Value variable_name="amount" attribute_name="t_lemma">800</Value>
      <Value variable_name="unit" attribute_name="t_lemma">1</Value>
      <Value variable_name="material" attribute_name="t_lemma">nafta</Value>
      <Value variable_name="where" attribute_name="t_lemma">potok</Value>
    </Data>
  </Match>
  <Match root_id="jihmor68220.txt-001-pls3" match_string="3:0,12:4,21:1,22:2,27:3">
    <Sentence>Z palivové nádrže vozidla uniklo do půdy v příkopu vedle silnice zhruba
350 litrů nafty, a proto byli o události informováni také pracovníci odboru životního
prostředí Městského úřadu ve Vyškově a České inspekce životního prostředí.</Sentence>
    <Data>
      <Value variable_name="amount" attribute_name="t_lemma">350</Value>
      <Value variable_name="unit" attribute_name="t_lemma">1</Value>
      <Value variable_name="material" attribute_name="t_lemma">nafta</Value>
      <Value variable_name="where" attribute_name="t_lemma">půda</Value>
    </Data>
  </Match>
  ...

```

Diagram illustrating the raw data extraction output with annotations:


- litre**: Points to the unit "1" in the first match.
- water stream**: Points to the material "nafta" in the first match.
- diesel**: Points to the material "nafta" in the first match.
- soil**: Points to the material "půda" in the second match.

```

SELECT amount.t_lemma, unit.t_lemma, material.t_lemma, where.t_lemma
FROM ***extraction rule***

```

Design of extraction rules – iterative process



- 1 **Frequency analysis** → representative key-words.
- 2 Investigating of matching trees → **tuning** of tree query.
- 3 **Complexity** of the query \cong complexity of extracted data.

Corpus of Fire-department articles

- Fire-department articles
- Published by The Ministry of Interior of the Czech Republic³
- Processed more than 800 articles from different regions of Czech Republic
- 1.2 MB of textual data
- Linguistic tools produced 10 MB of annotations, run time 3.5 hours
- Extracting information about injured and killed people
- 470 matches of the extraction rule, 200 numeric values of quantity (described later)

³<http://www.mvcr.cz/rss/regionhzs.html>

1 Information Extraction Problem

- Information Extraction
- Example Tasks

2 Tools

- PDT
- GATE
- PDT in GATE

3 Our Solution

- Basic Idea
- Manually Created Rules
- Learning of Rules
 - Inductive Logic Programming
 - Integration of the extraction process
- Evaluation
- Conclusion

4 IE & the Semantic Web

Inductive Logic Programming

- Inductive Logic Programming (ILP)
 - is a Machine Learning procedure for **multirelational** learning
 - Heuristic and iterative method, learning is usually slow
 - It is capable to deal with graph or **tree structures** naturally
 - Learns form positive and negative **examples**
 - Positive and negative **tree nodes**
 - It is necessary to **label tree nodes** from corresponding labeled text (not trivial problem)
- Learned rules are strict (no weights, probabilities, etc.)
 - Easier human understanding, modification
 - Possibility of sharing of rules amongst different tools
 - Lower performance (precision, recall)

ILP principles

- Learning examples $E = P \cup N$ (Positive and Negative)
- Background knowledge B
- ILP task – to find hypothesis H such that:

$$(\forall e \in P)(B \cup H \models e) \ \& \ (\forall n \in N)(B \cup H \not\models n).$$

ILP Example

Types of ground variables

```
animal(dog). animal(dolphin) ... animal(penguin).  
class(mammal). class(fish). class(reptile). class(bird).  
covering(hair). covering(none). covering(scales).  
habitat(land). habitat(water). habitat(air).
```

Background knowledge

```
has_covering(dog, hair). has_covering(crocodile, scales).  
has_legs(dog, 4). ... has_legs(penguin, 2). etc.  
has_milk(dog). ... has_milk(platypus). etc.  
homeothermic(dog). ... homeothermic(penguin). etc.  
habitat(dog, land). ... habitat(penguin, water). etc.  
has_eggs(platypus). ... has_eggs(eagle). etc.  
has_gills(trout). ... has_gills(eel). etc.
```

ILP Example

Positive examples

```
class(lizard, reptile).  
class(trout, fish).  
class(bat, mammal).
```


Negative examples

```
class(trout, mammal).  
class(herring, mammal).  
class(platypus, reptile).
```

Induced rules

```
class(A, reptile) :- has_covering(A, scales),  
                    has_legs(A, 4).  
class(A, mammal) :- homeothermic(A), has_milk(A).  
class(A, fish) :- has_legs(A, 0), has_eggs(A).  
class(A, reptile) :- has_covering(A, scales),  
                    habitat(A, land).  
class(A, bird) :- has_covering(A, feathers).
```

Integration of ILP in our extraction process



- Main point: transformation of trees to **logic representation**.
- Human annotator does **not** need to be a linguistic **expert**.

Learning of Rules

Logic representation of linguistic trees



Zpravodajství

ČZS Jihoomoravského kraje

15.05.2007


V trabantu zemřeli dva lidé

K tragické nehodě dnes dopoledne hasiči vyjžděli na silnici z obce Čoska do Kuliší na Brněnsku.

Nehoda byla spornějším způsobem zjištěna ve 13.15 hodin. Na místě zasahovala jednotka profesionálních hasičů ze stanice Hřbitovní. Jednalo se o bílý sňahu autobus Karosa s vozidlem Trabant. Po dostupných informacích trabant jedoucí ve zřímě do Kuliší. Přemě vylze do předsměti, kde narážel do linkového autobusu dopravce. Nehoda ze zřímě nad Sazavou. Ve zdemolovaném trabantu n. místě zemřeli dva muži – řidič a senior a další muž, jehož totožnost zatím není známa.

Hasiči ušli na vozidlo protipožární opatření a po vyšetření dokumentování nehody dopravní policí vrak trabantu zakázali na autobus pomocí lane odtrhli. Po odstranění střechy trabantu pak byly vyprázdněny těla obou mužů. Obě vozidla – trabant i autobus, po dopravní odstraňování na kraj vozovky a uvolnění tak jeden jízdní pruh. Uševních kapalin nebyl zjištěn. Po 18. hodině pomohli vrak trabantu k rozložení a asistovali při odtažení autobusu. Po ukončení vozovky od 16.30 hod. místo nehody otevřeli policisté a uvolnili zemi.

Source web page




```
tree_root(node0_0). node(node0_0).
id(node0_0, t_jihomoravsky49640_txt_001_pls4).
***** node0_1 *****
node(node0_1).
functor(node0_1, pred).
gram_sempos(node0_1, v).
t_lemma(node0_1, zemrit).
***** node0_2 *****
node(node0_2).
functor(node0_2, act).
gram_sempos(node0_2, n_pron_def_pers).
t_lemma(node0_2, x_perspron).
***** node0_3 *****
node(node0_3). id(node0_3,
functor(node0_3, loc).
gram_sempos(node0_3, n_denot).
t_lemma(node0_3, trabant).
...
edge(node0_0, node0_1). edge(node0_1, node0_2).
edge(node0_1, node0_3). edge(node0_3, node0_4).
edge(node0_4, node0_5). edge(node0_5, node0_6).
edge(node0_3, node0_7). edge(node0_3, node0_8).
```

Logic representation

Linguistic trees

Root/Subtree Preprocessing/Postprocessing (Chunk learning)



..., škodu vyšetřovatel předběžně vyčísлил na **osm tisíc korun**.

..., investigating officer preliminarily reckoned the damage to be **eight thousand Crowns** (CZK).

Examples of learned rules, Czech words are translated.

Example

[Rule 1] [Pos cover = 14 Neg cover = 0]

```
damage_root(A) :- lex_rf(B,A), has_sempos(B,'n.quant.def'),
    tDependency(C,B), tDependency(C,D),
    has_t_lemma(D,'investigator').
```

[Rule 2] [Pos cover = 13 Neg cover = 0]

```
damage_root(A) :- lex_rf(B,A), has_functor(B,'TOWH'),
    tDependency(C,B), tDependency(C,D), has_t_lemma(D,'damage').
```

[Rule 1] [Pos cover = 7 Neg cover = 0]

```
injuries(A) :- lex_rf(B,A), has_functor(B,'PAT'),
    has_gender(B,anim), tDependency(B,C), has_t_lemma(C,'injured').
```

[Rule 8] [Pos cover = 6 Neg cover = 0]

```
injuries(A) :- lex_rf(B,A), has_gender(B,anim), tDependency(C,B),
    has_t_lemma(C,'injure'), has_negation(C,neg0).
```

Evaluation results

task/method	matching	missing	excess	overlap	prec.%	recall%	F1.0%
damage/ILP	14	0	7	6	51.85	70.00	59.57
damage/ILP – lenient measures					74.07	100.00	85.11
dam./ILP-roots	16	4	2	0	88.89	80.00	84.21
damage/Paum	20	0	6	0	76.92	100.00	86.96
injuries/ILP	15	18	11	0	57.69	45.45	50.85
injuries/Paum	25	8	54	0	31.65	75.76	44.64
inj./Paum-afun	24	9	38	0	38.71	72.73	50.53

- 10-fold cross validation
- Two tasks: ‘damage’ and ‘injuries’
- Root/subtree preprocessing/postprocessing used for ‘damage’ task

1 Information Extraction Problem

- Information Extraction
- Example Tasks

2 Tools

- PDT
- GATE
- PDT in GATE

3 Our Solution

- Basic Idea
- Manually Created Rules
- Learning of Rules
 - Inductive Logic Programming
 - Integration of the extraction process
- Evaluation
- Conclusion

4 IE & the Semantic Web

Summary

- Implemented a system for extraction of semantic information
- Based on third party linguistic tools (**TectoMT**⁴)
- Extraction rules adopted from **Netgraph**⁵ application.
- **ILP** used for learning rules.
- All methods integrated inside **GATE**⁶.
- Main advantages:
 - Automated selection of learning features
 - “Language independent”
 - Rule based

⁴<http://ufal.mff.cuni.cz/tectomt/>

⁵<http://quest.ms.mff.cuni.cz/netgraph/>

⁶<http://gate.ac.uk/>

Future work

- Use some **Knowledge Base** (e.g. WordNet).
- Adaptation of this method on **other languages**.
- Evaluation of the method on **other datasets**.
- Be able to provide **more semantics**.
 - e.g. sophisticated semantic interpretation of extracted data

1 Information Extraction Problem

- Information Extraction
- Example Tasks

2 Tools

- PDT
- GATE
- PDT in GATE

3 Our Solution

- Basic Idea
- Manually Created Rules
- Learning of Rules
 - Inductive Logic Programming
 - Integration of the extraction process
- Evaluation
- Conclusion


4 IE & the Semantic Web

Semantic Web Introduction

We use semantic web **ontologies** to express the semantics.

- RDF, OWL languages
- Motivated by description logics
- Concepts or **Classes**
- Predicates or **Relations**
- Individuals or **Instances**
- RDF **triples**: <Subject> <Predicate> <Object>
- RDF triples form a **named oriented graph**
 - Basic data structure of the Semantic Web

Ontology (example)



- PROTON (PROTo ONtology)

<http://proton.semanticweb.org/>

1 Information Extraction Problem

- Information Extraction
- Example Tasks

2 Tools

- PDT
- GATE
- PDT in GATE


3 Our Solution

- Basic Idea
- Manually Created Rules
- Learning of Rules
 - Inductive Logic Programming
 - Integration of the extraction process
- Evaluation
- Conclusion

4 IE & the Semantic Web

Semantic Annotation (<http://www.ontotext.com/kim/>)

XYZ announced profits in Q3, planning to build a \$120M plant in Bulgaria, and more and more and more and more text



1 Information Extraction Problem

- Information Extraction
- Example Tasks

2 Tools


- PDT
- GATE
- PDT in GATE

3 Our Solution

- Basic Idea
- Manually Created Rules
- Learning of Rules
 - Inductive Logic Programming
 - Integration of the extraction process
- Evaluation
- Conclusion


4 IE & the Semantic Web

Semantic interpretation of extraction rules



- Determines how particular values of attributes are used.
- Gives semantics to extraction rule.
- Gives semantics to extracted data.


Semantic data output



- Two instances of two ontology classes.

The experimental ontology

Incident		
actionManner	String*	
negation	Boolean	
actionType	String	
hasParticipant	Instance*	Participant



Participant	
participantType	String
participantQuantity	Integer

- Two **classes**
 - Incident and Participant
- One **object property** relation
 - hasParticipant
- Five **datatype property** relations
 - actionManner
(light or heavy injury)
 - negation
 - actionType
(injury or death)
 - participantType
(man, woman, driver, etc.)
 - participantQuantity

1 Information Extraction Problem

- Information Extraction
- Example Tasks

2 Tools

- PDT
- GATE
- PDT in GATE

3 Our Solution


- Basic Idea
- Manually Created Rules
- Learning of Rules
 - Inductive Logic Programming
 - Integration of the extraction process
- Evaluation
- Conclusion

4 IE & the Semantic Web

Transformation of PML to RDF

- Quite simple XSLT transformation
- Allows working with PDT annotations inside Semantic Web tools
 - Ontology Editors
 - Reasoners
 - Query tools (graph queries)
 - ?Visualization and navigation tools?
- In our case interpretation of extraction rules by a OWL reasoner

Extraction Rules Interpreted by OWL Reasoner



- Tool **independent** extraction ontologies

PDT in The Protégé Ontology Editor

The screenshot displays the Protégé Ontology Editor interface for the ontology `node/SCzechA-s4-w13`. The interface is divided into three main panels:

- Types Panel (Top Left):** Shows the hierarchy of types. `MentionRoot` is highlighted with a red circle. Below it are `Node` and `Thing`. The "Same individuals" and "Different individuals" options are also visible.
- Members list Panel (Bottom Left):** Lists the members of the ontology. The member `node/SCzechA-s4-w13` is highlighted with a blue background.
- Property assertions Panel (Right):** Shows the property assertions for the selected member. The `mention_root "damage"` assertion is highlighted with a red circle. Other assertions include `hasParent node/SCzechA-s4-w12`, `m.rf node/SCzechM-s4-w13`, `hasChild node/SCzechA-s4-w14`, `lemma "osm1408"`, `edge_to_collapse "1"^^PlainLiteral`, `ord "13"`, `afun "Obj"`, `edge_to_collapse "1"`, `afun "Obj"^^PlainLiteral`, `form "osm"`, `tag "Cn-S4-----"^^PlainLiteral`, `is_auxiliary "0"`, `form "osm"^^PlainLiteral`, `is_auxiliary "0"^^PlainLiteral`, `tag "Cn-S4-----"`, `lemma "osm`8"^^PlainLiteral`, and `ord "13"^^PlainLiteral`.

Examples of extraction rules in the native Prolog format.

[Rule 1] [Pos cover = 23 Neg cover = 6]

```
mention_root(acquired,A) :-
    'lex.rf'(B,A), t_lemma(B,'Inc'), tDependency(C,B),
    tDependency(C,D), formeme(D,'n:in+X'), tDependency(E,C).
```

[Rule 11] [Pos cover = 25 Neg cover = 6]

```
mention_root(acquired,A) :-
    'lex.rf'(B,A), t_lemma(B,'Inc'), tDependency(C,B),
    formeme(C,'n:obj'), tDependency(C,D), functor(D,'APP').
```

[Rule 75] [Pos cover = 14 Neg cover = 1]

```
mention_root(acquired,A) :-
    'lex.rf'(B,A), t_lemma(B,'Inc'), functor(B,'APP'),
    tDependency(C,B), number(C,pl).
```

Examples of extraction rules in Protégé 4 – Rules View's format

[Rule 1]

```
lex.rf(?b, ?a), t_lemma(?b, "Inc"), tDependency(?c, ?b),
tDependency(?c, ?d), formeme(?d, "n:in+X"),
tDependency(?c, ?e)
    -> mention_root(?a, "acquired")
```

[Rule 11]

```
lex.rf(?b, ?a), t_lemma(?b, "Inc"), tDependency(?c, ?b),
formeme(?c, "n:obj"), tDependency(?c, ?d), functor(?d, "APP")
    -> mention_root(?a, "acquired")
```

[Rule 75]

```
lex.rf(?b, ?a), t_lemma(?b, "Inc"), functor(?b, "APP"),
tDependency(?c, ?b), number(?c, "pl")
    -> mention_root(?a, "acquired")
```