Upwatch documentation

Ron Arts

Upwatch documentation

by Ron Arts

Copyright © 2002 by UpWatch BV, The Netherlands

Table of Contents

Pretace		I
1. About UpWatch		1
-		
•		
O I		
	irements	
<u> </u>	nents	
<u>-</u>	icits	
1 - 1		
1 0	S	
•	3	
S		
_	1	
0 0		
4.3. Queues		7
5. How it all works		8
5.1. General Overview		8
5.1.1. The Upwatch c	client	8
5.1.2. The Upwatch s	server	8
5.1.3. The Upwatch n	nonitors	8
5.1.4. Special program	ms	8
5.2. A Detailed Description	1	8
5.2.1. Database Layo	ut	9
5.2.2. What a probe d	loes	9
5.2.3. What happens	to the probe results?	9
5.2.4. uw_process: ste	oring results in the database	9
5.3. Scaling up		11
A. Interfaces and file layouts		12
A.1. Probe result file		12
	ıe	
	file layout	
	otocol	
-	ric probe	
9	d layout	
	yout	
•	System probe	
2 0	record layout	
-	ise layout	
-	GET request	
1.0	ecord layout	
	J	

	B.3.2. httpget database layout	. 17
	B.4. imap - Test a IMAP server, optionally with user/password	.18
	B.4.1. imap result record layout	.18
	B.4.2. imap database layout	. 19
	B.5. iptraf - Incoming and outgoing traffic to an IP adddress, network or interface	.20
	B.5.1. iptraf result record layout	.20
	B.5.2. iptraf database layout	.20
	B.6. mssql - Do a Microsoft SQL Server query	.21
	B.6.1. mssql result record layout	
	B.6.2. mssql database layout	.22
	B.7. mysql - Do a MySQL query	.23
	B.7.1. mysql result record layout	.23
	B.7.2. mysql database layout	. 24
	B.8. ping - send ICMP echo requests	
	B.8.1. ping result record layout	
	B.8.2. ping database layout	
	B.9. pop3 - Test a POP3 server, optionally with user/password	
	B.9.1. pop3 result record layout	
	B.9.2. pop3 database layout	
	B.10. postgresql - Do a PostgreSQL query	
	B.10.1. postgresql result record layout	
	B.10.2. postgresql database layout	
	B.11. smtp - Test an SMTP server	
	B.11.1. smtp result record layout	
	B.11.2. smtp database layout	
	B.12. snmpget - Query an SNMP variable using an SNMP GET	
	B.12.1. snmpget result record layout	
	B.12.2. snmpget database layout	
	B.13. sysstat - System information like load average, CPU/MEM usage etc	
	B.13.1. sysstat result record layout	
	B.13.2. sysstat database layout	
	B.14. hwstat - Hardware information like CPU temperature, fan speed	
	B.14.1. hwstat result record layout	
	B.14.2. hwstat database layout	
	B.15. errlog - System error log analysis	
	B.15.1. errlog result record layout	
	B.15.2. errlog database layout	
	B.16. diskfree - Free disk space	
	B.16.1. diskfree result record layout	.40
	B.16.2. diskfree database layout	.40
	B.17. tcpconnect - Connect to a TCP port	
	B.17.1. tcpconnect result record layout	
	B.17.2. tcpconnect database layout	
C. A	dding a probedding a probe	
_,,,	C.1. So you want to add a probe?	
	C.2. Basic steps for adding a probe	
	C.2.1. Think carefully before you start	
	C.2.2. Pick a real good name	
	C.2.3. Design the Database Fields	
	C.2.4. Write the code	
	C.2.5. Write the uw_process extension.	
	C.2.3. WITH HIC AW_PLOCESS CALCIDION	.+J

C.2.6. Add PHP pages_to_CMS	45
C.2.7. Write documentation	
C.3. Non-standard Probes	45
Index	46

List of Tables

bb attributes. bb attributes	13
bb elements. bb elements	13
bb definition record layout. bb definition record layout	13
bb result record layout. bb result record layout	14
bb_cpu attributes. bb_cpu attributes	14
bb_cpu elements. bb_cpu elements	15
bb_cpu definition record layout. bb_cpu definition record layout	15
bb_cpu result record layout. bb_cpu result record layout	15
httpget attributes. httpget attributes	16
httpget elements. httpget elements	17
httpget definition record layout. httpget definition record layout	
httpget result record layout. httpget result record layout	
imap attributes. imap attributes	18
imap elements. imap elements	
imap definition record layout. imap definition record layout	
imap result record layout. imap result record layout	
iptraf attributes. iptraf attributes	
iptraf elements. iptraf elements	
iptraf definition record layout. iptraf definition record layout	
iptraf result record layout. iptraf result record layout	
mssql attributes. mssql attributes	
mssql elements. mssql elements	
mssql definition record layout. mssql definition record layout	
mssql result record layout. mssql result record layout	
mysql attributes. mysql attributes	
mysql elements. mysql elements	
mysql definition record layout. mysql definition record layout	
mysql result record layout. mysql result record layout	
ping attributes. ping attributes	
ping elements. ping elements	25
ping definition record layout. ping definition record layout	26
ping result record layout. ping result record layout	26
pop3 attributes. pop3 attributes	27
pop3 elements. pop3 elements	27
pop3 definition record layout. pop3 definition record layout	27
pop3 result record layout. pop3 result record layout	28
postgresql attributes. postgresql attributes	28
postgresql elements. postgresql elements	29
postgresql definition record layout. postgresql definition record layout	29
postgresql result record layout. postgresql result record layout	30
smtp attributes. smtp attributes	30
smtp elements. smtp elements	
smtp definition record layout. smtp definition record layout	31
smtp result record layout. smtp result record layout	31
snmpget attributes. snmpget attributes	32
snmpget elements. snmpget elements.	32
snmpget definition record layout. snmpget definition record layout	32
snmpget result record layout. snmpget result record layout	33
sysstat attributes, sysstat attributes	34

sysstat elements. sysstat elements	34
sysstat definition record layout. sysstat definition record layout	34
sysstat result record layout. sysstat result record layout	35
hwstat attributes. hwstat attributes	
hwstat elements. hwstat elements	
hwstat definition record layout. hwstat definition record layout	37
hwstat result record layout. hwstat result record layout	38
errlog attributes. errlog attributes	39
errlog elements. errlog elements	39
errlog definition record layout. errlog definition record layout	39
errlog result record layout. errlog result record layout	39
diskfree attributes. diskfree attributes	40
diskfree elements. diskfree elements	40
diskfree definition record layout. diskfree definition record layout	40
diskfree result record layout. diskfree result record layout	41
tepeonnect attributes. tepeonnect attributes	41
tcpconnect elements. tcpconnect elements	42
tepconnect definition record layout. tepconnect definition record layout	
tcpconnect result record layout. tcpconnect result record layout	42

Preface

People, especially managers, like to have facts and figures when taking decisions, either because a lot of money may be involved, or their job (or both). If you want to prove your website (or switch, or basically any other device) was available, showed the proper performance, or just want to know current and past CPU load, you've come to the right place.

Chapter 1. About UpWatch

1.1. History

UpWatch originated from the loins of Netland Internet Services BV, located in Amsterdam, The Netherlands. It is a hosting company which started business in 1993.

We started to offer managed hosting services in 1995. Very soon we found out that our customers managed to bring down their own server at impossible times, and requested immediate support to bring it back up again. We weren't happy with this, but so weren't our customers. They demanded uptime and response time guarantees. We on our hand wanted to find out if downtime was our fault or the customers doing.

We started doing Service Level Agreements, and started monitoring. Also we started to limits our customers' access to their own servers. If they want guarantees, they should give us some power.

The monitoring system we initially chose was Big Brother (http://bb4.com). This really is a great package, but it had some problems for us. It didn't look professional (we felt we couldn't give the URL to our customers), it wasn't opensource, it was absolutely not scalable, and it was hard to integrate with our backoffice.

Also the CEO of Netland (yours truly) was considering setting up a internet service company for monitoring servers over the internet. And that needed scalable software. So in 2000 we started designing, and programming. All this resulted in UpWatch.

1.2. Features

With Upwatch you can both monitor various parameters continuously, and built a history of output values. So when for example you get complaints that you website was slow on Saturday evening, you can look back and find out if it was true, and even pinpoint a cause. So here's the full feature list:

- opensource: Apache/PHP/MySQL frontend, C/Perl backend
- fully documented, manpages and part of the docs are auto-generated
- efficient: supports more then 10s of thousands of probes
- · reliable: forgiving towards database and network failures
- scalable: processing can be spread out over multiple machines
- multitenanting support: monitor more than one company
- · supports multiple monitoring locations
- · clients available for Linux, *BDS, Windows
- · clients know about dialup
- · notifications by email and SMS
- Big Brother support: can run with BB clients, imports bb-hosts file
- · Probes can be added through the web interface
- remote probes: HTTP GET, IMAP, MSSQL, MySQL, ping, POP3, PostgreSQL, SMTP, SNMP, TCP Connect any port

- local probes: CPU, loadavg, memory, blockio, swap, diskspace, temperature, fanspeed, line voltages, analyse any logfile with regular expressions.
- special probe iptraf, you can install that on your core routers to measure IP traffic to/from every IP address on your internal network
- results are XML format, and can be pre/post processed
- uses store/forward in maildir queues for monitoring results
- OS support: clients for Linux, FreeBSD, Windows. Server runs on Linux or freeBSD, monitors run on linux. SuSE/Redhat/Fedora RPM's can be generated from the source tree.
- generates realtime raw, daily, weekly, monthly, yearly and 5-yearly graphical reports
- overview screens for server statuses
- you can temporarily hide or disable probes

Chapter 2. Installation

2.1. Getting upwatch

Currently, upwatch is not released, and is not allowed to be distributed. The only way to get it, is through written permission of UpWatch BV.

If you aquired that, you will either receive access to CVS, or will receive a tar.gz file, or .RPM's.

Building and installing upwatch is not for the faint of heart. It uses lots of external libraries which may or may not be available on your platform. I myself use Redhat 8/9 for development, and test compilation on RH7, Fedora Core 1/2, SuSE8.2, Solaris, FreeBSD, and Yellowdog Linux 3.0.

2.2. Requirements

2.2.1. Run-time requirements

First ensure that the time/date on all hosts is correctly set.

Run time requirements differ per probe. Look in the corresponding .def file (or in the spec file for the probe), here's a list of everything we expect on a machine running all probes, and the database (I'll also list the version we use ourselves):

- glib2 >= 2.0.4
- xml2 (any version will do)
- freetds >= 0.6.0 compiled with --enable-threadsafe
- mysql 3.23.49
- postgreSQL 7.1.0
- net-snmp 5.0.6
- · -lcrypto
- libnet 1.0.2a (www.packetfactory.net/libnet/)
- libpcap 0.6.2

Delivered with upwatch are libstatgrab, xmbmon, and the State Threads Library.

2.2.2. Build requirements

Of course you can build the software yourself. Apart from the normal GNU compilation tools, and the development versions of the aforementioned packages, you'll need the following on your system to build upwatch:

- autogen 5.3.6 (autogen.sourceforge.net)
- libxslt 1.0.15
- docbook 1.48, including the entire toolchain: openjade, jadetex, tetex, netpbm, perl-SGMLSpm
- lynx 2.8.4

· RPM tools, if you want to build RPM's

If you run redhat, debian or SuSe, don't forget to install the devel packages if there are any.

2.3. Compiling upwatch

Just in case you really want to (or need to) compile upwatch yourself, it's pretty easy:

\$ tar xzvf upwatch-x.x.tar.gz

\$ cd upwatch-x.x

\$./configure

\$ make

Nothing to it... In case of problems, you're probably missing some library or header files, or they are in unexpected places. Look in config.log.

You can optionally specify --enable-monitors, --enable-iptraf and/or --enable-server to configure. Default configure only builds the client, docs, and utils.

2.4. Actual Installation

Before you install the software decide on the architecture. If you know in advance you'll have to monitor thousands of hosts, or the probes will exhaust your machine otherwise, you may have to split your installation across several machines. There may be more reasons to do that. Consult Scaling up and How it all works

For simplicity we assume you run everything on the same host. In this case just install all rpm's on this host. What if you can't use RPM's? Then type the following command as root:

\$ make install

2.5. PHP pages

The PHP pages can just be copied to any directory. There is an include directory. Copy that a some location ouside the web root, and enter its location in the .htaccess file in the web root dir. Also enter the database details in config.php.

2.6. Security considerations

All upwatch directories are readable and writable by members of the group upwatch. Most all executables run as user upwatch. Some probes need root-access, most notable uw_ping, and they will be installed suid root. These probes drop root privileges wherever possible. Further you can assign each probe its own database user and grant that user access rights to its own database tables. The probes itself don't write to the database, they only read from the pr_xxx_def tables.

The PHP web user should have SELECT, UPDATE, DELETE access to all tables.

uw_access, and **uw_accessbb** are the programs most vulnerable to crackers, as they wait for incoming connections on a TCP port (1985/1984). If possible, use **chroot** and firewall rules to limit connections to real probes only. Something similar holds for **mysql**. Most probes will want access, and passwords can be sniffed. For real security use ssh-tunnels.

2.7. Database

First things first. Depending on the size of your installation you may run out of database or record space. It happened to me on the iptraf probe. I was measuring traffic for 4000 IP addresses and ran out of space after a month on the pr_iptraf_raw table - it hit the max_data_length limit. I had to issue the following commands:

```
$ mysql -u root --password=PASSWORD mysql> alter table pr_iptraf_raw max_rows = 1000000000;
```

and this took almost two hours! So you better look at your own situation and adjust the settings MAX_ROWS and AVG_RECORD_SIZE accordingly for each table.

Create the database as follows. You DO have a root password set for mysql don't you?

```
$ mysqladmin -u root --password=PASSWORD create upwatch
$ mysql -u root --password=PASSWORD < upwatch.mysql
```

Of course you need to assign users and GRANT them access. Note that mosts probes will want read access to their definition table. In many situations you can use just one user for that. Give that user access with:

```
$ mysql -u root --PASSWORD=PASSWORD mysql mysql> GRANT SELECT ON upwatch.pr_ping_def TO user@'192.168.170.23' IDENTIFIED BY 'PASSWD'
```

Chapter 3. Configuration

3.1. Probe configuration

Each probe first reads the general configuration file /etc/upwatch.conf and then its own configurationfile in /etc/upwatch.d if it exists. Normally some general things like the debug and logging level, and the database access are specified in the first file, and any probe-specific setting in the second file. You can also override settings from the generic file in the probe-specific file.

Each program has a manual page that documents options. Every long commandine option can also be entered in a configuration file.

3.2. Database configuration

Chapter 4. Administration

4.1. Logging

The upwatch package contains various ways of logging errors. The standard way is to its own logfile <code>/var/log/upwatch/upwatch.log</code>. Other ways are logging to stderr (probably not practical) and to the syslog. Tweak the <code>debug</code> to increase the amount of logging. Setting the debug level higher than 2 should only be used for debugging serious problems, for example it causes daemons to stay always in the foreground. In debuglevel 0 only errors are logged, in debuglevel 1 some progress information is logged.

The website has its own logfile in log/error.log

4.2. Managing daemons

In most Linux distributions you can start/stop daemons using the scripts in /etc/init.d. Don't forget: you will miss sample data in the database if a probe is not running. You can watch what a probe is running if you run **ps ax**.

4.3. Queues

Queues play an important part in upwatch. The queues are so-called maildir queues. This means that while the queuefile is written, it is written to a temporary directory, and when it's closed it is hardlinked to the actual queue directory. This way you can be absolutely sure that if you find a file in the queue, it is complete and nobody has the file open. Only one process reads from the queue and deletes the file when done.

Chapter 5. How it all works

5.1. General Overview

The system primary function is to fill lots of database tables, to offer views on those tables, and to page operators in case things go wrong. To enable this upwatch consists of a MySQL database, lots of probe daemons (one daemon per probe, usually one probe per daemon), some supporting daemons, a PHP website, and other software, like SMS and mail interfaces.

The software can be divided into four parts:

- · upwatch client runs on a machine
- · server, accepts and processes results
- · monitors, contains software for remotely monitoring.
- · special software, like iptraf

5.1.1. The Upwatch client

The client consists of two programs: uw_sysstat and uw_send. uw_sysstat every minute collects information like CPU load, disk I/O, swapping activity and so on, and writes it to an XML file in the spooldirectory. This directory is checked every 5 seconds, and all files appearing there are sent by uw_send to the central repository. uw_send has a commandline option (--once) to let it be started by cronjobs, or for example when an ISDN connection has become online.

5.1.2. The Upwatch server

The server consists of three programs: uw_accept, uw_setip and uw_process. The monitoring results are accept by uw_accept which listen on port 1985 (configurable), and drop the XML results into the uw_process spool directory, where it is picked up, and stored into the database by uw_process. For compatibility with Big Brother (www.bb4.com) clients, there is an uw_acceptbb daemon, which listens on the Big Brother port (1984), and converts Big Brother messages into upwatch XML files. Lastly, uw_setip listens to messages from the uw_tellip script, which should be started by clients whenever their IP address changes.

5.1.3. The Upwatch monitors

The monitors are daemons that run on some central monitoring server, and run checks on servers remotely, such as POP3, HTTP, SNMP or other services. All their results are sent by uw_send, as usual.

5.1.4. Special programs

Their are special programs that don't fall into any other category, for example uw_iptraf. This is a daemon that should run on a border gateway router, and that measures IP traffic on a per-IP basis.

5.2. A Detailed Description

5.2.1. Database Layout

Things start at the database. For every probe it contains the following tables:

- · Definition table
- · Raw results table
- Tables for compressed results per day, week, month, year and 5 year
- · A table with an overview of state changes

The definition table contains, of course, the definition of this particular probe, this is of course probe specific but at a minimum it contains usually contains the target ip address. We'll see what the other tables are for later on.

5.2.2. What a probe does

There are actually three kinds of probes:

- · Probes with database access, that measure a remote server
- · Probes without database access the measure remote servers
- · Probes without database access that g measure localhost

Every probe performs a repetative task: measuring some specific function on a specific host. So first step is to know what to measure and on which host. For this it reads from the probe definition table, or from its configfile if it does not depend on database access It creates a local - in memory - copy of that table just in case the database becomes unreachable for a period of time. It routinely walks this list and performs its task. The result are written in XML format to a queue which is specified in the probe configuration (note: all queues normally reside in /var/spool/upwatch). After that the probe just waits for the next round.

Many probes have to do a lot of work. They are programmed to do this as efficient as possible. For example: the uw_ping probe is coded as a tight loop around a single select statement. This is the most efficient way (as far as I know) to ping thousands of hosts in, say, 20 seconds. Other probes use pools of threads (like httpget) or are build using the State Threads library.

5.2.3. What happens to the probe results?

First, all results with status non-green are handed over to uw_examine, which tries to find out why the probe failed, and attaches a report to the probe. After this the results are put in the same queue as every other probe: uw_notify. uw_notify reads the result, looks at the probe status, and at previous statuses, and decides if someone should be notified by sms, email, or if it should be put into a high-priority queue.

The outgoing queue may be either the uw_process queue, or an uw_send queue, which is emptied by the uw_send process which sends all files to a remote queue on another host (received and queued by uw_accept).

uw_examine can do some additional tests like traceroute to the target host. It attaches this report to the probe result, and in its turn puts everything in an uw_process or uw_send queue.

5.2.4. uw_process: storing results in the database

When the probe results arrive in the uw_process queue it is picked up by the workhorse of the lot, uw_process. It fills the result tables for the probes.

The raw results table contains just that, raw probe results.

order by stattime desc limit 1

Raw results are compressed into period tables in the following way (using week as an example): a week is divided into 100 equal timeslots. For computing the plot values for a slot the process reads all values from the day table in the same timeslot. These values are averaged and put in the week table. The same process happens for the month and year tables. This way we ensure that we never have to read more then 100 database records to produce a graph for a day, week, month, year or 5-year period.

Status changes are logged in a 'current status' table and in a status history (pr_hist). These two accommodate for easy retrieval by the webpages.

The pseudo-code below shows an example of how uw_process takes a probe result and puts this result in the database. as an example I'll take a pop3 result (class = 5, and our example probe has id 25)

```
IF PROBEDEFINITION NOT IN THE CACHE OR IT'S TOO OLD
      select server, color, stattime, yellow, red from pr_status where class = '8' and probe = '25'"
      IF NOT FOUND IN STATUS FILE
        select server, yellow, red_from_pr_pop3_def where id = '25'
        IF NOT FOUND IN DEFINITION TABLE
          SKIP THIS PROBE
          probes without id (because they don't have database access) may be added here
        ENDIF not in definition table
      ENDIF not in status file
      GET MOST RECENT PROBE RESULT TIME:
     select stattime from pr_pop3_raw use index(probstat) where probe = '25' order by stattime desc limit 1
     ENDIF not in cache
     STORE RESULT:
    insert into pr_pop3_raw set probe = '25', yellow = '1', red = '2', stattime = 'xxxxx', color = 'xx',
      connect = '1', total = '2', message = 'none'
     IF CURRENT PROBE IS NEWER THEN ANY WE'VE SEEN SO FAR
      copy previous record stattime from def record
     ELSE
     select color, stattime from pr_pop3_raw use index(probstat) where probe = '25' and stattime < 'xxxx'
      order by stattime desc limit 1
     ENDIF
     IF THIS IS THE FIRST RESULT EVER SEEN FOR THIS PROBE
     insert into pr_status set class = '8', probe = '25', stattime = 'xxx', expires = 'xxx', color = '200',
        server = '2', message = 'none', yellow = '1', red = '2'
     ELSE IF WE HAVE NOT SEEN THIS PROBE BEFORE
      IF THE COLOR DIFFERS FROM THE PREVIOUS RECORD
        CREATE HISTORY RECORD:
      insert into pr_hist set server = '2', class = '8', probe = '25', stattime = 'xxx', prv_color = '500', color = '200', mes
sage = 'none'
        RETRIEVE FOLLOWING RECORD:
      select color, stattime from pr_pop3_raw use index(probstat) where probe = '25' and stattime < 'xxxx'
```

```
IF FOUND AND HAS THE SAME COLOR DELETE ANY HISTORY RECORDS:
          delete from pr_hist where stattime = 'xxxx' and probe = '25' and class = '8'
      delete from pr_status where stattime = 'xxx' and probe = '25' and class = '8'
        ENDIF following found and has same color
        IF CURRENT RECORD IS THE NEWEST UPDATE STATUS AND SERVER STATUS
       update pr status set stattime = 'xxx', expires = 'xxxy', color = '200', message = 'none', yellow = '1', red = '2'
          where probe = '25' and class = '8'
          update server set color = '20' where id = '2'
        ENDIF newest
      ENDIF color differs
      IF CURRENT RAW RECORD IS THE MOST RECENT
        FOR EACH PERIOD
          IF WE ENTERED A SLOT TIMESLOT IN THE PERIOD
            SUMMARIZE:
         select avg(connect), avg(total), max(color), avg(yellow), avg(red) from pr_pop3_day use index(probstat)
            where probe = '25' and stattime >= slotlow and stattime < slothigh
         insert into pr_pop3_week set connect = '1', total = '2', probe = 25, color = '200', stattime = slot,
             yellow = '1', red = '2', slot = '34'
          ENDIF
        ENDFOR
      ELSE
        FOR EACH PERIOD
         IF THE FIRST RECORD FOR THE NEXT SLOT HAS BEEN SEEN
          RE-SUMMARIZE CURRENT SLOT
        select avg(connect), avg(total), max(color), avg(yellow), avg(red) from pr_pop3_day use index(probstat)
           where probe = '25' and stattime >= slotlow and stattime < slothigh
        insert into pr_pop3_week set connect = '1', total = '2', probe = 25, color = '200', stattime = slot, yel-
low = '1',
            red = '2', slot = '34'
         ENDIF
      ENDIF
     ENDIF
```

5.3. Scaling up

Various parts of the system may need more resources. Luckily Upwatch is designed to scale up considerably. Of course it cannot scale infinately. The last bottleneck will probably be the database. Although MySQL is known for its speed, even that has its limits.

The probes may be scaled up, sometimes by giving them more filehandles, later by moving them to another host

The website may be scaled up by spreading it out across several hosts

The database may be scaled up by putting it on separate hardware, using faster CPU and more spindles (disks), and ultimately using MySQL mirrorring to divide reading and writing across separate machines, or spreading out the tables across multtiple machines. MySQL has lots of info on increasing performance..

Appendix A. Interfaces and file layouts

A.1. Probe result file

Every probe result is written in XML format into a queue file. This file will be picked up by the process emptying the queue, usually uw_send, or uw_process. The file must have a specific name, and a specific layout.

A.1.1. Probe file name

The name of the file is composed of the current epoch time in seconds, microseconds, process id, and hostname on which the queue resides, all separated by dots. An example would be:

• 1031601982.341878.27470.ron-ibook.nbs.arts-betel.org

From a shell you can generate such a name using echo 'date +%s'.500.\$\$. 'hostname'

A.1.2. Generic probe file layout

The probe result file is in XML format, described in /usr/lib/upwatch/dtdt/result.dtd.

A.1.3. uw_accept protocol

The protocol used by uw_accept is almost exactly like the POP3 protocol. login with USER and PASS, then enter DATA filesize and start uploading

Appendix B. Probe specifications

B.1. bb - Big Brother generic probe

B.1.1. bb result record layout

Table bb attributes. bb attributes

Name	Туре	Requi	dd efau	tDescription
host	NMTOKEN	NO		host where this element originated

Table bb elements. bb elements

Name	Option	aDescription	
ipaddress	NO	target ip address	
date	NO	date/time for this result	
expires	NO	when this result expires	
color	NO	color as this probe thinks it should be	
received	NO	date/time this result was received by the upwatch	
		server	

B.1.2. bb database layout

Table bb definition record layout. bb definition record layout

Field	Туре	Key	Defau	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO		_	value for yellow alert

red	float	NO		value for red alert
disable	enum('yes', 'no')	NO	no	disable this probe
hide	enum('yes', 'no')	NO	no	hide probe results from viewing
bbname	char	NO		Big Brother name of this probe

Table bb result record layout. bb result record layout

Field	Туре	Key	Defau	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO			value for yellow alert
red	float	NO			value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value

B.2. bb_cpu - Big Brother System probe

B.2.1. bb_cpu result record layout

Table bb_cpu attributes. bb_cpu attributes

Name	Туре	Requi	rddefaultDescription
host	NMTOKEN	NO	host where this element originated
loadavg	NMTOKEN	NO	Load average as computed by upwatch
user	NMTOKEN	NO	CPU user time
system	NMTOKEN	NO	CPU system time
idle	NMTOKEN	NO	CPU idle time
swapped	NMTOKEN	NO	Amount of blocks written to swap device
free	NMTOKEN	NO	Free memory
buffered	NMTOKEN	NO	Amount of memory used for OS buffers

cached	NMTOKEN	NO	Amount of memory used for disk buffers
used	NMTOKEN	NO	Amount of memory used by processes

Table bb_cpu elements. bb_cpu elements

Name	Option	aDescription
ipaddress	NO	target ip address
date	NO	date/time for this result
expires	NO	when this result expires
color	NO	color as this probe thinks it should be
received	NO	date/time this result was received by the upwatch
		server

B.2.2. bb_cpu database layout

Table bb_cpu definition record layout. bb_cpu definition record layout

Field	Туре	Key	Defaul	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe
hide	enum('yes', 'no')	NO	no		hide probe results from viewing

Table bb_cpu result record layout. bb_cpu result record layout

15

Field	Туре	Key	Defau	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value
loadavg	float	NO	0		Load average as computed by upwatch
user	tinyint unsigned	NO	0		CPU user time
system	tinyint unsigned	NO	0		CPU system time
idle	tinyint unsigned	NO	0		CPU idle time
swapped	int unsigned	NO	0		Amount of blocks written to swap device
free	int unsigned	NO	0		Free memory
buffered	int unsigned	NO	0		Amount of memory used for OS buffers
cached	int unsigned	NO	0		Amount of memory used for disk buffers
used	int unsigned	NO	0		Amount of memory used by processes

B.3. httpget - Do a HTTP GET request

B.3.1. httpget result record layout

Table httpget attributes. httpget attributes

Name	Туре	Requi	dd efaul	tDescription
lookup	NMTOKEN	NO		time needed for DNS lookup
connect	NMTOKEN	NO		time for connection to complete
pretransfer	NMTOKEN	NO		time for any pre-transfer actions

total NMTOKEN	NO	total time needed
---------------	----	-------------------

Table httpget elements. httpget elements

Name	Option	₁ Description	
id	NO	id of this probe in the database	
ipaddress	NO	target ip address	
date	NO	date/time for this result	
expires	NO	when this result expires	
color	NO	color as this probe thinks it should be	
received	NO	date/time this result was received by the upwatch	
		server	

B.3.2. httpget database layout

Table httpget definition record layout. httpget definition record layout

Field	Туре	Key	Defau	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO	1		value for yellow alert
red	float	NO	3		value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe
hide	enum('yes', 'no')	NO	no		hide probe results from viewing
hostname	varchar(80)	NO			Hostname for the HTTP request
port	int unsigned	NO	80		Port for the HTTP request
uri	varchar(255)	NO			URI part

Table httpget result record layout. httpget result record layout

Field	Туре	Key	Defau	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	1		value for yellow alert
red	float	NO	3		value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value
lookup	float	NO	0		time needed for DNS lookup
connect	float	NO	0		time for connection to complete
pretransfer	float	NO	0		time for any pre-transfer actions
total	float	NO	0		total time needed

B.4. imap - Test a IMAP server, optionally with user/password

B.4.1. imap result record layout

Table imap attributes. imap attributes

Name	Туре	Requi	d d efaul	tDescription
connect	NMTOKEN	NO		time for connection to complete
total	NMTOKEN	NO		total time needed

Table imap elements. imap elements

Name	Option	D escription			
id	NO	id of this probe in the database			
ipaddress	NO	target ip address			
date	NO	date/time for this result			
expires	NO	when this result expires			
color	NO	color as this probe thinks it should be			

received	NO	date/time this result was received by the upwatch
		server

B.4.2. imap database layout

Table imap definition record layout. imap definition record layout

Field	Туре	Key	Defau	ltExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe
hide	enum('yes', 'no')	NO	no		hide probe results from viewing
username	varchar(64)	NO			Username
password	char	NO			Password

Table imap result record layout. imap result record layout

Field	Туре	Key	Defaul	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
stattime	int unsigned	YES	0		time when result was generated

color	smallint unsigned	YES	200	color value
connect	float	NO	0	time for connection to complete
total	float	NO	0	total time needed

B.5. iptraf - Incoming and outgoing traffic to an IP adddress, network or interface

B.5.1. iptraf result record layout

Table iptraf attributes. iptraf attributes

Name	Туре	Requi	dd efaul	tDescription
incoming	NMTOKEN	NO		total incoming bytes
outgoing	NMTOKEN	NO		total outgoing bytes

Table iptraf elements. iptraf elements

Name	Option	aDescription
ipaddress	NO	target ip address
date	NO	date/time for this result
expires	NO	when this result expires
color	NO	color as this probe thinks it should be
received	NO	date/time this result was received by the upwatch server
interval	NO	time between measurements

B.5.2. iptraf database layout

Table iptraf definition record layout. iptraf definition record layout

Field	Туре	Key	Defaul	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id

contact	int unsigned	YES	1	user field: pointer to contact database
notify	int unsigned	YES	1	notifier id
ipaddress	varchar(15)	YES		target ipaddress
description	text	NO		description
freq	smallint unsigned	NO	1	frequency in minutes
yellow	float	NO	300	value for yellow alert
red	float	NO	500	value for red alert
disable	enum('yes', 'no')	NO	no	disable this probe
hide	enum('yes', 'no')	NO	no	hide probe results from viewing

Table iptraf result record layout. iptraf result record layout

Field	Type	Key	Defau	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	300		value for yellow alert
red	float	NO	500		value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value
incoming	float	NO	0		total incoming bytes
outgoing	float	NO	0		total outgoing bytes

B.6. mssql - Do a Microsoft SQL Server query

B.6.1. mssql result record layout

Table mssql attributes. mssql attributes

Name	Туре	Requi	dd efau	tDescription
connect	NMTOKEN	NO		time for connection to complete

total NMTOKEN	NO	total time needed
---------------	----	-------------------

Table mssql elements. mssql elements

Name	Option	a Description
id	NO	id of this probe in the database
ipaddress	NO	target ip address
date	NO	date/time for this result
expires	NO	when this result expires
color	NO	color as this probe thinks it should be
received	NO	date/time this result was received by the upwatch
		server

B.6.2. mssql database layout

Table mssql definition record layout. mssql definition record layout

Field	Type	Key	Defau	ltExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO	0.5		value for yellow alert
red	float	NO	0.8		value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe
hide	enum('yes', 'no')	NO	no		hide probe results from viewing
dbname	char	NO			Name of the database for the query
dbuser	char	NO			Database user
dbpasswd	char	NO			Database password

query	text	NO		Query to perform. This
				should return at least 1
				row

Table mssql result record layout. mssql result record layout

Field	Туре	Key	Defau	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	0.5		value for yellow alert
red	float	NO	0.8		value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value
connect	float	NO	0		time for connection to complete
total	float	NO	0		total time needed

B.7. mysql - Do a MySQL query

B.7.1. mysql result record layout

Table mysql attributes. mysql attributes

Name	Туре	Requi	d d efaul	tDescription
connect	NMTOKEN	NO		time for connection to complete
total	NMTOKEN	NO		total time needed

Table mysql elements. mysql elements

Name	Option	aDescription
id	NO	id of this probe in the database
		•
ipaddress	NO	target ip address
date	NO	date/time for this result
expires	NO	when this result expires

color	NO	color as this probe thinks it should be
received	NO	date/time this result was received by the upwatch
		server

B.7.2. mysql database layout

Table mysql definition record layout. mysql definition record layout

Field	Туре	Key	Defau	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO	0.3		value for yellow alert
red	float	NO	0.5		value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe
hide	enum('yes', 'no')	NO	no		hide probe results from viewing
dbname	char	NO			Name of the database for the query
dbuser	char	NO			Database user
dbpasswd	char	NO			Database password
query	text	NO			Query to perform. This should return at least 1 row

Table mysql result record layout. mysql result record layout

Field	Туре	Key	Defaul	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result

probe	int unsigned	YES	1	probe identifier
yellow	float	NO	0.3	value for yellow alert
red	float	NO	0.5	value for red alert
stattime	int unsigned	YES	0	time when result was generated
color	smallint unsigned	YES	200	color value
connect	float	NO	0	time for connection to complete
total	float	NO	0	total time needed

B.8. ping - send ICMP echo requests

Five ICMP echo requests are sent. For each request the time is measured between the echo and the resulting ICMP reply packet.

B.8.1. ping result record layout

Table ping attributes. ping attributes

Name	Туре	Required efault Description		
value	NMTOKEN	NO		Average turn-around time
lowest	NMTOKEN	NO		lowest turn-around time
highest	NMTOKEN	NO		highest turn-around time

Table ping elements. ping elements

Name	Option	aDescription
id	NO	id of this probe in the database
ipaddress	NO	target ip address
date	NO	date/time for this result
expires	NO	when this result expires
color	NO	color as this probe thinks it should be
received	NO	date/time this result was received by the upwatch
		server

B.8.2. ping database layout

Table ping definition record layout. ping definition record layout

Field	Туре	Key	Defau	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe
hide	enum('yes', 'no')	NO	no		hide probe results from viewing
count	int unsigned	NO	5		Number of ping packets to send

Table ping result record layout. ping result record layout

Field	Туре	Key	Defau	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value
value	float	NO	0		Average turn-around time
lowest	float	NO	0		lowest turn-around time

highest	float	NO	0	highest turn-around
				time

B.9. pop3 - Test a POP3 server, optionally with user/password

B.9.1. pop3 result record layout

Table pop3 attributes. pop3 attributes

Name	Туре	Requi	dd efau	tDescription
connect	NMTOKEN	NO		time for connection to complete
total	NMTOKEN	NO		total time needed

Table pop3 elements. pop3 elements

Name	Option	aDescription
id	NO	id of this probe in the database
ipaddress	NO	target ip address
date	NO	date/time for this result
expires	NO	when this result expires
color	NO	color as this probe thinks it should be
received	NO	date/time this result was received by the upwatch server

B.9.2. pop3 database layout

Table pop3 definition record layout. pop3 definition record layout

Field	Туре	Key	Defau	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id

ipaddress	varchar(15)	YES		target ipaddress
description	text	NO		description
freq	smallint unsigned	NO	1	frequency in minutes
yellow	float	NO	3	value for yellow alert
red	float	NO	5	value for red alert
disable	enum('yes', 'no')	NO	no	disable this probe
hide	enum('yes', 'no')	NO	no	hide probe results from viewing
username	varchar(64)	NO		Username
password	char	NO		Password

Table pop3 result record layout. pop3 result record layout

Field	Туре	Key	Defau	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value
connect	float	NO	0		time for connection to complete
total	float	NO	0		total time needed

B.10. postgresql - Do a PostgreSQL query

B.10.1. postgresql result record layout

Table postgresql attributes. postgresql attributes

Name	Туре	Requi	dd efau	tDescription
connect	NMTOKEN	NO		time for connection to complete

total NMTOKEN	NO	total time needed
---------------	----	-------------------

Table postgresql elements. postgresql elements

Name	Option	a Description	
id	NO	id of this probe in the database	
ipaddress	NO	target ip address	
date	NO	date/time for this result	
expires	NO	when this result expires	
color	NO	color as this probe thinks it should be	
received	NO	date/time this result was received by the upwatch	
		server	

B.10.2. postgresql database layout

Table postgresql definition record layout. postgresql definition record layout

Field	Туре	Key	Defau	ltExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe
hide	enum('yes', 'no')	NO	no		hide probe results from viewing
dbname	char	NO			Name of the database for the query
dbuser	char	NO			Database user
dbpasswd	char	NO			Database password

query	text	NO		Query to perform. This
				should return at least 1
				row

Table postgresql result record layout. postgresql result record layout

Field	Туре	Key	Defaul	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value
connect	float	NO	0		time for connection to complete
total	float	NO	0		total time needed

B.11. smtp - Test an SMTP server

B.11.1. smtp result record layout

Table smtp attributes. smtp attributes

Name	Туре	Requi	dd efaul	tDescription
connect	NMTOKEN	NO		time for connection to complete
total	NMTOKEN	NO		total time needed

Table smtp elements. smtp elements

Name	Option	ndDescription	
id	NO	id of this probe in the database	
		•	
ipaddress	NO	target ip address	
date	NO	date/time for this result	
expires	NO	when this result expires	

color	NO	color as this probe thinks it should be
received	NO	date/time this result was received by the upwatch
		server

B.11.2. smtp database layout

Table smtp definition record layout. smtp definition record layout

Field	Type	Key	Defau	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe
hide	enum('yes', 'no')	NO	no		hide probe results from viewing

Table smtp result record layout. smtp result record layout

Field	Туре	Key	Defau	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value

	connect	float	NO	0	time for connection to
-	total	float	NO	0	total time needed

B.12. snmpget - Query an SNMP variable using an SNMP GET

B.12.1. snmpget result record layout

Table snmpget attributes. snmpget attributes

Name	Туре	Requi	dd efau	tDescription
value	NMTOKEN	NO		Value of OID queried

Table snmpget elements. snmpget elements

Name	Option	4Description	
id	NO	id of this probe in the database	
ipaddress	NO	target ip address	
date	NO	date/time for this result	
expires	NO	when this result expires	
color	NO	color as this probe thinks it should be	
received	NO	date/time this result was received by the upwatch	
		server	

B.12.2. snmpget database layout

Table snmpget definition record layout. snmpget definition record layout

Field	Туре	Key	Defaul	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id

ipaddress	varchar(15)	YES		target ipaddress
description	text	NO		description
freq	smallint unsigned	NO	1	frequency in minutes
yellow	float	NO	3	value for yellow alert
red	float	NO	5	value for red alert
disable	enum('yes', 'no')	NO	no	disable this probe
hide	enum('yes', 'no')	NO	no	hide probe results from viewing
community	char	NO	public	community string for SNMPv1/v2c transactions
OID	varchar(255)	NO		Object ID
dispname	char	NO		Display Name
dispunit	char	NO		Display Unit
multiplier	float	NO	1	Multiplier for result values
mode		NO	absolu	te plot absolute or relative values

Table snmpget result record layout. snmpget result record layout

Field	Туре	Key	Defau	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value
value	float	NO	0		Value of OID queried

B.13. sysstat - System information like load average, CPU/MEM usage etc

B.13.1. sysstat result record layout

Table sysstat attributes. sysstat attributes

Name	Туре	Required	efaultDescription
loadavg	NMTOKEN	NO	The load average as reported by the system
user	NMTOKEN	NO	CPU user time
system	NMTOKEN	NO	CPU system time
idle	NMTOKEN	NO	CPU idle time
swapin	NMTOKEN	NO	Amount of blocks swapped in from disk
swapout	NMTOKEN	NO	Amount of blocks swapped out to disk
blockin	NMTOKEN	NO	Amount of blocks read from block devices
blockout	NMTOKEN	NO	Amount of blocks written to block devices
swapped	NMTOKEN	NO	Amount of blocks written to swap device
free	NMTOKEN	NO	Free memory
buffered	NMTOKEN	NO	Amount of memory used for OS buffers
cached	NMTOKEN	NO	Amount of memory used for disk buffers
used	NMTOKEN	NO	Amount of memory used by processes
systemp	NMTOKEN	NO	System temperature in Celsius

Table sysstat elements. sysstat elements

Name	Option	a Description	
server	NO	id of this server in the database	
ipaddress	NO	target ip address	
date	NO	date/time for this result	
expires	NO	when this result expires	
color	NO	color as this probe thinks it should be	
interval	NO	time between measurements	
received	NO	date/time this result was received by the upwatch	
		server	

B.13.2. sysstat database layout

Table sysstat definition record layout. sysstat definition record layout

Field	Туре	Key	Defau	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe
hide	enum('yes', 'no')	NO	no		hide probe results from viewing

Table sysstat result record layout. sysstat result record layout

Field	Туре	Key	Defaul	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value
loadavg	float	NO	0		The load average as reported by the system
user	tinyint unsigned	NO	0		CPU user time
system	tinyint unsigned	NO	0		CPU system time
idle	tinyint unsigned	NO	0		CPU idle time

swapin	int unsigned	NO	0	Amount of blocks swapped in from disk
swapout	int unsigned	NO	0	Amount of blocks swapped out to disk
blockin	int unsigned	NO	0	Amount of blocks read from block devices
blockout	int unsigned	NO	0	Amount of blocks written to block devices
swapped	int unsigned	NO	0	Amount of blocks written to swap device
free	int unsigned	NO	0	Free memory
buffered	int unsigned	NO	0	Amount of memory used for OS buffers
cached	int unsigned	NO	0	Amount of memory used for disk buffers
used	int unsigned	NO	0	Amount of memory used by processes
systemp	tinyint	NO	0	System temperature in Celsius

B.14. hwstat - Hardware information like CPU temperature, fan speed

B.14.1. hwstat result record layout

Table hwstat attributes. hwstat attributes

Name	Type	Requir	EdefaultDescription
temp1	NMTOKEN	NO	First temperature sensor - usually CPU temp
temp2	NMTOKEN	NO	Second temperature sensor - usually motherboard
temp3	NMTOKEN	NO	Third temperature sensor - usually enclosure
rot1	NMTOKEN	NO	First fan rotation speed - usually CPU fan
rot2	NMTOKEN	NO	Second fan rotation speed
rot3	NMTOKEN	NO	Third fan rotation speed
vc0	NMTOKEN	NO	CPU core voltage #1

vc1	NMTOKEN	NO	CPU core voltage #2
v33	NMTOKEN	NO	Voltage of 3.3V line
v50p	NMTOKEN	NO	Voltage of 5V line
v12p	NMTOKEN	NO	Voltage of 12V line
v12n	NMTOKEN	NO	Voltage of -12V line
v50n	NMTOKEN	NO	Voltage of -5V line

Table hwstat elements. hwstat elements

Name	Option	aDescription	
server	NO	id of this server in the database	
ipaddress	NO	target ip address	
date	NO	date/time for this result	
expires	NO	when this result expires	
color	NO	color as this probe thinks it should be	
interval	NO	time between measurements	
received	NO	date/time this result was received by the upwatch server	

B.14.2. hwstat database layout

Table hwstat definition record layout. hwstat definition record layout

Field	Туре	Key	Defau	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO	40		value for yellow alert
red	float	NO	50		value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe

hide	enum('yes',	NO	no	hide probe results from
	'no')			viewing

Table hwstat result record layout. hwstat result record layout

Field	Туре	Key	Defau	ltExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	40		value for yellow alert
red	float	NO	50		value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value
temp1	float	NO	0		First temperature sensor - usually CPU temp
temp2	float	NO	0		Second temperature sensor - usually motherboard
temp3	float	NO	0		Third temperature sensor - usually enclosure
rot1	int	NO	0		First fan rotation speed - usually CPU fan
rot2	int	NO	0		Second fan rotation speed
rot3	int	NO	0		Third fan rotation speed
vc0	float	NO	0		CPU core voltage #1
vc1	float	NO	0		CPU core voltage #2
v33	float	NO	0		Voltage of 3.3V line
v50p	float	NO	0		Voltage of 5V line
v12p	float	NO	0		Voltage of 12V line
v12n	float	NO	0		Voltage of -12V line
v50n	float	NO	0		Voltage of -5V line

B.15. errlog - System error log analysis

B.15.1. errlog result record layout

Table errlog attributes. errlog attributes

Name	Туре	Requi	dd efau	tDescription
host	NMTOKEN	NO host where this element o		host where this element originated

Table errlog elements. errlog elements

Name	Option	aDescription
ipaddress	NO	target ip address
date	NO	date/time for this result
expires	NO	when this result expires
color	NO	color as this probe thinks it should be
received	NO	date/time this result was received by the upwatch
		server

B.15.2. errlog database layout

Table errlog definition record layout. errlog definition record layout

Field	Туре	Key	Defau	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO			value for yellow alert
red	float	NO			value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe
hide	enum('yes', 'no')	NO	no		hide probe results from viewing

Table errlog result record layout. errlog result record layout

Field	Туре	Key	Defau	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO			value for yellow alert
red	float	NO			value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value

B.16. diskfree - Free disk space

B.16.1. diskfree result record layout

Table diskfree attributes. diskfree attributes

Name	Туре	Required efault		ultDescription	
host	NMTOKEN	NO host where this element orig		host where this element originated	

Table diskfree elements. diskfree elements

Name	Option	aDescription
ipaddress	NO	target ip address
date	NO	date/time for this result
expires	NO	when this result expires
color	NO	color as this probe thinks it should be
received	NO	date/time this result was received by the upwatch
		server

B.16.2. diskfree database layout

Table diskfree definition record layout. diskfree definition record layout

Field	Туре	Key	Defaul	tExtra	Description

id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO			value for yellow alert
red	float	NO			value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe
hide	enum('yes', 'no')	NO	no		hide probe results from viewing

Table diskfree result record layout. diskfree result record layout

Field	Туре	Key	Defaul	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO			value for yellow alert
red	float	NO			value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value

B.17. tcpconnect - Connect to a TCP port

B.17.1. tcpconnect result record layout

Table tepconnect attributes. tepconnect attributes

Name	Туре	Requi	dd efaul	tDescription
connect	NMTOKEN	NO		time for connection to complete
total	NMTOKEN	NO		total time needed

Table tepconnect elements. tepconnect elements

Name	Option	a Description
id	NO	id of this probe in the database
ipaddress	NO	target ip address
date	NO	date/time for this result
expires	NO	when this result expires
color	NO	color as this probe thinks it should be
received	NO	date/time this result was received by the upwatch
		server

B.17.2. tcpconnect database layout

Table tepconnect definition record layout. tepconnect definition record layout

			1		
Field	Type	Key	Defaul	tExtra	Description
id	int	PRI		auto_increment	probe unique numerical id
pgroup	int unsigned	NO	2		group id
server	int	NO	1		server id
contact	int unsigned	YES	1		user field: pointer to contact database
notify	int unsigned	YES	1		notifier id
ipaddress	varchar(15)	YES			target ipaddress
description	text	NO			description
freq	smallint unsigned	NO	1		frequency in minutes
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
disable	enum('yes', 'no')	NO	no		disable this probe
hide	enum('yes', 'no')	NO	no		hide probe results from viewing
port	int	NO	25		port to connect to

Table tepconnect result record layout. tepconnect result record layout

Field	Туре	Key	Defau	tExtra	Description
id	bigint unsigned	PRI		auto_increment	unique id for result
probe	int unsigned	YES	1		probe identifier
yellow	float	NO	3		value for yellow alert
red	float	NO	5		value for red alert
stattime	int unsigned	YES	0		time when result was generated
color	smallint unsigned	YES	200		color value
connect	float	NO	0		time for connection to complete
total	float	NO	0		total time needed

Appendix C. Adding a probe

C.1. So you want to add a probe?

Are you really sure? Adding a probe involves writing C code, creating and designing database tables and queue result files, creating PHP pages, and PHP graphs, writing documentation and submitting these changes to CVS. It is a lot of work, how rewarding it may be.

In the following overview we'll show you how to add a probe. All man-pages, spec-files, documentation will be auto-generated if you follow instructions below.

C.2. Basic steps for adding a probe

C.2.1. Think carefully before you start

You should not think lightly of adding a probe. Think things over before you start. Isn't there a probe available you can use? Or maybe you can get away with extending an existing one? If not, perhaps you can copy and modify one?

If not, you're in for the rewarding process of adding a new probe. Go to the next step.

C.2.2. Pick a real good name

You should think of a real good descriptive name for your probe. It should describe exactly what it does. Leave room for future probes that do something similar, also think about future extension to the probe itself.. Don't be satisfied too soon. For the rest of this small tutorial, we'll assume you probe willed be called cputemp for monitoring the host CPU temperature (which in fact already exists as part of the sysstat probe).

C.2.3. Design the Database Fields

Also a probe needs to enter its status into pr_status, and its history into pr_history and you should add code for this in the uw_process part..

C.2.4. Write the code

Create a new directory named uw_cputemp, copy all files in templates/probe to it. Look into those files, do a search and replace all occurrences of template with cputemp. Go one directory up, edit configure.in. Add a line uw_cputemp/Makefile to the AC_CONFIG_FILES section. Add uw_cputemp to the PROGNAMES variable in Makefile.am. Run:

- \$./autogen.sh
- \$./configure
- \$ cd uw_cputemp
- \$ make clean
- \$ make

No errors should show up.

Now start coding in uw_cputemp/run.c, specifically in the function run(). You should have enough examples in the other probes. Basically the probe should read a list of probedefinitions from a database, execute all probes, and writes the results into a spoolfile. There are utility functions for doing this in libupwatch.

Important: Test your code thoroughly for memory leaks and error conditions.

C.2.5. Write the uw process extension

The output of your probe is processed by uw_process. You should add a new source file called process_cputemp.c, that reads the probe results and writes them to the database tables. Be careful for the logic in this part. Add an entry in the struct _probe_proc array in uw_process/run.c, and a extern int process_cputemp(char *spec, GString *remark); just above it.

C.2.6. Add PHP pages_to_CMS

- Copy all *.php files from templates/php-cms to the en/database directory. Rename every *template* file to *cputemp*.
- Copy the pr_template_def.rec file to /home/cms/home/cms/www/php/cms. Do the usual replace, and take care this def file reflects the layout of pr_cputemp_def table in the database.
- Go to www/php/cms/custforms.php. Find the line which says START OF PROBES. Add an entry to the \$f_probes array.
- Copy a section of another probe. Adapt as needed.

•

Important: Create an empty record in the database with id = 1i

C.2.7. Write documentation

Note that every probe is documented briefly in the cmd_options.def file. You should also document the probe in this manual. Personally I use KDE's Kate with the XML plugin. Go the the doc directory. Copy template-specs.xml to cputemp-specs.xml. Add a line to probesspecs.xml, and an ENTITY line at the top of upwatch.xml. Add cputemp-specs.xml to the XMLFILES line in Makefile.am. Rerun ./autogen.sh, ./configure in the top directory. Run make in the doc directory.

C.3. Non-standard Probes

To be done

Index