

Launching an RDP session

After an RDP session request becomes available, the requester can launch the remote desktop connection to start the session.

TIP: As a requester, you can customize the RDP session. On the **My Request** page, click  **Settings** and under **Remote Desktop (RDP) Connection Settings**, you can configure some optional settings.

To launch a remote desktop connection

1. If the **User Supplied** option is selected in the policy, you will be prompted to enter your user credentials. After entering the requested credentials, click **Apply**. This will retrieve the information (for example, Username Connection String) required to launch the remote desktop session.
2. In the web client:

NOTE: The  **Start RDP Session** option is available only if enabled by user preferences.

- If you have an application registered (`rdp://` for RDP sessions), click the  **Start RDP Session** button associated with the asset name then click **Connect**. For more information on application registration, see [KB 313918](#). You must enter a password and One Identity recommends `sg`. A blank password will cause the session to fail.
- If you do not have an application registered, click  **Download RDP File**. You must enter a password and One Identity recommends `sg`. A blank password will cause the session to fail.

Begin your RDP session and close the session

1. In the remote desktop session, run the commands or programs on the target host.
If there is no activity in an open session for about 10 minutes, the session will be closed. However, as long as the request is in an **Available** state, you can launch the session again to resume your tasks.

2. After you are completed, log out of the target host and select  **Check in** to complete the session request process.