

1. Employee Information

Program

```
using System;
using System.Web.UI;

namespace FORM
{
    public partial class WebForm1 : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {

        }

        protected void Button1_Click(object sender, EventArgs e)
        {
            int a = Convert.ToInt32(TextBox8.Text);
            int b = Convert.ToInt32(TextBox9.Text);

            int g = a * b;

            TextBox10.Text = g.ToString();
        }
    }
}
```

Source code

```
<%@ Page Language="C#" AutoEventWireup="true"
    CodeBehind="WebForm1.aspx.cs"
    Inherits="FORM.WebForm1" %>
```

```
<!DOCTYPE html>
```

```
<html xmlns="http://www.w3.org/1999/xhtml">
```

```
<head runat="server">
```

```
<title>Employee Information System</title>
```

```
</head>
```

```
<body>
```

```
<form id="form1" runat="server">
```

```
<h2>EMPLOYEE INFORMATION SYSTEM</h2>
```

```
<asp:Label ID="Label1" runat="server" Text="EMP NAME:"></asp:Label>
```

```
<asp:TextBox ID="TextBox1" runat="server"></asp:TextBox>
```

```
<br /><br />
```

```
<asp:Label ID="Label2" runat="server" Text="EMP ID:"></asp:Label>
```

```
<asp:TextBox ID="TextBox2" runat="server"></asp:TextBox>
```

```
<br /><br />
```

```
<asp:Label ID="Label3" runat="server" Text="DESIGNATION:"></asp:Label>
```

```
<asp:TextBox ID="TextBox3" runat="server"></asp:TextBox>
```

```
<br /><br />
```

```
<asp:Label ID="Label4" runat="server" Text="AGE:"></asp:Label>
```

```
<asp:TextBox ID="TextBox4" runat="server"></asp:TextBox>
```

```
<br /><br />
```

<asp:Label ID="Label5" runat="server" Text="SALARY:"></asp:Label>

<asp:TextBox ID="TextBox5" runat="server"></asp:TextBox>

<asp:Label ID="Label6" runat="server" Text="ADDRESS:"></asp:Label>

<asp:TextBox ID="TextBox6" runat="server"></asp:TextBox>

<asp:Label ID="Label8" runat="server" Text="EXPERIENCE:"></asp:Label>

<asp:TextBox ID="TextBox7" runat="server"></asp:TextBox>

<asp:Label ID="Label9" runat="server" Text="NO OF PRODUCTS:"></asp:Label>

<asp:TextBox ID="TextBox8" runat="server"></asp:TextBox>

<asp:Label ID="Label10" runat="server" Text="COST:"></asp:Label>

<asp:TextBox ID="TextBox9" runat="server"></asp:TextBox>

<asp:Label ID="Label7" runat="server" Text="TOTAL:"></asp:Label>

<asp:TextBox ID="TextBox10" runat="server"></asp:TextBox>

<asp:Button ID="Button1"

runat="server"

Text="CLICK HERE TO REGISTER"

OnClick="Button1_Click" />

</form>

</body>

</html>

2. ATM Transaction

Program

```
using System;

using System.Web.UI;

namespace radio
{
    public partial class _Default : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {
        }

        protected void RadioButtonList1_SelectedIndexChanged(
            object sender, EventArgs e)
        {
            if (RadioButtonList1.SelectedValue == "Deposit" ||
                RadioButtonList1.SelectedValue == "Withdraw")
            {
                Label5.Visible = true;

                Label5.Text = "Welcome " + TextBox1.Text;

                Label6.Visible = true;
                TextBox3.Visible = true;
            }
            else
            {
                Label5.Visible = false;

                Label6.Visible = false;
            }
        }
    }
}
```

```

        TextBox3.Visible = false;
        Label7.Visible = false;
    }
}

protected void TextBox3_TextChanged(object sender, EventArgs e)
{
    if (RadioButtonList1.SelectedValue == "Deposit")
    {
        Label7.Visible = true;
        Label7.Text = "Your amount " + TextBox3.Text
            + " is credited";
    }
    else if (RadioButtonList1.SelectedValue == "Withdraw")
    {
        Label7.Visible = true;
        Label7.Text = "Your amount " + TextBox3.Text
            + " is debited";
    }
}
}
}

```

Source code

```

<%@ Page Language="C#" AutoEventWireup="true"
    CodeBehind="Default.aspx.cs"
    Inherits="radio._Default" %>

<!DOCTYPE html>

```

```
<html xmlns="http://www.w3.org/1999/xhtml">
```

```
<head runat="server">
```

```
<title>ATM Transaction</title>
```

```
</head>
```

```
<body>
```

```
<form id="form1" runat="server">
```

```
<h2>ATM TRANSACTION</h2>
```

```
<asp:Label ID="Label1" runat="server"
```

```
Text="Name"></asp:Label>
```

```
<asp:TextBox ID="TextBox1" runat="server">
```

```
</asp:TextBox>
```

```
<br /><br />
```

```
<asp:Label ID="Label2" runat="server"
```

```
Text="Enter the PIN"></asp:Label>
```

```
<asp:TextBox ID="TextBox2" runat="server"
```

```
TextMode="Password"></asp:TextBox>
```

```
<br /><br />
```

```
<asp:Label ID="Label3" runat="server"
```

```
Text="Choose any one:"></asp:Label>
```


<asp:RadioButtonList ID="RadioButtonList1"
 runat="server"
 AutoPostBack="True"
 OnSelectedIndexChanged="RadioButtonList1_SelectedIndexChanged">

<asp:ListItem>Deposit</asp:ListItem>
<asp:ListItem>Withdraw</asp:ListItem>

</asp:RadioButtonList>

<asp:Label ID="Label5" runat="server"
 Visible="False"></asp:Label>

<asp:Label ID="Label6" runat="server"
 Text="Enter the amount"
 Visible="False"></asp:Label>

<asp:TextBox ID="TextBox3" runat="server"
 AutoPostBack="True"
 OnTextChanged="TextBox3_TextChanged"
 Visible="False"></asp:TextBox>

<asp:Label ID="Label7" runat="server"
Visible="False"></asp:Label>

</form>

</body>

</html>

3. Railway Reservation

Program

```
using System;
using System.Web.UI;

namespace loginform
{
    public partial class railway : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {

        }

        protected void Calendar1_SelectionChanged(object sender, EventArgs e)
        {
            DateTime d, d1;

            d = DateTime.Now.Date;
            d1 = Calendar1.SelectedDate;

            if (d1 >= d)
            {
                TextBox4.Text = d1.ToShortDateString();
            }
            else
            {
                Response.Write("<script>alert('Invalid date')</script>");
            }
        }
    }
}
```

```
protected void Button1_Click(object sender, EventArgs e)
{
    Label1.Text = "Your journey date is " + TextBox4.Text;
}
}
```

Source code

```
<%@ Page Language="C#" AutoEventWireup="true"
    CodeBehind="railway.aspx.cs"
    Inherits="loginform.railway" %>
```

```
<!DOCTYPE html>
```

```
<html xmlns="http://www.w3.org/1999/xhtml">
```

```
<head runat="server">
```

```
<title>Railway Reservation</title>
```

```
</head>
```

```
<body>
```

```
<form id="form1" runat="server">
```

```
<h2>RAILWAY RESERVATION</h2>
```

```
<asp:Label ID="Label2" runat="server"
```

```
Text="NAME:"></asp:Label>
```

```
<asp:TextBox ID="TextBox1" runat="server">
</asp:TextBox>
```

```
<br /><br />
```

```
<asp:Label ID="Label3" runat="server"
Text="FROM:"></asp:Label>
```

```
<asp:TextBox ID="TextBox2" runat="server">
</asp:TextBox>
```

```
<br /><br />
```

```
<asp:Label ID="Label4" runat="server"
Text="TO:"></asp:Label>
```

```
<asp:TextBox ID="TextBox3" runat="server">
</asp:TextBox>
```

```
<br /><br />
```

```
<asp:Label ID="Label5" runat="server"
Text="JOURNEY DATE:"></asp:Label>
```

```
<asp:TextBox ID="TextBox4" runat="server">
</asp:TextBox>
```

```
<br /><br />
```

```
<asp:Calendar ID="Calendar1"
    runat="server"
    OnSelectionChanged="Calendar1_SelectionChanged">
</asp:Calendar>
```

```
<br />
```

```
<asp:Button ID="Button1"
    runat="server"
    Text="BOOK TICKET"
    OnClick="Button1_Click" />
```

```
<br /><br />
```

```
<asp:Label ID="Label1"
    runat="server">
</asp:Label>
```

```
</form>
```

```
</body>
```

```
</html>
```

4. Validator

Program

```
using System;

using System.Web.UI;

using System.Web.UI.WebControls;

namespace customvalidation
{
    public partial class customvalidation : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {

        }

        protected void CustomValidator1_ServerValidate(
            object source,
            ServerValidateEventArgs args)
        {
            if (args.Value.Length > 20)
            {
                args.IsValid = false;
            }
            else
            {
                args.IsValid = true;
            }
        }
    }
}
```

```

protected void Button1_Click(object sender, EventArgs e)
{
    if (Page.IsValid)
    {
        Response.Write("Your feedback has been submitted");
    }
}
}
}

```

Source Code

```

<%@ Page Language="C#" AutoEventWireup="true"
    CodeBehind="customvalidation.aspx.cs"
    Inherits="customvalidation.customvalidation" %>

```

```

<!DOCTYPE html>

```

```

<html xmlns="http://www.w3.org/1999/xhtml">

```

```

<head runat="server">

```

```

    <title>Custom Validator</title>

```

```

</head>

```

```

<body>

```

```

<form id="form1" runat="server">

```

```

    <h2>CUSTOM VALIDATOR</h2>

```

```
<asp:Label ID="Label1"
```

```
    runat="server"
```

```
    Text="Name">
```

```
</asp:Label>
```

```
<asp:TextBox ID="TextBox1"
```

```
    runat="server">
```

```
</asp:TextBox>
```

```
<asp:RequiredFieldValidator
```

```
    ID="RequiredFieldValidator1"
```

```
    runat="server"
```

```
    ControlToValidate="TextBox1"
```

```
    ErrorMessage="Name is required"
```

```
    ForeColor="Red">
```

```
</asp:RequiredFieldValidator>
```

```
<br /><br />
```

```
<asp:Label ID="Label2"
```

```
    runat="server"
```

```
    Text="Age">
```

```
</asp:Label>
```

```
<asp:TextBox ID="TextBox2"
```

```
    runat="server">
```

```
</asp:TextBox>
```

```
<asp:RequiredFieldValidator
```

```
ID="RequiredFieldValidator4"
runat="server"
ControlToValidate="TextBox2"
ErrorMessage="Age is required"
ForeColor="Red">
</asp:RequiredFieldValidator>
```

```
<asp:RangeValidator
ID="RangeValidator1"
runat="server"
ControlToValidate="TextBox2"
MinimumValue="20"
MaximumValue="40"
Type="Integer"
ErrorMessage="Age should be between 20 and 40"
ForeColor="Red">
</asp:RangeValidator>
```

```
<br /><br />
```

```
<asp:Label ID="Label4"
runat="server"
Text="Phone No">
</asp:Label>
```

```
<asp:TextBox ID="TextBox4"
runat="server">
</asp:TextBox>
```

```
<asp:RegularExpressionValidator
    ID="RegularExpressionValidator1"
    runat="server"
    ControlToValidate="TextBox4"
    ValidationExpression="\d{10}"
    ErrorMessage="Phone number must contain 10 digits"
    ForeColor="Red">
</asp:RegularExpressionValidator>
```

```
<br /><br />
```

```
<asp:Label ID="Label3"
    runat="server"
    Text="Feedback">
</asp:Label>
```

```
<asp:TextBox ID="TextBox3"
    runat="server"
    TextMode="MultiLine">
</asp:TextBox>
```

```
<asp:RequiredFieldValidator
    ID="RequiredFieldValidator3"
    runat="server"
    ControlToValidate="TextBox3"
    ErrorMessage="Feedback is required"
    ForeColor="Red">
</asp:RequiredFieldValidator>
```

```
<asp:CustomValidator
    ID="CustomValidator1"
    runat="server"
    ControlToValidate="TextBox3"
    ErrorMessage="Feedback should be less than 20 characters"
    ForeColor="Red"
    OnServerValidate="CustomValidator1_ServerValidate">
</asp:CustomValidator>
```

```
<br /><br />
```

```
<asp:Button ID="Button1"
    runat="server"
    Text="Submit"
    OnClick="Button1_Click" />
```

```
</form>
```

```
</body>
```

```
</html>
```

5. Customer Validator

Program

```
using System;

using System.Web.UI;

using System.Web.UI.WebControls;

namespace validation
{
    public partial class WebForm1 : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {

        }

        protected void CustomValidator1_ServerValidate(
            object source,
            ServerValidateEventArgs args)
        {
            if (args.Value.Length > 20)
            {
                args.IsValid = false;
            }
            else
            {
                args.IsValid = true;
            }
        }

        protected void Button1_Click(object sender, EventArgs e)
```

```
{  
    if (Page.IsValid)  
    {  
        Response.Write("Your feedback has been submitted");  
    }  
}  
}
```

```
<%@ Page Language="C#" AutoEventWireup="true"  
    CodeBehind="WebForm1.aspx.cs"  
    Inherits="validation.WebForm1" %>
```

```
<!DOCTYPE html>
```

```
<html xmlns="http://www.w3.org/1999/xhtml">
```

```
<head runat="server">  
    <title>Custom Validation</title>  
</head>
```

```
<body>
```

```
<form id="form1" runat="server">
```

```
<h2>CUSTOM VALIDATION</h2>
```

```
<asp:Label ID="Label1"
```

```
        runat="server"
        Text="Name">
</asp:Label>

<asp:TextBox ID="TextBox1"
        runat="server">
</asp:TextBox>

<asp:RequiredFieldValidator
        ID="RequiredFieldValidator1"
        runat="server"
        ControlToValidate="TextBox1"
        ErrorMessage="Name is required"
        ForeColor="Red">
</asp:RequiredFieldValidator>

<br /><br />

<asp:Label ID="Label2"
        runat="server"
        Text="Age">
</asp:Label>

<asp:TextBox ID="TextBox2"
        runat="server">
</asp:TextBox>

<asp:RequiredFieldValidator
        ID="RequiredFieldValidator2"
```

```
runat="server"
ControlToValidate="TextBox2"
ErrorMessage="Age is required"
ForeColor="Red">
</asp:RequiredFieldValidator>
```

```
<br /><br />
```

```
<asp:Label ID="Label3"
runat="server"
Text="Mobile No">
</asp:Label>
```

```
<asp:TextBox ID="TextBox3"
runat="server">
</asp:TextBox>
```

```
<asp:RequiredFieldValidator
ID="RequiredFieldValidator3"
runat="server"
ControlToValidate="TextBox3"
ErrorMessage="Mobile no is required"
ForeColor="Red">
</asp:RequiredFieldValidator>
```

```
<br /><br />
```

```
<asp:Label ID="Label4"
runat="server"
```

```
Text="Feedback">
</asp:Label>
```

```
<asp:TextBox ID="TextBox4"
runat="server"
TextMode="MultiLine">
</asp:TextBox>
```

```
<asp:RequiredFieldValidator
ID="RequiredFieldValidator4"
runat="server"
ControlToValidate="TextBox4"
ErrorMessage="Feedback is required"
ForeColor="Red">
</asp:RequiredFieldValidator>
```

```
<asp:CustomValidator
ID="CustomValidator1"
runat="server"
ControlToValidate="TextBox4"
ErrorMessage="Feedback should be less than 20 characters"
ForeColor="Red"
OnServerValidate="CustomValidator1_ServerValidate">
</asp:CustomValidator>
```

```
<br /><br />
```

```
<asp:Button ID="Button1"
runat="server"
```

Text="Submit"

OnClick="Button1_Click" />

</form>

</body>

</html>

6. Student Management System

program

```
using System;
using System.Collections.Generic;
using System.Web;
using System.Web.UI;
using System.Web.UI.WebControls;

namespace StudentManagementSystem
{
    public partial class _Default : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {

        }

        protected void Button1_Click(object sender, EventArgs e)
        {
            Label6.Text = "Student Details";
            Label7.Text = "Student ID: " + TextBox1.Text;
            Label8.Text = "Name: " + TextBox2.Text;
            Label9.Text = "Age: " + TextBox3.Text;
            Label10.Text = "Course: " + TextBox4.Text;
            Label11.Text = "Phone: " + TextBox5.Text;
        }
    }
}
```

Source Code:

```
<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="Default.aspx.cs"
Inherits="StudentManagementSystem._Default" %>
```

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
```

```
<html xmlns="http://www.w3.org/1999/xhtml">
```

```
<head id="Head1" runat="server">
```

```
    <title>Student Management System</title>
```

```
</head>
```

```
<body>
```

```
<form id="form1" runat="server">
```

```
    <h2>STUDENT MANAGEMENT SYSTEM</h2>
```

```
    <asp:Label ID="Label1" runat="server" Text="STUDENT ID"></asp:Label>
```

```
    <asp:TextBox ID="TextBox1" runat="server"></asp:TextBox>
```

```
    <br /><br />
```

```
    <asp:Label ID="Label2" runat="server" Text="NAME"></asp:Label>
```

```
    <asp:TextBox ID="TextBox2" runat="server"></asp:TextBox>
```

```
    <br /><br />
```

```
    <asp:Label ID="Label3" runat="server" Text="AGE"></asp:Label>
```

```
    <asp:TextBox ID="TextBox3" runat="server"></asp:TextBox>
```

```
    <br /><br />
```

<asp:Label ID="Label4" runat="server" Text="COURSE"></asp:Label>

<asp:TextBox ID="TextBox4" runat="server"></asp:TextBox>

<asp:Label ID="Label5" runat="server" Text="PHONE"></asp:Label>

<asp:TextBox ID="TextBox5" runat="server"></asp:TextBox>

<asp:Button ID="Button1" runat="server"

Text="SUBMIT"

OnClick="Button1_Click" />

<asp:Label ID="Label6" runat="server"></asp:Label>

<asp:Label ID="Label7" runat="server"></asp:Label>

<asp:Label ID="Label8" runat="server"></asp:Label>

<asp:Label ID="Label9" runat="server"></asp:Label>

<asp:Label ID="Label10" runat="server"></asp:Label>

<asp:Label ID="Label11" runat="server"></asp:Label>

</form>

</body>

</html>

7. Library Management System

Program:

```
using System;
using System.Collections.Generic;
using System.Web;
using System.Web.UI;
using System.Web.UI.WebControls;

namespace Library_Management_System
{
    public partial class _Default : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {

        }

        protected void Calendar1_SelectionChanged(object sender, EventArgs e)
        {
            TextBox5.Text = Calendar1.SelectedDate.ToShortDateString();
        }

        protected void Button1_Click(object sender, EventArgs e)
        {
            DateTime issueDate = Calendar1.SelectedDate;
            DateTime dueDate = issueDate.AddDays(14);

            Label7.Visible = true;

            Label7.Text = "Book issued successfully. Due Date: "
```

```

        + dueDate.ToShortDateString();
    }
}
}

```

Source Code:

```

<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="Default.aspx.cs"
Inherits="Library_Management_System._Default" %>

```

```

<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">

```

```

<html xmlns="http://www.w3.org/1999/xhtml">

```

```

<head id="Head1" runat="server">

```

```

    <title>Library Management System</title>

```

```

</head>

```

```

<body>

```

```

<form id="form1" runat="server">

```

```

    <h2>LIBRARY MANAGEMENT SYSTEM</h2>

```

```

    <asp:Label ID="Label1" runat="server"

```

```

        Text="Book ID"></asp:Label>

```

```

    <asp:TextBox ID="TextBox1" runat="server"></asp:TextBox>

```

```

    <br /><br />

```

```

    <asp:Label ID="Label2" runat="server"

```

```

        Text="Book Name"></asp:Label>

```

```

    <asp:TextBox ID="TextBox2" runat="server"></asp:TextBox>

```


<asp:Label ID="Label3" runat="server"

Text="Author Name"></asp:Label>

<asp:TextBox ID="TextBox3" runat="server"></asp:TextBox>

<asp:Label ID="Label4" runat="server"

Text="Student Name"></asp:Label>

<asp:TextBox ID="TextBox4" runat="server"></asp:TextBox>

<asp:Label ID="Label5" runat="server"

Text="Issue Date"></asp:Label>

<asp:TextBox ID="TextBox5" runat="server"

ReadOnly="true"></asp:TextBox>

<asp:Calendar ID="Calendar1" runat="server"

OnSelectionChanged="Calendar1_SelectionChanged">

</asp:Calendar>

<asp:Button ID="Button1" runat="server"

Text="ISSUE BOOK"

OnClick="Button1_Click" />

<asp:Label ID="Label7" runat="server"

Visible="false"></asp:Label>

</form>

</body>

</html>

8. Bus reservation management

Program:

```
using System;
using System.Collections.Generic;
using System.Web;
using System.Web.UI;
using System.Web.UI.WebControls;

namespace Bus_reservation
{
    public partial class _Default : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {

        }

        protected void Calendar1_SelectionChanged(object sender, EventArgs e)
        {
            TextBox4.Text = Calendar1.SelectedDate.ToShortDateString();
        }

        protected void Button1_Click(object sender, EventArgs e)
        {
            Label6.Visible = true;

            Label6.Text = "Bus ticket reserved successfully for "
                + TextBox4.Text;
        }
    }
}
```

```
}
```

Source Code:

```
<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="Default.aspx.cs"
Inherits="Bus_reservation._Default" %>
```

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
```

```
<html xmlns="http://www.w3.org/1999/xhtml">
```

```
<head id="Head1" runat="server">
```

```
<title>Bus Reservation System</title>
```

```
</head>
```

```
<body>
```

```
<form id="form1" runat="server">
```

```
<h2>BUS RESERVATION SYSTEM</h2>
```

```
<asp:Label ID="Label1" runat="server"
```

```
Text="Passenger Name"></asp:Label>
```

```
<asp:TextBox ID="TextBox1" runat="server"></asp:TextBox>
```

```
<br /><br />
```

```
<asp:Label ID="Label2" runat="server"
```

```
Text="From"></asp:Label>
```

```
<asp:TextBox ID="TextBox2" runat="server"></asp:TextBox>
```


<asp:Label ID="Label3" runat="server"
Text="To"></asp:Label>

<asp:TextBox ID="TextBox3" runat="server"></asp:TextBox>

<asp:Label ID="Label4" runat="server"
Text="Journey Date"></asp:Label>

<asp:TextBox ID="TextBox4" runat="server"
ReadOnly="true"></asp:TextBox>

<asp:Calendar ID="Calendar1" runat="server"
OnSelectionChanged="Calendar1_SelectionChanged">
</asp:Calendar>

<asp:Label ID="Label5" runat="server"
Text="Number of Seats"></asp:Label>

<asp:TextBox ID="TextBox5" runat="server"></asp:TextBox>


```
<asp:Button ID="Button1" runat="server"
    Text="BOOK TICKET"
    OnClick="Button1_Click" />
```

```
<br /><br />
```

```
<asp:Label ID="Label6" runat="server"
    Visible="false"></asp:Label>
```

```
</form>
```

```
</body>
```

```
</html>
```

9. Flight Reservation Management

Program:

```
using System;
using System.Collections.Generic;
using System.Web;
using System.Web.UI;
using System.Web.UI.WebControls;

namespace Flight_Reservation
{
    public partial class _Default : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {

        }

        protected void Calendar1_SelectionChanged(object sender, EventArgs e)
        {
            TextBox4.Text = Calendar1.SelectedDate.ToShortDateString();
        }

        protected void Button1_Click(object sender, EventArgs e)
        {
            Label6.Visible = true;

            Label6.Text = "Flight ticket reserved successfully for "
                + TextBox4.Text;
        }
    }
}
```

```
}
```

Source Code:

```
<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="Default.aspx.cs"
Inherits="Flight_Reservation._Default" %>
```

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
```

```
<html xmlns="http://www.w3.org/1999/xhtml">
```

```
<head id="Head1" runat="server">
```

```
<title>Flight Reservation System</title>
```

```
</head>
```

```
<body>
```

```
<form id="form1" runat="server">
```

```
<h2>FLIGHT RESERVATION SYSTEM</h2>
```

```
<asp:Label ID="Label1" runat="server"
```

```
Text="Passenger Name"></asp:Label>
```

```
<asp:TextBox ID="TextBox1" runat="server"></asp:TextBox>
```

```
<br /><br />
```

```
<asp:Label ID="Label2" runat="server"
```

```
Text="From"></asp:Label>
```

```
<asp:TextBox ID="TextBox2" runat="server"></asp:TextBox>
```


<asp:Label ID="Label3" runat="server"
Text="To"></asp:Label>

<asp:TextBox ID="TextBox3" runat="server"></asp:TextBox>

<asp:Label ID="Label4" runat="server"
Text="Travel Date"></asp:Label>

<asp:TextBox ID="TextBox4" runat="server"
ReadOnly="true"></asp:TextBox>

<asp:Calendar ID="Calendar1" runat="server"
OnSelectionChanged="Calendar1_SelectionChanged">
</asp:Calendar>

<asp:Label ID="Label5" runat="server"
Text="Number of Passengers"></asp:Label>

<asp:TextBox ID="TextBox5" runat="server"></asp:TextBox>


```
<asp:Button ID="Button1" runat="server"
```

```
Text="BOOK FLIGHT"
```

```
OnClick="Button1_Click" />
```

```
<br /><br />
```

```
<asp:Label ID="Label6" runat="server"
```

```
Visible="false"></asp:Label>
```

```
</form>
```

```
</body>
```

```
</html>
```

10. Payroll

Program:

```
using System;
using System.Collections.Generic;
using System.Web;
using System.Web.UI;
using System.Web.UI.WebControls;

namespace Payroll
{
    public partial class _Default : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {

        }

        protected void Button1_Click(object sender, EventArgs e)
        {
            double basicSalary = Convert.ToDouble(TextBox4.Text);
            double allowance = Convert.ToDouble(TextBox5.Text);
            double deduction = Convert.ToDouble(TextBox6.Text);

            double netSalary = basicSalary + allowance - deduction;

            Label8.Visible = true;
            Label8.Text = "Net Salary: ₹" + netSalary;
        }
    }
}
```

Source Code:

```
<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="Default.aspx.cs"
Inherits="Payroll._Default" %>
```

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
```

```
<html xmlns="http://www.w3.org/1999/xhtml">
```

```
<head id="Head1" runat="server">
```

```
    <title>Payroll Management System</title>
```

```
</head>
```

```
<body>
```

```
<form id="form1" runat="server">
```

```
    <h2>PAYROLL MANAGEMENT SYSTEM</h2>
```

```
    <asp:Label ID="Label1" runat="server"
```

```
        Text="Employee ID"></asp:Label>
```

```
    <asp:TextBox ID="TextBox1" runat="server"></asp:TextBox>
```

```
    <br /><br />
```

```
    <asp:Label ID="Label2" runat="server"
```

```
        Text="Employee Name"></asp:Label>
```

```
    <asp:TextBox ID="TextBox2" runat="server"></asp:TextBox>
```

```
    <br /><br />
```

<asp:Label ID="Label3" runat="server"
Text="Department"></asp:Label>

<asp:TextBox ID="TextBox3" runat="server"></asp:TextBox>

<asp:Label ID="Label4" runat="server"
Text="Basic Salary"></asp:Label>

<asp:TextBox ID="TextBox4" runat="server"></asp:TextBox>

<asp:Label ID="Label5" runat="server"
Text="Allowance"></asp:Label>

<asp:TextBox ID="TextBox5" runat="server"></asp:TextBox>

<asp:Label ID="Label6" runat="server"
Text="Deduction"></asp:Label>

<asp:TextBox ID="TextBox6" runat="server"></asp:TextBox>


```
<asp:Button ID="Button1" runat="server"
    Text="CALCULATE SALARY"
    OnClick="Button1_Click" />
```

```
<br /><br />
```

```
<asp:Label ID="Label8" runat="server"
    Visible="false"></asp:Label>
```

```
</form>
```

```
</body>
```

```
</html>
```

11. Electricity Bill

Program:

```
using System;
using System.Collections.Generic;
using System.Web;
using System.Web.UI;
using System.Web.UI.WebControls;

namespace Electricity_Bill
{
    public partial class _Default : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {

        }

        protected void Button1_Click(object sender, EventArgs e)
        {
            int units = Convert.ToInt32(TextBox3.Text);
            double amount;

            if (units <= 100)
            {
                amount = units * 2;
            }
            else if (units <= 200)
            {
                amount = units * 3;
            }
        }
    }
}
```

```

        else
        {
            amount = units * 5;
        }

        Label5.Visible = true;

        Label5.Text = "Electricity Bill Amount: ₹" + amount;
    }
}
}

```

Source Code:

```

<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="Default.aspx.cs"
Inherits="Electricity_Bill._Default" %>

```

```

<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">

```

```

<html xmlns="http://www.w3.org/1999/xhtml">

```

```

<head id="Head1" runat="server">

```

```

    <title>Electricity Bill</title>

```

```

</head>

```

```

<body>

```

```

<form id="form1" runat="server">

```

```

    <h2>ELECTRICITY BILL</h2>

```

```

    <asp:Label ID="Label1" runat="server"

```

```

        Text="Consumer Name"></asp:Label>

```

```
<asp:TextBox ID="TextBox1" runat="server"></asp:TextBox>
```

```
<br /><br />
```

```
<asp:Label ID="Label2" runat="server"  
    Text="Consumer Number"></asp:Label>
```

```
<asp:TextBox ID="TextBox2" runat="server"></asp:TextBox>
```

```
<br /><br />
```

```
<asp:Label ID="Label3" runat="server"  
    Text="Units Consumed"></asp:Label>
```

```
<asp:TextBox ID="TextBox3" runat="server"></asp:TextBox>
```

```
<br /><br />
```

```
<asp:Button ID="Button1" runat="server"  
    Text="GENERATE BILL"  
    OnClick="Button1_Click" />
```

```
<br /><br />
```

```
<asp:Label ID="Label5" runat="server"  
    Visible="false"></asp:Label>
```

```
</form>
```

```
</body>
```

</html>