
## **ESP8266 PINOUT**

## NOTES:

⚠ Typ. pin current 6mA (Max. 12mA)



- PWM

ADC

N/C

CONTROL



## ESP8266 PINOUT

Pin	Name	Useful notes (cf. datasheet for details)
1	VDDA	Analog Power 3.0 ~3.6V
2	LNA	RF Antenna Interface
3	VDD3P3	Amplifier Power 3.0~3.6V
4	VDD3P3	Amplifier Power 3.0~3.6V
5	VDD_RTC	NC (1.1V)
6	TOUT	ADC pin; can be used to monitor VDD3P3
7	CHIP_EN	Active high enable pin (Low: small current)
8	XPD_DCDC	
9	MTMS	IR Remote Tx
10	MTDI	
11	VDDPST	Digital/IO Power Supply (1.8V~3.3V)
12	MTCK	
13	MTDO	
14	GPIO2	UART Tx
15	GPIO0	
16	GPIO4	
17	VDDPST	Digital/IO Power Supply (1.8V~3.3V)
18	SDIO_DATA_2	Connect to SD_D2 (Series R: 200Ω)
19	SDIO_DATA_3	Connect to SD_D3 (Series R: 200Ω)
20	SDIO_CMD	Connect to SD_CMD (Series R: 200Ω)
21	SDIO_CLK	Connect to SD_CLK (Series R: 200Ω)
22	SDIO_DATA_0	Connect to SD_D0 (Series R: 200Ω)
23	SDIO_DATA_1	Connect to SD_D1 (Series R: 200Ω)
24	GPIO5	IR Remote Rx
25	U0RXD	UART Rx during flash programming
26	U0TXD	UART Tx during flash programming
27	XTAL_OUT	Connect to crystal oscillator output
28	XTAL_IN	Connect to crystal oscillator input
29	VDDD	Analog Power 3.0V~3.6V
30	VDDA	Analog Power 3.0V~3.6V
31	RES12K	Serial connection w 12 k $\Omega$ resistor and ground
32	EXT_RSTB	Active low external reset signal
33	GND PAD	Pad is connected to ground

Full datasheet: https://acrobotic.com/datasheets/esp8266

