## Github link:

→https://github.com/Badetto/FLCD\_Lab2

## Finite Automata:

Description: Is an algorithm that iterates through the given transitions values given by the user and checks if the given sequence is valid based on the **Private variables:** "States", "Alphabet", "Transitions", "InitialState" and "FinalStates" (their names are suggestive).

→ **ReadFile**: It reads values from a file, thus initializing all 5 Private variables, also if one of the private variables is empty it will throw an exception.

→ CheckSequence (sequence: list<string>): bool: It returns true if the given sequence is valid, otherwise it will return false. A sequence is valid if you can go from a state to another one via some transitions (based on the values from the sequence taken in order); the first state must be an initial state, and the last state must be a final state.

→ **Display:** One print method for each private variable.

## BNF for input file:

```
<file> ::= <states> <in_state> <out_states> <alphabet> <transitions> <states> ::= "states" <newline> <state_list> <
    <state_list> ::= <state> <newline> { <state> <newline> }
    <in_state> ::= "in_state" <newline> <state> <newline> <
        <out_states> ::= "out_states" <newline> <state_list> <alphabet> ::= "alphabet" <newline> <symbol_list> <<symbol_list> ::= <symbol> <newline> { <symbol> <newline> }
    <transitions> ::= "transitions" <newline> <transition list>
```

```
<transition_list> ::= <transition> <newline> { <transition> <newline> }

<transition> ::= <state> "," <symbol> "," <state>

<state> ::= <character> { <character> }

<symbol> ::= <character> | "_"

<character> ::= "a" | "b" | ... | "z" | "A" | "B" | ... | "Z" | "0" | "1" | ... | "9"

<newline> ::= "\n"
```