

Package ‘rsyncrosim’

March 4, 2021

Type Package

Title The R Interface to 'SyncroSim'

Version 1.2.11

Description 'SyncroSim' is a generalized framework for managing scenario-based datasets ([<https://syncrosim.com/>](https://syncrosim.com/)). 'rsyncrosim' provides an interface to 'SyncroSim'. Simulation models can be added to 'SyncroSim' in order to transform these datasets, taking advantage of general features such as defining scenarios of model inputs, running Monte Carlo simulations, and summarizing model outputs. 'rsyncrosim' requires 'SyncroSim' 2.2.13 or higher (API documentation: [<https://docs.syncrosim.com/>](https://docs.syncrosim.com/)).

License MIT + file LICENSE

LazyData TRUE

Encoding UTF-8

Imports methods,
DBI,
RSQLite,
raster,
gtools

Suggests knitr,
testthat,
ggplot2,
Rcpp,
rgdal,
rmarkdown

SystemRequirements SyncroSim (>=2.2.22)

Collate 'AAAClassDefinitions.R'

'addModule.R'
'addPackage.R'
'addPackageFile.R'
'addRow.R'
'addon.R'
'autogentags.R'
'backup.R'
'basePackage.R'
'breakpoint.R'
'command.R'
'datasheet.R'

'datasheetRaster.R'
 'dateModified.R'
 'delete.R'
 'deleteModule.R'
 'deletePackage.R'
 'dependency.R'
 'description.R'
 'disableAddon.R'
 'enableAddon.R'
 'filepath.R'
 'ignoreDependencies.R'
 'info.R'
 'internalHelpers.R'
 'name.R'
 'scenarioId.R'
 'projectId.R'
 'sqlStatement.R'
 'scenario.R'
 'project.R'
 'ssimLibrary.R'
 'session.R'
 'internalWrappers.R'
 'mergeDependencies.R'
 'model.R'
 'module.R'
 'owner.R'
 'package.R'
 'parentId.R'
 'print.R'
 'printCmd.R'
 'readOnly.R'
 'rsyncrosim.R'
 'run.R'
 'runLog.R'
 'saveDatasheet.R'
 'silent.R'
 'ssimEnvironment.R'
 'ssimUpdate.R'
 'updatePackage.R'
 'version.R'

RoxygenNote 7.1.1

VignetteBuilder knitr

URL <https://github.com/syncrosim/rsyncrosim/>

BugReports <https://github.com/syncrosim/rsyncrosim/issues/>

R topics documented:

addBreakpoint	4
addModule	5
addon	5

addPackage	6
addPackageFile	7
addRow	8
autogentags	8
autogentags<-	9
backup	9
basePackage	10
breakpoint	10
command	11
datasheet	12
datasheetRaster	15
dateModified	17
delete	18
deleteBreakpoint	19
deleteModule	20
deletePackage	20
dependency	21
description	22
description<-	22
disableAddon	23
enableAddon	24
envInputFolder	24
envOutputFolder	25
envReportProgress	25
envTempFolder	26
filepath	26
ignoreDependencies	27
ignoreDependencies<-	27
info	28
mergeDependencies	28
mergeDependencies<-	29
model	29
module	30
name	30
name<-	31
owner	32
owner<-	32
package	33
parentId	34
printCmd	34
project	35
Project-class	36
projectId	37
readOnly	37
readOnly<-	38
rsyncsim	38
run	39
runLog	40
saveDatasheet	41
scenario	43
Scenario-class	44
scenarioId	45

session	45
Session-class	46
session<-	46
silent	47
silent<-	48
sqlStatement	48
ssimEnvironment	49
ssimLibrary	50
SsimLibrary-class	51
ssimUpdate	52
tempfilepath	52
updatePackage	53
version	53

Index	55
--------------	-----------

addBreakpoint	<i>Add a Scenario breakpoint.</i>
---------------	-----------------------------------

Description

When the Scenario is run the breakpoint's callback function will be called for the specified iterations or timesteps.

Usage

```
addBreakpoint(x, transformerName, breakpointType, arguments, callback)
```

```
## S4 method for signature 'Scenario'
```

```
addBreakpoint(x, transformerName, breakpointType, arguments, callback)
```

Arguments

x	A SyncroSim Scenario.
transformerName	A Stochastic Time Transformer (e.g. stsim_Runtime).
breakpointType	bi: before iteration; ai: after iteration; bt: before timestep; at: after timestep.
arguments	A vector of timesteps or iterations e.g. c(1,2).
callback	A function to be called when the breakpoint is hit.

Details

Breakpoints are only supported for Stochastic Time Transformers.

Value

A SyncroSim Scenario with an updated list of breakpoints.

Examples

```

callbackFunction <- function(x, iteration, timestep) {
  print(paste0("Breakpoint hit: ", scenarioId(x)))
}

temp_dir <- tempdir()
myses <- session()
mylib <- ssimLibrary(name = file.path(temp_dir, "testlib"), session = myses)
myScenario <- scenario(mylib, "testScenario")

myScenario <- addBreakpoint(x= myScenario, transformerName= "stsim_Runtime", breakpointType = "bi",
  arguments = c(1,2), callback = callbackFunction)

```

addModule	<i>Add module</i>
-----------	-------------------

Description

Add module or modules to SyncroSim Deprecated. See: [addPackage](#) and [addPackageFile](#).

Usage

```

addModule(filename, session = NULL)

## S4 method for signature 'character'
addModule(filename, session = NULL)

```

Arguments

filename	Character string or vector of these. The path to an .ssimpkg file on disk, or a vector of filepaths.
session	Session.

Value

Deprecated: produces an error.

addon	<i>addon(s) of an SsimLibrary or Session</i>
-------	--

Description

The addon(s) of an SsimLibrary or Session.

Usage

```

addon(ssimObject)

## S4 method for signature 'character'
addon(ssimObject)

## S4 method for signature 'missingOrNULL'
addon(ssimObject)

## S4 method for signature 'Session'
addon(ssimObject)

## S4 method for signature 'SsimObject'
addon(ssimObject)

```

Arguments

ssimObject SsimLibrary/Project/Scenario or Session.

Value

A dataframe of addons.

Examples

```

temp_dir <- tempdir()
myses <- session()
myLibrary <- ssimLibrary(name = file.path(temp_dir,"testlib"), session = myses)

addon(myLibrary)

```

addPackage	<i>Adds a package to SyncroSim</i>
------------	------------------------------------

Description

Adds a package to SyncroSim. This functions will query the SyncroSim package server for the package name provided as input.

Usage

```

addPackage(name, session = NULL)

## S4 method for signature 'ANY,character'
addPackage(name, session = NULL)

## S4 method for signature 'ANY,missingOrNULL'
addPackage(name, session = NULL)

## S4 method for signature 'ANY,Session'
addPackage(name, session = NULL)

```

Arguments

name	Character string. The name of the package to install.
session	Session.

Value

This function will invisibly return 'TRUE' upon success (i.e.successful install) and 'FALSE' upon failure.

addPackageFile	<i>Adds a package to SyncroSim</i>
----------------	------------------------------------

Description

Adds a package to SyncroSim from a package file.

Usage

```
addPackageFile(filename, session = NULL)

## S4 method for signature 'ANY,character'
addPackageFile(filename, session = NULL)

## S4 method for signature 'ANY,missingOrNULL'
addPackageFile(filename, session = NULL)

## S4 method for signature 'ANY,Session'
addPackageFile(filename, session = NULL)
```

Arguments

filename	Character string. The path to a SyncroSim package file.
session	Session.

Value

This function invisibly returns 'TRUE' upon success (i.e.successful install) and 'FALSE' upon failure.

addRow	<i>Add row(s) to a dataframe.</i>
--------	-----------------------------------

Description

Adds row(s) to a dataframe.

Usage

```
addRow(targetDataframe, value)
```

```
## S4 method for signature 'data.frame'
addRow(targetDataframe, value)
```

Arguments

targetDataframe	Dataframe.
value	Dataframe, character string vector, or list. Columns in value should be a subset of columns in targetDataframe.

Details

Preserves the types and factor levels of the targetDataframe. Fills missing values if possible using factor levels. If value is a named vector or list, it will be converted to a single row dataframe. If value is an unnamed vector or list, the number of elements should equal the number of columns in the targetDataframe; elements are assumed to be in same order as dataframe columns.

Value

A dataframe with new rows.

autogentags	<i>Auto Generation Tags for a Scenario.</i>
-------------	---

Description

Retrieves the Auto Generation Tags for a Scenario.

Usage

```
autogentags(ssimObject)
```

```
## S4 method for signature 'character'
autogentags(ssimObject)
```

```
## S4 method for signature 'Scenario'
autogentags(ssimObject)
```


`autogentags<-`

9

Arguments

`ssimObject` Scenario.

Value

Returns the Auto Generation Tags.

<code>autogentags<-</code>	<i>Auto Generation Tags for a Scenario.</i>
-------------------------------	---

Description

Sets the Auto Generation Tags for a Scenario.

Usage

```
autogentags(ssimObject) <- value

## S4 replacement method for signature 'character'
autogentags(ssimObject) <- value

## S4 replacement method for signature 'Scenario'
autogentags(ssimObject) <- value
```

Arguments

`ssimObject` Scenario.
`value` character.

Value

The updated `ssimObject`.

<code>backup</code>	<i>Backup a SsimLibrary.</i>
---------------------	------------------------------

Description

Backup a SsimLibrary.

Usage

```
backup(ssimObject)

## S4 method for signature 'character'
backup(ssimObject)

## S4 method for signature 'SsimObject'
backup(ssimObject)
```

Arguments

ssimObject SsimLibrary/Project/Scenario.

Value

This function invisibly returns 'TRUE' upon success (i.e.successful backup) and 'FALSE' upon failure.

basePackage	<i>Installed base packages</i>
-------------	--------------------------------

Description

Base packages installed with this version of SyncroSim.

Usage

```
basePackage(ssimObject = NULL)

## S4 method for signature 'character'
basePackage(ssimObject = NULL)

## S4 method for signature 'missingOrNULL'
basePackage(ssimObject = NULL)

## S4 method for signature 'Session'
basePackage(ssimObject = NULL)

## S4 method for signature 'SsimLibrary'
basePackage(ssimObject = NULL)
```

Arguments

ssimObject Session or SsimLibrary.

Value

A dataframe of base packages (for Session) or named vector of character strings (for SsimLibrary).

breakpoint	<i>Lists the breakpoints for a Scenario.</i>
------------	--

Description

Lists the breakpoints for a Scenario.

Usage

```
breakpoint(x)

## S4 method for signature 'Scenario'
breakpoint(x)
```

Arguments

`x` A SyncroSim Scenario.

Value

Does not return anything, used for printing purposes.

command	<i>SyncroSim console command</i>
---------	----------------------------------

Description

Issues a command to the SyncroSim console and returns the output.

Usage

```
command(args, session = NULL, program = "SyncroSim.Console.exe", wait = TRUE)
```

Arguments

<code>args</code>	Character string, named list, named vector, unnamed list, or unnamed vector. Arguments for the SyncroSim console. See details.
<code>session</code>	Session. If NULL, a default session will be used.
<code>program</code>	Character. The name of the target SyncroSim executable. Options include SyncroSim.Console.exe (default), SyncroSim.Server.exe, SyncroSim.PackageManager.exe and SyncroSim.Multiband.exe.
<code>wait</code>	Logical. If TRUE (default) R will wait for the command to finish before proceeding. Note that <code>silent(session)</code> is ignored if <code>wait=FALSE</code> .

Details

Example args, and the resulting character string passed to the SyncroSim console:

- Character string e.g. `"-create -help"`: `"-create -help"`
- Named list or named vector e.g. `list(name1=NULL,name2=value2)`: `"-name1 -name2=value2"`
- Unnamed list or unnamed vector e.g. `c("create","help")`: `"-create -help"`

Value

A character string, output from the SyncroSim program.

Examples

```
# Use a default session to create a new library in the current working directory.
args <- list(create = NULL, library = NULL,
            name = paste0(tempdir(), "/temp.ssim"),
            package = "stsim")
output <- command(args, session = session(printCmd = TRUE))
output

# Three different ways to provide args to command
command(c("create", "help"))
command("--create --help")
command(list(create = NULL, help = NULL))
```

datasheet

Get a datasheet

Description

Retrieves a SyncroSim datasheet.

Usage

```
datasheet(
  ssimObject,
  name = NULL,
  project = NULL,
  scenario = NULL,
  summary = NULL,
  optional = FALSE,
  empty = FALSE,
  lookupsAsFactors = TRUE,
  sqlStatement = list(select = "SELECT *", groupBy = ""),
  includeKey = FALSE,
  forceElements = FALSE,
  fastQuery = FALSE
)
```

S4 method for signature 'list'

```
datasheet(
  ssimObject,
  name = NULL,
  project = NULL,
  scenario = NULL,
  summary = NULL,
  optional = FALSE,
  empty = FALSE,
  lookupsAsFactors = TRUE,
  sqlStatement = list(select = "SELECT *", groupBy = ""),
  includeKey = FALSE,
  forceElements = FALSE,
  fastQuery = FALSE
)
```

```

)

## S4 method for signature 'character'
datasheet(
  ssimObject,
  name,
  project,
  scenario,
  summary,
  optional,
  empty,
  lookupsAsFactors,
  sqlStatement,
  includeKey,
  fastQuery
)

## S4 method for signature 'SsimObject'
datasheet(
  ssimObject,
  name = NULL,
  project = NULL,
  scenario = NULL,
  summary = NULL,
  optional = FALSE,
  empty = FALSE,
  lookupsAsFactors = TRUE,
  sqlStatement = list(select = "SELECT *", groupBy = ""),
  includeKey = FALSE,
  forceElements = FALSE,
  fastQuery = FALSE
)

```

Arguments

<code>ssimObject</code>	SsimLibrary/Project/Scenario, or list of objects. Note that all objects in a list must be of the same type, and belong to the same library.
<code>name</code>	Character or vector of these. Sheet name(s). If NULL, all datasheets in the <code>ssimObject</code> will be returned. Note that setting <code>summary=FALSE</code> and <code>name=NULL</code> pulls all datasheets, which is time consuming and not generally recommended.
<code>project</code>	Character, numeric, or vector of these. One or more Project names, ids or objects. Note that integer ids are slightly faster.
<code>scenario</code>	Character, numeric, or vector of these. One or more Scenario names, ids or objects. Note that integer ids are slightly faster.
<code>summary</code>	Logical. If TRUE returns a dataframe of sheet names and other info. If FALSE returns dataframe or list of dataframes.
<code>optional</code>	Logical. If <code>summary=TRUE</code> and <code>optional=TRUE</code> returns only scope, name and <code>displayName</code> . If <code>summary=FALSE</code> and <code>optional=TRUE</code> returns all of the datasheet's columns, including the optional columns. If <code>summary=TRUE</code> , <code>optional=FALSE</code> , returns only those columns that are mandatory and contain data (if <code>empty=FALSE</code>). Ignored if <code>summary=FALSE</code> , <code>empty=FALSE</code> and <code>lookupsAsFactors=FALSE</code> .

<code>empty</code>	Logical. If TRUE returns empty dataframes for each datasheet. Ignored if <code>summary=TRUE</code> .
<code>lookupsAsFactors</code>	Logical. If TRUE (default) dependencies returned as factors with allowed values (levels). Set FALSE to speed calculations. Ignored if <code>summary=TRUE</code> .
<code>sqlStatement</code>	List returned by <code>sqlStatement()</code> . SELECT and GROUP BY SQL statements passed to SQLite database. Ignored if <code>summary=TRUE</code> .
<code>includeKey</code>	Logical. If TRUE include primary key in table.
<code>forceElements</code>	Logical. If FALSE and name has a single element returns a dataframe; otherwise returns a list of dataframes. Ignored if <code>summary=TRUE</code> .
<code>fastQuery</code>	Logical. If TRUE, the request is optimized for performance. Ignored if combined with <code>summary</code> , <code>empty</code> , or <code>sqlStatement</code> flags.

Details

If `summary=TRUE` or `summary=NULL` and `name=NULL` a dataframe describing the datasheets is returned. If `optional=TRUE` columns include: `scope`, `package`, `name`, `displayName`, `isSingle`, `isOutput`, `data`. `data` only displayed for scenarios. `dataInherited` and `dataSource` columns added if a scenario has dependencies. If `optional=FALSE` columns include: `scope`, `name`, `displayName`. All other arguments are ignored.

Otherwise, for each element in `name` a datasheet is returned as follows:

- If `lookupsAsFactors=TRUE` (default): Each column is given the correct data type, and dependencies returned as factors with allowed values (levels). A warning is issued if the lookup has not yet been set.
- If `empty=TRUE`: Each column is given the correct data type. Fast (1 less console command).
- If `empty=FALSE` and `lookupsAsFactors=FALSE`: Column types are not checked, and the optional argument is ignored. Fast (1 less console command).
- If `ssimObject` is a list of Scenario or Project objects (output from `run()`, `scenario()` or `project()`): Adds `ScenarioID/ProjectID` column if appropriate.
- If `scenario/project` is a vector: Adds `ScenarioID/ProjectID` column as necessary.
- If requested datasheet has scenario scope and contains info from more than one scenario: `ScenarioID/ScenarioName/ScenarioParent` columns identify the scenario by name, id, and parent (if a result scenario).
- If requested datasheet has project scope and contains info from more than one project: `ProjectID/ProjectName` columns identify the project by name and id.

Value

If `summary=TRUE` returns a dataframe of datasheet names and other info, otherwise returns a dataframe or list of these.

datasheetRaster	<i>Get spatial inputs or outputs from a Scenario(s).</i>
-----------------	--

Description

Get spatial inputs or outputs from one or more SyncroSim scenarios.

Usage

```
datasheetRaster(  
  ssimObject,  
  datasheet,  
  column = NULL,  
  scenario = NULL,  
  iteration = NULL,  
  timestep = NULL,  
  subset = NULL,  
  forceElements = FALSE  
)  
  
## S4 method for signature 'character'  
datasheetRaster(  
  ssimObject,  
  datasheet,  
  column = NULL,  
  scenario = NULL,  
  iteration = NULL,  
  timestep = NULL,  
  subset = NULL,  
  forceElements = FALSE  
)  
  
## S4 method for signature 'list'  
datasheetRaster(  
  ssimObject,  
  datasheet,  
  column = NULL,  
  scenario = NULL,  
  iteration = NULL,  
  timestep = NULL,  
  subset = NULL,  
  forceElements = FALSE  
)  
  
## S4 method for signature 'SsimObject'  
datasheetRaster(  
  ssimObject,  
  datasheet,  
  column = NULL,  
  scenario = NULL,  
  iteration = NULL,
```

```

    timestep = NULL,
    subset = NULL,
    forceElements = FALSE
)

## S4 method for signature 'Scenario'
datasheetRaster(
  ssimObject,
  datasheet,
  column = NULL,
  scenario = NULL,
  iteration = NULL,
  timestep = NULL,
  subset = NULL,
  forceElements = FALSE
)

```

Arguments

ssimObject	SsimLibrary/Project/Scenario or list of Scenarios. If SsimLibrary/Project, then scenario argument is required.
datasheet	character string. The name of the datasheet containing the raster data.
column	character string. The name of the column in the datasheet containing the file-names for raster data. If NULL then use the first column that contains raster filenames.
scenario	character string, integer, or vector of these. The scenarios to include. Required if ssimObject is an SsimLibrary/Project, ignored if ssimObject is a list of Scenarios.
iteration	integer, character string, or vector of integer/character strings. Iteration(s) to include. If NULL then all iterations are included. If no Iteration column in the datasheet, then ignored.
timestep	integer, character string, or vector of integer/character string. Timestep(s) to include. If NULL then all timesteps are included. If no Timestep column in the datasheet, then ignored.
subset	logical expression indicating datasheet rows to return. e.g. expression(grepl("Ts0001",Filename,fixed)) See subset() for details.
forceElements	logical. If TRUE then returns a single raster as a RasterStack; otherwise returns a single raster as a RasterLayer directly.

Details

The names() of the returned raster stack contain metadata. For datasheets without Filename this is: paste0(<datasheet name>,".Scn",<scenario id>,".",<tif name>) For datasheets containing Filename this is: paste0(<datasheet name>,".Scn",<scenario id>,".It",<iteration>,".Ts",<timestep>)

Value

A RasterLayer, RasterStack or RasterBrick object. See raster package documentation for details.

Examples

```
## Not run:
## Not run as it would require a result scenario (long runtime)
datasheetRaster(myResult,
  datasheet = "OutputSpatialState",
  subset = expression(grepl("Ts0001", Filename, fixed = TRUE))
)

## End(Not run)
```

dateModified	<i>The last date a SsimLibrary/Project/Scenario was modified.</i>
--------------	---

Description

The most recent modification date of an SsimLibrary/Project/Scenario.

Usage

```
dateModified(ssimObject)

## S4 method for signature 'character'
dateModified(ssimObject)

## S4 method for signature 'SsimLibrary'
dateModified(ssimObject)

## S4 method for signature 'Project'
dateModified(ssimObject)

## S4 method for signature 'Scenario'
dateModified(ssimObject)
```

Arguments

ssimObject SsimLibrary/Project/Scenario.

Value

A character string of the date and time of the most recent modification to the ssimObject provided as input.

delete

Delete library, project, scenario, datasheet

Description

Deletes one or more items. Note that this is irreversible.

Usage

```
delete(
  ssimObject,
  project = NULL,
  scenario = NULL,
  datasheet = NULL,
  force = FALSE
)

## S4 method for signature 'character'
delete(
  ssimObject,
  project = NULL,
  scenario = NULL,
  datasheet = NULL,
  force = FALSE
)

## S4 method for signature 'SsimObject'
delete(
  ssimObject,
  project = NULL,
  scenario = NULL,
  datasheet = NULL,
  force = FALSE
)
```

Arguments

ssimObject	SsimLibrary/Project/Scenario, or path to a library.
project	character string, numeric, or vector of these. One or more project names or ids. Note that project argument is ignored if ssimObject is a list. Note that integer ids are slightly faster.
scenario	character string, numeric, or vector of these. One or more scenario names or ids. Note that scenario argument is ignored if ssimObject is a list. Note that integer ids are slightly faster.
datasheet	character string or vector of these. One or more datasheet names.
force	logical. If FALSE (default), user will be prompted to approve removal of each item.

Value

This function returns invisibly a list of boolean values corresponding to each of the input: 'TRUE' upon success (i.e. successful deletion) and 'FALSE' upon failure.

Examples

```
temp_dir <- tempdir()
myses <- session()
myLibrary <- ssimLibrary(name = file.path(temp_dir, "testlib"), session = myses)

myProject <- project(myLibrary, project = "a project")
project(myLibrary)
delete(myLibrary, project = "a project", force = TRUE)
project(myLibrary)
```

deleteBreakpoint	<i>Delete a Scenario breakpoint.</i>
------------------	--------------------------------------

Description

This function will delete a Scenario breakpoint.

Usage

```
deleteBreakpoint(x, transformerName = NULL, breakpointType = NULL)

## S4 method for signature 'Scenario'
deleteBreakpoint(x, transformerName = NULL, breakpointType = NULL)
```

Arguments

x A SyncroSim Scenario.

transformerName A Stochastic Time Transformer (e.g. stsim_Runtime). Optional.

breakpointType bi: before iteration; ai: after iteration; bt: before timestep; at: after timestep. Optional.

Value

A SyncroSim Scenario with an updated list of breakpoints.

Examples

```
temp_dir <- tempdir()
myses <- session()
mylib <- ssimLibrary(name = file.path(temp_dir, "testlib"), session = myses)
myScenario <- scenario(mylib, "testScenario")

myScenario <- deleteBreakpoint(myScenario)
myScenario <- deleteBreakpoint(myScenario, transformerName = "stsim_Runtime")
```

deleteModule	<i>Delete module or modules</i>
--------------	---------------------------------

Description

Deprecated. See: [deletePackage](#).

Usage

```
deleteModule(name, session = NULL, force = FALSE)

## S4 method for signature 'ANY,missingOrNULLOrChar'
deleteModule(name, session = NULL, force = FALSE)

## S4 method for signature 'ANY,Session'
deleteModule(name, session = NULL, force = FALSE)
```

Arguments

name	Character string or vector of these. A module or vector of modules to remove. See <code>modules()</code> for options.
session	Session.
force	logical. If TRUE, delete without requiring confirmation from user.

Value

Returns "saved" or error message.

deletePackage	<i>Deletes a package</i>
---------------	--------------------------

Description

Deletes a package from your SyncroSim installation.

Usage

```
deletePackage(name, session = NULL, force = FALSE)

## S4 method for signature 'ANY,character'
deletePackage(name, session = NULL, force = FALSE)

## S4 method for signature 'ANY,missingOrNULL'
deletePackage(name, session = NULL, force = FALSE)

## S4 method for signature 'ANY,Session'
deletePackage(name, session = NULL, force = FALSE)
```

Arguments

name	Character. The name of the package to delete.
session	Session.
force	logical. If T, delete without requiring confirmation from user.

Value

This function invisibly returns 'TRUE' upon success (i.e. successful deletion) and 'FALSE' upon failure.

dependency	<i>Set or remove Scenario dependency(s), or get existing dependencies.</i>
------------	--

Description

Set or remove Scenario dependency(s), or get existing dependencies.

Usage

```
dependency(scenario, dependency = NULL, remove = FALSE, force = FALSE)

## S4 method for signature 'character'
dependency(scenario, dependency = NULL, remove = FALSE, force = FALSE)

## S4 method for signature 'Scenario'
dependency(scenario, dependency = NULL, remove = FALSE, force = FALSE)
```

Arguments

scenario	character string, integer, or vector of these. Name or ID of scenario(s) to which a dependency is to be added (or has been already added if remove=TRUE). If NULL then ssimObject must be a Scenario. Note that integer ids are slightly faster.
dependency	Scenario, character string, integer, or list/vector of these. The scenario(s) that are the source of the dependency, in order from lowest to highest precedence. If NULL other arguments are ignored and the list of existing dependencies is returned.
remove	logical. If F (default) dependencies are added. If T, dependencies are removed.
force	logical. If F (default) prompt before removing dependencies.

Details

If dependency==NULL, other arguments are ignored, and set of existing dependencies is returned in order of precedence (from highest to lowest precedence). Otherwise, returns list of saved or error messages for each dependency of each scenario.

Note that the order of dependencies can be important - dependencies added most recently take precedence over existing dependencies. So, dependencies included in the dependency argument take precedence over any other existing dependencies. If the dependency argument includes more than one element, elements are ordered from lowest to highest precedence.

Value

If dependency is NULL, a dataframe of existing dependencies, or list of these if multiple inputs are provided. If dependency is not NULL, the function invisibly returns a list bearing the names of the dependencies inputted and carrying a logical 'TRUE' upon success (i.e. successful addition or deletion) and 'FALSE' upon failure.

description	<i>Description of an SsimLibrary/Project/Scenario.</i>
-------------	--

Description

The description of an SsimLibrary/ProjectScenario.

Usage

```
description(ssimObject)

## S4 method for signature 'character'
description(ssimObject)

## S4 method for signature 'SsimObject'
description(ssimObject)
```

Arguments

ssimObject SsimLibrary/Project/Scenario.

Value

A character string describing the ssimObject.

description<-	<i>Set the description of an SsimLibrary/Project/Scenario.</i>
---------------	--

Description

Set the description of an SsimLibrary/ProjectScenario.

Usage

```
description(ssimObject) <- value

## S4 replacement method for signature 'character'
description(ssimObject) <- value

## S4 replacement method for signature 'SsimObject'
description(ssimObject) <- value
```

Arguments

ssimObject	Scenario/Project/SsimLibrary.
value	The new description.

Value

The object with updated description.

disableAddon	<i>Disable addon or addons.</i>
--------------	---------------------------------

Description

Disable addon or addons of an SsimLibrary, or Project/Scenario with an associated SsimLibrary.

Usage

```
disableAddon(ssimLibrary, name)

## S4 method for signature 'character'
disableAddon(ssimLibrary, name)

## S4 method for signature 'SsimLibrary'
disableAddon(ssimLibrary, name)
```

Arguments

ssimLibrary	SsimLibrary.
name	Character string or vector of addon names.

Value

This function invisibly returns 'TRUE' upon success (i.e. successful deactivation of the addon) and 'FALSE' upon failure.

Examples

```
temp_dir <- tempdir()
myses <- session()
myLibrary <- ssimLibrary(name = file.path(temp_dir, "testlib"), session = myses)

enableAddon(myLibrary, c("stsimecodep"))
addon(myLibrary)
disableAddon(myLibrary, c("stsimecodep"))
addon(myLibrary)
```

enableAddon	<i>Enable addon or addons.</i>
-------------	--------------------------------

Description

Enable addon or addons of a SsimLibrary.

Usage

```
enableAddon(ssimLibrary, name)

## S4 method for signature 'character'
enableAddon(ssimLibrary, name)

## S4 method for signature 'SsimLibrary'
enableAddon(ssimLibrary, name)
```

Arguments

ssimLibrary	SsimLibrary.
name	Character string or vector of addon names.

Value

This function invisibly returns 'TRUE' upon success (i.e. successful activation of the addon) and 'FALSE' upon failure.

Examples

```
temp_dir <- tempdir()
myses <- session()
myLibrary <- ssimLibrary(name = file.path(temp_dir, "testlib"), session = myses)

enableAddon(myLibrary, c("stsim-ecological-departure"))
addon(myLibrary)
disableAddon(myLibrary, c("stsim-ecological-departure"))
addon(myLibrary)
```

envInputFolder	<i>SyncroSim DataSheet Input Folder</i>
----------------	---

Description

Creates and returns a SyncroSim DataSheet Input Folder.

Usage

```
envInputFolder(scenario, datasheetName)
```


Arguments

scenario Scenario. A SyncroSim result scenario.
datasheetName character. The input datasheet name.

Value

Returns a folder name for the specified data sheet.

envOutputFolder	<i>SyncroSim DataSheet Output Folder</i>
-----------------	--

Description

Creates and returns a SyncroSim DataSheet Output Folder.

Usage

```
envOutputFolder(scenario, datasheetName)
```

Arguments

scenario Scenario. A SyncroSim result scenario.
datasheetName character. The output datasheet name.

Value

Returns a folder name for the specified data sheet.

envReportProgress	<i>Reports progress for a SyncroSim simulation</i>
-------------------	--

Description

Reports progress for a SyncroSim simulation.
Begins a SyncroSim simulation.
Steps a SyncroSim simulation.
Ends a SyncroSim simulation.

Usage

```
envReportProgress(iteration, timestep)  
  
envBeginSimulation(totalSteps)  
  
envStepSimulation()  
  
envEndSimulation()
```

Arguments

iteration	integer. The current iteration.
timestep	integer. The current timestep.
totalSteps	integer. The total number of steps in the simulation.

Value

No returned value, used for side effects.

No returned value, used for side effects.

envTempFolder	<i>SyncroSim Temporary Folder</i>
---------------	-----------------------------------

Description

Creates and returns a SyncroSim Temporary Folder.

Usage

```
envTempFolder(folderName)
```

Arguments

folderName	character. The folder name.
------------	-----------------------------

Value

Returns a temporary folder name.

filepath	<i>The path to a SyncroSim object on disk</i>
----------	---

Description

The path to a SyncroSim Session, SSimLibrary, Project or Scenario on disk.

Usage

```
filepath(ssimObject)
```

```
## S4 method for signature 'character'
filepath(ssimObject)
```

```
## S4 method for signature 'Session'
filepath(ssimObject)
```

```
## S4 method for signature 'SsimObject'
filepath(ssimObject)
```

Arguments

ssimObject An object containing a filepath.

Value

A character string: the path to a SyncroSim object on disk.

ignoreDependencies	<i>Ignore Dependencies for a Scenario.</i>
--------------------	--

Description

Retrieves the Ignore Dependencies Datafeeds for a Scenario.

Usage

```
ignoreDependencies(ssimObject)

## S4 method for signature 'character'
ignoreDependencies(ssimObject)

## S4 method for signature 'Scenario'
ignoreDependencies(ssimObject)
```

Arguments

ssimObject Scenario.

Value

Returns Ignore Dependencies Datafeeds.

ignoreDependencies<-	<i>Ignore Dependencies Datafeeds for a Scenario.</i>
----------------------	--

Description

Sets the Ignore Dependencies Datafeed for a Scenario.

Usage

```
ignoreDependencies(ssimObject) <- value

## S4 replacement method for signature 'character'
ignoreDependencies(ssimObject) <- value

## S4 replacement method for signature 'Scenario'
ignoreDependencies(ssimObject) <- value
```

Arguments

ssimObject Scenario.
 value Character.

Value

Returns the updated ssimObject.

info	<i>Information about an library</i>
------	-------------------------------------

Description

Get basic information about a Library.

Usage

```
info(ssimLibrary)

## S4 method for signature 'SsimLibrary'
info(ssimLibrary)
```

Arguments

ssimLibrary A SsimLibrary object.

Value

Returns a data.frame with information on the properties of the library object.

mergeDependencies	<i>Merge Dependencies for a Scenario.</i>
-------------------	---

Description

Retrieves whether or not a Scenario is configured to merge dependencies at run time.

Usage

```
mergeDependencies(ssimObject)

## S4 method for signature 'character'
mergeDependencies(ssimObject)

## S4 method for signature 'Scenario'
mergeDependencies(ssimObject)
```

Arguments

ssimObject Scenario.

Value

Returns a logical: 'TRUE' if the scenario is configured to merge dependencies at run time, and 'FALSE' otherwise.

```
mergeDependencies<-      Merge Dependencies for a Scenario.
```

Description

Sets whether or not a Scenario is configured to merge dependencies at run time.

Usage

```
mergeDependencies(ssimObject) <- value

## S4 replacement method for signature 'character'
mergeDependencies(ssimObject) <- value

## S4 replacement method for signature 'Scenario'
mergeDependencies(ssimObject) <- value
```

Arguments

ssimObject	Scenario.
value	Logical. If TRUE the Scenario will be set to merge dependencies at run time.

Value

Returns the updated ssimObject.

model	<i>Installed models</i>
-------	-------------------------

Description

Deprecated. See: [package](#).

Usage

```
model(ssimObject = NULL)

## S4 method for signature 'character'
model(ssimObject = NULL)

## S4 method for signature 'missingOrNULL'
model(ssimObject = NULL)

## S4 method for signature 'Session'
model(ssimObject = NULL)

## S4 method for signature 'SsimLibrary'
model(ssimObject = NULL)
```

Arguments

ssimObject Session or SsimLibrary.

Value

A dataframe of models (for Session) or named vector of character strings (for SsimLibrary).

module	<i>Installed modules</i>
--------	--------------------------

Description

Deprecated. See: [package](#).

Usage

```
module(session)

## S4 method for signature 'missingOrNULL'
module(session)

## S4 method for signature 'character'
module(session)

## S4 method for signature 'Session'
module(session)
```

Arguments

session Session.

Value

Returns a dataframe of modules.

name	<i>The name of a SyncroSim library, project or scenario.</i>
------	--

Description

Retrieves the name of an SsimLibrary, Project or Scenario.

Usage

```

name(ssimObject)

## S4 method for signature 'character'
name(ssimObject)

## S4 method for signature 'SsimLibrary'
name(ssimObject)

## S4 method for signature 'Scenario'
name(ssimObject)

## S4 method for signature 'Project'
name(ssimObject)

```

Arguments

ssimObject SsimLibrary, Project, or Scenario.

Value

Character string: the name of the ssimObject.

name<-	<i>Set ssimObject name.</i>
--------	-----------------------------

Description

Set the name of a SyncroSim Project, Scenario or Library.

Usage

```

name(ssimObject) <- value

## S4 replacement method for signature 'character'
name(ssimObject) <- value

## S4 replacement method for signature 'SsimLibrary'
name(ssimObject) <- value

## S4 replacement method for signature 'Project'
name(ssimObject) <- value

## S4 replacement method for signature 'Scenario'
name(ssimObject) <- value

```

Arguments

ssimObject Scenario/Project/SsimLibrary.
value The updated ssimObject.

Value

The updated ssim Object.

owner	<i>The owner of a SsimLibrary/Project/Scenario.</i>
-------	---

Description

Retrieves the owner of a SsimLibrary/ProjectScenario.

Usage

```
owner(ssimObject)

## S4 method for signature 'character'
owner(ssimObject)

## S4 method for signature 'SsimLibrary'
owner(ssimObject)

## S4 method for signature 'Project'
owner(ssimObject)

## S4 method for signature 'Scenario'
owner(ssimObject)
```

Arguments

ssimObject SsimLibrary/Project/Scenario.

Value

A character string: the owner of the ssimObject.

owner<-	<i>Set the owner of an SsimLibrary/Project/Scenario.</i>
---------	--

Description

Set the owner of an SsimLibrary/Project/Scenario.

Usage

```
owner(ssimObject) <- value

## S4 replacement method for signature 'character'
owner(ssimObject) <- value

## S4 replacement method for signature 'SsimObject'
owner(ssimObject) <- value
```


Arguments

ssimObject	Scenario/Project/SsimLibrary.
value	The new owner.

Value

The updated ssimObject.

package	<i>Installed or available packages</i>
---------	--

Description

Packages installed or available for this version of SyncroSim.

Usage

```
package(session, installed = TRUE)

## S4 method for signature 'missingOrNULL'
package(session, installed = TRUE)

## S4 method for signature 'character'
package(session, installed = TRUE)

## S4 method for signature 'Session'
package(session, installed = TRUE)
```

Arguments

session	Session.
installed	Logical. 'TRUE' to list installed packages and 'FALSE' to list available packages.

Value

Returns a data.frame of packages installed.

parentId	<i>The parent scenario id of a SyncroSim Scenario.</i>
----------	--

Description

Retrieves the id of the parent of a SyncroSim results scenario.

Usage

```
parentId(scenario)

## S4 method for signature 'character'
parentId(scenario)

## S4 method for signature 'Scenario'
parentId(scenario)
```

Arguments

scenario A Scenario object.

Value

An integer id of the parent scenario. If the input scenario does not have a parent, the function returns 'NA'.

printCmd	<i>Get printCmd of a Session.</i>
----------	-----------------------------------

Description

Retrieves a printCmd setting of a Session object.

Usage

```
printCmd(session = NULL)

## S4 method for signature 'Session'
printCmd(session = NULL)

## S4 method for signature 'missingOrNULLOrChar'
printCmd(session = NULL)
```

Arguments

session Session or character. A Session object or path to a session. If NULL, the default session will be used.

Value

Returns a logical value: 'TRUE' if the session is configured to print commands and 'FALSE' if it is not.

project	<i>Create or open a project or projects.</i>
---------	--

Description

Creates or retrieves a project or multiple projects from a library.

Usage

```
project(
  ssimObject = NULL,
  project = NULL,
  sourceProject = NULL,
  summary = NULL,
  forceElements = FALSE,
  overwrite = FALSE
)
```

Arguments

ssimObject	SsimLibrary/Scenario or character. A ssimObject containing a filepath to a library, or a filepath.
project	Character, integer, or vector of these. Names or ids of one or more projects. Note that integer ids are slightly faster.
sourceProject	Character, integer, or Project object. If not NULL, new projects will be copies of the sourceProject.
summary	Logical. If TRUE then return the project(s) in a dataframe with the projectId, name, description, owner, dateModified, readOnly. Default is TRUE if project=NULL and ssimObject is not Scenario/Project, FALSE otherwise.
forceElements	Logical. If TRUE then returns a single project as a named list; otherwise returns a single project as a Project object. Applies only when summary=FALSE.
overwrite	Logical. If TRUE an existing Project will be overwritten.

Details

For each element of project:

- If element identifies an existing project: Returns the existing Project.
- If element identifies more than one project: Error.
- If element does not identify an existing project: Creates a new Project named element. Note that SyncroSim automatically assigns an id to a new project.

Value

Returns a Project object representing a SyncroSim project. If summary is 'TRUE', returns a dataframe of project names and descriptions.

Examples

```
# Create a Library and create a new Project
temp_dir <- tempdir()
myses <- session()
myLibrary <- ssimLibrary(name = file.path(temp_dir,"testlib"), session = myses)

myProject <- project(ssimObject = myLibrary, project = "My new project name")

# Get a named list of existing Projects.
# Each element in the list is named by a character version of the Project ID.
myProjects <- project(myLibrary, summary = FALSE)
names(myProjects) # vector of the project ids

# Get an existing Project.
myProject <- myProjects[[1]]
myProject <- project(myLibrary, project = "My new project name")

# Get/set the project properties
name(myProject)
name(myProject) <- "New project name"
```

Project-class

SyncroSim Project class

Description

Project object representing a SyncroSim Project.

Slots

`session` The Session associated with the Project's Library.

`filepath` The path to the Project's Library on disk.

`datasheetNames` Names and scopes of datasheets in the Project's Library.

`projectId` The Project id.

See Also

See [project](#) for options when creating or loading a SyncroSim Project.

projectId	<i>The projectId of a SyncroSim project or scenario.</i>
-----------	--

Description

Retrieves the projectId of a SyncroSim Project or Scenario.

Usage

```
projectId(ssimObject)

## S4 method for signature 'character'
projectId(ssimObject)

## S4 method for signature 'Project'
projectId(ssimObject)

## S4 method for signature 'Scenario'
projectId(ssimObject)
```

Arguments

ssimObject Project/Scenario.

Value

Returns an integer project id.

readOnly	<i>Read-only status of a SsimLibrary/Project/Scenario.</i>
----------	--

Description

Whether or not a SsimLibrary/ProjectScenario is read-only.

Usage

```
readOnly(ssimObject)

## S4 method for signature 'character'
readOnly(ssimObject)

## S4 method for signature 'SsimLibrary'
readOnly(ssimObject)

## S4 method for signature 'Project'
readOnly(ssimObject)

## S4 method for signature 'Scenario'
readOnly(ssimObject)
```

Arguments

ssimObject SsimLibrary/Project/Scenario.

Value

Returns a logical value: 'TRUE' if the ssimObject is read only and 'FALSE' otherwise.

readOnly<- *Set the read/write status of a SsimLibrary/Project/Scenario.*

Description

Set the read-only status of a SsimLibrary/Project/Scenario. Applies to child objects if ssimObject is a SsimLibrary or Project.

Usage

```
readOnly(ssimObject) <- value

## S4 replacement method for signature 'character'
readOnly(ssimObject) <- value

## S4 replacement method for signature 'SsimObject'
readOnly(ssimObject) <- value
```

Arguments

ssimObject Scenario/Project/SsimLibrary.
value Logical. If T the ssimObject will be read-only.

Value

The updated ssimObject.

rsyncrosim *rsyncrosim: The R interface to SyncroSim: <https://syncrosim.com/>*

Description

rsyncrosim provides an interface to SyncroSim, a generalized framework for running and managing scenario-based stochastic simulations over space and time. Different kinds of simulation models can "plug-in" to SyncroSim as packages and take advantage of general features common to many kinds of simulation models, such as defining scenarios of inputs, running Monte Carlo simulations, and viewing charts and maps of outputs.

Details

To learn more about rsyncrosim, start with the vignette tutorial: `browseVignettes("rsyncrosim")`.

run*Run scenarios*

Description

Run one or more SyncroSim scenarios.

Usage

```
run(  
  ssimObject,  
  scenario = NULL,  
  summary = FALSE,  
  jobs = 1,  
  transformerName = NULL,  
  forceElements = FALSE  
)  
  
## S4 method for signature 'character'  
run(  
  ssimObject,  
  scenario = NULL,  
  summary = FALSE,  
  jobs = 1,  
  transformerName = NULL,  
  forceElements = FALSE  
)  
  
## S4 method for signature 'list'  
run(  
  ssimObject,  
  scenario = NULL,  
  summary = FALSE,  
  jobs = 1,  
  transformerName = NULL,  
  forceElements = FALSE  
)  
  
## S4 method for signature 'SsimObject'  
run(  
  ssimObject,  
  scenario = NULL,  
  summary = FALSE,  
  jobs = 1,  
  transformerName = NULL,  
  forceElements = FALSE  
)  
  
## S4 method for signature 'BreakpointSession'  
run(ssimObject, scenario, summary, jobs, forceElements)
```

Arguments

ssimObject	SsimLibrary/Project/Scenario or a list of Scenarios. Or the path to a library on disk.
scenario	Character, integer, or vector of these. Scenario names or ids. Or NULL. Note that integer ids are slightly faster.
summary	Logical. If FALSE (default) result Scenario objects are returned. If TRUE (faster) result scenario ids are returned.
jobs	Integer. The number of jobs to run. Passed to SyncroSim where multithreading is handled.
transformerName	Character. The name of the transformer to run.
forceElements	Logical. If TRUE then returns a single result scenario as a named list; otherwise returns a single result scenario as a Scenario object. Applies only when summary=FALSE.

Details

Note that breakpoints are ignored unless ssimObject is a single scenario.

Value

If summary = FALSE, returns a result Scenario object or a named list of result Scenarios. The name is the parent scenario for each result. If summary = TRUE, returns summary info for result scenarios.

runLog	<i>The run log of a result Scenario</i>
--------	---

Description

The run log of a result Scenario.

Usage

```
runLog(scenario)

## S4 method for signature 'character'
runLog(scenario)

## S4 method for signature 'Scenario'
runLog(scenario)
```

Arguments

scenario	A Scenario object.
----------	--------------------

Value

Returns a character string: the run log for a result scenario.

saveDatasheet	<i>Save datasheet(s)</i>
---------------	--------------------------

Description

Saves datasheets to a SsimLibrary/Project/Scenario.

Usage

```
saveDatasheet(  
  ssimObject,  
  data,  
  name = NULL,  
  fileData = NULL,  
  append = NULL,  
  forceElements = FALSE,  
  force = FALSE,  
  breakpoint = FALSE,  
  import = TRUE,  
  path = NULL  
)  
  
## S4 method for signature 'character'  
saveDatasheet(  
  ssimObject,  
  data,  
  name = NULL,  
  fileData = NULL,  
  append = NULL,  
  forceElements = FALSE,  
  force = FALSE,  
  breakpoint = FALSE,  
  import = TRUE,  
  path = NULL  
)  
  
## S4 method for signature 'SsimObject'  
saveDatasheet(  
  ssimObject,  
  data,  
  name = NULL,  
  fileData = NULL,  
  append = NULL,  
  forceElements = FALSE,  
  force = FALSE,  
  breakpoint = FALSE,  
  import = TRUE,  
  path = NULL  
)
```

Arguments

ssimObject	SsimLibrary/Project/Scenario.
data	A dataframe, named vector, or list of these. One or more datasheets to load.
name	Character or vector of these. The name(s) of the datasheet(s) to be saved. If a vector of names is provided, then a list must be provided for the data argument. Names provided here will override those provided with data argument's list.
fileData	Named list or raster stack. Names are file names (without paths), corresponding to entries in data. The elements are objects containing the data associated with each name. Currently only supports Raster objects as elements.
append	Logical. If TRUE, the incoming data will be appended to the datasheet if possible. Default TRUE for project/library-scope datasheets, and FALSE for scenario-scope datasheets. See 'details' for more information about this argument.
forceElements	Logical. If FALSE (default) a single return message will be returned as a character string. Otherwise it will be returned in a list.
force	Logical. If datasheet scope is project/library, and append=FALSE, datasheet will be deleted before loading the new data. This can also delete other definitions and results, so user will be prompted for approval unless force=TRUE.
breakpoint	Set to TRUE when modifying datasheets in a breakpoint function.
import	Logical. Set to TRUE to import the data after saving.
path	Character. An optional output path.

Details

ssimObject/project/scenario should identify a single ssimObject.

If fileData !=NULL, each element of names(fileData) should correspond uniquely to at most one entry in data. If a name is not found in data the element will be ignored with a warning. If names(fileData) are full filepaths, rsyncrosim will write each object to the corresponding path for subsequent loading by SyncroSim. Note this is generally more time-consuming because the files must be written twice. If names(fileData) are not filepaths (faster, recommended), rsyncrosim will write each element directly to the appropriate SyncroSim input/output folders. rsyncrosim will write each element of fileData directly to the appropriate SyncroSim input/output folders. If fileData != NULL, data should be a dataframe, vector, or list of length 1, not a list of length >1.

About the 'append' argument:

- A datasheet is a **VALIDATION SOURCE** if its data can be used to validate column values in a different datasheet.
- The append argument will be ignored if the datasheet is a validation source and has a project scope. In this case the data will be **MERGED**.

Value

This function invisibly returns a vector or list of logical values for each input: 'TRUE' upon success (i.e.successful save) and 'FALSE' upon failure.

scenario	<i>Create or open one or more Scenarios.</i>
----------	--

Description

Create or retrieves one or more Scenarios from a library

Usage

```
scenario(
  ssimObject = NULL,
  scenario = NULL,
  sourceScenario = NULL,
  summary = NULL,
  results = FALSE,
  forceElements = FALSE,
  overwrite = FALSE
)
```

Arguments

ssimObject	SsimLibrary/Project or character. An ssimObject containing a filepath to a library, or a filepath.
scenario	Character, integer, or vector of these. Names or ids of one or more scenarios. Note integer ids are slightly faster.
sourceScenario	Character or integer. If not NULL, new scenarios will be copies of the sourceScenario.
summary	Logical. If TRUE then loads and returns the scenario(s) in a named vector/dataframe with the scenarioId, name, description, owner, dateModified, readOnly, parentId. Default is TRUE if scenario=NULL, FALSE otherwise.
results	Logical. If TRUE only return result scenarios.
forceElements	Logical. If TRUE then returns a single scenario as a named list; otherwise returns a single scenario as a Scenario object. Applies only when summary=FALSE.
overwrite	Logical. If TRUE an existing Scenario will be overwritten.

Details

For each element of scenario:

- If element/project/ssimObject uniquely identifies an existing scenario: Returns the existing Scenario
- If element/project/ssimObject uniquely identifies more than one existing scenario: Error
- If element/project/ssimObject do not identify an existing scenario or project: Error
- If element/project/ssimObject do not identify an existing scenario and element is numeric: Error - a name is required for new scenarios. SyncroSim will automatically assign an id when a scenario is created.
- If element/project/ssimObject do not identify an existing scenario and do identify a project, and element is a character string: Creates a new Scenario named element in the project. SyncroSim automatically assigns an id. If sourceScenario is not NULL the new scenario will be a copy of sourceScenario.

Value

A Scenario object representing a SyncroSim scenario, a list of Scenario objects, or a dataframe of scenario names and descriptions. If `summary = FALSE`, returns one or more [Scenario](#) objects representing SyncroSim scenarios. If `summary = TRUE`, returns scenario summary info.

Examples

```
# Create a new scenario
temp_dir <- tempdir()
myses <- session()
myLibrary <- ssimLibrary(name = file.path(temp_dir,"testlib"), session = myses)

myProject <- project(myLibrary, project = "a project")
myScenario <- scenario(myProject, scenario = "a scenario", overwrite = TRUE)
```

Scenario-class	<i>SyncroSim Scenario class</i>
----------------	---------------------------------

Description

Scenario object representing a SyncroSim Scenario.

Slots

`session` The Session associated with the Scenario.

`filepath` The path to the Scenario's Library on disk.

`datasheetNames` Names and scope of all datasheets in Scenario's Library.

`projectId` The project id.

`scenarioId` The scenario id.

`parentId` For a result scenario, this is the id of the parent scenario. 0 indicates this is not a result scenario.

`breakpoints` An (optional) list of Breakpoint objects.

See Also

See [scenario](#) for options when creating or loading a SyncroSim Scenario.

scenarioId	<i>The scenarioId of a scenario.</i>
------------	--------------------------------------

Description

Retrieves the scenarioId of a Scenario.

Usage

```
scenarioId(scenario)

## S4 method for signature 'character'
scenarioId(scenario)

## S4 method for signature 'Scenario'
scenarioId(scenario)
```

Arguments

scenario Scenario.

Value

Integer id of the input scenario.

session	<i>Creates or returns a SyncroSim session.</i>
---------	--

Description

Methods to create or return a SyncroSim session.

Usage

```
session(x = NULL, silent = TRUE, printCmd = FALSE)

## S4 method for signature 'missingOrNULLOrChar'
session(x = NULL, silent = TRUE, printCmd = FALSE)

## S4 method for signature 'SsimObject'
session(x = NULL, silent = TRUE, printCmd = FALSE)
```

Arguments

x	Character or SsimObject. An optional path to the SyncroSim installation.
silent	Logical. Applies only if x is a path or NULL. If TRUE, warnings from the console are ignored. Otherwise they are printed.
printCmd	Logical. Applies only if x is a path or NULL. If TRUE, arguments passed to the SyncroSim console are also printed. Helpful for debugging. FALSE by default.

Value

A SyncroSim Session object.

Examples

```
# Create Session
temp_dir <- tempdir()
mySession <- session()
myLibrary <- ssimLibrary(name = file.path(temp_dir,"testlib"), session = mySession)

filepath(mySession) # Lists the folder location of SyncroSim session
version(mySession) # Lists the version of SyncroSim session
package(mySession) # Dataframe of the packages installed with this version of SyncroSim
basePackage(mySession) # Dataframe of the base packages installed with this version of SyncroSim
```

Session-class

SyncroSim Session class

Description

A SyncroSim Session object contains a link to a SyncroSim installation. SsimLibrary, Project and Scenario objects contain a Session used to query and modify the object.

Slots

filepath The path to the SyncroSim installation.

silent If FALSE, all SyncroSim output with non-zero exit status is printed. Helpful for debugging. Default=TRUE.

printCmd If TRUE, arguments passed to the SyncroSim console are also printed. Helpful for debugging. Default=FALSE.

See Also

See [session](#) for options when creating a Session.

session<-

Set a SyncroSim session.

Description

Set the Session of a SsimLibrary, Project or Scenario object.

Usage

```

session(ssimObject) <- value

## S4 replacement method for signature 'character'
session(ssimObject) <- value

## S4 replacement method for signature 'SsimObject'
session(ssimObject) <- value

```

Arguments

ssimObject	SsimObject/Project/Scenario.
value	A SyncroSim Session.

Details

In order to avoid problems with SyncroSim version compatibility and library updating, the new session must have the same filepath as the session of the SsimObject e.g. `filepath(value)==filepath(session(ssimObject))`

Value

Returns a SyncroSim object containing a Session.

silent	<i>Check if a Session is silent</i>
--------	-------------------------------------

Description

Checks whether a SyncroSim Session is silent or not.

Usage

```

silent(session)

## S4 method for signature 'Session'
silent(session)

## S4 method for signature 'missingOrNULLOrChar'
silent(session)

```

Arguments

session	Session or character. A SyncroSim Session object or path to a session. If NULL, the default session will be used.
---------	---

Value

Returns a logical value: 'TRUE' if the session is silent and 'FALSE' otherwise.

silent<-	<i>Set silent property of a Session</i>
----------	---

Description

Set silent property of a session to TRUE or FALSE

Usage

```
silent(session) <- value

## S4 replacement method for signature 'character'
silent(session) <- value

## S4 replacement method for signature 'Session'
silent(session) <- value
```

Arguments

session	Session.
value	Logical.

Value

The updated ssimObject.

sqlStatement	<i>Construct an SQLite query</i>
--------------	----------------------------------

Description

Creates SELECT, GROUP BY and WHERE SQL statements. The resulting list of SQL statements will be converted to an SQLite database query by the datasheet() function.

Usage

```
sqlStatement(
  groupBy = NULL,
  aggregate = NULL,
  aggregateFunction = "SUM",
  where = NULL
)
```


Arguments

groupBy	Character string or vector of these. Vector of variables (column names) to GROUP BY.
aggregate	Character string or vector of these. Vector of variables (column names) to aggregate using aggregateFunction.
aggregateFunction	Character string. An SQL aggregate function (e.g. SUM, COUNT).
where	Named list. A list of subset variables. Names are column names, and elements are the values to be selected from each column.

Details

Variables are column names of the datasheet. See column names using `datasheet(empty=TRUE)`. Variables not included in `groupBy`, `aggregate` or `where` will be dropped from the table. Note that it is not possible to construct a complete SQL query at this stage, because the `datasheet()` function may add `ScenarioID` and/or `ProjectID` to the query.

Value

Returns a list of SELECT, GROUP BY and WHERE SQL statements used by `datasheet()` to construct an SQLite database query.

Examples

```
# Query the total Amount for each combination of ScenarioID, Iteration, Timestep and StateLabelXID,
# including only Timesteps 0,1 and 2, and Iterations 3 and 4.
mySQL <- sqlStatement(
  groupBy = c("ScenarioID", "Iteration", "Timestep", "StateLabelXID"),
  aggregate = c("Amount"), where = list(Timestep = c(0, 1, 2), Iteration = c(3, 4))
)
mySQL
```

ssimEnvironment

SyncroSim Environment

Description

Retrieves SyncroSim specific environment variables.

Usage

```
ssimEnvironment()
```

Value

Returns a data.frame of SyncroSim specific environment variables.

ssimLibrary	<i>Create or open a library</i>
-------------	---------------------------------

Description

Creates or opens a [SsimLibrary](#) object. If summary = TRUE, returns library summary info. If summary = NULL, returns library summary info if ssimObject is a SsimLibrary, SsimLibrary object otherwise.

Usage

```
ssimLibrary(
  name = NULL,
  summary = NULL,
  package = NULL,
  session = NULL,
  addon = NULL,
  forceUpdate = FALSE,
  overwrite = FALSE
)

## S4 method for signature 'SsimObject'
ssimLibrary(
  name = NULL,
  summary = NULL,
  package = NULL,
  session = NULL,
  addon = NULL,
  forceUpdate = FALSE,
  overwrite = FALSE
)

## S4 method for signature 'missingOrNULLOrChar'
ssimLibrary(
  name = NULL,
  summary = NULL,
  package = NULL,
  session = NULL,
  addon = NULL,
  forceUpdate = FALSE,
  overwrite = FALSE
)
```

Arguments

name	Character string, Project/Scenario/SsimLibrary. The path to a library or SsimObject.
summary	Logical. Default TRUE.
package	Character. The package type. The default is "stsim".
session	Session. If NULL, session() will be used.

addon	Character or character vector. One or more addons. See <code>addon()</code> for options.
forceUpdate	Logical. If FALSE (default) user will be prompted to approve any required updates. If TRUE, required updates will be applied silently.
overwrite	Logical. If TRUE an existing Library will be overwritten.

Details

- If name is SyncroSim Project or Scenario: Returns the [SsimLibrary](#) associated with the Project or Scenario.
- If name is NULL: Create/open a SsimLibrary in the current working directory with the filename SsimLibrary.ssim.
- If name is a string: If string is not a valid path treat as filename in working directory. If no file suffix provided in string then add .ssim. Attempts to open a library of that name. If library does not exist creates a library of type package in the current working directory.
- If given a name and a package: Create/open a library called <name>.ssim. Returns an error if the library already exists but is a different type of package.

Value

Returns a SsimLibrary object.

Examples

```
# Create or open a library using the default session
myLibrary <- ssimLibrary(name = file.path(tempdir(), "mylib"))

# Create library using a specific session
mySession <- session()
myLibrary <- ssimLibrary(name = file.path(tempdir(), "mylib"), session = mySession)

session(myLibrary)
filepath(myLibrary)
info(myLibrary)
```

SsimLibrary-class	<i>SyncroSim Library class</i>
-------------------	--------------------------------

Description

SsimLibrary object representing a SyncroSim Library.

Slots

session The SyncroSim Session.
 filepath The path to the Library on disk.
 datasheetNames The name and scope of all datasheets in the Library.

See Also

See [ssimLibrary](#) for options when creating or loading a SyncroSim Library.

ssimUpdate	<i>Apply updates</i>
------------	----------------------

Description

Apply updates to a SyncroSim Library, or a Project or Scenario associated with a Library.

Usage

```
ssimUpdate(ssimObject)

## S4 method for signature 'character'
ssimUpdate(ssimObject)

## S4 method for signature 'SsimObject'
ssimUpdate(ssimObject)
```

Arguments

ssimObject SsimLibrary/Project/Scenario.

Value

This function invisibly returns 'TRUE' upon success (i.e.successful update) and 'FALSE' upon failure.

tempfilepath	<i>The temporary file path to a SyncroSim object on disk</i>
--------------	--

Description

The temporary file path to a SyncroSim Session, SSimLibrary, Project or Scenario on disk.

Usage

```
tempfilepath(ssimObject)

## S4 method for signature 'character'
tempfilepath(ssimObject)

## S4 method for signature 'Session'
tempfilepath(ssimObject)

## S4 method for signature 'SsimObject'
tempfilepath(ssimObject)
```

Arguments

ssimObject An object containing a filepath.

Value

A character string: the temporary file path to a SyncroSim object on disk.

updatePackage	<i>Update Package</i>
---------------	-----------------------

Description

Updates a SyncroSim package.

Usage

```
updatePackage(name = NULL, session = NULL, listonly = FALSE)

## S4 method for signature 'ANY,character'
updatePackage(name = NULL, session = NULL, listonly = FALSE)

## S4 method for signature 'ANY,missingOrNULL'
updatePackage(name = NULL, session = NULL, listonly = FALSE)

## S4 method for signature 'ANY,Session'
updatePackage(name = NULL, session = NULL, listonly = FALSE)
```

Arguments

name	Character string. The name of the package to update. If NULL, all packages will be updated.
session	Session.
listonly	Logical. If TRUE, available updates are listed only.

Value

This function invisibly returns ‘TRUE’ upon success (i.e.successful update) and ‘FALSE’ upon failure.

version	<i>The SyncroSim version</i>
---------	------------------------------

Description

The version of a SyncroSim Session.

Usage

```
version(session = NULL)

## S4 method for signature 'character'
version(session = NULL)

## S4 method for signature 'missingOrNULL'
version(session = NULL)

## S4 method for signature 'Session'
version(session = NULL)
```

Arguments

session	Session.
---------	----------

Value

A character string e.g. "2.2.13".

Index

addBreakpoint, [4](#)
addBreakpoint, Scenario-method
 (addBreakpoint), [4](#)
addModule, [5](#)
addModule, character-method (addModule),
 [5](#)
addon, [5](#)
addon, character-method (addon), [5](#)
addon, missingOrNULL-method (addon), [5](#)
addon, Session-method (addon), [5](#)
addon, SsimObject-method (addon), [5](#)
addPackage, [5](#), [6](#)
addPackage, ANY, character-method
 (addPackage), [6](#)
addPackage, ANY, missingOrNULL-method
 (addPackage), [6](#)
addPackage, ANY, Session-method
 (addPackage), [6](#)
addPackageFile, [5](#), [7](#)
addPackageFile, ANY, character-method
 (addPackageFile), [7](#)
addPackageFile, ANY, missingOrNULL-method
 (addPackageFile), [7](#)
addPackageFile, ANY, Session-method
 (addPackageFile), [7](#)
addRow, [8](#)
addRow, data.frame-method (addRow), [8](#)
autogentags, [8](#)
autogentags, character-method
 (autogentags), [8](#)
autogentags, Scenario-method
 (autogentags), [8](#)
autogentags<-, [9](#)
autogentags<-, character-method
 (autogentags<-), [9](#)
autogentags<-, Scenario-method
 (autogentags<-), [9](#)

backup, [9](#)
backup, character-method (backup), [9](#)
backup, SsimObject-method (backup), [9](#)
basePackage, [10](#)
basePackage, character-method
 (basePackage), [10](#)
basePackage, missingOrNULL-method
 (basePackage), [10](#)
basePackage, Session-method
 (basePackage), [10](#)
basePackage, SsimLibrary-method
 (basePackage), [10](#)
breakpoint, [10](#)
breakpoint, Scenario-method
 (breakpoint), [10](#)

command, [11](#)

datasheet, [12](#)
datasheet, character-method (datasheet),
 [12](#)
datasheet, list-method (datasheet), [12](#)
datasheet, SsimObject-method
 (datasheet), [12](#)
datasheetRaster, [15](#)
datasheetRaster, character-method
 (datasheetRaster), [15](#)
datasheetRaster, list-method
 (datasheetRaster), [15](#)
datasheetRaster, Scenario-method
 (datasheetRaster), [15](#)
datasheetRaster, SsimObject-method
 (datasheetRaster), [15](#)
dateModified, [17](#)
dateModified, character-method
 (dateModified), [17](#)
dateModified, Project-method
 (dateModified), [17](#)
dateModified, Scenario-method
 (dateModified), [17](#)
dateModified, SsimLibrary-method
 (dateModified), [17](#)
delete, [18](#)
delete, character-method (delete), [18](#)
delete, SsimObject-method (delete), [18](#)
deleteBreakpoint, [19](#)
deleteBreakpoint, Scenario-method
 (deleteBreakpoint), [19](#)
deleteModule, [20](#)

- deleteModule, ANY, missingOrNULLOrChar-method
(deleteModule), 20
- deleteModule, ANY, Session-method
(deleteModule), 20
- deletePackage, 20, 20
- deletePackage, ANY, character-method
(deletePackage), 20
- deletePackage, ANY, missingOrNULL-method
(deletePackage), 20
- deletePackage, ANY, Session-method
(deletePackage), 20
- dependency, 21
- dependency, character-method
(dependency), 21
- dependency, Scenario-method
(dependency), 21
- description, 22
- description, character-method
(description), 22
- description, SsimObject-method
(description), 22
- description<-, 22
- description<-, character-method
(description<-), 22
- description<-, SsimObject-method
(description<-), 22
- disableAddon, 23
- disableAddon, character-method
(disableAddon), 23
- disableAddon, SsimLibrary-method
(disableAddon), 23

- enableAddon, 24
- enableAddon, character-method
(enableAddon), 24
- enableAddon, SsimLibrary-method
(enableAddon), 24
- envBeginSimulation (envReportProgress),
25
- envEndSimulation (envReportProgress), 25
- envInputFolder, 24
- envOutputFolder, 25
- envReportProgress, 25
- envStepSimulation (envReportProgress),
25
- envTempFolder, 26

- filepath, 26
- filepath, character-method (filepath), 26
- filepath, Session-method (filepath), 26
- filepath, SsimObject-method (filepath),
26

- ignoreDependencies, 27
- ignoreDependencies, character-method
(ignoreDependencies), 27
- ignoreDependencies, Scenario-method
(ignoreDependencies), 27
- ignoreDependencies<-, 27
- ignoreDependencies<-, character-method
(ignoreDependencies<-), 27
- ignoreDependencies<-, Scenario-method
(ignoreDependencies<-), 27
- info, 28
- info, SsimLibrary-method (info), 28

- mergeDependencies, 28
- mergeDependencies, character-method
(mergeDependencies), 28
- mergeDependencies, Scenario-method
(mergeDependencies), 28
- mergeDependencies<-, 29
- mergeDependencies<-, character-method
(mergeDependencies<-), 29
- mergeDependencies<-, Scenario-method
(mergeDependencies<-), 29
- model, 29
- model, character-method (model), 29
- model, missingOrNULL-method (model), 29
- model, Session-method (model), 29
- model, SsimLibrary-method (model), 29
- module, 30
- module, character-method (module), 30
- module, missingOrNULL-method (module), 30
- module, Session-method (module), 30

- name, 30
- name, character-method (name), 30
- name, Project-method (name), 30
- name, Scenario-method (name), 30
- name, SsimLibrary-method (name), 30
- name<-, 31
- name<-, character-method (name<-), 31
- name<-, Project-method (name<-), 31
- name<-, Scenario-method (name<-), 31
- name<-, SsimLibrary-method (name<-), 31

- owner, 32
- owner, character-method (owner), 32
- owner, Project-method (owner), 32
- owner, Scenario-method (owner), 32
- owner, SsimLibrary-method (owner), 32
- owner<-, 32
- owner<-, character-method (owner<-), 32
- owner<-, SsimObject-method (owner<-), 32

- package, 29, 30, 33

- package, character-method (package), 33
- package, missingOrNULL-method (package), 33
- package, Session-method (package), 33
- parentId, 34
- parentId, character-method (parentId), 34
- parentId, Scenario-method (parentId), 34
- printCmd, 34
- printCmd, missingOrNULLOrChar-method (printCmd), 34
- printCmd, Session-method (printCmd), 34
- Project (Project-class), 36
- project, 35, 36
- Project-class, 36
- projectId, 37
- projectId, character-method (projectId), 37
- projectId, Project-method (projectId), 37
- projectId, Scenario-method (projectId), 37
- readOnly, 37
- readOnly, character-method (readOnly), 37
- readOnly, Project-method (readOnly), 37
- readOnly, Scenario-method (readOnly), 37
- readOnly, SsimLibrary-method (readOnly), 37
- readOnly<-, 38
- readOnly<-, character-method (readOnly<-), 38
- readOnly<-, SsimObject-method (readOnly<-), 38
- rsyncrosim, 38
- run, 39
- run, BreakpointSession-method (run), 39
- run, character-method (run), 39
- run, list-method (run), 39
- run, SsimObject-method (run), 39
- runLog, 40
- runLog, character-method (runLog), 40
- runLog, Scenario-method (runLog), 40
- saveDatasheet, 41
- saveDatasheet, character-method (saveDatasheet), 41
- saveDatasheet, SsimObject-method (saveDatasheet), 41
- Scenario, 44
- Scenario (Scenario-class), 44
- scenario, 43, 44
- Scenario-class, 44
- scenarioId, 45
- scenarioId, character-method (scenarioId), 45
- scenarioId, Scenario-method (scenarioId), 45
- Session, 47
- Session (Session-class), 46
- session, 45, 46
- session, missingOrNULLOrChar-method (session), 45
- session, SsimObject-method (session), 45
- Session-class, 46
- session<-, 46
- session<-, character-method (session<-), 46
- session<-, SsimObject-method (session<-), 46
- silent, 47
- silent, missingOrNULLOrChar-method (silent), 47
- silent, Session-method (silent), 47
- silent<-, 48
- silent<-, character-method (silent<-), 48
- silent<-, Session-method (silent<-), 48
- sqlStatement, 48
- ssimEnvironment, 49
- SsimLibrary, 50, 51
- SsimLibrary (SsimLibrary-class), 51
- ssimLibrary, 50, 51
- ssimLibrary, missingOrNULLOrChar-method (ssimLibrary), 50
- ssimLibrary, SsimObject-method (ssimLibrary), 50
- SsimLibrary-class, 51
- ssimUpdate, 52
- ssimUpdate, character-method (ssimUpdate), 52
- ssimUpdate, SsimObject-method (ssimUpdate), 52
- tempfilepath, 52
- tempfilepath, character-method (tempfilepath), 52
- tempfilepath, Session-method (tempfilepath), 52
- tempfilepath, SsimObject-method (tempfilepath), 52
- updatePackage, 53
- updatePackage, ANY, character-method (updatePackage), 53
- updatePackage, ANY, missingOrNULL-method (updatePackage), 53

updatePackage,ANY,Session-method
 (updatePackage), [53](#)

version, [53](#)

version,character-method (version), [53](#)

version,missingOrNull-method (version),
 [53](#)

version,Session-method (version), [53](#)