

Decision Trees

Learn about decision trees and how they're used.

Chapter Goals:

- Learn about decision trees and how they are constructed
- Learn how decision trees are used for classification and regression


A. Making decisions

Each model we've looked at so far is based on creating an optimal linear combination of dataset features for either regression or classification. However, another popular model in data science for both classification and regression is the decision tree

(https://en.wikipedia.org/wiki/Decision_tree_learning). It is a binary tree (https://en.wikipedia.org/wiki/Binary_tree) where each node of the tree decides on a particular feature of the dataset, and we descend to the node's left or right child depending on the feature's value.

If a feature is boolean, we go left or right from the node depending on if the feature value is true or false. If a feature is numeric, we can decide to go left or right based on a decision boundary for the feature (e.g. go left if the feature value is less than 1, otherwise go right).

The leaves of the decision tree determine the class label to predict (in classification) or the real number value to predict (in regression).




A decision tree for deciding what to eat. This is an example of multiclass classification.

In scikit-learn, we implement classification decision trees with the `DecisionTreeClassifier` ([https://scikit-learn.org/stable/modules/generated/sklearn.tree.DecisionTreeClassifier](https://scikit-learn.org/stable/modules/generated/sklearn.tree.DecisionTreeClassifier.html#sklearn.tree.DecisionTreeClassifier)) object, and regression trees with the `DecisionTreeRegressor` ([https://scikit-learn.org/stable/modules/generated/sklearn.tree.DecisionTreeRegressor](https://scikit-learn.org/stable/modules/generated/sklearn.tree.DecisionTreeRegressor.html#sklearn.tree.DecisionTreeRegressor)) object. Both objects are part of the `tree` module in scikit-learn.

The code below demonstrates how to create decision trees for classification and regression. Each decision tree uses the `fit` function for fitting on data and labels.

```
1 from sklearn import tree
2 clf_tree1 = tree.DecisionTreeClassifier()
3 reg_tree1 = tree.DecisionTreeRegressor()
4 clf_tree2 = tree.DecisionTreeClassifier(
5     max_depth=8) # max depth of 8
6 reg_tree2 = tree.DecisionTreeRegressor(
7     max_depth=5) # max depth of 5
8
9 # predefined dataset
10 print('Data shape: {}'.format(data.shape))
11 # Binary labels
12 print('Labels:\n{}\n'.format(repr(labels)))
13 clf_tree1.fit(data, labels)
```



How we define "best" depends on the decision tree algorithm that's used. Since scikit-learn uses the CART (https://en.wikipedia.org/wiki/Predictive_analytics#Classification_and_regression_trees_28CART.29) algorithm, we use Gini Impurity

(https://en.wikipedia.org/wiki/Decision_tree_learning#Gini_impurity)

MSE (mean squared error), and MAE (mean absolute error) to decide on the best feature at each node.

Specifically, for classification trees we choose the feature at each node that minimizes the remaining dataset observations' Gini Impurity. For regression trees we choose the feature at each node that minimizes the remaining dataset observations' MSE or MAE, depending on which you choose to use (the default for `DecisionTreeRegressor` is MSE).

Time to Code!

The coding exercises in this chapter use the `DecisionTreeRegressor` object of the `tree` module for regression modeling.

You will create a decision tree with max depth equal to 5, then fit the tree on (predefined) data and labels.

Set `d_tree` equal to `tree.DecisionTreeRegressor` initialized with 5 for the `max_depth` keyword argument.

Call `d_tree.fit` on data and labels.

1 # CODE HERE

Solution

```
1 d_tree = tree.DecisionTreeRegressor(max_depth=5)
2 d_tree.fit(data, labels)
3
```

← Back

Next →

Logistic Regression

Training and Testing

☒ Mark as Completed

47% completed, meet the criteria and claim your course certificate!

Buy Certificate



Report an
Issue



Ask a Question

(https://discuss.educative.io/tag/decision-trees__data-modeling-with-scikit-learn__machine-learning-for-software-engineers)