Towed-Sensor Surveillance UAV

AMERICAN UNIVERSITY OF THE MIDDLE EAST

1.0 EXECUTIVE SUMMARY


Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

DESIGN AT A GLANCE



WINGSPAN	M2 GROSS MASS
[span] m	[TOGW M2] kg
SENSOR MASS	M2 PAYLOAD
[m sensor] kg	[units] units
M2 FIVE-LAP TIME	M3 LAPS
[5-lap time] s	[laps] laps
GM DROP HEIGHT	PRED. MISSION SCORE
[h] m	[total] / 7.50

2.0 MANAGEMENT SUMMARY

2.1 Team Organization

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

2.2 Schedule and Milestones

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

TABLE 01 Sub-team responsibilities and the skill sets each requires.

SUB-TEAM	RESPONSIBILITY	REQUIRED SKILLS
Aero & Performance	Sizing, lap and energy model, stability and control	[skills]
Structures & Manufacturing	Airframe design, layup and build, load tests	[skills]
Propulsion & Avionics	Motor, propeller, battery, ESC, radio and fail-safe	[skills]
Sensor Systems	Sensor, D&R reel, shipping container, rigging	[skills]
Flight Operations	Pilot, observer, ground crew, checklists	[skills]
Business & Logistics	Budget, sponsorship, travel, documentation	[skills]




FIG. 01 [takeaway]. Milestones: proposal 31 Oct; Q&A rounds from 1 Nov; PDR; CDR; prototype first flight; sensor bench test; design report 19 Feb; competition aircraft first flight; Pre-Tech/First-Flight certification; fly-off 15–18 Apr.




FIG. 02 [takeaway]: one owner for every scored subsystem.

TABLE 02 Program budget, all costs including travel (USD).

CATEGORY	COST	SHARE
Airframe, prototypes, test rigs	$1,800	[%]
Propulsion, avionics, radio	$1,914	[%]
Batteries, charging sacks, fuses	$1,029	[%]
Sensor electronics and lights	$547	[%]
Containers, simulators, drop rig	$245	[%]
Spares, props, adhesives, consumables	$357	[%]
Crating materials	$150	[%]
Travel and aircraft freight	[$]	[%]
Fly-off fee, AIAA/AMA memberships	[$]	[%]
Contingency ([%])	[$]	[%]
Total	[$]	**100%**

2.3 Budget

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this

TABLE 03 Funding sources and status.

SOURCE	AMOUNT	STATUS
[college allocation]	[$]	[confirmed?]
[sponsor]	[$]	[pending?]
Total	[$]	

section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

3.0 CONCEPTUAL DESIGN APPROACH

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

3.1 Mission Requirements Decomposition

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy

TABLE 04 Mission requirements decomposed into subsystem requirements. Requirement IDs (SR) are cited in later trades and design decisions. [confirm SR list]

MISSION	SCORE	KEY CONSTRAINTS	DERIVED SUBSYSTEM REQUIREMENTS
M1 Staging	$M_1 = 1.0$	3 laps in 5 min; no payload; may be waived and credited by a successful M2	SR-01 stable and controllable empty; SR-02 full assembly and checks in the 5-min staging box
M2 Delivery	$M_2 = 1 + \frac{W/t}{(W/t)_{\max}}$	Sensor in container plus simulators; 5 laps timed; TOP face up; no friction-only retention	SR-03 bay sized for N units; SR-04 positive mechanical restraint; SR-05 CG in limits for every load case
M3 Sensor	$M_3 = 2 + \frac{NW_s}{(NW_s)_{\max}}$	Deploy before first downwind turn; lights OFF, SOLID, FLASHING, OFF; stow before landing	SR-06 internal powered reel, tow $\geq 1.5b$; SR-07 light command over the tow line; SR-08 sensor aerodynamically stable
Ground	$GM = 0.5 + \frac{W_s h}{(W_s h)_{\max}}$	6 drops onto concrete, $h \leq 1.524$ m (60 in); rigging changes within 5 min; zero sensor damage	SR-09 container absorbs $W_s h$; SR-10 quick-swap O/E rigging, flush attachment
System	–	Span ≤ 1.829 m (6 ft); TOGW < 24.95 kg (55 lb); ≤ 100 Wh; no autopilot, GPS or camera; positive hatch latches	SR-11 pilot-in-the-loop only; SR-12 latches without magnets; SR-13 energy for M2 at full payload

sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

3.2 Scoring Model and Sensitivity Study

The total mission score is the sum of four mission scores, each a fixed completion credit plus a term normalized by the best team in the field:[1]

$$S_{\mathrm{M}} = M_1 + \left[1 + \frac{(W/t)}{(W/t)_{\max}}\right] + \left[2 + \frac{NW_s}{(NW_s)_{\max}}\right] + \left[0.5 + \frac{W_s h}{(W_s h)_{\max}}\right] \tag{1}$$

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized

[1] AIAA, *2026–27 Design, Build, Fly Rules*, Draft, Sep. 2026, Sec. 3.3.



FIG. 03 [takeaway]: which parameter moves total mission score most.

to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

3.3 Configuration Trade Studies



FIG. 04 [takeaway]: the chosen design point on the coupled M2/M3/GM trade.




FIG. 05 [confirm W/S and V in airfoil.toml] Selected for the race envelope, not peak efficiency: in the turn, SD7037 gives 1.9× the c_l/c_d of MH 114 (77 against 40), the highest-peak section of the 13 tested. XFoil 6.99, $Re = 5.0 \times 10^5$, $N_{crit} = 9$; it over-predicts $(L/D)_{max}$ by 9–22 % against UIUC tunnel data. Curves end at $c_{l,max}$. Shaded: $c_l = 2n(W/S)/(\rho V^2)$ from cruise to the $n = 2.9$ turn at $\rho = 1.064$ kg/m³, the 1-in-10 hot afternoon at TIMPA.

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

3.4 Preliminary Design and Sizing

3.4.1 Sizing method

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized

TABLE 05 Configuration decisions and the requirement that drove each.

DECISION	OPTIONS CONSIDERED	SELECTED	DRIVER
Wing planform	High-AR, delta	[sel.]	[SR]
Airfoil	13 sections	[sel.]	[SR]
Wing position	Low, mid, high	[sel.]	[SR]
Tail	Conventional, V, H	[sel.]	[SR]
Landing gear	Tricycle, taildragger	[sel.]	[SR]
Retraction	Fixed, retractable	[sel.]	[SR]
Propulsion	Tractor, pusher, twin	[sel.]	[SR]
Sensor bay	Door, open slot	[sel.]	SR-06

TABLE 06 Deployment-and-recovery architecture trade (scores 1–5; selected option inverted).

CRITERION	WT.	OPT. A	OPT. B	OPT. C
Recovery reliability	[w]	–	–	–
Signal path integrity	[w]	–	–	–
Deploy/stow time	[w]	–	–	–
Weight and volume	[w]	–	–	–
Manufacturability	[w]	–	–	–
Weighted total	**1.00**	–	–	–




FIG. 06 [takeaway]: which requirement sets T/W and W/S.

to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. [2]

3.4.2 Aircraft concept

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this

[2] 10th percentile at the daily high of 2,878 hourly KTUS observations, 15–18 April 1996–2025, reduced to TIMPA's 667 m (USGS 3DEP). Iowa Environmental Mesonet, "ASOS Data Download," Iowa State Univ., https://mesonet.agron.iastate.edu [retrieved 11 Oct. 2026].




FIG. 07 [takeaway]: the configuration and where the sensor exits.

TABLE 07 Preliminary design parameters.

PARAMETER	VALUE	UNIT
Wingspan	[span]	m
Wing area	[S]	m²
Aspect ratio	[AR]	–
Empty mass	[m empty]	kg
Gross mass, M2 / M3	[TOGW M2] / [TOGW M3]	kg
Battery energy	[Wh]	Wh
Cruise speed	[V cruise]	m/s
Air density, hot day	1.064	kg/m³
Sensor mass (max)	[m sensor]	kg
Tow-line length	[tow length]	m

TABLE 08 Mission targets and predicted scores.

MISSION	TARGET	SCORE
M1 Staging	[waive or fly]	1.00
M2 Delivery	[units] units, [m payload] kg, [5-lap time] s	[M2]
M3 Sensor	[laps] laps at [m sensor] kg	[M3]
GM Ground	[h] m at [m sensor] kg	[GM]
Total mission score		[total]

section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

3.4.3 Sensor and D&R system

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder




FIG. 08 [takeaway]: the command path to the sensor lights.

copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. The aircraft is flown pilot-in-the-loop at all times: no autopilot or flight controller is carried, and stabilization is limited to optional rate gyros.

3.4.4 Shipping container and rigging

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. All hatches and the container lid use positive mechanical latches; magnets are never the latching method.

3.5 Mission Design Approach and Scoring Targets

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget

for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

4.0 MANUFACTURING PLAN

4.1 Preliminary Manufacturing Flow

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.




FIG. 09 [takeaway]: parallel airframe, sensor and container lanes converge at integration.

TABLE 09 Critical processes, why they matter, and risk mitigation.

PROCESS	WHY CRITICAL	MITIGATION
Reel slip ring	Signal and tow on one line	Bench cycling on a spare receiver
Sensor body	Stability, drop survival	Blower-rig screen (TC-01)
Container liner	Absorbs $W_s h$	Drop series to 1.524 m (TC-02)
Wing spar	Tip-load test at MGTOW	Prototype tip-lift proof test

4.2 Critical Processes and Technologies

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

5.0 TEST PLANNING

Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout. Placeholder copy sized to this section's word budget for layout.

TABLE 10 Component, ground and flight test plan.

TEST	PASS CRITERION	DATE
Ground and component		
Thrust stand	Amps < fuse rating	[date]
Wing-tip lift at MGTOW	No damage (§4.2.4)	[date]
Light visibility in sun	≥ 90 % at 200 m	[date]
Tow-line signal	3 of 3 modes	[date]
D&R cycle	≥ 1.5*b* out, stows	[date]
Drop series to 1.524 m	No damage, 3/3 lit	[date]
GM drill, 5 min	Worst run ≤ 4:00	[date]
Staging drill, 5 min	Worst run ≤ 4:00	[date]
Range, fail-safe, CG	§4.2.5 checks pass	[date]
Flight		
Handling and trim	Level-flight video	[date]
Sensor tow stability	No rotation	[date]
Stepped M2 payload	5 laps < 5 min	[date]
Full M3 sequence	§3.3.3.3 sequence	[date]
Energy per mission	≥ 20 % reserve	[date]