Sensor Light Visibility

AMERICAN UNIVERSITY OF THE MIDDLE EAST

DOC AUM-DBF-27-TC-003
REV C / 12 OCT 2026

1.0 OBJECTIVE

Choose the sensor light type, colour, optic, drive current and flash pattern that ground observers read correctly (OFF, SOLID ON or FLASHING ON) in bright sun at course distances. Measure each candidate's current to size the sensor battery.

Method. A light rig shows randomized modes to observers at 100, 150 and 200 m, who score what they see without conferring. The turn markers are 152.4 m either side of the start line (§3.3.3). A 60° turn at 24 m/s carries the airplane about 35 m past the marker, so 200 m covers the far end of the course plus some lateral offset and altitude.

Limitation. A fixed rig watched by observers who know where to look is easier than a moving sensor. Treat the pass threshold as a minimum.

TEST AT A GLANCE

OBSERVERS	DURATION
≥ 3 people	2–3 h
DISTANCES	CANDIDATES
100–200 m	4–6
TRIALS	WINDOW
10 per stop	11–14 h local

2.0 RULES THAT APPLY

- **Lights** (§3.1.1): three separate lights (forward, centre, aft) along the sensor's long axis. Each may be a single light or an array. They must be visible in flight to the Flight Director in bright Arizona sun; type and colour are the team's choice.
- **Modes** (§3.1.1): OFF; SOLID ON (all lights on); FLASHING ON (all lights on and off together). The team chooses the on and off durations, but the Flight Director must be able to tell the mode from the ground.
- **Command and power** (§3.1.1): commanded from the flight or payload transmitter, with the receiver in the airplane. The control electronics and a battery meeting §3.2.3 are inside the sensor.
- **Mission 3** (§3.3.3.3): lights OFF when deployed, SOLID after lap 1, FLASHING after lap 2, OFF after the final lap.

3.0 TEST ARTICLES AND EQUIPMENT

- **Light rig:** a bar about the sensor's length with forward, centre and aft positions, carrying one candidate at a time. Candidates come from PR-01 A19–A23: high-power stars bare and with 15° and 30° optics, 5 mm arrays, and SMD strip, in white, red and amber.
- **Driver:** a Pico (A24) with constant-current drivers (A22) or MOSFETs. Its presets are OFF, SOLID, and FLASH at 40, 60 and 120 cycles per minute (50 % duty), plus a strobe (0.1 s on, once per second). The operator selects modes with a switch the observers cannot see.
- **Power:** one labelled 1S LiPo per candidate (A25) and the inline current meter (A27).
- **Mount:** a mast, rooftop or balcony edge, so observers see the rig against open sky with the lights facing them, as they will see the sensor from below.
- **Stations:** cones at 100, 150 and 200 m, placed with a tape or measuring wheel. Phone GPS (about ±5 m) is acceptable.
- A die for the operator, the trial grid (page 4) for the operator and each observer at each distance, and phones for calls and photos.

4.0 SAFETY

- High-power LEDs dazzle at close range: never look into them on the bench. Heat-sink the stars.
- Charge and store every LiPo in a charging sack.
- Work on roofs and masts in pairs, away from unguarded edges. Keep observers off roads on long sight lines.

5.0 PROCEDURE

1. **Bench.** For each candidate, measure the current in SOLID and the average current in each FLASH preset at the chosen drive, and log the battery voltage.
2. Mount the rig with the observers at 100 m, the sun behind them if possible. Log the time, sky condition and sun position.
3. For each candidate run 10 trials with FLASH at 60 cycles per minute. Before each trial the operator rolls the die: 1–2 OFF, 3–4 SOLID, 5–6 FLASH. The mode is held for 10 s, then the operator calls “next”. Observers write O, S or F independently, without talking, and the operator logs the true mode.
4. Repeat at 150 and 200 m. If time allows, repeat at 200 m with the sun behind the rig, the worst case.
5. At 200 m, with the best candidate, show the four flash presets in random order. Each observer ranks them by how clearly they read as flashing.
6. Photograph and film the rig from each distance for the proposal.

6.0 DATA REDUCTION

For each candidate and distance, pool all observers’ calls. Record the percentage correct and the confusions (S read as F, F as S, O as S). The reference rate comes from aviation: anti-collision lights flash 40–100 cycles per minute (14 CFR 25.1401(c)), and the presets bracket that range. The sensor battery capacity must satisfy

$$C \geq \frac{I\,t}{\eta}, \tag{1}$$

where I is the chosen light’s mean current, t the longest lights-on time per flight plus a reserve, and η the usable fraction of the rated capacity.

7.0 PASS CRITERIA AND USE OF RESULTS

Pass: at 200 m, at least 90 % correct calls with all observers pooled, and no SOLID read as FLASHING or the reverse.

Use: the winning type, colour, optic and drive current define the sensor lights and close SR-07, “visible in full sun” (Table 04). The chosen flash preset goes into the payload light-control firmware, and the measured current sizes the sensor battery (SR-09, §3.2.3). File the sheet as `testing/data/TC-03_<date>.csv` and the media in `testing/media/TC-03/`.

8.0 DATA SHEET

Date _____ Site _____ Operator _____

Observers _____ Sky and sun position _____

TABLE 01 Bench currents at the chosen drive. FLASH: average current at 60 cycles per minute.

CAND.	LED TYPE	COLOUR	OPTIC	DRIVE, MA	SOLID, MA	FLASH, MA	PACK, V
A							
B							
C							
D							
E							
F							

TABLE 02 Results: percentage of correct calls, all observers pooled, and the confusions seen.

CAND.	100 M, %	150 M, %	200 M, %	200 M, SUN BEHIND	CONFUSIONS AND NOTES
A					
B					
C					
D					
E					
F					

TABLE 03 Flash preset ranking at 200 m (1 = clearest).

PRESET	OBS. 1	OBS. 2	OBS. 3	OBS. 4	MEAN RANK
40 cycles/min, 50 % duty					
60 cycles/min, 50 % duty					
120 cycles/min, 50 % duty					
Strobe, 0.1 s once per second					

9.0 TRIAL GRID

One sheet per person per distance. The operator writes the true mode; observers write what they see: O, S or F.

Name _____ Role: operator / observer Distance (m) _____ Time _____

TABLE 04 Calls by candidate and trial.

CAND.	1	2	3	4	5	6	7	8	9	10
A										
B										
C										
D										
E										
F										