

GuildMark

Design System

Color · Typography · Components · Tokens

v1.0 · May 2026

60+

Design Tokens

2

Theme Modes

25+

Components

3

Tier Palettes

This document is the authoritative reference for the GuildMark visual language. All tokens are defined in theme.css and tokens.ts in the guildmark repository.

1. Color Tokens

All CSS custom properties from theme.css — light and dark mode

1.1 Surface & Layout

Base surfaces used for page backgrounds, cards, and overlays.

Token	Light	Dark
--background Page background	#F8FAFC	#2B2B2B
--foreground Primary text	#0F172A	#F1F5F9
--card Card surface	FFFFFF	#383838
--card-foreground Card text	#0F172A	#F1F5F9
--popover Popover surface	FFFFFF	#383838
--popover-foreground Popover text	#0F172A	#F1F5F9
--border Default border	#CBD5E1	#444444
--input Input border	#CBD5E1	#444444
--input-background Input fill	#F1F5F9	#3F3F3F

1.2 Interactive / Brand

Primary brand blue powers all interactive elements — CTAs, links, focus rings.

Token	Light	Dark
--primary Brand blue — buttons, links	#3B82F6	#3B82F6
--primary-foreground Text on primary	FFFFFF	FFFFFF
--secondary Secondary surface	EFF6FF	#3F3F3F
--secondary-foreground Secondary text	#1D4ED8	#E2E8F0
--muted Muted surface	#F1F5F9	#3F3F3F
--muted-foreground Muted text	#64748B	#94A3B8
--accent Accent hover surface	EFF6FF	#3F3F3F
--accent-foreground Accent hover text	#1E40AF	#E2E8F0
--ring Focus ring	#3B82F6	#3B82F6

1.3 Brand Palette

Extended brand tokens for tinted backgrounds, icon wells, and highlighted areas.

Token	Light	Dark
--brand-primary Primary CTA color	#3B82F6	 #3B82F6 
--brand-primary-foreground Text on primary	#FFFFFF 	#FFFFFF 
--brand-secondary Hover / pressed state	#2563EB	 #2563EB 
--brand-subtle Tinted background	rgba(59,130,246,0.10) 	rgba(59,130,246,0.15) 
--brand-subtle-border Tinted border	rgba(59,130,246,0.20) 	rgba(59,130,246,0.30) 

1.4 Semantic Colors

Status, alert, and feedback colors. Use consistently across toasts, badges, and icons.

Token	Light	Dark
--success Positive outcome	#10B981	 #34D399 
--success-foreground	#FFFFFF 	#FFFFFF 
--warning Caution / attention	#F59E0B	 #FBBF24 
--warning-foreground	#FFFFFF 	#FFFFFF 
--danger Error / destructive	#DC2626	 #EF4444 
--danger-foreground	#FFFFFF 	#FFFFFF 
--info Informational	#3B82F6	 #60A5FA 
--info-foreground	#FFFFFF 	#FFFFFF 
--destructive Destructive action (button variant)	#DC2626	 #EF4444 

2. Condition Grade Palette

Asset condition grades A / B / C — used on listing cards and badges

Grades communicate physical condition at a glance. Each grade has a background fill, a text color for use on white, a subtle tinted surface, and a foreground for use on the filled background.

Token	Light	Dark
--grade-a Grade A fill — Excellent	#3B82F6	#3B82F6
--grade-a-foreground	#FFFFFF	#FFFFFF
--grade-a-subtle Tinted surface	#EFF6FF	rgba(59,130,246,0.15)
--grade-a-text Text on white / dark	#1D4ED8	#93C5FD
--grade-b Grade B fill — Good	#F59E0B	#F59E0B
--grade-b-foreground	#FFFFFF	#FFFFFF
--grade-b-subtle	#FFF8EB	rgba(245,158,11,0.15)
--grade-b-text	#92400E	#FCD34D
--grade-c Grade C fill — Fair	#EF4444	#EF4444
--grade-c-foreground	#FFFFFF	#FFFFFF
--grade-c-subtle	#FEF2F2	rgba(239,68,68,0.15)
--grade-c-text	#991B1B	#FCA5A5

Visual reference

--grade-a	--grade-b	--grade-c	--grade-a-subtle	--grade-b-subtle	--grade-c-subtle
A · Excellent	B · Good	C · Fair	A subtle (light)	B subtle (light)	C subtle (light)

3. AMPS Premium Palette

Purple palette reserved for GM Pro / AMPS tier features


The AMPS (Asset Management & Portfolio Services) tier uses a distinct purple palette to visually distinguish premium features from standard GuildMark functionality. Never use these colors for standard UI elements.

Token	Light	Dark
--amps-accent Primary purple — badges, highlights	#7C3AED	#7C3AED
--amps-accent-foreground	FFFFFF	FFFFFF
--amps-highlight Secondary purple — gradients	#8B5CF6	#8B5CF6
--amps-highlight-foreground	FFFFFF	FFFFFF
--amps-surface Tinted surface	F5F3FF	#323232
--amps-surface-foreground Text on surface	#0F172A	#F1F5F9

Gradient

The canonical AMPS gradient is always left-to-right, accent → highlight:

```
linear-gradient(to right, #7C3AED, #8B5CF6)
```



4. Data Visualization Colors

Chart series, reference lines, and delta indicators

4.1 Chart Series

Used in area, line, and bar charts. Series 1 maps to portfolio/primary data. Access via the `chartColors` export in `tokens.ts`.

series[0]	series[1]	series[2]	series[3]	reference
Portfolio value	#A78BFA	#C4B5FD	#DDD6FE	Book / target

4.2 Delta Indicators

Consistent positive/negative/neutral coloring across sparklines, badges, and trend labels.

Token	Light	Dark
chartColors.positive Value increased / good trend	#10B981	#10B981
chartColors.negative Depreciation / bad trend	#EF4444	#EF4444
chartColors.neutral Forecast / no change	#94A3B8	#94A3B8

4.3 Semantic Chart Tokens (CSS vars)

Token	Light	Dark
--chart-1 Primary series	#3B82F6	#60A5FA
--chart-2 Secondary series	#60A5FA	#3B82F6
--chart-3 Tertiary series	#F59E0B	#FBBF24
--chart-4 Quaternary series	#34D399	#34D399
--chart-5 Quinary series	#F87171	#F87171

5. Typography

Typefaces, scale, and weight system

5.1 Typefaces

Role	Family	Fallback stack	CSS Variable
Body / UI	Inter	-apple-system, BlinkMacSystemFont	--font-sans
Data / Code	JetBrains Mono	Fira Code, Cascadia Code	--font-mono

5.2 Type Scale

Base font size is 16px (--font-size). All scale values use Tailwind's rem-based scale.

Tailwind class	Size (rem)	Size (px)	Usage
text-xs	0.75rem	12px	Labels, badges, captions
text-sm	0.875rem	14px	Secondary body, table cells
text-base	1rem	16px	Primary body text
text-lg	1.125rem	18px	h3 headings
text-xl	1.25rem	20px	h2 headings
text-2xl	1.5rem	24px	h1 headings
text-3xl	1.875rem	30px	Hero / KPI numbers
text-4xl	2.25rem	36px	Dashboard large KPIs

5.3 Font Weights

Token	Value	Usage
--font-weight-normal	400	Body text, input values
--font-weight-medium	500	Headings, labels, buttons

6. Spacing & Shape

Border radius tokens and sidebar layout tokens

6.1 Border Radius

All radii derive from the base `--radius` token (0.625rem / 10px). Use the Tailwind aliases to stay consistent.

CSS Token	Tailwind alias	Computed value	Usage
<code>--radius</code>	—	0.625rem / 10px	Base token (do not use directly)
<code>--radius-sm</code>	<code>rounded-sm</code>	~6px	Small chips, inner elements
<code>--radius-md</code>	<code>rounded-md</code>	~8px	Buttons, inputs, badges
<code>--radius-lg</code>	<code>rounded-lg</code>	10px	Cards, dialogs, panels
<code>--radius-xl</code>	<code>rounded-xl</code>	~14px	Large modals, sheets

6.2 Sidebar Tokens

Token	Light	Dark
<code>--sidebar</code> Sidebar background	#F1F5F9	 #323232
<code>--sidebar-foreground</code> Sidebar text	#0F172A	 #F1F5F9
<code>--sidebar-primary</code> Active item	#3B82F6	 #3B82F6
<code>--sidebar-primary-foreground</code>	#FFFFFF	 #FFFFFF
<code>--sidebar-accent</code> Hover surface	#EFF6FF	 #3F3F3F
<code>--sidebar-accent-foreground</code> Hover text	#1E40AF	 #E2E8F0
<code>--sidebar-border</code> Sidebar border	#CBD5E1	 #444444

7. Component Reference

Button variants, badges, form controls, and custom components

7.1 Button

Defined in components/ui/button.tsx using cva. All buttons use rounded-md (--radius-md) and font-weight-medium by default.

Variant	Background	Text	Hover	Usage
default	primary	white	primary/90	Primary CTA — most prominent action
destructive	destructive	white	destructive/90	Delete, cancel, irreversible actions
outline	background	foreground	accent bg	Secondary actions, toggles
secondary	secondary	secondary-fg	secondary/80	Less prominent secondary actions
ghost	transparent	foreground	accent bg	Icon buttons, nav items
link	transparent	primary	underline	Inline text actions

Button sizes

Size	Height	Padding	Class
sm	32px	px-3	h-8 rounded-md
default	36px	px-4	h-9
lg	40px	px-6	h-10 rounded-md
icon	36×36px	—	size-9 rounded-md

7.2 Custom Components

Component	File	Props	Description
ValueBadge	components/ValueBadge.tsx	value: number, label?	Percentage delta pill — blue if ≥ 0, red if < 0. Uses font-mono.
SpecPill	components/SpecPill.tsx	children: ReactNode	Gray chip for asset specs (RAM, SSD, CPU). Light: slate-100, dark: slate-500.
MarketSignal	components/MarketSignal.tsx	strength: 1–5	5-bar signal strength indicator. Filled bars use --primary; empty bars use --muted.

7.3 shadcn/ui Component Inventory

All shadcn components in components/ui/ inherit the CSS token system. No manual color overrides are needed — swap themes by updating theme.css only.

Accordion	AlertDialog	Alert	AspectRatio
Avatar	Badge	Breadcrumb	Button
Calendar	Carousel	Chart	Checkbox
Collapsible	Command	ContextMenu	Dialog
Drawer	DropdownMenu	Form	HoverCard
InputOtp	Input	Label	Menubar
NavigationMenu	Pagination	Popover	Progress
RadioGroup	Resizable	ScrollArea	Select
Separator	Sheet	Sidebar	Skeleton
Slider	Sonner	Switch	Table
Tabs	Textarea	Toggle	ToggleGroup

Tooltip			
---------	--	--	--

8. Usage Guidelines & Rules

How to correctly apply tokens in code

8.1 Prefer CSS variables over hardcoded values

All colors in JSX/TSX must reference CSS variables via Tailwind utility classes. Only use the JS tokens in tokens.ts when a library cannot consume CSS variables (e.g. Recharts stroke prop, canvas fillStyle, PDF generation).

```
✓ Do className="bg-primary text-primary-foreground"
✗ Don't style={{ backgroundColor: "#3B82F6", color: "#fff" }}
```

8.2 Dark mode

Dark mode is toggled by adding the .dark class to the root element (managed by useTheme.ts). All CSS variables redefine automatically — no conditional className logic is needed for color. Use dark: variants only for opacity or layout differences.

8.3 AMPS gating

Purple AMPS tokens must only appear in UI elements that are gated behind the AMPS subscription tier. Using them on free-tier features confuses the tier signal. The standard tier always uses brand blue (--primary).

8.4 Semantic color intent

Situation	Token to use
Positive % delta, success toast	--success (#10B981 light / #34D399 dark)
Error, delete action, warning toast	--danger / --destructive
Informational tooltip	--info (same as --primary)
Caution, pending state	--warning (#F59E0B)
Asset grade — Excellent	--grade-a + --grade-a-subtle
Asset grade — Good	--grade-b + --grade-b-subtle
Asset grade — Fair	--grade-c + --grade-c-subtle
AMPS-exclusive UI	--amps-accent + --amps-surface

8.5 Source of truth

The canonical token definitions live in two files:

```
guildmark/src/styles/theme.css — CSS custom properties (all UI contexts)
guildmark/src/app/lib/tokens.ts — JS constants (Recharts, canvas, PDF)
```

If a token is updated, both files must be kept in sync. theme.css is the master; tokens.ts mirrors the values that libraries need.