

INFO-F403 Introduction to Language Theory and Compilation

Chapeaux Thomas
Dagnely Pierre

February 19, 2013

Lexical units	regular expressions
INT	(UNARY+ + UNARY-)(0+1+2+3+4+5+6+7+8+9)*
FLOAT	(UNARY+ + UNARY-)(0+1+2+3+4+5+6+7+8+9)*.(0+1+2+3+4+5+6+7+8+9)*
BOOL	(0+1)
STRING (?)	Σ
VARIABLE	INT + FLOAT + BOOL + STRING
OPERATOR	! + * + / + - + +
OPERATOR-COMP	< + > + <= + >= + == + != + && + + not + lt + gt + le + ge + eq + ne
UNARY+	+
UNARY-	-
SEMICOLON	;
COMA	,
AND	&
OPEN-PAR	(
CLOSE-PAR)
OPEN-BRAC	{
CLOSE-BRAC	}
DOLLAR	\$
OPEN-COND	IF
CLOSE-COND	ELSE
ADD-COND	ELSE IF
NEG-COND	UNLESS
RETURN	return
FUNCTION-ID	SUB
EXPRESSION (?)	VARIABLE OPERATOR VARIABLE EXPRESSION OPERATOR VARIABLE
EXPRESSION-COND (?)	VARIABLE OPERATOR-COMP VARIABLE EXPRESSION OPERATOR-COMP VARIABLE
CONDITION (?)	((OPEN-COND+NEG-COND)EXPRESSION-COND OPEN-BRAC INSTRUCTIONS* CLOSE-BRAC (ADD-COND EXPRESSION-COND OPEN-BRAC INSTRUCTIONS* CLOSE-BRAC)* (CLOSE-COND EXPRESSION-COND OPEN-BRAC INSTRUCTIONS* CLOSE-BRAC)) + EXPRESSION (OPEN-COND + NEG-COND) EXPRESSION-COND
INSTRUCTIONS	((CONDITION SEMICOLON)* + (EXPRESSION SEMICOLON)* + (FUNCTION-CALL SEMICOLON))*
FUNCTION-NAME	?restrictions?
PARAM-NAME	?restrictions?
PARAM	DOLLAR PARAM-NAME (COMA DOLLAR PARAM-NAME)*
USER-FUNCT-CALL	AND FUNCTION-NAME (OPEN-PAR CLOSE-PAR + OPEN-PAR PARAM CLOSE-PAR + PARAM) SEMICOLON
PERL-FUNCT-CALL	defined EXPRESSION + int EXPRESSION + length EXPRESSION scalar EXPRESSION + substr EXPRESSION COMA INT COMA INT scalar EXPRESSION + substr EXPRESSION COMA INT + print (?liste de string)
FUNCTION-CALL	USER-FUNCT-CALL + PERL-FUNCT-CALL
FUNCTION	FUNCTION-ID FUNCTION-NAME (OPEN-PAR CLOSE PAR + OPEN-PAR PARAM CLOSE-PAR) OPEN-BRAC INSTRUCTIONS (RETURN EXPRESSION + RETURN EXPRESSION-COND + RETURN VARIABLE) SEMICOLON CLOSE-BRAC
FUNCTION-LIST	FUNCTION*
PROGRAM	(FUNCTION-LIST + INSTRUCTIONS)*

(slide 13)