Laboratory Report

Activity #1

<Write the calculations and solutions performed in Activity #1. Include sources codes and schematic diagrams if required in the e

Laboratory Exercise No.:	2	**Date Performed:**	09/18/2025
Laboratory Exercise Title:	Addressing Modes		
Name of Student(s):	Christian Jay Y. Gallardo, Jhon Fil Tizon	**Document Version:**	1

Activity #1:

Instruction	Register and memory value after the instruction is executed
MOV AL, 25	AX: 0019H, IP: 0102H
MOV AX, 2345	AX: 0929H, IP: 0105H
MOV BX, AX	BX: 0929H, IP: 0107H
MOV CL, AL	CX: 0029H, IP: 0109H
MOV AL, DATA1	AX: 0925H, 010CH
MOV AX, DATA2	AX: 1234H, IP: 010F
MOV DATA3, AL	IP: 0112H
MOV DATA4, AX	IP:0115H
MOV BX, OFFSET DATA5	BX: 0131H, IP: 0118H
MOV AX, [BX]	AX: 2345H, 011AH
MOV DI, 02H	IP: 011D, DI: 0002H
MOV AX, [BX+DI]	AX: 6789H, IP: 011FH
MOV AX, [BX+0002H]	Ax: 6789H, IP:0122H

MOV AL, [DI+2]	AX: 6700H, IP: 0125H
MOV AX, [BX+DI+0002H]	AX: 9090H, 0128H
INT 20H	CS: F400H, IP: 0150H, SP FFF8H

Activity #2

Instruction	Register value after the instruction is executed
MOV BX, OFFSET SRC	BX = OFFSET SRC
MOV DI, 0000H	DI = 0000H
MOV AX, [BX+DI+0002H]	AX = 2222H
MOV BX, OFFSET DST	BX = OFFSET DST
MOV SI, 0000H	SI = 0000H
MOV [BX+SI+0000H], AX	no change
MOV BX, OFFSET SRC	BX = OFFSET SRC
MOV DI, 0002H	DI = 0002H
MOV AX, [BX+DI+0002H]	AX = 3333H
MOV BX, OFFSET DST	BX = OFFSET DST
MOV SI, 0002H	SI = 0002H
MOV [BX+SI+0000H], AX	no change
MOV BX, OFFSET SRC	BX = OFFSET SRC
MOV DI, 0004H	DI = 0004H
MOV AX, [BX+DI+0002H]	AX = 4444H
MOV BX, OFFSET DST	BX = OFFSET DST
MOV SI, 0004H	SI = 0004H
MOV [BX+SI+0000H], AX	no change
MOV BX, OFFSET SRC	BX = OFFSET SRC

MOV DI, 0006H	DI = 0006H
MOV AX, [BX+DI+0002H]	AX = 5555H
MOV BX, OFFSET DST	BX = OFFSET DST
MOV SI, 0006H	SI = 0006H
MOV [BX+SI+0000H], AX	no change
INT 20H	no change

Output Screenshots:




emulator: Exercise2-Activity2.com_
file math debug view external virtual devices virtual drive help
Load reload step back single step run step delay ms: 0
registers
AX 33 33
BX 01 00
CX 00 59
DX 00 00
CS 0700
IP 012C
SS 0700
SP FFFC
BP 0000
SI 0000
DI 0002
DS 0700
ES 0700
0700:012C
0700:012C
ADC [BX + DI], DX
AND AH, [BP + SI]
XOR SI, [BP + DI]
INC SP
INC SP
PUSH BP
PUSH BP
ADD [BX + SI], AL
ADD [BX + SI], AL
ADD [BX + SI], AL
ADD [BX + SI], AL
MOV BX, 0010h
MOV DI, 00000h
MOV AX, [BX + DI] + 02h
MOV BX, 0010h
MOV SI, 00000h
MOV [BX + SI], AX
MOV BX, 0010h
MOV DI, 00002h
MOV AX, [BX + DI] + 02h
MOV BX, 0010h
screen source reset aux vars debug stack flags
original source code
; You may customize this and other start-up templates;
; The location of this template is c:\emu8086\inc\0_com_template.txt
org 100h
SRC DW 1111H,2222H,3333H,4444H,5555H
DST DW 0000H,0000H,0000H,0000H
START:
MOV BX, OFFSET SRC
MOV DI, 0000H
MOV AX, [BX+DI+0002H]
MOV BX, OFFSET DST
MOV SI, 0000H
MOV [BX+SI+0000H], AX
MOV BX, OFFSET SRC
MOV DI, 0002H
MOV AX, [BX+DI+0002H]
MOV BX, OFFSET DST
MOV SI, 0002H
MOV [BX+SI+0000H], AX
MOV BX, OFFSET SRC
MOV DI, 0004H
MOV AX, [BX+DI+0002H]
MOV BX, OFFSET DST
MOV SI, 0004H
MOV [BX+SI+0000H], AX
MOV BX, OFFSET SRC
MOV DI, 0006H
MOV AX, [BX+DI+0002H]
MOV BX, OFFSET DST
MOV SI, 0006H
MOV [BX+SI+0000H], AX
INT 20H
ret