

Filter type	Purpose	3x3	5x5
Mean	In the calculation, mean of the part where the filter is used is calculated.	$\frac{1}{9} \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$	$\frac{1}{25} \begin{bmatrix} 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 \end{bmatrix}$
Gaussian	It is used for noise <b>removal</b> It can be used <b>as a pre-processing for edge detection algorithms.</b>	$\frac{1}{16} \begin{bmatrix} 1 & 2 & 1 \\ 2 & 4 & 2 \\ 1 & 2 & 1 \end{bmatrix}$	$\frac{1}{256} \begin{bmatrix} 1 & 4 & 6 & 4 & 1 \\ 4 & 16 & 24 & 16 & 4 \\ 6 & 24 & 36 & 24 & 6 \\ 4 & 16 & 24 & 16 & 4 \\ 1 & 4 & 6 & 4 & 1 \end{bmatrix}$
Median	Takes the median number of the part where the filter is used on.  It can be used for simple <b>noise removal</b> but makes <b>edges blurry.</b>	-	-
Sobel Filter in X direction	Edge detection in X direction = Gaussian * 1 <sup>st</sup> Derivative in X (The calculation is done in 1D)	$\begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix}$	$\begin{bmatrix} -1 & -2 & 0 & 2 & 1 \\ -4 & -8 & 0 & 8 & 4 \\ -6 & -12 & 0 & 12 & 6 \\ -4 & -8 & 0 & 8 & 4 \\ -1 & -2 & 0 & 2 & 1 \end{bmatrix}$
Sobel Filter in Y direction	Edge detection in Y direction = Gaussian + 1 <sup>st</sup> Derivative in Y (The calculation is done in 1D)	$\begin{bmatrix} -1 & -2 & -1 \\ 0 & 0 & 0 \\ 1 & 2 & 1 \end{bmatrix}$	$\begin{bmatrix} -1 & -4 & -6 & -4 & -1 \\ -2 & -8 & -12 & -8 & -2 \\ 0 & 0 & 0 & 0 & 0 \\ 2 & 8 & 12 & 8 & 2 \\ 1 & 4 & 6 & 4 & 1 \end{bmatrix}$
$\begin{bmatrix} 1 \\ 2 \\ 1 \end{bmatrix} \cdot \begin{bmatrix} -1 & 0 & 1 \end{bmatrix} = \begin{bmatrix} 1 \cdot -1 & 1 \cdot 0 & 1 \cdot 1 \\ 2 \cdot -1 & 2 \cdot 0 & 2 \cdot 1 \\ 1 \cdot -1 & 1 \cdot 0 & 1 \cdot 1 \end{bmatrix} = \begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix}$			
Laplacian	Isotropic (rotation-invariant)  <b>2<sup>nd</sup> Derivative Filter</b>  <b>Detects curvatures</b>	$\begin{bmatrix} 0 & -1 & 0 \\ -1 & 4 & -1 \\ 0 & -1 & 0 \end{bmatrix}$	$\begin{bmatrix} 0 & 0 & -1 & 0 & 0 \\ 0 & -1 & -2 & -1 & 0 \\ -1 & -2 & 16 & -2 & -1 \\ 0 & -1 & -2 & -1 & 0 \\ 0 & 0 & -1 & 0 & 0 \end{bmatrix}$
Prewitt Filter	Similar to Sobel filters but uniform weights in the filter.	$\begin{bmatrix} -1 & 0 & +1 \\ -1 & 0 & +1 \\ -1 & 0 & +1 \end{bmatrix}$ <b>G<sub>x</sub></b>	$\begin{bmatrix} +1 & +1 & +1 \\ 0 & 0 & 0 \\ -1 & -1 & -1 \end{bmatrix}$ <b>G<sub>y</sub></b>

# 1. Forward difference

$$\left. \frac{dI}{dx} \right|_x \approx I[x + 1] - I[x]$$

- Uses current and next point
- Two-point stencil
- Slightly biased toward future (forward)
- Simple but less accurate

Optional scaling if step size is  $h$ :

$$\frac{dI}{dx} \approx \frac{I[x + 1] - I[x]}{h}$$

# 2. Backward difference

$$\left. \frac{dI}{dx} \right|_x \approx I[x] - I[x - 1]$$

- Uses current and previous point
- Two-point stencil
- Slightly biased toward past (backward)

Optional step size  $h$ :

$$\frac{dI}{dx} \approx \frac{I[x] - I[x - 1]}{h}$$

### 3. Central difference

$$\left. \frac{dI}{dx} \right|_x \approx \frac{I[x+1] - I[x-1]}{2}$$

- Uses points on both sides of current point
- **Symmetric**, more accurate
- Basis for **Sobel** and **derivative-of-Gaussian** filters

Optional step size  $h$ :

$$\frac{dI}{dx} \approx \frac{I[x+1] - I[x-1]}{2h}$$

✅ Typically **preferred** because it approximates the derivative at the **center pixel**.

### 4. 2D extension

For an image  $I(x, y)$ :

- Forward difference in x:  $I[x+1, y] - I[x, y]$
- Forward difference in y:  $I[x, y+1] - I[x, y]$

Similarly, central difference:

$$\frac{\partial I}{\partial x} \approx \frac{I[x+1, y] - I[x-1, y]}{2}, \quad \frac{\partial I}{\partial y} \approx \frac{I[x, y+1] - I[x, y-1]}{2}$$

- Central difference in 2D is the **foundation for Sobel filters**.

# Second Derivative Filters

Mathematical meaning

$$\frac{\partial^2 I}{\partial x^2}, \quad \frac{\partial^2 I}{\partial y^2}$$

In 2D:

$$\nabla^2 I = \frac{\partial^2 I}{\partial x^2} + \frac{\partial^2 I}{\partial y^2}$$

Discrete approximation

$$\frac{d^2 I}{dx^2} \approx I(x+1) - 2I(x) + I(x-1)$$


What it detects

- Changes of the change
- Curvature
- Zero-crossings at edges

Images for understanding filters (intuitively)


Mean Filter (Averaging)

$$F(x, y) * H(u, v) = G(x, y)$$




$$* \frac{1}{9} \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$$

"box filter"



## Median Filter




## Sobel Filters


Original Image




Sobel X





Sobel Y




Sobel XY combined using OR







Original




Laplacian




Canny



Sobel X



Sobel Y



Sobel X+Y

- Canny is the **edge detection algorithm** not a filter
- Marr-Hildreth is the **edge detection algorithm** not a filter
- Roberts is a filter (operator)