Manuscript Template for the International Journal of Control, Automation, and Systems: ICROS & KIEE

Gil Dong Hong , Adam Smith , and Ikuro Mizumoto*

Abstract: This article describes the preparation procedure for publication in the International Journal of Control, Automation, and Systems (IJCAS), and this template applies both for initial submission and the final camera-ready manuscript of the paper. When authors submit their work for review, it is necessary to follow these instructions. Abstract should not exceed 300 words for regular papers or 75 words for technical notes and correspondence, and without equations, references, or footnotes.

Keywords: At least four key words or phrases in alphabetical order, separated by commas.

1. INTRODUCTION

This document is a template for Microsoft *Word*. If you are reading a paper version of this document, please download the electronic file, Manuscript template.doc from http://ijcas.com, so you can use it to prepare your manuscript. If you would prefer to use LATEX, please download the IJCAS' LATEX style and sample files from the same Web page. We actually recommend you to use LATEX for fast typesetting and publication schedule because the publication is based on it, but we also accept Microsoft *Word* files for the authors' convenience.

It is *necessary* to adhere these instructions when a manu-script is submitted for review. It is highly recommended to submit the manuscript in *two column format using font size 10 in MS Word. The authors must strictly follow these instructions* in order to maintain the high standard of the journal.

Each paper must be divided into three parts. The first part includes the title, authors' name, abstract and keywords. The second part is the main body of the paper and the third part is the author's profile.

2. PAPER SIZE AND FORMAT

Each paper size should be A4 and the following margins should be set:

Left margin20 mmRight margin20 mmTop margin22 mm

Bottom margin 30 mm Heading 12 mm

Also, using the above margins, the article can be printed on U.S. Letter size papers.

The paper should be within the allowed page length.

- 1) Regular paper: Up to 10 pages
- 2) Technical notes and correspondence: Up to 5 pages

Page length is mesured in two-coloumn format in this template. Over-length paper can be considered, but justification needs to be provided when the initial submission is made. Over-length charge will be applied for publication if accepted.

3. FONTS AND STYLE

3.1. First part

The first part includes the paper title, authors' name, abstract and keywords. All fonts must be in Time New Roman, and the font size of the title, authors' name, abstract, and keywords is bold 14pt, bold 10pt, 10pt, and 10pt, respectively.

3.2. Paper body

The second part consisting of the paper body must be edited in double column format, with each column 80 mm in width and separated by 8 mm. The top-level heading, usually called section and numbered in Roman numerals, shall appear centered on the column with Time New Roman capital bold 10pt. The numbered level-two heading

Manuscript received January 10, 2015; revised March 10, 2015; accepted May 10, 2015. Recommended by Associate Editor Soon-Shin Lee under the direction of Editor Milton John. This journal was supported by the Korean Federation of Science and Technology Societies Grant.

Gil-Dong Hong is with the School of Electrical and Computer Engineering, Best University, 635-4 Yeoksam-dong, Gangnam-gu, Seoul 135-703, Korea (e-mail: journal@ijcas.com). Adam Smith and Ikura Mizumoto are with the School of Mechanical Engineering, World University, 1050 Jackson St., Albany, CA 94000, U.S.A. (e-mails: {smith, newton}@icros.org).

* Corresponding author.



must be shown in Time New Roman 10 pt font. The main text uses Time New Roman 10 pt with single spacing. New paragraphs indent 3.5 mm on the first line.

3.3. Subsection

The numbering of the subsection should take the above form.

4. FIGURE / TABLE / EQUATION

4.1. Figure

Clear original figures should be used. The authors should submit the original graphic files separately along with the main article file (for the camera-ready version after acceptance). The preferred formats for graphics are Tagged Image File (.tif), Encapsulated Postscript (.eps) and JPG (.jpg) format. High-contrast line figures should be prepared with 600 dpi resolution, and color/gray figures should be prepared with more than 300 dpi resolution. The color figures should be clearly seen even though they are printed with black and white printers.




Fig. 1. The caption must be shown after the figure. The caption must be shown after the figure. The caption must be shown after the figure. The caption must be shown after the figure.

4.2. Table

Table 1. The caption must be shown before the table.

	A	В	C
(1)	150 %	16.3 %	18.2 %
(2)	31.1 %	33.8 %	29.8 %
(3)	13.3 % (* sample)	12.1 %	11.1 %

4.3. Equation

The equations should be numbered serially throughout the paper. The equation number should be located to the far right of the line in parenthesis. Equations are shown left aligned on the column.

Theorem 1: Equations are made as follows:

$$\dot{x} = Ax + Bu,\tag{1}$$

$$y = Cx + Du. (2)$$

Proof: Each equation should be separated by a comma. Assuming that the Equation Editor is used, the settings for individual font sizes are

Main equation: 10 pt (Times New Roman),

Subscript/superscript: 7 pt (Times New Roman),

Sub-subscript: 6 pt (Times New Roman),

Symbol: 150%, Sub-symbol: 100%.

The equation number should be set with a right tap as shown in (1) and (2). This is the end of proof.

Remark 1: The journal office knows how to convert all equations into font 10 at once. Please inquire for this before preparing the final manuscript. This will be handy for you.

4.4. Equation/figure/table citation

(1)-(2) stand for the system dynamics. Fig. 1 is the figure. Table 1 is cited as such. In the paper, all authors are required to use the SI unit.

4.5. References

References should appear in a separate bibliography at the end of the paper, with items referred to by numerals in square brackets [1,4-5]. Time New Roman 10 pt is used for references [5]. References should be complete in IJ-CAS style shown in the Reference section of this article. An article should include vol., no., and pages.

4.6. Author information

Brief biographies and either clear glossy photographs (25mm x 30mm) of the authors or TIF files of the figures should be submitted after the paper is accepted.

5. CONCLUSION


The authors should prepare their article for both initial and final submission following the "Information for Authors" available at http://ijcas.com and this file. If accepted, the authors will be required to provide the text of the final version of their manuscript on the website http://ijcas.com.

APPENDIX A

The author(s) can insert an appendix with a meaningful title here.

REFERENCES

- [1] R. C. Baker and B. Charlie, "Nonlinear unstable systems," *International Journal of Control*, vol. 23, no. 4, pp. 123-145, May 1989.
- [2] G.-D. Hong, "Linear controllable systems," *Nature*, vol. 135, no. 5, pp. 18-27, July 1990.
- [3] K. S. Hong and C. S. Kim, "Linear stable systems," *IEEE Trans. on Automatic Control*, vol. 33, no. 3, pp. 1234-1245, December 1993.
- [4] Z. Shiler, S. Filter, and S. Dubowski, "Time optimal paths and acceleration lines of robotic manipulators," *Proc. of the 26th Conf. Decision and Control*, pp. 98-99, 1987.
- [5] M. Young, The Technical Writer's Handbook, Mill Valley, Seoul, 1989.



Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.