```
devasc@labvm:~/labs/devnet-src/git-intro/devasc-study-team$ cd ~/labs/devnet-src/python
devasc@labvm:~/labs/devnet-src/python$ pwd
/home/devasc/labs/devnet-src/python
devasc@labvm:~/labs/devnet-src/python$ /home/devasc/labs/devnet-src/python
bash: /home/devasc/labs/devnet-src/python: Is a directory
devasc@labvm:~/labs/devnet-src/python$ nano myCity.py
devasc@labvm:~/labs/devnet-src/python$
```

```
File  Edit  View  Search  Terminal  Help
  GNU nano 4.8                                                          my
def myCity(city):
    print("I live in " + city + ".")

myCity("Austin")
myCity("Tokyo")
myCity("Salzburg")
```

```
devasc@labvm:~/labs/devnet-src/python$ nano myCity.py
devasc@labvm:~/labs/devnet-src/python$ nano myCity.py
devasc@labvm:~/labs/devnet-src/python$ python3 myCity.py
I live in Austin.
I live in Tokyo.
I live in Salzburg.
devasc@labvm:~/labs/devnet-src/python$
```

part 4

```
devasc@labvm: ~/labs/devnet-src/python
File  Edit  View  Search  Terminal  Help
  GNU nano 4.8                                                  myLocation.py
class Location:
    def __init__(self, name, country):
        self.name = name
        self.country = country

    def myLocation(self):
        print("Hi, my name is " + self.name + " and I live in " + self.country + ".")


# First instantiation of the Location class
loc1 = Location("Tomas", "Portugal")
loc1.myLocation()

# Two more instantiations
loc2 = Location("Ying", "China")
loc3 = Location("Amare", "Kenya")

loc2.myLocation()
loc3.myLocation()

# Your own location
your_loc = Location("Bekmuraz", "Kyrgyzstan")
your_loc.myLocation()
```

```
devasc@labvm:~/labs/devnet-src/python$ nano myLocation.py
devasc@labvm:~/labs/devnet-src/python$ python3 myLocation.py
Hi, my name is Tomas and I live in Portugal.
Hi, my name is Ying and I live in China.
Hi, my name is Amare and I live in Kenya.
Hi, my name is Bekmuraz and I live in Kyrgyzstan.
devasc@labvm:~/labs/devnet-src/python$
```

Part 5. Review the circleClass.py Script

it

```
 GNU nano 4.8                                                    circleClass.py
class Circle:
    def __init__(self, radius):
        self.radius = radius

    def circumference(self):
        pi = 3.14
        circumferenceValue = pi * self.radius * 2
        return circumferenceValue

    def printCircumference(self):
        myCircumference = self.circumference()
        print(
            "Circumference of a circle with a radius of "
            + str(self.radius)
            + " is "
            + str(myCircumference)
        )


# First instantiation
circle1 = Circle(2)
circle1.printCircumference()

# Two more instantiations
circle2 = Circle(5)
circle2.printCircumference()

circle3 = Circle(7)
circle3.printCircumference()
```

```
devasc@labvm:~/labs/devnet-src/python$ nano circleClass.py
devasc@labvm:~/labs/devnet-src/python$ nano circleClass.py
devasc@labvm:~/labs/devnet-src/python$ python3 circleClass.py
Circumference of a circle with a radius of 2 is 12.56
Circumference of a circle with a radius of 5 is 31.400000000000002
Circumference of a circle with a radius of 7 is 43.96
devasc@labvm:~/labs/devnet-src/python$
```