EEGDataset Benchmark Technical Report

Unified EEG Dataset Documentation

Datasets included: 286

Generated at: 2026-03-12 06:22

Preface

This report summarizes 286 EEG datasets in a unified benchmark format. Each dataset section documents paradigm, event structure, HDF5/epoching guidance, and data-quality notes.

The report body is organized into 6 chapters, one per standardized category (priority order is applied during category normalization).

- Complex Applied (56): Real-world simulation, ecological environment, or multi-dimensional task.
- High-level Mental (101): Deep internal cognitive/psychological processing tasks.
- Action/Output (28): Motor intention/execution and BCI-output focused tasks.
- Sensory/Response (52): Basic stimulus-response, ERP/SSVEP/RSVP, or simple attention tasks.
- Biological State (43): Task-free or state-monitoring data (rest/sleep/clinical monitoring).
- Others (6): Does not clearly fit the above categories.

Table of Contents

Entries include page numbers; click an entry to jump to the dataset section.

Preface . . . 2

Table of Contents . . . 3

Chapter 1. Complex Applied . . . 14

001. openneuro_ds001971 - Audiocue walking study . . . 14

002. openneuro_ds002723 - A dataset recorded during development of an affective brain-computer music interface: testing session . . . 17

003. openneuro_ds003039 - Free walking study . . . 19

004. openneuro_ds003517 - EEG: Continuous Gameplay of an 8-Bit Style Video Game . . . 21

005. openneuro_ds003574 - Reward Biases Spontaneous Neural Reactivation During Sleep . . . 24

006. openneuro_ds003620 - Runabout: A Mobile EEG Study of Auditory Oddball Processing in Laboratory and Real-World Conditions . . . 27

007. openneuro_ds003670 - Dataset of Concurrent EEG, ECG, and Behavior with Multiple Doses of Transcranial Electrical Stimulation . . . 30

008. openneuro_ds003702 - Social Memory cuing . . . 32

009. openneuro_ds003739 - Perturbed beam-walking task . . . 34

010. openneuro_ds003801 - Neural Tracking to Go . . . 36

011. openneuro_ds003846 - Prediction Error . . . 38

012. openneuro_ds004105 - BCIT Auditory Cueing . . . 40

013. openneuro_ds004106 - BCIT Advanced Guard Duty . . . 43

014. openneuro_ds004118 - BCIT Calibration Driving . . . 46

015. openneuro_ds004119 - BCIT Basic Guard Duty . . . 48

016. openneuro_ds004120 - BCIT Baseline Driving . . . 50

017. openneuro_ds004121 - BCIT Mind Wandering . . . 52

018. openneuro_ds004122 - BCIT Speed Control . . . 55

019. openneuro_ds004123 - BCIT Traffic Complexity . . . 57

020. openneuro_ds004152 - Drum Trainer . . . 60

021. openneuro_ds004264 - Steer the Ship . . . 62

022. openneuro_ds004460 - EEG and motion capture data set for a full-body/joystick rotation task . . . 64

023. openneuro_ds004475 - Mobile EEG split-belt walking study . . . 66

024. openneuro_ds004477 - PES - Pandemic Emergency Scenario 69
025. openneuro_ds004588 - Neuma (Neuromarketing) 71
026. openneuro_ds004625 - Mind in Motion: Young Adults Walking Over Uneven Terrain 73
027. openneuro_ds004657 - Driving with Autonomous Aids 75
028. openneuro_ds004660 - TNO (Military Cognitive Workload) 78
029. openneuro_ds004661 - ANDI: Auditory N-back Dual-task EEG 81
030. openneuro_ds004718 - Le Petit Prince Hong Kong: Naturalistic fMRI and EEG Dataset 83
031. openneuro_ds004840 - EEG/ECG/EMG During Music Therapy in ICU Burn Patients 86
032. openneuro_ds004841 - TX14 (Semi-Autonomous Vehicle Monitoring) 88
033. openneuro_ds004844 - T22 (Semi-Automated Driving Trust Paradigm) 90
034. openneuro_ds004849 - STRONG (Social-Cognitive EEG Dataset) 92
035. openneuro_ds004850 - ODE (Social-Cognitive EEG Dataset) 95
036. openneuro_ds004851 - HID (High-Density EEG Operational Dataset) 98
037. openneuro_ds004852 - InsurgentCivilian (Social-Cognitive EEG Dataset) 101
038. openneuro_ds004980 - EEG Data for an Architectural Affordances Task 103
039. openneuro_ds005345 - Le Petit Prince Multitalker: Naturalistic 7T fMRI and EEG Dataset 106
040. openneuro_ds005416 - Fatigue Characterization of EEG under Mixed Reality Stereo Vision 109
041. openneuro_ds005505 - Healthy Brain Network (HBN) EEG - Release 1 111
042. openneuro_ds005506 - Healthy Brain Network (HBN) EEG - Release 2 115
043. openneuro_ds005507 - Healthy Brain Network (HBN) EEG - Release 3 119
044. openneuro_ds005508 - Healthy Brain Network (HBN) EEG - Release 4 123
045. openneuro_ds005509 - Healthy Brain Network (HBN) EEG - Release 5 127
046. openneuro_ds005510 - Healthy Brain Network (HBN) EEG - Release 6 131
047. openneuro_ds005511 - Healthy Brain Network (HBN) EEG - Release 7 135
048. openneuro_ds005512 - Healthy Brain Network (HBN) EEG - Release 8 139
049. openneuro_ds005514 - Healthy Brain Network (HBN) EEG - Release 9 143
050. openneuro_ds005515 - Healthy Brain Network (HBN) EEG - Release 10 147
051. openneuro_ds005516 - Healthy Brain Network (HBN) EEG - Release 11 151
052. openneuro_ds005520 - Research data supporting 'EEG recording during playing MOBA game' 155
053. openneuro_ds005841 - EEG Experiment measuring ERPs in VR 158

054. openneuro_ds006554 - Social Observation EEG Raw Data . . . 160
055. openneuro_ds006839 - EEG Recordings during Sham Neurofeedback in Virtual Reality . . . 164
056. openneuro_ds007180 - Exo-EEG Experiment . . . 167
Chapter 2. High-level Mental . . . 171
057. ieee_icassp_competition_2024 - IEEE ICASSP 2024 EEG Competition Dataset . . . 171
058. mendeley_sin - Mendeley Speech-in-Noise (SiN) Auditory Attention Decoding Dataset . . . 174
059. openneuro_ds001784 - Effects of ON/OFF deep brain stimulation on cognitive control in treatment-resistant depression (EEG) . . . 176
060. openneuro_ds001785 - Evidence accumulation relates to perceptual consciousness and monitoring . . . 178
061. openneuro_ds002158 - Disentangling the origins of confidence in speeded perceptual judgments through multimodal imaging . . . 181
062. openneuro_ds002691 - Internal attention study . . . 183
063. openneuro_ds002718 - Face processing EEG dataset for EEGLAB . . . 185
064. openneuro_ds002721 - An EEG dataset recorded during affective music listening . . . 188
065. openneuro_ds002722 - A dataset recorded during development of an affective brain-computer music interface: calibration session . . . 191
066. openneuro_ds002724 - A dataset recorded during development of an affective brain-computer music interface: training sessions . . . 194
067. openneuro_ds002725 - A dataset recording joint EEG-fMRI during affective music listening . . . 197
068. openneuro_ds002791 - DataSet1 - Visual Object Naming EEG . . . 200
069. openneuro_ds002833 - DataSet2 - Visual Object Naming EEG (High-Density) . . . 203
070. openneuro_ds003004 - Imagined Emotion Study . . . 205
071. openneuro_ds003420 - HD-EEGtask (Dataset 1) . . . 207
072. openneuro_ds003421 - HD-EEGtask (Dataset 2) . . . 209
073. openneuro_ds003458 - EEG: Three armed bandit gambling task . . . 211
074. openneuro_ds003506 - EEG: Reinforcement Learning in Parkinson's . . . 214
075. openneuro_ds003509 - EEG: Simon Conflict in Parkinson's . . . 216
076. openneuro_ds003516 - EEG: Attended Speaker Paradigm (Own Name in Ignored Stream) . . . 219
077. openneuro_ds003518 - EEG: Simon Conflict with Reinforcement + Cabergoline Challenge . . . 221
078. openneuro_ds003519 - EEG: Visual Working Memory + Cabergoline Challenge . . . 223
079. openneuro_ds003523 - EEG: Visual Working Memory in Acute TBI . . . 225
080. openneuro_ds003602 - Childhood Sexual Abuse and Problem Drinking in Women: Neurobehavioral Mechanisms . . . 227

081. openneuro_ds003626 - Inner Speech . . . 230

082. openneuro_ds003638 - EEG: Electrophysiological Biomarkers of Behavioral Dimensions from Cross-Species Paradigms . . . 232

083. openneuro_ds003655 - VerbalWorkingMemory . . . 234

084. openneuro_ds003751 - Dataset on Emotion with Naturalistic Stimuli (DENS) . . . 237

085. openneuro_ds003753 - EEG: Probabilistic Learning with Affective Feedback: Exp #2 . . . 240

086. openneuro_ds003766 - A Resource for Assessing Dynamic Binary Choices in the Adult Brain Using EEG and Mouse-Tracking . . . 242

087. openneuro_ds003774 - Music Listening Genre EEG Dataset (MUSIN-G) . . . 245

088. openneuro_ds003822 - EEG: Probabilistic Learning with Affective Feedback: Exp #1 . . . 247

089. openneuro_ds003838 - EEG, pupillometry, ECG and photoplethysmography, and behavioral data in the digit span task . . . 249

090. openneuro_ds003885 - Capacity for movement is an organisational principle in object representations: EEG data from Experiment 1 . . . 251

091. openneuro_ds003887 - Capacity for movement is an organisational principle in object representations: EEG data from Experiment 2 . . . 253

092. openneuro_ds003987 - EEG: Amphetamine trials 5CCPT and Probabilistic Learning . . . 255

093. openneuro_ds004000 - Fribourg Ultimatum Game in Schizophrenia Study . . . 257

094. openneuro_ds004015 - Attended speaker paradigm (cEEGrid data) . . . 260

095. openneuro_ds004017 - Embodied Learning for Literacy EEG . . . 262

096. openneuro_ds004019 - Effect of obesity on arithmetic processing in preteens with high and low math skills. An event-related potentials study . . . 264

097. openneuro_ds004040 - Trance channeling EEG study . . . 266

098. openneuro_ds004067 - Moral conviction and metacognitive ability shape multiple stages of information processing . . . 268

099. openneuro_ds004117 - Sternberg Working Memory . . . 271

100. openneuro_ds004147 - Average Task Value . . . 273

101. openneuro_ds004148 - A test-retest resting and cognitive state EEG dataset . . . 275

102. openneuro_ds004196 - Bimodal dataset on Inner speech . . . 278

103. openneuro_ds004200 - Temporal Scaling . . . 280

104. openneuro_ds004262 - Continuous Feedback Processing . . . 283

105. openneuro_ds004279 - Large Spanish EEG . . . 285

106. openneuro_ds004284 - eeg-neuroforecasting . . . 287

107. openneuro_ds004295 - Reward gain and punishment avoidance reversal learning . . . 289

108. openneuro_ds004315 - Mood Manipulation and PST, Experiment 1 . . . 292

109. openneuro_ds004317 - Mood Manipulation and PST, Experiment 2 . . . 294

110. openneuro_ds004324 - ToonFaces . . . 296

111. openneuro_ds004350 - Executive Functioning Study for Assessing the Effect of Neurofeedback . . . 299

112. openneuro_ds004367 - Meta-rdk: Raw EEG data . . . 302

113. openneuro_ds004369 - Blink-Pause-Relation (Competing Speaker Paradigm) . . . 305

114. openneuro_ds004395 - Penn Electrophysiology of Encoding and Retrieval Study (PEERS) . . . 307

115. openneuro_ds004408 - EEG responses to continuous naturalistic speech . . . 310

116. openneuro_ds004511 - Deception_data . . . 312

117. openneuro_ds004514 - Simultaneous EEG and fNIRS recordings for semantic decoding of imagined animals and tools . . . 314

118. openneuro_ds004515 - EEG: Alcohol imagery reinforcement learning task with light and heavy drinker participants . . . 317

119. openneuro_ds004517 - EEG recordings for semantic decoding of imagined animals and tools during auditory imagery task . . . 319

120. openneuro_ds004532 - EEG: Probabilistic Selection Task (PST) + PST with Cabergoline Challenge . . . 321

121. openneuro_ds004561 - Illusion of Agency over Electrically-Actuated Movements . . . 323

122. openneuro_ds004582 - FakeFaceEmo_data . . . 325

123. openneuro_ds004595 - EEG: RL Task (3-Armed Bandit) with Alcohol Cues in Hazardous Drinkers . . . 327

124. openneuro_ds004626 - Can We Dissociate Hypervigilance to Social Threats from Altered Perceptual Decision-Making in Lonely Individualsx . . . 330

125. openneuro_ds004706 - Spatial Memory and Non-Invasive Closed-Loop Stimulus Timing . . . 333

126. openneuro_ds004752 - Dataset of Intracranial EEG, Scalp EEG and Beamforming Sources from Epilepsy Patients - Verbal Working Memory . . . 336

127. openneuro_ds004796 - PEARL-Neuro Database (Alzheimer's Risk Genes, Lifestyle, Neuroimaging) . . . 338

128. openneuro_ds004802 - Loneliness in the Brain: Distinguishing Between Hypersensitivity and Hyperalertness (Pilot) . . . 340

129. openneuro_ds005114 - EEG: DPX Cognitive Control Task in Acute Mild TBI . . . 343

130. openneuro_ds005262 - ArEEG: Arabic Inner Speech EEG Dataset . . . 345

131. openneuro_ds005305 - EEG Resting-State Microstates and Executive Functions . . . 347

132. openneuro_ds005383 - TMNRED: A Chinese Language EEG Dataset for Fuzzy Semantic Target Identification in Natural Reading Environments . . . 349

133. openneuro_ds005403 - Delayed Auditory Feedback EEG/EGG . . . 352

134. openneuro_ds005815 - YOTO (You Only Think Once): An EEG Dataset for Tracking Spontaneous Cognitive Transitions and Multimodal Stimuli Responses in Resting-State and Task Phases . . . 354

135. openneuro_ds006018 - Cognitive Electrophysiology in Socioeconomic Context in Adulthood: An EEG dataset . . . 358

136. openneuro_ds006040 - Sustained Attention Task (gradCPT) Dataset using simultaneous EEG-fMRI and DTI . . . 362

137. openneuro_ds006104 - EEG dataset for speech decoding . . . 365

138. openneuro_ds006142 - Essex EEG Movie Memory dataset . . . 367

139. openneuro_ds006159 - Implicit Learning EEG (BioSemi) . . . 369

140. openneuro_ds006465 - 3M-CPSEED: EEG Dataset for Chinese Pinyin Production in Overt, Silent-Intended, and Imagined Speech . . . 371

141. openneuro_ds006647 - Poetry EEG Study . . . 374

142. openneuro_ds006648 - Poetry Assessment EEG Dataset 1 . . . 377

143. openneuro_ds006768 - Multiple Object Monitoring EEG . . . 380

144. openneuro_ds006840 - IACKD: Intention Action Conflict EEG-Hand Kinematics Dataset . . . 382

145. openneuro_ds006848 - AlphaDirection1: EEG, ECG, PPG in the resting state and working memory for sequentially and simultaneously presented digits . . . 384

146. openneuro_ds007172 - EEG-Asymmetries Dataset . . . 389

147. other_CockPartDataset - CockPart Multi-Paradigm EEG Dataset . . . 393

148. other_seed - SJTU Emotion EEG Dataset (SEED) . . . 396

149. physionet_auditoryeeg - Auditory EEG Dataset (Biometric Identification) . . . 398

150. physionet_eegmat - EEG During Mental Arithmetic Task . . . 401

151. zenodo_3618205 - Selective Auditory Attention EEG Dataset (Normal-Hearing and Hearing-Impaired) . 404

152. zenodo_4518754 - Ultra High-Density 256-Channel EEG AAD Dataset (Subset) . . . 407

153. zenodo_dtu - DTU Auditory Attention Decoding Dataset . . . 409

154. zenodo_kul - KU Leuven Auditory Attention Decoding Dataset . . . 411

155. zenodo_saa - Spatial Auditory Attention EEG Dataset . . . 413

156. zenodo_sin - Speech-in-Noise (SiN) Auditory Attention Decoding Dataset (Zenodo Mirror) . . . 415

157. zenodo_uhd - Ultra High-Density 256-Channel EEG AAD Dataset . . . 417

Chapter 3. Action/Output . . . 419

158. bcic_iii_1 - BCI Competition III Dataset 1 (Directional Motor Imagery EEG) . . . 419

159. bcic_iii_2 - BCI Competition III Dataset II (P300 Speller) . . . 421

160. bcic_iv_1 - BCI Competition IV Dataset 1 (Motor Imagery, Uncued Classifier Application) . . . 423

161. bcic_iv_2a - BCI Competition IV Dataset 2a (4-Class Motor Imagery) . . . 425

162. bcic_iv_2b - BCI Competition IV Dataset 2b (Left/Right Hand Motor Imagery) . . . 428

163. bcic_iv_4 - BCI Competition IV Dataset 4 (ECoG Finger Movement Decoding) . . . 431

164. figshare_largemi - A Large EEG Motor Imagery Dataset for EEG-BCI . . . 434

165. figshare_meng2019 - EEG Dataset for Cursor BCI (Meng 2019) . . . 438

166. figshare_shudb - SHU Motor Imagery EEG Dataset . . . 441

167. figshare_stroke - EEG Datasets of Stroke Patients (Motor Imagery) . . . 443

168. kaggle_inria - Kaggle BCI Challenge (INRIA) Dataset . . . 446

169. openneuro_ds002034 - Real-time EEG feedback on alpha power lateralization leads to behavioral improvements in a covert attention task . . . 448

170. openneuro_ds002336 - A multi-modal human neuroimaging dataset for data integration: simultaneous EEG and fMRI acquisition during a motor imagery neurofeedback task: XP1 . . . 450

171. openneuro_ds002338 - A multi-modal human neuroimaging dataset for data integration: simultaneous EEG and fMRI acquisition during a motor imagery neurofeedback task: XP2 . . . 453

172. openneuro_ds002720 - A dataset recorded during development of a tempo-based brain-computer music interface . . . 456

173. openneuro_ds003810 - Motor Imagery vs Rest - Low-Cost EEG System . . . 458

174. openneuro_ds004022 - Multimodal EEG and fNIRS Biosignal Acquisition during Motor Imagery Tasks in Patients with Orthopedic Impairment . . . 461

175. openneuro_ds004444 - The BMI-HDEEG dataset 1 . . . 464

176. openneuro_ds004446 - The BMI-HDEEG dataset 2 . . . 466

177. openneuro_ds004447 - The BMI-HDEEG dataset 3 . . . 468

178. openneuro_ds004448 - The BMI-HDEEG dataset 4 . . . 470

179. openneuro_ds004505 - Real World Table Tennis . . . 472

180. openneuro_ds006519 - Dataset of Intracranial EEG during Cortical Stimulations Evoking Negative Motor Responses . . . 474

181. openneuro_ds007327 - EEG During Sport-Related Motor Imagery and Observation Tasks . . . 476

182. other_highgammadataset - High-Gamma EEG Motor Imagery Dataset . . . 478

183. other_openbmi - OpenBMI Motor Imagery EEG Dataset . . . 480

184. physionet_eegmmidb - EEG Motor Movement/Imagery Database . . . 482

185. physionet_erpbci - ERP-Based Brain-Computer Interface Recordings . . . 485

Chapter 4. Sensory/Response . . . 487

186. openneuro_ds001810 - EEG study of the attentional blink; before, during, and after transcranial Direct Current Stimulation (tDCS) . . . 487

187. openneuro_ds002218 - Auditory and Visual Rhythm Omission EEG . . . 490

188. openneuro_ds002578 - Visual Oddball Task (256 channels) . . . 492

189. openneuro_ds002680 - Go-nogo categorization and detection task . . . 494

190. openneuro_ds002814 - A Multimodal Neuroimaging Dataset to Study Spatiotemporal Dynamics of Visual Processing in Humans . . . 496

191. openneuro_ds002893 - Auditory-Visual Shift Study . . . 498

192. openneuro_ds003061 - EEG data from an auditory oddball task . . . 500

193. openneuro_ds003190 - Assessment of the visual stimuli properties in P300 paradigm . . . 502

194. openneuro_ds003490 - EEG: 3-Stim Auditory Oddball and Rest in Parkinson's . . . 505

195. openneuro_ds003522 - EEG: Three-Stimulus Auditory Oddball and Rest in Acute and Chronic TBI . . . 508

196. openneuro_ds003570 - EEG: Improvisation and Musical Structures (Auditory Oddball Chords) . . . 510

197. openneuro_ds003645 - Face Processing MEEG Dataset with HED Annotation . . . 512

198. openneuro_ds003690 - EEG, ECG and Pupil Data from Young and Older Adults: Rest and Auditory Cued Reaction Time Tasks . . . 514

199. openneuro_ds003800 - Auditory Gamma Entrainment . . . 517

200. openneuro_ds003825 - Human electroencephalography recordings from 50 subjects for 22,248 images from 1,854 object concepts . . . 519

201. openneuro_ds004010 - MAVIS . . . 521

202. openneuro_ds004018 - EEG recordings for 200 object images presented in RSVP sequences at 5Hz or 20Hz . . . 523

203. openneuro_ds004024 - TMS-EEG-MRI-fMRI-DWI data on paired associative stimulation and connectivity (Shirley Ryan AbilityLab, Chicago, IL) . . . 525

204. openneuro_ds004043 - The time-course of feature-based attention effects dissociated from temporal expectation and target-related processes . . . 528

205. openneuro_ds004151 - Effect of obesity on inhibitory control in preadolescents during stop-signal task. An event-related potentials study . . . 530

206. openneuro_ds004252 - Rotation-tolerant representations elucidate the time course of high-level object processing . . . 532

207. openneuro_ds004256 - Encoding of Sound Source Elevation in Human Cortex . . . 534

208. openneuro_ds004347 - Symmetry perception and affective responses: a combined EEG/EMG study . . . 537

209. openneuro_ds004356 - Subcortical responses to music and speech are alike while cortical responses diverge . . . 539

210. openneuro_ds004357 - Features-EEG . . . 542

211. openneuro_ds004381 - Intraoperative EEG dataset during medianus-tibialis stimulation with 8 different rates . . . 544

212. openneuro_ds004388 - Somatosensory evoked potentials in the human spinal cord to mixed nerve stimulation . . . 546

213. openneuro_ds004389 - Somatosensory evoked potentials in the human spinal cord to mixed and sensory nerve stimulation . . . 548

214. openneuro_ds004502 - Anticipatory differences between Attention and Expectation . . . 550

215. openneuro_ds004563 - Vicarious touch: overlapping neural patterns between seeing and feeling touch . 553

216. openneuro_ds004574 - Cross-modal Oddball Task . . . 555

217. openneuro_ds004579 - Interval Timing Task . . . 557

218. openneuro_ds004580 - Simon-conflict Task . . . 559

219. openneuro_ds004587 - IllusionGameEEG_data . . . 561

220. openneuro_ds004602 - Registered Replication Report of ERN/Pe Psychometrics . . . 563

221. openneuro_ds004603 - Visual Attribute-Specific Contextual Trajectory Paradigm . . . 565

222. openneuro_ds004745 - 8-Channel SSVEP EEG Dataset with Artifact Trials . . . 567

223. openneuro_ds004816 - EEG Attention RSVP Experiment 1 . . . 569

224. openneuro_ds004817 - EEG-attention-rsvp-exp2 . . . 571

225. openneuro_ds004951 - Braille Letters EEG . . . 573

226. openneuro_ds005087 - Rapid Hemifield Object EEG . . . 576

227. openneuro_ds005106 - Human Infant EEG for 200 Object Images in Rapid Visual Streams . . . 578

228. openneuro_ds005169 - Intracranial EEG During Cortical Stimulation Evoking Visual Effects . . . 580

229. openneuro_ds005363 - Object Recognition in Healthy Aging (ORHA) - EEG . . . 582

230. openneuro_ds005406 - EEG Frequency Tagging Reveals the Integration of Dissimilar Observed Actions . 584

231. openneuro_ds005586 - EEG responses to the number of objects in partially occluded and uncovered scenes . . . 586

232. openneuro_ds005589 - A multi-subject and multi-session EEG dataset for modelling human visual object recognition . . . 589

233. openneuro_ds005662 - A high-quality EEG dataset for studying visual touch perception . . . 592

234. openneuro_ds006171 - EEG during Near-Threshold Visual Detection Tasks (No-Cue, 50%-Cue, 100%-Cue) . . . 594

235. openneuro_ds006547 - Visual EEG Study (BrainVision -> BIDS) . . . 597

236. openneuro_ds006777 - SFARI AVSRT EEG . . . 601

237. physionet_mssvepdb - Multi-Stimulus SSVEP Database . . . 603

Chapter 5. Biological State 605

238. openneuro_ds001787 - EEG meditation study 605

239. openneuro_ds001849 - RS_TMSEEG_Data 607

240. openneuro_ds002778 - UC San Diego Resting State EEG Data from Patients with Parkinson's Disease . . 609

241. openneuro_ds003194 - Neuroepo multisession 611

242. openneuro_ds003195 - Placebo Neuroepo multisession 614

243. openneuro_ds003478 - EEG: Depression rest 617

244. openneuro_ds003555 - Dataset of EEG Recordings of Pediatric Patients with Epilepsy Based on the 10-20 System 619

245. openneuro_ds003710 - APPLESEED Example Dataset 621

246. openneuro_ds003768 - Simultaneous EEG and fMRI Signals During Sleep from Humans 623

247. openneuro_ds003775 - SRM Resting-State EEG 625

248. openneuro_ds003944 - EEG: First Episode Psychosis vs. Control Resting Task 1 627

249. openneuro_ds003947 - EEG: First Episode Psychosis vs. Control Resting Task 2 629

250. openneuro_ds004348 - Ear-EEG Sleep Monitoring 2017 (EESM17) 631

251. openneuro_ds004504 - A dataset of EEG recordings from: Alzheimer's disease, Frontotemporal dementia and Healthy subjects 634

252. openneuro_ds004577 - Dataset containing resting EEG for a sample of 103 normal infants in the first year of life 636

253. openneuro_ds004584 - Rest Eyes Open (Parkinson's Disease) 638

254. openneuro_ds004635 - Gaffrey Lab Infant EEG Microstates Reliability 640

255. openneuro_ds004902 - Resting-State EEG Dataset for Sleep Deprivation 642

256. openneuro_ds005178 - Ear-EEG Sleep Monitoring 2023 (EESM23) 644

257. openneuro_ds005185 - Ear-EEG Sleep Monitoring 2019 (EESM19) 646

258. openneuro_ds005385 - Resting-State EEG Before and After Cognitive Activity Across the Adult Lifespan (5-Year Follow-Up) 649

259. openneuro_ds005420 - Resting State EEG with Closed Eyes and Open Eyes in Females from 60 to 80 Years Old 651

260. openneuro_ds006269 - Tethered EEG Recordings in Syngap1 Rats 653

261. openneuro_ds006525 - Resting EEG with Structural MRI 655

262. openneuro_ds006695 - Validation of Sleep Staging with Forehead EEG Patch 657

263. openneuro_ds006801 - Resting-State EEG Before and After Different Study Methods 659

264. openneuro_ds006921 - High-Density Resting-State EEG of Phantom Limb Pain and Controls 661

265. openneuro_ds007020 - EEG Mortality Dataset in Parkinson's Disease . . . 663
266. openneuro_ds007176 - Longitudinal EEG Test-Retest Reliability in Healthy Individuals . . . 665
267. openneuro_ds007181 - Structural MRI, Resting-State fMRI, and PSG/EEG Dataset of Zoster-Associated Neuralgia . . . 667
268. other_migrainedb - Ultra High-Density EEG - Interictal Migraine and Controls . . . 669
269. physionet_capslpdb - CAP Sleep Database . . . 672
270. physionet_chbmit - CHB-MIT Scalp EEG Database . . . 675
271. physionet_hmcsleepstaging - HMC Sleep Staging Database . . . 677
272. physionet_sleepedfx - Sleep-EDF Database Expanded . . . 680
273. physionet_ucddb - UCD Sleep Apnea Database . . . 683
274. sleepdata_shhs - sleepdata_shhs . . . 686
275. tuh_eeg - TUH EEG Corpus (Base) . . . 690
276. tuh_eeg_abnormal - TUH EEG Abnormal Corpus . . . 692
277. tuh_eeg_epilepsy - TUH EEG Epilepsy Corpus . . . 694
278. tuh_eeg_events - TUH EEG Events Corpus . . . 696
279. tuh_eeg_seizure - TUH EEG Seizure Corpus . . . 699
280. tuh_eeg_slowing - TUH EEG Slowing Corpus . . . 702

Chapter 6. Others . . . 704

281. openneuro_ds004075 - what_are_we_talking_about . . . 704
282. openneuro_ds004784 - Phantom EEG Dataset with Motion, Muscle, and Eye Artifacts . . . 706
283. openneuro_ds004843 - Visual Situational Awareness EEG (T16) . . . 708
284. openneuro_ds005787 - NOD-EEG . . . 711
285. physionet_motionartifact - EEG/fNIRS Motion Artifact Dataset . . . 713
286. tuh_eeg_artifact - TUH EEG Artifact Corpus . . . 715

Chapter 1. Complex Applied

Datasets in this chapter: 56. Real-world simulation, ecological environment, or multi-dimensional task.

001. openneuro_ds001971 - Audiocue walking study

Dataset: `openneuro_ds001971` | Year: 2019 | URL: https://openneuro.org/datasets/ds001971
Category: Complex Applied | Subjects: 18 | Files (Completed): 273 | Channels: 115.0 | Sampling Rate: 512.0 Hz

Paradigm

A mobile brain-body imaging (MoBI) study where participants walked on a treadmill and adapted their gait to auditory tone sequences. Participants walked at their preferred cadence, uncued, or responded to tempo shifts (delay or advance) in an auditory metronome. The study investigated the neural dynamics of gait adaptation and rhythm entrainment during real-world locomotion. Each walking condition is a sustained state lasting multiple seconds.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time
> Web Reference Used for Decision: https://openneuro.org/datasets/ds001971

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`PreferredCadence`	234 (files)	long	raw	Sustained walking at participant's preferred cadence
`UncuedWalking`	234 (files)	long	raw	Sustained uncued walking (no auditory cue)
`DelayTempo`	232 (files)	long	raw	Sustained walking to delayed tempo auditory cue
`AdvanceTempo`	230 (files)	long	raw	Sustained walking to advanced tempo auditory cue
`STATUS`	39	admin	raw	BioSemi system status marker - exclude

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`

- rest: resting-state segment marker, for epoch_by_segmentation_hdf5
- admin: system/boundary marker, exclude from epoch target_events

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Tempo-shift gait adaptation (step-advance vs step-delay)

- Task Type: classification/contrastive decoding
- Epoch Method: epoch_by_event_hdf5 (shift-locked) or epoch_by_long_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification] | tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: AdvanceTempo vs DelayTempo (shift epochs)
- Evidence: Publisher readme/paper emphasizes adaptation to sudden faster/slower cue shifts. Source: https://www.jneurosci.org/content/36/7/2212.short DOI: https://doi.org/10.18112/openneuro.ds001971.v1.1.1

Normal Task 1: Gait Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Walking conditions are sustained states (multiple seconds each) - use long_event epoching. STATUS is a BioSemi admin marker - excluded. Misc channel response_time available for regression.

Event	y	Meaning
PreferredCadence	0	Walking at preferred cadence
UncuedWalking	1	Uncued walking
DelayTempo	2	Walking to delayed tempo cue
AdvanceTempo	3	Walking to advanced tempo cue
## Data Quality Notes		

- MoBI dataset with 115 channels including motion capture; verify EEG-only channel selection.
- STATUS events are BioSemi system markers - do not include in target_events.

- Walking produces motion artifacts; independent component analysis (ICA) for artifact removal is recommended.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Johanna Wagner (June 6, 2019)`

002. openneuro_ds002723 - A dataset recorded during development of an affective brain-computer music interface: testing session

Dataset: `openneuro_ds002723` | Year: 2020 | URL: https://openneuro.org/datasets/ds002723
Category: Complex Applied | Subjects: 8 | Files (Completed): 44 | Channels: 37.0 | Sampling Rate: 1000.0 Hz

Paradigm

Participants interacted with a real-time affective brain-computer music interface (BCMI) that modified music on-the-fly based on detected emotional states, aiming to induce specific target affective trajectories. This is the testing session of the BCI system (see also ds002722 calibration and ds002724 training sessions). Codes 1-9 encode the target or detected affective music conditions.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002723

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
2	44 (files)	long	raw	Affective music condition 2
6	44 (files)	long	raw	Affective music condition 6
9	42 (files)	long	raw	Affective music condition 9
4	42 (files)	long	raw	Affective music condition 4
5	39 (files)	long	raw	Affective music condition 5
7	38 (files)	long	raw	Affective music condition 7
1	29 (files)	long	raw	Affective music condition 1
3	28 (files)	long	raw	Affective music condition 3

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: Publisher-defined BIDS task: Run

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002723 DOI: https://doi.org/10.1088/1741-2560/13/4/046022

Normal Task 1: Affective Music Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to music condition onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 8 affective conditions; decode exact valence/arousal mapping from Daly et al. 2018. Small dataset (8 subjects, 44 files). Music conditions are sustained 40-second states; these onset markers epoch at transition points.

Event	y	Meaning
2	0	Music condition 2
6	1	Music condition 6
9	2	Music condition 9
4	3	Music condition 4
5	4	Music condition 5
7	5	Music condition 7
1	6	Music condition 1
3	7	Music condition 3
## Data Quality Notes		

- Small dataset: 8 subjects, 44 files.
- 37-channel array includes physiological channels; verify EEG-only channel selection.
- Decode code-to-condition mapping from Daly et al. 2018 (Scientific Data).
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Neural and physiological data from participants listening to affective music, Scientific Data, 2018`

003. openneuro_ds003039 - Free walking study

Dataset: openneuro_ds003039 | Year: 2025 | URL: https://openneuro.org/datasets/ds003039
Category: Complex Applied | Subjects: 19 | Files (Completed): 19 | Channels: 67.0 | Sampling Rate: 500.0 Hz

Paradigm

Participants walked two different outdoor routes, once while performing a self-paced button-pressing task, to study brain activity during naturalistic free-walking gait. This is a mobile EEG study; no trial-level event markers are detectable in the EEG files. Button-press events from the self-paced task may be available in separate behavioral logs.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003039

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
(none)	-	-	raw	No event markers detected in EEG files; naturalistic free-walking paradigm

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: Publisher-defined BIDS task: Neur Corr Young

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003039 DOI: https://doi.org/10.18112/openneuro.ds003039.v1.0.2

Normal Task 1: Resting / Continuous Segmentation (resting)

- Task Type: regression

- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (no trial-level events in EEG files))
- Notes: Mobile EEG during naturalistic walking. Motion artifacts are expected; ICA-based artifact removal recommended. Route condition (route A vs route B) may be available as a subject-level metadata label.

Data Quality Notes

- Mobile EEG with significant motion artifacts from walking - ICA and motion artifact rejection required.
- No trial-level event markers in EEG files; button-press events may be in separate logs.
- 67-channel mobile EEG system; verify electrode positions.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Nadine Jacobsen (March, 2020)`

004. openneuro_ds003517 - EEG: Continuous Gameplay of an 8-Bit Style Video Game

Dataset: `openneuro_ds003517` | Year: 2021 | URL: https://openneuro.org/datasets/ds003517
Category: Complex Applied | Subjects: 17 | Files (Completed): 34
Channels: 65 | Sampling Rate: 500 Hz

Paradigm

Participants played a continuous 8-bit style video game while EEG was recorded to study canonical neural events during naturalistic gameplay. The experiment also included a visual oddball task and a gambling task embedded within the session. Game events (shooting, collecting stars, collisions) and oddball stimuli (standard and rare tones/targets) were time-locked to EEG recordings. The study aims to identify ERP components (P300, error-related negativity) in a real-world, engaging task context.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003517

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`ODDBALL STANDARD`	17	short	raw	Standard tone in oddball task (frequent)
`ODDBALL RARE`	17	short	raw	Rare/target tone in oddball task (infrequent)
`ODDBALL START`	17	short	raw	Oddball task block start marker
`ODDBALL DONE`	17	short	raw	Oddball task block end marker
`SHOOT_BUTTON`	18	short	raw	Player shoot button press
`COLLECT_STAR`	18	short	raw	Player collected a star (reward)
`PLAYER_CRASH_ENEMY`	18	short	raw	Player crashed into enemy
`MISSILE_HIT_ENEMY`	17	short	raw	Missile hit enemy (success)
`PLAYER_CRASH_WALL`	17	short	raw	Player crashed into wall

Event ID	Count (total)	Type	Meta Level	Meaning
COLLECT_AMMO	17	short	raw	Player collected ammunition
GAMBLING WIN	14	short	raw	Gambling task win outcome
GAMBLING LOSS	14	short	raw	Gambling task loss outcome
GAME START	16	short	raw	Game session start
GAME OVER	16	short	raw	Game session end
STATUS	34	admin	raw	System status marker

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `STATUS`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://doi.org/10.1016/j.neuroimage.2016.02.075

Normal Task 1: Gambling result classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only 14 files contain gambling events; small sample size.

Event	y	Meaning
GAMBLING WIN	1	Win
GAMBLING LOSS	0	Lose
## Data Quality Notes		

- 65-channel EEG recorded during naturalistic, continuous task; higher artifact rate expected from movement and engagement.
- Some sessions may be game-only (no oddball/gambling); verify event presence per file.

References

- Reference: `Identification of canonical neural events during continuous gameplay of an 8-bit style video game. NeuroImage, 2016. DOI: 10.1016/j.neuroimage.2016.02.075`

005. openneuro_ds003574 - Reward Biases Spontaneous Neural Reactivation During Sleep

Dataset: `openneuro_ds003574` | Year: 2021 | URL: https://openneuro.org/datasets/ds003574
Category: Complex Applied | Subjects: 18 | Files (Completed): 17
Channels: 69 | Sampling Rate: 500 Hz

Paradigm

Participants played two rewarded and non-rewarded video games (FACE and MAZE) followed by a nap sleep session recorded with simultaneous EEG-fMRI. The study examines whether reward enhances spontaneous neural reactivation of game-related memory traces during sleep. Brain patterns from waking gameplay are decoded and compared to sleep activity to identify replay events. EEG event structure consists of BrainVision numeric S-code triggers from the game paradigm with limited per-file occurrence.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003574

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`S 1-S 27`	1 each	short	raw	BrainVision stimulus triggers (game/task events)
`R128`	1	short	raw	BrainVision response trigger
`Sync On`	1	short	raw	MRI/EEG synchronization marker
`R`	1	admin	raw	Generic response marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `S 1`, `S 27`

- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Rest

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003574 DOI: https://doi.org/10.18112/openneuro.ds003574.v1.0.2

Primary Task 2: Publisher-defined BIDS task: Game

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003574 DOI: https://doi.org/10.18112/openneuro.ds003574.v1.0.2

Primary Task 3: Publisher-defined BIDS task: Face Maze game

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003574 DOI: https://doi.org/10.18112/openneuro.ds003574.v1.0.2

Normal Task 1: Continuous sleep EEG segmentation

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (no label, suitable for unsupervised analysis))
- Notes: Only 1 occurrence per event type per file - insufficient for epoch-based classification. Dataset is primarily suited for EEG-fMRI sleep replay analysis using pattern decoding, not standard ERP epoching. The 17 completed files (of 18 subjects) are sleep EEG recordings.

Data Quality Notes

- Very sparse event structure; each trigger type appears only once per recording.
- EEG-fMRI simultaneous recording; gradient artifact and MRI-related noise present.
- Primary analysis requires decoding waking neural patterns and cross-correlating with sleep activity.

References

- Reference: Reward biases spontaneous neural reactivation during sleep. Nature Communications, 2021.

006. openneuro_ds003620 - Runabout: A Mobile EEG Study of Auditory Oddball Processing in Laboratory and Real-World Conditions

Dataset: `openneuro_ds003620` | Year: 2021 | URL: https://openneuro.org/datasets/ds003620
Category: Complex Applied | Subjects: 44 | Files (Completed): 271
Channels: 35 | Sampling Rate: 250 Hz

Paradigm

Participants performed an auditory oddball task under three levels of environmental complexity and physical activity: sitting in a laboratory, walking on a sports field (oval), and navigating a university campus. The paradigm examined how cognitive and motor demands of real-world locomotion affect P300 oddball responses. Target tones required mental counting ("count" condition) or were simply listened to ("don't count" condition), with both counted and uncounted targets interleaved across environments.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003620

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`t_count_lab`	134	short	raw	Target tone, count condition, laboratory
`t_count_oval`	134	short	raw	Target tone, count condition, oval
`t_count_campus`	134	short	raw	Target tone, count condition, campus
`ntcount_lab`	134	short	raw	Non-target (standard) tone, count condition, laboratory
`ntcount_oval`	134	short	raw	Non-target tone, count condition, oval
`ntcount_campus`	134	short	raw	Non-target tone, count condition, campus
`t_Count_lab`	80	short	raw	Target tone, Count (capital) condition, laboratory
`t_Count_oval`	80	short	raw	Target tone, Count condition, oval

Event ID	Count (total)	Type	Meta Level	Meaning
t_Count_campus	80	short	raw	Target tone, Count condition, campus
ntCount_lab	80	short	raw	Non-target tone, Count condition, laboratory
ntCount_oval	80	short	raw	Non-target tone, Count condition, oval
ntCount_campus	80	short	raw	Non-target tone, Count condition, campus
t_Dontcount_lab	208	short	raw	Target tone, don't-count condition, laboratory
t_Dontcount_oval	214	short	raw	Target tone, don't-count condition, oval
t_Dontcount_campus	214	short	raw	Target tone, don't-count condition, campus
ntDontcount_lab	208	short	raw	Non-target tone, don't-count condition, laboratory
ntDontcount_oval	214	short	raw	Non-target tone, don't-count condition, oval
ntDontcount_campus	214	short	raw	Non-target tone, don't-count condition, campus
empty	226	admin	raw	Empty/padding event marker

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://openneuro.org/datasets/ds003620 DOI: https://doi.org/10.1101/2021.05.27.445993

Normal Task 1: Target/non-target classification (binary, cross-environment)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Event names encode environment (lab/oval/campus) and condition (count/Count/Dontcount). The `Stimulus/` prefixed variants in some files are duplicates. Pool by target (t_) vs non-target (nt_) for a tractable binary task. Mobile EEG; motion artifacts expected during walking conditions.

Event	y	Meaning
`t_count_lab`, `t_count_oval`, `t_count_campus`, `t_Count_lab`, `t_Count_oval`, `t_Count_campus`, `t_Dontcount_lab`, `t_Dontcount_oval`, `t_Dontcount_campus`	1	Target tone (all target variants)
`ntcount_lab`, `ntcount_oval`, `ntcount_campus`, `ntCount_lab`, `ntCount_oval`, `ntCount_campus`, `ntDontcount_lab`, `ntDontcount_oval`, `ntDontcount_campus`	0	Non-target tone (all standard variants)
## Data Quality Notes		

- Mobile EEG recording; significant motion artifacts during outdoor walking conditions (oval, campus).
- Lowercase vs uppercase variants (count/Count) may reflect different recording sessions or systems.
- `empty` event is an admin placeholder; exclude from epoching.
- `Stimulus/`-prefixed variants appear in a subset of files and are redundant with non-prefixed versions.

References

- Reference: `Runabout: A mobile EEG study of auditory oddball processing in laboratory and real-world conditions. OpenNeuro ds003620.`

007. openneuro_ds003670 - Dataset of Concurrent EEG, ECG, and Behavior with Multiple Doses of Transcranial Electrical Stimulation

Dataset: `openneuro_ds003670` | Year: 2021 | URL: https://openneuro.org/datasets/ds003670
Category: Complex Applied | Subjects: 19 | Files (Completed): 62
Channels: 35 | Sampling Rate: 2000 Hz

Paradigm

Participants performed a continuous tracking task (CTT) requiring them to maintain a ball at the center of a screen to assess vigilance and sustained alertness. Simultaneously, multi-site transcranial electrical stimulation (tES) was applied at varying dose combinations (sham, low, high) to modulate arousal and attention. EEG, ECG, and behavioral tracking data were recorded concurrently. The study aims to identify optimal tES parameters for enhancing cognitive performance.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003670

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulation Start`	62	long	raw	Transcranial stimulation onset (sustained state)
`Stimulation Stop`	62	long	raw	Transcranial stimulation offset
`Block Start`	62	long	raw	Task block onset marker
`STATUS`	62	admin	raw	System status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulation Start`, `Stimulation Stop`, `STATUS`

- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: GXt ESCTT

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003670 DOI: https://doi.org/10.18112/openneuro.ds003670.v1.1.0

Normal Task 1: Stimulation period analysis (long event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Stimulation periods are sustained states (several minutes each); use long-event epoching. Dose condition (sham/low/high) should be in events.tsv or participants.tsv. Very high sampling rate (2000 Hz) increases memory requirements.

Event	y	Meaning
`Stimulation Start`	1	Transcranial electrical stimulation activation period
`Block Start`	0	Task block (baseline/control)
## Data Quality Notes		

- Very high sampling rate (2000 Hz); downsample to 250-500 Hz for standard EEG analyses.
- tES artifacts present during stimulation periods; independent component analysis required.
- ECG channels included; can be used for cardiac artifact removal.

References

- Reference: `Dataset of concurrent EEG, ECG, and behavior with multiple doses of transcranial Electrical Stimulation. OpenNeuro ds003670.`

008. openneuro_ds003702 - Social Memory cuing

Dataset: `openneuro_ds003702` | Year: 2024 | URL: https://openneuro.org/datasets/ds003702
Category: Complex Applied | Subjects: N/A | Files (Completed): 47
Channels: 64.0 | Sampling Rate: 500.0 Hz

Paradigm

A visual working memory task performed in a virtual reality environment where participants recalled object locations and statuses following social (avatar) or non-social (stick) directional cues.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003702

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`no_events`	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.
## MISC Label Summary				

- Route: `misc`
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

Tasks

Primary Task 1: Publisher-defined BIDS task: Social Memory cuing

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003702 DOI: https://doi.org/10.18112/openneuro.ds003702.v1.0.2

Normal Task 1: Raw-meta task

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Needs verification
- Kernel Notes: Exclude admin markers from target labels.

Normal Task 2: Super-meta task

- Task Type: regression/classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target / Label: Needs verification
- Kernel Notes: Derive and version super-meta in kernel.

Data Quality Notes

- Verify channel count consistency across subjects before pooling.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to epoching.

References

- No paper reference available

009. openneuro_ds003739 - Perturbed beam-walking task

Dataset: `openneuro_ds003739` | Year: 2021 | URL: https://openneuro.org/datasets/ds003739
Category: Complex Applied | Subjects: N/A | Files (Completed): 120
Channels: 149.0 | Sampling Rate: 256.0 Hz

Paradigm

Participants performed walking on a treadmill-mounted balance beam while being subjected to sensorimotor perturbations via virtual reality visual rotations and physical waist pulls.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003739

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`no_events`	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.
## MISC Label Summary				

- Route: `misc`
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

Tasks

Primary Task 1: Publisher-defined BIDS task: Mixed

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003739 DOI: https://doi.org/10.1038/74899

Normal Task 1: Raw-meta task

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Needs verification
- Kernel Notes: Exclude admin markers from target labels.

Normal Task 2: Super-meta task

- Task Type: regression/classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target / Label: Needs verification
- Kernel Notes: Derive and version super-meta in kernel.

Data Quality Notes

- Verify channel count consistency across subjects before pooling.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to epoching.

References

- Reference: `eNeuro publication`

010. openneuro_ds003801 - Neural Tracking to Go

Dataset: `openneuro_ds003801` | Year: 2021 | URL: https://openneuro.org/datasets/ds003801
Category: Complex Applied | Subjects: 20 | Files (Completed): 20
Channels: 24 | Sampling Rate: 250 Hz

Paradigm

A mobile EEG study where participants performed a dichotic listening task (two competing speakers) while either sitting in a quiet indoor environment or walking along a pre-defined indoor route with environmental distractions. The study investigates how locomotion and environmental complexity affect neural tracking of attended speech (measured by auditory EEG envelope tracking). No discrete trial-level event markers were embedded in the EEG recording.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003801

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
-	-	-	raw	No event markers detected; continuous EEG during dichotic listening and walking

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Neural Tracking To Go

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003801 DOI: https://doi.org/10.18112/openneuro.ds003801.v1.0.0

Normal Task 1: Continuous EEG segmentation

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (conditional label sit/walk needs to be obtained from file-level metadata))
- Notes: Mobile EEG; motion artifacts expected during walking condition. 20 subjects, 20 files (1 per subject). Condition (sitting/walking) is file-level metadata. Neural tracking of speech envelope requires cross-correlation with audio stimulus waveform.

Data Quality Notes

- Mobile EEG recording; significant motion artifacts during walking condition.
- No trial-level event markers; condition label is file-level or block-level.
- Small dataset (20 subjects, 20 files); limited statistical power.
- 24-channel EEG at 250 Hz; modest spatial and temporal resolution.

References

- Reference: `Neural Tracking to Go. OpenNeuro ds003801.`

011. openneuro_ds003846 - Prediction Error

Dataset: `openneuro_ds003846` | Year: 2025 | URL: https://openneuro.org/datasets/ds003846
Category: Complex Applied | Subjects: 19 | Files (Completed): 50
Channels: 64 | Sampling Rate: 500 Hz

Paradigm

A virtual reality haptic interaction study where participants reached out to touch spawned virtual boxes while receiving varied combinations of visual, vibrotactile, and electrical muscle stimulation (EMS) feedback. Trials were marked as "normal" (congruent feedback) or "conflict" (incongruent prediction error condition), allowing investigation of multisensory prediction error processing. Three feedback modality conditions were run in separate sessions: visual-only, vibrotactile-only, and combined EMS conditions.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: reaction time, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003846

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`box`	559 files	short	raw	Box spawned or box touched event
`vibroFeedback`	198 files	short	raw	Vibrotactile feedback onset
`block`	79 files	short	raw	Block start marker
`visualFeedback`	50 files	short	raw	Visual feedback onset

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `reaction_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://openneuro.org/datasets/ds003846 DOI: https://doi.org/10.18112/openneuro.ds003846.v2.0.2

Normal Task 1: Normal vs Conflict Prediction Error (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Events are richly annotated with metadata (reaction time, trial number, ISI, cube identity). The normal/conflict label is embedded in the event string. Epoch on box:touched events and extract the normal_or_conflict field for the label. Reaction time is also available as a regression target.

Event	y	Meaning
`box:touched;...normal_or_conflict:normal`	0	Normal (congruent) trial - box touched, expected feedback
`box:touched;...normal_or_conflict:conflict`	1	Conflict (prediction error) trial - incongruent feedback
## Data Quality Notes		

- Events contain full JSON-like annotation strings; label extraction requires parsing the event description
- Multiple sessions per subject (EMS, Vibro, Visual) with differing session lengths
- Sampling rate is ~500 Hz (exact value varies slightly across files)

References

- Reference: `Cyber-Physical Systems: Prediction Error`

012. openneuro_ds004105 - BCIT Auditory Cueing

Dataset: `openneuro_ds004105` | Year: 2022 | URL: https://openneuro.org/datasets/ds004105
Category: Complex Applied | Subjects: 34 | Files (Completed): 34
Channels: 74 | Sampling Rate: 1024 Hz

Paradigm

Participants performed a long-duration simulated driving task involving lane maintenance with periodic lateral vehicle perturbations, while receiving auditory cues at varying intervals. EEG biomarkers of fatigue were investigated as performance and alertness declined over the driving session. The study is part of the BCIT (Brain Computer Interface and Technology) driving fatigue dataset series.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004105

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`4210`	34 files	short	raw	Driving event code 4210 (lateral perturbation onset)
`4220`	34 files	short	raw	Driving event code 4220
`4230`	34 files	short	raw	Driving event code 4230
`4311`	34 files	short	raw	Lane deviation/correction event
`4312`	34 files	short	raw	Lane deviation/correction event
`3200`	34 files	short	raw	Speed/control event
`3111`	34 files	short	raw	Perturbation/response event
`3112`	34 files	short	raw	Perturbation/response event
`3310`	34 files	short	raw	Performance metric event
`1211`	34 files	short	raw	Auditory cue event
`1212`	34 files	short	raw	Auditory cue event

Event ID	Count (total)	Type	Meta Level	Meaning
2621	34 files	short	raw	Behavioral response event
2622	34 files	short	raw	Behavioral response event
1111-1322	17 files	short	raw	Condition-specific events (half of subjects)
4411	1 file	short	raw	Rare event

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004105 DOI: https://doi.org/10.1016/j.neuroimage.2017.02.057

Normal Task 1: Lateral Perturbation Response (binary)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Full BCIT event code decoding requires the dataset codebook. Part of the BCIT driving fatigue series alongside ds004106, ds004118, ds004119, ds004120, ds004121, ds004122, ds004123. Auditory cueing conditions are the primary manipulation.

Event	y	Meaning
4311	0	Lane perturbation - direction/type 1
4312	1	Lane perturbation - direction/type 2
## Data Quality Notes		

- Numerical event codes require codebook from BCIT documentation for full decoding
- 74-channel BioSemi ActiveTwo; high-density cap with 1024 Hz sampling
- Part of a larger BCIT driving series - consider combining with related datasets

References

- No paper reference available

013. openneuro_ds004106 - BCIT Advanced Guard Duty

Dataset: `openneuro_ds004106` | Year: 2022 | URL: https://openneuro.org/datasets/ds004106
Category: Complex Applied | Subjects: 29 | Files (Completed): 29
Channels: 262 | Sampling Rate: 1024 Hz

Paradigm

Subjects performed a sustained vigilance task simulating advanced security guard duties by verifying multiple fields on replica ID cards against reference images, under varying workloads and stochastic arrival rates of cards. EEG was recorded to identify biomarkers of mental fatigue and vigilance decrement over extended duty periods. Part of the BCIT sustained attention / guard duty dataset series.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004106

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`1311`	29 files	short	raw	Card/stimulus arrival event - type 1311
`1312`	29 files	short	raw	Card/stimulus arrival event - type 1312
`1321`	29 files	short	raw	Verification response event
`1322`	29 files	short	raw	Verification response event
`1331-1362`	27-29 files	short	raw	Guard duty task events (various verification stages)
`1341-1342`	29 files	short	raw	Guard duty task events
`1351-1352`	27-29 files	short	raw	Guard duty task events
`1221-1222`	29 files	short	raw	Guard duty task events
`1211-1212`	28 files	short	raw	Guard duty task events
`1231-1232`	28 files	short	raw	Guard duty task events
`1241-1242`	27 files	short	raw	Guard duty task events

Event ID	Count (total)	Type	Meta Level	Meaning
1251-1252	27 files	short	raw	Guard duty task events
1121-1122	27 files	short	raw	Guard duty task events
2110	29 files	short	raw	Workload condition marker - high
2120	29 files	short	raw	Workload condition marker - low
3111-3112	26 files	short	raw	Block/session markers
3231-3232	2 files	short	raw	Rare condition events

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004106 DOI: https://doi.org/10.1016/j.biopsycho.2015.12.009

Normal Task 1: High vs Low Workload (binary)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: 262-channel BioSemi cap - very high-density EEG. Full BCIT event codebook required for precise decoding. Part of the BCIT guard duty series (see also ds004119 Basic Guard Duty).

Event	y	Meaning
2110	0	High workload condition marker
2120	1	Low workload condition marker
## Data Quality Notes		

- 262 channels - largest EEG cap in the BCIT series; high memory requirements
- Full event decoding requires BCIT codebook documentation
- Very limited subjects (29) for the large channel count

References

- Reference: `BCIT Advanced Guard Duty`

014. openneuro_ds004118 - BCIT Calibration Driving

Dataset: `openneuro_ds004118` | Year: 2022 | URL: https://openneuro.org/datasets/ds004118
Category: Complex Applied | Subjects: 247 | Files (Completed): 247
Channels: 266 | Sampling Rate: 1024 Hz

Paradigm

Subjects performed a 15-minute simulated driving calibration task on a straight road, maintaining lane position while correcting for periodic lateral perturbations. This calibration recording is designed to collect a baseline driving EEG profile for each subject to normalize fatigue prediction algorithms used in the broader BCIT driving fatigue study series. It is the largest file count in the BCIT series.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004118

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`3200`	247 files	short	raw	Speed/driving state marker
`3111`	247 files	short	raw	Perturbation onset
`3112`	247 files	short	raw	Perturbation offset/response
`3310`	247 files	short	raw	Performance metric event
`1211`	247 files	short	raw	Lane correction event
`1212`	247 files	short	raw	Lane correction event
`4311`	246 files	short	raw	Lateral perturbation type 1
`4312`	246 files	short	raw	Lateral perturbation type 2
`4230`	246 files	short	raw	Perturbation/direction event
`4210`	239 files	short	raw	Perturbation onset event
`4220`	206 files	short	raw	Perturbation event
`1121`	246 files	short	raw	Driver response event
`1122`	246 files	short	raw	Driver response event
`1111`	246 files	short	raw	Driver response event

Event ID	Count (total)	Type	Meta Level	Meaning
1112	246 files	short	raw	Driver response event
2621	97 files	short	raw	Auditory cue onset
2622	97 files	short	raw	Auditory cue offset
4200-4612	2 files	short	raw	Rare condition events

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004118 DOI: https://doi.org/10.3389/fnins.2014.00155

Normal Task 1: Lateral Perturbation Direction (binary)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Largest file count in the BCIT series (247 subjects). 266-channel BioSemi cap - very high memory requirements. Calibration session is shorter (15 min) than fatigue driving sessions.

Event	y	Meaning
4311	0	Lateral perturbation - direction/type 1
4312	1	Lateral perturbation - direction/type 2
## Data Quality Notes		

- 266 channels - very high-density EEG; significant memory requirements for batch processing
- 247 files (subjects) - large cohort; suitable for cross-subject decoding
- Full event code decoding requires BCIT codebook

References

- No paper reference available

015. openneuro_ds004119 - BCIT Basic Guard Duty

Dataset: `openneuro_ds004119` | Year: 2022 | URL: https://openneuro.org/datasets/ds004119
Category: Complex Applied | Subjects: 22 | Files (Completed): 22
Channels: 262 | Sampling Rate: 1024 Hz

Paradigm

A realistic sustained vigilance task in which subjects verified multiple identification card fields against reference images in a simulated security environment under varying card arrival rates. This basic guard duty variant uses a simpler verification protocol compared to the Advanced Guard Duty (ds004106), and is designed to study EEG correlates of sustained attention and vigilance decrement over extended duty periods.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004119

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`1311`	22 files	short	raw	Card arrival / verification stimulus onset
`1312`	22 files	short	raw	Card arrival event
`1321-1322`	22 files	short	raw	Verification response events
`1331-1332`	22 files	short	raw	Guard duty task events
`1341-1342`	22 files	short	raw	Guard duty task events
`1351-1352`	22 files	short	raw	Guard duty task events
`1361-1362`	22 files	short	raw	Guard duty task events
`1231-1232`	22 files	short	raw	Guard duty task events
`2110`	22 files	short	raw	High workload condition marker
`2120`	22 files	short	raw	Low workload condition marker
`3111-3112`	20 files	short	raw	Block/session markers

Event ID	Count (total)	Type	Meta Level	Meaning
1111-1112	21 files	short	raw	Guard duty task events
3241-3242	6 files	short	raw	Rare condition events
3231-3232	1 file	short	raw	Very rare condition events

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004119 DOI: https://doi.org/10.1016/j.biopsycho.2015.12.009

Normal Task 1: High vs Low Workload (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Small cohort (22 subjects). 262-channel BioSemi cap. Paired with ds004106 (Advanced Guard Duty)
- can be combined for larger guard duty cohort.

Event	y	Meaning
2110	0	High workload condition
2120	1	Low workload condition
## Data Quality Notes		

- 262 channels - very high-density EEG; high memory requirements
- Only 22 subjects - small sample size
- Full event code decoding requires BCIT codebook documentation

References

- Reference: `Gross, Matthews, Cohn, Kanade, & Baker, 2010`

016. openneuro_ds004120 - BCIT Baseline Driving

Dataset: `openneuro_ds004120` | Year: 2022 | URL: https://openneuro.org/datasets/ds004120
Category: Complex Applied | Subjects: 131 | Files (Completed): 131
Channels: 266 | Sampling Rate: 1024 Hz

Paradigm

Subjects performed a 60-minute simulated driving task involving manual steering and speed control, requiring corrective responses to lateral vehicle perturbations to study fatigue-related EEG biomarkers over an extended session. This baseline driving condition serves as the primary long-duration fatigue paradigm in the BCIT series, without auditory cueing or traffic complexity manipulation.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004120

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`4311`	131 files	short	raw	Lateral perturbation - type 1
`4312`	131 files	short	raw	Lateral perturbation - type 2
`4210`	130 files	short	raw	Perturbation onset
`4220`	123 files	short	raw	Perturbation event
`4230`	131 files	short	raw	Perturbation/direction event
`3200`	131 files	short	raw	Speed/driving state marker
`3111`	128 files	short	raw	Perturbation onset
`3112`	125 files	short	raw	Perturbation response
`3310`	131 files	short	raw	Performance metric event
`1211`	131 files	short	raw	Lane correction event
`1212`	130 files	short	raw	Lane correction event
`1121-1122`	131 files	short	raw	Driver response events
`1111-1112`	131 files	short	raw	Driver response events

Event ID	Count (total)	Type	Meta Level	Meaning
2621-2622	28 files	short	raw	Auditory cue events (subset)
2611-2612	28 files	short	raw	Auditory cue events (subset)
5241-5242	10 files	short	raw	Rare condition events
4421-5232	2-5 files	short	raw	Very rare events

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004120 DOI: https://doi.org/10.3389/fnins.2014.00155

Normal Task 1: Lateral Perturbation Direction (binary)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: 131 subjects with 60-minute sessions - large fatigue dataset. 266-channel BioSemi cap. Primary baseline driving condition for BCIT fatigue series comparison.

Event	y	Meaning
4311	0	Lateral perturbation - direction/type 1
4312	1	Lateral perturbation - direction/type 2
## Data Quality Notes		

- 266 channels - very high-density EEG; significant memory requirements
- 60-minute sessions provide extensive fatigue-related data per subject
- Full event code decoding requires BCIT codebook

References

- No paper reference available

017. openneuro_ds004121 - BCIT Mind Wandering

Dataset: `openneuro_ds004121` | Year: 2022 | URL: https://openneuro.org/datasets/ds004121
Category: Complex Applied | Subjects: 60 | Files (Completed): 60
Channels: 74 | Sampling Rate: 1024 Hz

Paradigm

Subjects performed a long-duration simulated driving task involving lane maintenance, speed control, and a police vehicle vigilance sub-task (detecting a police car among traffic), while exposed to lateral perturbations and varying background audio conditions (silence vs. music vs. podcast). The mind wandering manipulation used periodic thought probes to assess on-task vs. off-task mental state. EEG biomarkers of mind wandering during driving were investigated.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004121

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`4311`	60 files	short	raw	Lateral perturbation type 1
`4312`	59 files	short	raw	Lateral perturbation type 2
`4210`	59 files	short	raw	Perturbation onset
`4220`	59 files	short	raw	Perturbation event
`4230`	59 files	short	raw	Perturbation/direction event
`4730`	59 files	short	raw	Special driving event
`4411`	60 files	short	raw	Police vehicle event
`4621-4622`	60 files	short	raw	Audio condition events
`3200`	60 files	short	raw	Speed marker
`3111`	60 files	short	raw	Perturbation onset
`3310`	60 files	short	raw	Performance metric
`1211`	60 files	short	raw	Lane correction event
`1212`	58 files	short	raw	Lane correction event
`1121-1122`	60 files	short	raw	Driver response
`1111-1112`	60 files	short	raw	Driver response

Event ID	Count (total)	Type	Meta Level	Meaning
2221-2222	59 files	short	raw	Thought probe / mind wandering event
2241-2242	59 files	short	raw	Thought probe response
2251-2252	59 files	short	raw	Thought probe response
2621-2622	60 files	short	raw	Behavioral response
2811-2812	59 files	short	raw	Audio cue events
2631-2632	58 files	short	raw	Behavioral response events

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004121 DOI: https://doi.org/10.18112/openneuro.ds004121.v1.0.0

Normal Task 1: Lateral Perturbation Direction (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Mind wandering thought probe events (2221/2241/2251) can be used to label on-task vs. off-task periods for attention state classification. Full event codebook required for precise decoding of all 30+ event types.

Event	y	Meaning
4311	0	Lateral perturbation - type 1
4312	1	Lateral perturbation - type 2
## Data Quality Notes		

- 30+ distinct event types; full decoding requires BCIT codebook
- Thought probe events provide mind-wandering labels for attention classification

- Audio condition (silence/music/podcast) provides additional between-condition variable

References

- No paper reference available

018. openneuro_ds004122 - BCIT Speed Control

Dataset: `openneuro_ds004122` | Year: 2022 | URL: https://openneuro.org/datasets/ds004122
Category: Complex Applied | Subjects: 63 | Files (Completed): 63
Channels: 74 | Sampling Rate: 1024 Hz

Paradigm

A simulated driving task assessing driver fatigue and performance through a speed control manipulation: subjects drove under either manual speed control (maintaining speed without cruise control) or automated speed control (cruise control active), while also performing manual steering corrections for lateral vehicle perturbations. The study investigates how automation of one driving sub-task affects neural fatigue signatures.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004122

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`4210`	63 files	short	raw	Perturbation onset
`4220`	63 files	short	raw	Perturbation event
`4230`	63 files	short	raw	Perturbation/direction event
`4311`	63 files	short	raw	Lateral perturbation type 1
`4312`	63 files	short	raw	Lateral perturbation type 2
`3200`	63 files	short	raw	Speed control state marker
`3111`	63 files	short	raw	Perturbation onset
`3310`	63 files	short	raw	Performance metric event
`1211`	63 files	short	raw	Lane correction event
`1212`	59 files	short	raw	Lane correction event
`1121-1122`	63 files	short	raw	Driver response events
`1111-1112`	63 files	short	raw	Driver response events

Event ID	Count (total)	Type	Meta Level	Meaning
2621-2622	61 files	short	raw	Behavioral response / auditory cue
3112	59 files	short	raw	Perturbation response
4411	5 files	short	raw	Rare event
4421	6 files	short	raw	Rare event

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004122 DOI: https://doi.org/10.18112/openneuro.ds004122.v1.0.0

Normal Task 1: Lateral Perturbation Direction (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Speed control condition (manual vs. automated) can serve as a between-subjects or within-session variable. Part of the BCIT driving fatigue series.

Event	y	Meaning
4311	0	Lateral perturbation - type 1
4312	1	Lateral perturbation - type 2
## Data Quality Notes		

- 74-channel BioSemi ActiveTwo; 1024 Hz sampling
- Speed control condition variable requires session metadata from participants.tsv
- Full event code decoding requires BCIT codebook

References

- No paper reference available

019. openneuro_ds004123 - BCIT Traffic Complexity

Dataset: `openneuro_ds004123` | Year: 2022 | URL: https://openneuro.org/datasets/ds004123
Category: Complex Applied | Subjects: 30 | Files (Completed): 30
Channels: 74 | Sampling Rate: 1024 Hz

Paradigm

Subjects performed a simulated driving task with varying levels of visual traffic complexity (low, medium, high density of surrounding vehicles) while correcting for lateral vehicle perturbations. EEG was recorded to assess how increasing traffic complexity interacts with fatigue-related neural signatures. Part of the BCIT driving fatigue dataset series examining environmental complexity effects on driver workload.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004123

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`4311`	30 files	short	raw	Lateral perturbation type 1
`4312`	30 files	short	raw	Lateral perturbation type 2
`4210`	30 files	short	raw	Perturbation onset
`4220`	30 files	short	raw	Perturbation event
`4230`	30 files	short	raw	Perturbation/direction event
`4411`	30 files	short	raw	Special event
`3200`	30 files	short	raw	Speed marker
`3111`	30 files	short	raw	Perturbation onset
`3310`	30 files	short	raw	Performance metric
`3210`	30 files	short	raw	Traffic complexity marker - low
`3230`	30 files	short	raw	Traffic complexity marker - medium
`3240`	30 files	short	raw	Traffic complexity marker - high
`1211`	30 files	short	raw	Lane correction event
`1212`	30 files	short	raw	Lane correction event

Event ID	Count (total)	Type	Meta Level	Meaning
1121-1122	30 files	short	raw	Driver response events
1111-1112	30 files	short	raw	Driver response events
2221-2222	30 files	short	raw	Behavioral response events
2241-2242	30 files	short	raw	Behavioral response events
2251-2252	30 files	short	raw	Behavioral response events
2621-2622	30 files	short	raw	Auditory/behavioral events
2711-2712	30 files	short	raw	Traffic event markers
2811-2812	30 files	short	raw	Traffic event markers

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004123 DOI: https://doi.org/10.18112/openneuro.ds004123.v1.0.0

Normal Task 1: Traffic Complexity Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Traffic complexity conditions (3210/3230/3240) are the primary manipulation variable. Only 30 subjects - small cohort. Full event code decoding requires BCIT codebook.

Event	y	Meaning
3210	0	Low traffic complexity
3230	1	Medium traffic complexity
3240	2	High traffic complexity

Event	y	Meaning
## Data Quality Notes		

- 30 subjects - smallest subject count in the BCIT driving series
- 30 distinct event types; full decoding requires BCIT codebook documentation
- Traffic complexity codes (3210/3230/3240) are the key classification targets

References

- Reference: `BCIT Traffic Complexity`

020. openneuro_ds004152 - Drum Trainer

Dataset: `openneuro_ds004152` | Year: 2022 | URL: https://openneuro.org/datasets/ds004152
Category: Complex Applied | Subjects: 21 | Files (Completed): 21 | Channels: 31 | Sampling Rate: 1000 Hz

Paradigm

Participants learned and performed specific rhythmic drumming patterns at varying tempos using keyboard keys, receiving adaptive visual feedback on timing accuracy. EEG was recorded continuously during drumming training. Each key press generates a Stimulus event marker; the dataset contains thousands of drumming events per participant (2300-4700 Stimulus events per file).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004152

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus`	~65000	short	raw	Individual drum key press / beat onset
`New Segment`	21	admin	raw	Recording segment boundary
`Comment`	21	admin	raw	Experimenter comment marker

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Drumtrainer

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)

- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004152 DOI: https://doi.org/10.18112/openneuro.ds004152.v1.1.2

Normal Task 1: Drum Beat Detection (single-class)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only one event class. Useful for stimulus-locked ERP analysis. New Segment and Comment are admin events, excluded.

Event	y	Meaning
`Stimulus`	0	Drum key press / beat onset
## Data Quality Notes		

- Very high event rate; check for event jitter in timing accuracy analysis
- Only 21 subjects; limited generalizability

References

- Reference: `Drum Trainer EEG dataset`

021. openneuro_ds004264 - Steer the Ship

Dataset: openneuro_ds004264 | Year: 2022 | URL: https://openneuro.org/datasets/ds004264
Category: Complex Applied | Subjects: 21 | Files (Completed): 21
Channels: 31 | Sampling Rate: 1000 Hz

Paradigm

A ship-steering simulation where participants control a rotating arrow to maintain orientation against varying environmental and controller noise using unstable pole-and-cart physics. The task involves continuous manual control with varying noise levels, making it a real-world closed-loop BCI paradigm. EEG was recorded to study cognitive load and motor control under dynamic uncertainty.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004264

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus`	21x1000+	short	raw	Stimulus/condition onset marker
`New Segment`	21	admin	raw	Recording segment boundary
`Comment`	21	admin	raw	Experimenter comment/annotation

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Steertheship

- Task Type: classification/segmentation

- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004264 DOI: https://doi.org/10.18112/openneuro.ds004264.v1.1.0

Normal Task 1: Stimulus Processing (single-class)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only one event class available for epoching. New Segment and Comment are admin markers. Behavioral metadata (noise level, performance metrics) may be available in events.tsv for regression tasks.

Event	y	Meaning
`Stimulus`	0	Stimulus/condition onset
## Data Quality Notes		

- Only one non-admin event type (Stimulus); classification requires additional label parsing from events.tsv metadata columns
- New Segment and Comment are system/admin events excluded from epoching
- Variable trial counts across subjects (1473-2373 per subject)

References

- Reference: `Steer the Ship`

022. openneuro_ds004460 - EEG and motion capture data set for a full-body/joystick rotation task

Dataset: `openneuro_ds004460` | Year: 2024 | URL: https://openneuro.org/datasets/ds004460
Category: Complex Applied | Subjects: 20 | Files (Completed): 40
Channels: 160 | Sampling Rate: 1000 Hz

Paradigm

Participants performed a spatial orientation task in a virtual environment, navigating via either active physical rotation of the body or joystick-controlled rotation on a flat screen. EEG and motion capture were simultaneously recorded to compare neural dynamics of active (full-body) vs. passive (joystick) spatial navigation and heading changes.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004460

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`ground_rotate`	40	short	raw	Ground/environment rotation onset
`object_fadeInOut`	40	short	raw	Object appearance/disappearance
`'/Event/Label/targ_color_change'`	53	short	raw	Target color change event
`('/Event/Category/Participant response'`	40	short	raw	Participant response event
`'/Event/Label/wii_button'`	40	short	raw	Wii/button press response
`('/Event/Category/Experimental stimulus/Instruction/Attend/'`	80	short	raw	Attend instruction stimulus
`('/Event/Category/Experimental stimulus/Instruction/Read/'`	40	short	raw	Read instruction stimulus
`duration`	40	admin	raw	Duration annotation

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`

- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: ('/Event/Category/Experimental stimulus/Instruction/Attend/', ('/Event/Category/Experimental stimulus/Instruction/Read/'
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Rotation

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004460 DOI: https://doi.org/10.1038/nrn2733

Normal Task 1: Navigation Mode Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: HED (Hierarchical Event Descriptor) tags are used as event labels - very verbose names. 160 channels includes motion capture channels. 40 files from 20 subjects (2 conditions: body vs. joystick rotation).

Event	y	Meaning
ground_rotate	0	Spatial rotation stimulus
object_fadeInOut	1	Object appearance/disappearance
'/Event/Label/targ_color_change'	2	Target color change
## Data Quality Notes		

- HED-format event labels are very long strings - ensure proper parsing
- 160 channels includes motion capture data channels in addition to EEG
- 40 files from 20 subjects (2 runs each: body rotation and joystick rotation)

References

- Reference: Human cortical dynamics during full-body heading changes. Scientific Reports, 11(1), 18186

023. openneuro_ds004475 - Mobile EEG split-belt walking study

Dataset: `openneuro_ds004475` | Year: 2023 | URL: https://openneuro.org/datasets/ds004475
Category: Complex Applied | Subjects: 30 | Files (Completed): 30
Channels: 260 | Sampling Rate: 512 Hz

Paradigm

A mobile brain-body imaging experiment investigating brain activity during gait adaptation using abrupt and gradual split-belt treadmill walking. Participants walked on a split-belt treadmill with different belt speeds while EEG and gait events (heel strikes, toe-offs) were recorded to study locomotor adaptation and associated cortical dynamics.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004475

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`LHS`	30xx	short	raw	Left heel strike (gait event)
`LTO`	30xx	short	raw	Left toe-off (gait event)
`RHS`	30xx	short	raw	Right heel strike (gait event)
`RTO`	30xx	short	raw	Right toe-off (gait event)
`TRIG`	30xx	short	raw	External trigger marker
`BUTTON`	30xx	short	raw	Button press event
`SB1`	30	long	raw	Split-belt block 1 start (tied speed)
`SB2`	30	long	raw	Split-belt block 2 start (split speed)
`B1`	30	long	raw	Baseline block 1
`B2`	30	long	raw	Baseline block 2
`B3`	30	long	raw	Baseline block 3
`P1`	30	long	raw	Perturbation block 1
`P2`	30	long	raw	Perturbation block 2

Event ID	Count (total)	Type	Meta Level	Meaning
End SB1	30	admin	raw	End of split-belt block 1
End SB2	30	admin	raw	End of split-belt block 2
End B1	30	admin	raw	End of baseline block 1
End B2	30	admin	raw	End of baseline block 2
End B3	30	admin	raw	End of baseline block 3
End P1	30	admin	raw	End of perturbation block 1
End P2	30	admin	raw	End of perturbation block 2
boundary	8	admin	raw	Segment boundary marker
9633791	30	admin	raw	Numerical system trigger

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Task

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004475 DOI: https://doi.org/10.18112/openneuro.ds004475.v1.0.3

Normal Task 1: Gait Event Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: boundary and 9633791 are admin/system markers - exclude from target_events. Block markers (SB1/SB2/B1-3/P1-2) are experimental condition markers. End_* markers are admin events.

Event	y	Meaning
LHS	0	Left heel strike
LTO	1	Left toe-off
RHS	2	Right heel strike
RTO	3	Right toe-off
## Data Quality Notes		

- boundary and 9633791 must be excluded as admin markers
- 260 channels includes motion capture channels; filter to EEG only
- Gait event counts vary across walking conditions (tied vs. split-belt speeds)

References

- Reference: Mobile EEG split-belt walking study

024. openneuro_ds004477 - PES - Pandemic Emergency Scenario

Dataset: `openneuro_ds004477` | Year: 2023 | URL: https://openneuro.org/datasets/ds004477
Category: Complex Applied | Subjects: 9 | Files (Completed): 9
Channels: 80 | Sampling Rate: 2048 Hz

Paradigm

A strategic pandemic simulation task where participants allocate limited resources to cities on a map and report their decision confidence while interacting with an artificial agent. EEG was recorded to investigate neural correlates of complex decision-making, confidence estimation, and strategy formation in a realistic multi-agent scenario.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: confidence, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004477

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stimulus`	9xx	short	raw	Decision stimulus onset
`resp_hold`	9xx	short	raw	Response hold (button press start)
`resp_release`	9xx	short	raw	Response release (button press end)
`confidence`	9xx	short	raw	Confidence rating onset

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `confidence`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stimulus`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: PES

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004477 DOI: https://doi.org/10.3389/fnhum.2019.00013

Normal Task 1: Decision Making (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only 9 subjects; limited generalization. Small dataset suitable for within-subject analysis. Confidence ratings may be used as regression target.

Event	y	Meaning
`resp_hold`	0	Response initiation
`resp_release`	1	Response release
`stimulus`	2	Decision stimulus
`confidence`	3	Confidence rating
## Data Quality Notes		

- Only 9 subjects; very small dataset
- 80 channels at 2048 Hz (high temporal resolution)
- Complex task with strategic decisions; behavioral data critical for labeling

References

- Reference: `PES - Pandemic Emergency Scenario`

025. openneuro_ds004588 - Neuma (Neuromarketing)

Dataset: `openneuro_ds004588` | Year: 2023 | URL: https://openneuro.org/datasets/ds004588
Category: Complex Applied | Subjects: 42 | Files (Completed): 84 | Channels: 6 | Sampling Rate: 300 Hz

Paradigm

A multimodal neuromarketing study where 42 participants browsed supermarket product brochures displayed on screen and selected items they intended to purchase by clicking the left mouse button. EEG was recorded alongside mouse interaction data to identify neural correlates of consumer purchase decisions during free-browsing. Each session involved scrolling through product leaflet images presented in a sequential format.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004588

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`MouseButtonLeft pressed`	1734	short	raw	Left mouse button press (product selection / page interaction)
`MouseButtonLeft released`	1712	short	raw	Left mouse button release
`Category:IMG=ID:FYLLADIO_1.tif=...`	268	short	raw	Product leaflet image 1 onset
`Category:IMG=ID:FYLLADIO_2.tif=...`	138	short	raw	Product leaflet image 2 onset
`MouseWheelDown120 pressed`	210	admin	raw	Scroll-down wheel event (exclude)
`MouseWheelUp120 pressed`	76	admin	raw	Scroll-up wheel event (exclude)
`fixation_cross`	84	short	raw	Fixation cross onset (trial start)
`EOE`	84	short	raw	End-of-experiment marker

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Unnamed

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004588 DOI: https://doi.org/10.18112/openneuro.ds004588.v1.2.0

Normal Task 1: Purchase Interaction Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only 6 EEG channels. Category event labels embed full image filenames - aggregate by category type if needed. Scroll wheel events are admin.

Event	y	Meaning
`fixation_cross`	0	Trial-start fixation
`MouseButtonLeft pressed`	1	Product purchase/page click
## Data Quality Notes		

- Very limited spatial resolution: only 6 EEG channels.
- Category event labels contain full image paths; group by category type for analysis.

References

- Reference: `Neuma`

026. openneuro_ds004625 - Mind in Motion: Young Adults Walking Over Uneven Terrain

Dataset: `openneuro_ds004625` | Year: 2023 | URL: https://openneuro.org/datasets/ds004625
Category: Complex Applied | Subjects: 32 | Files (Completed): 543 | Channels: 284 | Sampling Rate: 500 Hz

Paradigm

Participants walked over uneven terrain at different speeds while high-density EEG, EMG, and kinematic data were simultaneously recorded, with a seated resting condition also included. The study examines neural correlates of locomotor control and gait adaptation during ambulatory tasks. Gait events (heel-strikes, toe-offs) were synchronized with EEG via force-sensitive insoles.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004625

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`LHS`	65124	short	raw	Left heel strike
`LTO`	65105	short	raw	Left toe off
`RHS`	63800	short	raw	Right heel strike
`RTO`	63792	short	raw	Right toe off
`CGY-T 1`	2786	short	raw	Terrain change trigger
`CGY-M 1`	676	short	raw	Gait measurement marker
`spare-M 1`	635	short	raw	Spare measurement marker
`boundary`	543	admin	raw	Segment boundary (exclude)
`TrialStart`	543	long	raw	Trial start marker
`TrialEnd`	543	long	raw	Trial end marker
`LS-Sync`	536	admin	raw	Insole sync pulse (exclude)
`CWR-M 1`	269	short	raw	Cobblestone walk marker

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Mixed

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004625 DOI: https://doi.org/10.18112/openneuro.ds004625.v1.0.2

Normal Task 1: Gait Event Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: High channel count (284-channel HD-EEG). boundary and LS-Sync are admin - exclude. TrialStart/TrialEnd define walking bouts. Extensive motion artifact rejection required.

Event	y	Meaning
`LHS`	0	Left heel strike
`LTO`	1	Left toe off
`RHS`	2	Right heel strike
`RTO`	3	Right toe off
## Data Quality Notes		

- High-density EEG (284 channels) with significant motion artifacts from walking.
- boundary and LS-Sync markers are administrative - exclude.
- Mobile EEG data - apply ICA-based artifact correction.

References

- Reference: `Mind in Motion: Young Adults Walking Over Uneven Terrain`

027. openneuro_ds004657 - Driving with Autonomous Aids

Dataset: `openneuro_ds004657` | Year: 2023 | URL: https://openneuro.org/datasets/ds004657
Category: Complex Applied | Subjects: N/A | Files (Completed): 119 | Channels: 74 | Sampling Rate: 1024 Hz

Paradigm

Participants performed a semi-automated driving task involving lane maintenance and collision avoidance to evaluate human trust in automation across manual and varying autonomous assistance conditions. The 7-digit hierarchical trigger codes encode the driving condition, task phase, and condition variant. Codes 2310002/2310001 dominate with ~10,367 events each; 4111101 appears ~10,051 times. All other codes appear 1,081-1,819 times each - consistent with less-frequent driving scenarios or transitions.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004657

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`2310002`	10367	long	raw	Driving condition 231, variant 2 (dominant)
`2310001`	10367	long	raw	Driving condition 231, variant 1 (dominant)
`4111101`	10051	long	raw	Driving condition 411, variant 1
`2320001`	1819	long	raw	Driving condition 232, variant 1
`2320002`	1819	long	raw	Driving condition 232, variant 2
`1410001`	1383	long	raw	Driving condition 141, variant 1
`1410002`	1383	long	raw	Driving condition 141, variant 2
`1420001`	1226	long	raw	Driving condition 142, variant 1
`1420002`	1226	long	raw	Driving condition 142, variant 2
`1320001`	1175	long	raw	Driving condition 132, variant 1

Event ID	Count (total)	Type	Meta Level	Meaning
1320002	1175	long	raw	Driving condition 132, variant 2
2541001	1174	long	raw	Driving condition 254, variant 1
2781021	1094	long	raw	Driving condition 278, variant 021
2781022	1094	long	raw	Driving condition 278, variant 022
2561001	1081	long	raw	Driving condition 256, variant 1

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Drive

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004657 DOI: https://doi.org/10.18112/openneuro.ds004657.v1.0.3

Normal Task 1: Driving Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 7-digit codes require mapping from dataset README. Codes 2310001/2310002/4111101 dominate (>10k each); all others are minority classes (1k-1.8k). Group by leading 3-4 digits for higher-level condition classification.

Event	y	Meaning
2310001	0	Driving condition 231, variant 1
2310002	1	Driving condition 231, variant 2
4111101	2	Driving condition 411, variant 1
## Data Quality Notes		

- 7-digit hierarchical trigger codes require decode from README or paper.

- Codes 2310001/2310002/4111101 dominate (>10k each); other codes are minority classes.
- Subject count not specified in BIDS metadata.

References

- Reference: `Driving with Autonomous Aids`

028. openneuro_ds004660 - TNO (Military Cognitive Workload)

Dataset: `openneuro_ds004660` | Year: 2023 | URL: https://openneuro.org/datasets/ds004660
Category: Complex Applied | Subjects: 42 | Files (Completed): 42
Channels: 38 | Sampling Rate: 512 Hz

Paradigm

A military-relevant cognitive workload study conducted at TNO research institute, involving multiple hierarchically encoded task conditions represented by 5-digit numeric trigger codes. The paradigm likely involves surveillance, target detection, or dual-task conditions common in defense research. Event codes encode task type, difficulty level, and stimulus properties in a hierarchical scheme.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004660

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
14211	42922	short	raw	Hierarchical task code - primary condition
14212	42922	short	raw	Hierarchical task code - primary condition variant
21111	9228	short	raw	Hierarchical task code
14112	9228	short	raw	Hierarchical task code
14111	9228	short	raw	Hierarchical task code
13001	3663	short	raw	Hierarchical task code
13002	3663	short	raw	Hierarchical task code
21201	3663	short	raw	Hierarchical task code
15521	1840	short	raw	Hierarchical task code
15421	1840	short	raw	Hierarchical task code

Event ID	Count (total)	Type	Meta Level	Meaning
14121	1680	short	raw	Hierarchical task code
14122	1680	short	raw	Hierarchical task code

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://openneuro.org/datasets/ds004660 DOI: https://doi.org/10.18112/openneuro.ds004660.v1.0.2

Normal Task 1: Conditional classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: All codes are hierarchically structured 5-digit identifiers. Full decode table required from TNO dataset README or associated paper.

Event	y	Meaning
14211	0	Primary task code
14212	1	Primary task code variant
21111	2	Task code
14112	3	Task code
14111	4	Task code
13001	5	Task code
13002	6	Task code

Event	y	Meaning
21201	7	Task code
## Data Quality Notes		

- All event codes are 5-digit hierarchical numeric identifiers - full decode needed.
- 30+ unique event types; group by high-level condition category for practical classification.

References

- Reference: TNO

029. openneuro_ds004661 - ANDI: Auditory N-back Dual-task EEG

Dataset: `openneuro_ds004661` | Year: 2024 | URL: https://openneuro.org/datasets/ds004661
Category: Complex Applied | Subjects: 17 | Files (Completed): 17 | Channels: 64 | Sampling Rate: 128 Hz

Paradigm

A dual-task paradigm combining a guided visual search task (tracking a red annulus) with an auditory N-back working memory task to study cognitive interference. Event code `10` marks the dominant condition (likely standard/no-target trials, 29,820 total) and `11` marks the minority condition (likely target/match trials, 2,948 total). The large imbalance between codes suggests `10` = non-target and `11` = N-back target detection.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004661

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`10`	29820	short	raw	Non-target trial (dominant condition)
`11`	2948	short	raw	N-back target match (minority condition)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Nback

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004661 DOI: https://doi.org/10.18112/openneuro.ds004661.v1.1.0

Normal Task 1: Target vs Non-target N-back Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`

- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Strong class imbalance (29,820 vs 2,948 ~ 10:1); undersample class 0 or use weighted loss. Low sampling rate (128 Hz) limits spectral resolution. Verify code meanings from dataset README or Ries et al., 2016.

Event	y	Meaning
`10`	0	Non-target trial
`11`	1	N-back target match
## Data Quality Notes		

- Only 2 event codes; binary classification.
- Strong class imbalance (~10:1); undersample majority class.
- Low sampling rate (128 Hz); limited for high-frequency analyses.

References

- Reference: `Ries, et al., 2016`

030. openneuro_ds004718 - Le Petit Prince Hong Kong: Naturalistic fMRI and EEG Dataset

Dataset: `openneuro_ds004718` | Year: 2025 | URL: https://openneuro.org/datasets/ds004718
Category: Complex Applied | Subjects: 52 | Files (Completed): 102 | Channels: 62 | Sampling Rate: 1000 Hz

Paradigm

Naturalistic listening task where older Cantonese-speaking adults (65+) listened to a Cantonese translation of "The Little Prince" divided into story sections, followed by periodic comprehension checks, during simultaneous EEG and fMRI recording. Numeric trigger codes 1-30+ mark story segments, comprehension questions, and experimental conditions. Code 14 is most frequent (1,053 total), followed by codes 15 (648), and many codes at ~258 each - consistent with a factorial design across 102 files with ~2-10 events per file per code.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004718

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`14`	1053	long	raw	Story section / condition code 14
`15`	648	long	raw	Story section / condition code 15
`7`	270	long	raw	Story section / condition code 7
`3`	268	long	raw	Story section / condition code 3
`5`	266	long	raw	Story section / condition code 5
`4`	263	long	raw	Story section / condition code 4
`6`	262	long	raw	Story section / condition code 6
`88`	259	long	raw	Story section / condition code 88
`40-112`	~258 each	long	raw	Additional story/condition codes
`1-30`	~257-258 each	long	raw	Story section codes 1-30

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Lpp HK

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004718 DOI: https://doi.org/10.18112/openneuro.ds004718.v1.1.2

Primary Task 2: Publisher-defined BIDS task: Rest

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004718 DOI: https://doi.org/10.18112/openneuro.ds004718.v1.1.2

Normal Task 1: Story Section / Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Numeric codes require full decode from dataset README or events.tsv. Naturalistic listening paradigm; continuous EEG during extended story segments. Code 14 is dominant (1,053) vs many codes at ~258 - likely reflects story structure (code 14 = more frequent section). 30+ distinct numeric codes; consider grouping.

Event	y	Meaning
1	0	Story/condition code 1
2	1	Story/condition code 2
3	2	Story/condition code 3
4	3	Story/condition code 4
5	4	Story/condition code 5
6	5	Story/condition code 6

Event	y	Meaning
7	6	Story/condition code 7
## Data Quality Notes		

- Numeric code meaning requires README or events.tsv decode.
- Naturalistic paradigm - EEG is continuous during extended listening blocks.
- Simultaneous 7T fMRI and EEG - verify gradient artifact removal.

References

- Reference: `Le Petit Prince Hong Kong: Naturalistic fMRI and EEG dataset from older Cantonese speakers`

031. openneuro_ds004840 - EEG/ECG/EMG During Music Therapy in ICU Burn Patients

Dataset: `openneuro_ds004840` | Year: 2023 | URL: https://openneuro.org/datasets/ds004840
Category: Complex Applied | Subjects: 9 | Files (Completed): 68 | Channels: 10 | Sampling Rate: 1024 Hz

Paradigm

Electrophysiological recordings (EEG, ECG, EMG) of adult burn patients in a clinical ICU environment during Music-Assisted Relaxation (MAR) therapy sessions. No event markers are present; EEG is continuous throughout the therapy recording. The study investigates physiological responses to music therapy as a pain and anxiety management intervention.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004840

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
(no events)	-	-	raw	No event markers detected in events.tsv

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Task music Therapy

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004840 DOI: https://doi.org/10.18112/openneuro.ds004840.v1.0.1

Primary Task 2: Publisher-defined BIDS task: Task post Music Therapy

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`

- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004840 DOI: https://doi.org/10.18112/openneuro.ds004840.v1.0.1

Primary Task 3: Publisher-defined BIDS task: Task pre Music Therapy

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004840 DOI: https://doi.org/10.18112/openneuro.ds004840.v1.0.1

Normal Task 1: Continuous Segmentation (segmentation)

- Task Type: regression
- Epoch Method: `segmentation`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: None
- Notes: No event markers. Use sliding-window segmentation. Condition labels (pre-therapy / during / post-therapy) may be available from session metadata or participants.tsv.

Data Quality Notes

- No event markers; continuous EEG during music therapy.
- Clinical ICU environment - subject motion, medical equipment interference expected.
- Only 10 channels including ECG and EMG - limited spatial resolution for EEG analysis.

References

- Reference: `Dataset of electrophysiological signals (EEG, ECG, EMG) during Music therapy with adult burn patients in the Intensive Care Unit.`

032. openneuro_ds004841 - TX14 (Semi-Autonomous Vehicle Monitoring)

Dataset: `openneuro_ds004841` | Year: 2023 | URL: https://openneuro.org/datasets/ds004841
Category: Complex Applied | Subjects: 11 | Files (Completed): 11 | Channels: 70 | Sampling Rate: 256 Hz

Paradigm

Participants monitored a semi-autonomous vehicle system and performed local situational awareness tasks within a simulated environment, with EEG recorded to characterize cognitive states during supervised automation. Event codes are hierarchically structured 7-digit identifiers encoding operational state and task type.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004841

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`2210001`	998	long	raw	Hierarchical operational state code
`2210002`	947	long	raw	Hierarchical operational state code
`2110000`	220	long	raw	Hierarchical operational state code
`4310000`	195	long	raw	Hierarchical operational state code
`4100001`	195	long	raw	Hierarchical operational state code
`4320000`	195	long	raw	Hierarchical operational state code
`4300010`	107	long	raw	Hierarchical operational state code
`4300020`	96	long	raw	Hierarchical operational state code

Event ID	Count (total)	Type	Meta Level	Meaning
4300100	80	long	raw	Hierarchical operational state code
1110002	76	long	raw	Hierarchical operational state code
1110001	76	long	raw	Hierarchical operational state code

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Drive On Mission

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004841 DOI: https://doi.org/10.18112/openneuro.ds004841.v1.0.1

Normal Task 1: Operational State Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: All codes are 7-digit hierarchical identifiers. Full decode table required from dataset README. Only 11 subjects - small dataset.

Event	y	Meaning
2210001	0	Operational state code
2210002	1	Operational state code
2110000	2	Operational state code
4310000	3	Operational state code
4100001	4	Operational state code
4320000	5	Operational state code
## Data Quality Notes		

- 7-digit hierarchical numeric codes - full decode needed.
- Only 11 subjects; limited sample size for generalization.

References

- Reference: `TX14. ReadMe: TX14 dataset`

033. openneuro_ds004844 - T22 (Semi-Automated Driving Trust Paradigm)

Dataset: `openneuro_ds004844` | Year: 2023 | URL: https://openneuro.org/datasets/ds004844
Category: Complex Applied | Subjects: 68 | Files (Completed): 68 | Channels: 72 | Sampling Rate: 1024 Hz

Paradigm

Simulated semi-automated driving in a leader-follower paradigm focused on predicting and influencing trust-based decisions regarding control authority hand-off and take-over between human and automation. EEG was recorded during sustained driving across multiple automation levels. Event codes are hierarchically structured 7-digit identifiers encoding driving state and automation mode.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004844

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`2310002`	8978	long	raw	Driving state code
`2310001`	8978	long	raw	Driving state code
`4111101`	8716	long	raw	Driving state code
`2572001`	3231	long	raw	Driving state code
`2562001`	2880	long	raw	Driving state code
`2552001`	1983	long	raw	Driving state code
`3110002`	1884	long	raw	Driving state code
`2812002`	1884	long	raw	Driving state code
`3110001`	1884	long	raw	Driving state code
`2812001`	1884	long	raw	Driving state code
`2714111`	1591	long	raw	Driving state code
`1410001`	1591	long	raw	Driving state code
`1410002`	1591	long	raw	Driving state code

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Drive

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004844 DOI: https://doi.org/10.18112/openneuro.ds004844.v1.0.0

Normal Task 1: Driving State Classification (multiclass/long)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: All codes are 7-digit hierarchical identifiers encoding driving condition and automation level. Full decode table required from dataset README. Related dataset: ds004657.

Event	y	Meaning
`2310002`	0	Driving state code
`2310001`	1	Driving state code
`4111101`	2	Driving state code
`2572001`	3	Driving state code
`2562001`	4	Driving state code
`2552001`	5	Driving state code
`3110002`	6	Driving state code
`2812002`	7	Driving state code
## Data Quality Notes		

- All event codes are 7-digit hierarchical numeric identifiers - full decode needed.
- 40+ unique codes; group by condition category for practical classification.

References

- Reference: `Predicting and influencing trust-based decisions about control authority hand-off and take-over during simulated, semi-automated driving in a leader-follower paradigm`

034. openneuro_ds004849 - STRONG (Social-Cognitive EEG Dataset)

Dataset: `openneuro_ds004849` | Year: 2023 | URL: https://openneuro.org/datasets/ds004849
Category: Complex Applied | Subjects: 1 | Files (Completed): 1 | Channels: 64 | Sampling Rate: 128 Hz

Paradigm

An EEG dataset recorded during a social-cognitive paradigm involving multiple hierarchically encoded stimulus conditions. The 5-digit numeric trigger codes encode stimulus type, valence, and response. The dataset contains a single aggregated file across participants; specific task details require decoding from events.tsv.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004849

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`2200`	1627	short	raw	Dominant trigger code (primary condition)
`72011`	338	short	raw	Trigger code (category 7, type 2)
`52011`	332	short	raw	Trigger code (category 5, type 2)
`75011`	320	short	raw	Trigger code
`55011`	317	short	raw	Trigger code
`73011`	316	short	raw	Trigger code
`74011`	312	short	raw	Trigger code
`53011`	308	short	raw	Trigger code
`54011`	307	short	raw	Trigger code
`1`	195	short	raw	Trigger code 1 (sync/startx)
`71011`	174	short	raw	Trigger code
`2201`	173	short	raw	Trigger code
`51011`	170	short	raw	Trigger code

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Nback

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004849 DOI: https://doi.org/10.18112/openneuro.ds004849.v1.0.0

Normal Task 1: Stimulus Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Full decode needed from events.tsv. Only 1 file (single aggregated file). Related datasets: ds004850, ds004852.

Event	y	Meaning
`2200`	0	Primary condition code
`72011`	1	Trigger code
`52011`	2	Trigger code
`75011`	3	Trigger code
`55011`	4	Trigger code
`73011`	5	Trigger code
`74011`	6	Trigger code
`53011`	7	Trigger code
`54011`	8	Trigger code
`71011`	9	Trigger code
`2201`	10	Trigger code
`51011`	11	Trigger code
## Data Quality Notes		

- Single aggregated file; individual subject data not separable without additional metadata.
- Full trigger decode required from events.tsv.

References

- Reference: STRONG

035. openneuro_ds004850 - ODE (Social-Cognitive EEG Dataset)

Dataset: `openneuro_ds004850` | Year: 2023 | URL: https://openneuro.org/datasets/ds004850
Category: Complex Applied | Subjects: 1 | Files (Completed): 1 | Channels: 64 | Sampling Rate: 128 Hz

Paradigm

An EEG dataset (ODE) recorded during a social-cognitive paradigm with hierarchically encoded stimulus conditions. Shares the identical event structure with the STRONG (ds004849) and InsurgentCivilian (ds004852) datasets, suggesting these are companion recordings from the same experimental series. The single aggregated file requires events.tsv decoding for full interpretation.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004850

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`2200`	1627	short	raw	Dominant trigger code (primary condition)
`72011`	338	short	raw	Trigger code (category 7, type 2)
`52011`	332	short	raw	Trigger code
`75011`	320	short	raw	Trigger code
`55011`	317	short	raw	Trigger code
`73011`	316	short	raw	Trigger code
`74011`	312	short	raw	Trigger code
`53011`	308	short	raw	Trigger code
`54011`	307	short	raw	Trigger code
`1`	195	short	raw	Trigger code 1
`71011`	174	short	raw	Trigger code
`2201`	173	short	raw	Trigger code
`51011`	170	short	raw	Trigger code

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Nback

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004850 DOI: https://doi.org/10.18112/openneuro.ds004850.v1.0.0

Normal Task 1: Stimulus Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Identical event structure to ds004849 (STRONG) and ds004852 (InsurgentCivilian). Single aggregated file.

Event	y	Meaning
`2200`	0	Primary condition code
`72011`	1	Trigger code
`52011`	2	Trigger code
`75011`	3	Trigger code
`55011`	4	Trigger code
`73011`	5	Trigger code
`74011`	6	Trigger code
`53011`	7	Trigger code
`54011`	8	Trigger code
`71011`	9	Trigger code
`2201`	10	Trigger code
`51011`	11	Trigger code
## Data Quality Notes		

- Single aggregated file; individual subject data not separable.
- Identical event structure to ds004849 and ds004852 - likely companion recordings.

References

- Reference: ODE

036. openneuro_ds004851 - HID (High-Density EEG Operational Dataset)

Dataset: `openneuro_ds004851` | Year: 2024 | URL: https://openneuro.org/datasets/ds004851
Category: Complex Applied | Subjects: 65 | Files (Completed): 65 | Channels: 72 | Sampling Rate: 2048 Hz

Paradigm

High-density EEG recorded in an operational context involving multiple conditions encoded as 4-digit numeric trigger codes. The code structure suggests stimulus classes (1xxx: primary task events, 7xxx/8xxx: secondary stimulus categories) within a cognitive workload or situational awareness paradigm.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004851

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`1010`	2181	short	raw	Primary event onset (type A)
`1011`	2179	short	raw	Primary event (type A variant)
`1020`	1970	short	raw	Primary event (type B)
`1021`	1970	short	raw	Primary event (type B variant)
`1040`	1912	short	raw	Primary event (type D)
`1041`	1912	short	raw	Primary event (type D variant)
`8100`	973	short	raw	Secondary stimulus category 8, type 1
`8101`	973	short	raw	Secondary stimulus category 8, type 1 variant
`1061`	474	short	raw	Primary event (type F variant)
`1060`	474	short	raw	Primary event (type F)
`8011`	195	short	raw	Secondary stimulus
`8010`	195	short	raw	Secondary stimulus

Event ID	Count (total)	Type	Meta Level	Meaning
8021	194	short	raw	Secondary stimulus
8020	194	short	raw	Secondary stimulus
7001-7019	~65 each	short	raw	Tertiary stimulus category (19 types)

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: HID

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004851 DOI: https://doi.org/10.18112/openneuro.ds004851.v2.1.0

Normal Task 1: Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Very high sampling rate (2048 Hz) - downsample before analysis. Full decode table required from dataset README.

Event	y	Meaning
1010	0	Primary event type A
1011	1	Primary event type A variant
1020	2	Primary event type B
1021	3	Primary event type B variant
1040	4	Primary event type D
1041	5	Primary event type D variant
8100	6	Secondary stimulus
8101	7	Secondary stimulus variant
## Data Quality Notes		

- Very high sampling rate (2048 Hz) - downsample for efficiency.

- 30+ distinct codes; grouping by prefix category recommended.

References

- Reference: `HID`

037. openneuro_ds004852 - InsurgentCivilian (Social-Cognitive EEG Dataset)

Dataset: `openneuro_ds004852` | Year: 2023 | URL: https://openneuro.org/datasets/ds004852
Category: Complex Applied | Subjects: 1 | Files (Completed): 1 | Channels: 64 | Sampling Rate: 128 Hz

Paradigm

An EEG dataset (InsurgentCivilian) recorded during a social-cognitive paradigm where participants were likely required to classify ambiguous human figures as insurgents or civilians, a common threat-detection paradigm used in military research. Shares the identical event structure with STRONG (ds004849) and ODE (ds004850), suggesting these are companion recordings from the same experimental series.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004852

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`2200`	1627	short	raw	Dominant trigger code (primary condition)
`72011`	338	short	raw	Trigger code (category 7, type 2)
`52011`	332	short	raw	Trigger code
`75011`	320	short	raw	Trigger code
`55011`	317	short	raw	Trigger code
`73011`	316	short	raw	Trigger code
`74011`	312	short	raw	Trigger code
`53011`	308	short	raw	Trigger code
`54011`	307	short	raw	Trigger code
`1`	195	short	raw	Trigger code 1
`71011`	174	short	raw	Trigger code
`2201`	173	short	raw	Trigger code
`51011`	170	short	raw	Trigger code

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Nback

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004852 DOI: https://doi.org/10.18112/openneuro.ds004852.v1.0.0

Normal Task 1: Stimulus Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Identical event structure to ds004849 (STRONG) and ds004850 (ODE). Single aggregated file.

Event	y	Meaning
`2200`	0	Primary condition code
`72011`	1	Trigger code
`52011`	2	Trigger code
`75011`	3	Trigger code
`55011`	4	Trigger code
`73011`	5	Trigger code
`74011`	6	Trigger code
`53011`	7	Trigger code
`54011`	8	Trigger code
`71011`	9	Trigger code
`2201`	10	Trigger code
`51011`	11	Trigger code
## Data Quality Notes		

- Single aggregated file; individual subject data not separable.
- Identical event structure to ds004849 and ds004850 - companion recordings.

References

- Reference: `InsurgentCivilian`

038. openneuro_ds004980 - EEG Data for an Architectural Affordances Task

Dataset: `openneuro_ds004980` | Year: 2024 | URL: https://openneuro.org/datasets/ds004980
Category: Complex Applied | Subjects: 17 | Files (Completed): 17 | Channels: 64 | Sampling Rate: 500 Hz

Paradigm

Participants navigated a virtual architectural environment using keyboard controls while EEG was recorded to investigate neural responses to architectural affordances - the action possibilities offered by built spaces. The study examines how the brain processes spatial features (doors, corridors, rooms) that afford specific navigational actions. SAM (Self-Assessment Manikin) rating events mark periodic subjective valence/arousal/dominance assessments.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004980

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Key released: UpArrow (forward)`	13072	short	raw	Forward key release
`Key pressed: UpArrow (forward)`	13063	short	raw	Forward key press
`Key pressed: RightArrow (turn right)`	8915	short	raw	Right turn key press
`Key released: RightArrow (turn right)`	8911	short	raw	Right turn key release
`Key pressed: LeftArrow (turn left)`	7360	short	raw	Left turn key press
`Key released: LeftArrow (turn left)`	7356	short	raw	Left turn key release
`Player left StartSquare`	6904	short	raw	Participant exits start zone
`Player entered SAM Activator`	4584	short	raw	SAM rating zone entered
`SAM:start`	4521	short	raw	SAM rating starts

Event ID	Count (total)	Type	Meta Level	Meaning
SAM:completed	4517	short	raw	SAM rating completed
Player left SAM Activator	4567	short	raw	SAM rating zone exited
Wall touched: trial failed!	2183	short	raw	Navigation error
Door opened	2427	short	raw	Door affordance activated
ColliderRoom1 has been entered	1528	short	raw	Room 1 entered
ColliderRoom2 has been entered	1523	short	raw	Room 2 entered

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Default Task

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004980 DOI: https://doi.org/10.18112/openneuro.ds004980.v1.0.0

Normal Task 1: Navigation Action Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: SAM events (SAM:start, SAM:completed) mark subjective rating periods - treat separately or exclude. Reset/admin events (Reset insideActivator flag, player position reseted) are admin.

Event	y	Meaning
Key pressed: UpArrow (forward)	0	Forward navigation
Key pressed: RightArrow (turn right)	1	Right turn
Key pressed: LeftArrow (turn left)	2	Left turn
Door opened	3	Door affordance activated
ColliderRoom1 has been entered	4	Room 1 entered
ColliderRoom2 has been entered	5	Room 2 entered
## Data Quality Notes		

- 30+ unique event types; focus on key presses and spatial boundary events.

- SAM rating events mark active rating periods - exclude from navigation classification.

References

- Reference: `EEG data set for an architectural affordances task`

039. openneuro_ds005345 - Le Petit Prince Multitalker: Naturalistic 7T fMRI and EEG Dataset

Dataset: openneuro_ds005345 | Year: 2025 | URL: https://openneuro.org/datasets/ds005345
Category: Complex Applied | Subjects: 25 | Files (Completed): 28
Channels: 64 | Sampling Rate: 500 Hz

Paradigm

Participants engaged in naturalistic listening to excerpts of "Le Petit Prince" (The Little Prince) under single-talker and multi-talker conditions during simultaneous EEG and 7T fMRI recording. The study investigates neural processing of speech under cocktail-party-style listening conditions. Stimulus/S 11 marks single-talker condition onsets; Stimulus/S 31-S 34 mark multi-talker condition variants. Comment/actiCAP Data On is an EEG system administrative marker.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005345

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
Stimulus/S 11	~19/file	long	raw	Single-talker listening block onset
Stimulus/S 31	~6/file	long	raw	Multi-talker condition variant 31 onset
Stimulus/S 32	~6/file	long	raw	Multi-talker condition variant 32 onset
Stimulus/S 33	~6/file	long	raw	Multi-talker condition variant 33 onset
Stimulus/S 34	~6/file	long	raw	Multi-talker condition variant 34 onset
Comment/actiCAP Data On	25/file	admin	raw	EEG recording system marker (exclude)

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Stimulus/S 11, Stimulus/S 31, Stimulus/S 32, Stimulus/S 33, Stimulus/S 34
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Multitalker

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005345 DOI: https://doi.org/10.18112/openneuro.ds005345.v1.0.1

Primary Task 2: Publisher-defined BIDS task: Rest

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005345 DOI: https://doi.org/10.18112/openneuro.ds005345.v1.0.1

Normal Task 1: Listening Condition Classification (binary/multiclass)

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5 s, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Comment/actiCAP Data On is admin - exclude. Naturalistic listening paradigm with sustained EEG blocks. Very small dataset (28 files, 25 subjects).

Event	y	Meaning
Stimulus/S 11	0	Single-talker listening
Stimulus/S 31	1	Multi-talker condition 31
Stimulus/S 32	2	Multi-talker condition 32
Stimulus/S 33	3	Multi-talker condition 33
Stimulus/S 34	4	Multi-talker condition 34
## Data Quality Notes		

- Very small dataset (28 files, 25 subjects).
- Comment/actiCAP Data On is an admin system marker - exclude from epoching.
- Simultaneous 7T fMRI - MR gradient artifacts may require removal if present.

References

- Reference: Le Petit Prince Multitalker: Naturalistic 7T fMRI and EEG Dataset

040. openneuro_ds005416 - Fatigue Characterization of EEG under Mixed Reality Stereo Vision

Dataset: `openneuro_ds005416` | Year: 2024 | URL: https://openneuro.org/datasets/ds005416
Category: Complex Applied | Subjects: 23 | Files (Completed): 23 | Channels: 64 | Sampling Rate: 1000 Hz

Paradigm

Participants viewed resting and movement scenes in a Mixed Reality (MR) stereo vision environment to characterize EEG-based fatigue during periodic visual depth and velocity changes. The study investigates neural correlates of visual fatigue induced by MR headset viewing under different dynamic visual conditions. No trial events were captured in events.tsv; data is continuous.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005416

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
(no events)	-	-	raw	No event markers detected in events.tsv

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Watching Task

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005416 DOI: https://doi.org/10.18112/openneuro.ds005416.v1.0.1

Normal Task 1: Continuous Segmentation (segmentation)

- Task Type: regression
- Epoch Method: `segmentation`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: None

- Notes: No event markers in events.tsv. EEG is continuous during MR viewing task. Use sliding-window segmentation. Condition labels (fatigue level, visual condition) may be available from session metadata.

Data Quality Notes

- No event markers; continuous EEG during MR task.
- High sampling rate (1000 Hz) adequate for spectral fatigue analysis.
- MR headset may introduce electrical interference artifacts.

References

- Reference: `Fatigue Characterization of EEG under Mixed Reality Stereo Vision`

041. openneuro_ds005505 - Healthy Brain Network (HBN) EEG - Release 1

Dataset: `openneuro_ds005505` | Year: 2025 | URL: https://openneuro.org/datasets/ds005505
Category: Complex Applied | Subjects: 136 | Files (Completed): 1342 | Channels: 129 | Sampling Rate: 500 Hz

Paradigm

The Healthy Brain Network (HBN) EEG Release 1 is a large-scale, multi-task developmental battery collected from children and adolescents. Participants completed naturalistic movie watching, eyes-open/closed resting state, sensory contrast detection (contrastTrial), surrounding suppression, sequence learning (seqLearning), and symbol search tasks. The dataset aims to characterize neurodevelopmental and psychopathological profiles across a broad pediatric population.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, externalizing, phenotypic, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005505

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stim_ON`	13278	short	raw	Contrast detection stimulus onset
`fixpoint_ON`	13248	short	raw	Fixation point onset (trial start cue)
`contrastTrial_start`	8884	long	raw	Contrast detection trial block onset
`left_buttonPress`	5095	short	raw	Participant button press - left hand
`right_buttonPress`	4634	short	raw	Participant button press - right hand
`right_target`	4251	short	raw	Right-side target stimulus
`left_target`	4243	short	raw	Left-side target stimulus
`break cnt`	1488	admin	raw	Break/counter marker between blocks
`trialResponse`	1247	short	raw	Trial response event
`instructed_toOpenEyes`	816	long	raw	Instruction to open eyes (resting block)
`video_start`	761	long	raw	Movie clip onset

Event ID	Count (total)	Type	Meta Level	Meaning
boundary	728	admin	raw	Segment boundary marker
video_stop	723	long	raw	Movie clip offset
instructed_toCloseEyes	680	long	raw	Instruction to close eyes (resting block)
resting_start	136	long	raw	Resting-state block onset
seqLearning_start	122	long	raw	Sequence learning block onset
learningBlock_1	122	long	raw	Sequence learning block 1 onset
9999	1136	admin	raw	End-of-recording marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: externalizing_factor, p_factor, response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: stim_ON
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Despicable Me

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 2: Publisher-defined BIDS task: Seq Learning6target

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)

- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 3: Publisher-defined BIDS task: Seq Learning8target

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Normal Task 1: Raw-meta event decoding and classification (event-level)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use non-admin events such as `left_target`, `right_target`, `trialResponse`, `stim_ON`.
- Kernel Notes: Exclude admin markers from supervised target sets.

Normal Task 2: Raw-meta state decoding (long-event)

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use state/block markers such as `instructed_toOpenEyes`, `instructed_toCloseEyes`, `resting_start`, `video_start`, `video_stop`.
- Kernel Notes: Keep block-label mapping stable across releases.

Normal Task 3: Super-meta response-time regression (competition-style)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: event-centered windows (task-dependent), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `response_time`
- Kernel Notes: Parse trial chains and write regression targets with unit/version metadata.

Normal Task 4: Super-meta psychopathology-factor modeling

- Task Type: regression (or discretized classification baseline)
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `p_factor` / `externalizing_factor` (schema dependent)
- Kernel Notes: Join EEG with phenotypic tables by subject key and use subject-wise splits to prevent leakage.

Data Quality Notes

- HBN is a heterogeneous multi-task battery; task availability differs across participants and files.
- Event naming and density are not perfectly uniform across releases; mapping tables should be explicit.
- Admin markers (`boundary`, `9999`, etc.) are frequent and must be filtered before model target construction.
- Super-meta tasks are sensitive to join quality (subject ID harmonization, missingness, leakage control).
- Report clearly whether each experiment uses raw meta labels or super meta labels.

References

- OpenNeuro dataset page: `https://openneuro.org/datasets/ds005505/versions/1.0.1`
- EEG2025 challenge portal: `https://eeg2025.github.io/`
- EEGUnity kernel tutorial (rich/super meta abstraction): `https://eegunity.readthedocs.io/en/v0.7.0/tutorial/How%20to%20Reading%20Rich%20Meta%20Data%20via%20Kernel.html`
- EEGUnity batch API (`epoch_by_event_hdf5`, `epoch_by_long_event_hdf5`): `https://eegunity.readthedocs.io/en/v0.7.0/eegunity.modules.batch.html`

042. openneuro_ds005506 - Healthy Brain Network (HBN) EEG - Release 2

Dataset: `openneuro_ds005506` | Year: 2025 | URL: https://openneuro.org/datasets/ds005506
Category: Complex Applied | Subjects: 152 | Files (Completed): 1405 | Channels: 129 | Sampling Rate: 500 Hz

Paradigm

The Healthy Brain Network (HBN) EEG Release 2 is a large-scale, multi-task developmental battery collected from children and adolescents. Participants completed naturalistic movie watching, eyes-open/closed resting state, sensory contrast detection, surrounding suppression, sequence learning, and symbol search tasks. The dataset aims to characterize neurodevelopmental and psychopathological profiles across a broad pediatric population.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, externalizing, phenotypic, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005506

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stim_ON`	14116	short	raw	Contrast detection stimulus onset
`fixpoint_ON`	14081	short	raw	Fixation point onset (trial start cue)
`contrastTrial_start`	9310	long	raw	Contrast detection trial block onset
`left_buttonPress`	5762	short	raw	Participant button press - left hand
`right_buttonPress`	4970	short	raw	Participant button press - right hand
`right_target`	4463	short	raw	Right-side target stimulus
`left_target`	4439	short	raw	Left-side target stimulus
`break cnt`	1577	admin	raw	Break/counter marker between blocks
`trialResponse`	1372	short	raw	Trial response event
`instructed_toOpenEyes`	883	long	raw	Instruction to open eyes (resting block)

Event ID	Count (total)	Type	Meta Level	Meaning
boundary	799	admin	raw	Segment boundary marker
video_start	797	long	raw	Movie clip onset
video_stop	765	long	raw	Movie clip offset
instructed_toCloseEyes	736	long	raw	Instruction to close eyes (resting block)
resting_start	150	long	raw	Resting-state block onset
9999	1150	admin	raw	End-of-recording marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: externalizing_factor, p_factor, response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: stim_ON
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Seq Learning6target

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 2: Publisher-defined BIDS task: The Present

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 3: Publisher-defined BIDS task: Resting State

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Normal Task 1: Raw-meta event decoding and classification (event-level)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use non-admin events such as `left_target`, `right_target`, `trialResponse`, `stim_ON`.
- Kernel Notes: Exclude admin markers from supervised target sets.

Normal Task 2: Raw-meta state decoding (long-event)

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use state/block markers such as `instructed_toOpenEyes`, `instructed_toCloseEyes`, `resting_start`, `video_start`, `video_stop`.
- Kernel Notes: Keep block-label mapping stable across releases.

Normal Task 3: Super-meta response-time regression (competition-style)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: event-centered windows (task-dependent), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `response_time`
- Kernel Notes: Parse trial chains and write regression targets with unit/version metadata.

Normal Task 4: Super-meta psychopathology-factor modeling

- Task Type: regression (or discretized classification baseline)
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `p_factor` / `externalizing_factor` (schema dependent)
- Kernel Notes: Join EEG with phenotypic tables by subject key and use subject-wise splits to prevent leakage.

Data Quality Notes

- HBN is a heterogeneous multi-task battery; task availability differs across participants and files.

- Event naming and density are not perfectly uniform across releases; mapping tables should be explicit.
- Admin markers (`boundary`, `9999`, etc.) are frequent and must be filtered before model target construction.
- Super-meta tasks are sensitive to join quality (subject ID harmonization, missingness, leakage control).
- Report clearly whether each experiment uses raw meta labels or super meta labels.

References

- OpenNeuro dataset page: `https://openneuro.org/datasets/ds005506/versions/1.0.1`
- EEG2025 challenge portal: `https://eeg2025.github.io/`
- EEGUnity kernel tutorial (rich/super meta abstraction): `https://eegunity.readthedocs.io/en/v0.7.0/tutorial/How%20to%20Reading%20Rich%20Meta%20Data%20via%20Kernel.html`
- EEGUnity batch API (`epoch_by_event_hdf5`, `epoch_by_long_event_hdf5`): `https://eegunity.readthedocs.io/en/v0.7.0/eegunity.modules.batch.html`

043. openneuro_ds005507 - Healthy Brain Network (HBN) EEG - Release 3

Dataset: `openneuro_ds005507` | Year: 2025 | URL: https://openneuro.org/datasets/ds005507
Category: Complex Applied | Subjects: 183 | Files (Completed): 1812 | Channels: 129 | Sampling Rate: 500 Hz

Paradigm

The Healthy Brain Network (HBN) EEG Release 3 is a large-scale, multi-task developmental battery collected from children and adolescents. Participants completed naturalistic movie watching, eyes-open/closed resting state, sensory contrast detection, surrounding suppression, sequence learning, and symbol search tasks. The dataset aims to characterize neurodevelopmental and psychopathological profiles across a broad pediatric population.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, externalizing, phenotypic, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005507

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stim_ON`	18602	short	raw	Contrast detection stimulus onset
`fixpoint_ON`	18564	short	raw	Fixation point onset (trial start cue)
`contrastTrial_start`	12072	long	raw	Contrast detection trial block onset
`left_buttonPress`	6995	short	raw	Participant button press - left hand
`right_buttonPress`	6266	short	raw	Participant button press - right hand
`right_target`	5800	short	raw	Right-side target stimulus
`left_target`	5753	short	raw	Left-side target stimulus
`break cnt`	1973	admin	raw	Break/counter marker between blocks
`trialResponse`	1757	short	raw	Trial response event
`instructed_toOpenEyes`	1101	long	raw	Instruction to open eyes (resting block)

Event ID	Count (total)	Type	Meta Level	Meaning
boundary	1074	admin	raw	Segment boundary marker
video_start	1041	long	raw	Movie clip onset
video_stop	1013	long	raw	Movie clip offset
instructed_toCloseEyes	915	long	raw	Instruction to close eyes (resting block)
resting_start	184	long	raw	Resting-state block onset
9999	1446	admin	raw	End-of-recording marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: externalizing_factor, p_factor, response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: stim_ON
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Seq Learning8target

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 2: Publisher-defined BIDS task: Seq Learning6target

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 3: Publisher-defined BIDS task: Symbol Search

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Normal Task 1: Raw-meta event decoding and classification (event-level)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use non-admin events such as `left_target`, `right_target`, `trialResponse`, `stim_ON`.
- Kernel Notes: Exclude admin markers from supervised target sets.

Normal Task 2: Raw-meta state decoding (long-event)

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use state/block markers such as `instructed_toOpenEyes`, `instructed_toCloseEyes`, `resting_start`, `video_start`, `video_stop`.
- Kernel Notes: Keep block-label mapping stable across releases.

Normal Task 3: Super-meta response-time regression (competition-style)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: event-centered windows (task-dependent), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `response_time`
- Kernel Notes: Parse trial chains and write regression targets with unit/version metadata.

Normal Task 4: Super-meta psychopathology-factor modeling

- Task Type: regression (or discretized classification baseline)
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `p_factor` / `externalizing_factor` (schema dependent)
- Kernel Notes: Join EEG with phenotypic tables by subject key and use subject-wise splits to prevent leakage.

Data Quality Notes

- HBN is a heterogeneous multi-task battery; task availability differs across participants and files.

- Event naming and density are not perfectly uniform across releases; mapping tables should be explicit.
- Admin markers (`boundary`, `9999`, etc.) are frequent and must be filtered before model target construction.
- Super-meta tasks are sensitive to join quality (subject ID harmonization, missingness, leakage control).
- Report clearly whether each experiment uses raw meta labels or super meta labels.

References

- OpenNeuro dataset page: `https://openneuro.org/datasets/ds005507/versions/1.0.1`
- EEG2025 challenge portal: `https://eeg2025.github.io/`
- EEGUnity kernel tutorial (rich/super meta abstraction): `https://eegunity.readthedocs.io/en/v0.7.0/tutorial/How%20to%20Reading%20Rich%20Meta%20Data%20via%20Kernel.html`
- EEGUnity batch API (`epoch_by_event_hdf5`, `epoch_by_long_event_hdf5`): `https://eegunity.readthedocs.io/en/v0.7.0/eegunity.modules.batch.html`

044. openneuro_ds005508 - Healthy Brain Network (HBN) EEG - Release 4

Dataset: `openneuro_ds005508` | Year: 2025 | URL: https://openneuro.org/datasets/ds005508
Category: Complex Applied | Subjects: 324 | Files (Completed): 3342 | Channels: 129 | Sampling Rate: 500 Hz

Paradigm

The Healthy Brain Network (HBN) EEG Release 4 is a large-scale, multi-task developmental battery collected from children and adolescents. Participants completed naturalistic movie watching, eyes-open/closed resting state, sensory contrast detection, surrounding suppression, sequence learning, and symbol search tasks. The dataset aims to characterize neurodevelopmental and psychopathological profiles across a broad pediatric population.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, externalizing, phenotypic, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005508

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stim_ON`	35171	short	raw	Contrast detection stimulus onset
`fixpoint_ON`	35072	short	raw	Fixation point onset (trial start cue)
`contrastTrial_start`	20646	long	raw	Contrast detection trial block onset
`left_buttonPress`	11751	short	raw	Participant button press - left hand
`right_buttonPress`	10656	short	raw	Participant button press - right hand
`right_target`	9909	short	raw	Right-side target stimulus
`left_target`	9806	short	raw	Left-side target stimulus
`break cnt`	3452	admin	raw	Break/counter marker between blocks
`trialResponse`	3286	short	raw	Trial response event
`instructed_toOpenEyes`	1929	long	raw	Instruction to open eyes (resting block)

Event ID	Count (total)	Type	Meta Level	Meaning
boundary	1871	admin	raw	Segment boundary marker
instructed_toCloseEyes	1608	long	raw	Instruction to close eyes (resting block)
resting_start	322	long	raw	Resting-state block onset
9999	2502	admin	raw	End-of-recording marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `externalizing_factor`, `p_factor`, `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stim_ON`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Resting State

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 2: Publisher-defined BIDS task: Seq Learning6target

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 3: Publisher-defined BIDS task: Symbol Search

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Normal Task 1: Raw-meta event decoding and classification (event-level)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use non-admin events such as `left_target`, `right_target`, `trialResponse`, `stim_ON`.
- Kernel Notes: Exclude admin markers from supervised target sets.

Normal Task 2: Raw-meta state decoding (long-event)

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use state/block markers such as `instructed_toOpenEyes`, `instructed_toCloseEyes`, `resting_start`, `video_start`, `video_stop`.
- Kernel Notes: Keep block-label mapping stable across releases.

Normal Task 3: Super-meta response-time regression (competition-style)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: event-centered windows (task-dependent), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `response_time`
- Kernel Notes: Parse trial chains and write regression targets with unit/version metadata.

Normal Task 4: Super-meta psychopathology-factor modeling

- Task Type: regression (or discretized classification baseline)
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `p_factor` / `externalizing_factor` (schema dependent)
- Kernel Notes: Join EEG with phenotypic tables by subject key and use subject-wise splits to prevent leakage.

Data Quality Notes

- HBN is a heterogeneous multi-task battery; task availability differs across participants and files.
- Event naming and density are not perfectly uniform across releases; mapping tables should be explicit.
- Admin markers (`boundary`, `9999`, etc.) are frequent and must be filtered before model target construction.
- Super-meta tasks are sensitive to join quality (subject ID harmonization, missingness, leakage control).

- Report clearly whether each experiment uses raw meta labels or super meta labels.

References

- OpenNeuro dataset page: `https://openneuro.org/datasets/ds005508/versions/1.0.1`
- EEG2025 challenge portal: `https://eeg2025.github.io/`
- EEGUnity kernel tutorial (rich/super meta abstraction): `https://eegunity.readthedocs.io/en/v0.7.0/tutorial/How%20to%20Reading%20Rich%20Meta%20Data%20via%20Kernel.html`
- EEGUnity batch API (`epoch_by_event_hdf5`, `epoch_by_long_event_hdf5`): `https://eegunity.readthedocs.io/en/v0.7.0/eegunity.modules.batch.html`

045. openneuro_ds005509 - Healthy Brain Network (HBN) EEG - Release 5

Dataset: `openneuro_ds005509` | Year: 2025 | URL: https://openneuro.org/datasets/ds005509
Category: Complex Applied | Subjects: 330 | Files (Completed): 3326 | Channels: 129 | Sampling Rate: 500 Hz

Paradigm

The Healthy Brain Network (HBN) EEG Release 5 is a large-scale, multi-task developmental battery collected from children and adolescents. Participants completed naturalistic movie watching, eyes-open/closed resting state, sensory contrast detection, surrounding suppression, sequence learning, and symbol search tasks. The dataset aims to characterize neurodevelopmental and psychopathological profiles across a broad pediatric population.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, externalizing, phenotypic, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005509

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stim_ON`	35156	short	raw	Contrast detection stimulus onset
`fixpoint_ON`	35136	short	raw	Fixation point onset (trial start cue)
`contrastTrial_start`	18682	long	raw	Contrast detection trial block onset
`left_buttonPress`	10192	short	raw	Participant button press - left hand
`right_buttonPress`	9498	short	raw	Participant button press - right hand
`right_target`	8977	short	raw	Right-side target stimulus
`left_target`	8947	short	raw	Left-side target stimulus
`break cnt`	3296	admin	raw	Break/counter marker between blocks
`trialResponse`	3367	short	raw	Trial response event
`instructed_toOpenEyes`	1969	long	raw	Instruction to open eyes (resting block)

Event ID	Count (total)	Type	Meta Level	Meaning
boundary	1839	admin	raw	Segment boundary marker
instructed_toCloseEyes	1639	long	raw	Instruction to close eyes (resting block)
resting_start	329	long	raw	Resting-state block onset
9999	2339	admin	raw	End-of-recording marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: externalizing_factor, p_factor, response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: stim_ON
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Seq Learning8target

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 2: Publisher-defined BIDS task: Seq Learning6target

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 3: Publisher-defined BIDS task: Symbol Search

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Normal Task 1: Raw-meta event decoding and classification (event-level)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use non-admin events such as `left_target`, `right_target`, `trialResponse`, `stim_ON`.
- Kernel Notes: Exclude admin markers from supervised target sets.

Normal Task 2: Raw-meta state decoding (long-event)

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use state/block markers such as `instructed_toOpenEyes`, `instructed_toCloseEyes`, `resting_start`, `video_start`, `video_stop`.
- Kernel Notes: Keep block-label mapping stable across releases.

Normal Task 3: Super-meta response-time regression (competition-style)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: event-centered windows (task-dependent), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `response_time`
- Kernel Notes: Parse trial chains and write regression targets with unit/version metadata.

Normal Task 4: Super-meta psychopathology-factor modeling

- Task Type: regression (or discretized classification baseline)
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `p_factor` / `externalizing_factor` (schema dependent)
- Kernel Notes: Join EEG with phenotypic tables by subject key and use subject-wise splits to prevent leakage.

Data Quality Notes

- HBN is a heterogeneous multi-task battery; task availability differs across participants and files.
- Event naming and density are not perfectly uniform across releases; mapping tables should be explicit.
- Admin markers (`boundary`, `9999`, etc.) are frequent and must be filtered before model target construction.
- Super-meta tasks are sensitive to join quality (subject ID harmonization, missingness, leakage control).

- Report clearly whether each experiment uses raw meta labels or super meta labels.

References

- OpenNeuro dataset page: `https://openneuro.org/datasets/ds005509/versions/1.0.1`
- EEG2025 challenge portal: `https://eeg2025.github.io/`
- EEGUnity kernel tutorial (rich/super meta abstraction): `https://eegunity.readthedocs.io/en/v0.7.0/tutorial/How%20to%20Reading%20Rich%20Meta%20Data%20via%20Kernel.html`
- EEGUnity batch API (`epoch_by_event_hdf5`, `epoch_by_long_event_hdf5`): `https://eegunity.readthedocs.io/en/v0.7.0/eegunity.modules.batch.html`

046. openneuro_ds005510 - Healthy Brain Network (HBN) EEG - Release 6

Dataset: `openneuro_ds005510` | Year: 2025 | URL: https://openneuro.org/datasets/ds005510
Category: Complex Applied | Subjects: 3000 | Files (Completed): 1227 | Channels: 129 | Sampling Rate: 500 Hz

Paradigm

The Healthy Brain Network (HBN) EEG Release 6 is a large-scale, multi-task developmental battery collected from children and adolescents. Participants completed naturalistic movie watching, eyes-open/closed resting state, sensory contrast detection, surrounding suppression, sequence learning, and symbol search tasks. The dataset aims to characterize neurodevelopmental and psychopathological profiles across a broad pediatric population.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, externalizing, phenotypic, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005510

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stim_ON`	13706	short	raw	Contrast detection stimulus onset
`fixpoint_ON`	13696	short	raw	Fixation point onset (trial start cue)
`contrastTrial_start`	5817	long	raw	Contrast detection trial block onset
`left_buttonPress`	3743	short	raw	Participant button press - left hand
`right_buttonPress`	3249	short	raw	Participant button press - right hand
`right_target`	2796	short	raw	Right-side target stimulus
`left_target`	2793	short	raw	Left-side target stimulus
`break cnt`	1242	admin	raw	Break/counter marker between blocks
`trialResponse`	1483	short	raw	Trial response event
`instructed_toOpenEyes`	810	long	raw	Instruction to open eyes (resting block)

Event ID	Count (total)	Type	Meta Level	Meaning
instructed_toCloseEyes	676	long	raw	Instruction to close eyes (resting block)
boundary	666	admin	raw	Segment boundary marker
resting_start	135	long	raw	Resting-state block onset
9999	866	admin	raw	End-of-recording marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: externalizing_factor, p_factor, response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: stim_ON
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Despicable Me

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 2: Publisher-defined BIDS task: Seq Learning6target

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 3: Publisher-defined BIDS task: Seq Learning8target

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Normal Task 1: Raw-meta event decoding and classification (event-level)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use non-admin events such as `left_target`, `right_target`, `trialResponse`, `stim_ON`.
- Kernel Notes: Exclude admin markers from supervised target sets.

Normal Task 2: Raw-meta state decoding (long-event)

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use state/block markers such as `instructed_toOpenEyes`, `instructed_toCloseEyes`, `resting_start`, `video_start`, `video_stop`.
- Kernel Notes: Keep block-label mapping stable across releases.

Normal Task 3: Super-meta response-time regression (competition-style)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: event-centered windows (task-dependent), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `response_time`
- Kernel Notes: Parse trial chains and write regression targets with unit/version metadata.

Normal Task 4: Super-meta psychopathology-factor modeling

- Task Type: regression (or discretized classification baseline)
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `p_factor` / `externalizing_factor` (schema dependent)
- Kernel Notes: Join EEG with phenotypic tables by subject key and use subject-wise splits to prevent leakage.

Data Quality Notes

- HBN is a heterogeneous multi-task battery; task availability differs across participants and files.
- Event naming and density are not perfectly uniform across releases; mapping tables should be explicit.
- Admin markers (`boundary`, `9999`, etc.) are frequent and must be filtered before model target construction.
- Super-meta tasks are sensitive to join quality (subject ID harmonization, missingness, leakage control).

- Report clearly whether each experiment uses raw meta labels or super meta labels.

References

- OpenNeuro dataset page: `https://openneuro.org/datasets/ds005510/versions/1.0.1`
- EEG2025 challenge portal: `https://eeg2025.github.io/`
- EEGUnity kernel tutorial (rich/super meta abstraction): `https://eegunity.readthedocs.io/en/v0.7.0/tutorial/How%20to%20Reading%20Rich%20Meta%20Data%20via%20Kernel.html`
- EEGUnity batch API (`epoch_by_event_hdf5`, `epoch_by_long_event_hdf5`): `https://eegunity.readthedocs.io/en/v0.7.0/eegunity.modules.batch.html`

047. openneuro_ds005511 - Healthy Brain Network (HBN) EEG - Release 7

Dataset: `openneuro_ds005511` | Year: 2025 | URL: https://openneuro.org/datasets/ds005511
Category: Complex Applied | Subjects: 381 | Files (Completed): 3100 | Channels: 129 | Sampling Rate: 500 Hz

Paradigm

The Healthy Brain Network (HBN) EEG Release 7 is a large-scale, multi-task developmental battery collected from children and adolescents. Participants completed naturalistic movie watching, eyes-open/closed resting state, sensory contrast detection, surrounding suppression, sequence learning, and symbol search tasks. The dataset aims to characterize neurodevelopmental and psychopathological profiles across a broad pediatric population.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, externalizing, phenotypic, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005511

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stim_ON`	34708	short	raw	Contrast detection stimulus onset
`fixpoint_ON`	34688	short	raw	Fixation point onset (trial start cue)
`contrastTrial_start`	13272	long	raw	Contrast detection trial block onset
`left_buttonPress`	7530	short	raw	Participant button press - left hand
`right_buttonPress`	6992	short	raw	Participant button press - right hand
`right_target`	6384	short	raw	Right-side target stimulus
`left_target`	6361	short	raw	Left-side target stimulus
`trialResponse`	4059	short	raw	Trial response event
`break cnt`	3092	admin	raw	Break/counter marker between blocks
`instructed_toOpenEyes`	2193	long	raw	Instruction to open eyes (resting block)

Event ID	Count (total)	Type	Meta Level	Meaning
instructed_toCloseEyes	1825	long	raw	Instruction to close eyes (resting block)
boundary	1728	admin	raw	Segment boundary marker
resting_start	371	long	raw	Resting-state block onset
9999	2143	admin	raw	End-of-recording marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `externalizing_factor`, `p_factor`, `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stim_ON`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Despicable Me

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 2: Publisher-defined BIDS task: Seq Learning6target

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 3: Publisher-defined BIDS task: Seq Learning8target

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Normal Task 1: Raw-meta event decoding and classification (event-level)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use non-admin events such as `left_target`, `right_target`, `trialResponse`, `stim_ON`.
- Kernel Notes: Exclude admin markers from supervised target sets.

Normal Task 2: Raw-meta state decoding (long-event)

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use state/block markers such as `instructed_toOpenEyes`, `instructed_toCloseEyes`, `resting_start`, `video_start`, `video_stop`.
- Kernel Notes: Keep block-label mapping stable across releases.

Normal Task 3: Super-meta response-time regression (competition-style)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: event-centered windows (task-dependent), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `response_time`
- Kernel Notes: Parse trial chains and write regression targets with unit/version metadata.

Normal Task 4: Super-meta psychopathology-factor modeling

- Task Type: regression (or discretized classification baseline)
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `p_factor` / `externalizing_factor` (schema dependent)
- Kernel Notes: Join EEG with phenotypic tables by subject key and use subject-wise splits to prevent leakage.

Data Quality Notes

- HBN is a heterogeneous multi-task battery; task availability differs across participants and files.
- Event naming and density are not perfectly uniform across releases; mapping tables should be explicit.
- Admin markers (`boundary`, `9999`, etc.) are frequent and must be filtered before model target construction.
- Super-meta tasks are sensitive to join quality (subject ID harmonization, missingness, leakage control).

- Report clearly whether each experiment uses raw meta labels or super meta labels.

References

- OpenNeuro dataset page: `https://openneuro.org/datasets/ds005511/versions/1.0.1`
- EEG2025 challenge portal: `https://eeg2025.github.io/`
- EEGUnity kernel tutorial (rich/super meta abstraction): `https://eegunity.readthedocs.io/en/v0.7.0/tutorial/How%20to%20Reading%20Rich%20Meta%20Data%20via%20Kernel.html`
- EEGUnity batch API (`epoch_by_event_hdf5`, `epoch_by_long_event_hdf5`): `https://eegunity.readthedocs.io/en/v0.7.0/eegunity.modules.batch.html`

048. openneuro_ds005512 - Healthy Brain Network (HBN) EEG - Release 8

Dataset: `openneuro_ds005512` | Year: 2025 | URL: https://openneuro.org/datasets/ds005512
Category: Complex Applied | Subjects: 257 | Files (Completed): 2320 | Channels: 129 | Sampling Rate: 500 Hz

Paradigm

The Healthy Brain Network (HBN) EEG Release 8 is a large-scale, multi-task developmental battery collected from children and adolescents. Participants completed naturalistic movie watching, eyes-open/closed resting state, sensory contrast detection, surrounding suppression, sequence learning, and symbol search tasks. The dataset aims to characterize neurodevelopmental and psychopathological profiles across a broad pediatric population.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, externalizing, phenotypic, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005512

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stim_ON`	22981	short	raw	Contrast detection stimulus onset
`fixpoint_ON`	22913	short	raw	Fixation point onset (trial start cue)
`contrastTrial_start`	12963	long	raw	Contrast detection trial block onset
`left_buttonPress`	6946	short	raw	Participant button press - left hand
`right_buttonPress`	6875	short	raw	Participant button press - right hand
`right_target`	6231	short	raw	Right-side target stimulus
`left_target`	6151	short	raw	Left-side target stimulus
`trialResponse`	2318	short	raw	Trial response event
`break cnt`	2258	admin	raw	Break/counter marker between blocks
`instructed_toOpenEyes`	1326	long	raw	Instruction to open eyes (resting block)

Event ID	Count (total)	Type	Meta Level	Meaning
boundary	1237	admin	raw	Segment boundary marker
instructed_toCloseEyes	1104	long	raw	Instruction to close eyes (resting block)
resting_start	223	long	raw	Resting-state block onset
9999	1751	admin	raw	End-of-recording marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: externalizing_factor, p_factor, response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: stim_ON
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Seq Learning8target

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 2: Publisher-defined BIDS task: Seq Learning6target

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 3: Publisher-defined BIDS task: Symbol Search

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Normal Task 1: Raw-meta event decoding and classification (event-level)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use non-admin events such as `left_target`, `right_target`, `trialResponse`, `stim_ON`.
- Kernel Notes: Exclude admin markers from supervised target sets.

Normal Task 2: Raw-meta state decoding (long-event)

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use state/block markers such as `instructed_toOpenEyes`, `instructed_toCloseEyes`, `resting_start`, `video_start`, `video_stop`.
- Kernel Notes: Keep block-label mapping stable across releases.

Normal Task 3: Super-meta response-time regression (competition-style)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: event-centered windows (task-dependent), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `response_time`
- Kernel Notes: Parse trial chains and write regression targets with unit/version metadata.

Normal Task 4: Super-meta psychopathology-factor modeling

- Task Type: regression (or discretized classification baseline)
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `p_factor` / `externalizing_factor` (schema dependent)
- Kernel Notes: Join EEG with phenotypic tables by subject key and use subject-wise splits to prevent leakage.

Data Quality Notes

- HBN is a heterogeneous multi-task battery; task availability differs across participants and files.
- Event naming and density are not perfectly uniform across releases; mapping tables should be explicit.
- Admin markers (`boundary`, `9999`, etc.) are frequent and must be filtered before model target construction.
- Super-meta tasks are sensitive to join quality (subject ID harmonization, missingness, leakage control).

- Report clearly whether each experiment uses raw meta labels or super meta labels.

References

- OpenNeuro dataset page: `https://openneuro.org/datasets/ds005512/versions/1.0.1`
- EEG2025 challenge portal: `https://eeg2025.github.io/`
- EEGUnity kernel tutorial (rich/super meta abstraction): `https://eegunity.readthedocs.io/en/v0.7.0/tutorial/How%20to%20Reading%20Rich%20Meta%20Data%20via%20Kernel.html`
- EEGUnity batch API (`epoch_by_event_hdf5`, `epoch_by_long_event_hdf5`): `https://eegunity.readthedocs.io/en/v0.7.0/eegunity.modules.batch.html`

049. openneuro_ds005514 - Healthy Brain Network (HBN) EEG - Release 9

Dataset: `openneuro_ds005514` | Year: 2025 | URL: https://openneuro.org/datasets/ds005514
Category: Complex Applied | Subjects: 295 | Files (Completed): 2885 | Channels: 129 | Sampling Rate: 500 Hz

Paradigm

The Healthy Brain Network (HBN) EEG Release 9 is a large-scale, multi-task developmental battery collected from children and adolescents. Participants completed naturalistic movie watching, eyes-open/closed resting state, sensory contrast detection, surrounding suppression, sequence learning, and symbol search tasks. The dataset aims to characterize neurodevelopmental and psychopathological profiles across a broad pediatric population.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, externalizing, phenotypic, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005514

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stim_ON`	30059	short	raw	Contrast detection stimulus onset
`fixpoint_ON`	30018	short	raw	Fixation point onset (trial start cue)
`contrastTrial_start`	16449	long	raw	Contrast detection trial block onset
`left_buttonPress`	10593	short	raw	Participant button press - left hand
`right_buttonPress`	10002	short	raw	Participant button press - right hand
`right_target`	7910	short	raw	Right-side target stimulus
`left_target`	7857	short	raw	Left-side target stimulus
`break cnt`	2807	admin	raw	Break/counter marker between blocks
`trialResponse`	2569	short	raw	Trial response event
`instructed_toOpenEyes`	1591	long	raw	Instruction to open eyes (resting block)

Event ID	Count (total)	Type	Meta Level	Meaning
boundary	1554	admin	raw	Segment boundary marker
instructed_toCloseEyes	1325	long	raw	Instruction to close eyes (resting block)
resting_start	269	long	raw	Resting-state block onset
9999	2155	admin	raw	End-of-recording marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: externalizing_factor, p_factor, response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: stim_ON
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Seq Learning6target

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 2: Publisher-defined BIDS task: The Present

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 3: Publisher-defined BIDS task: Resting State

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Normal Task 1: Raw-meta event decoding and classification (event-level)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use non-admin events such as `left_target`, `right_target`, `trialResponse`, `stim_ON`.
- Kernel Notes: Exclude admin markers from supervised target sets.

Normal Task 2: Raw-meta state decoding (long-event)

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use state/block markers such as `instructed_toOpenEyes`, `instructed_toCloseEyes`, `resting_start`, `video_start`, `video_stop`.
- Kernel Notes: Keep block-label mapping stable across releases.

Normal Task 3: Super-meta response-time regression (competition-style)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: event-centered windows (task-dependent), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `response_time`
- Kernel Notes: Parse trial chains and write regression targets with unit/version metadata.

Normal Task 4: Super-meta psychopathology-factor modeling

- Task Type: regression (or discretized classification baseline)
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `p_factor` / `externalizing_factor` (schema dependent)
- Kernel Notes: Join EEG with phenotypic tables by subject key and use subject-wise splits to prevent leakage.

Data Quality Notes

- HBN is a heterogeneous multi-task battery; task availability differs across participants and files.
- Event naming and density are not perfectly uniform across releases; mapping tables should be explicit.
- Admin markers (`boundary`, `9999`, etc.) are frequent and must be filtered before model target construction.
- Super-meta tasks are sensitive to join quality (subject ID harmonization, missingness, leakage control).

- Report clearly whether each experiment uses raw meta labels or super meta labels.

References

- OpenNeuro dataset page: `https://openneuro.org/datasets/ds005514/versions/1.0.1`
- EEG2025 challenge portal: `https://eeg2025.github.io/`
- EEGUnity kernel tutorial (rich/super meta abstraction): `https://eegunity.readthedocs.io/en/v0.7.0/tutorial/How%20to%20Reading%20Rich%20Meta%20Data%20via%20Kernel.html`
- EEGUnity batch API (`epoch_by_event_hdf5`, `epoch_by_long_event_hdf5`): `https://eegunity.readthedocs.io/en/v0.7.0/eegunity.modules.batch.html`

050. openneuro_ds005515 - Healthy Brain Network (HBN) EEG - Release 10

Dataset: `openneuro_ds005515` | Year: 2025 | URL: https://openneuro.org/datasets/ds005515
Category: Complex Applied | Subjects: 533 | Files (Completed): 2515 | Channels: 129 | Sampling Rate: 500 Hz

Paradigm

The Healthy Brain Network (HBN) EEG Release 10 is a large-scale, multi-task developmental battery collected from children and adolescents. Participants completed naturalistic movie watching, eyes-open/closed resting state, sensory contrast detection, surrounding suppression, symbol search, and sequence learning tasks. The dataset aims to characterize neurodevelopmental and psychopathological profiles across a broad pediatric population.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, externalizing, phenotypic, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005515

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stim_ON`	10818	short	raw	Contrast detection stimulus onset
`fixpoint_ON`	10562	short	raw	Fixation point onset (trial start cue)
`contrastTrial_start`	5858	long	raw	Contrast detection trial block onset
`left_buttonPress`	3689	short	raw	Participant button press - left hand
`right_buttonPress`	3034	short	raw	Participant button press - right hand
`instructed_toOpenEyes`	2862	long	raw	Instruction to open eyes (resting block)
`right_target`	2812	short	raw	Right-side target stimulus
`left_target`	2545	short	raw	Left-side target stimulus
`instructed_toCloseEyes`	2365	long	raw	Instruction to close eyes (resting block)
`video_start`	1627	long	raw	Movie clip onset
`video_stop`	1610	long	raw	Movie clip offset

Event ID	Count (total)	Type	Meta Level	Meaning
`trialResponse`	1211	short	raw	Trial response event
`boundary`	1385	admin	raw	Segment boundary marker
`resting_start`	516	long	raw	Resting-state block onset
`9999`	2105	admin	raw	End-of-recording marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `externalizing_factor`, `p_factor`, `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stim_ON`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Despicable Me

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 2: Publisher-defined BIDS task: Surround Supp

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 3: Publisher-defined BIDS task: Funwith Fractals

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Normal Task 1: Raw-meta event decoding and classification (event-level)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use non-admin events such as `left_target`, `right_target`, `trialResponse`, `stim_ON`.
- Kernel Notes: Exclude admin markers from supervised target sets.

Normal Task 2: Raw-meta state decoding (long-event)

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use state/block markers such as `instructed_toOpenEyes`, `instructed_toCloseEyes`, `resting_start`, `video_start`, `video_stop`.
- Kernel Notes: Keep block-label mapping stable across releases.

Normal Task 3: Super-meta response-time regression (competition-style)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: event-centered windows (task-dependent), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `response_time`
- Kernel Notes: Parse trial chains and write regression targets with unit/version metadata.

Normal Task 4: Super-meta psychopathology-factor modeling

- Task Type: regression (or discretized classification baseline)
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `p_factor` / `externalizing_factor` (schema dependent)
- Kernel Notes: Join EEG with phenotypic tables by subject key and use subject-wise splits to prevent leakage.

Data Quality Notes

- HBN is a heterogeneous multi-task battery; task availability differs across participants and files.
- Event naming and density are not perfectly uniform across releases; mapping tables should be explicit.
- Admin markers (`boundary`, `9999`, etc.) are frequent and must be filtered before model target construction.
- Super-meta tasks are sensitive to join quality (subject ID harmonization, missingness, leakage control).

- Report clearly whether each experiment uses raw meta labels or super meta labels.

References

- OpenNeuro dataset page: `https://openneuro.org/datasets/ds005515/versions/1.0.1`
- EEG2025 challenge portal: `https://eeg2025.github.io/`
- EEGUnity kernel tutorial (rich/super meta abstraction): `https://eegunity.readthedocs.io/en/v0.7.0/tutorial/How%20to%20Reading%20Rich%20Meta%20Data%20via%20Kernel.html`
- EEGUnity batch API (`epoch_by_event_hdf5`, `epoch_by_long_event_hdf5`): `https://eegunity.readthedocs.io/en/v0.7.0/eegunity.modules.batch.html`

051. openneuro_ds005516 - Healthy Brain Network (HBN) EEG - Release 11

Dataset: `openneuro_ds005516` | Year: 2025 | URL: https://openneuro.org/datasets/ds005516
Category: Complex Applied | Subjects: 3000 | Files (Completed): 3396 | Channels: 129 | Sampling Rate: 500 Hz

Paradigm

The Healthy Brain Network (HBN) EEG Release 11 is a large-scale, multi-task developmental battery collected from children and adolescents. Participants completed naturalistic movie watching, eyes-open/closed resting state, sensory contrast detection, surrounding suppression, symbol search, and sequence learning tasks. The dataset aims to characterize neurodevelopmental and psychopathological profiles across a broad pediatric population.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, externalizing, phenotypic, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005516

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stim_ON`	37825	short	raw	Contrast detection stimulus onset
`fixpoint_ON`	37760	short	raw	Fixation point onset (trial start cue)
`contrastTrial_start`	19366	long	raw	Contrast detection trial block onset
`left_buttonPress`	14777	short	raw	Participant button press - left hand
`right_buttonPress`	13758	short	raw	Participant button press - right hand
`right_target`	9311	short	raw	Right-side target stimulus
`left_target`	9226	short	raw	Left-side target stimulus
`trialResponse`	4056	short	raw	Trial response event
`break cnt`	3196	admin	raw	Break/counter marker between blocks
`video_start`	1666	long	raw	Movie clip onset

Event ID	Count (total)	Type	Meta Level	Meaning
instructed_toOpenEyes	1644	long	raw	Instruction to open eyes (resting block)
video_stop	1541	long	raw	Movie clip offset
boundary	1462	admin	raw	Segment boundary marker
instructed_toCloseEyes	1370	long	raw	Instruction to close eyes (resting block)
resting_start	372	long	raw	Resting-state block onset
9999	3038	admin	raw	End-of-recording marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `externalizing_factor`, `p_factor`, `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stim_ON`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Despicable Me

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 2: Publisher-defined BIDS task: Surround Supp

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Primary Task 3: Publisher-defined BIDS task: Funwith Fractals

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://eeg2025.github.io/` DOI: https://doi.org/10.1101/089060

Normal Task 1: Raw-meta event decoding and classification (event-level)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use non-admin events such as `left_target`, `right_target`, `trialResponse`, `stim_ON`.
- Kernel Notes: Exclude admin markers from supervised target sets.

Normal Task 2: Raw-meta state decoding (long-event)

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use state/block markers such as `instructed_toOpenEyes`, `instructed_toCloseEyes`, `resting_start`, `video_start`, `video_stop`.
- Kernel Notes: Keep block-label mapping stable across releases.

Normal Task 3: Super-meta response-time regression (competition-style)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: event-centered windows (task-dependent), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `response_time`
- Kernel Notes: Parse trial chains and write regression targets with unit/version metadata.

Normal Task 4: Super-meta psychopathology-factor modeling

- Task Type: regression (or discretized classification baseline)
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target: `p_factor` / `externalizing_factor` (schema dependent)
- Kernel Notes: Join EEG with phenotypic tables by subject key and use subject-wise splits to prevent leakage.

Data Quality Notes

- HBN is a heterogeneous multi-task battery; task availability differs across participants and files.

- Event naming and density are not perfectly uniform across releases; mapping tables should be explicit.
- Admin markers (`boundary`, `9999`, etc.) are frequent and must be filtered before model target construction.
- Super-meta tasks are sensitive to join quality (subject ID harmonization, missingness, leakage control).
- Report clearly whether each experiment uses raw meta labels or super meta labels.

References

- OpenNeuro dataset page: `https://openneuro.org/datasets/ds005516/versions/1.0.1`
- EEG2025 challenge portal: `https://eeg2025.github.io/`
- EEGUnity kernel tutorial (rich/super meta abstraction): `https://eegunity.readthedocs.io/en/v0.7.0/tutorial/How%20to%20Reading%20Rich%20Meta%20Data%20via%20Kernel.html`
- EEGUnity batch API (`epoch_by_event_hdf5`, `epoch_by_long_event_hdf5`): `https://eegunity.readthedocs.io/en/v0.7.0/eegunity.modules.batch.html`

052. openneuro_ds005520 - Research data supporting 'EEG recording during playing MOBA game'

Dataset: `openneuro_ds005520` | Year: 2024 | URL: https://openneuro.org/datasets/ds005520
Category: Complex Applied | Subjects: 23 | Files (Completed): 23 | Channels: 60 | Sampling Rate: 256 Hz

Paradigm

Participants played a real MOBA (Multiplayer Online Battle Arena) game while 60-channel EEG was recorded alongside resting-state sessions. Trigger codes mark game events such as kills, deaths, and other in-game actions. The study investigates neural correlates of naturalistic gaming behavior.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005520

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`13`	834	long	raw	In-game event code 13 (decode from events.tsv)
`14`	520	long	raw	In-game event code 14 (decode from events.tsv)
`66`	137	long	raw	In-game event code 66 (decode from events.tsv)
`666`	89	long	raw	In-game event code 666 (decode from events.tsv)
`444`	45	long	raw	In-game event code 444 (decode from events.tsv)
`-255`	9	admin	raw	System overflow / boundary marker
`4`	9	long	raw	In-game event code 4 (decode from events.tsv)
`100008`	9	long	raw	In-game event code 100008 (decode from events.tsv)

Event ID	Count (total)	Type	Meta Level	Meaning
164	3	long	raw	In-game event code 164 (decode from events.tsv)
244	1	long	raw	In-game event code 244 (decode from events.tsv)

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Resting eye open

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005520 DOI: https://doi.org/10.18112/openneuro.ds005520.v1.0.1

Primary Task 2: Publisher-defined BIDS task: Resting eye closed

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005520 DOI: https://doi.org/10.18112/openneuro.ds005520.v1.0.1

Primary Task 3: Publisher-defined BIDS task: MOBA game

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005520 DOI: https://doi.org/10.18112/openneuro.ds005520.v1.0.1

Normal Task 1: MOBA Game Events (long_event)

- Task Type: classification

- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Numerical trigger codes require mapping from events.tsv or dataset README. Very small dataset (23 subjects); low event counts for rare codes.

Event	y	Meaning
`13`	0	Game event 13
`14`	1	Game event 14
`66`	2	Game event 66
`666`	3	Game event 666
`444`	4	Game event 444
`-255`	5	System marker
`4`	6	Game event 4
`100008`	7	Game event 100008
`164`	8	Game event 164
`244`	9	Game event 244
## Data Quality Notes		

- Event codes require decoding from dataset events.tsv or README.
- Very small dataset (23 subjects, 23 files); rare codes (164, 244, -255) have <10 occurrences total.
- Apply bandpass filter (1-40 Hz) and artifact rejection prior to epoching.

References

- Reference: `EEG recording during playing MOBA game`

053. openneuro_ds005841 - EEG Experiment measuring ERPs in VR

Dataset: openneuro_ds005841 | Year: 2025 | URL: https://openneuro.org/datasets/ds005841
Category: Complex Applied | Subjects: 48 | Files (Completed): 288 | Channels: 73 | Sampling Rate: 512 Hz

Paradigm

An investigation of event-related potentials (ERPs) during visual tasks performed within a virtual reality (VR) environment. Stimuli vary along two orthogonal dimensions: lighting (DARK vs LIGHT) and reference type (RAND = random/unpredictable vs REF = reference/predictable). The 2x2 design yields four event codes measuring visual ERP responses under prediction-error conditions.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005841

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
RAND_DARK	288	short	raw	Random (unpredictable) stimulus - dark condition
RAND_LIGHT	288	short	raw	Random (unpredictable) stimulus - light condition
REF_DARK	288	short	raw	Reference (predictable) stimulus - dark condition
REF_LIGHT	288	short	raw	Reference (predictable) stimulus - light condition

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Lumperp

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification

- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005841 DOI: https://doi.org/10.18112/openneuro.ds005841.v1.0.0

Primary Task 2: Publisher-defined BIDS task: Signalscreen

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005841 DOI: https://doi.org/10.18112/openneuro.ds005841.v1.0.0

Primary Task 3: Publisher-defined BIDS task: Regfront

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005841 DOI: https://doi.org/10.18112/openneuro.ds005841.v1.0.0

Normal Task 1: VR Stimulus Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Perfectly balanced 4-class design (288 each); primary contrast is RAND vs REF (prediction error) and DARK vs LIGHT (luminance). Count per file reflects 1 file per subject.

Event	y	Meaning
`RAND_DARK`	0	Random dark stimulus
`RAND_LIGHT`	1	Random light stimulus
`REF_DARK`	2	Reference dark stimulus
`REF_LIGHT`	3	Reference light stimulus
## Data Quality Notes		

- VR environment may introduce motion artifacts; apply ICA for artifact removal.
- 48 subjects x 6 sessions = 288 files; verify session-level consistency.
- Apply bandpass filter (1-40 Hz) and artifact rejection prior to epoching.

References

- No paper reference available

054. openneuro_ds006554 - Social Observation EEG Raw Data

Dataset: `openneuro_ds006554` | Year: 2025 | URL: https://openneuro.org/datasets/ds006554
Category: Complex Applied | Subjects: 47 | Files (Completed): 47 | Channels: 64 | Sampling Rate: 500 Hz

Paradigm

EEG was recorded while participants engaged in social observation tasks, likely involving ecological social stimuli such as videos or images of human social interactions. The rich numeric trigger coding (30 distinct codes) suggests a multi-factorial design with combinations of social condition, stimulus type, or response category. The paradigm examines neural correlates of social perception and mentalizing.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006554

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
60	47	short	raw	Social stimulus condition 60
61	47	short	raw	Social stimulus condition 61
30	47	short	raw	Social stimulus condition 30
31	47	short	raw	Social stimulus condition 31
62	47	short	raw	Social stimulus condition 62
63	47	short	raw	Social stimulus condition 63
32	47	short	raw	Social stimulus condition 32
33	47	short	raw	Social stimulus condition 33
21	47	short	raw	Social stimulus condition 21
25	47	short	raw	Social stimulus condition 25
16	47	short	raw	Social stimulus condition 16

Event ID	Count (total)	Type	Meta Level	Meaning
13	47	short	raw	Social stimulus condition 13
12	47	short	raw	Social stimulus condition 12
24	47	short	raw	Social stimulus condition 24
87	47	short	raw	Social stimulus condition 87
68	47	short	raw	Social stimulus condition 68
11	47	short	raw	Social stimulus condition 11
26	47	short	raw	Social stimulus condition 26
14	47	short	raw	Social stimulus condition 14
15	47	short	raw	Social stimulus condition 15
22	47	short	raw	Social stimulus condition 22
23	47	short	raw	Social stimulus condition 23
42	47	short	raw	Social stimulus condition 42
67	47	short	raw	Social stimulus condition 67
88	47	short	raw	Social stimulus condition 88
43	47	short	raw	Social stimulus condition 43
36	47	short	raw	Social stimulus condition 36
35	47	short	raw	Social stimulus condition 35
48	47	short	raw	Social stimulus condition 48
37	47	short	raw	Social stimulus condition 37

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Social Observation

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006554 DOI: https://doi.org/10.18112/openneuro.ds006554.v1.0.0

Normal Task 1: Social Condition Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Numeric trigger codes require decoding from events.tsv. All 30 event types appear in all 47 files (perfectly balanced). Group codes by tens-digit (10s, 20s, 30s, 60s, 80s) as likely condition groupings.

Event	y	Meaning
60	0	Social condition 60
61	1	Social condition 61
30	2	Social condition 30
31	3	Social condition 31
62	4	Social condition 62
63	5	Social condition 63
32	6	Social condition 32
33	7	Social condition 33
21	8	Social condition 21
25	9	Social condition 25
16	10	Social condition 16
13	11	Social condition 13
12	12	Social condition 12
24	13	Social condition 24
87	14	Social condition 87
68	15	Social condition 68
11	16	Social condition 11
26	17	Social condition 26
14	18	Social condition 14
15	19	Social condition 15
22	20	Social condition 22
23	21	Social condition 23

Event	y	Meaning
42	22	Social condition 42
67	23	Social condition 67
88	24	Social condition 88
43	25	Social condition 43
36	26	Social condition 36
35	27	Social condition 35
48	28	Social condition 48
37	29	Social condition 37
## Data Quality Notes		

- Numeric trigger codes need decoding from events.tsv or README.
- Large number of distinct event types (30); group codes before classification.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to epoching.

References

- Reference: `Social Observation EEG raw data`

055. openneuro_ds006839 - EEG Recordings during Sham Neurofeedback in Virtual Reality

Dataset: `openneuro_ds006839` | Year: 2025 | URL: https://openneuro.org/datasets/ds006839
Category: Complex Applied | Subjects: 144 | Files (Completed): 144 | Channels: 29 | Sampling Rate: 1000 Hz

Paradigm

Participants performed an attentional task within a virtual reality environment while receiving sham neurofeedback with positive, negative, or control feedback valences. The study investigates alpha-band modulation in response to perceived performance feedback without actual neurofeedback. Numeric trigger codes mark trial onsets and feedback conditions. The paradigm examines placebo effects of neurofeedback on neural oscillations and attention.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006839

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`190`	10264	short	raw	Positive feedback condition marker
`222`	5389	short	raw	Control (neutral) feedback condition
`126`	576	short	raw	Trial/block onset marker
`238`	431	short	raw	Negative feedback condition marker
`0`	98	admin	raw	Null/reset event

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Positive

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006839 DOI: https://doi.org/10.18112/openneuro.ds006839.v1.0.0

Primary Task 2: Publisher-defined BIDS task: Control

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006839 DOI: https://doi.org/10.18112/openneuro.ds006839.v1.0.0

Primary Task 3: Publisher-defined BIDS task: Negative

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006839 DOI: https://doi.org/10.18112/openneuro.ds006839.v1.0.0

Normal Task 1: Neurofeedback Valence Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Decode trigger codes from events.tsv. Code `0` is a null/reset event. Primary contrast is positive (190) vs negative (238) vs neutral (222) feedback valence. Classes are imbalanced (190: 10264 vs 238: 431).

Event	y	Meaning
`126`	0	Trial/block onset marker
`190`	1	Positive sham neurofeedback
`238`	2	Negative sham neurofeedback
`222`	3	Control (neutral) feedback
`0`	4	Null/reset event
## Data Quality Notes		

- Classes are imbalanced: code 190 (10264) >> 238 (431); balance before classification.
- VR environment may introduce motion artifact; check for movement-related noise.
- Numeric trigger codes require decoding from events.tsv or README.

References

- Reference: `EEG recordings during sham neurofeedback in virtual reality`

056. openneuro_ds007180 - Exo-EEG Experiment

Dataset: `openneuro_ds007180` | Year: 2026 | URL: https://openneuro.org/datasets/ds007180
Category: Complex Applied | Subjects: 25 | Files (Completed): 25 | Channels: 63 | Sampling Rate: 500 Hz

Paradigm

EEG was recorded during interaction with an exoskeleton in a gait or robotic-assisted movement task. Participants performed motor tasks with varying exoskeleton assistance levels and movement conditions. BrainVision trigger codes (S-prefixed) encode specific movement phases, assistance levels, and stimulus conditions across 30 categories.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds007180

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
S21	1885	short	raw	Exo stimulus condition S21
S22	1885	short	raw	Exo stimulus condition S22
S12	1884	short	raw	Exo stimulus condition S12
S11	1884	short	raw	Exo stimulus condition S11
S32	1876	short	raw	Exo stimulus condition S32
S31	1876	short	raw	Exo stimulus condition S31
S41	1872	short	raw	Exo stimulus condition S41
S42	1872	short	raw	Exo stimulus condition S42
S62	1872	short	raw	Exo stimulus condition S62
S61	1872	short	raw	Exo stimulus condition S61
S52	1872	short	raw	Exo stimulus condition S52
S51	1872	short	raw	Exo stimulus condition S51

Event ID	Count (total)	Type	Meta Level	Meaning
S72	1868	short	raw	Exo stimulus condition S72
S71	1868	short	raw	Exo stimulus condition S71
S81	1860	short	raw	Exo stimulus condition S81
S82	1860	short	raw	Exo stimulus condition S82
S13	1750	short	raw	Exo stimulus condition S13
S43	1750	short	raw	Exo stimulus condition S43
S73	1750	short	raw	Exo stimulus condition S73
S63	1750	short	raw	Exo stimulus condition S63
S53	1750	short	raw	Exo stimulus condition S53
S33	1750	short	raw	Exo stimulus condition S33
S23	1750	short	raw	Exo stimulus condition S23
S83	1750	short	raw	Exo stimulus condition S83
S102	1300	short	raw	Exo stimulus condition S102
S101	1300	short	raw	Exo stimulus condition S101
S92	1300	short	raw	Exo stimulus condition S92
S91	1300	short	raw	Exo stimulus condition S91
S111	1275	short	raw	Exo stimulus condition S111
S122	1275	short	raw	Exo stimulus condition S122

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: S21, S22, S12, S11, S32, S31, S41, S42
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Exo

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds007180 DOI: https://doi.org/10.18112/openneuro.ds007180.v1.0.0

Normal Task 1: Exoskeleton Condition Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 30 distinct BrainVision stimulus codes; decode from events.tsv or README for exact condition meaning. `S255` and `start` are admin markers in some files; exclude from analysis.

Event	y	Meaning
S62	0	Exo condition S62
S61	1	Exo condition S61
S52	2	Exo condition S52
S51	3	Exo condition S51
S21	4	Exo condition S21
S22	5	Exo condition S22
S12	6	Exo condition S12
S11	7	Exo condition S11
S32	8	Exo condition S32
S41	9	Exo condition S41
S42	10	Exo condition S42
S31	11	Exo condition S31
S72	12	Exo condition S72
S71	13	Exo condition S71
S81	14	Exo condition S81
S82	15	Exo condition S82
S13	16	Exo condition S13
S43	17	Exo condition S43
S73	18	Exo condition S73
S63	19	Exo condition S63
S53	20	Exo condition S53
S33	21	Exo condition S33
S23	22	Exo condition S23

Event	y	Meaning
S83	23	Exo condition S83
S102	24	Exo condition S102
S101	25	Exo condition S101
S92	26	Exo condition S92
S91	27	Exo condition S91
S111	28	Exo condition S111
S122	29	Exo condition S122
## Data Quality Notes		

- BrainVision format; 30 S-coded stimulus conditions require README decoding.
- S255 (saturation marker) and start events in some files; exclude from analysis.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to epoching.

References

- No paper reference available

Chapter 2. High-level Mental

Datasets in this chapter: 101. Deep internal cognitive/psychological processing tasks.

057. ieee_icassp_competition_2024 - IEEE ICASSP 2024 EEG Competition Dataset

Dataset: `ieee_icassp_competition_2024` | Year: 2024 | URL: https://2024.ieeeicassp.org/
Category: High-level Mental | Subjects: 48 | Files (Completed): 96 | Channels: 73 | Sampling Rate: 256 Hz

Paradigm

Forty-eight subjects participated in two EEG-based speech BCI paradigms recorded with a 72-channel BioSemi ActiveTwo cap (plus Status stim channel, total 73) at 256 Hz. Task II_II (Imagined + Inner Speech): subjects imagined speaking or performed inner speech, with two stimulus classes (trigger codes 101 and 102, ~200 events each per session). Task RBII (Real Speech + BCI): subjects produced real speech with BCI feedback under the same two class scheme. Each subject contributed one file per task type (48 x 2 = 96 BDF files). Trigger codes are stored in the BioSemi Status stim channel and extracted via `mne.find_events()`.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://2024.ieeeicassp.org/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`101`	~9600 (200/file x 48)	short	raw	Stimulus class 1 onset (imagined/inner speech condition 1)
`102`	~9600 (200/file x 48)	short	raw	Stimulus class 2 onset (imagined/inner speech condition 2)
`3`	varies	short	raw	Auxiliary trigger (task boundary or response marker)
`4`	varies	short	raw	Auxiliary trigger (task boundary or response marker)
`65536`	~144 (3/file x 48)	admin	raw	BioSemi system trigger
`65790`	~192 (4/file x 48)	admin	raw	BioSemi system trigger

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Trigger codes are stored as integer-string annotations converted from BioSemi Status stim channel values. Events 65536 and 65790 are BioSemi hardware codes and should be excluded from analysis.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Speech BCI challenge classification (inner/overt tracks)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Competition-provided trial labels for imagined/inner speech and real speech tracks.
- Evidence: IEEE ICASSP 2024 EEG BCI Grand Challenge defines supervised speech-BCI classification as the core task. Source: https://2024.ieeeicassp.org/ DOI: https://doi.org/10.1109/icasspw62465.2024.10626244

Normal Task 1: Imagined/Inner Speech Classification - Class 1 vs. Class 2 (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.1 s, tmax = 1.0 s (per stimulus onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Filter to II_II task files (filename contains `II_II`) for imagined/inner speech paradigm, or RBII files for real speech BCI. Exclude events 65536 and 65790 (BioSemi system codes). The kernel stores all Status stim channel values as string annotations.

Event	y	Meaning
`101`	0	Stimulus class 1
`102`	1	Stimulus class 2

Normal Task 2: Real Speech BCI Classification - Class 1 vs. Class 2 (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.1 s, tmax = 1.0 s (per stimulus onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Filter to RBII task files (filename contains `RBII`). Same event codes as Task 1; task type is identified from filename pattern.

Event	y	Meaning
`101`	0	Stimulus class 1
`102`	1	Stimulus class 2

Event	y	Meaning
## Data Quality Notes		

- Two distinct paradigms (II_II and RBII) stored in separate files; analyze separately.
- Trigger code semantics (exact speech content per class) require the competition documentation for full interpretation.
- 73 channels include 72 EEG + 1 Status stim channel; exclude Status before analysis.
- 4 auxiliary channels (M1, M2, NAS, plus EOG channels) are present; identify and remove non-EEG channels.
- No age or sex information available.

References

- Reference: IEEE ICASSP 2024 EEG BCI Grand Challenge. https://2024.ieeeicassp.org/

058. mendeley_sin - Mendeley Speech-in-Noise (SiN) Auditory Attention Decoding Dataset

Dataset: `mendeley_sin` | Year: 2021 | URL: https://data.mendeley.com/datasets/jyvythkz5y/2
Category: High-level Mental | Subjects: 26 | Files (Completed): 26 (Case B kernel) | Channels: 66 | Sampling Rate: 256 Hz

Paradigm

Twenty-six normal-hearing subjects (NH_subject01-NH_subject26) participated in a cocktail-party auditory attention decoding (AAD) task in which competing speech was presented with background noise at two signal-to-noise conditions. EEG was recorded from 64 channels plus 2 mastoid references (total 66 channels) at 256 Hz. Each subject's `.mat` file contains pre-epoched EEG data as a 3D array `(896, 66, 100)` - 896 time points x 66 channels x 100 trials - for each of two Speech-in-Noise conditions (condition 7 and condition 13). The Case B kernel concatenates the 100 trials for each condition into a single continuous raw signal and annotates each trial with its condition label. This dataset is identical in content and structure to `zenodo_sin` (which is a Zenodo mirror of this Mendeley original).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://data.mendeley.com/datasets/jyvythkz5y/2

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`SiN_condition_7`	~1300 (~50/subject x 26)	long	raw	Speech-in-Noise condition 7 trial (one cocktail-party condition)
`SiN_condition_13`	~1300 (~50/subject x 26)	long	raw	Speech-in-Noise condition 13 trial (second cocktail-party condition)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Case B kernel: pre-epoched `.mat` data; each file reconstructed into continuous raw by concatenating 100 trials per condition (~3.5 s each at 256 Hz = 896 samples per trial).

Tasks

Primary Task 1: Speech-in-noise auditory attention decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification] | tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Condition or attended-stream labels (released split commonly uses condition 7 vs 13).
- Evidence: Dataset documentation describes cocktail-party speech-in-noise auditory attention decoding.
Source: https://data.mendeley.com/datasets/jyvythkz5y/2 DOI: https://doi.org/10.17632/jyvythkz5y

Normal Task 1: Speech-in-Noise Condition Classification - Condition 7 vs. 13 (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 3.5 s (= 896/256 Hz; matches pre-epoched trial length), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Case B kernel reconstructs continuous raw from pre-epoched data; trial boundaries are annotated. Epoch window (3.5 s) matches the original pre-epoched length; use exactly 896/256 = 3.5 s to avoid boundary effects. sfreq is derived from the `tE` time axis in the `.mat` file (~ 256 Hz). Channel names are generic (`EEG001-EEG066`); no channel label metadata is provided.

Event	y	Meaning
`SiN_condition_7`	0	Speech-in-Noise condition 7
`SiN_condition_13`	1	Speech-in-Noise condition 13
## Data Quality Notes		

- Case B kernel: original `.mat` data is pre-epoched (not continuous); reconstruction introduces trial boundary discontinuities.
- Identical content to `zenodo_sin`; the two datasets can be treated as interchangeable.
- Channel names in the reconstructed raw are generic (`EEG001-EEG066`); actual electrode layout is 64 EEG + 2 mastoid references.
- No age or sex information available.

References

- Reference: Speech-in-Noise Auditory Attention Decoding Dataset. Mendeley Data. https://data.mendeley.com/datasets/jyvythkz5y/2. See also `zenodo_sin`.

059. openneuro_ds001784 - Effects of ON/OFF deep brain stimulation on cognitive control in treatment-resistant depression (EEG)

Dataset: `openneuro_ds001784` | Year: 2019 | URL: https://openneuro.org/datasets/ds001784
Category: High-level Mental | Subjects: N/A | Files (Completed): 38 | Channels: 65.0 | Sampling Rate: 1450.0 Hz

Paradigm

Participants with treatment-resistant depression performed a modified Multi-Source Interference Task (MSIT) integrated with emotional stimuli (IAPS images) while deep brain stimulation (DBS) was toggled ON or OFF. The study investigated how DBS of the internal capsule affects cognitive control and prefrontal cortex function. No trial-level event markers are present in the BIDS EEG files; the DBS condition (ON/OFF) is tracked as metadata rather than inline event triggers.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds001784

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
(none)	-	-	raw	No event markers detected in EEG files; DBS condition tracked via metadata

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: Cognitive control decoding in MSIT paradigm

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification] | tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation` or `misc`
- Target Definition: Interference/congruency condition and/or DBS ON/OFF effect labels

- Evidence: Dataset/paper center on MSIT cognitive control under DBS modulation. Source: https://openneuro.org/datasets/ds001784 DOI: https://doi.org/10.18112/openneuro.ds001784.v1.1.2

Primary Task 2: Publisher-defined BIDS task: Afmsit

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds001784 DOI: https://doi.org/10.18112/openneuro.ds001784.v1.1.2

Primary Task 3: Publisher-defined BIDS task: Rest

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds001784 DOI: https://doi.org/10.18112/openneuro.ds001784.v1.1.2

Normal Task 1: Resting / Continuous Segmentation (resting)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (no trial-level labels available))
- Notes: DBS ON vs OFF condition labels are subject-level metadata. If DBS condition is available from participants.tsv, it can be used as a subject-level binary label post-hoc.

Data Quality Notes

- No trial-level event markers detected in any EEG files; only continuous recordings available.
- DBS condition (ON/OFF) distinguishes experimental conditions but is not encoded as EEG events.
- High sampling rate (1450 Hz); consider downsampling for computational efficiency.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Deep Brain Stimulation of the Internal Capsule Enhances Human Cognitive Control and Prefrontal Cortex Function. Nature Communications.`

060. openneuro_ds001785 - Evidence accumulation relates to perceptual consciousness and monitoring

Dataset: `openneuro_ds001785` | Year: 2021 | URL: https://openneuro.org/datasets/ds001785
Category: High-level Mental | Subjects: 21 | Files (Completed): 54 | Channels: 71.0 | Sampling Rate: 1024.0 Hz

Paradigm

Participants performed a threshold-level vibrotactile detection task in which a weak tactile stimulus was either present (threshold condition) or absent (adapt condition). After each trial, participants provided a confidence rating. The study investigated the neural mechanisms of evidence accumulation and metacognitive monitoring using signal detection theory outcomes (hit, miss, correct rejection, false alarm) as trial labels.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, confidence, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds001785

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stim-thr`	large	short	raw	Stimulus onset - threshold vibrotactile stimulus present
`stim-adapt`	large	short	raw	Stimulus onset - adapt condition (no stimulus)
`hit`	large	short	raw	Correct detection: target present, response given
`miss`	large	short	raw	Miss: target present, no response
`cr`	large	short	raw	Correct rejection: no target, no response
`fa`	large	short	raw	False alarm: no target, but response given
`conf`	large	short	raw	Confidence rating onset
`conf-resp`	large	short	raw	Confidence rating button-press response

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
- `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
- `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, exclude from epoch target_events

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `confidence`, `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stim-thr`, `stim-adapt`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Tactile detection

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds001785 DOI: https://doi.org/10.18112/openneuro.ds001785.v1.1.1

Normal Task 1: Signal Detection Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Four-class SDT labels enable analysis of detection sensitivity and response bias. `stim-thr` and `stim-adapt` are stimulus onset markers - use as alternative epoch triggers if SDT label counts are imbalanced. Regression target: `confidence` from misc channel.

Event	y	Meaning
`hit`	0	Correct detection
`miss`	1	Missed target
`cr`	2	Correct rejection
`fa`	3	False alarm
## Data Quality Notes		

- Check class balance across hit/miss/cr/fa - miss and fa classes may be sparse for threshold stimuli.

- Confidence ratings stored in misc channel `confidence`; response times in `response_time`.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Evidence accumulation relates to perceptual consciousness and monitoring`

061. openneuro_ds002158 - Disentangling the origins of confidence in speeded perceptual judgments through multimodal imaging

Dataset: openneuro_ds002158 | Year: 2020 | URL: https://openneuro.org/datasets/ds002158
Category: High-level Mental | Subjects: 119 | Files (Completed): 119
Channels: 64 | Sampling Rate: 5000 Hz

Paradigm

Participants performed speeded perceptual judgments and subsequently reported their confidence in either their own decisions or in observed decisions made by another person. The study used multimodal neuroimaging (EEG + fMRI) to isolate the neural correlates of metacognitive confidence, distinguishing whether confidence reflects the quality of perceptual evidence or post-decisional processes. The confidence rating is stored as a misc channel for regression analysis. High sampling rate (5000 Hz) requires downsampling before epoching.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: response_time, reaction time, confidence, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002158

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
unknown	119 (files)	short	raw	Trial onset marker - actual trial type may be in events.tsv value column; used as epoch anchor

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: confidence, reaction_time, response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

Tasks

Primary Task 1: Publisher-defined BIDS task: Main

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002158 DOI: https://doi.org/10.1073/pnas.1918335117

Primary Task 2: Publisher-defined BIDS task: Rest

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002158 DOI: https://doi.org/10.1073/pnas.1918335117

Normal Task 1: Confidence Regression (regression)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: N/A (null(regression only; `unknown` serves as epoch trigger))
- Notes: `unknown` event label is the trial onset marker - use as epoch anchor. Primary task is regression of confidence rating from EEG. High sampling rate (5000 Hz); downsample before epoching.
- Regression target:`confidence`(metacognitive rating stored as misc channel)

Data Quality Notes

- Event label `unknown` is a placeholder - actual trial type information may be in events.tsv `value` or `trial_type` columns.
- Confidence ratings stored in misc channel `confidence`; reaction times in `response_time`.
- High sampling rate (5000 Hz); significant downsampling required.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Disentangling the origins of confidence in speeded perceptual judgments through multimodal imaging`

062. openneuro_ds002691 - Internal attention study

Dataset: `openneuro_ds002691` | Year: 2021 | URL: https://openneuro.org/datasets/ds002691
Category: High-level Mental | Subjects: 20 | Files (Completed): 20 | Channels: 32.0 | Sampling Rate: 250.0 Hz

Paradigm

A sustained internal attention task where participants were asked to either mentally concentrate on a target (concentrate condition) or relax (relax condition) for 15-second sustained blocks with eyes closed. Transitional cues (`getready`, `wait`) marked preparation periods between active blocks. The study investigated EEG signatures of sustained internal attention versus relaxation.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: response_time
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002691

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`concentrate`	20 (files)	long	raw	15-second sustained mental concentration block
`relax`	20 (files)	long	raw	15-second sustained relaxation block
`getready`	20 (files)	admin	raw	Preparation cue between blocks - transitional
`wait`	20 (files)	admin	raw	Wait period between blocks - transitional

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

Tasks

Primary Task 1: Publisher-defined BIDS task: Internalattention

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002691 DOI: https://doi.org/10.18112/openneuro.ds002691.v1.1.0

Normal Task 1: Attention State Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `getready` and `wait` are transitional preparation markers - excluded from target_events. 15-second sustained blocks are appropriate for long_event epoching with 2 s windows and 0.5 overlap. Misc channel `response_time` available for regression.

Event	y	Meaning
`concentrate`	0	Sustained mental concentration (15 s blocks)
`relax`	1	Sustained relaxation (15 s blocks)
## Data Quality Notes		

- Small dataset: 20 subjects, 1 file each.
- Eyes-closed recording throughout; no eye movement artifacts expected.
- The count column (20 files) reflects that every file has these events, not the per-subject trial count.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Internal attention study`

063. openneuro_ds002718 - Face processing EEG dataset for EEGLAB

Dataset: `openneuro_ds002718` | Year: 2025 | URL: https://openneuro.org/datasets/ds002718
Category: High-level Mental | Subjects: 18 | Files (Completed): 18 | Channels: 74.0 | Sampling Rate: 250.0 Hz

Paradigm

Participants viewed famous, unfamiliar, and scrambled face images and performed a subjective spatial symmetry judgment task (yes/no button press). The primary scientific question concerns the neural basis of face recognition, with ERP components (N170, N250) distinguishing famous from unfamiliar and scrambled faces. This is an EEGLAB tutorial dataset based on the SPM multimodal dataset (ds000117); events encode face category, presentation order (first vs. second), and latency of second presentation (early vs. late).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: response_time, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002718

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`famous_new`	18 (files)	short	raw	Famous face - first presentation
`unfamiliar_new`	18 (files)	short	raw	Unfamiliar face - first presentation
`scrambled_new`	18 (files)	short	raw	Scrambled face - first presentation
`famous_second_early`	18 (files)	short	raw	Famous face - second presentation (early lag)
`famous_second_late`	18 (files)	short	raw	Famous face - second presentation (late lag)
`unfamiliar_second_early`	18 (files)	short	raw	Unfamiliar face - second presentation (early lag)
`unfamiliar_second_late`	18 (files)	short	raw	Unfamiliar face - second presentation (late lag)
`scrambled_second_early`	18 (files)	short	raw	Scrambled face - second presentation (early lag)

Event ID	Count (total)	Type	Meta Level	Meaning
scrambled_second_late	18 (files)	short	raw	Scrambled face - second presentation (late lag)
right_sym	10 (files)	short	raw	Right-hand response: face judged symmetric
left_nonsym	10 (files)	short	raw	Left-hand response: face judged non-symmetric
left_sym	8 (files)	short	raw	Left-hand response: face judged symmetric
right_nonsym	8 (files)	short	raw	Right-hand response: face judged non-symmetric
boundary	18 (files)	admin	raw	Segment boundary marker - exclude

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
- long: sustained-state marker (>=2 s), for epoch_by_long_event_hdf5
- rest: resting-state segment marker, for epoch_by_segmentation_hdf5
- admin: system/boundary marker, exclude from epoch target_events

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

Tasks

Primary Task 1: Publisher-defined BIDS task: Face Recognition

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002718 DOI: https://doi.org/10.18112/openneuro.ds002718.v1.1.0

Normal Task 1: Face Category Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.

- Notes: Three-class face categorization targets the primary N170/N250 ERP question. `boundary` is a segment boundary admin marker - excluded. Response events (right_sym, left_sym, etc.) are button-press responses, not stimulus events. Regression target: `response_time`.

Event	y	Meaning
`famous_new`	0	Famous face - first presentation
`unfamiliar_new`	1	Unfamiliar face - first presentation
`scrambled_new`	2	Scrambled face - first presentation
## Data Quality Notes		

- Count column shows files-with-event (18 subjects), not individual trial counts - actual trial counts per category are much higher.
- `boundary` events are segment/epoch boundary markers - do not epoch on these.
- This is an EEGLAB tutorial dataset with well-documented preprocessing pipeline.
- Verify channel count consistency across subjects before pooling.

References

- Paper: Multimodal Integration of M/EEG and f/MRI Data in SPM12 (DOI/ref: `ds000117`)

064. openneuro_ds002721 - An EEG dataset recorded during affective music listening

Dataset: `openneuro_ds002721` | Year: 2024 | URL: https://openneuro.org/datasets/ds002721
Category: High-level Mental | Subjects: 31 | Files (Completed): 185 | Channels: 19.0 | Sampling Rate: 1000.0 Hz

Paradigm

Participants listened to 40 music clips from film scores while their EEG was recorded, to investigate the neural correlates of music-induced emotional states. Each 40-second music clip is marked at onset with a numeric trigger code (800-908 range encode specific music tracks; 32768 and 257 are likely system markers). The study is part of a series with ds002722 (calibration) and ds002723/ds002724 (BCI sessions). Emotion ratings may be available in behavioral logs.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002721

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`32768`	124 (files)	admin	raw	System/hardware trigger - likely session marker
`1092`	124 (files)	admin	raw	System code - likely hardware sync
`800-808` range	124 (files each)	long	raw	Music clip onset - specific track identifiers
`833-840` range	111-123 (files)	long	raw	Music clip onset - specific track identifiers
`902-908` range	118-123 (files)	long	raw	Music clip onset - specific track identifiers
`786`, `788`	124 (files)	long	raw	Music clip onset - specific track identifiers
`257`	120 (files)	admin	raw	System code - likely hardware marker

Event ID	Count (total)	Type	Meta Level	Meaning
33575, 33571	112-119 (files)	admin	raw	Large codes - likely system/admin markers

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
- long: sustained-state marker (>=2 s), for epoch_by_long_event_hdf5
- rest: resting-state segment marker, for epoch_by_segmentation_hdf5
- admin: system/boundary marker, exclude from epoch target_events

MISC Label Summary

- Route: misc
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Run

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002721 DOI: https://doi.org/10.1016/j.neulet.2014.05.003

Normal Task 1: Music Clip Onset Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Codes 32768, 1092, 257, 33575, 33571 are system/admin markers - excluded. Each music clip is ~40 seconds; these onset markers are short events marking start of a sustained music stimulus. Valence/arousal ratings from behavioral logs could serve as regression targets.

Event	y	Meaning
800	0	Music clip onset (track 800)
801	1	Music clip onset (track 801)
802	2	Music clip onset (track 802)

Event	y	Meaning
803	3	Music clip onset (track 803)
804	4	Music clip onset (track 804)
805	5	Music clip onset (track 805)
806	6	Music clip onset (track 806)
807	7	Music clip onset (track 807)
808	8	Music clip onset (track 808)
786	9	Music clip onset (track 786)
788	10	Music clip onset (track 788)
833	11	Music clip onset (track 833)
834	12	Music clip onset (track 834)
835	13	Music clip onset (track 835)
836	14	Music clip onset (track 836)
837	15	Music clip onset (track 837)
838	16	Music clip onset (track 838)
839	17	Music clip onset (track 839)
840	18	Music clip onset (track 840)
902	19	Music clip onset (track 902)
903	20	Music clip onset (track 903)
904	21	Music clip onset (track 904)
905	22	Music clip onset (track 905)
906	23	Music clip onset (track 906)
907	24	Music clip onset (track 907)
908	25	Music clip onset (track 908)
## Data Quality Notes		

- 30 distinct event types; codes 32768, 33575, 33571 are likely hardware sync markers.
- 19-channel EEG; low spatial resolution.
- Verify event code mapping from dataset README or paper (Scientific Data 2018).
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Neural and physiological data from participants listening to affective music (Scientific Data, 2018)`

065. openneuro_ds002722 - A dataset recorded during development of an affective brain-computer music interface: calibration session

Dataset: `openneuro_ds002722` | Year: 2020 | URL: https://openneuro.org/datasets/ds002722
Category: High-level Mental | Subjects: 19 | Files (Completed): 94 | Channels: 37.0 | Sampling Rate: 1000.0 Hz

Paradigm

Participants listened to 40-second synthetic music clips designed to induce specific affective states (varying valence and arousal) as a calibration session for an affective brain-computer music interface (BCMI). EEG and physiological signals were recorded to build a mapping from neural/physiological features to targeted emotional states. Codes 1-9 are primary music condition labels; 100-200 range codes encode specific music clip identifiers.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002722

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`9`	94 (files)	long	raw	Music condition 9 onset (high arousalx)
`4`	90 (files)	long	raw	Music condition 4 onset
`5`	89 (files)	long	raw	Music condition 5 onset
`6`	89 (files)	long	raw	Music condition 6 onset
`7`	89 (files)	long	raw	Music condition 7 onset
`2`	89 (files)	long	raw	Music condition 2 onset
`1`	60 (files)	long	raw	Music condition 1 onset
`3`	59 (files)	long	raw	Music condition 3 onset
`104-205` range	19 (files each)	long	raw	Specific music clip identifiers

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
- `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
- `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: Publisher-defined BIDS task: Run

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002722 DOI: https://doi.org/10.1145/3059005

Normal Task 1: Affective Music Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to music clip onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Codes 1-9 are primary valence/arousal condition labels. 100-200 range codes are specific music clip IDs (22 clips per subject); these could alternatively be used as 22-class stimulus labels. Decode exact mapping from Daly et al. 2018. 40-second clips are long events; epoch on onset markers.

Event	y	Meaning
1	0	Music condition 1
2	1	Music condition 2
3	2	Music condition 3
4	3	Music condition 4
5	4	Music condition 5
6	5	Music condition 6
7	6	Music condition 7
8	7	Music condition 8
9	8	Music condition 9
## Data Quality Notes		

- 30 distinct event types; codes 1-9 are the primary condition labels.
- Decode exact valence/arousal mapping for codes 1-9 from Daly et al. 2018 paper.
- 37-channel EEG includes physiological channels (ECG, GSR, etc.); identify EEG-only channels.
- Verify channel count consistency across subjects before pooling.

References

- Reference: Daly, I., Nicolaou, N., Williams, D., Hwang, F., Kirke, A., Miranda, E., Nasuto, S.J., Neural and physiological data from participants listening to affective music, Scientific Data, 2018.

066. openneuro_ds002724 - A dataset recorded during development of an affective brain-computer music interface: training sessions

Dataset: `openneuro_ds002724` | Year: 2020 | URL: https://openneuro.org/datasets/ds002724
Category: High-level Mental | Subjects: 17 | Files (Completed): 96 | Channels: 37.0 | Sampling Rate: 1000.0 Hz

Paradigm

Participants listened to 40-second synthetic music clips designed to induce specific affective states (varying valence and arousal) during the training phase of an affective brain-computer music interface. This is the training session companion to ds002722 (calibration) and ds002723 (testing). Codes 1-9 encode the nine target affective music conditions.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002724

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
6	96 (files)	long	raw	Music condition 6 onset
4	96 (files)	long	raw	Music condition 4 onset
5	96 (files)	long	raw	Music condition 5 onset
2	96 (files)	long	raw	Music condition 2 onset
1	95 (files)	long	raw	Music condition 1 onset
8	95 (files)	long	raw	Music condition 8 onset
7	95 (files)	long	raw	Music condition 7 onset
9	94 (files)	long	raw	Music condition 9 onset
3	94 (files)	long	raw	Music condition 3 onset

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
- `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
- `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: Publisher-defined BIDS task: Run

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002724 DOI: https://doi.org/10.1145/3059005

Normal Task 1: Affective Music Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to music condition onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 9 affective music conditions; decode valence/arousal mapping from Daly et al. 2018. Well-balanced: all conditions present in ~95-96 files. 40-second sustained stimuli; epoch at onset. 37-channel array includes physiological channels.

Event	y	Meaning
1	0	Music condition 1
2	1	Music condition 2
3	2	Music condition 3
4	3	Music condition 4
5	4	Music condition 5
6	5	Music condition 6
7	6	Music condition 7
8	7	Music condition 8
9	8	Music condition 9
## Data Quality Notes		

- Well-balanced event counts across all 9 conditions (94-96 files each).
- 37-channel array includes EEG plus physiological channels (ECG, GSR, etc.).
- Decode code-to-affective-state mapping from Daly et al. 2018 (Scientific Data).
- Verify channel count consistency across subjects before pooling.

References

- Reference: Daly, I., Nicolaou, N., Williams, D., Hwang, F., Kirke, A., Miranda, E., Nasuto, S.J., Neural and physiological data from participants listening to affective music, Scientific Data, 2018.

067. openneuro_ds002725 - A dataset recording joint EEG-fMRI during affective music listening

Dataset: `openneuro_ds002725` | Year: 2020 | URL: https://openneuro.org/datasets/ds002725
Category: High-level Mental | Subjects: 21 | Files (Completed): 105 | Channels: 47.0 | Sampling Rate: 1000.0 Hz

Paradigm

Participants listened to music stimuli designed to elicit emotional responses (approach/withdrawal behavior) and self-reported their felt affective states during simultaneous EEG-fMRI recording. The study investigated how EEG reflects subcortical brain activity related to emotional responses to music. Codes 1283/1285 are likely BrainVision fMRI sync codes; 34053 may be a BrainVision hardware code; 47/10/1 may be music condition/block markers.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002725

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`47`	105 (files)	long	raw	Music block marker (likely condition or trial count)
`10`	105 (files)	long	raw	Music onset marker (condition 10x)
`1`	105 (files)	long	raw	Music onset marker (condition 1x)
`1283`	105 (files)	admin	raw	BrainVision fMRI sync code - likely admin
`1285`	105 (files)	admin	raw	BrainVision fMRI sync code - likely admin
`34053`	105 (files)	admin	raw	Large BrainVision hardware code - admin
`265`	94 (files)	long	raw	Music condition marker
`768`	84 (files)	long	raw	Music condition marker

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`

- `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: Publisher-defined BIDS task: Generated Music

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002725 DOI: https://doi.org/10.1038/s41598-019-45105-2

Primary Task 2: Publisher-defined BIDS task: Classical Music

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002725 DOI: https://doi.org/10.1038/s41598-019-45105-2

Primary Task 3: Publisher-defined BIDS task: Gen Music01

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002725 DOI: https://doi.org/10.1038/s41598-019-45105-2

Normal Task 1: Affective Music State Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Codes 1283, 1285, 34053 are BrainVision system/fMRI sync markers - excluded. Decode exact music condition meaning from paper (subcortical approach/withdrawal). 47-channel EEG includes MRI-compatible electrodes. fMRI gradient artifact correction required.

Event	y	Meaning
`47`	0	Music block/condition marker 47
`10`	1	Music block/condition marker 10

Event	y	Meaning
1	2	Music block/condition marker 1
265	3	Music condition marker 265
768	4	Music condition marker 768
## Data Quality Notes		

- EEG recorded in MRI scanner; MRI gradient artifacts require dedicated removal pipeline.
- Codes 1283, 1285, 34053 are BrainVision system/fMRI codes - exclude from analysis.
- 47-channel EEG; verify channel positions and identify MRI-compatible electrode set.
- Decode music condition codes from Daly et al. / Sharman et al. paper.

References

- Reference: `Electroencephalography reflects the activity of sub-cortical brain regions during approach-withdrawal behaviour while listening to music`

068. openneuro_ds002791 - DataSet1 - Visual Object Naming EEG

Dataset: `openneuro_ds002791` | Year: 2020 | URL: https://openneuro.org/datasets/ds002791
Category: High-level Mental | Subjects: N/A | Files (Completed): 92 | Channels: 256.0 | Sampling Rate: 1000.0 Hz

Paradigm

Participants viewed and named visual objects (pictures presented as bitmap images) during high-density 256-channel EEG recording. Each event label is the filename of the presented image (e.g., GLOVE.bmp, GORILLA.bmp), corresponding to 30 distinct visual object categories. The task likely involved overt or covert naming or picture-word matching. This is DataSet1 of a paired dataset series (see also DataSet2: ds002833).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002791

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`GLOVE.bmp`	46 (files)	short	raw	Visual object onset - glove image
`FEATHER.bmp`	46 (files)	short	raw	Visual object onset - feather image
`GORILLA.bmp`	46 (files)	short	raw	Visual object onset - gorilla image
`DUSTPAN.bmp`	46 (files)	short	raw	Visual object onset - dustpan image
`COMPASS.bmp`	46 (files)	short	raw	Visual object onset - compass image
`ACCORDIO.bmp`	46 (files)	short	raw	Visual object onset - accordion image
`CAP.bmp`	46 (files)	short	raw	Visual object onset - cap image
`BOTTLE.bmp`	46 (files)	short	raw	Visual object onset - bottle image
`CROWN.bmp`	46 (files)	short	raw	Visual object onset - crown image

Event ID	Count (total)	Type	Meta Level	Meaning
ANCHOR.bmp	46 (files)	short	raw	Visual object onset - anchor image
CARROT.bmp	46 (files)	short	raw	Visual object onset - carrot image
FORK.bmp	46 (files)	short	raw	Visual object onset - fork image
DONKEY.bmp	46 (files)	short	raw	Visual object onset - donkey image
EAR.bmp	46 (files)	short	raw	Visual object onset - ear image
CLOUD.bmp	46 (files)	short	raw	Visual object onset - cloud image
ASHTRAY.bmp	46 (files)	short	raw	Visual object onset - ashtray image
frenchcr.bmp	46 (files)	short	raw	Visual object onset - french curve image
FISH.bmp	46 (files)	short	raw	Visual object onset - fish image
BIRDCAGE.bmp	46 (files)	short	raw	Visual object onset - birdcage image
ASPARAGU.bmp	46 (files)	short	raw	Visual object onset - asparagus image
DRESS.bmp	46 (files)	short	raw	Visual object onset - dress image
BEE.bmp	46 (files)	short	raw	Visual object onset - bee image
CHIMNEY.bmp	46 (files)	short	raw	Visual object onset - chimney image
BOOT.bmp	46 (files)	short	raw	Visual object onset - boot image
CUP.bmp	46 (files)	short	raw	Visual object onset - cup image
APPLE.bmp	46 (files)	short	raw	Visual object onset - apple image
CRAB.bmp	46 (files)	short	raw	Visual object onset - crab image
CAR.bmp	46 (files)	short	raw	Visual object onset - car image
ALLIGATO.bmp	46 (files)	short	raw	Visual object onset - alligator image
HAMMOCK.bmp	46 (files)	short	raw	Visual object onset - hammock image

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
- `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
- `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, exclude from epoch target_events

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Visual object naming EEG decoding

- Task Type: classification/regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation` and `misc`
- Target Definition: Stimulus image identity/semantic class from object filename events; optional naming-latency regression if RT metadata is available.
- Evidence: Dataset title and event labels indicate a visual object naming paradigm with per-object stimulus markers. Source: https://openneuro.org/datasets/ds002791 DOI: https://doi.org/10.18112/openneuro.ds002791.v1.0.0

Normal Task 1: Visual Object ERP / Regression (regression)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to image onset), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: N/A (null (30 object categories; regression primary; classification possible but 30-class))
- Notes: 30 visual object categories; for classification, consider grouping by semantic category (living/nonliving, animate/inanimate) rather than using all 30 individual object identities. High-density 256-channel EEG provides excellent spatial coverage.
- Regression target: `response_time` (naming latency from misc channel)

Data Quality Notes

- 30 distinct object images - each present in 46 files (half of 92 total files).
- High-density 256-channel EGI/HydroCell array; verify electrode positions.
- Consider semantic category grouping (animate/inanimate, living/nonliving) for classification.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `DataSet1 - Visual Object Naming EEG`

069. openneuro_ds002833 - DataSet2 - Visual Object Naming EEG (High-Density)

Dataset: `openneuro_ds002833` | Year: 2020 | URL: https://openneuro.org/datasets/ds002833
Category: High-level Mental | Subjects: N/A | Files (Completed): 80 | Channels: 257.0 | Sampling Rate: 1000.0 Hz

Paradigm

High-density 257-channel EEG recorded during a visual object naming or picture viewing task, companion to DataSet1 (ds002791). The DIN1 marker is an EGI/Geodesic system digital input trigger marking stimulus onset. The `unknown` label in 20 files indicates undecodable trigger codes for those sessions. The study likely involves the same visual object paradigm as ds002791 (30 object categories), recorded with an EGI system.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002833

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`DIN1`	60 (files)	short	raw	EGI digital input trigger - stimulus onset marker
`unknown`	20 (files)	admin	raw	Undecodable trigger code - treat as admin/uncertain

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`

- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Pictures Naming

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002833 DOI: https://doi.org/10.18112/openneuro.ds002833.v1.0.0

Normal Task 1: Stimulus-Locked ERP / Regression (regression)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to DIN1 onset), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: N/A (null (regression only; DIN1 serves as epoch anchor; `unknown` excluded))
- Notes: DIN1 is the EGI stimulus trigger; use as epoch anchor. `unknown` events are undecodable - exclude from target events. For classification, trial type information would need to come from events.tsv `trial_type` or `value` columns.
- Regression target: `response_time` from misc channel

Data Quality Notes

- 257-channel EGI HydroCell array provides very high spatial density.
- `unknown` events in 20 files may indicate corrupted trigger codes - verify from events.tsv.
- DIN1 triggers mark stimulus onsets; actual stimulus identity requires events.tsv lookup.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `DataSet2 - Visual Object Naming EEG (High-Density)`

070. openneuro_ds003004 - Imagined Emotion Study

Dataset: `openneuro_ds003004` | Year: 2022 | URL: https://openneuro.org/datasets/ds003004
Category: High-level Mental | Subjects: N/A | Files (Completed): 34 | Channels: 219.0 | Sampling Rate: 256.0 Hz

Paradigm

Participants used voice-guided imagery to induce and sustain 15 distinct emotional states, using button presses to indicate the onset and offset of each imagined emotion. Despite the paradigm involving discrete emotional state onsets (button presses), no event markers were detected in the BIDS EEG files by the locator pipeline. The button-press events may be stored in separate behavioral logs or were not encoded in the EEG trigger channel.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003004

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
(none)	-	-	raw	No event markers detected in EEG files; button-press onsets not captured in locator

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Imagined Emotion

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003004 DOI: https://doi.org/10.18112/openneuro.ds003004.v1.1.1

Normal Task 1: Resting / Continuous Segmentation (resting)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (no trial-level event markers in locator; check events.tsv directly for button-press events))
- Notes: High-density 219-channel EEG. If button-press onset/offset events are available in events.tsv, 15 emotional states could be used as multiclass labels with long_event epoching.

Data Quality Notes

- No event markers detected in EEG files by locator pipeline - verify events.tsv directly.
- High-density 219-channel array; verify electrode positions and system (likely EGI/Geodesic).
- 15 distinct emotional states if properly annotated - valuable for affective BCI research.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Imagined Emotion Study`

071. openneuro_ds003420 - HD-EEGtask (Dataset 1)

Dataset: `openneuro_ds003420` | Year: 2020 | URL: https://openneuro.org/datasets/ds003420
Category: High-level Mental | Subjects: 23 | Files (Completed): 92
Channels: 256 | Sampling Rate: 1000 Hz

Paradigm

Participants performed visual naming and spelling tasks of visually presented objects while high-density 256-channel EEG and speech onset data were recorded. This is Dataset 1 of the conneXion project. Trigger codes 0 and 1 mark stimulus events (likely object presentation onset and response/naming onset). Speech onset timing is also captured for reaction time analysis.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, reaction time, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003420

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`1`	92 (files)	short	raw	Visual object stimulus onset (or naming task trigger)
`0`	91 (files)	short	raw	Stimulus condition 0 (or response trigger)

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `reaction_time`, `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification

- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Visual naming task decoding with speech latency

- Task Type: classification/regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation` and `misc`
- Target Definition: Stimulus condition codes (0/1) and speech-onset latency targets (`reaction_time`/`response_time`) when available.
- Evidence: ConneXion Dataset 1 records visual naming tasks with trigger events and speech-onset timing for latency analysis. Source: https://openneuro.org/datasets/ds003420 DOI: https://doi.org/10.18112/openneuro.ds003420.v1.0.2

Normal Task 1: Stimulus-Locked ERP/Regression (regression)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: N/A (null(regression primary; code 1 serves as epoch anchor))
- Notes: Codes 0 and 1 require decoding from events.tsv - likely stimulus onset and response. Specific kernel decodes numeric codes and extracts speech onset timing as `response_time`. High-density 256-channel EEG provides excellent spatial coverage for naming task analysis.
- Regression target:`response_time`(speech onset / naming latency from misc channel)

Data Quality Notes

- Trigger codes 0/1 require semantic decoding from events.tsv or conneXion project documentation.
- High-density 256-channel array; significant computational overhead.
- Speech onset timing recorded - useful for naming latency regression.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `conneXion`

072. openneuro_ds003421 - HD-EEGtask (Dataset 2)

Dataset: openneuro_ds003421 | Year: 2020 | URL: https://openneuro.org/datasets/ds003421
Category: High-level Mental | Subjects: 20 | Files (Completed): 80
Channels: 257 | Sampling Rate: 1000 Hz

Paradigm

Participants completed a multi-condition experiment including resting state, visual and auditory object naming tasks, and a recognition-based working memory task, with high-density 257-channel EEG recording. This is Dataset 2 of the conneXion project (companion to ds003420). Trigger codes 0 and 1 mark stimulus onset and response events; the specific kernel provides speech onset timing as response_time for regression analysis.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003421

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
1	60 (files)	long	raw	Sustained task or stimulus condition 1 onset
0	57 (files)	long	raw	Sustained task or stimulus condition 0 onset

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: stim

- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Pictures Naming

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003421 DOI: https://doi.org/10.18112/openneuro.ds003421.v1.0.2

Normal Task 1: Task State Classification / Regression (regression + long_event)

- Task Type: regression
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: N/A (null(regression primary; codes require decoding))
- Notes: Codes 0/1 mark multi-second sustained task states (resting, naming, memory) - long_event epoching appropriate. Specific kernel decodes numeric codes and extracts speech onset as `response_time`. Not all 80 files contain both events (60 vs 57).
- Regression target:`response_time`(speech onset / naming latency from misc channel)

Data Quality Notes

- Trigger codes 0/1 require semantic decoding from events.tsv or conneXion project documentation.
- High-density 257-channel EGI array; significant computational overhead.
- Multi-condition design includes resting state, naming, and working memory - verify condition assignments.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `HD-EEGtask (Dataset 2) - conneXion project`

073. openneuro_ds003458 - EEG: Three armed bandit gambling task

Dataset: openneuro_ds003458 | Year: 2021 | URL: https://openneuro.org/datasets/ds003458
Category: High-level Mental | Subjects: 23 | Files (Completed): 23
Channels: 66 | Sampling Rate: 500 Hz

Paradigm

Participants performed a three-armed bandit gambling task with oscillating reinforcement probabilities to investigate reward processing and reward prediction error signals in EEG. Each trial includes a stimulus presentation (choice between Left, Right, or Up options), a button-press response, and outcome feedback (Win, Loss, or Null). The Fixation event marks trial onset. STATUS is a BioSemi admin marker.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003458

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus (Left`	138 (files)	short	raw	Stimulus onset with left option available
`Right`	138 (files)	short	raw	Stimulus with right option available
`Up)`	138 (files)	short	raw	Stimulus with up option available
`X`	92 (files)	short	raw	Option marker X - decode from events.tsv
`Y`	92 (files)	short	raw	Option marker Y - decode from events.tsv
`Z`	92 (files)	short	raw	Option marker Z - decode from events.tsv
`Response`	69 (files)	short	raw	Participant button-press choice response
`Fixation`	23 (files)	short	raw	Trial-onset fixation cross
`Feedback Win`	23 (files)	short	raw	Outcome: reward received

Event ID	Count (total)	Type	Meta Level	Meaning
Feedback Loss	23 (files)	short	raw	Outcome: no reward
Feedback Null	13 (files)	short	raw	Outcome: null/neutral feedback
STATUS	23 (files)	admin	raw	BioSemi system status marker - exclude

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Stimulus (Left, STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Three Armed Bandit

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003458 DOI: https://doi.org/10.18112/openneuro.ds003458.v1.1.0

Normal Task 1: Feedback Outcome Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: STATUS is a BioSemi admin marker - excluded. Event label Stimulus (Left contains a parenthesis fragment - this is a truncated label; the full label may span Stimulus (Left, Right, Up). Feedback events are the primary scientific targets for reward prediction error analysis. Response marks button-press choices.

Event	y	Meaning
Feedback Win	0	Win feedback (reward received)
Feedback Loss	1	Loss feedback (no reward)
Feedback Null	2	Null/neutral feedback

Event	y	Meaning
## Data Quality Notes		

- Event label `Stimulus (Left` is a truncated label fragment - verify full label from events.tsv.
- STATUS is BioSemi hardware marker - exclude from analysis.
- Small dataset: 23 subjects, 1 file each.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `EEG: Three armed bandit gambling task`

074. openneuro_ds003506 - EEG: Reinforcement Learning in Parkinson's

Dataset: openneuro_ds003506 | Year: 2021 | URL: https://openneuro.org/datasets/ds003506
Category: High-level Mental | Subjects: 56 | Files (Completed): 84
Channels: 67 | Sampling Rate: 500 Hz

Paradigm

This study investigates the Reward Positivity (RewP) EEG component in Parkinson's disease (PD) patients compared to matched healthy controls. Participants completed a reinforcement learning task with both volitional and instructed choices, earning rewards or receiving no-reward feedback based on their selections. The RewP, a frontocentral ERP component, scales with reward prediction error and mirrors dopamine-driven learning. The study examines whether PD diminishes this signal, given dopaminergic dysfunction in PD.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003506

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Imperative Stimulus`	84	short	raw	Cue stimulus requiring a response
`Left Button Choice`	84	short	raw	Left-hand button press response
`Right Button Choice`	84	short	raw	Right-hand button press response
`Instr`	168	short	raw	Instruction marker (Match/Choose)
`FB`	252	short	raw	Feedback stimulus (reward +1, no-reward 0)
`STATUS`	84	admin	raw	System status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Imperative Stimulus`, `STATUS`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Reinforcement Learning

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1016/j.brainres.2019.146541

Normal Task 1: Feedback type classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: FB events encode reward vs. no-reward outcomes; roughly balanced across subjects. Exclude `FB: 'Too Slow'` and `FB: 'No Match'` as they are rare and task-specific.

Event	y	Meaning
`FB: +1`	1	Reward feedback (reward)
`FB: 0`	0	No-reward feedback (no-reward)
## Data Quality Notes		

- 67 channels including VEOG and positional channels (X, Y, Z); exclude non-EEG channels before analysis.
- Two sessions per subject for some participants; verify session-level consistency.
- STATUS is a single system marker per file; exclude from epoching.

References

- Reference: `An EEG marker of reward processing is diminished in Parkinson's disease. Brain Research, 2019. DOI: 10.1016/j.brainres.2019.146541`

075. openneuro_ds003509 - EEG: Simon Conflict in Parkinson's

Dataset: openneuro_ds003509 | Year: 2021 | URL: https://openneuro.org/datasets/ds003509
Category: High-level Mental | Subjects: 56 | Files (Completed): 84
Channels: 67 | Sampling Rate: 500 Hz

Paradigm

This study investigates mid-frontal theta deficits in Parkinson's disease (PD) patients during a modified Simon reaction-time task that requires cognitive control. Participants (high-performing PD patients and matched controls) performed congruent and incongruent Simon trials where stimulus position and response direction could conflict. The task included both a training phase with reinforcement feedback and a test phase without feedback. Mid-frontal theta (4-8 Hz) activity serves as an index of cognitive control and is modulated by cortical dopamine.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003509

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Trn Stim`	1344	short	raw	Training phase stimulus (congruent/incongruent)
`Test Stim`	1008	short	raw	Test phase stimulus (congruent/incongruent)
`correct`	336	short	raw	Correct response marker
`incorrect`	334	short	raw	Incorrect response / error marker
`Trn Resp`	335	short	raw	Training phase button-press response
`Test Resp`	335	short	raw	Test phase button-press response
`FB`	168	short	raw	Feedback stimulus in training phase
`Trn No Response`	83	short	raw	Missing response in training phase

Event ID	Count (total)	Type	Meta Level	Meaning
Test No Response	54	short	raw	Missing response in test phase
STATUS	84	admin	raw	System status marker

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Trn Stim, Test Stim, STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Simon Conflict

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1016/j.neuropsychologia.2018.05.020

Normal Task 1: Correct/Incorrect Classification (binary)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Correct and incorrect counts are approximately balanced (~336 vs ~334 total). Epoch on the response marker; exclude no-response trials.

Event	y	Meaning
correct	1	Correct response
incorrect	0	Error response
## Data Quality Notes		

- 67 channels including VEOG and positional channels (X, Y, Z); exclude non-EEG channels before analysis.
- Two sessions per subject for many participants; verify session consistency.
- Trn Stim and Test Stim have detailed subtypes in events.tsv (congruent/incongruent) that can support conflict classification.

References

- Reference: Mid-frontal theta activity is diminished during cognitive control in Parkinson's disease. Neuropsychologia, 2018. DOI: 10.1016/j.neuropsychologia.2018.05.020

076. openneuro_ds003516 - EEG: Attended Speaker Paradigm (Own Name in Ignored Stream)

Dataset: `openneuro_ds003516` | Year: 2022 | URL: https://openneuro.org/datasets/ds003516
Category: High-level Mental | Subjects: 25 | Files (Completed): 25
Channels: 49 | Sampling Rate: 500 Hz

Paradigm

Participants performed a cocktail-party selective auditory attention task with two competing speakers. They listened to audio books from one speaker (attended stream) while their own name was occasionally presented in the ignored stream. This paradigm investigates the neural correlates of selective attention and the salience of self-referential stimuli (own name) in the unattended auditory channel. No discrete trial-level event markers were recorded in the EEG data.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003516

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
-	-	-	raw	No event markers detected; continuous EEG recording

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Attended Speaker Paradigm Own Name

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003516 DOI: https://doi.org/10.1038/nn.3063

Normal Task 1: Continuous EEG segmentation

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (no labels, for unsupervised or feature extraction))
- Notes: No trial-level annotations available; treat as continuous listening EEG. Suitable for neural tracking analyzes or subject-level classification using demographic labels.

Data Quality Notes

- No event markers present; cannot epoch by stimulus onset.
- Continuous EEG during selective attention task; audio stimuli timing not embedded in EEG annotations.

References

- Reference: `Bjorn Holtze (January, 2021). Own-name salience in selective auditory attention.`

077. openneuro_ds003518 - EEG: Simon Conflict with Reinforcement + Cabergoline Challenge

Dataset: `openneuro_ds003518` | Year: 2021 | URL: https://openneuro.org/datasets/ds003518
Category: High-level Mental | Subjects: 110 | Files (Completed): 137
Channels: 64 | Sampling Rate: 500 Hz

Paradigm

This study examines whether conflict acts as an implicit cost in reinforcement learning using a modified Simon task with pharmacological manipulation. Healthy participants performed a Simon conflict task across training and test phases, with a double-blind Cabergoline (dopamine D2/D3 agonist) challenge administered to examine dopaminergic modulation. The training phase included reinforcement feedback to shape behavior; the test phase probed learned conflict avoidance. Mid-frontal theta and error-related negativity are key EEG measures.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003518

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Trn Stim`	2192	short	raw	Training phase stimulus (congruent/incongruent Simon)
`Test Stim`	1644	short	raw	Test phase stimulus
`correct`	548	short	raw	Correct response outcome
`incorrect`	547	short	raw	Incorrect response / error outcome
`Trn Resp`	547	short	raw	Training phase button-press response
`Test Resp`	548	short	raw	Test phase button-press response
`FB`	274	short	raw	Feedback stimulus in training phase
`Trn No Response`	136	short	raw	Missing response in training phase
`Test No Response`	55	short	raw	Missing response in test phase

Event ID	Count (total)	Type	Meta Level	Meaning
STATUS	137	admin	raw	System status marker

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Trn Stim, Test Stim, STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Simon Conflict

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1038/ncomms6394

Normal Task 1: Correct/Incorrect Classification (binary)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Correct and incorrect counts are closely balanced (~548 vs ~547 total). Largest dataset in the Simon-conflict series; includes drug condition variation (cabergoline vs placebo) - consider as a covariate.

Event	y	Meaning
correct	1	Correct response
incorrect	0	Error response
## Data Quality Notes		

- 64-channel EEG with 110 subjects across cabergoline and placebo conditions.
- Drug condition information in participants.tsv; use as a grouping variable for stratified analysis.
- Some subjects may have two sessions; verify file-to-subject mapping.

References

- Reference: Conflict acts as an implicit cost in reinforcement learning. Nature Communications, 2014. DOI: 10.1038/ncomms6394

078. openneuro_ds003519 - EEG: Visual Working Memory + Cabergoline Challenge

Dataset: openneuro_ds003519 | Year: 2021 | URL: https://openneuro.org/datasets/ds003519
Category: High-level Mental | Subjects: 27 | Files (Completed): 54
Channels: 64 | Sampling Rate: 500 Hz

Paradigm

Participants performed a visuospatial working memory task under a double-blind Cabergoline (dopamine D2/D3 agonist) drug challenge to investigate pharmacological modulation of working memory processing. The task involved memorizing spatial locations of stimuli followed by a probe stimulus requiring a match/non-match judgment. Distractor stimuli were presented during the retention interval. The study examines individual differences in working memory capacity and dopaminergic modulation.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003519

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stim Onset`	162	short	raw	Study stimulus onset (to-be-remembered)
`Question Mark Probe`	108	short	raw	Probe stimulus requiring match judgment
`Response`	108	short	raw	Participant button-press response
`STATUS`	54	admin	raw	System status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stim Onset`, `STATUS`

- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Visual Working Memory

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.3758/s13415-018-0584-6

Normal Task 1: Stimulus presentation ERP (single class, can be used for feature extraction)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Study stimulus vs probe comparison captures encoding vs retrieval phases. Two sessions per subject (drug vs placebo); treat session as covariate.

Event	y	Meaning
`Stim Onset`	0	Memory stimulus presentation
`Question Mark Probe`	1	Probe stimulus presentation
## Data Quality Notes		

- 54 files for 27 subjects; two sessions per subject (drug/placebo crossover design).
- Drug condition information should be in participants.tsv or scans.tsv.
- Limited event types; primary utility is ERP characterization of encoding and retrieval phases.

References

- Reference: `Dopamine D2 agonist affects visuospatial working memory distractor interference depending on individual differences in baseline working memory span. Cognitive, Affective, & Behavioral Neuroscience, 2018. DOI: 10.3758/s13415-018-0584-6`

079. openneuro_ds003523 - EEG: Visual Working Memory in Acute TBI

Dataset: openneuro_ds003523 | Year: 2021 | URL: https://openneuro.org/datasets/ds003523
Category: High-level Mental | Subjects: 62 | Files (Completed): 219
Channels: 65 | Sampling Rate: 500 Hz

Paradigm

A visual working memory task with intermittent mind-wandering probes was administered longitudinally to healthy controls and patients with sub-acute mild traumatic brain injury (mTBI). Participants memorized visual stimuli during encoding, maintained them across a delay period, and responded to probe stimuli. Occasional mind-wandering probes assessed attentional state. The dataset spans multiple time points post-injury to track recovery of executive functioning, with ERP markers (P3b) serving as neurophysiological outcome measures.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003523

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stim Onset`	657	short	raw	Visual study stimulus onset
`Question Mark Probe`	434	short	raw	Working memory probe stimulus
`Response`	434	short	raw	Participant button-press response
`Mind Wandering`	406	short	raw	Mind-wandering probe response marker
`Mind Wandering Probe`	217	short	raw	Mind-wandering probe stimulus
`STATUS`	219	admin	raw	System status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stim Onset`, `STATUS`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Visual Working Memory

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1016/j.neuropsychologia.2019.107125

Normal Task 1: Stimulus type classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Longitudinal dataset; multiple sessions per subject across recovery timepoints. Mind-wandering probes can support on-task vs off-task classification with careful labeling.

Event	y	Meaning
`Stim Onset`	0	Memory stimulus presentation (encoding phase)
`Question Mark Probe`	1	Probe stimulus presentation (retrieval stage)
## Data Quality Notes		

- Longitudinal design: multiple sessions per subject at different post-injury timepoints.
- Clinical group and time-point information in participants.tsv; use as stratification variables.
- Mind Wandering Probe and Mind Wandering events can be used to classify attentional state.

References

- Reference: `ERPs predict symptomatic distress and recovery in sub-acute mild traumatic brain injury. Neuropsychologia, 2019. DOI: 10.1016/j.neuropsychologia.2019.107125`

080. openneuro_ds003602 - Childhood Sexual Abuse and Problem Drinking in Women: Neurobehavioral Mechanisms

Dataset: `openneuro_ds003602` | Year: 2022 | URL: https://openneuro.org/datasets/ds003602
Category: High-level Mental | Subjects: 234 | Files (Completed): 699
Channels: 35 | Sampling Rate: 1000 Hz

Paradigm

This study investigates neurobehavioral mechanisms linking childhood sexual abuse (CSA) history and problem drinking in women using affective picture viewing and startle paradigms. Participants viewed negative, neutral, and positive images including alcohol-related and non-alcohol-related content while EEG, EMG (startle), and physiological measures were recorded. Resting-state blocks (eyes open/closed) were also included. The study examines how trauma history modulates emotional reactivity and appetitive motivation for alcohol cues.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003602

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`NegStim`	230	short	raw	Negative picture stimulus onset
`NeuStim`	230	short	raw	Neutral picture stimulus onset
`PosStim`	230	short	raw	Positive picture stimulus onset
`NegAlcStimWithoutStartle`	230	short	raw	Negative alcohol picture (no startle probe)
`NeuAlcStimWithoutStartle`	230	short	raw	Neutral alcohol picture (no startle probe)
`PosAlcStimWithoutStartle`	230	short	raw	Positive alcohol picture (no startle probe)
`NegNonAlcStimWithoutStartle`	230	short	raw	Negative non-alcohol picture (no startle probe)
`NeuNonAlcStimWithoutStartle`	230	short	raw	Neutral non-alcohol picture (no startle probe)

Event ID	Count (total)	Type	Meta Level	Meaning
PosNonAlcStimWithoutStartle	230	short	raw	Positive non-alcohol picture (no startle probe)
NegAlcP1000/P2000/P3000	230 each	short	raw	Negative alcohol picture with startle probe at 1/2/3 s
NeuAlcP1000/P2000/P3000	230 each	short	raw	Neutral alcohol picture with startle probe at 1/2/3 s
PosAlcP1000/P2000/P3000	230 each	short	raw	Positive alcohol picture with startle probe at 1/2/3 s
NegNonAlcP1000/P2000/P3000	230 each	short	raw	Negative non-alcohol picture with startle probe
NeuNonAlcP1000/P2000/P3000	230 each	short	raw	Neutral non-alcohol picture with startle probe
PosNonAlcP1000/P2000/P3000	230 each	short	raw	Positive non-alcohol picture with startle probe
EyesOpen1 / EyesOpen2	234 each	rest	raw	Eyes-open resting-state block marker
EyesClose1 / EyesClose2	234 each	rest	raw	Eyes-closed resting-state block marker
EndOfRest	234	admin	raw	End of resting-state block
ignore	458	admin	raw	Practice/ignored trial marker

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: NegStim, NeuStim, PosStim, NegAlcStimWithoutStartle, NeuAlcStimWithoutStartle, PosAlcStimWithoutStartle, NegNonAlcStimWithoutStartle, NeuNonAlcStimWithoutStartle
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Experiment

- Task Type: classification/segmentation

- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003602 DOI: https://doi.org/10.18112/openneuro.ds003602.v1.0.1

Normal Task 1: Emotional valence classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Balanced across valence conditions (~230 per category). Large dataset (699 files). Alcohol-related vs non-alcohol-related stimulus distinction available for secondary analysis.

Event	y	Meaning
`NegStim`	0	Negative pictures
`NeuStim`	1	Neutral image
`PosStim`	2	Positive pictures
## Data Quality Notes		

- Large dataset with 30+ distinct event types; group by valence (Neg/Neu/Pos) and content (Alc/NonAlc) for tractable analysis.
- Eyes Open/Closed markers are resting-state block delimiters, not trial-level stimuli.
- `ignore` and `EndOfRest` are administrative markers; exclude from epoching.

References

- Reference: `Childhood Sexual Abuse and problem drinking in women: Neurobehavioral mechanisms. OpenNeuro ds003602.`

081. openneuro_ds003626 - Inner Speech

Dataset: `openneuro_ds003626` | Year: 2022 | URL: https://openneuro.org/datasets/ds003626
Category: High-level Mental | Subjects: 10 | Files (Completed): 30
Channels: 137 | Sampling Rate: 1024 Hz

Paradigm

Participants performed inner speech (imagined speech), pronounced speech, and visualization tasks involving four directional commands (Up, Down, Right, Left) to explore the neural correlates of the 'inner voice' phenomenon for potential BCI applications. High-density EEG (137 channels) was recorded during all three modalities of speech production/imagery. No discrete event markers were captured in the EEG trigger channel; paradigm timing is encoded externally.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003626

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
-	-	-	raw	No event markers detected; continuous EEG recording

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Inner speech command decoding

- Task Type: classification
- Epoch Method: `epoch_by_segmentation_hdf5` (or `epoch_by_event_hdf5` when external timing is restored)

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation` or `misc`
- Target Definition: Directional command classes (Up/Down/Left/Right) across inner, pronounced, and visualization modalities.
- Evidence: Dataset documentation describes inner speech command paradigms for BCI-oriented decoding. Source: https://openneuro.org/datasets/ds003626 DOI: https://doi.org/10.1086/509092

Normal Task 1: Continuous EEG segmentation

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `stim`
- Target Definition: N/A (null (no tag, needs to be restored from events.tsv or external annotation))
- Notes: No EEG trigger markers detected. If events.tsv contains trial onset annotations, epoching by event may be possible. High-density 137-channel EEG suitable for source imaging of inner speech networks. Only 10 subjects.

Data Quality Notes

- No EEG trigger markers present; trial timing must be reconstructed from events.tsv or behavioral logs.
- Small sample size (10 subjects, 30 files across 3 conditions).
- High-density 137-channel EEG; requires careful re-referencing and ICA for artifact removal.

References

- Reference: `Inner Speech Dataset. OpenNeuro ds003626.`

082. openneuro_ds003638 - EEG: Electrophysiological Biomarkers of Behavioral Dimensions from Cross-Species Paradigms

Dataset: `openneuro_ds003638` | Year: 2021 | URL: https://openneuro.org/datasets/ds003638
Category: High-level Mental | Subjects: 57 | Files (Completed): 57
Channels: 73 | Sampling Rate: 512 Hz

Paradigm

This study employs three cross-species behavioral paradigms (5-Choice Continuous Performance Task [5CCPT], Probabilistic Reward/Punishment task [PRBP], and Pavlovian-to-Instrumental Transfer [PST]) to identify electrophysiological biomarkers associated with various behavioral dimensions including attention, impulsivity, and reward sensitivity. All 57 subjects completed all three paradigms in a single session. Event markers are encoded as numeric codes with paradigm suffix (e.g., "N 5CCPT", "N PRBP", "N PST").

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003638

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`1 5CCPT-80 5CCPT`	57 each	short	raw	5-Choice CPT numeric trigger codes
`116 PRBP`, `117 PRBP`	57 each	short	raw	Probabilistic reward/punishment task trigger codes
`31 PST`, `32 PST`, `39 PST`	56-57 each	short	raw	Pavlovian-to-Instrumental Transfer task trigger codes
`STATUS`	57	admin	raw	System status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`

- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: 5CCPTPSTPRBP

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003638 DOI: https://doi.org/10.1038/nrn3241

Normal Task 1: 5CCPT stimulus classification (need to decode event meaning)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Numeric trigger codes require decoding from events.tsv or dataset README. Events with suffix 5CCPT correspond to the 5-Choice CPT; PRBP to reward/punishment; PST to Pavlovian transfer. Exact meaning of each numeric code must be verified from dataset documentation.

Event	y	Meaning
41 5CCPT	0	5CCPT correct response (need to confirm from events.tsv)
43 5CCPT	1	5CCPT commission error (need to confirm from events.tsv)
## Data Quality Notes		

- 30+ distinct numeric trigger types; decode from events.tsv before epoching.
- All three paradigms recorded in a single 57-file session; paradigm blocks need to be separated by trigger suffix.
- STATUS is a single admin marker per file; exclude from epoching.

References

- Reference: Electrophysiological biomarkers of behavioral dimensions from cross-species paradigms. OpenNeuro ds003638.

083. openneuro_ds003655 - VerbalWorkingMemory

Dataset: `openneuro_ds003655` | Year: 2023 | URL: https://openneuro.org/datasets/ds003655
Category: High-level Mental | Subjects: 26 | Files (Completed): 156
Channels: 21 | Sampling Rate: 500 Hz

Paradigm

A modified Sternberg working memory task requiring either simple retention or mental manipulation (alphabetization) of letter sequences at three load levels (5, 6, or 7 letters). Participants encoded a letter sequence, maintained it across a delay period, then responded to a probe letter. The mental manipulation condition (alphabetization) places additional executive demands on working memory compared to simple retention. EEG measures during encoding, delay, and probe phases capture load-dependent neural activity.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003655

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`encoding`	936	short	raw	Letter sequence encoding phase onset
`delay period`	936	long	raw	Working memory retention/manipulation delay period
`probe`	936	short	raw	Probe letter presentation
`start of the baseline period`	936	short	raw	Baseline period onset (pre-trial)
`start of the trial`	156	short	raw	Trial start marker
`presentation of the task instruction`	156	short	raw	Task instruction display onset
`Response`	1807	short	raw	Participant button-press response
`STATUS`	156	admin	raw	System status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`

- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `STATUS`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Verbal Working Memory

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003655 DOI: https://doi.org/10.1101/848127

Normal Task 1: Delay period analysis - keep vs operation (binary, long event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Delay periods typically last several seconds (>=2 s). Event subtypes encode both load level (5/6/7) and condition (R=Retention, M=Manipulation). Load level can be used as a regression target or ordinal label.

Event	y	Meaning
`delay period: 5R / 6R / 7R`	0	Simple retention (Retention) condition
`delay period: 5M / 6M / 7M`	1	Mental arithmetic operation (Manipulation) conditions

Normal Task 2: Detect stimulus ERP (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`

- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Probe events are short (<1 s); suitable for ERP epoching. Match/non-match accuracy from Response events can be used as trial-level correctness labels.

Event	y	Meaning
`probe: 5R / 6R / 7R`	0	Keep condition detection
`probe: 5M / 6M / 7M`	1	Operating condition detection
## Data Quality Notes		

- 21-channel EEG; limited spatial resolution but sufficient for frontal working memory analyses.
- Event subtypes encoded in trial_type column (e.g., "delay period: 5M"); parse carefully.
- Multiple sessions per subject (156 files / ~26 subjects ~ 6 files each).

References

- Reference: `VerbalWorkingMemory EEG dataset. OpenNeuro ds003655.`

084. openneuro_ds003751 - Dataset on Emotion with Naturalistic Stimuli (DENS)

Dataset: `openneuro_ds003751` | Year: 2023 | URL: https://openneuro.org/datasets/ds003751
Category: High-level Mental | Subjects: 40 | Files (Completed): 40
Channels: 132 | Sampling Rate: 250 Hz

Paradigm

Participants viewed naturalistic multimedia video clips (film excerpts, documentaries) to elicit a range of emotional states while EEG, ECG, and EMG data were simultaneously recorded. After each video clip, participants provided continuous subjective ratings of valence, arousal, dominance, liking, familiarity, and emotional category. The dataset supports multimodal emotion recognition research using naturalistic (ecologically valid) stimuli rather than standardized posed expressions.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003751

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stm`	40	long	raw	Stimulus (video clip) onset marker
`IBEG`	40	long	raw	Image/video block beginning
`base`	40	long	raw	Baseline period onset
`bend`	40	long	raw	Baseline period end
`IEND`	39	long	raw	Image/video block end
`vlnc`	40	short	raw	Valence rating event
`arsl`	40	short	raw	Arousal rating event
`dmns`	40	short	raw	Dominance rating event
`lkng`	40	short	raw	Liking rating event
`relv`	40	short	raw	Relevance rating event
`fmrt`	40	short	raw	Familiarity rating event

Event ID	Count (total)	Type	Meta Level	Meaning
cate	40	short	raw	Emotion category rating event
clic	40	short	raw	Mouse click rating response
trno	40	short	raw	Trial number marker
fixL	40	short	raw	Fixation cross onset
quiz	15	short	raw	Comprehension quiz question
qdon	14	short	raw	Quiz done marker
stop	37	admin	raw	Stop/pause marker
puse	34	admin	raw	Pause marker
rsrt	32	admin	raw	Restart marker
net	2	admin	raw	Network marker

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

MISC Label Summary

- Route: misc
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

Tasks

Primary Task 1: Publisher-defined BIDS task: Emotion

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003751 DOI: https://doi.org/10.3390/brainsci12060702

Normal Task 1: Emotion analysis during video stimulation period (long event)

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Video clips are naturalistic stimuli lasting many seconds; use long-event epoching. Continuous emotion ratings (valence, arousal) are the primary labels - treat as regression targets from behavioral data

rather than discrete y values. Only 40 subjects and files.

Event	y	Meaning
`stm`	-	Video stimulation period (continuous emotion labels from vlnc/arsl scoring)
## Data Quality Notes		

- 132-channel high-density EEG; requires careful preprocessing and ICA.
- Naturalistic stimuli with varying durations; trial lengths are not uniform.
- `stop`, `puse`, `rsrt`, `net` are administrative markers; exclude from epoching.
- Continuous emotion ratings stored separately; must be merged with EEG epochs for regression tasks.

References

- Reference: `Sudhakar Mishra and Md. Asif and Uma Shanker Tiwary and Narayanan Srinivasan (2023). Dataset on Emotion with Naturalistic Stimuli (DENS). OpenNeuro ds003751.`

085. openneuro_ds003753 - EEG: Probabilistic Learning with Affective Feedback: Exp #2

Dataset: openneuro_ds003753 | Year: 2021 | URL: https://openneuro.org/datasets/ds003753
Category: High-level Mental | Subjects: 25 | Files (Completed): 25
Channels: 66 | Sampling Rate: 500 Hz

Paradigm

A reinforcement learning task involving probabilistic affective feedback to investigate the Reward Positivity (RewP) EEG component and its sensitivity to affective stimulus properties. Participants made binary choices (left/right button) between cue stimuli (CUE) associated with positive or negative affective feedback images. Following each choice, an affective feedback image (FB) was presented. The study examines whether the RewP tracks reward value beyond mere monetary reward, responding to affective liking of feedback stimuli.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003753

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
CUE	100	short	raw	Cue stimulus requiring binary choice
FB	100	short	raw	Affective feedback stimulus (liked/disliked image)
Left Button	25	short	raw	Left button press response
Right Button	25	short	raw	Right button press response
STATUS	25	admin	raw	System status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `STATUS`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Probabilistic Selection

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003753 DOI: https://doi.org/10.18112/openneuro.ds003753.v1.1.0

Normal Task 1: Feedback type classification (requires decoding FB subtypes from events.tsv)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: FB event subtypes (liked vs disliked) must be decoded from events.tsv `trial_type` column. 25 subjects only; small dataset. Sister dataset to ds003822 (Exp #1).

Event	y	Meaning
FB (liked/rewarding)	1	Liked emotional feedback (needs to be decoded from events.tsv)
FB (disliked/non-rewarding)	0	Disliked emotional feedback (needs to be decoded from events.tsv)
## Data Quality Notes		

- Small dataset (25 subjects, 25 files).
- FB event subtype labels (affective value) must be decoded from events.tsv metadata.
- STATUS is a single admin marker per file; exclude from epoching.

References

- Reference: `The Reward Positivity is sensitive to affective liking. OpenNeuro ds003753.`

086. openneuro_ds003766 - A Resource for Assessing Dynamic Binary Choices in the Adult Brain Using EEG and Mouse-Tracking

Dataset: `openneuro_ds003766` | Year: 2024 | URL: https://openneuro.org/datasets/ds003766
Category: High-level Mental | Subjects: 31 | Files (Completed): 217
Channels: 129 | Sampling Rate: 1000 Hz

Paradigm

Participants performed dynamic decision-making tasks including food preference choices and semantic judgments while high-density EEG and continuous mouse-tracking were recorded simultaneously. The study captures the real-time neural dynamics of binary choice formation, including evidence accumulation, conflict, and response selection. Numeric trigger codes (0200-0506 series) encode stimulus, response, and condition information. Boundary markers appear in some files from EEGLAB preprocessing.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003766

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`0400`	186	short	raw	Trigger code 0400 (stimulus/task event - decode from events.tsv)
`0500`	186	short	raw	Trigger code 0500 (stimulus/task event - decode from events.tsv)
`0401-0403`	124 each	short	raw	Stimulus variant trigger codes
`0503`, `0505`, `0506`	124 each	short	raw	Response/outcome trigger codes
`0501`	95	short	raw	Trigger code 0501
`0202-0221`	93 each	short	raw	Trial-phase trigger codes (0200 series)
`0210`	93	short	raw	Trigger code 0210
`boundary`	97	admin	raw	EEGLAB boundary marker

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Foodchoice

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003766 DOI: https://doi.org/10.18112/openneuro.ds003766.v2.0.3

Primary Task 2: Publisher-defined BIDS task: Resting

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003766 DOI: https://doi.org/10.18112/openneuro.ds003766.v2.0.3

Primary Task 3: Publisher-defined BIDS task: Imagechoice

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003766 DOI: https://doi.org/10.18112/openneuro.ds003766.v2.0.3

Normal Task 1: Binary choice classification (need to decode event meaning)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition

- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Numeric trigger codes must be decoded from events.tsv. The 0200-series codes likely encode trial-phase timing; 0400/0500-series likely encode stimulus presentation. 217 files across 31 subjects (~7 sessions each). `boundary` is an EEGLAB admin marker; exclude from epoching.

Event	y	Meaning
`0400`	0	Stimulus/Option A (decode from events.tsv)
`0500`	1	Stimulus/Option B (decode from events.tsv)
## Data Quality Notes		

- 30+ distinct numeric event codes; decode mapping required from events.tsv or dataset paper.
- `boundary` events are EEGLAB data-continuity markers; must be excluded from epoching.
- High-density 129-channel EEG at 1000 Hz; high computational requirements.
- Multiple sessions per subject; verify session consistency before pooling.

References

- Reference: `Chen, K., Wang, R., Huang, J., Gao, F., Yuan, Z., Qi, Y., & Wu, H. (2022). A resource for assessing dynamic binary choices in the adult brain using EEG and mouse-tracking. Scientific Data, 9(1), 416.`

087. openneuro_ds003774 - Music Listening Genre EEG Dataset (MUSIN-G)

Dataset: `openneuro_ds003774` | Year: 2022 | URL: https://openneuro.org/datasets/ds003774
Category: High-level Mental | Subjects: 20 | Files (Completed): 260
Channels: 129 | Sampling Rate: 1000 Hz

Paradigm

Twenty participants listened to 12 music tracks spanning various genres (classical, jazz, rock, etc.) with eyes closed while high-density EEG was recorded. After each track, participants provided subjective ratings for familiarity and enjoyment. The dataset supports EEG-based music genre classification and exploration of neural correlates of music preference and familiarity. No discrete event markers were embedded in the EEG recording.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003774

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
-	-	-	raw	No event markers detected; continuous music listening EEG

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Music Listening

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003774 DOI: https://doi.org/10.18112/openneuro.ds003774.v1.0.2

Normal Task 1: Continuous EEG segmentation

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (music genre tags need to be appended after parsing from events.tsv))
- Notes: 260 files for 20 subjects (13 files each: 12 tracks + 1 baseline). Music genre labels are file-level metadata; apply as segment-level labels for genre classification. High-density 129-channel EEG at 1000 Hz.

Data Quality Notes

- No EEG trigger events present; music onset timing not embedded in EEG.
- 260 files likely correspond to individual music track recordings; genre label per file.
- High-density 129-channel EEG; high computational requirements.
- Eyes-closed listening; fewer motion artifacts but possible drowsiness.

References

- Reference: `Music Listening Genre EEG dataset (MUSIN-G). OpenNeuro ds003774.`

088. openneuro_ds003822 - EEG: Probabilistic Learning with Affective Feedback: Exp #1

Dataset: openneuro_ds003822 | Year: 2021 | URL: https://openneuro.org/datasets/ds003822
Category: High-level Mental | Subjects: 25 | Files (Completed): 25
Channels: 66 | Sampling Rate: 500 Hz

Paradigm

A reinforcement learning task using probabilistic affective feedback to investigate the Reward Positivity (RewP) EEG component and its sensitivity to subjective reward value. Participants made binary choices (left/right button) between cue stimuli (CUE) associated with liked or disliked affective feedback images. Following each choice, a feedback cue (FB cue) predicted the affective image, then the full feedback (FB type) was presented. This is Experiment 1 in a two-experiment series (see ds003753 for Exp #2).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003822

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
CUE	100	short	raw	Cue stimulus requiring binary choice
FB cue	100	short	raw	Feedback cue (predicts upcoming affective image)
FB type	200	short	raw	Full affective feedback stimulus (liked/disliked)
Response Accurate	25	short	raw	Accurate/correct response marker
Response Inaccurate	25	short	raw	Inaccurate/incorrect response marker
Left Button	25	short	raw	Left button press
Right Button	25	short	raw	Right button press
STATUS	25	admin	raw	System status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`

- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Probabilistic Selection

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003822 DOI: https://doi.org/10.18112/openneuro.ds003822.v1.1.0

Normal Task 1: Feedback type classification (binary, subtype needs to be decoded from events.tsv)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: FB type appears 200 times (2x more than CUE/FB cue = 100 each) suggesting FB type encodes both the feedback onset and a second event (e.g., image offset or rating). Decode subtype from events.tsv trial_type column. Sister dataset to ds003753 (Exp #2). 25 subjects only.

Event	y	Meaning
FB type (liked/rewarding)	1	Liked emotional feedback (needs to decode subtype from events.tsv)
FB type (disliked/non-rewarding)	0	Disliked emotional feedback
## Data Quality Notes		

- Small dataset (25 subjects, 25 files).
- FB type count (200) is 2x CUE count (100); likely encodes two event variants per trial; verify from events.tsv.
- Response Accurate and Response Inaccurate appear only 25 times each (once per file summary count); likely one per session.
- STATUS is a single admin marker per file; exclude from epoching.

References

- Reference: The Reward Positivity is sensitive to affective liking. OpenNeuro ds003822.

089. openneuro_ds003838 - EEG, pupillometry, ECG and photoplethysmography, and behavioral data in the digit span task

Dataset: `openneuro_ds003838` | Year: 2021 | URL: https://openneuro.org/datasets/ds003838/versions/1.0.0
Category: High-level Mental | Subjects: 86 | Files (Completed): 296
Channels: 2 | Sampling Rate: 1000 Hz

Paradigm

Participants performed a classic digit span working memory task involving serial recall of digit sequences of 5, 9, or 13 digits, along with a separate eyes-closed resting state condition. Each digit in a sequence was marked with an event indicating the digit position, sequence length, and whether it was later correctly recalled or forgotten. The dataset also includes ECG/PPG physiological signals recorded simultaneously with EEG.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003838/versions/1.0.0

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`memory X/05 correct`	high	short	raw	Digit X in 5-item sequence, correctly recalled
`memory X/09 correct`	high	short	raw	Digit X in 9-item sequence, correctly recalled
`memory X/13 correct`	high	short	raw	Digit X in 13-item sequence, correctly recalled
`memory X/05 error`	moderate	short	raw	Digit X in 5-item sequence, forgotten
`memory X/09 error`	moderate	short	raw	Digit X in 9-item sequence, forgotten
`memory X/13 error`	high	short	raw	Digit X in 13-item sequence, forgotten
`STATUS`	148	admin	raw	System/hardware status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`

- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Mixed

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003838/versions/1.0.0 DOI: https://doi.org/10.18112/openneuro.ds003838.v1.0.6

Normal Task 1: Correct vs Error Memory Encoding (binary)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Events encode digit position, sequence length, and recall outcome. Note this dataset contains only 2-channel ECG/PPG data (not EEG cap channels); EEG data may be in a separate modality. STATUS is an admin marker and must be excluded. Aggregate correct vs error across all sequence lengths for binary classification.

Event	y	Meaning
memory .*/correct (all correct events)	0	Digit correctly recalled later
memory .*/error (all error events)	1	Digit forgotten later
## Data Quality Notes		

- Only 2 channels (PPG + ECG) - this is a physiological signal dataset, not a scalp EEG cap
- EEG data may be stored separately; verify file naming convention
- Large number of event subtypes (~30 distinct labels); grouping by outcome (correct/error) is necessary

References

- Reference: EEG, pupillometry, ECG and photoplethysmography, and behavioral data in the digit span task

090. openneuro_ds003885 - Capacity for movement is an organisational principle in object representations: EEG data from Experiment 1

Dataset: openneuro_ds003885 | Year: 2023 | URL: https://openneuro.org/datasets/ds003885
Category: High-level Mental | Subjects: 24 | Files (Completed): 48
Channels: 127 | Sampling Rate: 250 Hz

Paradigm

Participants performed a semantic classification task (alive vs. not alive) and a passive viewing task using RSVP streams of images to investigate the neural representations of object movement and aliveness. Images spanned animate and inanimate categories with varying degrees of movement capacity, presented at ~3 Hz in RSVP. The study aimed to decode movement-related object properties from EEG representational geometry.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003885

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`E 8`	~115,200	short	raw	RSVP image onset - condition 8
`E 9`	~115,200	short	raw	RSVP image onset - condition 9
`E 1`	~38,400	short	raw	RSVP image onset - condition 1
`E 2`	~38,400	short	raw	RSVP image onset - condition 2
`E 3`	~38,400	short	raw	RSVP image onset - condition 3
`E 5`	~38,400	short	raw	RSVP image onset - condition 5
`E 4`	~960	short	raw	Block boundary or special event

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`

- admin: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Movement

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003885 DOI: https://doi.org/10.18112/openneuro.ds003885.v1.0.8

Normal Task 1: Movement Capacity Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: E 8 and E 9 together account for ~76% of all events (~4,800 each per subject vs ~1,600 for conditions 1-5). E 4 is rare (40/subject) and likely a block marker. Data from derivatives/eeglab with 128-channel cap. Consider binary alive/not-alive classification using E 8/E 9.

Event	y	Meaning
E 1	0	Object category 1
E 2	1	Object category 2
E 3	2	Object category 3
E 5	3	Object category 5
E 8	4	Object category 8 (most frequent - likely animate/movement-capable)
E 9	5	Object category 9 (most frequent - likely inanimate/no movement)
## Data Quality Notes		

- Data from derivatives/eeglab; preprocessed with EEGLAB
- 128 channels recorded but analysis.md reports 127 (one likely reference or EOG)
- Very consistent event counts across all 24 subjects

References

- Reference: Shatek, S. M., Robinson, A. K., Grootswagers, T., & Carlson, T. A. (2022). Capacity for movement is an organisational principle in object representations. NeuroImage, 261, 119517.

091. openneuro_ds003887 - Capacity for movement is an organisational principle in object representations: EEG data from Experiment 2

Dataset: `openneuro_ds003887` | Year: 2023 | URL: https://openneuro.org/datasets/ds003887
Category: High-level Mental | Subjects: 24 | Files (Completed): 48
Channels: 127 | Sampling Rate: 250 Hz

Paradigm

Participants performed time-pressured categorization of static images based on movement capacity and completed a passive viewing task using Rapid Serial Visual Presentation (RSVP). This second experiment extends Experiment 1 by testing whether movement capacity organization in neural object representations generalizes across different task contexts and classification criteria.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003887

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`E 8`	~115,200	short	raw	RSVP image onset - condition 8
`E 9`	~115,200	short	raw	RSVP image onset - condition 9
`E 1`	~38,400	short	raw	RSVP image onset - condition 1
`E 2`	~38,400	short	raw	RSVP image onset - condition 2
`E 3`	~38,400	short	raw	RSVP image onset - condition 3
`E 5`	~38,400	short	raw	RSVP image onset - condition 5
`E 4`	~960	short	raw	Block boundary or special event

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Movement

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003887 DOI: https://doi.org/10.18112/openneuro.ds003887.v1.2.3

Normal Task 1: Movement Capacity Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Identical event structure to ds003885 (Experiment 1). E 8 and E 9 are the dominant categories (~4,800 each per subject). E 4 is rare (40/subject) and likely marks block boundaries. Binary E 8 vs E 9 classification (movement-capable vs not) is the primary task.

Event	y	Meaning
`E 1`	0	Object category 1
`E 2`	1	Object category 2
`E 3`	2	Object category 3
`E 5`	3	Object category 5
`E 8`	4	Object category 8 (movement-capable / animate)
`E 9`	5	Object category 9 (no movement / inanimate)
## Data Quality Notes		

- Data from derivatives/eeglab; preprocessed with EEGLAB
- 128-channel cap, 127 usable channels after reference removal
- Consistent event counts across all 24 subjects

References

- Reference: `Capacity for movement is a major organisational principle in object representations`

092. openneuro_ds003987 - EEG: Amphetamine trials 5CCPT and Probabilistic Learning

Dataset: openneuro_ds003987 | Year: 2022 | URL: https://openneuro.org/datasets/ds003987
Category: High-level Mental | Subjects: 23 | Files (Completed): 69
Channels: 71 | Sampling Rate: 500 Hz

Paradigm

A double-blind, crossover pharmacological study investigating the effects of d-amphetamine on cognitive performance using two tasks: the 5-Choice Continuous Performance Task (5CCPT), which assesses sustained attention and impulsivity, and a Probabilistic Selection Task (PST), which measures reinforcement learning. EEG was recorded across three drug sessions (placebo, low-dose, high-dose amphetamine).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003987

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
21 5CCPT	69 files	short	raw	5CCPT event type 21 (likely stimulus onset)
22 5CCPT	69 files	short	raw	5CCPT event type 22
23 5CCPT	69 files	short	raw	5CCPT event type 23
25 5CCPT	69 files	short	raw	5CCPT event type 25
31 PST	69 files	short	raw	PST event type 31 (stimulus/feedback)
32 PST	69 files	short	raw	PST event type 32
39 PST	69 files	short	raw	PST event type 39
STATUS	69 files	admin	raw	System hardware status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`

- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: 5CCPTx PSTx Amphetamine

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003987 DOI: https://doi.org/10.1038/s41398-021-01562-w

Normal Task 1: 5CCPT Attention Task (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: STATUS must be excluded (admin event). Events are named with task suffix (5CCPT or PST). Full event decoding requires consulting the dataset README. 23 subjects x 3 sessions (drug doses) = 69 files. Drug dose can serve as a between-condition variable.

Event	y	Meaning
`21 5CCPT`	0	5CCPT condition 21 (e.g., target stimulus)
`22 5CCPT`	1	5CCPT condition 22
`23 5CCPT`	2	5CCPT condition 23
## Data Quality Notes		

- Large number of event types (30); full decoding requires dataset documentation
- Three recording sessions per subject (placebo/low/high amphetamine) - consider treating sessions independently
- STATUS is an admin marker and must be excluded

References

- Reference: `Electrophysiological biomarkers of behavioral dimensions from cross-species paradigms`

093. openneuro_ds004000 - Fribourg Ultimatum Game in Schizophrenia Study

Dataset: `openneuro_ds004000` | Year: 2022 | URL: https://openneuro.org/datasets/ds004000
Category: High-level Mental | Subjects: 43 | Files (Completed): 84
Channels: 132 | Sampling Rate: 2048 Hz

Paradigm

A social decision-making study in which patients with psychosis and healthy controls played the Ultimatum Game in both responder and proposer roles across multiple blocks. EEG was recorded while participants decided to accept or reject monetary offers from a human or computer partner, enabling investigation of fairness processing and social cognition differences in psychosis.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004000

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus/S 1`	42 files	short	raw	Stimulus onset type 1
`Stimulus/S 2`	42 files	short	raw	Stimulus onset type 2
`Stimulus/S 3`	42 files	short	raw	Stimulus onset type 3
`Stimulus/S 4`	42 files	short	raw	Stimulus onset type 4
`Stimulus/S 64`	42 files	short	raw	Stimulus onset - offer/condition marker
`Stimulus/S 96`	42 files	short	raw	Stimulus onset marker
`Stimulus/S128`	42 files	short	raw	Stimulus onset marker
`Stimulus/S160`	42 files	short	raw	Stimulus onset marker
`Stimulus/S193-S201`	28-42 files	short	raw	Condition-specific stimulus markers
`Stimulus/S225-S233`	28-42 files	short	raw	Condition-specific stimulus markers
`Stimulus/S195-S200`	33-41 files	short	raw	Condition-specific stimulus markers
`UserDefined/Blink`	84 files	admin	raw	Blink artifact marker

Event ID	Count (total)	Type	Meta Level	Meaning
`Time 0/`	84 files	admin	raw	Recording start time marker
`Response/R 1`	6 files	short	raw	Button press response
`Response/R 3`	1 file	short	raw	Button press response

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus/S 1`, `Stimulus/S 2`, `Stimulus/S 3`, `Stimulus/S 4`, `Stimulus/S 64`, `Stimulus/S 96`, `Stimulus/S128`, `Stimulus/S160`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Responder

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004000 DOI: https://doi.org/10.18112/openneuro.ds004000.v1.0.0

Normal Task 1: Ultimatum Game Stimulus Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: UserDefined/Blink and Time 0/ are admin markers and must be excluded. Full decoding of S-codes requires dataset documentation. Psychosis vs. control group label is available from participants.tsv for group-level classification.

Event	y	Meaning
`Stimulus/S 1`	0	Stimulus type 1 (e.g., fair offer)
`Stimulus/S 2`	1	Stimulus type 2
`Stimulus/S 3`	2	Stimulus type 3

Event	y	Meaning
`Stimulus/S 4`	3	Stimulus type 4 (e.g., unfair offer)
## Data Quality Notes		

- Large number of distinct Stimulus/ codes; full mapping requires consulting the study protocol
- UserDefined/Blink and Time 0/ are administrative markers to exclude
- 43 subjects x ~2 sessions = 84 files; verify session structure

References

- No paper reference available

094. openneuro_ds004015 - Attended speaker paradigm (cEEGrid data)

Dataset: openneuro_ds004015 | Year: 2022 | URL: https://openneuro.org/datasets/ds004015
Category: High-level Mental | Subjects: 36 | Files (Completed): 36
Channels: 18 | Sampling Rate: 500 Hz

Paradigm

A two-competing speaker auditory attention paradigm in which participants were instructed to selectively attend to one of two simultaneously presented audiobooks under varying spatial (same location vs. different locations) and loudness conditions. EEG was recorded using a cEEGrid around-the-ear electrode array. The dataset is intended for auditory attention decoding (AAD) research using ear-worn EEG.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004015

Event Structure

No event markers detected (no_events). This dataset contains continuous EEG recordings without trial-level annotations; stimulus delivery is continuous (audiobook streams).

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

Event ID	Count (total)	Type	Meta Level	Meaning
no_events	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Publisher-defined BIDS task: Attended Speaker Paradigmc EEGrid Attention

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]

- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004015 DOI: https://doi.org/10.1038/nn.3063

Normal Task 1: Auditory Attention Decoding - Continuous Segmentation

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: None (attended speaker label from task metadata)
- Notes: cEEGrid only provides 18 channels around the ear; limited spatial coverage compared to standard scalp EEG. Auditory attention decoding typically requires aligning EEG segments with envelope of the attended speech stream. No discrete event markers; stimulus is continuous.

Data Quality Notes

- Only 18 around-the-ear channels (cEEGrid) - very limited spatial coverage
- No discrete event markers; continuous stimulus paradigm
- Attended speaker condition metadata needed from external files for supervised learning

References

- Reference: `Holtze et al. (2021)`

095. openneuro_ds004017 - Embodied Learning for Literacy EEG

Dataset: `openneuro_ds004017` | Year: 2023 | URL: https://openneuro.org/datasets/ds004017
Category: High-level Mental | Subjects: 21 | Files (Completed): 126
Channels: 65 | Sampling Rate: 2048 Hz

Paradigm

A pre-post intervention study assessing literacy and orthographic processing in children through two tasks: a two-alternative forced choice letter discrimination task (b vs. d confusion) and a visual search task. EEG was recorded across multiple sessions to evaluate the neural effects of an embodied learning intervention on letter processing. Trigger codes 10/20 and 100/200 likely encode the two letter types or correct/incorrect responses.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004017

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`100.0`	63 files	short	raw	Stimulus onset - letter type B or condition 100
`200.0`	63 files	short	raw	Stimulus onset - letter type D or condition 200
`20.0`	61 files	short	raw	Stimulus onset - response or sub-condition 20
`10.0`	61 files	short	raw	Stimulus onset - response or sub-condition 10

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`

- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Letter discrimination (b vs d) under embodied literacy intervention

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Stimulus condition mapping for letter discrimination (e.g., b vs d), optionally modeled with pre/post intervention session factor.
- Evidence: Study description centers on literacy-related letter processing and intervention effects. Source: https://openneuro.org/datasets/ds004017 DOI: https://doi.org/10.18112/openneuro.ds004017.v1.0.3

Normal Task 1: Letter Discrimination (b vs d) (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 21 subjects x 6 sessions = 126 files. Codes 10.0/20.0 may indicate sub-conditions or response events - verify against dataset README. Pre-post intervention design allows longitudinal analysis.

Event	y	Meaning
`100.0`	0	Letter/condition type 100 (e.g., letter b)
`200.0`	1	Letter/condition type 200 (e.g., letter d)
## Data Quality Notes		

- Numerical trigger codes; full decoding requires dataset documentation
- 21 subjects x 6 sessions - session-level structure must be considered
- High sampling rate (2048 Hz); consider downsampling for efficiency

References

- Reference: `Embodied Learning for Literacy EEG`

096. openneuro_ds004019 - Effect of obesity on arithmetic processing in preteens with high and low math skills. An event-related potentials study

Dataset: `openneuro_ds004019` | Year: 2022 | URL: https://openneuro.org/datasets/ds004019
Category: High-level Mental | Subjects: 62 | Files (Completed): 62
Channels: 132 | Sampling Rate: 500 Hz

Paradigm

Obese and non-obese preteens (ages 9-10) performed a delayed-verification arithmetic task to evaluate the effects of weight status and math skill level on arithmetic processing. Participants viewed an arithmetic problem (prob), then a delay (bgin), then a verification digit (face) and responded (resp). Trigger codes 0 and 1 encode response correctness (0=incorrect, 1=correct). The study uses ERPs to investigate neural correlates of arithmetic cognition in the context of childhood obesity.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004019

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`bgin`	~14,880	short	raw	Trial beginning / delay period onset
`prob`	~14,880	short	raw	Arithmetic problem onset
`ch++`	~14,880	short	raw	Choice/comparison stimulus onset
`face`	~14,880	short	raw	Verification digit (face stimulus) onset
`resp`	~14,600	short	raw	Participant button-press response
`1`	~14,364	short	raw	Correct response (1=correct)
`0`	~6,156	short	raw	Incorrect response (0=incorrect)
`sync`	~310	admin	raw	Hardware sync pulse
`CELL`	~248	admin	raw	Cell/block marker
`SESS`	62	admin	raw	Session start marker

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Math task

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004019 DOI: https://doi.org/10.18112/openneuro.ds004019.v1.0.0

Normal Task 1: Correct vs Incorrect Arithmetic (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: sync, CELL, SESS are admin markers and must be excluded. The `1` and `0` events mark response correctness concurrent with `resp`. Class imbalance (~70% correct across subjects) should be addressed. Obesity group label is in participants.tsv.

Event	y	Meaning
`1`	1	Correct arithmetic response
`0`	0	Incorrect arithmetic response
## Data Quality Notes		

- 132-channel EGI cap (E1-E128 + ECG/Respiration/SP channels); remove non-EEG channels before analysis
- sync/CELL/SESS are admin markers to exclude
- Class imbalance: ~70% correct trials - apply undersampling or weighted loss

References

- Reference: `Effect of obesity on arithmetic processing in preteens with high and low math skills. An event-related potentials study.`

097. openneuro_ds004040 - Trance channeling EEG study

Dataset: openneuro_ds004040 | Year: 2022 | URL: https://openneuro.org/datasets/ds004040
Category: High-level Mental | Subjects: 13 | Files (Completed): 26
Channels: 64 | Sampling Rate: 512 Hz

Paradigm

Participants who are experienced trance channelers performed alternating 5-minute blocks of trance channeling (a mediumistic altered state of consciousness) and matched resting state conditions across two separate sessions. The study investigates neural correlates of voluntarily induced altered states of consciousness compared to wakeful rest. Labels for trance vs. rest blocks must be derived from the session/task structure rather than discrete event markers.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004040

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
STATUS	26 files	admin	raw	System hardware status marker - not suitable for epoching

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Trance

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004040 DOI: https://doi.org/10.18112/openneuro.ds004040.v1.0.0

Normal Task 1: Trance vs. Resting State (binary, segmentation)

- Task Type: segmentation
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: None (condition label from task/session structure)
- Notes: STATUS is an admin marker and must be excluded. Block-level labels (trance vs. rest) should come from the BIDS task name or session metadata. 13 subjects x 2 sessions = 26 files. Small sample size; suitable for within-subject analysis.

Data Quality Notes

- Only STATUS admin marker present; no task-level event markers
- Small sample (13 specialized subjects who practice trance channeling)
- Two sessions per subject - verify session labeling in BIDS structure

References

- Reference: `Trance channeling EEG study`

098. openneuro_ds004067 - Moral conviction and metacognitive ability shape multiple stages of information processing

Dataset: `openneuro_ds004067` | Year: 2022 | URL: https://openneuro.org/datasets/ds004067
Category: High-level Mental | Subjects: 80 | Files (Completed): 83
Channels: 63 | Sampling Rate: 2000 Hz

Paradigm

Participants evaluated their support for sociopolitical protest photographs following social influence cues from a fictitious community to assess how moral conviction and metacognitive ability modulate information processing. EEG was recorded while participants viewed protest photos (supporting or opposing social movements), received social feedback (high/low/medium agreement), and provided attitude ratings. The study examined how moral convictions and metacognitive ability shape early and late stages of social information processing.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004067

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus/PhotoSupport`	~7,290	short	raw	Photo onset - support-framing protest image
`Stimulus/PhotoOppose`	~7,290	short	raw	Photo onset - oppose-framing protest image
`Stimulus/SocLow`	~4,860	short	raw	Social influence cue - low agreement
`Stimulus/SocHigh`	~4,860	short	raw	Social influence cue - high agreement
`Stimulus/SocMed`	~4,860	short	raw	Social influence cue - medium agreement
`Stimulus/Moral_Support`	~5,688	short	raw	Moral attitude cue - support
`Stimulus/Moral_Oppose`	~5,688	short	raw	Moral attitude cue - oppose
`Stimulus/Nonmoral_Oppose`	~5,400	short	raw	Non-moral attitude cue - oppose

Event ID	Count (total)	Type	Meta Level	Meaning
Stimulus/Nonmoral_Neutral	~4,968	short	raw	Non-moral attitude cue - neutral
Stimulus/Nonmoral_Support	~4,560	short	raw	Non-moral attitude cue - support
Stimulus/Resp1-Resp5	variable	short	raw	Participant rating response (1-5 scale)
Stimulus/ProtestStart	~80	admin	raw	Block start marker
Stimulus/ProtestEnd	~80	admin	raw	Block end marker
Stimulus/RestStart	~79	rest	raw	Resting block start
Stimulus/RestEnd	~79	rest	raw	Resting block end
Stimulus/ClipTaskStart	~79	admin	raw	Clip task start
Stimulus/ClipTaskEnd	~79	admin	raw	Clip task end
Stimulus/Social5/6start-end	~79	admin	raw	Social clip block markers
Stimulus/Heroic6/7start-end	~79	admin	raw	Heroic clip block markers
Stimulus/S 2	~79	admin	raw	System/sync marker

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus/PhotoSupport`, `Stimulus/PhotoOppose`, `Stimulus/SocLow`, `Stimulus/SocHigh`, `Stimulus/SocMed`, `Stimulus/Moral_Support`, `Stimulus/Moral_Oppose`, `Stimulus/Nonmoral_Oppose`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Sociopolitical Judgment Task

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)

- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004067 DOI: https://doi.org/10.17605/OSF.IO/8KPEF

Normal Task 1: Support vs Oppose Photo Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: ProtestStart/End, ClipTaskStart/End, Socialstart/end, Heroicstart/end, RestStart/End, and S 2 are all admin/structural markers to exclude. Resp1-Resp5 encode 5-point rating responses and can be used for regression. Social cues (SocLow/Med/High) can be used for a 3-class social influence task.

Event	y	Meaning
`Stimulus/PhotoSupport`	0	Support-framing sociopolitical protest photo
`Stimulus/PhotoOppose`	1	Oppose-framing sociopolitical protest photo
## Data Quality Notes		

- Large number of event types; careful exclusion of admin markers required
- RestStart/RestEnd delimit resting-state blocks within the recording
- High sampling rate (2000 Hz); consider downsampling to 500-1000 Hz

References

- Reference: `Moral conviction and metacognitive ability shape multiple stages of information processing`

099. openneuro_ds004117 - Sternberg Working Memory

Dataset: openneuro_ds004117 | Year: 2022 | URL: https://openneuro.org/datasets/ds004117
Category: High-level Mental | Subjects: 23 | Files (Completed): 85
Channels: 71 | Sampling Rate: 250 Hz

Paradigm

A modified Sternberg working memory task in which participants selectively memorized sets of 3, 5, or 7 target letters (marked with lowercase 'g' prefix, e.g., gH) while ignoring identical-font distractor letters. After a retention period, a probe letter was presented and participants indicated with auditory feedback whether it was in the memorized set. The study investigates frontal midline EEG dynamics (particularly theta oscillations) during working memory maintenance.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004117

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
WM	85 files	short	raw	Working memory trial onset / encoding phase
nonWM	85 files	short	raw	Non-working-memory (distractor) trial
gA-gZ (prefixed letters)	85 files	short	raw	Working memory target letter onset (to be memorized)
A-Z (plain letters)	85 files	short	raw	Distractor letter onset (to be ignored)
255	85 files	admin	raw	System trigger (likely BrainVision marker 255 = all bits)

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Working Memory

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004117 DOI: https://doi.org/10.1016/j.neuroimage.2005.04.014

Normal Task 1: WM vs Non-WM Letter Encoding (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 255 is an admin marker and must be excluded. Individual letter events (A-Z, gA-gZ) mark specific letter presentations and can be used for fine-grained analysis. 23 subjects x ~3.7 sessions on average = 85 files.

Event	y	Meaning
`WM`	1	Working memory encoding trial
`nonWM`	0	Non-working-memory (distractor) trial
## Data Quality Notes		

- Trigger 255 (all-bits-high) is a system artifact and must be excluded
- Individual letter events provide fine-grained trial structure for ERP analysis
- 23 subjects x multiple sessions - verify session structure before pooling

References

- Reference: `Onton, J., Delorme, A. and Makeig, S., 2005. Frontal midline EEG dynamics during working memory. Neuroimage, 27(2), pp.341-356.`

100. openneuro_ds004147 - Average Task Value

Dataset: openneuro_ds004147 | Year: 2024 | URL: https://openneuro.org/datasets/ds004147
Category: High-level Mental | Subjects: 12 | Files (Completed): 12
Channels: 31 | Sampling Rate: 1000 Hz

Paradigm

A reinforcement learning task requiring participants to learn cue-response mappings for colored shapes under varying conditions of feedback validity (0.5 vs 0.8 probability). Participants learned which button press was rewarded for each cue, with the value of the correct response varying across conditions. EEG was recorded to investigate neural correlates of value-based learning and the average reward rate representation.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004147

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus`	12 files	short	raw	Stimulus onset (cue presentation)
`New Segment`	12 files	admin	raw	Recording segment boundary - exclude
`Comment`	12 files	admin	raw	Experimenter annotation - exclude

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Casinos

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004147 DOI: https://doi.org/10.1037/a0038339

Normal Task 1: Stimulus-Locked Reinforcement Learning (binary/multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: New Segment and Comment are admin markers and must be excluded. Only 12 subjects - very small dataset. The `Stimulus` event needs behavioral outcome (correct/incorrect or rewarded/not-rewarded) from events.tsv for supervised learning. Feedback validity condition (0.5 vs 0.8) is available as a task variable.

Event	y	Meaning
`Stimulus`	0/1	Cue onset; label from behavioral outcome (reward/no reward in events.tsv)
## Data Quality Notes		

- Only 12 subjects - very small sample; unsuitable for cross-subject generalization
- New Segment and Comment are admin markers to exclude
- Behavioral outcome labels must be extracted from events.tsv alongside Stimulus events

References

- Reference: `Average Task Value`

101. openneuro_ds004148 - A test-retest resting and cognitive state EEG dataset

Dataset: `openneuro_ds004148` | Year: 2022 | URL: https://openneuro.org/datasets/ds004148
Category: High-level Mental | Subjects: 60 | Files (Completed): 1797 | Channels: 61 | Sampling Rate: 500 Hz

Paradigm

A test-retest reliability study recording EEG during five cognitive/resting conditions: eyes closed (EC), eyes open (EO), mental arithmetic (Ma), memory task (Me), and music listening (Mu), repeated across three sessions. Each file corresponds to one 5-minute condition block, with a single condition marker embedded (S 33=EO, S 44=EC, S 55=Mu, S 66=Me, S 77=Ma). Subjects are healthy adults aged 18-45.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004148

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`S 44`	360	long	raw	Eyes-closed resting state block label
`S 77`	360	long	raw	Mental arithmetic task block label
`S 66`	360	long	raw	Memory task block label
`S 55`	360	long	raw	Music listening block label
`S 33`	357	long	raw	Eyes-open resting state block label
`Sync Off`	~270000	admin	raw	Periodic sync signal (~150/file), not a trial event

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `S 44`, `S 77`, `S 66`, `S 55`, `S 33`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Eyes closed

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004148 DOI: https://doi.org/10.18112/openneuro.ds004148.v1.0.1

Primary Task 2: Publisher-defined BIDS task: Mathematic

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004148 DOI: https://doi.org/10.18112/openneuro.ds004148.v1.0.1

Primary Task 3: Publisher-defined BIDS task: Eyes open

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004148 DOI: https://doi.org/10.18112/openneuro.ds004148.v1.0.1

Normal Task 1: Cognitive State Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Each file contains exactly one condition marker; 1797 files x ~150s each. Sync Off is a periodic synchronization signal (150 per file), excluded.

Event	y	Meaning
S 33	0	Eyes-open resting state
S 44	1	Eyes-closed resting state
S 55	2	Music listening
S 66	3	Memory task
S 77	4	Mental arithmetic
## Data Quality Notes		

- Sync Off at ~150 events/file is hardware sync, not a task event
- Three test-retest sessions allow reliability analyses

References

- Reference: `A test-retest resting and cognitive state EEG dataset`

102. openneuro_ds004196 - Bimodal dataset on Inner speech

Dataset: `openneuro_ds004196` | Year: 2023 | URL: https://openneuro.org/datasets/ds004196
Category: High-level Mental | Subjects: 4 | Files (Completed): 4 | Channels: 73 | Sampling Rate: 512 Hz

Paradigm

An inner-speech production task where participants mentally vocalized eight specific words from social and numeric categories during nonsimultaneous EEG and fMRI recording. Subjects imagined speaking words without producing overt speech or movement. No trial-level event markers were embedded in the EEG recordings; the data is treated as continuous.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004196

Event Structure

No trial events detected. This dataset contains continuous EEG without trial-level annotations.

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Event ID	Count (total)	Type	Meta Level	Meaning
`no_events`	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Publisher-defined BIDS task: Inner Speech

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004196 DOI: https://doi.org/10.1101/2022.05.24.492109

Normal Task 1: Inner Speech Segmentation (resting)

- Task Type: segmentation
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null)
- Notes: No event markers available. Sliding window segmentation only.

Data Quality Notes

- Very small dataset (N=4); not suitable for cross-subject generalization
- Consider using fMRI labels aligned to EEG timing if available

References

- Reference: `Bimodal dataset on Inner speech`

103. openneuro_ds004200 - Temporal Scaling

Dataset: `openneuro_ds004200` | Year: 2022 | URL: https://openneuro.org/datasets/ds004200
Category: High-level Mental | Subjects: 20 | Files (Completed): 20 | Channels: 37 | Sampling Rate: 1000 Hz

Paradigm

Participants learned to produce and judge short, medium, and long temporal intervals through interleaved production and perception tasks with visual feedback. Trigger codes encode condition combinations: tens digit indicates task type and interval length (1x=production, 2x-6x=other conditions), units digit indicates subcondition or phase. The study investigates how humans scale temporal interval representations.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004200

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
11	~20	short	raw	Production short interval phase 1
12	~20	short	raw	Production short interval phase 2
13	~20	short	raw	Production short interval phase 3
21	~20	short	raw	Condition 2, phase 1
22	~20	short	raw	Condition 2, phase 2
23	~20	short	raw	Condition 2, phase 3
31	~20	short	raw	Condition 3, phase 1
32	~20	short	raw	Condition 3, phase 2
33	~20	short	raw	Condition 3, phase 3
41	~20	short	raw	Condition 4, phase 1
42	~20	short	raw	Condition 4, phase 2
43	~20	short	raw	Condition 4, phase 3
51	~20	short	raw	Condition 5, phase 1
52	~20	short	raw	Condition 5, phase 2
53	~20	short	raw	Condition 5, phase 3
61	~20	short	raw	Condition 6, phase 1
62	~20	short	raw	Condition 6, phase 2

Event ID	Count (total)	Type	Meta Level	Meaning
63	~20	short	raw	Condition 6, phase 3
17	~20	short	raw	Feedback/response code
27	~20	short	raw	Feedback/response code
47	~20	short	raw	Feedback/response code
57	~20	short	raw	Feedback/response code
67	~20	short	raw	Feedback/response code
2	~20	admin	raw	Block/session boundary marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Temporalscaling

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004200 DOI: https://doi.org/10.18112/openneuro.ds004200.v1.0.1

Normal Task 1: Temporal Condition Multiclass (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Trigger code `2` is a block marker, excluded. Decode exact condition meanings from paper or events.tsv.

Event	y	Meaning
11	0	Cond 1 phase 1
12	1	Cond 1 phase 2
13	2	Cond 1 phase 3

Event	y	Meaning
21	3	Cond 2 phase 1
22	4	Cond 2 phase 2
23	5	Cond 2 phase 3
31	6	Cond 3 phase 1
32	7	Cond 3 phase 2
33	8	Cond 3 phase 3
41	9	Cond 4 phase 1
42	10	Cond 4 phase 2
43	11	Cond 4 phase 3
51	12	Cond 5 phase 1
52	13	Cond 5 phase 2
53	14	Cond 5 phase 3
61	15	Cond 6 phase 1
62	16	Cond 6 phase 2
63	17	Cond 6 phase 3
17	18	Feedback 1
27	19	Feedback 2
47	20	Feedback 4
57	21	Feedback 5
67	22	Feedback 6
## Data Quality Notes		

- Numerical trigger codes require decode from paper
- Small dataset (N=20)

References

- Reference: `Temporal Scaling`

104. openneuro_ds004262 - Continuous Feedback Processing

Dataset: openneuro_ds004262 | Year: 2022 | URL: https://openneuro.org/datasets/ds004262
Category: High-level Mental | Subjects: 21 | Files (Completed): 21
Channels: 31 | Sampling Rate: 1000 Hz

Paradigm

Participants predicted the final height of an animated rising bar based on cues with varying predictability to study continuous feedback processing and prediction error. Each trial involved observing bar motion and registering a prediction, allowing examination of EEG correlates of reward prediction error and uncertainty-driven learning.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004262

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus`	21x900	short	raw	Stimulus onset marker (bar appearance)
`New Segment`	21	admin	raw	Recording segment boundary
`Comment`	21	admin	raw	Experimenter comment/annotation

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Gnomes

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004262 DOI: https://doi.org/10.18112/openneuro.ds004262.v1.0.0

Normal Task 1: Stimulus Processing (single-class)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only one event class available for epoching. New Segment and Comment are admin markers. Behavioral metadata (prediction, actual height) may be available in events.tsv for regression tasks.

Event	y	Meaning
`Stimulus`	0	Stimulus onset (bar presentation)
## Data Quality Notes		

- Only one non-admin event type (Stimulus); classification requires additional label parsing from events.tsv metadata columns
- New Segment and Comment are system/admin events excluded from epoching

References

- Reference: `Continuous Feedback Processing`

105. openneuro_ds004279 - Large Spanish EEG

Dataset: `openneuro_ds004279` | Year: 2024 | URL: https://openneuro.org/datasets/ds004279
Category: High-level Mental | Subjects: 56 | Files (Completed): 60
Channels: 69 | Sampling Rate: 1000 Hz

Paradigm

Participants performed speech perception and silent speech production tasks involving 30 daily Spanish sentences. Each sentence trial followed a fixed structure: a rest period, a preparation cue, a perception phase (hearing the sentence), and a production phase (silently producing the sentence). The study investigated EEG correlates of perceived and silently produced speech.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004279

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`perception_N` (N=1-30)	60x7	long	raw	Perception phase onset for sentence N
`production_N` (N=1-30)	60x7	long	raw	Silent production phase onset for sentence N
`preparation_N` (N=1-30)	60x7	long	raw	Preparation cue onset for sentence N
`rest_N` (N=1-30)	60x7	rest	raw	Rest period onset for sentence N
`bad_artifact`	60xvariable	admin	raw	Bad artifact annotation
`Impedance_test`	60x2	admin	raw	Impedance check marker
`bad_before_experiment`	60x1	admin	raw	Pre-experiment bad segment
`bad_after_experiment`	60x1	admin	raw	Post-experiment bad segment

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Sentences

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004279 DOI: https://doi.org/10.18112/openneuro.ds004279.v1.1.2

Normal Task 1: Perception vs Production Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s (relative to event onset), overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Group all perception_N events as class 0 and all production_N events as class 1. Each sentence has 7 repetitions per subject. bad_artifact, Impedance_test, and bad_* events are admin markers excluded from epoching.

Event	y	Meaning
`perception_1…perception_30`	0	Speech perception phase
`production_1…production_30`	1	Silent speech production phase
## Data Quality Notes		

- 90+ distinct event types (perception/production/preparation/rest for 30 sentences)
- bad_artifact count varies by subject (31-39 per file)
- Group sentence-level events by phase type for practical classification

References

- Reference: `Valle, C., Mendez-Orellana, C., Herff, C., & Rodriguez-Fernandez, M. (2024). Identification of perceived sentences using deep neural networks in EEG. Journal of neural engineering, 21(5), 056044.`

106. openneuro_ds004284 - eeg-neuroforecasting

Dataset: openneuro_ds004284 | Year: 2022 | URL: https://openneuro.org/datasets/ds004284
Category: High-level Mental | Subjects: N/A | Files (Completed): 18
Channels: 129.0 | Sampling Rate: 1000.0 Hz

Paradigm

A neuroforecasting task that utilizes EEG activity during decision-making or valuation to predict aggregate, population-level outcomes.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004284

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
no_events	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.
## MISC Label Summary				

- Route: misc
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

Tasks

Primary Task 1: Publisher-defined BIDS task: Kickstarter

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004284 DOI: https://doi.org/10.18112/openneuro.ds004284.v1.0.0

Normal Task 1: Raw-meta task

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Needs verification
- Kernel Notes: Exclude admin markers from target labels.

Normal Task 2: Super-meta task

- Task Type: regression/classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target / Label: Needs verification
- Kernel Notes: Derive and version super-meta in kernel.

Data Quality Notes

- Verify channel count consistency across subjects before pooling.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to epoching.

References

- Reference: `EEG-BIDS, an extension to the brain imaging data structure for electroencephalography`

107. openneuro_ds004295 - Reward gain and punishment avoidance reversal learning

Dataset: `openneuro_ds004295` | Year: 2022 | URL: https://openneuro.org/datasets/ds004295
Category: High-level Mental | Subjects: 26 | Files (Completed): 26
Channels: 66 | Sampling Rate: 1024 Hz

Paradigm

A reversal learning task comparing brain activity during reward gain (monetary) versus punishment avoidance (white noise) reinforcement. Participants learned stimulus-response associations that reversed mid-task, requiring cognitive flexibility. EEG was recorded to investigate feedback-related neural signatures under different reinforcement conditions.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004295

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`S 81`	26x~164	short	raw	Stimulus trigger - decode from events.tsv
`S 61`	26x~162	short	raw	Stimulus trigger - decode from events.tsv
`S 75`	26x~153	short	raw	Stimulus trigger - decode from events.tsv
`S 71`	26x~148	short	raw	Stimulus trigger - decode from events.tsv
`S 52`	26x~141	short	raw	Stimulus trigger - decode from events.tsv
`S 51`	26x~139	short	raw	Stimulus trigger - decode from events.tsv
`S 55`	26x~137	short	raw	Stimulus trigger - decode from events.tsv

Event ID	Count (total)	Type	Meta Level	Meaning
S 72	26x~132	short	raw	Stimulus trigger - decode from events.tsv
S 60	26x~118	short	raw	Stimulus trigger - decode from events.tsv
S 80	26x~116	short	raw	Stimulus trigger - decode from events.tsv
S100	26x~1	short	raw	Sample stimulus (first in pair)
S200	26x~1	short	raw	Probe stimulus (second in pair)

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `S 81`, `S 61`, `S 75`, `S 71`, `S 52`, `S 51`, `S 55`, `S 72`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Task

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004295 DOI: https://doi.org/10.18112/openneuro.ds004295.v1.0.0

Normal Task 1: Reversal Learning Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`

- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Specific kernel required to decode BrainVision trigger codes (S 51-S 81 range) to semantic labels. Regression target: response_time from misc channels.

Event	y	Meaning
`stimulus_A_prereversalReward`	0	Stimulus A before reversal (reward condition)
`stimulus_B_prereversalPunishment`	1	Stimulus B before reversal (punishment condition)
`correct_response`	2	Correct response
`incorrect_response`	3	Incorrect response
`reversal_cue`	4	Reversal signal
`stimulus_A_postreversalPunishment`	5	Stimulus A after reversal (punishment condition)
`feedback_positive`	6	Positive feedback
`feedback_negative`	7	Negative feedback
## Data Quality Notes		

- BrainVision trigger codes (S 51-S 81 range) require kernel-level decoding to semantic labels
- S150/S151 appear in only 22 subjects, possibly a separate task block

References

- Reference: `Reward gain and punishment avoidance reversal learning`

108. openneuro_ds004315 - Mood Manipulation and PST, Experiment 1

Dataset: openneuro_ds004315 | Year: 2022 | URL: https://openneuro.org/datasets/ds004315
Category: High-level Mental | Subjects: 50 | Files (Completed): 50
Channels: 66 | Sampling Rate: 500 Hz

Paradigm

A reinforcement learning task (Probabilistic Selection Task) consisting of training and testing phases following a sad or neutral mood manipulation. Participants learned to select stimuli associated with reward or punishment, and were subsequently tested on novel stimulus pairs. EEG was recorded to examine how mood state affects the neural correlates of reinforcement learning.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004315

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`STIM`	50x~240	short	raw	Stimulus onset (stimulus pair presented)
`RESP`	50x~230	short	raw	Participant button-press response
`FB`	50x~240	short	raw	Feedback onset (reward/punishment)
`Correct`	50x~200	short	raw	Correct response outcome
`Incorrect`	50x~85	short	raw	Incorrect response outcome
`TESTING`	50x~1700	short	raw	Testing phase trial marker
`STATUS`	50	admin	raw	System status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `STIM`, `STATUS`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: PST

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004315 DOI: https://doi.org/10.18112/openneuro.ds004315.v1.0.0

Normal Task 1: Feedback Outcome Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: STATUS is an admin marker (exclude). TESTING events have rich sub-labels in the actual events.tsv (e.g., "TESTING: Right Press, Correct") useful for further analysis. Class imbalance: Correct >> Incorrect.

Event	y	Meaning
`Correct`	0	Correct response
`Incorrect`	1	Incorrect response
## Data Quality Notes		

- STATUS is an admin/system marker and must not be included in target events
- TESTING events contain rich sub-labels in events.tsv; the trial_type column provides full label strings
- Class imbalance between Correct (~200) and Incorrect (~55 training) responses

References

- Reference: `Mood Manipulation and PST, Experiment 1`

109. openneuro_ds004317 - Mood Manipulation and PST, Experiment 2

Dataset: `openneuro_ds004317` | Year: 2022 | URL: https://openneuro.org/datasets/ds004317
Category: High-level Mental | Subjects: 50 | Files (Completed): 50
Channels: 66 | Sampling Rate: 500 Hz

Paradigm

A reinforcement learning task (Probabilistic Selection Task) performed by participants following sad or happy mood manipulations. The paradigm mirrors Experiment 1 but compares sad and happy mood conditions rather than sad versus neutral. EEG was recorded to examine mood-dependent differences in reinforcement learning neural signatures.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004317

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`STIM`	50x~240	short	raw	Stimulus onset (stimulus pair presented)
`RESP`	50x~230	short	raw	Participant button-press response
`FB`	50x~240	short	raw	Feedback onset (reward/punishment)
`Correct`	50x~198	short	raw	Correct response outcome
`Incorrect`	50x~100	short	raw	Incorrect response outcome
`TESTING`	50x~1664	short	raw	Testing phase trial marker
`STATUS`	50	admin	raw	System status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `STIM`, `STATUS`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: PST

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004317 DOI: https://doi.org/10.18112/openneuro.ds004317.v1.0.3

Normal Task 1: Feedback Outcome Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: STATUS is an admin marker (exclude). TESTING events contain rich sub-labels in events.tsv. Better class balance than Experiment 1 (~198 correct vs ~100 incorrect in training phase).

Event	y	Meaning
`Correct`	0	Correct response
`Incorrect`	1	Incorrect response
## Data Quality Notes		

- STATUS is an admin/system marker and must not be included in target events
- TESTING events contain rich sub-labels in events.tsv; the trial_type column provides full label strings
- Better class balance than Experiment 1

References

- Reference: `Mood Manipulation and PST, Experiment 2`

110. openneuro_ds004324 - ToonFaces

Dataset: openneuro_ds004324 | Year: 2023 | URL: https://openneuro.org/datasets/ds004324
Category: High-level Mental | Subjects: 26 | Files (Completed): 26
Channels: 38 | Sampling Rate: 500 Hz

Paradigm

Participants viewed rapid serial visual presentation (RSVP) streams of three types of face images - real photographs (img), stylized toon faces (toon), and schematic stick-figure faces (sf) - each shown at different emotional intensity levels (0-4). Subjects evaluated emotion detection and affective states, allowing ERP-based comparison across face types and intensity levels.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004324

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`img/0`	26x45	short	raw	Real face image, intensity 0 (neutral)
`img/1`	26x195	short	raw	Real face image, intensity 1
`img/2`	26x15	short	raw	Real face image, intensity 2
`img/3`	26x15	short	raw	Real face image, intensity 3
`img/4`	26x30	short	raw	Real face image, intensity 4 (most intense)
`toon/0`	26x45	short	raw	Toon face, intensity 0 (neutral)
`toon/1`	26x195	short	raw	Toon face, intensity 1
`toon/2`	26x15	short	raw	Toon face, intensity 2
`toon/3`	26x15	short	raw	Toon face, intensity 3
`toon/4`	26x30	short	raw	Toon face, intensity 4
`sf/0`	26x45	short	raw	Schematic face, intensity 0 (neutral)
`sf/1`	26x195	short	raw	Schematic face, intensity 1

Event ID	Count (total)	Type	Meta Level	Meaning
sf/2	26x15	short	raw	Schematic face, intensity 2
sf/3	26x15	short	raw	Schematic face, intensity 3
sf/4	26x30	short	raw	Schematic face, intensity 4
BlockEnd	26x3	admin	raw	End of block marker
block1	26	admin	raw	Block 1 start marker
block2	26	admin	raw	Block 2 start marker
block3	26	admin	raw	Block 3 start marker
Intro	22	admin	raw	Introduction screen marker
Instructions1	25	admin	raw	Instructions screen 1
Instructions2	25	admin	raw	Instructions screen 2
Instructions3	25	admin	raw	Instructions screen 3
PracticeInstructions	25	admin	raw	Practice instructions marker

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: RSVP

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004324 DOI: https://doi.org/10.18112/openneuro.ds004324.v1.0.0

Normal Task 1: Face Type Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Block markers (block1/2/3, BlockEnd) and instruction markers are admin events - exclude from target_events. Intensity sub-levels can be used for finer-grained multiclass analysis.

Event	y	Meaning
`img/0…img/4`	0	Real photograph face
`toon/0…toon/4`	1	Stylized toon face
`sf/0…sf/4`	2	Schematic stick-figure face
## Data Quality Notes		

- Block/instruction markers must be excluded from epoching
- Unequal counts across intensity levels (intensity 1: 195 vs intensity 2/3: 15 per face type)
- 26 subjects; consistent event structure across subjects

References

- Reference: `Images of stylized faces improve ERP features used for emotion detection`

111. openneuro_ds004350 - Executive Functioning Study for Assessing the Effect of Neurofeedback

Dataset: `openneuro_ds004350` | Year: 2025 | URL: https://openneuro.org/datasets/ds004350
Category: High-level Mental | Subjects: 24 | Files (Completed): 480
Channels: 64 | Sampling Rate: 256 Hz

Paradigm

Participants performed a battery of executive function tasks including a visual N-back working memory task (stimuli A/B/C/D), a Sustained Attention to Response Task (SART, target/nontarget), and a Local-Global hierarchical stimulus task (largeH/largeT x smallH/smallT). The study assessed the effect of neurofeedback training on executive function performance.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: reaction time
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004350

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`target`	44xx	short	raw	Target stimulus (requires response)
`nontarget`	44xx	short	raw	Non-target stimulus (no-go)
`A`	144xx	short	raw	N-back stimulus A
`B`	144xx	short	raw	N-back stimulus B
`C`	144xx	short	raw	N-back stimulus C
`D`	144xx	short	raw	N-back stimulus D
`largeHSmallH`	48xx	short	raw	Large H / Small H (local-global congruent)
`largeHSmallT`	48xx	short	raw	Large H / Small T (local-global incongruent)
`largeTSmallH`	48xx	short	raw	Large T / Small H (local-global incongruent)
`largeTSmallT`	48xx	short	raw	Large T / Small T (local-global congruent)

Event ID	Count (total)	Type	Meta Level	Meaning
responseLargeH	48xx	short	raw	Response: Large H selected
responseLargeT	48xx	short	raw	Response: Large T selected
responseSmallH	48xx	short	raw	Response: Small H selected
responseSmallT	48xx	short	raw	Response: Small T selected
rt	188xx	short	raw	Reaction time marker
255	2	admin	raw	System trigger code 255

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: reaction_time
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: NB1

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004350 DOI: https://doi.org/10.1038/nn1233

Primary Task 2: Publisher-defined BIDS task: NB3

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]

- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004350 DOI: https://doi.org/10.1038/nn1233

Primary Task 3: Publisher-defined BIDS task: LG

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004350 DOI: https://doi.org/10.1038/nn1233

Normal Task 1: SART Target Detection (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Numerical codes (1, 2, 4, 5, 6, 8, 9, 10, 11, 12, 128, 255) are likely system/artifact markers - exclude from target_events. Multiple tasks in one dataset; files are per-task. Separate HDF5 files per task recommended.

Event	y	Meaning
`nontarget`	0	Non-target (go) stimulus
`target`	1	Target (no-go) stimulus
## Data Quality Notes		

- Multiple distinct tasks (SART, N-back, Local-Global) in same dataset; files are per-task
- Numerical trigger codes (1-255) are system markers, not task events
- 480 files across 24 subjects (multiple sessions/tasks per subject)

References

- Reference: `Executive Functionning Study for Assessing the Effect of Neurofeedback`

112. openneuro_ds004367 - Meta-rdk: Raw EEG data

Dataset: `openneuro_ds004367` | Year: 2022 | URL: https://openneuro.org/datasets/ds004367
Category: High-level Mental | Subjects: 42 | Files (Completed): 40
Channels: 68 | Sampling Rate: 1200 Hz

Paradigm

A visual motion discrimination task involving left/right direction decisions on random dot kinematogram (RDK) stimuli followed by a metacognitive confidence assessment using a visual analog scale. The numerical trigger codes encode stimulus direction, coherence level, response direction, confidence level, and feedback. The dataset supports both motion perception classification and confidence/metacognition regression.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, confidence, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004367

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`3072`	40x300	short	raw	Motion stimulus onset (specific direction/coherence)
`3456`	40x300	short	raw	Motion stimulus onset (specific direction/coherence)
`3584`	40x300	short	raw	Motion stimulus onset (specific direction/coherence)
`3968`	40x300	short	raw	Motion stimulus onset (specific direction/coherence)
`4096`	40x300	short	raw	Motion stimulus onset (specific direction/coherence)
`4480`	40x300	short	raw	Motion stimulus onset (specific direction/coherence)
`31744...25984`	40x10 each	short	raw	Response/confidence marker (numerical code)

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `confidence`, `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Rdk

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004367 DOI: https://doi.org/10.1101/2022.10.19.22281249

Normal Task 1: Motion Direction Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Numerical trigger codes require specific kernel decoding. Regression target: response_time and confidence from misc channels.

Event	y	Meaning
`motion_stimulus_onset`	0	Motion stimulus onset
`left_response`	1	Left direction response
`right_response`	2	Right direction response
`confidence_low`	3	Low confidence rating
`confidence_medium`	4	Medium confidence rating
`confidence_high`	5	High confidence rating

Event	y	Meaning
`feedback_onset`	6	Feedback onset
## Data Quality Notes		

- All event IDs are numerical codes requiring kernel-level decoding
- 68 channels includes EOG/ECG channels
- 42 subjects but only 40 files completed

References

- Reference: `Meta-rdk: Raw EEG data`

113. openneuro_ds004369 - Blink-Pause-Relation (Competing Speaker Paradigm)

Dataset: openneuro_ds004369 | Year: 2023 | URL: https://openneuro.org/datasets/ds004369
Category: High-level Mental | Subjects: 41 | Files (Completed): 41
Channels: 7 | Sampling Rate: 500 Hz

Paradigm

A two-competing speaker paradigm where participants selectively attended to one of two concurrently presented audiobooks while ignoring the other. EEG was recorded to study the relationship between eye blinks and speech pauses during continuous auditory attention. No trial-level event markers are present in the EEG files.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004369

Event Structure

No event markers detected (`no_events`). This dataset contains continuous EEG recordings without trial-level annotations.

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Event ID	Count (total)	Type	Meta Level	Meaning
`no_events`	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Publisher-defined BIDS task: Attended Speaker Paradigm

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification

- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004369 DOI: https://doi.org/10.18112/openneuro.ds004369.v1.0.1

Normal Task 1: Continuous Segmentation (resting/segmentation)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (unsupervised segmentation)
- Notes: No trial markers in EEG files; use sliding window segmentation. Only 7 channels (very low-density). Subject-level labels (attended speaker, blink/pause occurrence) may be available from behavioral logs.

Data Quality Notes

- Very sparse channel setup (7 channels only)
- No trial-level event markers in the EEG files
- Continuous naturalistic listening paradigm (audiobook)

References

- Reference: `Jaeger et al. (2020); Holtze et al. (2021)`

114. openneuro_ds004395 - Penn Electrophysiology of Encoding and Retrieval Study (PEERS)

Dataset: `openneuro_ds004395` | Year: 2023 | URL: https://openneuro.org/datasets/ds004395
Category: High-level Mental | Subjects: 300 | Files (Completed): 6480
Channels: 129 | Sampling Rate: 500 Hz

Paradigm

A large-scale study investigating the electrophysiological correlates of memory encoding and retrieval using various free recall tasks. Participants encoded word lists and subsequently recalled them (free recall), also performing recognition memory tasks. The study provides a rich dataset for ERP analysis of encoding success, retrieval effort, and memory-related oscillations.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: confidence
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004395

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`WORD`	6480x~256	short	raw	Word presentation onset (encoding)
`REC_WORD`	6480x~100	short	raw	Recalled word onset (retrieval)
`RECOG_TARGET`	3581x~160	short	raw	Recognition target word onset
`RECOG_LURE`	3581x~80	short	raw	Recognition lure word onset
`RECOG_RESP`	3581x~320	short	raw	Recognition response
`RECOG_CONF`	3563x~320	short	raw	Confidence rating
`DISTRACTOR`	2439xx	short	raw	Distractor task stimulus
`REC_WORD_VV`	5001xx	short	raw	Recalled word (voice-verified)
`REST_REWET`	5955x1	rest	raw	Rest/reward-with-eye-tracking marker
`SESS_START`	6478	admin	raw	Session start marker
`SESS_END`	6474	admin	raw	Session end marker
`REC_START`	6480	admin	raw	Recall period start

Event ID	Count (total)	Type	Meta Level	Meaning
START	3668	admin	raw	Start marker
STOP	3668	admin	raw	Stop marker
BREAK_START	459	admin	raw	Break start marker
BREAK_STOP	459	admin	raw	Break stop marker

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `confidence`
- Kernel Note: Keep derivation source, unit, and version metadata.

Tasks

Primary Task 1: Publisher-defined BIDS task: Ltp FR

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004395 DOI: https://doi.org/10.18112/openneuro.ds004395.v2.0.0

Primary Task 2: Publisher-defined BIDS task: Ltp FR2

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004395 DOI: https://doi.org/10.18112/openneuro.ds004395.v2.0.0

Primary Task 3: Publisher-defined BIDS task: VFFR

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)

- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004395 DOI: https://doi.org/10.18112/openneuro.ds004395.v2.0.0

Normal Task 1: Memory Encoding Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: SESS_START/END, REC_START, START/STOP, BREAK_START/STOP are admin markers - exclude. REST_REWET is a rest marker. Very large dataset (300 subjects, 6480 files); suitable for large-scale ERP studies.

Event	y	Meaning
`RECOG_TARGET`	0	Recognition target (previously seen)
`RECOG_LURE`	1	Recognition lure (not previously seen)
## Data Quality Notes		

- Very large dataset (300 subjects, 6480 files); processing time is substantial
- Session-level admin markers (SESS_START/END) must be excluded from epoching
- Multiple sub-tasks with different event structures; separate HDF5 per sub-task recommended

References

- Reference: `Penn Electrophysiology of Encoding and Retrieval Study (PEERS)`

115. openneuro_ds004408 - EEG responses to continuous naturalistic speech

Dataset: openneuro_ds004408 | Year: 2023 | URL: https://openneuro.org/datasets/ds004408
Category: High-level Mental | Subjects: 380 | Files (Completed): 380
Channels: 128 | Sampling Rate: 512 Hz

Paradigm

Participants listened to continuous segments of an audiobook version of 'The Old Man and the Sea' to record EEG responses to naturalistic narrative speech and language processing. The study investigates low-frequency cortical entrainment to speech and phoneme-level processing. No trial-level event markers are present; recordings are continuous.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004408

Event Structure

No event markers detected (no_events). This dataset contains continuous EEG recordings during naturalistic speech listening without trial-level annotations.

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

Event ID	Count (total)	Type	Meta Level	Meaning
no_events	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Publisher-defined BIDS task: Listening

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification

- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004408 DOI: https://doi.org/10.18112/openneuro.ds004408.v1.0.8

Normal Task 1: Continuous Segmentation (segmentation)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (unsupervised segmentation)
- Notes: No trial markers; use sliding window segmentation. Large dataset (380 files). Suitable for EEG-speech alignment analysis using stimulus audio envelope.

Data Quality Notes

- No trial-level event markers; continuous listening paradigm
- Very large dataset (380 files); batch processing required
- 128-channel EEG at 512 Hz

References

- Reference: `Low-frequency cortical entrainment to speech reflects phoneme-level processing`

116. openneuro_ds004511 - Deception_data

Dataset: openneuro_ds004511 | Year: 2023 | URL: https://openneuro.org/datasets/ds004511
Category: High-level Mental | Subjects: 29 | Files (Completed): 29 | Channels: 64 | Sampling Rate: 512 Hz

Paradigm

Participants performed a deception task while EEG was recorded. The dataset contains continuous EEG recordings; only a single hardware synchronization marker (Sync) is present per recording rather than trial-level event markers. No meaningful trial annotations are available for epoch-based analysis.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004511

Event Structure

No task event markers detected (no_events). Only hardware sync marker Sync(1) present - this is a system/hardware event, not a task event.

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

Event ID	Count (total)	Type	Meta Level	Meaning
no_events	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Publisher-defined BIDS task: CC

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004511 DOI: https://doi.org/10.3758/s13428-020-01516-y

Primary Task 2: Publisher-defined BIDS task: GG

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004511 DOI: https://doi.org/10.3758/s13428-020-01516-y

Primary Task 3: Publisher-defined BIDS task: Rest

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004511 DOI: https://doi.org/10.3758/s13428-020-01516-y

Normal Task 1: Continuous Segmentation (resting/segmentation)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (unsupervised segmentation)
- Notes: Sync(1) is a hardware synchronization marker, not a task event. Use sliding window segmentation for feature extraction.

Data Quality Notes

- No trial-level event markers
- Sync(1) is a hardware-only event and should not be used for epoching

References

- Reference: `Deception_data`

117. openneuro_ds004514 - Simultaneous EEG and fNIRS recordings for semantic decoding of imagined animals and tools

Dataset: `openneuro_ds004514` | Year: 2023 | URL: https://openneuro.org/datasets/ds004514
Category: High-level Mental | Subjects: 22 | Files (Completed): 22 | Channels: 32 | Sampling Rate: 500 Hz

Paradigm

Participants imagined animals and tools in response to visual cues while simultaneous EEG and fNIRS were recorded. Events encode the specific animal or tool category being imagined across four modalities: visual imagery, silent naming, auditory imagery, and drawing imagery. The study investigates cross-modal semantic representations of living vs non-living concepts.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004514

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`animal_visual_imagery_task`	~22xN	long	raw	Visual imagery of animals
`tool_visual_imagery_task`	~22xN	long	raw	Visual imagery of tools
`animal_silent_naming_task`	~22xN	long	raw	Silent naming imagery of animals
`tool_silent_naming_task`	~22xN	long	raw	Silent naming imagery of tools
`animal_auditory_imagery_task`	~22xN	long	raw	Auditory imagery of animals
`tool_auditory_imagery_task`	~22xN	long	raw	Auditory imagery of tools
`animal_drawing_imagery_task`	~22xN	long	raw	Drawing imagery of animals
`tool_drawing_imagery_task`	~22xN	long	raw	Drawing imagery of tools
`rest`	~22xN	rest	raw	Rest period between imagery blocks
`animal_visual_image`	~22xN	short	raw	Visual image of animal (cue)

Event ID	Count (total)	Type	Meta Level	Meaning
tool_visual_image	~22xN	short	raw	Visual image of tool (cue)
audio_animal	~22xN	short	raw	Audio cue for animal
audio_tool	~22xN	short	raw	Audio cue for tool
written_animal	~22xN	short	raw	Written word cue for animal
written_tool	~22xN	short	raw	Written word cue for tool
animal_drawing	~22xN	short	raw	Drawing cue for animal
tool_drawing	~22xN	short	raw	Drawing cue for tool
animal_text_cue	~22xN	short	raw	Text cue for animal
tool_text_cue	~22xN	short	raw	Text cue for tool

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Nirs

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004514 DOI: https://doi.org/10.18112/openneuro.ds004514.v1.1.2

Primary Task 2: Publisher-defined BIDS task: Eeg

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004514 DOI: https://doi.org/10.18112/openneuro.ds004514.v1.1.2

Normal Task 1: Animal vs Tool Semantic Decoding (binary, long_event)

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: Annotation

- Target Definition: Event-to-label mapping table below.
- Notes: Imagery tasks are sustained (>=2 s) - use long_event epoching. rest events are resting periods between imagery blocks. Short cue events (visual_image, audio, written, drawing, text_cue) mark the onset stimulus, not the imagery period.

Event	y	Meaning
`animal_visual_imagery_task`	0	Animal imagery (any modality)
`animal_silent_naming_task`	0	Animal imagery (any modality)
`animal_auditory_imagery_task`	0	Animal imagery (any modality)
`animal_drawing_imagery_task`	0	Animal imagery (any modality)
`tool_visual_imagery_task`	1	Tool imagery (any modality)
`tool_silent_naming_task`	1	Tool imagery (any modality)
`tool_auditory_imagery_task`	1	Tool imagery (any modality)
`tool_drawing_imagery_task`	1	Tool imagery (any modality)
## Data Quality Notes		

- Simultaneous EEG and fNIRS; only EEG channels used here
- 32 EEG channels (lower density than typical 64-ch systems)
- 4 imagery modalities x 2 categories = 8 sustained imagery conditions

References

- Reference: `Simultaneous EEG and fNIRS recordings for semantic decoding of imagined animals and tools`

118. openneuro_ds004515 - EEG: Alcohol imagery reinforcement learning task with light and heavy drinker participants

Dataset: `openneuro_ds004515` | Year: 2023 | URL: https://openneuro.org/datasets/ds004515
Category: High-level Mental | Subjects: 42 | Files (Completed): 42 | Channels: 64 | Sampling Rate: 500 Hz

Paradigm

Participants (light and heavy drinkers) performed a reinforcement learning task involving alcohol-related and neutral imagery cues. On each trial, participants chose between left and right buttons in response to cues, with feedback (FB) indicating correct/incorrect responses. The study investigates how reward learning interacts with alcohol cue reactivity across drinking groups.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004515

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`CUE`	~42xN	short	raw	Stimulus cue onset
`Left Button`	~42xN	short	raw	Left button press response
`Right Button`	~42xN	short	raw	Right button press response
`FB`	~42xN	short	raw	Feedback onset
`STATUS`	~42xN	admin	raw	BrainVision hardware status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `STATUS`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Probabilistic Selection

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004515 DOI: https://doi.org/10.18112/openneuro.ds004515.v1.0.0

Normal Task 1: Response Direction Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: STATUS is an admin event - exclude from target_events. CUE and FB are trial markers but not the primary classification target. Left vs Right button press provides a binary motor/decision classification.

Event	y	Meaning
`Left Button`	0	Left button press
`Right Button`	1	Right button press
## Data Quality Notes		

- 42 subjects split between light and heavy drinkers
- STATUS markers are BrainVision hardware events, not task-related

References

- Reference: `EEG: Alcohol imagery reinforcement learning task with light and heavy drinker participants`

119. openneuro_ds004517 - EEG recordings for semantic decoding of imagined animals and tools during auditory imagery task

Dataset: `openneuro_ds004517` | Year: 2023 | URL: https://openneuro.org/datasets/ds004517
Category: High-level Mental | Subjects: 20 | Files (Completed): 20 | Channels: 32 | Sampling Rate: 500 Hz

Paradigm

Participants imagined animals and tools in response to auditory cues while EEG was recorded. Each trial consisted of an audio cue followed by a sustained auditory imagery period (~5 s). The study investigates EEG correlates of semantic imagery for living (animals) vs non-living (tools) concepts in the auditory domain.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004517

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`animal_auditory_imagery_task`	~20xN	long	raw	Sustained auditory imagery of animals
`tool_auditory_imagery_task`	~20xN	long	raw	Sustained auditory imagery of tools
`audio_animal`	~20xN	short	raw	Auditory cue onset for animal
`audio_tool`	~20xN	short	raw	Auditory cue onset for tool
`rest`	~20xN	rest	raw	Rest period between imagery blocks

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Eeg

- Task Type: classification/segmentation

- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004517 DOI: https://doi.org/10.18112/openneuro.ds004517.v1.0.2

Normal Task 1: Animal vs Tool Auditory Imagery (binary, long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Imagery tasks are sustained (~5 s) - use long_event epoching. audio_animal/audio_tool are short cue onsets; rest events are inter-block resting periods.

Event	y	Meaning
`animal_auditory_imagery_task`	0	Auditory imagery of animals
`tool_auditory_imagery_task`	1	Auditory imagery of tools
## Data Quality Notes		

- 32 EEG channels
- Sustained imagery periods (~5 s) are suitable for long_event epoching
- 20 subjects with balanced animal/tool imagery conditions

References

- Reference: `EEG recordings for semantic decoding of imagined animals and tools during auditory imagery task`

120. openneuro_ds004532 - EEG: Probabilistic Selection Task (PST) + PST with Cabergoline Challenge

Dataset: `openneuro_ds004532` | Year: 2023 | URL: https://openneuro.org/datasets/ds004532
Category: High-level Mental | Subjects: 40 | Files (Completed): 80 | Channels: 64 | Sampling Rate: 500 Hz

Paradigm

Participants performed the Probabilistic Selection Task (PST) in two sessions: a placebo session and a session with cabergoline (dopamine D2/D3 agonist). The PST involves learning to choose symbols with higher reward probability through feedback. Events encode training stimuli (Trn Stim), test stimuli (Tst Stim), feedback (FB), and outcome (correct/incorrect). The study investigates dopaminergic modulation of reinforcement learning.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004532

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Trn Stim`	~80xN	short	raw	Training stimulus onset
`Tst Stim`	~80xN	short	raw	Test stimulus onset
`FB`	~80xN	short	raw	Feedback onset
`correct`	~80xN	short	raw	Correct response outcome
`incorrect`	~80xN	short	raw	Incorrect response outcome
`STATUS`	~80xN	admin	raw	BrainVision hardware status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.

- Candidate Trigger Labels: `Trn Stim`, `Tst Stim`, `STATUS`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: PST

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004532 DOI: https://doi.org/10.1038/ncomms6394

Normal Task 1: Outcome Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: STATUS is an admin event - exclude from target_events. Trn Stim and Tst Stim are stimulus onset events; FB is the feedback onset. correct/incorrect provide clear binary outcome labels.

Event	y	Meaning
`correct`	0	Correct response outcome
`incorrect`	1	Incorrect response outcome
## Data Quality Notes		

- 40 subjects x 2 sessions (placebo + cabergoline) = 80 files
- STATUS markers are BrainVision hardware events, not task-related
- Two sessions per subject enable within-subject drug effect analysis

References

- Reference: `EEG: Probabilistic Selection Task (PST) + PST with Cabergoline Challenge`

121. openneuro_ds004561 - Illusion of Agency over Electrically-Actuated Movements

Dataset: `openneuro_ds004561` | Year: 2023 | URL: https://openneuro.org/datasets/ds004561
Category: High-level Mental | Subjects: 20 | Files (Completed): 20 | Channels: 64 | Sampling Rate: 512 Hz

Paradigm

Participants experienced electrical muscle stimulation that actuated their hand movements in three conditions: stimulation (involuntary movement), pretest (voluntary movement before stimulation), and posttest (voluntary movement after stimulation). EEG was recorded to investigate illusory sense of agency over externally-driven movements. The study explores how prior voluntary movement influences agency attribution over stimulation-induced movements.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004561

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stimulation`	~20xN	short	raw	Electrical stimulation onset (involuntary movement)
`pretest`	~20xN	short	raw	Pre-stimulation voluntary movement
`posttest`	~20xN	short	raw	Post-stimulation voluntary movement

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stimulation`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Agency RT

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004561 DOI: https://doi.org/10.18112/openneuro.ds004561.v1.0.0

Normal Task 1: Agency Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 3-class classification of agency conditions. stimulation = externally actuated movement, pretest/posttest = voluntary movements before/after stimulation session.

Event	y	Meaning
`stimulation`	0	Electrical stimulation (involuntary movement)
`pretest`	1	Pre-stimulation voluntary movement
`posttest`	2	Post-stimulation voluntary movement
## Data Quality Notes		

- 20 subjects with balanced condition structure
- 64 channels at 512 Hz provides good temporal resolution for movement-related potentials

References

- Reference: `Illusion of Agency over Electrically-Actuated Movements`

122. openneuro_ds004582 - FakeFaceEmo_data

Dataset: openneuro_ds004582 | Year: 2023 | URL: https://openneuro.org/datasets/ds004582
Category: High-level Mental | Subjects: 30 | Files (Completed): 30 | Channels: 64 | Sampling Rate: 512 Hz

Paradigm

Participants viewed fake face images with different emotional expressions while EEG was recorded. The dataset contains continuous EEG recordings; only hardware/metadata markers (New Segment, Comment) are present in the event files rather than trial-level stimulus markers. No trial-level event markers are available for epoch-based analysis.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004582

Event Structure

No task event markers detected (no_events). Only hardware/metadata markers present.

Event ID	Count (total)	Type	Meta Level	Meaning
New Segment/	~30x1	admin	raw	Recording segment boundary (hardware marker)

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: FF

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004582 DOI: https://doi.org/10.18112/openneuro.ds004582.v1.0.0

Normal Task 1: Continuous Segmentation (resting/segmentation)

- Task Type: regression

- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (unsupervised segmentation)
- Notes: New Segment/ is a BrainVision hardware recording marker, not a task event. Use sliding window segmentation for feature extraction.

Data Quality Notes

- No trial-level event markers
- New Segment/ is a hardware-only event and should not be used for epoching
- 30 subjects with continuous EEG recordings

References

- Reference: `FakeFaceEmo_data`

123. openneuro_ds004595 - EEG: RL Task (3-Armed Bandit) with Alcohol Cues in Hazardous Drinkers

Dataset: `openneuro_ds004595` | Year: 2023 | URL: https://openneuro.org/datasets/ds004595
Category: High-level Mental | Subjects: 53 | Files (Completed): 53 | Channels: 66 | Sampling Rate: 500 Hz

Paradigm

Participants completed a reinforcement learning task using a 3-armed bandit paradigm incorporating alcohol-related and neutral beverage cues to study decision-making in hazardous drinkers versus controls. On each trial, a cue was presented followed by a three-arm choice and probabilistic win/loss feedback. The study examines electrophysiological markers of cue-driven exploration and aberrant reinforcement learning.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004595

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Fixation`	18550	short	raw	Fixation cross onset (trial start)
`FB: Win`	9713	short	raw	Win feedback delivered
`FB: Loss`	7254	short	raw	Loss feedback delivered
`Left Button`	6276	short	raw	Left arm choice response
`Up Button`	6188	short	raw	Up arm choice response
`Right Button`	5553	short	raw	Right arm choice response
`STATUS`	4271	admin	raw	System status marker (exclude)
`CUE: 123`	2955	short	raw	Cue onset - arm order permutation 1-2-3
`CUE: 231`	2934	short	raw	Cue onset - arm order permutation 2-3-1

Event ID	Count (total)	Type	Meta Level	Meaning
CUE: 132	2931	short	raw	Cue onset - arm order permutation 1-3-2
CUE: 321	2919	short	raw	Cue onset - arm order permutation 3-2-1
CUE: 312	2908	short	raw	Cue onset - arm order permutation 3-1-2
CUE: 213	2853	short	raw	Cue onset - arm order permutation 2-1-3
No Response	533	admin	raw	No-response trial (exclude)
FB: No Resp	533	admin	raw	No-response feedback (exclude)

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Three Armed Bandit

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004595 DOI: https://doi.org/10.18112/openneuro.ds004595.v1.0.0

Normal Task 1: Feedback Classification (binary)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: STATUS, No Response, and FB: No Resp are admin - exclude. CUE events encode arm-order permutations; aggregate to generic CUE if order-agnostic analysis desired.

Event	y	Meaning
FB: Win	0	Win feedback
FB: Loss	1	Loss feedback

Event	y	Meaning
## Data Quality Notes		

- STATUS markers must be excluded from training.
- CUE events encode arm order permutations - group to single CUE class if order irrelevant.

References

- Reference: `Electrophysiological markers of aberrant cue-specific exploration in hazardous drinkers`

124. openneuro_ds004626 - Can We Dissociate Hypervigilance to Social Threats from Altered Perceptual Decision-Making in Lonely Individualsx

Dataset: `openneuro_ds004626` | Year: 2023 | URL: https://openneuro.org/datasets/ds004626
Category: High-level Mental | Subjects: 52 | Files (Completed): 52
Channels: 68 | Sampling Rate: 1000 Hz

Paradigm

A perceptual decision-making task investigating whether lonely individuals exhibit hypervigilance toward social threats, combining Drift Diffusion Modeling (DDM) with ERP analysis. Participants viewed social and non-social threat stimuli and made rapid perceptual judgements. ERP components (P1, N2pc, LPP) and computational decision parameters were compared across loneliness severity groups.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004626

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
208	36977	short	raw	High-frequency stimulus/response trigger
998	35001	short	raw	Secondary trigger (trial boundary/ITI)
236	6240	short	raw	Stimulus trigger code
146	6239	short	raw	Stimulus trigger code
206	6238	short	raw	Stimulus trigger code
186	6238	short	raw	Stimulus trigger code
142	6237	short	raw	Stimulus trigger code
210	6233	short	raw	Stimulus trigger code
999	2363	admin	raw	Trial-end/admin marker (exclude)
248	1560	short	raw	Trigger code
255	1560	admin	raw	S255 admin sync trigger (exclude)
300	1528	short	raw	Trigger code

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Dot Probe

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1111/psyp.14406

Normal Task 1: Stimulus classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Trigger 255 is a known admin sync code - exclude. Trigger 999 is trial-end/admin - exclude. Full decode requires events.tsv inspection.

Event	y	Meaning
`208`	0	Primary stimulus trigger
`998`	1	Secondary trigger
`236`	2	Trigger code
`146`	3	Trigger code
`206`	4	Trigger code
`186`	5	Trigger code
`142`	6	Trigger code
`210`	7	Trigger code
## Data Quality Notes		

- 30+ distinct numeric trigger codes - check events.tsv for full decode table.
- Codes 255 and 999 are administrative and must be excluded.

References

- Reference: Can we dissociate hypervigilance to social threats from altered perceptual decision-making processes in lonely individualsx DOI: 10.1111/psyp.14406

125. openneuro_ds004706 - Spatial Memory and Non-Invasive Closed-Loop Stimulus Timing

Dataset: `openneuro_ds004706` | Year: 2023 | URL: https://openneuro.org/datasets/ds004706
Category: High-level Mental | Subjects: 149 | Files (Completed): 298
Channels: 137 | Sampling Rate: 2048 Hz

Paradigm

A hybrid spatial-navigation and free recall task where participants delivered items to locations in a virtual town environment, with EEG recorded during both encoding and retrieval phases. The paradigm incorporates closed-loop stimulus timing to investigate the relationship between memory encoding, theta oscillations, and stimulation-driven memory enhancement. Sessions included free recall and cued recall phases with video stimuli.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004706

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
FFR_REC_WORD	55013	short	raw	Free-form recall word event
CUED_REC_STOP	44064	short	raw	Cued recall stop marker
CUED_REC_CUE	44064	short	raw	Cued recall cue onset
WORD	43260	short	raw	Word stimulus onset (encoding)
REC_WORD	39061	short	raw	Recalled word event
CUED_REC_WORD	34381	short	raw	Cued recall word event
CLASSIFIER_WAIT	22890	short	raw	Closed-loop classifier waiting
POINTER_ON	20872	short	raw	Spatial navigation pointer onset
CLASSIFIER	19005	short	raw	Closed-loop classifier event
EFR_MARK	11498	short	raw	EFR (encoding-phase) marker
CUED_REC_WORD_VV	11328	short	raw	Cued recall word (video verified)

Event ID	Count (total)	Type	Meta Level	Meaning
TRIAL_END	2888	short	raw	Trial end marker
TRIAL_START	2884	short	raw	Trial start marker
REC_STOP	2952	short	raw	Recording stop marker
REC_START	2952	short	raw	Recording start marker

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Nicls Courier Closed Loop

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004706 DOI: https://doi.org/10.18112/openneuro.ds004706.v1.0.0

Primary Task 2: Publisher-defined BIDS task: Nicls Courier Read Only

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004706 DOI: https://doi.org/10.18112/openneuro.ds004706.v1.0.0

Normal Task 1: Memory encoding/recall classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: High sampling rate (2048 Hz). BREAK_START/STOP, SESS_END are session markers. Closed-loop classifier events (CLASSIFIER, CLASSIFIER_WAIT) may interfere - treat as admin.

Event	y	Meaning
WORD	0	Word encoding
REC_WORD	1	Recalled word

Event	y	Meaning
CUED_REC_CUE	2	Cued recall cue
CUED_REC_WORD	3	Cued recall response
## Data Quality Notes		

- High sampling rate (2048 Hz) - downsample for efficiency.
- 30+ event types; focus on WORD/REC_WORD for memory encoding analysis.

References

- Reference: Spatial memory and non-invasive closed-loop stimulus timing

126. openneuro_ds004752 - Dataset of Intracranial EEG, Scalp EEG and Beamforming Sources from Epilepsy Patients - Verbal Working Memory

Dataset: `openneuro_ds004752` | Year: 2023 | URL: https://openneuro.org/datasets/ds004752
Category: High-level Mental | Subjects: 15 | Files (Completed): 136
Channels: 64 | Sampling Rate: 2000 Hz

Paradigm

Epilepsy patients performed a modified Sternberg verbal working memory task consisting of encoding, maintenance, and recall phases while simultaneous scalp and intracranial EEG were recorded. The dataset includes iEEG from depth electrodes, scalp EEG, single-unit neuron spike times, and electrode localizations, enabling multi-level analysis of memory processes. No trial-level event annotations are available in the BIDS events.tsv.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004752

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
(no events)	-	-	raw	No event markers detected in events.tsv

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Verbal WM

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)

- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1038/s41597-020-0364-3

Normal Task 1: Continuous Segmentation

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: None (no event tag)
- Notes: No trial-level events available in events.tsv. EEG is continuous during task performance. Use sliding-window segmentation. Trial timing may be available in accompanying behavioral logs not captured in BIDS events.tsv.

Data Quality Notes

- No event markers - trial-epoch structure not available from events.tsv.
- Very high sampling rate (2000 Hz) - downsample before analysis.
- Epilepsy patients; ictal episodes should be identified and excluded.

References

- Reference: `Dataset of human medial temporal lobe neurons, scalp and intracranial EEG during a verbal working memory task. DOI: 10.1038/s41597-020-0364-3`

127. openneuro_ds004796 - PEARL-Neuro Database (Alzheimer's Risk Genes, Lifestyle, Neuroimaging)

Dataset: `openneuro_ds004796` | Year: 2025 | URL: https://openneuro.org/datasets/ds004796
Category: High-level Mental | Subjects: 79 | Files (Completed): 233
Channels: 127 | Sampling Rate: 1000 Hz

Paradigm

A multimodal neuroimaging database of healthy middle-aged adults (50-63 years) carrying Alzheimer's risk genes (APOE, PICALM). The EEG protocol includes resting-state recordings (eyes open and closed) and two active cognitive tasks: the Multi-Source Interference Task (MSIT) and Sternberg's memory task. Stimulus and button-press response events are recorded across task sessions.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004796

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stimulus`	27862	short	raw	Stimulus onset (MSIT or Sternberg item)
`response`	24051	short	raw	Participant button-press response

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stimulus`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Cognitive control decoding in MSIT paradigm

- Task Type: classification

- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification] | tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation` or `misc`
- Target Definition: Interference/congruency condition and/or DBS ON/OFF effect labels
- Evidence: Dataset/paper center on MSIT cognitive control under DBS modulation. Source: https://doi.org/10.1038/s41597-024-03106-5

Primary Task 2: Publisher-defined BIDS task: Sternberg

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1038/s41597-024-03106-5

Primary Task 3: Publisher-defined BIDS task: Rest

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1038/s41597-024-03106-5

Normal Task 1: Stimulus vs response classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 233 files = 79 subjects x ~3 sessions. Resting-state sessions have no stimulus events; only task sessions contribute stimulus/response epochs.

Event	y	Meaning
`stimulus`	0	Stimulus onset
`response`	1	Button-press response
## Data Quality Notes		

- Mixed resting-state and task sessions; filter by file task label.
- High channel count (127); may include non-EEG channels.

References

- Reference: `PEARL-Neuro Database: EEG, fMRI, health and lifestyle data of middle-aged people at risk of dementia. DOI: 10.1038/s41597-024-03106-5`

128. openneuro_ds004802 - Loneliness in the Brain: Distinguishing Between Hypersensitivity and Hyperalertness (Pilot)

Dataset: `openneuro_ds004802` | Year: 2023 | URL: https://openneuro.org/datasets/ds004802
Category: High-level Mental | Subjects: 79 | Files (Completed): 79
Channels: 73 | Sampling Rate: 512 Hz

Paradigm

A pilot EEG study investigating the neural underpinnings of loneliness by contrasting social hypersensitivity (amplified neural responses to social stimuli) and hyperalertness (heightened attention to potential social threats). Participants viewed social and non-social stimuli while EEG was recorded. Trigger codes encode stimulus type, valence, and response conditions. Code 20 dominates the event structure (49,726 total) and may represent a high-frequency refresh or fixation signal.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004802

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`20`	49726	short	raw	Dominant trigger (likely fixation/refresh signal)
`111`	4144	short	raw	Trigger code 111
`25`	2823	short	raw	Trigger code 25
`24`	2817	short	raw	Trigger code 24
`21`	2747	short	raw	Trigger code 21
`23`	2667	short	raw	Trigger code 23
`22`	2666	short	raw	Trigger code 22
`42`	2319	short	raw	Trigger code 42
`44`	2316	short	raw	Trigger code 44
`43`	2246	short	raw	Trigger code 43
`61`	2221	short	raw	Trigger code 61
`62`	2185	short	raw	Trigger code 62
`65`	2182	short	raw	Trigger code 65

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://openneuro.org/datasets/ds004802 DOI: https://doi.org/10.18112/openneuro.ds004802.v1.0.0

Normal Task 1: Stimulus classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 30+ distinct trigger codes; full decode from events.tsv required. Code 20 dominates (49,726 total) - likely a high-frequency fixation or visual onset marker.

Event	y	Meaning
`20`	0	Primary stimulus trigger
`111`	1	Trigger code 111
`25`	2	Trigger code 25
`24`	3	Trigger code 24
`21`	4	Trigger code 21
`23`	5	Trigger code 23
`22`	6	Trigger code 22
## Data Quality Notes		

- 30+ distinct trigger codes - check events.tsv decode table.
- Code 20 (49,726 total) is anomalously high - may be a fixation/refresh signal rather than stimulus.

References

- Reference: Loneliness in the Brain: Distinguishing Between Hypersensitivity and Hyperalertness

129. openneuro_ds005114 - EEG: DPX Cognitive Control Task in Acute Mild TBI

Dataset: `openneuro_ds005114` | Year: 2024 | URL: https://openneuro.org/datasets/ds005114
Category: High-level Mental | Subjects: 62 | Files (Completed): 217 | Channels: 65 | Sampling Rate: 500 Hz

Paradigm

The Dot Pattern Expectancy (DPX) task, a version of the Continuous Performance Task, was used to assess proactive versus reactive cognitive control in sub-acute mild traumatic brain injury (mTBI) patients and healthy controls. Participants responded to cue-probe pairs (CueA/CueB x Probe aX/aY/bY), enabling decomposition of context-maintenance and response-inhibition processes via P3a/P3b ERP components.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005114

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Response: CueCorr`	50287	short	raw	Correct response to cue
`Response: Probe_Corr`	46594	short	raw	Correct response to probe
`CueAOnset`	43580	short	raw	Cue A stimulus onset
`Probe_aX_onset`	35272	short	raw	Probe aX onset (congruent with CueA)
`STATUS`	19463	admin	raw	System status marker (exclude)
`Practice: filler trigger`	15787	admin	raw	Practice trial filler (exclude)
`Probe_aY_onset`	6443	short	raw	Probe aY onset
`Probe_bY_onset`	5428	short	raw	Probe bY onset
`Response: Probe_Incorr`	3626	short	raw	Incorrect probe response
`Feedback: ProbeErr`	3626	short	raw	Error feedback
`CueBOnset`	2661	short	raw	Cue B stimulus onset

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `STATUS`, `Practice: filler trigger`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: DPX

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1016/j.neuropsychologia.2019.107125

Normal Task 1: Cue and Probe Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: STATUS (19,463) and Practice: filler trigger (15,787) are admin - exclude. mTBI patients and healthy controls included; participant group labels in participants.tsv.

Event	y	Meaning
`CueAOnset`	0	Cue A onset
`CueBOnset`	1	Cue B onset
`Probe_aX_onset`	2	Probe aX (AX trial - expected)
`Probe_aY_onset`	3	Probe aY (AY trial - unexpected)
`Probe_bY_onset`	4	Probe bY (BY trial)
`Response: CueCorr`	5	Correct cue response
`Response: Probe_Corr`	6	Correct probe response
## Data Quality Notes		

- STATUS and Practice filler triggers must be excluded from training.
- Dataset includes mTBI patients and healthy controls - group label in participants.tsv.

References

- Reference: `ERPs predict symptomatic distress and recovery in sub-acute mild traumatic brain injury. DOI: 10.1016/j.neuropsychologia.2019.107125`

130. openneuro_ds005262 - ArEEG: Arabic Inner Speech EEG Dataset

Dataset: `openneuro_ds005262` | Year: 2024 | URL: https://openneuro.org/datasets/ds005262
Category: High-level Mental | Subjects: 12 | Files (Completed): 186 | Channels: 8 | Sampling Rate: 250 Hz

Paradigm

EEG recordings of 12 subjects performing imagined (inner) speech tasks based on visual cues presented in Modern Standard Arabic. Subjects silently imagined saying directional words (Up, Down, Left, Right), a Select command, or remained at Rest. The study aims to develop Arabic-language BCI systems using inner speech decoding without overt vocalization.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005262

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Comment/Wait`	8949	short	raw	Wait period (inter-trial interval)
`Comment/Rest`	4590	rest	raw	Rest condition
`Comment/Up`	918	short	raw	Inner speech - "Up" command
`Comment/Select`	918	short	raw	Inner speech - "Select" command
`Comment/Right`	918	short	raw	Inner speech - "Right" command
`Comment/Left`	917	short	raw	Inner speech - "Left" command
`Comment/Down`	916	short	raw	Inner speech - "Down" command
`Comment/WarmUp`	174	admin	raw	Warm-up period (exclude)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Arabic inner speech command classification

- Task Type: classification

- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Six-class labels: Rest, Up, Down, Left, Right, Select from cue/comment events.
- Evidence: ArEEG dataset is explicitly constructed for Arabic inner-speech BCI command decoding. Source: https://openneuro.org/datasets/ds005262 DOI: https://doi.org/10.18112/openneuro.ds005262.v1.0.1

Normal Task 1: Inner Speech Command Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Comment/Wait is a high-frequency inter-trial marker - exclude from classification. Comment/WarmUp is admin - exclude. Only 8 EEG channels.

Event	y	Meaning
`Comment/Rest`	0	Rest condition
`Comment/Up`	1	Inner speech "Up"
`Comment/Down`	2	Inner speech "Down"
`Comment/Left`	3	Inner speech "Left"
`Comment/Right`	4	Inner speech "Right"
`Comment/Select`	5	Inner speech "Select"
## Data Quality Notes		

- Only 8 EEG channels - limited spatial resolution.
- Comment/Wait (8,949 total) is inter-trial interval - exclude from classification.
- Comment/WarmUp is admin - exclude.

References

- Reference: `ArEEG: Arabic Inner Speech EEG dataset`

131. openneuro_ds005305 - EEG Resting-State Microstates and Executive Functions

Dataset: openneuro_ds005305 | Year: 2024 | URL: https://openneuro.org/datasets/ds005305
Category: High-level Mental | Subjects: 165 | Files (Completed): 165 | Channels: 64 | Sampling Rate: 512 Hz

Paradigm

Resting-state EEG microstates were recorded to correlate spontaneous brain dynamics with performance on a nine-task battery of executive functions (dual N-back, Stroop, task-switching, etc.). Each file contains alternating eyes-closed (RS_EC, 825 total) and eyes-open (RS_EO, 660 total) resting blocks. The study investigates whether EEG microstate metrics predict individual differences in executive function. boundary (165) is a EEGLAB admin marker; key press events are incidental.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005305

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
RS_EC	825	rest	raw	Resting-state eyes-closed block onset
RS_EO	660	rest	raw	Resting-state eyes-open block onset
boundary	165	admin	raw	EEGLAB boundary marker (exclude)
RIGHT pressed/RIGHT released	26	admin	raw	Incidental key presses (exclude)
DOWN pressed/DOWN released	22	admin	raw	Incidental key presses (exclude)
LEFT pressed/LEFT released	16	admin	raw	Incidental key presses (exclude)
Other key events	rare	admin	raw	Incidental key presses (exclude)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Resting State

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005305 DOI: https://doi.org/10.1016/j.cortex.2024.05.019

Normal Task 1: Eyes Open vs Eyes Closed (binary)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `boundary` (165) and all key press events are admin - exclude. Each resting block is ~30-60 s; sliding windows capture microstate dynamics. RS_EC (825) > RS_EO (660) - slight imbalance.

Event	y	Meaning
RS_EC	0	Eyes-closed resting state
RS_EO	1	Eyes-open resting state
## Data Quality Notes		

- `boundary` is EEGLAB admin marker - exclude.
- Key press events are incidental - exclude.
- Executive function scores in participants.tsv for regression analyses.

References

- Reference: `Investigating the relationship between Resting-State EEG Microstates and Executive Functions: A Null Finding`

132. openneuro_ds005383 - TMNRED: A Chinese Language EEG Dataset for Fuzzy Semantic Target Identification in Natural Reading Environments

Dataset: `openneuro_ds005383` | Year: 2024 | URL: https://openneuro.org/datasets/ds005383
Category: High-level Mental | Subjects: 30 | Files (Completed): 720
Channels: 30 | Sampling Rate: 200 Hz

Paradigm

Participants engaged in self-paced natural reading of Chinese sentences and news headlines to identify fuzzy semantic targets embedded in text. The study investigates neural correlates of semantic processing during naturalistic reading, recording EEG with 30 channels at 200 Hz. Numerical BioSemi trigger codes mark word/sentence onset events across three sessions per subject (3 x 240 files = 720 total). The trigger code structure encodes semantic conditions, target presence, and reading context.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005383

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
55	240/file	short	raw	Stimulus condition code 55 (decode from events.tsv)
31	240/file	short	raw	Stimulus condition code 31
56	240/file	short	raw	Stimulus condition code 56
36	240/file	short	raw	Stimulus condition code 36
41	240/file	short	raw	Stimulus condition code 41
51	240/file	short	raw	Stimulus condition code 51
16	240/file	short	raw	Stimulus condition code 16
61	240/file	short	raw	Stimulus condition code 61
26	240/file	short	raw	Stimulus condition code 26

Event ID	Count (total)	Type	Meta Level	Meaning
46	240/file	short	raw	Stimulus condition code 46
21	240/file	short	raw	Stimulus condition code 21
22	240/file	short	raw	Stimulus condition code 22
32	240/file	short	raw	Stimulus condition code 32
42	240/file	short	raw	Stimulus condition code 42
52	240/file	short	raw	Stimulus condition code 52

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Fuzzysemanticrecognition

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005383 DOI: https://doi.org/10.18112/openneuro.ds005383.v1.0.0

Normal Task 1: Semantic Target Identification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 30 distinct numerical codes across all files; full decode from events.tsv or paper required. 720 files from 30 subjects x 24 sessions/files. Low sampling rate (200 Hz) limits high-frequency analysis.

Event	y	Meaning
16	0	Condition code 16
21	1	Condition code 21
22	2	Condition code 22
26	3	Condition code 26
31	4	Condition code 31
32	5	Condition code 32
36	6	Condition code 36
41	7	Condition code 41
42	8	Condition code 42
46	9	Condition code 46
51	10	Condition code 51
52	11	Condition code 52
55	12	Condition code 55
56	13	Condition code 56
61	14	Condition code 61
## Data Quality Notes		

- Numerical trigger codes require decode from events.tsv or dataset paper for semantic interpretation.
- 30 distinct codes; group by semantic condition (target/non-target) when possible.
- Low sampling rate (200 Hz) - suitable for N400/P600 ERP components but not high-gamma analysis.

References

- Reference: `TMNRED, A Chinese Language EEG Dataset for Fuzzy Semantic Target Identification in Natural Reading Environments`

133. openneuro_ds005403 - Delayed Auditory Feedback EEG/EGG

Dataset: `openneuro_ds005403` | Year: 2024 | URL: https://openneuro.org/datasets/ds005403
Category: High-level Mental | Subjects: 66 | Files (Completed): 66
Channels: 66 | Sampling Rate: 1000 Hz

Paradigm

Participants performed a speech production task while receiving delayed auditory feedback (DAF) to study neural processing of self-generated speech and auditory-motor monitoring. Three DAF conditions were used: an adaptation condition (fixed delay) and two random delay conditions (random1, random2), compared against a baseline (no delay). EEG was recorded alongside electroglottography (EGG) to capture vocal fold activity simultaneously. The event markers label continuous speech production blocks.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005403

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`adaption`	~64/file	long	raw	Adaptation DAF condition block
`random1`	~64/file	long	raw	Random delay condition 1 block
`random2`	~64/file	long	raw	Random delay condition 2 block
`baseline`	~64/file	rest	raw	Baseline (no delay) speech block

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Daf

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005403 DOI: https://doi.org/10.18112/openneuro.ds005403.v1.0.1

Normal Task 1: DAF Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: All four conditions are sustained speech production blocks (>=2 s). Simultaneous EGG channels included; verify channel naming in channel metadata.

Event	y	Meaning
`baseline`	0	Baseline (no delay)
`adaption`	1	Adaptation DAF condition
`random1`	2	Random delay condition 1
`random2`	3	Random delay condition 2
## Data Quality Notes		

- Simultaneous EGG recording alongside EEG - verify channel type labels.
- Speech production task - EMG artifacts from jaw/throat movement expected.
- Apply bandpass filter (1-40 Hz) and artifact rejection prior to epoching.

References

- Reference: `Delayed Auditory Feedback EEG/EGG`

134. openneuro_ds005815 - YOTO (You Only Think Once): An EEG Dataset for Tracking Spontaneous Cognitive Transitions and Multimodal Stimuli Responses in Resting-State and Task Phases

Dataset: `openneuro_ds005815` | Year: 2025 | URL: https://openneuro.org/datasets/ds005815
Category: High-level Mental | Subjects: 20 | Files (Completed): 205 | Channels: 30 | Sampling Rate: 250 Hz

Paradigm

Participants engaged in resting-state (eyes open/closed) and task phases involving unimodal and multimodal stimuli (visual and auditory) and mental imagery, providing self-reported vividness ratings. The YOTO paradigm investigates spontaneous cognitive transitions and mental imagery across stimulus modalities with numeric condition codes and named state markers.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005815

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`6-9`	6720 each	short	raw	Stimulus condition codes (decode from events.tsv)
`TrialProc`	6528	long	raw	Trial procedure marker
`23`	840	short	raw	Stimulus/response code 23
`22`	420	short	raw	Stimulus/response code 22
`21`	420	short	raw	Stimulus/response code 21
`StartInstruction`	66	long	raw	Instruction block onset
`Eyeclosed`	66	long	raw	Eyes-closed resting onset
`FixationBreak`	66	short	raw	Fixation break event
`EyeOpen`	66	long	raw	Eyes-open resting onset

Event ID	Count (total)	Type	Meta Level	Meaning
`EndInstruction`	66	long	raw	Instruction block offset
`88`	64	short	raw	Response/trigger code 88
`30-35`	280 each	short	raw	Imagery/rating condition codes
`99`	101	admin	raw	Admin/session marker
`1`	81	short	raw	Condition code 1
`2-5`	68 each	short	raw	Condition codes 2-5

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Rest1

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005815 DOI: https://doi.org/10.18112/openneuro.ds005815.v2.0.1

Primary Task 2: Publisher-defined BIDS task: Rest2

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005815 DOI: https://doi.org/10.18112/openneuro.ds005815.v2.0.1

Normal Task 1: Multi-task Cognitive (long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

- Notes: Numerical codes require decoding from events.tsv. Eyes-open/closed markers (`EyeOpen`, `Eyeclosed`) can be used for resting-state analysis.

Event	y	Meaning
`99`	0	Admin/session marker
`1`	1	Condition code 1
`2`	2	Condition code 2
`3`	3	Condition code 3
`5`	4	Condition code 5
`StartInstruction`	5	Instruction onset
`Eyeclosed`	6	Eyes-closed onset
`FixationBreak`	7	Fixation break
`EyeOpen`	8	Eyes-open onset
`EndInstruction`	9	Instruction offset
`88`	10	Response code 88
`6`	11	Condition code 6
`7`	12	Condition code 7
`8`	13	Condition code 8
`9`	14	Condition code 9
`23`	15	Code 23
`22`	16	Code 22
`21`	17	Code 21
`30`	18	Imagery code 30
`35`	19	Imagery code 35
`25`	20	Imagery code 25
`32`	21	Imagery code 32
`31`	22	Imagery code 31
`27`	23	Imagery code 27
`28`	24	Imagery code 28
`24`	25	Imagery code 24
`33`	26	Imagery code 33
`26`	27	Imagery code 26
`29`	28	Imagery code 29
`34`	29	Imagery code 34
## Data Quality Notes		

- Numerical event codes require mapping from dataset events.tsv or README.
- Small dataset (20 subjects); low statistical power for rare conditions.
- Apply bandpass filter (1-40 Hz) and artifact rejection prior to epoching.

References

- Reference: YOTO (You Only Think Once): An EEG Dataset for Tracking Spontaneous Cognitive Transitions and Multimodal Stimuli Responses in Resting-State and Task Phases

135. openneuro_ds006018 - Cognitive Electrophysiology in Socioeconomic Context in Adulthood: An EEG dataset

Dataset: `openneuro_ds006018` | Year: 2025 | URL: https://openneuro.org/datasets/ds006018
Category: High-level Mental | Subjects: 127 | Files (Completed): 357 | Channels: 31 | Sampling Rate: 500 Hz

Paradigm

A suite of standardized ERP tasks from the ERP CORE compendium (Kappenman et al. 2021) measuring neural correlates of perception, cognition, and action in adults in relation to socioeconomic status and ADHD symptoms. Tasks include N170 (face perception), MMN (mismatch negativity), N2pc (visual attention), P3 (cognitive updating), N400 (semantic processing), ERN (error monitoring), and LRP (lateralized readiness potential).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006018

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`S201`	40081	short	raw	ERP CORE stimulus code 201
`S 80`	30199	short	raw	ERP CORE stimulus code 80
`S212`	10400	short	raw	ERP CORE stimulus code 212
`S111`	9971	short	raw	ERP CORE stimulus code 111
`S222`	9017	short	raw	ERP CORE stimulus code 222
`S121`	8449	short	raw	ERP CORE stimulus code 121
`S 22`	8268	short	raw	ERP CORE stimulus code 22
`S 11`	8263	short	raw	ERP CORE stimulus code 11
`S 12`	8252	short	raw	ERP CORE stimulus code 12
`S 21`	8244	short	raw	ERP CORE stimulus code 21

Event ID	Count (total)	Type	Meta Level	Meaning
S 70	7977	short	raw	ERP CORE stimulus code 70
S202	6292	short	raw	ERP CORE stimulus code 202
S221	5197	short	raw	ERP CORE stimulus code 221
S122	4665	short	raw	ERP CORE stimulus code 122
S211	3707	short	raw	ERP CORE stimulus code 211

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: S201, S 80, S212, S111, S222, S121, S 22, S 11
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://openneuro.org/datasets/ds006018 DOI: https://doi.org/10.18112/openneuro.ds006018.v1.2.2

Primary Task 2: Publisher-defined BIDS task: Passive Auditory Oddball

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006018 DOI: https://doi.org/10.18112/openneuro.ds006018.v1.2.2

Primary Task 3: Publisher-defined BIDS task: Active Visual Oddball

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)

- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006018 DOI: https://doi.org/10.18112/openneuro.ds006018.v1.2.2

Normal Task 1: ERP CORE Multi-paradigm (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Multi-paradigm ERP CORE dataset. `boundary` is admin and excluded. Codes encode task x condition combinations per ERP CORE documentation.

Event	y	Meaning
`S 12`	0	ERP code 12
`S 22`	1	ERP code 22
`S 21`	2	ERP code 21
`S 11`	3	ERP code 11
`S201`	4	ERP code 201
`S202`	5	ERP code 202
`S221`	6	ERP code 221
`S122`	7	ERP code 122
`S212`	8	ERP code 212
`S222`	9	ERP code 222
`S111`	10	ERP code 111
`S121`	11	ERP code 121
`S211`	12	ERP code 211
`S112`	13	ERP code 112
`S 80`	14	ERP code 80
`S 70`	15	ERP code 70
`S180`	16	ERP code 180
`S 1`	17	ERP code 1
`S 25`	18	ERP code 25
`S 23`	19	ERP code 23
`S 24`	20	ERP code 24
`S 53`	21	ERP code 53
`S 43`	22	ERP code 43
`S 45`	23	ERP code 45
`S 44`	24	ERP code 44
`S 41`	25	ERP code 41
`S 13`	26	ERP code 13
`S 14`	27	ERP code 14

Event	y	Meaning
S 42	28	ERP code 42
## Data Quality Notes		

- Multi-paradigm dataset - participants completed multiple ERP CORE tasks; segment by task if needed.
- `boundary` is an administrative marker, excluded from target_events.
- Apply bandpass filter (0.1-40 Hz) and artifact rejection; baseline correct [-0.2, 0] s.

References

- Reference: `Isbell, E., Peters, A. N., Richardson, D. M., & Rodas De Len, N. E. (2025). Cognitive electrophysiology in socioeconomic context in adulthood. Scientific Data, 12(1), 19.`

136. openneuro_ds006040 - Sustained Attention Task (gradCPT) Dataset using simultaneous EEG-fMRI and DTI

Dataset: `openneuro_ds006040` | Year: 2025 | URL: https://openneuro.org/datasets/ds006040
Category: High-level Mental | Subjects: 28 | Files (Completed): 1064 | Channels: 64 | Sampling Rate: 5000 Hz

Paradigm

The dataset uses the Gradual Continuous Performance Task (gradCPT) to measure sustained attention via simultaneous EEG and fMRI recording. Participants detect rare city scenes (targets, S245) within a stream of common mountain scenes (standards, S155). Additional tasks include resting state, visual checkerboard stimulation, and mental imagery. MRI synchronization pulses (TR, Sync On) and cardiac (qrs) signals are also recorded.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006040

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`S155`	201922	short	raw	Standard stimulus (mountain scene, frequent)
`S245`	201110	short	raw	Target stimulus (city scene, rare)
`Sync On`	195242	admin	raw	MRI sync pulse onset
`qrs`	170358	admin	raw	Cardiac QRS complex
`TR`	106494	admin	raw	MRI TR repetition marker
`T 1`	52960	admin	raw	Timing marker
`S254`	813	short	raw	Response / button press
`[]`	15	admin	raw	Empty/null event

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `S155`, `S245`, `S254`

- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: ECOFF

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006040 DOI: https://doi.org/10.18112/openneuro.ds006040.v1.0.1

Primary Task 2: Publisher-defined BIDS task: IMAGON

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006040 DOI: https://doi.org/10.18112/openneuro.ds006040.v1.0.1

Primary Task 3: Publisher-defined BIDS task: CBON

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006040 DOI: https://doi.org/10.18112/openneuro.ds006040.v1.0.1

Normal Task 1: gradCPT Sustained Attention (long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Primary scientific contrast is S155 (standard) vs S245 (target) for gradCPT attention decoding. `Sync On`, `TR`, `qrs`, `T 1` are MRI/cardiac markers. Very high sampling rate (5000 Hz); downsample before processing.

Event	y	Meaning
`Sync On`	0	MRI sync pulse
`S155`	1	Standard (mountain)
`TR`	2	MRI TR marker
`S245`	3	Target (city)

Event	y	Meaning
qrs	4	Cardiac QRS
T 1	5	Timing marker
S254	6	Button press/response
[]	7	Null event
## Data Quality Notes		

- Very high sampling rate (5000 Hz); downsample to <=1000 Hz for most analyses.
- Sync On, TR, qrs are MRI/cardiac markers and should be excluded from stimulus-locked analysis.
- Simultaneous EEG-fMRI data requires MRI artifact correction (template subtraction or similar).

References

- Reference: Sustained Attention Task (gradCPT) Dataset using simultaneous EEG-fMRI and DTI

137. openneuro_ds006104 - EEG dataset for speech decoding

Dataset: `openneuro_ds006104` | Year: 2025 | URL: https://openneuro.org/datasets/ds006104
Category: High-level Mental | Subjects: 24 | Files (Completed): 80 | Channels: 62 | Sampling Rate: 2000 Hz

Paradigm

A phoneme discrimination task where participants listened to speech sounds - including single phonemes, phoneme pairs, and words - while undergoing transcranial magnetic stimulation (TMS) to test the role of speech motor cortex in auditory speech perception. Subjects provided button-press responses after each sound. The dataset supports decoding of speech perception from TMS-EEG.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006104

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`TMS`	29260	short	raw	TMS pulse delivery
`stimulus`	29260	short	raw	Auditory speech stimulus onset

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stimulus`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Phonemes

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)

- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006104 DOI: https://doi.org/10.18112/openneuro.ds006104.v1.0.1

Primary Task 2: Publisher-defined BIDS task: Words

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006104 DOI: https://doi.org/10.18112/openneuro.ds006104.v1.0.1

Primary Task 3: Publisher-defined BIDS task: Single phoneme

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006104 DOI: https://doi.org/10.18112/openneuro.ds006104.v1.0.1

Normal Task 1: TMS vs Stimulus Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Binary classification (TMS vs stimulus). TMS pulses produce large artifacts; apply TMS artifact rejection before epoching.

Event	y	Meaning
`TMS`	0	TMS pulse
`stimulus`	1	Speech stimulus onset
## Data Quality Notes		

- Very high sampling rate (2000 Hz); downsample to 500 Hz for most analyses.
- TMS pulses produce large EEG artifacts requiring specialized artifact removal.
- Apply bandpass filter (1-80 Hz) after TMS artifact correction.

References

- Reference: `Moreira et al. "An open-access EEG dataset for speech decoding: Exploring the role of articulation and coarticulation"`

138. openneuro_ds006142 - Essex EEG Movie Memory dataset

Dataset: openneuro_ds006142 | Year: 2025 | URL: https://openneuro.org/datasets/ds006142
Category: High-level Mental | Subjects: 27 | Files (Completed): 27 | Channels: 64 | Sampling Rate: 2048 Hz

Paradigm

Memory recognition task where participants watched 10-second movie clips and identified whether they remembered them from previous viewings, including time-stamping recognition instants. Clips were shown twice; the first watch (`startOfRememberedClipFirstWatch`, `startOfRecognisedClipFirstWatch`) established encoding, while the second watch (`startOfSecondWatch`) tested recognition. Participants clicked when they recognized clips (`firstRecognitionClick`, `recognitionClick`).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006142

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
recognitionClick	6675	short	raw	Participant clicks upon recognition
endOfClip	6094	short	raw	Movie clip ends
trialStart	4153	long	raw	Trial onset
trialEnd	4153	long	raw	Trial offset
startOfNotRecognisedClip	2212	long	raw	Clip onset - not recognized
startOfSecondWatch	1941	long	raw	Second viewing onset
firstRecognitionClick	1881	short	raw	First recognition click in second watch
startOfRememberedClipFirstWatch	1426	long	raw	First viewing onset - later remembered
startOfRecognisedClipFirstWatch	515	long	raw	First viewing onset - later recognized

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Movie Memory

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006142 DOI: https://doi.org/10.18112/openneuro.ds006142.v1.0.2

Normal Task 1: Movie Memory Recognition (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Key contrast is remembered vs not-recognized clips at first watch onset. High sampling rate (2048 Hz); consider downsampling.

Event	y	Meaning
`endOfClip`	0	Clip end
`trialStart`	1	Trial start
`trialEnd`	2	Trial end
`recognitionClick`	3	Recognition response
`startOfNotRecognisedClip`	4	Not-recognized clip onset
`startOfSecondWatch`	5	Second viewing onset
`firstRecognitionClick`	6	First recognition click
`startOfRememberedClipFirstWatch`	7	First watch - remembered
`startOfRecognisedClipFirstWatch`	8	First watch - recognized
## Data Quality Notes		

- High sampling rate (2048 Hz); downsample to 512 Hz for standard ERP analysis.
- Small dataset (27 subjects); limited statistical power.
- Apply bandpass filter (0.1-40 Hz) and artifact rejection prior to epoching.

References

- Paper: `Annotating, Understanding, and Predicting Long-term Video Memorability`

139. openneuro_ds006159 - Implicit Learning EEG (BioSemi)

Dataset: openneuro_ds006159 | Year: 2025 | URL: https://openneuro.org/datasets/ds006159
Category: High-level Mental | Subjects: 35 | Files (Completed): 35 | Channels: 69 | Sampling Rate: 1024 Hz

Paradigm

An experimental study investigating the neural correlates of implicit learning using a BioSemi EEG system. Participants underwent repeated exposure to structured sequences without explicit instructions to learn the underlying patterns. No trial-level event annotations are present in the dataset; the EEG is recorded as a continuous stream during the implicit learning protocol.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006159

Event Structure

No event markers detected (no_events). This dataset contains continuous EEG recordings without trial-level annotations.

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Event ID	Count (total)	Type	Meta Level	Meaning
no_events	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Publisher-defined BIDS task: Implicitlearn

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006159 DOI: https://doi.org/10.18112/openneuro.ds006159.v1.0.0

Normal Task 1: Continuous Segmentation (segmentation)

- Task Type: regression

- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5 s
- Label Route: `Annotation`
- Target Definition: N/A (no event markers; segmentation only)
- Notes: No trial-level events available; purely continuous EEG. Labels must be derived from external metadata (e.g., block condition labels from participants.tsv if available).

Data Quality Notes

- No event markers present; continuous-only processing.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to segmentation.

References

- Reference: `MNE-BIDS: Organizing electrophysiological data into the BIDS format and facilitating their analysis`

140. openneuro_ds006465 - 3M-CPSEED: EEG Dataset for Chinese Pinyin Production in Overt, Silent-Intended, and Imagined Speech

Dataset: `openneuro_ds006465` | Year: 2025 | URL: https://openneuro.org/datasets/ds006465
Category: High-level Mental | Subjects: 20 | Files (Completed): 84 | Channels: 33 | Sampling Rate: 500 Hz

Paradigm

Participants performed three modes of speech production - overt (spoken aloud), silent-intended (mouthed without sound), and imagined (mental speech without movement) - for specific Chinese Pinyin sounds including initials and finals. The dataset enables comparison of neural signatures across overt, silent, and imagined speech conditions. Each trial consisted of a visual cue (stimulus_presentation) followed by a production phase and a response confirmation. Numeric codes 1-10 encode specific phoneme or condition types.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006465

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stimulus_presentation`	42	short	raw	Visual cue onset prompting speech production
`1`	302	short	raw	Phoneme/condition code 1
`2`	200	short	raw	Phoneme/condition code 2
`3`	200	short	raw	Phoneme/condition code 3
`4`	200	short	raw	Phoneme/condition code 4
`5`	200	short	raw	Phoneme/condition code 5
`6`	200	short	raw	Phoneme/condition code 6
`7`	200	short	raw	Phoneme/condition code 7
`8`	200	short	raw	Phoneme/condition code 8

Event ID	Count (total)	Type	Meta Level	Meaning
9	200	short	raw	Phoneme/condition code 9
10	200	short	raw	Phoneme/condition code 10
response	84	short	raw	Participant response / confirmation

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: stimulus_presentation
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Imaginedspeech

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006465 DOI: https://doi.org/10.18112/openneuro.ds006465.v2.0.0

Normal Task 1: Speech Production Mode Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Numeric codes 1-10 correspond to specific Pinyin sounds or speech modes; decode from events.tsv. response is a motor response event. Some files show only numeric triggers; mixed annotation format across subjects.

Event	y	Meaning
stimulus_presentation	0	Visual cue for speech production
1	1	Phoneme/condition code 1
5	2	Phoneme/condition code 5
6	3	Phoneme/condition code 6
7	4	Phoneme/condition code 7
4	5	Phoneme/condition code 4
3	6	Phoneme/condition code 3
2	7	Phoneme/condition code 2

Event	y	Meaning
10	8	Phoneme/condition code 10
8	9	Phoneme/condition code 8
9	10	Phoneme/condition code 9
## Data Quality Notes		

- Some files show only numeric triggers while others include `stimulus_presentation`; mixed annotation format across sessions.
- Derivatives (preprocessed) files available alongside raw data.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection before epoching.

References

- Reference: `3M-CPSEED: An EEG-based Dataset for Chinese Pinyin Production in Overt, Silent-intended, and Imagined Speech`

141. openneuro_ds006647 - Poetry EEG Study

Dataset: `openneuro_ds006647` | Year: 2025 | URL: https://openneuro.org/datasets/ds006647
Category: High-level Mental | Subjects: 51 | Files (Completed): 4 | Channels: 70 | Sampling Rate: 512 Hz

Paradigm

Participants read and evaluated 210 short poetic (Haiku, Senryu) and non-poetic control texts on five subjective dimensions: Aesthetic Appeal, Vivid Imagery, Being Moved, Originality, and Creativity. EEG was recorded during reading using a 64-channel BioSemi system. The study investigates neural correlates of aesthetic and creative cognition during poetry processing. BioSemi EDF trigger codes (65280-65288) encode stimulus onset and condition types.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006647

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`65284`	852	short	raw	BioSemi trigger - stimulus/condition onset
`65281`	848	short	raw	BioSemi trigger - stimulus/condition onset
`65282`	848	short	raw	BioSemi trigger - stimulus/condition onset
`65283`	848	short	raw	BioSemi trigger - stimulus/condition onset
`65280`	848	short	raw	BioSemi trigger - stimulus/condition onset
`65285`	848	short	raw	BioSemi trigger - stimulus/condition onset
`65286`	848	short	raw	BioSemi trigger - stimulus/condition onset
`65287`	848	short	raw	BioSemi trigger - stimulus/condition onset

Event ID	Count (total)	Type	Meta Level	Meaning
65288	848	short	raw	BioSemi trigger - stimulus/condition onset
boundary	5	admin	raw	Segment boundary marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Readpoetry

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006647 DOI: https://doi.org/10.18112/openneuro.ds006647.v1.0.1

Normal Task 1: Poetry Condition Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: BioSemi trigger codes 65280-65288; decode from events.tsv to determine poetry vs. control mapping. boundary is an admin segment marker (exclude). Only 4 files present despite 51 subjects reported - dataset may be a subset or pilot.

Event	y	Meaning
65284	0	BioSemi condition code 65284
65281	1	BioSemi condition code 65281
65282	2	BioSemi condition code 65282
65283	3	BioSemi condition code 65283
65280	4	BioSemi condition code 65280
65285	5	BioSemi condition code 65285
65286	6	BioSemi condition code 65286
65287	7	BioSemi condition code 65287
65288	8	BioSemi condition code 65288

Event	y	Meaning
## Data Quality Notes		

- Only 4 completed files despite 51 subjects reported; this appears to be a partial dataset.
- `boundary` is a segment boundary marker and must be excluded from analysis.
- BioSemi EDF trigger codes 65280-65288 need decoding from events.tsv.

References

- Reference: `Poetry EEG Study`

142. openneuro_ds006648 - Poetry Assessment EEG Dataset 1

Dataset: `openneuro_ds006648` | Year: 2025 | URL: https://openneuro.org/datasets/ds006648
Category: High-level Mental | Subjects: 47 | Files (Completed): 47 | Channels: 70 | Sampling Rate: 512 Hz

Paradigm

Participants read and evaluated 210 short English-language texts including Haikus and Senryus on five subjective dimensions related to aesthetic and creative cognition: Aesthetic Appeal, Vivid Imagery, Being Moved, Originality, and Creativity. EEG was recorded during reading using a 64-channel BioSemi system (70 channels total including references). This is the first of two poetry datasets (companion to ds006647) with full N=47 subject coverage.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006648

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`65284`	9993	short	raw	BioSemi trigger - stimulus/condition D onset
`65281`	9964	short	raw	BioSemi trigger - stimulus/condition A onset
`65282`	9964	short	raw	BioSemi trigger - stimulus/condition B onset
`65283`	9964	short	raw	BioSemi trigger - stimulus/condition C onset
`65286`	47	short	raw	BioSemi trigger - stimulus/condition F onset
`65287`	47	short	raw	BioSemi trigger - stimulus/condition G onset
`65288`	47	short	raw	BioSemi trigger - stimulus/condition H onset

Event ID	Count (total)	Type	Meta Level	Meaning
65285	46	short	raw	BioSemi trigger - stimulus/condition E onset
65280	18	short	raw	BioSemi trigger - rare/practice condition

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Readpoetry

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006648 DOI: https://doi.org/10.18112/openneuro.ds006648.v1.0.0

Normal Task 1: Poetry Aesthetic Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: BioSemi EDF trigger codes 65280-65288; decode from events.tsv for exact poetry/non-poetry mapping. Codes 65281-65284 are highly frequent (~9964-9993 each); codes 65285-65288 appear rarely (~46-47 total). Code 65280 appears in only 18 files.

Event	y	Meaning
65284	0	BioSemi condition code 65284
65281	1	BioSemi condition code 65281
65282	2	BioSemi condition code 65282
65283	3	BioSemi condition code 65283
65286	4	BioSemi condition code 65286
65287	5	BioSemi condition code 65287
65288	6	BioSemi condition code 65288
65285	7	BioSemi condition code 65285

Event	y	Meaning
65280	8	BioSemi condition code 65280
## Data Quality Notes		

- Codes 65285-65288 and 65280 are rare events; consider excluding from classification due to imbalance.
- BioSemi trigger codes need decoding from events.tsv to determine poetry/non-poetry mapping.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to epoching.

References

- Reference: Poetry Assessment EEG Dataset 1

143. openneuro_ds006768 - Multiple Object Monitoring EEG

Dataset: openneuro_ds006768 | Year: 2025 | URL: https://openneuro.org/datasets/ds006768
Category: High-level Mental | Subjects: 30 | Files (Completed): 210 | Channels: 65 | Sampling Rate: 1000 Hz

Paradigm

Subjects completed a Multiple Object Monitoring (MOM) task requiring sustained visual attention to track multiple moving objects simultaneously. In each trial, a subset of objects is designated as targets at the start, then all objects move during a tracking period, and subjects report which objects were targets. EEG captures neural correlates of visual attention load and tracking accuracy. Events mark trial onset, target designation, and distractor appearances.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006768

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`event`	20384	short	raw	Generic trial event marker
`target`	11004	short	raw	Target object onset (object to be tracked)
`distractor`	11004	short	raw	Distractor object onset

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: MOM

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006768 DOI: https://doi.org/10.1101/2025.07.10.663816

Normal Task 1: Target vs Distractor Classification (epoch_by_event)

- Task Type: classification

- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Well-balanced binary contrast: target vs. distractor (11004 each). `event` is a generic trial marker. 210 files from 30 subjects (7 runs/subject on average).

Event	y	Meaning
`event`	0	Generic trial event marker
`target`	1	Target object to be tracked
`distractor`	2	Distractor object
## Data Quality Notes		

- 210 files from 30 subjects suggests ~7 runs per subject.
- `event` is a generic trial marker; prefer specific `target`/`distractor` events for classification.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to epoching.

References

- Reference: `Multiple Object Monitoring (EEG)`

144. openneuro_ds006840 - IACKD: Intention Action Conflict EEG-Hand Kinematics Dataset

Dataset: `openneuro_ds006840` | Year: 2025 | URL: https://openneuro.org/datasets/ds006840
Category: High-level Mental | Subjects: 128 | Files (Completed): 128 | Channels: 29 | Sampling Rate: 1024 Hz

Paradigm

This dataset investigates the neural correlates and hand kinematics associated with conflicts between intended and executed actions. In an intention-action conflict paradigm, participants are cued to perform one action but must sometimes execute a competing action, creating conflict between motor intention and execution. EEG is recorded alongside hand kinematic data during pre-movement planning (`premove`), execution (`execution`), and successful hit trials (`hit`).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006840

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`execution`	7032	short	raw	Motor execution onset
`hit`	7032	short	raw	Successful action completion marker
`premove`	7029	short	raw	Pre-movement preparation period onset

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Intention action congruency

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006840 DOI: https://doi.org/10.18112/openneuro.ds006840.v1.0.0

Normal Task 1: Motor Phase Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Well-balanced 3-class design (~7032 each). Hand kinematic data available alongside EEG for multimodal analysis. BrainVision format.

Event	y	Meaning
`premove`	0	Pre-movement intention/preparation
`execution`	1	Motor execution onset
`hit`	2	Successful trial completion
## Data Quality Notes		

- Consistent event structure (~7029-7032 events per type); well-controlled paradigm.
- Kinematic data channels (VEOG, HEOG, Trigger) should be excluded from EEG analysis.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to epoching.

References

- Reference: `IACKD: Intention Action Conflict EEG-Hand Kinematics Dataset`

145. openneuro_ds006848 - AlphaDirection1: EEG, ECG, PPG in the resting state and working memory for sequentially and simultaneously presented digits

Dataset: `openneuro_ds006848` | Year: 2025 | URL: https://openneuro.org/datasets/ds006848/versions/1.0.0
Category: High-level Mental | Subjects: 30 | Files (Completed): 52
Channels: 65 | Sampling Rate: 1000 Hz

Paradigm

This dataset studies the directional characteristics of brain alpha waves during resting state and working memory tasks. Participants completed a verbal working memory digit span task in two encoding modes: serial presentation (one digit is displayed at a time) and simultaneous presentation (an entire set of digits are displayed at once), followed by serial recall; before the experiment, a resting state (eyes open/eyes closed alternating) recording was included, and cartoon clips were used to separate different experimental segments. Data is recorded simultaneously with EEG, ECG and PPG.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006848/versions/1.0.0

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Encoding_DigitValue_0`	3163	short	raw	Sequence encoding: number 0 presents onset
`Encoding_DigitValue_1`	3134	short	raw	Sequence encoding: number 1 presents onset
`Encoding_DigitValue_2`	3077	short	raw	Sequence encoding: number 2 presents onset
`Encoding_DigitValue_3`	3124	short	raw	Sequence encoding: number 3 presents onset
`Encoding_DigitValue_4`	3164	short	raw	Sequence encoding: number 4 presents onset
`Encoding_DigitValue_5`	3104	short	raw	Sequence encoding: number 5 presents onset

Event ID	Count (total)	Type	Meta Level	Meaning
Encoding_DigitValue_6	3103	short	raw	Sequence encoding: number 6 presents onset
Encoding_DigitValue_7	3131	short	raw	Sequence encoding: number 7 presents onset
Encoding_DigitValue_8	3117	short	raw	Sequence encoding: number 8 rendering onset
Encoding_DigitValue_9	3131	short	raw	Sequence encoding: number 9 presents onset
Encoding_Set_Simultaneous	1495	short	raw	Simultaneous encoding: the entire set of numbers is presented at once onset
Digits_Retrieval	5960	short	raw	The recall phase begins (the subject begins to report verbally)
Baseline_2s	5956	short	raw	2 s before each trial, the beginning of the baseline segment
Retention_Fast	1499	long	raw	Fast delay hold period (sequence encoding, short delay)
Retention_FastDelay	1499	long	raw	Fast delay additional waiting period (sequence encoding)
Retention_Slow	1466	long	raw	Slow delay hold period (sequence encoding, long delay)
Retention_Simultaneous	1495	long	raw	Retention period after simultaneous encoding
Rest	209	rest	raw	Resting state segment start mark
Eyes_Closed	87	rest	raw	Close your eyes and start to rest
Eyes_Opened	88	rest	raw	Open your eyes and start to rest
Boundary	157	admin	raw	BIDS file boundary mark
Experiment_End	29	admin	raw	Experiment end mark
Start_Cartoon	22	admin	raw	Cartoon short film starts (intersegment interference)
End_Cartoon	22	admin	raw	End of cartoon short

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Rest

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006848/versions/1.0.0 DOI: https://doi.org/10.18112/openneuro.ds006848.v1.0.0

Primary Task 2: Publisher-defined BIDS task: Verbalwm

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006848/versions/1.0.0 DOI: https://doi.org/10.18112/openneuro.ds006848.v1.0.0

Normal Task 1: Task 1 (main task): coding mode two classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: The categories are seriously unbalanced (sequence ~31000 times vs. simultaneous ~1495 times), downstream needs to downsample to 1:1

Event	y	Meaning
`Encoding_DigitValue_0`	0	Sequence code (number 0)
`Encoding_DigitValue_1`	0	Sequence code (number 1)
`Encoding_DigitValue_2`	0	Sequence code (number 2)
`Encoding_DigitValue_3`	0	Sequence code (number 3)
`Encoding_DigitValue_4`	0	Sequence code (number 4)
`Encoding_DigitValue_5`	0	Sequence code (number 5)
`Encoding_DigitValue_6`	0	Sequence code (number 6)

Event	y	Meaning
Encoding_DigitValue_7	0	Sequence code (number 7)
Encoding_DigitValue_8	0	Sequence code (number 8)
Encoding_DigitValue_9	0	Sequence code (number 9)
Encoding_Set_Simultaneous	1	Simultaneous encoding (whole group)

Normal Task 2: Digital Identification (11-class multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Each number category ~3100 times, Encoding_Set_Simultaneous ~1495 times, the overall balance is relatively balanced; This is the actual configuration in task_config.json

Event	y	Meaning
Encoding_DigitValue_0	0	Number 0 (sequence condition)
Encoding_DigitValue_1	1	number 1
...	...	...
Encoding_DigitValue_9	9	Number 9
Encoding_Set_Simultaneous	10	Present the entire group simultaneously

Normal Task 3: Retention period type classification (4-class, long event)

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: This task needs to be configured separately (different from the epoch method of task 2). The current main entry of task_config.json does not contain this task.

Event	y	Meaning
Retention_Fast	0	Sequence encoding, short delay hold period
Retention_FastDelay	1	Sequence encoding, short delay and extra wait
Retention_Slow	2	Sequence encoding, long delay hold period
Retention_Simultaneous	3	Retention period after simultaneous encoding

Normal Task 4: Resting state: open/closed eyes classification (binary, long event)

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: Annotation

- Target Definition: Event-to-label mapping table below.
- Notes: Each file has about 1-2 switches (87/88 times in total), the amount of data is limited; `Rest` is the segment start mark and is not directly used for epoch

Event	y	Meaning
`Eyes_Closed`	0	Close eyes and rest
`Eyes_Opened`	1	Rest with eyes open
## Data Quality Notes		

- The ratio of sequence encoding vs. simultaneous encoding categories is about 20:1, and downsampling is required to do a fair binary classification evaluation.
- `Boundary` is the BIDS file boundary, which will appear at the beginning of each file and must be excluded from the epoch target
- Some subjects' files lack the `Eyes_Closed`/`Eyes_Opened` mark (only 22/30 subjects have resting eye state records)
- Sampling rate 1000 Hz, stage5 will downsample to 200 Hz

References

- Reference: `AlphaDirection1: EEG, ECG, PPG in the resting state and working memory for sequentially and simultaneously presented digits`

146. openneuro_ds007172 - EEG-Asymmetries Dataset

Dataset: `openneuro_ds007172` | Year: 2026 | URL: https://openneuro.org/datasets/ds007172
Category: High-level Mental | Subjects: 100 | Files (Completed): 501 | Channels: 32 | Sampling Rate: 500 Hz

Paradigm

Multi-task EEG battery investigating hemispheric asymmetries across resting state and four cognitive categorization tasks: emotion recognition (face stimuli with emotional valence), language comprehension, face perception (identity discrimination), and visual discrimination (house images). The dataset examines relationships between N1 lateralization and alpha asymmetry across task domains. BrainVision trigger codes (Stimulus/S1xx and S2xx families) encode stimulus conditions per task.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds007172

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus/S111`	12800	long	raw	Emotion/language task condition S111
`Stimulus/S223`	12800	long	raw	Emotion/language task condition S223
`Stimulus/S212`	12800	long	raw	Emotion/language task condition S212
`Stimulus/S214`	12800	long	raw	Emotion/language task condition S214
`Stimulus/S211`	12800	long	raw	Emotion/language task condition S211
`Stimulus/S123`	12800	long	raw	Emotion/language task condition S123
`Stimulus/S114`	12800	long	raw	Emotion/language task condition S114
`Stimulus/S112`	12800	long	raw	Emotion/language task condition S112
`Stimulus/S222`	12000	long	raw	Emotion/language task condition S222
`Stimulus/S113`	12000	long	raw	Emotion/language task condition S113
`Stimulus/S121`	12000	long	raw	Emotion/language task condition S121

Event ID	Count (total)	Type	Meta Level	Meaning
Stimulus/S122	12000	long	raw	Emotion/language task condition S122
Stimulus/S124	12000	long	raw	Emotion/language task condition S124
Stimulus/S221	12000	long	raw	Emotion/language task condition S221
Stimulus/S213	12000	long	raw	Emotion/language task condition S213
Stimulus/S224	12000	long	raw	Emotion/language task condition S224
Stimulus/S217	11998	long	raw	Face task condition S217
Stimulus/S218	11998	long	raw	Face task condition S218
Stimulus/S118	11998	long	raw	Face task condition S118
Stimulus/S117	11998	long	raw	Face task condition S117
Stimulus/S227	11998	long	raw	Face task condition S227
Stimulus/S228	11998	long	raw	Face task condition S228
Stimulus/S127	11998	long	raw	Face task condition S127
Stimulus/S128	11998	long	raw	Face task condition S128
Stimulus/S 21	11998	long	raw	Houses/visual task condition S21
Stimulus/S 11	11998	long	raw	Houses/visual task condition S11
Stimulus/S 22	11998	long	raw	Houses/visual task condition S22
New Segment/	501	admin	raw	Segment boundary marker
Comment/actiCAP Data On	383	admin	raw	Hardware status marker
Comment/actiCAP USB Power On	134	admin	raw	Hardware status marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus/S111`, `Stimulus/S223`, `Stimulus/S212`, `Stimulus/S214`, `Stimulus/S211`, `Stimulus/S123`, `Stimulus/S114`, `Stimulus/S112`

- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Houses

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds007172 DOI: https://doi.org/10.1080/1357650x.2025.2591660

Primary Task 2: Publisher-defined BIDS task: Words

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds007172 DOI: https://doi.org/10.1080/1357650x.2025.2591660

Primary Task 3: Publisher-defined BIDS task: Emotions

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds007172 DOI: https://doi.org/10.1080/1357650x.2025.2591660

Normal Task 1: Multi-Condition EEG Asymmetry (long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 5 task files per subject (emotions, faces, houses, language, rest). `New Segment/`, `Comment/actiCAP Data On`, `Comment/actiCAP USB Power On` are hardware/admin markers; exclude from stimulus analysis.

Event	y	Meaning
`Comment/actiCAP Data On`	0	Hardware marker
`Comment/actiCAP USB Power On`	1	Hardware power marker
`Stimulus/S111`	2	Condition S111
`Stimulus/S223`	3	Condition S223

Event	y	Meaning
Stimulus/S212	4	Condition S212
Stimulus/S214	5	Condition S214
Stimulus/S211	6	Condition S211
Stimulus/S123	7	Condition S123
Stimulus/S114	8	Condition S114
Stimulus/S112	9	Condition S112
Stimulus/S222	10	Condition S222
Stimulus/S113	11	Condition S113
Stimulus/S121	12	Condition S121
Stimulus/S122	13	Condition S122
Stimulus/S124	14	Condition S124
Stimulus/S221	15	Condition S221
Stimulus/S213	16	Condition S213
Stimulus/S224	17	Condition S224
Stimulus/S217	18	Condition S217
Stimulus/S218	19	Condition S218
Stimulus/S118	20	Condition S118
Stimulus/S117	21	Condition S117
Stimulus/S227	22	Condition S227
Stimulus/S228	23	Condition S228
Stimulus/S127	24	Condition S127
Stimulus/S128	25	Condition S128
Stimulus/S 21	26	Condition S21
Stimulus/S 11	27	Condition S11
Stimulus/S 22	28	Condition S22
## Data Quality Notes		

- 501 files from 100 subjects includes 5 task types per subject.
- `New Segment/` and all `Comment/` markers are administrative; never use as classification targets.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to epoching.

References

- Reference: `Hemispheric asymmetries in the EEG: Is there an association between N1 lateralization and alpha asymmetryx`

147. other_CockPartDataset - CockPart Multi-Paradigm EEG Dataset

Dataset: `unknown_CockPartDataset` | Year: N/A | URL: N/A
Category: High-level Mental | Subjects: varies by paradigm | Files (Completed): 1590 (Case B kernel) | Channels: 128 | Sampling Rate: 128 Hz (N400/Natural Speech) / 512 Hz (Speech in Noise)

Paradigm

A multi-paradigm EEG corpus comprising four experimental subdatasets, all recorded from a 128-channel EEG cap. The four paradigms are:

1. N400: Subjects read or heard sentence contexts ending in high-cloze (predictable) or low-cloze (unpredictable) words; pre-epoched EEG trials at 128 Hz stored as `eegData_hiCloze` and `eegData_loCloze` arrays (128 channels x 103 timepoints x 150 trials) for 9 subjects.
2. Natural Speech: Subjects listened to natural continuous speech; raw continuous EEG stored at 128 Hz for 19 subjects (multiple runs per subject, up to ~420 run files total).
3. Natural Speech - Reverse: Subjects listened to time-reversed (unnatural) speech as a control condition; raw continuous EEG at 128 Hz for 10 subjects (200 run files).
4. Speech in Noise (SiN): Subjects listened to speech presented with background noise in audio-only (_a_) and video-only (_v_) modality conditions; raw continuous EEG at 512 Hz for 21 subjects (315 audio + 315 video files = 630 total SiN files).

The Case B kernel dispatches loading to the appropriate paradigm-specific method based on the file path.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: N/A (local/private dataset description)

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`N400_hiCloze`	150/subject x 9 = 1350	long	raw	N400 paradigm: high-cloze (predictable) word epoch
`N400_loCloze`	150/subject x 9 = 1350	long	raw	N400 paradigm: low-cloze (unpredictable) word epoch
`NaturalSpeech`	1/file x ~420	long	raw	Natural speech paradigm: whole-run annotation
`NaturalSpeechReverse`	1/file x ~200	long	raw	Reversed speech paradigm: whole-run annotation

Event ID	Count (total)	Type	Meta Level	Meaning
SiN_audio	1/file x 315	long	raw	Speech-in-Noise audio-only condition
SiN_video	1/file x 315	long	raw	Speech-in-Noise video-only condition

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Case B kernel: N400 epoch arrays are concatenated into a single continuous raw signal; each epoch onset is annotated individually. Natural Speech and SiN paradigms provide single whole-recording annotations per file.

Tasks

Normal Task 1: N400 Language ERP - High-Cloze vs. Low-Cloze (epoch_by_event)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = 0.0 s, tmax = 0.8 s (= 103/128 Hz; matches pre-epoched trial length), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Filter to N400 paradigm files (N400/EEG/Subject{N}.mat). Case B kernel concatenates hiCloze (150) then loCloze (150) epochs; epoch window (0.8 s) matches the original pre-epoched length. sfreq = 128 Hz.

Event	y	Meaning
N400_hiCloze	0	High-cloze (predictable) word - N400 attenuated
N400_loCloze	1	Low-cloze (unpredictable) word - N400 enhanced

Normal Task 2: Natural Speech Auditory Processing - Speech vs. Reversed Speech (epoch_by_long_event)

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5
- Epoch Parameters: tmin = 0.0 s, overlap = 0.0 s, use full recording duration from annotation, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Filter to Natural Speech and Natural Speech - Reverse paradigm files. sfreq = 128 Hz. Multiple runs per subject; run files are independent.

Event	y	Meaning
NaturalSpeech	0	Listening to natural (forward) speech
NaturalSpeechReverse	1	Listening to reversed (backward) speech

Normal Task 3: Speech-in-Noise Modality - Audio vs. Video (epoch_by_long_event)

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5

- Epoch Parameters: tmin = 0.0 s, overlap = 0.0 s, use full recording duration from annotation, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Filter to Speech in Noise paradigm files. sfreq = 512 Hz. Condition (audio/video) inferred from filename suffix (_a_ or _v_).

Event	y	Meaning
`SiN_audio`	0	Speech-in-Noise audio-only condition
`SiN_video`	1	Speech-in-Noise video-only condition

Normal Task 4: N400 cloze-condition decoding (high vs low cloze)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: `N400_hiCloze` vs `N400_loCloze` trial labels from the N400 subset.
- Evidence: Primary task inferred from internal dataset documentation only; external publication/reference is not yet available.
- Notes: Demoted from Primary Task because no external DOI/URL source is available.

Data Quality Notes

- Case B kernel: `.mat` files contain pre-epoched arrays or raw continuous EEG depending on the paradigm; paradigm is inferred from the directory structure in the file path.
- Channel names in reconstructed raw are generic (`EEG001-EEG128`); no electrode layout metadata is provided.
- Variable sampling rates across paradigms: N400 and Natural Speech = 128 Hz; Speech in Noise = 512 Hz. Do not mix paradigms without resampling.
- Dataset origin and publication unknown; provenance requires verification before publication.
- No age or sex information available.

References

- Reference: Unknown provenance. Multi-paradigm EEG corpus (CockPart Dataset). No associated publication identified.

148. other_seed - SJTU Emotion EEG Dataset (SEED)

Dataset: `other_seed` | Year: 2015 | URL: https://bcmi.sjtu.edu.cn/home/seed/
Category: High-level Mental | Subjects: 15 | Files (Completed): 81 | Channels: 62 | Sampling Rate: 1000 Hz

Paradigm

The SEED (SJTU Emotion EEG Dataset) was collected from 15 subjects who watched 15 emotional film clips (positive, neutral, negative) across three sessions (Zheng & Lu, 2015). EEG was recorded from 62 channels using an ESI NeuroScan system (Neuroscan cap) at 1000 Hz. Fifteen emotional video clips (~4 minutes each) were shown in each session, with sessions repeated on different days (up to 3 sessions per subject). Valence labels (+1 positive, 0 neutral, -1 negative) for each clip are stored in separate `*_label.mat` files; they are not embedded in the `.cnt` EEG recordings. The kernel does not extract emotion labels from EEG annotations; labels must be loaded externally.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://bcmi.sjtu.edu.cn/home/seed/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`0`	~81	admin	raw	File-level marker from `.cnt` format (no experimental meaning)
`255`	rare	admin	raw	End-of-file or reset marker in `.cnt` format

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Critical: Emotion valence labels (+1, 0, -1) are stored in companion `*_label.mat` files, NOT in the EEG event annotations. Events `0` and `255` are format-level markers with no experimental significance.

Tasks

Primary Task 1: Emotion recognition from EEG (positive/neutral/negative)

- Task Type: classification
- Epoch Method: `epoch_by_segmentation_hdf5` (or protocol-aligned event windows)
- Epoch Parameters: segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Valence class labels (positive/neutral/negative) assigned by film-clip protocol.

- Evidence: SEED is a standard EEG emotion-recognition benchmark with three valence classes. Source: https://bcmi.sjtu.edu.cn/home/seed/ DOI: https://doi.org/10.1109/tamd.2015.2431497

Normal Task 1: Emotion Valence Classification - 3-Class (epoch_by_segmentation + external labels)

- Task Type: classification
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: length = 4.0 s, overlap = 2.0 s (within each video clip window)
- Label Route: `Annotation`
- Target Definition: N/A from EEG annotations - apply labels post-hoc from `*_label.mat`:
- Notes: Segment the EEG into fixed windows during each video clip period. Map each epoch to the clip's valence label from the corresponding `*_label.mat` file. The kernel records subject ID and session ID in the description field to help align with label files.

Label	y	Meaning
`+1`	0	Positive emotion
`0`	1	Neutral emotion
`-1`	2	Negative emotion

Normal Task 2: Binary Emotion Classification - Positive vs. Negative (epoch_by_segmentation)

- Task Type: classification
- Epoch Method: `epoch_by_segmentation`
- Epoch Parameters: Needs verification
- Label Route: `Annotation`
- Target Definition: Needs verification.
- Notes: Use positive (y=0) and negative (y=2) labels only; discard neutral trials.

Data Quality Notes

- Emotion labels are not embedded in EEG files; they must be loaded from companion `*_label.mat` files and aligned with EEG epochs by trial order.
- EEG events `0` and `255` are file-format markers; exclude from all analyses.
- 3 sessions per subject on different days; within-session and cross-session analyses are common.
- 15 video clips per session x 3 sessions x 15 subjects = 675 trials total.
- NeuroScan `.cnt` format; 62-channel standard 10-20 EEG montage.

References

- Reference: Zheng W-L, Lu B-L (2015). Investigating Critical Frequency Bands and Channels for EEG-based Emotion Recognition with Deep Neural Networks. IEEE Trans. Autonomous Mental Development, 7(3), 162-175. https://bcmi.sjtu.edu.cn/home/seed/

149. physionet_auditoryeeg - Auditory EEG Dataset (Biometric Identification)

Dataset: `physionet_auditoryeeg` | Year: 2021 | URL: https://physionet.org/content/auditory-eeg/1.0.0/
Category: High-level Mental | Subjects: 19 | Files (Completed): 205 | Channels: 13 | Sampling Rate: 200 Hz

Paradigm

Nineteen subjects (s01-s20, one subject absent) aged 21-31 participated in a biometric EEG identification study using resting-state and auditory stimulus paradigms (Trujillo et al., 2021). EEG was recorded using an OpenBCI Cyton board (13 channels, gold-cup electrodes at T7, F8, Cz, P4 and surrounding positions). Each subject completed multiple recording sessions across different experimental conditions: two resting-state conditions (eyes open, eyes closed), eyes-open with noise isolation, and six auditory stimulus conditions (native song, non-native song, neutral music - via in-ear headphones or bone-conduction headphones). Each recording is labeled by experiment code (ex01-ex12) encoded in the filename. Files from subject 5 (ex05) lack structured event codes and retain raw experiment codes as annotations.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: questionnaire
> Web Reference Used for Decision: https://physionet.org/content/auditory-eeg/1.0.0/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`resting_eyes_open`	~50	long	raw	Resting state with eyes open (ex01)
`resting_eyes_closed`	~25	long	raw	Resting state with eyes closed (ex02)
`resting_eyes_open_noise_isolation`	~50	long	raw	Eyes open with acoustic isolation (ex04, ex06)
`auditory_native_song_in_ear`	~25	long	raw	Native-language song via in-ear headphones (ex07)
`auditory_nonnative_song_in_ear`	~25	long	raw	Non-native language song via in-ear headphones (ex08)
`auditory_neutral_music_in_ear`	~25	long	raw	Neutral instrumental music via in-ear headphones (ex09)
`auditory_native_song_bone`	~25	long	raw	Native song via bone-conduction headphones (ex10)

Event ID	Count (total)	Type	Meta Level	Meaning
auditory_nonnative_song_bone	~25	long	raw	Non-native song via bone-conduction headphones (ex11)
ex05	~19	long	raw	Uncoded experiment (raw experiment code, exclude from classification)

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Each annotation spans the entire recording file. Counts are approximate.

MISC Label Summary

- Route: misc
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: epoch_by_segmentation_hdf5 or epoch_by_long_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://physionet.org/content/auditory-eeg/1.0.0/ DOI: https://doi.org/10.13026/ps31

Normal Task 1: Auditory Condition Classification (epoch_by_long_event)

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5
- Epoch Parameters: tmin = 0.0 s, tmax = 5.0 s, overlap = 2.5 s, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Exclude ex05 files (uncoded). For a simpler 3-class task, group by stimulus type (native/non-native/neutral) ignoring headphone type.

Event	y	Meaning
auditory_native_song_in_ear	0	Native song, in-ear
auditory_nonnative_song_in_ear	1	Non-native song, in-ear
auditory_neutral_music_in_ear	2	Neutral music, in-ear
auditory_native_song_bone	3	Native song, bone-conduction
auditory_nonnative_song_bone	4	Non-native song, bone-conduction

Normal Task 2: Resting-State vs. Auditory Stimulus (epoch_by_long_event)

- Task Type: classification

- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 5.0 s, overlap = 2.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`resting_eyes_open`	0	Resting state
`resting_eyes_closed`	0	Resting state
`auditory_native_song_in_ear`	1	Any auditory condition
`auditory_nonnative_song_in_ear`	1	Any auditory condition
`auditory_neutral_music_in_ear`	1	Any auditory condition
`auditory_native_song_bone`	1	Any auditory condition
`auditory_nonnative_song_bone`	1	Any auditory condition
## Data Quality Notes		

- Only 13 EEG channels (non-standard OpenBCI placement); spatial coverage is limited.
- `ex05` files (subject 5 recordings in some conditions) retain raw experiment codes and should be excluded from condition-labeled classification.
- Primary use case is biometric identification (same person across sessions), not condition classification; adapt label source accordingly.
- Some subjects may be missing recordings for certain experiment codes.

References

- Reference: Trujillo LT et al. (2021). EEG recordings for biometric identification. Physionet. https://physionet.org/content/auditory-eeg/1.0.0/

150. physionet_eegmat - EEG During Mental Arithmetic Task

Dataset: physionet_eegmat | Year: 2020 | URL: https://physionet.org/content/eegmat/1.0.0/
Category: High-level Mental | Subjects: 36 | Files (Completed): 72 | Channels: 21 | Sampling Rate: 500 Hz

Paradigm

Thirty-six healthy subjects (Subject00-Subject35, ages 16-26, predominantly female) completed a mental arithmetic task while EEG was recorded from 21 channels using a Neurocom 23-channel system with Ag/AgCl electrodes (Zyma et al., 2019). Each subject contributed two files: a background resting-state recording (suffix `_1.edf`) and a mental arithmetic task recording (suffix `_2.edf`). During the mental arithmetic task, subjects performed serial subtraction (e.g., counting backwards by 7s) while EEG was recorded. A separate `Count quality` field in `subject-info.csv` rates the subject's arithmetic performance as Good or Bad, providing a behavioral quality label.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://physionet.org/content/eegmat/1.0.0/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Background EEG;Count Quality: Good`	27	long	raw	Resting-state recording, subject's arithmetic quality was Good
`Background EEG;Count Quality: Bad`	9	long	raw	Resting-state recording, subject's arithmetic quality was Bad
`Mental Arithmetic Task EEG;Count Quality: Good`	27	long	raw	Mental arithmetic recording, quality Good
`Mental Arithmetic Task EEG;Count Quality: Bad`	9	long	raw	Mental arithmetic recording, quality Bad

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Each annotation spans the entire recording. Counts are approximate (36 subjects x 2 files = 72 total; Good/Bad split estimated from subject distribution).

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://physionet.org/content/eegmat/1.0.0/ DOI: https://doi.org/10.13026/C2JQ1P

Normal Task 1: Mental Arithmetic vs. Resting State (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 5.0 s, overlap = 2.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Annotation spans the entire recording - use `epoch_by_long_event_hdf5` with sliding window. The event description encodes both task type and count quality; parse the prefix before the semicolon to extract the task label.

Event	y	Meaning
`Background EEG;Count Quality: Good`	0	Resting-state EEG (good quality)
`Background EEG;Count Quality: Bad`	0	Resting-state EEG (poor quality)
`Mental Arithmetic Task EEG;Count Quality: Good`	1	Mental arithmetic EEG (good quality)
`Mental Arithmetic Task EEG;Count Quality: Bad`	1	Mental arithmetic EEG (poor quality)

Normal Task 2: Mental Arithmetic Quality Prediction (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 5.0 s, overlap = 2.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use only arithmetic task files (`Mental Arithmetic Task EEG;*`); separate by `Count Quality: Good` (y=1) vs `Count Quality: Bad` (y=0).
- Notes: Predicts arithmetic performance quality from EEG. Class imbalance likely (more Good than Bad performers).

Data Quality Notes

- Two files per subject (`_1.edf` = background, `_2.edf` = task); pair them by Subject ID.
- Count quality (Good/Bad) is embedded in the annotation description after the semicolon; always parse carefully.
- ECG channel present (channel `A2-A1`) in some recordings; exclude from EEG feature extraction.
- Small dataset (36 subjects x 2 = 72 files); limited generalization.

References

- Reference: Zyma I, Tukaev S, Seleznov I, Kiyono K, Popov A, Chernykh M, Shpenkov O (2019). Electroencephalograms during mental arithmetic task performance. Data, 4(1), 14.

https://physionet.org/content/eegmat/1.0.0/

151. zenodo_3618205 - Selective Auditory Attention EEG Dataset (Normal-Hearing and Hearing-Impaired)

Dataset: `zenodo_3618205` | Year: 2020 | URL: https://zenodo.org/records/3618205
Category: High-level Mental | Subjects: 44 | Files (Completed): 74 | Channels: 73 | Sampling Rate: 512 Hz

Paradigm

Forty-four participants (22 normal-hearing, 22 hearing-impaired) underwent EEG recording in three tasks (Fuglsang et al., 2020): (1) selective auditory attention - two-talker competing speech; attend to one of two simultaneously presented speakers; (2) MMN - mismatch negativity; passive listening to a standard tone sequence with occasional deviant tones; (3) resting state - eyes open and closed. EEG was recorded with BioSemi ActiveTwo (64 channels + reference + auxiliary = ~73 total channels, 512 Hz). Nineteen of the 44 subjects also had in-ear EEG recorded. Event annotations are stored in BIDS-format `_events.tsv` sidecar files.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: questionnaire
> Web Reference Used for Decision: https://zenodo.org/records/3618205

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`attend_left`	varies	long	raw	Subject attends to the left-ear speaker (selective attention trial)
`attend_right`	varies	long	raw	Subject attends to the right-ear speaker (selective attention trial)
(MMN deviant events)	varies	short	raw	Deviant tone stimulus onset (MMN paradigm)
(resting state marker)	varies	rest	raw	Resting state block onset

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Exact event codes from BIDS `_events.tsv` sidecars. Selective attention trial labels and MMN deviant markers are both present; parse task type from filename.

MISC Label Summary

- Route: `misc`
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://zenodo.org/records/3618205 DOI: https://doi.org/10.5281/zenodo.3618205

Normal Task 1: Auditory Attention Decoding - Left vs. Right (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 60.0 s (or full trial duration), overlap = 30.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Use only files from the selective attention task. MMN and resting state files have different event structures.

Event	y	Meaning
`attend_left`	0	Attend to left-ear speaker
`attend_right`	1	Attend to right-ear speaker

Normal Task 2: Normal-Hearing vs. Hearing-Impaired Group Comparison (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: As in Task 1, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Needs verification.
- Notes: Group labels (normal-hearing / hearing-impaired) must be derived from subject ID and companion demographics file. Primary comparison is neural tracking of attended speech across the two groups.

Data Quality Notes

- Three distinct task types (selective attention, MMN, rest); always filter files by task type before analysis.
- 19 subjects also have in-ear EEG recordings; these appear as additional channels or separate files.
- Hearing-impaired subjects may have different audiological profiles; audiogram data is available in the dataset.

References

- Reference: Fuglsang SA et al. (2020). Midfrontal slow waves causally mediate the effect of pre-target attention on visual task performance. bioRxiv. Zenodo. https://zenodo.org/records/3618205

152. zenodo_4518754 - Ultra High-Density 256-Channel EEG AAD Dataset (Subset)

Dataset: `zenodo_4518754` | Year: 2021 | URL: https://zenodo.org/records/4518754
Category: High-level Mental | Subjects: 13 | Files (Completed): 156 | Channels: 256 | Sampling Rate: 1000 Hz

Paradigm

Thirteen subjects listened to two simultaneously presented Dutch stories (left vs. right ear) and were asked to attend to one speaker while ignoring the other (auditory attention decoding, AAD). EEG was recorded from 256 channels (BioSemi ActiveTwo ultra-high-density, Ag/AgCl) at 1000 Hz. Stories were presented via insert earphones at 60 dBA, with 180 deg spatial separation (left vs. right). Each subject completed multiple trials per session; each recording file corresponds to one trial labeled by attended direction (L/R) encoded in the filename (`S{N}_AAD_{trial}{L/R}.dap`). The kernel creates a single whole-trial `attend_left` or `attend_right` annotation per file.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://zenodo.org/records/4518754

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`attend_left`	~78	long	raw	Subject attends to the left-ear story for the entire recording
`attend_right`	~78	long	raw	Subject attends to the right-ear story for the entire recording

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Each file has exactly one annotation spanning the entire recording (~6 minutes per trial).

Tasks

Primary Task 1: Auditory attention decoding (attend left vs right)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Whole-trial attention direction labels (`attend_left` vs `attend_right`).

- Evidence: Dataset release describes high-density EEG auditory attention decoding as the primary objective. Source: https://zenodo.org/records/4518754 DOI: https://doi.org/10.5281/zenodo.4518754

Normal Task 1: Auditory Attention Decoding - Left vs. Right (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 10.0 s, overlap = 5.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only `.dap` header files are processed by the kernel; `.dat` and `.rs3` auxiliary files are skipped. Numeric event codes (1000001, 100255, 800000, 800001) from the stimulus system may also appear; use the whole-recording `attend_*` label for the primary target.

Event	y	Meaning
`attend_left`	0	Attend to left-ear speaker
`attend_right`	1	Attend to right-ear speaker
## Data Quality Notes		

- Ultra-high-density 256-channel EEG; spatial filtering and source analysis are computationally intensive.
- High sampling rate (1000 Hz); consider downsampling to 128 or 64 Hz for typical AAD decoding.
- Stimulus audio files are required for stimulus-reconstruction AAD methods; check availability.
- Only `.dap` files are EEG; auxiliary `.dat / .rs3` files are skipped by the kernel.

References

- Reference: Ultra high-density 255-channel EEG-AAD dataset. Zenodo. https://zenodo.org/records/4518754

153. zenodo_dtu - DTU Auditory Attention Decoding Dataset

Dataset: `zenodo_dtu` | Year: 2018 | URL: https://zenodo.org/records/1199011
Category: High-level Mental | Subjects: 18 | Files (Completed): 18 | Channels: 73 | Sampling Rate: 512 Hz

Paradigm

Eighteen subjects (S1-S18) participated in an auditory attention decoding (AAD) task in which two competing speakers were presented simultaneously and subjects were asked to attend to one speaker (Fuglsang et al., 2018). EEG was recorded from 64 channels (BioSemi ActiveTwo, 512 Hz) plus additional auxiliary channels (total 73). Each subject's recording is stored as a single MATLAB `.mat` file containing EEG data, stimulus onsets (`data.stimu`), and attended speaker labels (`data.attended`). The kernel extracts per-trial onset times and attended speaker indices to create trial-level annotations.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://zenodo.org/records/1199011

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`attend_speaker_1`	varies	long	raw	Subject attends to speaker 1 for the trial duration
`attend_speaker_2`	varies	long	raw	Subject attends to speaker 2 for the trial duration

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Note: The status_summary indicates that `stimu` and `attended` fields may be missing in some versions of the dataset (Needs verification:Needs verification); verify field availability before processing.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stimu`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Auditory attention decoding to competing speakers

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Attended speaker label per trial (`attend_speaker_1` vs `attend_speaker_2`).
- Evidence: DTU AAD dataset and associated paper explicitly benchmark attended-speaker decoding.
Source: https://zenodo.org/records/1199011 DOI: https://doi.org/10.5281/zenodo.1199011

Normal Task 1: Auditory Attention Decoding - Speaker 1 vs. Speaker 2 (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, use trial duration from annotation, overlap = 0.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Annotations are per-trial; trial boundaries from `data.stimu` onset times. If the dataset's `.mat` file is missing `stimu` or `attended` fields, the kernel will produce `unknown` annotations.

Event	y	Meaning
`attend_speaker_1`	0	Attend to speaker 1
`attend_speaker_2`	1	Attend to speaker 2
## Data Quality Notes		

- MATLAB `.mat` field names (`data.stimu`, `data.attended`) must be present; verify before processing.
- One file per subject (18 files total); each file contains all trials for that subject.
- Stimulus audio files (speech signals) are required for full stimulus-reconstruction AAD decoding.

References

- Reference: Fuglsang SA et al. (2018). Noise-robust cortical tracking of attended speech in real-world acoustic scenes. NeuroImage, 156, 435-444. https://zenodo.org/records/1199011

154. zenodo_kul - KU Leuven Auditory Attention Decoding Dataset

Dataset: `zenodo_kul` | Year: 2020 | URL: https://zenodo.org/records/4004271
Category: High-level Mental | Subjects: 15 | Files (Completed): 15 (Case B kernel) | Channels: 64 | Sampling Rate: 128 Hz

Paradigm

Fifteen subjects performed a dichotic listening auditory attention decoding (AAD) task (Biesmans et al., 2017). Two competing story narratives were presented simultaneously, one to each ear, and subjects were instructed to attend to one. EEG was recorded from 64 channels (BioSemi ActiveTwo, standard 10-20 layout) at 128 Hz. Each MATLAB `.mat` file contains 20 trials (10 attended-left + 10 attended-right), stored as a Python list of trial dictionaries. The Case B kernel concatenates all 20 trials from each file into a single continuous raw signal and creates per-trial annotations indicating the attended ear.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://zenodo.org/records/4004271

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`attended_left`	150 (10/subject x 15 subjects)	long	raw	Subject attends to the left-ear speaker
`attended_right`	150 (10/subject x 15 subjects)	long	raw	Subject attends to the right-ear speaker

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Case B kernel: 20 trials (each ~62.5 s at 128 Hz) concatenated into one continuous raw per file.

Tasks

Primary Task 1: Dichotic auditory attention decoding (left vs right ear)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Attended ear/speaker label in dichotic listening trials.
- Evidence: KUL AAD dataset is designed for supervised decoding of attended speech stream. Source: https://zenodo.org/records/4004271 DOI: https://doi.org/10.5281/zenodo.4004271

Normal Task 1: Auditory Attention Decoding - Left vs. Right Ear (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, use trial duration from annotation, overlap = 0.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Case B kernel uses `scipy.io.loadmat(simplify_cells=True)` and a custom `load()` method. Annotation durations match individual trial lengths. Balanced design: 10 trials per class per subject.

Event	y	Meaning
`attended_left`	0	Attended ear: left
`attended_right`	1	Attended ear: right
## Data Quality Notes		

- Low sampling rate (128 Hz); limits high-frequency analysis but is standard for EEG-AAD.
- 15 subjects only; relatively small cohort for robust model evaluation.
- No age or sex information available in the public release.
- Each file contains 20 trials; the Case B kernel creates discontinuities at trial boundaries (artificial concatenation).

References

- Reference: Biesmans W et al. (2017). Auditory-Inspired Speech Envelope Extraction Methods for Auditory Attention Detection in N-of-1 Trials. IEEE Trans. Neural Syst. Rehabil. Eng., 25(5), 428-437. https://zenodo.org/records/4004271

155. zenodo_saa - Spatial Auditory Attention EEG Dataset

Dataset: `zenodo_saa` | Year: 2019 | URL: https://zenodo.org/records/3357164
Category: High-level Mental | Subjects: 18 | Files (Completed): 18 | Channels: 41 | Sampling Rate: 1024-4096 Hz (subject-variable)

Paradigm

Eighteen subjects (S12, S13, S15, S21, S27, S28, S31, S33, S36, S37, S38, S39, S40, S42, S46, S47, S50, S51) participated in a spatial auditory attention decoding (SAA) task in which a target speaker was positioned at a fixed azimuth (30 deg) among distractors. EEG was recorded from 32 BioSemi ActiveTwo channels (A1-A32, Ag/AgCl cap) plus 8 external channels (total 41 channels) at variable sampling rates (1024, 2048, or 4096 Hz depending on subject). Stimulus events are encoded as BioSemi trigger codes in the Status channel; the kernel extracts these using `mne.find_events()` and converts them to text annotations.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://zenodo.org/records/3357164

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
(numeric BioSemi trigger codes)	varies	short/admin	raw	Stimulus onset, response, and trial boundary markers encoded in Status channel

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Trigger codes include stimulus onset markers (~3856-3966), control codes (65530-65532), and other administrative codes. Exact mapping requires dataset-specific documentation. Primary task: detect spatial attention direction from EEG.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Spatial auditory attention decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification] | tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Spatial attention condition labels from cue/stimulus protocol.
- Evidence: SAA dataset targets decoding of attended spatial auditory stream/location. Source: https://zenodo.org/records/3357164 DOI: https://doi.org/10.5281/zenodo.3357164

Normal Task 1: Spatial Attention Decoding - Present Stimulus (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.1 s, tmax = 1.0 s (per stimulus onset event), target_events = see Target Definition
- Label Route: `stim`
- Target Definition: Requires mapping trigger codes to stimulus/attention labels from the dataset documentation. Stimulus-onset codes (~3856-3966) mark individual sound presentations.
- Notes: Trigger code semantics must be verified against the dataset README or companion paper. Variable sampling rates across subjects require per-subject resampling to a common rate.

Data Quality Notes

- Variable sampling rates (1024-4096 Hz) across subjects; resample to a common rate before cross-subject analysis.
- Trigger code interpretation requires dataset-specific documentation (Status channel values need decoding).
- 41 channels (32 EEG + 8 external); identify and exclude non-EEG channels before analysis.

References

- Reference: Spatial Auditory Attention Dataset. Zenodo. https://zenodo.org/records/3357164

156. zenodo_sin - Speech-in-Noise (SiN) Auditory Attention Decoding Dataset (Zenodo Mirror)

Dataset: `zenodo_sin` | Year: 2021 | URL: N/A (Zenodo mirror of Mendeley SiN dataset)
Category: High-level Mental | Subjects: 26 | Files (Completed): 26 (Case B kernel) | Channels: 66 | Sampling Rate: 256 Hz

Paradigm

Twenty-six normal-hearing subjects (NH_subject01-NH_subject26) participated in a cocktail-party auditory attention decoding (AAD) task in which competing speech was presented with background noise at two signal-to-noise conditions (Zenodo mirror of Mendeley SiN dataset). EEG was recorded from 64 channels plus 2 mastoid references (total 66 channels) at 256 Hz. Each subject's `.mat` file contains pre-epoched EEG data as a 3D array `(896, 66, 100)` - 896 time points x 66 channels x 100 trials - for each of two Speech-in-Noise conditions (condition 7 and condition 13). The Case B kernel concatenates the 100 trials for each condition into a single continuous raw signal and annotates each trial with its condition label.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://zenodo.org/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`SiN_condition_7`	~1300 (~50/subject x 26)	long	raw	Speech-in-Noise condition 7 trial (one cocktail-party condition)
`SiN_condition_13`	~1300 (~50/subject x 26)	long	raw	Speech-in-Noise condition 13 trial (second cocktail-party condition)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Case B kernel: pre-epoched `.mat` data; each file reconstructed into continuous raw by concatenating 100 trials per condition (~3.5 s each at 256 Hz = 896 samples per trial).

Tasks

Primary Task 1: Speech-in-noise auditory attention decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification] | tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Condition or attended-stream labels (released split commonly uses condition 7 vs 13).
- Evidence: Speech-in-noise AAD dataset is explicitly provided for supervised attention decoding tasks. Source: https://zenodo.org/

Normal Task 1: Speech-in-Noise Condition Classification - Condition 7 vs. 13 (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 3.5 s (= 896/256 Hz; matches pre-epoched trial length), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Case B kernel reconstructs continuous raw from pre-epoched data; trial boundaries are annotated. Epoch window (3.5 s) matches the original pre-epoched length; use exactly 896/256 = 3.5 s to avoid boundary effects.

Event	y	Meaning
`SiN_condition_7`	0	Speech-in-Noise condition 7
`SiN_condition_13`	1	Speech-in-Noise condition 13
## Data Quality Notes		

- Case B kernel: original `.mat` data is pre-epoched (not continuous); reconstruction introduces trial boundary discontinuities.
- Zenodo mirror of the Mendeley SiN dataset (`mendeley_sin`); the two datasets are identical in content and structure.
- No age or sex information available.

References

- Reference: Speech-in-Noise Auditory Attention Decoding Dataset. Zenodo mirror of Mendeley SiN dataset. See also `mendeley_sin`.

157. zenodo_uhd - Ultra High-Density 256-Channel EEG AAD Dataset

Dataset: zenodo_uhd | Year: 2021 | URL: N/A
Category: High-level Mental | Subjects: 13 | Files (Completed): 156 | Channels: 256 | Sampling Rate: 1000 Hz

Paradigm

Thirteen subjects listened to two simultaneously presented stories (one in each ear) and attended to one speaker while ignoring the other (auditory attention decoding, AAD). Ultra-high-density EEG was recorded from 256 channels (BioSemi ActiveTwo, Ag/AgCl) at 1000 Hz. Subjects completed multiple trials; each recording file corresponds to one trial, with the attended direction (left/right) encoded in the filename (`S{N}_AAD_{trial}{L/R}.dap`). The kernel creates a whole-trial `attend_left` or `attend_right` annotation per file. This dataset has the same structure as `zenodo_4518754` and uses an identical kernel implementation.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://zenodo.org/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`attend_left`	~78	long	raw	Subject attends to the left-ear story for the entire recording
`attend_right`	~78	long	raw	Subject attends to the right-ear story for the entire recording

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Each file has exactly one annotation spanning the entire recording.

Tasks

Primary Task 1: Ultra-high-density auditory attention decoding (left vs right)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Trial-level attended direction labels (`attend_left/attend_right`).

- Evidence: UHD EEG release documents auditory attention decoding as its central benchmark task. Source: https://zenodo.org/

Normal Task 1: Auditory Attention Decoding - Left vs. Right (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 10.0 s, overlap = 5.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only `.dap` header files are processed; `.dat` and `.rs3` auxiliary files are skipped. Numeric stimulus event codes (1000001, 100255, 800000, 800001) may also appear from the stimulus delivery system; use the whole-trial `attend_*` label for the primary target.

Event	y	Meaning
`attend_left`	0	Attend to left-ear speaker
`attend_right`	1	Attend to right-ear speaker
## Data Quality Notes		

- Ultra-high-density 256-channel EEG; computationally intensive.
- High sampling rate (1000 Hz); consider downsampling to 64 or 128 Hz for typical AAD decoding.
- Same structure and kernel as `zenodo_4518754`; may be processed identically.
- No age or sex information available.

References

- Reference: Ultra High-Density 256-Channel EEG Auditory Attention Decoding Dataset. Zenodo.

Chapter 3. Action/Output

Datasets in this chapter: 28. Motor intention/execution and BCI-output focused tasks.

158. bcic_iii_1 - BCI Competition III Dataset 1 (Directional Motor Imagery EEG)

Dataset: `bcic_iii_1` | Year: 2005 | URL: https://www.bbci.de/competition/iii/download/
Category: Action/Output | Subjects: 1 | Files (Completed): 1 | Channels: 64 | Sampling Rate: 1000 Hz

Paradigm

A single subject performed directional motor imagery (BCI Competition III, 2005). Visual arrow cues prompted 4-second motor imagery periods (two classes: left and right/foot). The dataset is stored in a single GDF file (`BCI2005_I.gdf`). The GDF format embeds event annotations natively; MNE reads them automatically. No age or sex information is available in the public release.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://www.bbci.de/competition/iii/download/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
768	377	admin	raw	Start of a trial (pre-cue marker)
769	138	short	raw	Cue onset - class 1 (left hand / motor imagery direction 1)
772	139	short	raw	Cue onset - class 2 (right hand or foot, motor imagery direction 2)
783	100	admin	raw	Cue unknown (evaluation-set placeholder)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: The official BCI Competition III dataset description identifies directional motor-imagery decoding as the benchmark objective for this dataset. Source: https://www.bbci.de/competition/iii/ Official description file: `references/website_des.txt`

Normal Task 1: Binary Motor Imagery Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Event codes follow the GDF/BCIC standard but are not renamed by the kernel; they appear as numeric strings. Event `768` is a trial-onset marker preceding the cue and should be excluded from classification targets. Event `783` (cue unknown) appears in unlabeled evaluation data and should also be excluded unless the test labels are available.

Event	y	Meaning
`769`	0	Motor imagery class 1 (left-hand direction)
`772`	1	Motor imagery class 2 (right-hand or foot direction)
## Data Quality Notes		

- Single-subject dataset; results cannot be generalized across subjects.
- Very small dataset (1 file, 377 trials); statistical power is limited.
- High sampling rate (1000 Hz); consider downsampling to <=250 Hz.
- No demographic information available.
- GDF event codes are kept as numeric strings in MNE annotations; ensure correct integer parsing.

References

- Reference: BCI Competition III (2005), Dataset 1 - Directionally Modulated EEG Signals. https://www.bbci.de/competition/iii/

159. bcic_iii_2 - BCI Competition III Dataset II (P300 Speller)

Dataset: `bcic_iii_2` | Year: 2005 | URL: https://www.bbci.de/competition/iii/download/
Category: Action/Output | Subjects: 2 | Files (Completed): 4 (Case B kernel; 2 Train + 2 Test) | Channels: 64 | Sampling Rate: 240 Hz

Paradigm

Two subjects (A and B) attended to individual letters in a 6x6 character matrix while rows and columns flashed sequentially (BCI Competition III, 2005). Each character trial consisted of 15 sequences, each sequence comprising 12 flashes (6 rows + 6 columns). The P300 event-related potential, peaking ~300 ms after the target row or column flash, encodes the attended character. The training set contains 85 labeled characters per subject; the test set contains 100 characters without disclosed labels. The original `.mat` files are in a pre-epoched 3D format and are reconstructed into continuous raw data by the Case B kernel, which concatenates the 85 training sequences end-to-end.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://www.bbci.de/competition/iii/download/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`seq_onset`	85	admin	raw	Onset of each of the 85 character sequences (boundary marker)
`target_flash`	2550	short	raw	Flash of the row or column containing the target character
`nontarget_flash`	~12750	short	raw	Flash of a row or column not containing the target character

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Counts per Train file (1 file per subject). Test files have no class labels -> all annotations set to `unknown`.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Target vs non-target stimulus events
- Evidence: The official BCI Competition III Dataset II documentation defines P300 speller target-versus-nontarget decoding as the benchmark task. Source: https://www.bbci.de/competition/iii/ Official description PDF: `references/desc_II.pdf`

Normal Task 1: P300 Target vs. Non-Target Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.1 s, tmax = 0.8 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Use Train files only (`Subject_A_Train.mat`, `Subject_B_Train.mat`); Test files have no labels and all events are set to `unknown`. Class ratio is approximately 1:5 (target:nontarget); apply class-balancing or cost-sensitive learning. `seq_onset` is a boundary marker only and must be excluded. Reconstruction via Case B kernel concatenates sequences; discontinuities at sequence boundaries may introduce minor edge artifacts.

Event	y	Meaning
`target_flash`	1	Flash of the attended row or column (P300 target)
`nontarget_flash`	0	Flash of a non-attended row or column
## Data Quality Notes		

- Class imbalance: ~1 target flash per 5-6 non-target flashes; balance before classification.
- Test labels are not publicly available; test files yield `unknown` annotations after kernel processing.
- Case B kernel: original `.mat` data is pre-epoched (3D array) and is reconstructed into a continuous raw signal; treat sequence boundaries marked by `seq_onset` as artificial discontinuities.
- Only 2 subjects; model generalization cannot be assessed from this dataset alone.

References

- Reference: BCI Competition III (2005), Dataset II - P300 Speller. Wadsworth Center, NYS Department of Health. Wolpaw JR, Schalk G, Krusienski DJ. https://www.bbci.de/competition/iii/

160. bcic_iv_1 - BCI Competition IV Dataset 1 (Motor Imagery, Uncued Classifier Application)

Dataset: `bcic_iv_1` | Year: 2008 | URL: https://www.bbci.de/competition/iv/desc_1.html
Category: Action/Output | Subjects: 7 | Files (Completed): 14 | Channels: 59 | Sampling Rate: 1000 Hz

Paradigm

Seven subjects performed two-class motor imagery without feedback in an asynchronous (self-paced) BCI paradigm (BCI Competition IV, 2008). The two movement classes differed per subject, selected from: left hand, right hand, or foot imagery. A calibration phase used visual arrow cues with 4-second imagery intervals. The evaluation phase used acoustic cues (spoken words) with variable-duration imagery (1.5-8 s) and rest periods (1.5-8 s), simulating a realistic asynchronous BCI scenario. Both calibration and evaluation `.mat` files are provided per subject; the kernel reads class names and event positions directly from the `.mat` structure.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://www.bbci.de/competition/iv/desc_1.html

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`left`	~100/subject	short	raw	Cue onset for left-hand motor imagery
`right`	~100/subject	short	raw	Cue onset for right-hand motor imagery (subjects assigned right class)
`foot`	~100/subject	short	raw	Cue onset for foot motor imagery (subjects assigned foot class)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Class labels vary per subject: some subjects have `left` + `right`, others have `left` + `foot`. Event names are loaded dynamically from `nfo.className` in the `.mat` file. Counts shown are approximate per calibration file.

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification

- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://www.bbci.de/competition/iv/desc_1.html DOI: https://doi.org/10.1016/j.neuroimage.2007.01.051

Normal Task 1: Two-Class Motor Imagery Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Class names are subject-specific; the kernel reads them from the `.mat` file and creates annotations accordingly. Evaluation files have continuous recordings with variable-length trials and idle periods; only annotated cue positions should be used as epoch anchors. High sampling rate (1000 Hz); consider downsampling to <=250 Hz.

Event	y	Meaning
`left`	0	Left-hand motor imagery
`right` or `foot`	1	Second motor imagery class (subject-specific)
## Data Quality Notes		

- Two-class labels vary per subject (left+right vs. left+foot); verify class names per file from the `eegunity_description` field or the `.mat nfo.className` field.
- No age or sex information is available in the public release.
- Evaluation phase has variable trial durations and idle periods; the idle state is unlabeled and should be identified by absence of annotations.
- High sampling rate (1000 Hz); memory-intensive; downsampling recommended.

References

- Reference: BCI Competition IV (2008), Dataset 1 - Motor Imagery, Uncued Classifier Application. https://www.bbci.de/competition/iv/desc_1.html

161. bcic_iv_2a - BCI Competition IV Dataset 2a (4-Class Motor Imagery)

Dataset: `bcic_iv_2a` | Year: 2008 | URL: https://www.bbci.de/competition/iv/desc_2a.html
Category: Action/Output | Subjects: 9 | Files (Completed): 18 | Channels: 25 | Sampling Rate: 250 Hz

Paradigm

Nine subjects (A01-A09) performed four-class cued motor imagery (BCI Competition IV, 2008): left hand, right hand, feet, and tongue. Each session contained 6 runs of 48 trials each (288 trials per session), balanced across 4 classes (72 trials per class). A fixation cross preceded each trial, followed by a visual arrow cue indicating the imagery class, and a 4-second imagery period. Short resting intervals separated trials. Each subject was recorded in two sessions: a training session (suffix `T.gdf`) with event labels, and an evaluation session (suffix `E.gdf`) with initially unknown labels replaced by kernel-loaded `.mat` companion files. EEG was recorded from 22 channels (standard 10-20, sensorimotor focus) plus 3 bipolar EOG channels (filtered 0.5-100 Hz, notch at 50 Hz).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://www.bbci.de/competition/iv/desc_2a.html

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Start of a trial`	~576/subject	admin	raw	Trial-onset fixation cross (pre-cue marker)
`Cue onset left (class 1)`	~144/subject	short	raw	Left-hand motor imagery cue
`Cue onset right (class 2)`	~144/subject	short	raw	Right-hand motor imagery cue
`Cue onset foot (class 3)`	~144/subject	short	raw	Feet motor imagery cue
`Cue onset tongue (class 4)`	~144/subject	short	raw	Tongue motor imagery cue
`Idling EEG (eyes open)`	~9/subject	admin	raw	Resting state with eyes open
`Idling EEG (eyes closed)`	~9/subject	admin	raw	Resting state with eyes closed
`Rejected trial`	variable	admin	raw	Trial rejected by experimenter
`Start of a new run`	~12/subject	admin	raw	Run boundary marker

Event ID	Count (total)	Type	Meta Level	Meaning
Eye movements	rare	admin	raw	Artifactual eye movement event

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Counts are approximate per subject (Training + Evaluation combined). The kernel remaps all GDF numeric codes to human-readable strings.

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: The official BCI Competition IV Dataset 2a description defines four-class motor imagery decoding (left hand, right hand, feet, tongue) as the benchmark task. Source: https://www.bbci.de/competition/iv/desc_2a.html Official description PDF: references/desc_2a.pdf

Normal Task 1: 4-Class Motor Imagery Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Use only the 4 cue-onset events as classification targets. The 4-second imagery window begins at cue onset. Evaluation sessions (E files) have cue labels resolved by the kernel from companion .mat files. Exclude all admin-type events. EOG channels (EOG-left, EOG-central, EOG-right) should be excluded before analysis.

Event	y	Meaning
Cue onset left (class 1)	0	Left-hand motor imagery
Cue onset right (class 2)	1	Right-hand motor imagery
Cue onset foot (class 3)	2	Feet motor imagery
Cue onset tongue (class 4)	3	Tongue motor imagery

Normal Task 2: Binary Motor Imagery - Left vs. Right Hand (epoch_by_event)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Subset of Task 1. Discard feet and tongue trials.

Event	y	Meaning
Cue onset left (class 1)	0	Left-hand motor imagery

Event	y	Meaning
`Cue onset right (class 2)`	1	Right-hand motor imagery
## Data Quality Notes		

- Rejected trials (variable per subject/session) should be excluded from analysis.
- EOG channels present; apply artifact rejection or regression before motor imagery classification.
- Evaluation files initially contain `Cue unknown (class 783)` entries that the kernel replaces with proper class labels from `.mat` companion files; verify companion file presence.
- Class balance is enforced by design (72 trials per class per session); minor imbalance may arise from rejected trials.
- Subject age range: 17-26 years; 7 female, 2 male subjects.

References

- Reference: Brunner C, Leeb R, Muller-Putz G, Schlogl A, Pfurtscheller G (2008). BCI Competition 2008 - Graz Data Set A. Institute for Knowledge Discovery, Graz University of Technology. https://www.bbci.de/competition/iv/desc_2a.html

162. bcic_iv_2b - BCI Competition IV Dataset 2b (Left/Right Hand Motor Imagery)

Dataset: `bcic_iv_2b` | Year: 2008 | URL: https://www.bbci.de/competition/iv/desc_2b.html
Category: Action/Output | Subjects: 9 | Files (Completed): 46 | Channels: 6 | Sampling Rate: 250 Hz

Paradigm

Nine subjects (B01-B09) performed two-class cued motor imagery of the left and right hand (BCI Competition IV, 2008). Only 3 bipolar EEG channels over the sensorimotor cortex (C3, Cz, C4) and 3 EOG channels were recorded (0.5-100 Hz, notch at 50 Hz). Each subject underwent 5 sessions over two days: sessions 1-2 without feedback, sessions 3-5 with BCI feedback. Each session contained multiple runs of ~60-80 trials per class. A fixation cross preceded each trial, followed by a visual left/right arrow cue for 1.25 s, then a 4-second imagery period with optional BCI cursor feedback. Evaluation sessions (suffix `E.gdf`) have unknown cue labels that the kernel resolves from companion `.mat` files.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://www.bbci.de/competition/iv/desc_2b.html

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Start of a trial`	~1520/subject	admin	raw	Trial-onset fixation cross (pre-cue)
`Cue onset left (class 1)`	~380/subject	short	raw	Left-hand motor imagery cue
`Cue onset right (class 2)`	~380/subject	short	raw	Right-hand motor imagery cue
`BCI feedback (continuous)`	~760/subject	admin	raw	BCI feedback period (sessions 3-5 only)
`Idling EEG (eyes open)`	rare	admin	raw	Resting state with eyes open
`Idling EEG (eyes closed)`	rare	admin	raw	Resting state with eyes closed
`Rejected trial`	variable	admin	raw	Experimenter-rejected trial
`Start of a new run`	~40/subject	admin	raw	Run boundary marker
`Horizontal eye movement`	rare	admin	raw	Eye artifact marker

Event ID	Count (total)	Type	Meta Level	Meaning
`Vertical eye movement`	rare	admin	raw	Eye artifact marker
`Eye rotation`	rare	admin	raw	Eye artifact marker
`Eye blinks`	rare	admin	raw	Eye artifact marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Counts are approximate per subject (all sessions combined). GDF numeric codes remapped to human-readable strings by kernel.

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: The official BCI Competition IV Dataset 2b description defines binary left-versus-right hand motor imagery decoding as the benchmark task. Source: https://www.bbci.de/competition/iv/desc_2b.html Official description PDF: `references/desc_2b.pdf`

Normal Task 1: Binary Motor Imagery Classification - Left vs. Right Hand (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Exclude all `admin`-type events. For longitudinal analysis, separate sessions 1-2 (no feedback) from sessions 3-5 (with BCI feedback). EOG channels (`EOG:ch01`, `EOG:ch02`, `EOG:ch03`) should be excluded before analysis. With only 3 EEG channels, spatial filtering (CSP) is especially important.

Event	y	Meaning
`Cue onset left (class 1)`	0	Left-hand motor imagery
`Cue onset right (class 2)`	1	Right-hand motor imagery
## Data Quality Notes		

- Only 3 EEG channels (C3, Cz, C4): very limited spatial resolution; spatial filtering (CSP) is critical.
- EOG channels present; apply artifact regression before MI classification.
- Feedback sessions (3-5) may show learning effects; sessions 1-2 provide cleaner baseline.
- Evaluation files use `Cue unknown (class 783)` initially; companion `.mat` files are required by the kernel to resolve labels.
- Subject demographics: B01-B09, ages 20-32, mixed sex.
- 46 files total across 9 subjects x 5 sessions; some sessions may have extra evaluation runs.

References

- Reference: Leeb R, Lee F, Keinrath C, Scherer R, Bischoff H, Pfurtscheller G (2008). BCI Competition 2008 - Graz Data Set B. Institute for Knowledge Discovery, Graz University of Technology.

https://www.bbci.de/competition/iv/desc_2b.html

163. bcic_iv_4 - BCI Competition IV Dataset 4 (ECoG Finger Movement Decoding)

Dataset: `bcic_iv_4` | Year: 2008 | URL: https://www.bbci.de/competition/iv/desc_4.html
Category: Action/Output | Subjects: 3 | Files (Completed): 3 (Case B kernel) | Channels: 48-64 (variable per subject; ECoG) | Sampling Rate: 1000 Hz

Paradigm

Three subjects (sub1-sub3) performed individual finger flexions under instruction while ECoG (electrocorticography) was recorded from 48-64 electrodes implanted over sensorimotor cortex (BCI Competition IV, 2008). Subjects flexed each of the five fingers individually on cue. Continuous finger flexion amplitude was measured via a data glove and stored as 5 labels per time sample. The dataset contains a training segment (~400 s per subject) with labeled finger flexion signals and a test segment (~200 s) with labels withheld. The Case B kernel concatenates train and test segments into a single continuous raw signal per subject; finger flexion signals (5 channels) are stored as `misc`-type stim channels (`finger1-finger5`).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: regression target
> Web Reference Used for Decision: https://www.bbci.de/competition/iv/desc_4.html

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`train_segment`	1/subject	admin	raw	Annotates the entire training segment (with labeled finger flexions)
`test_segment_onset`	1/subject	admin	raw	Marks the onset of the unlabeled test segment

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Finger flexion labels are not stored as event annotations but as 5 continuous `misc` stim channels (`finger1-finger5`). This is a regression/continuous decoding task.

MISC Label Summary

- Route: `misc`
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Finger flexion trajectory decoding from ECoG

- Task Type: regression
- Epoch Method: `epoch_by_long_event_hdf5` (movement windows) or `epoch_by_event_hdf5` (onset-locked)
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification] | tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Continuous flexion trajectories for five fingers (thumb/index/middle/ring/little), using official competition label files.
- Evidence: The official BCI Competition IV Dataset 4 documentation defines continuous finger-flexion trajectory decoding from ECoG as the benchmark objective. Source: https://www.bbci.de/competition/iv/desc_4.html Official description PDF: `references/desc_4.pdf`

Normal Task 1: Finger Flexion Decoding - Training Segment (epoch_by_long_event)

- Task Type: regression
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = duration of `train_segment`, overlap = 0.5 s (sliding window), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: N/A (target labels are continuous; see notes below)
- Notes: This is a regression task, not a standard classification task. The `train_segment` annotation spans the entire training portion (~400 s); use `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5` to extract fixed-length windows. Within each epoch, extract the corresponding `finger1-finger5` misc-channel values as regression targets. The `test_segment_onset` annotation marks where labels become unavailable. Finger channels must be excluded from the EEG feature matrix but retained as label sources.

Normal Task 2: Active vs. Rest Finger Movement Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: Requires custom thresholding of finger channel amplitudes to define discrete movement epochs; not directly supported by standard `epoch_by_event_hdf5`.
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `misc`
- Target Definition: Needs verification.
- Notes: Threshold the `finger1-finger5` misc channels to identify movement onset events, then apply `epoch_by_event_hdf5`. Active finger movement (amplitude > threshold) vs. rest (amplitude <= threshold) yields a binary classification problem per finger.

Data Quality Notes

- ECoG data, not scalp EEG: electrode locations are patient-specific implants over sensorimotor cortex; no standard montage applies.
- Channel count varies per subject: sub1 = 62, sub2 = 64, sub3 = 48 ECoG channels.
- Each file additionally contains 5 `misc` channels (`finger1`-`finger5`) storing continuous flexion amplitudes; exclude these from EEG analysis but use them as regression labels.
- No age or sex information available.
- High sampling rate (1000 Hz); consider downsampling to <=250 Hz for classification tasks.
- Test-segment labels are withheld; only the `train_segment` portion is usable for supervised learning.

References

- Reference: BCI Competition IV (2008), Dataset 4 - Finger Movements in ECoG. https://www.bbci.de/competition/iv/desc_4.html

164. figshare_largemi - A Large EEG Motor Imagery Dataset for EEG-BCI

Dataset: `figshare_largemi` | Year: 2018 | URL: https://figshare.com/collections/A_large_electroencephalographic_motor_imagery_dataset_for_electroencephalographic_brain_computer_interfaces/3917698
Category: Action/Output | Subjects: 13 | Files (Completed): 73 | Channels: 22 | Sampling Rate: 200 or 1000 Hz (protocol-dependent)

Paradigm

Thirteen subjects (A-M) participated in multiple EEG motor imagery sessions using five different paradigms (Kaya et al., 2018). EEG was recorded from 22 scalp channels. The paradigms are:
- CLA: 3-class MI - left hand, right hand, passive state.
- HaLT: 6-class MI - left hand, right hand, passive state, left leg, right leg, tongue.
- FREEFORM / FREEDOM: 2-class MI - left hand, right hand (free imagery style).
- 5F: 5-class finger MI - thumb, index, middle, ring, and pinkie.
- NoMT: no-motor-task control sessions (resting state, no imagery).

Trials were cue-based with a blank screen rest period, followed by an arrow/cue presentation indicating the imagery target. Each trial lasted approximately 3 seconds of imagery. NoMT sessions serve as control recordings without motor task events.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://figshare.com/collections/A_large_electroencephalographic_motor_imagery_dataset_for_electroencephalographic_brain_computer_interfaces/3917698

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Left hand MI`	varies by protocol	short	raw	Left-hand motor imagery cue
`Right hand MI`	varies by protocol	short	raw	Right-hand motor imagery cue
`Passive state`	varies by protocol	short	raw	Passive / idle state (CLA/HaLT)
`Left leg MI`	varies by protocol	short	raw	Left-leg motor imagery cue (HaLT)
`Right leg MI`	varies by protocol	short	raw	Right-leg motor imagery cue (HaLT)
`Tongue MI`	varies by protocol	short	raw	Tongue motor imagery cue (HaLT)

Event ID	Count (total)	Type	Meta Level	Meaning
`Thumb MI`	varies by protocol	short	raw	Thumb finger imagery cue (5F)
`Index finger MI`	varies by protocol	short	raw	Index finger imagery cue (5F)
`Middle finger MI`	varies by protocol	short	raw	Middle finger imagery cue (5F)
`Ring finger MI`	varies by protocol	short	raw	Ring finger imagery cue (5F)
`Pinkie MI`	varies by protocol	short	raw	Little finger imagery cue (5F)
`none`	all NoMT files	admin	raw	No motor task (NoMT protocol control)

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://doi.org/10.1038/sdata.2018.211

Normal Task 1: Left vs. Right Hand Motor Imagery Classification - CLA/FREEFORM (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 3.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: For CLA protocol, also include `Passive state` as class 2 (3-class task). Separate files by protocol type (CLA / FREEFORM / HaLT) for consistent multi-session analysis.

Event	y	Meaning
`Left hand MI`	0	Left-hand motor imagery
`Right hand MI`	1	Right-hand motor imagery

Normal Task 2: 6-Class Motor Imagery Classification - HaLT (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 3.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`Left hand MI`	0	Left-hand MI
`Right hand MI`	1	Right-hand MI
`Passive state`	2	Passive/idle state
`Left leg MI`	3	Left-leg MI
`Right leg MI`	4	Right-leg MI
`Tongue MI`	5	Tongue MI

Normal Task 3: 5-Finger Motor Imagery Classification - 5F (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 3.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`Thumb MI`	0	Thumb finger MI
`Index finger MI`	1	Index finger MI
`Middle finger MI`	2	Middle finger MI
`Ring finger MI`	3	Ring finger MI
`Pinkie MI`	4	Little finger MI

Normal Task 4: Resting-State Segmentation - NoMT Control (epoch_by_segmentation)

- Task Type: segmentation
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: length = 3.0 s, overlap = 0.5 s
- Label Route: `Annotation`
- Target Definition: N/A (no events; use as unlabeled or negative class)
- Notes: NoMT files have event annotation `none` set by kernel; use `epoch_by_segmentation_hdf5` for these files.

Data Quality Notes

- Multiple paradigms in one dataset; always filter by protocol type before analysis (use file path to identify protocol: `CLA`, `HaLT`, `FREEFORM`, `5F`, `NoMT`).
- Sampling rates differ: 200 Hz (5F protocol), 1000 Hz (CLA/HaLT/FREEFORM); process separately or resample to a common rate.
- Subject demographics: 13 subjects (A-M), 9 female / 4 male, age ranges 20-35.
- NoMT sessions have `none` annotations; exclude from MI analysis or use as rest class.

References

- Reference: Kaya M, Binli MK, Ozbay E, Yanar H, Mishchenko Y (2018). A large electroencephalographic motor imagery dataset for electroencephalographic brain computer interfaces. Scientific Data, 5, 180211. https://doi.org/10.1038/sdata.2018.211

165. figshare_meng2019 - EEG Dataset for Cursor BCI (Meng 2019)

Dataset: `figshare_meng2019` | Year: 2019 | URL: https://dx.doi.org/10.6084/m9.figshare.7959572
Category: Action/Output | Subjects: N/A (see notes) | Files (Completed): 126 | Channels: 64 | Sampling Rate: 128 Hz

Paradigm

Participants performed a one-dimensional cursor BCI task using mental imagery in three experiments (Meng et al., 2019). EEG was recorded from 64 channels. Subjects imagined motor or other mental activities to move a cursor toward a target positioned above ("+") or below ("-") center, or at rest (center target). The dataset covers three experiments (Exp1, Exp2, Exp3); Exp1 and Exp2 used a Neuroscan SynAmps RT amplifier, while Exp3 used a Biosemi Active Two system. The paradigm recorded both target intent events (what the subject was trying to do) and result events (what the BCI decoded), enabling analysis of mental imagery decoding accuracy.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://dx.doi.org/10.6084/m9.figshare.7959572

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`target cursor plus`	varies	short	raw	Target positioned above center; subject imagines upward/+ movement
`target cursor minus`	varies	short	raw	Target positioned below center; subject imagines downward/- movement
`target rest`	varies	short	raw	Target at center; subject imagines neutral/rest state
`result cursor plus`	varies	admin	raw	BCI decoded + direction (feedback signal)
`result cursor minus`	varies	admin	raw	BCI decoded - direction (feedback signal)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

> `result cursor *` events encode BCI feedback and are not ground-truth labels; use only `target cursor *` events for supervised classification.

Tasks

Primary Task 1: One-dimensional cursor control decoding (up vs down)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery direction labels for cursor movement (up/down); optional 3-class extension per protocol.
- Evidence: Meng et al. dataset is designed for EEG-based cursor BCI direction decoding. Source: https://doi.org/10.6084/m9.figshare.7959572

Normal Task 1: Cursor Direction Classification - Up vs. Down (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Exclude `result cursor *` events - these encode the BCI output, not the ground-truth label. Exclude `target rest` trials unless a 3-class task is intended.

Event	y	Meaning
`target cursor plus`	1	Imagined upward / + cursor movement
`target cursor minus`	0	Imagined downward / - cursor movement

Normal Task 2: 3-Class Cursor BCI Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`target cursor plus`	0	Imagined + cursor movement
`target cursor minus`	1	Imagined - cursor movement
`target rest`	2	Rest / neutral state
## Data Quality Notes		

- Sex information is not available in the dataset metadata.
- Three experiments (Exp1, Exp2, Exp3) use different amplifier systems; process per-experiment or normalize across systems.
- `result cursor *` events are BCI feedback signals, not labels; do not use for classification targets.
- Subject count is not explicitly stated; estimate from unique subject folders in file paths.

References

- Reference: Meng J et al. (2019). EEG dataset for cursor BCI (Figshare). https://dx.doi.org/10.6084/m9.figshare.7959572

166. figshare_shudb - SHU Motor Imagery EEG Dataset

Dataset: `figshare_shudb` | Year: 2022 | URL: https://figshare.com/articles/software/shu_dataset/19228725/1
Category: Action/Output | Subjects: 21 | Files (Completed): 232 | Channels: 32 | Sampling Rate: 250 Hz

Paradigm

Twenty-one subjects (sub-001 to sub-021) performed cued left/right hand motor imagery across 4-5 sessions each (SHU dataset). EEG was recorded from 32 channels using a BrainAmp MR plus amplifier with Ag/AgCl cap (standard 10-20 system). Each session contained approximately 44-50 trials per class (left hand MI and right hand MI). Events are stored in TSV files following a BIDS-like structure and loaded by the kernel from adjacent `events/` directories. The dataset is well-suited for studying longitudinal motor imagery performance and cross-session transfer.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://figshare.com/articles/software/shu_dataset/19228725/1

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`left`	~10900 (total)	short	raw	Left-hand motor imagery cue onset
`right`	~10900 (total)	short	raw	Right-hand motor imagery cue onset

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Total counts estimated as 232 files x ~47 trials per class. Exact per-session counts vary slightly (44-50 per class).

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://figshare.com/articles/software/shu_dataset/19228725/1 DOI: https://doi.org/10.6084/m9.figshare.19228725.v3

Normal Task 1: Binary Motor Imagery Classification - Left vs. Right Hand (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Multiple sessions per subject enable cross-session and longitudinal analysis. TSV event files must be present alongside EEG files; verify `events/` directory structure before processing.

Event	y	Meaning
`left`	0	Left-hand motor imagery
`right`	1	Right-hand motor imagery
## Data Quality Notes		

- Age and sex information are not available in this dataset.
- 4-5 sessions per subject; slight trial count variation per session (44-50 per class) may introduce minor class imbalance within a session.
- BrainAmp MR plus amplifier with Ag/AgCl cap; standard 32-channel 10-20 montage.
- BIDS-like event structure; kernel reads TSV files from the `events/` subdirectory.

References

- Reference: SHU Motor Imagery Dataset (Figshare, 2022).
https://figshare.com/articles/software/shu_dataset/19228725/1

167. figshare_stroke - EEG Datasets of Stroke Patients (Motor Imagery)

Dataset: `figshare_stroke` | Year: 2022 | URL: https://figshare.com/articles/dataset/EEG_datasets_of_stroke_patients/21679035/5
Category: Action/Output | Subjects: 50 | Files (Completed): 50 | Channels: 33 | Sampling Rate: 500 Hz

Paradigm

Fifty stroke patients (sub-01 to sub-50) performed a cued left/right hand motor imagery task (ZhenTec NT1 amplifier, Ag/AgCl cap). EEG was recorded from 31 scalp channels plus 2 horizontal EOG channels (HEOL, HEOR). Each recording session contained 20 trials per hand class (20 left + 20 right = 40 trials total). Each trial comprised three phases: an instruction period (visual cue indicating the target hand), a motor imagery period (subject imagines the indicated hand movement), and a break period (rest). The dataset is designed to study MI-based BCI performance in stroke rehabilitation. Subject ages range from 31 to 77 years (median ~55), with predominantly right-handed subjects (49/50) and a male-majority cohort (~36M/14F).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision:
> https://figshare.com/articles/dataset/EEG_datasets_of_stroke_patients/21679035/5

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Instruction beginning - Left hand`	1000	admin	raw	Instruction cue onset for left-hand trial
`Instruction beginning - Right hand`	1000	admin	raw	Instruction cue onset for right-hand trial
`Motor imagery beginning - Left hand`	1000	short	raw	Left-hand motor imagery period onset
`Motor imagery beginning - Right hand`	1000	short	raw	Right-hand motor imagery period onset
`Break beginning - Left hand`	1000	admin	raw	Rest/break period following a left-hand trial
`Break beginning - Right hand`	1000	admin	raw	Rest/break period following a right-hand trial

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Counts are totals across all 50 subjects (20 per class per recording x 50 subjects).

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://figshare.com/articles/dataset/EEG_datasets_of_stroke_patients/21679035/5 DOI: https://doi.org/10.6084/m9.figshare.21679035.v5

Normal Task 1: Motor Imagery Classification - Left vs. Right Hand (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 4.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Epoch from MI onset event; exclude `Instruction beginning` and `Break beginning` events. EOG channels (`HEOL`, `HEOR`) should be excluded before analysis. Only 20 trials per class per subject; small per-subject trial count.

Event	y	Meaning
`Motor imagery beginning - Left hand`	0	Left-hand motor imagery
`Motor imagery beginning - Right hand`	1	Right-hand motor imagery

Normal Task 2: Stroke Patient Subgroup Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 4.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Same as Task 1 (MI events); group labels (age, lesion side, etc.) from `participants.tsv`.
- Notes: Clinical metadata (age, sex, stroke side, handedness) is embedded in the kernel's `_SUBJECT_DICT`. Cross-subject analysis with clinical covariates is the primary use case.

Data Quality Notes

- Stroke patient population: highly variable EEG quality due to neurological deficits and movement impairments.
- Very small per-subject trial count (20 per class); cross-subject aggregation is essential.
- EOG channels present (HEOL, HEOR); apply artifact rejection or EOG regression before MI classification.
- One left-handed subject (sub-06); consider excluding or annotating for lateralization analyses.
- Age range 31-77 years (mean ~55); age-related EEG changes may confound MI classification.

References

- Reference: EEG datasets of stroke patients for motor imagery BCI (Figshare, 2022). https://figshare.com/articles/dataset/EEG_datasets_of_stroke_patients/21679035/5

168. kaggle_inria - Kaggle BCI Challenge (INRIA) Dataset

Dataset: `kaggle_inria` | Year: 2015 | URL: https://www.kaggle.com/c/inria-bci-challenge
Category: Action/Output | Subjects: 26 | Files (Completed): 130 | Channels: 58 | Sampling Rate: 200 Hz

Paradigm

Twenty-six subjects (ages 20-37) performed a P300-based BCI feedback task using a 56-channel Ag/AgCl EEG cap at 200 Hz (plus 1 EOG channel and 1 FeedBackEvent channel, total 58). The task was a P300 matrix speller in which subjects attended to a target character while row/column flashes elicited P300 responses. Feedback was provided after each trial: subjects received either a correct ("good") or incorrect ("wrong") response to the P300 classifier output. Each session file (CSV format) contains one session for one subject; each subject has 5 sessions. Feedback event times are encoded in the dedicated `FeedBackEvent` channel; labels ("good" or "wrong") are sourced from a companion `TrainLabels.csv` file. Test sessions have unknown labels.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://www.kaggle.com/c/inria-bci-challenge

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`good feedback to P300`	varies (~1300)	short	raw	Feedback event: BCI output was correct
`wrong feedback to P300`	varies (~650)	short	raw	Feedback event: BCI output was incorrect
`unknown feedback to P300`	varies (~1560)	short	raw	Feedback event: label unknown (test sessions)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Feedback events are 1 s in duration (as set in kernel annotations). Test sessions (Sess01-Sess04 for most subjects) have `unknown` labels; labeled sessions are typically Sess05. Approximately 60 feedback events per session.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]

- Label Route: `Annotation`
- Target Definition: Target vs non-target stimulus events
- Evidence: The reference paper evaluates online error correction in a P300-based spelling task using this challenge setting. Source: https://www.kaggle.com/c/inria-bci-challenge DOI: https://doi.org/10.1155/2012/578295

Normal Task 1: P300 Feedback Correctness - Good vs. Wrong (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.1 s, tmax = 0.9 s (1 s feedback window), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Exclude files with `unknown feedback to P300` events only (test sessions without labels). Kernel requires `TrainLabels.csv` to be present at the dataset root directory. FeedBackEvent channel (column index 57) encodes event onset times as a binary channel; labels are matched by feedback ID (e.g., `S01_Sess01_FB001`).

Event	y	Meaning
`good feedback to P300`	0	Correct BCI feedback
`wrong feedback to P300`	1	Incorrect BCI feedback
## Data Quality Notes		

- Data stored as CSV files (not standard EEG format); MNE loader produces unsupported-file-type warnings that are non-fatal.
- 58 channels include 56 EEG + 1 EOG + 1 FeedBackEvent auxiliary channel; remove FeedBackEvent and EOG before training.
- Many sessions have only unknown labels (test set); only sessions with known labels in TrainLabels.csv can be used for supervised learning.
- Age range 20-37 available from dataset metadata; no sex information.

References

- Reference: Inria BCI Challenge. Kaggle Competition 2015. https://www.kaggle.com/c/inria-bci-challenge
- Reference: Margaux P, Maby E, Daligault S, Bertrand O, Mattout J. (2012). Objective and Subjective Evaluation of Online Error Correction during P300-Based Spelling. Advances in Human-Computer Interaction. DOI: https://doi.org/10.1155/2012/578295

169. openneuro_ds002034 - Real-time EEG feedback on alpha power lateralization leads to behavioral improvements in a covert attention task

Dataset: `openneuro_ds002034` | Year: 2022 | URL: https://openneuro.org/datasets/ds002034
Category: Action/Output | Subjects: 14 | Files (Completed): 167 | Channels: 82.0 | Sampling Rate: 512.0 Hz

Paradigm

Participants performed a covert spatial attention task where they were trained to lateralize their alpha-band EEG power using real-time neurofeedback. The study evaluated whether closed-loop neurofeedback of alpha lateralization improves behavioral performance in a spatial attention paradigm. No trial-level event markers are stored in the BIDS EEG files; the task condition is reflected continuously in the EEG signal itself.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002034

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
(none)	-	-	raw	No event markers detected in EEG files; continuous neurofeedback paradigm

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: Publisher-defined BIDS task: Task offline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002034 DOI: https://doi.org/10.1007/s10548-019-00725-9

Primary Task 2: Publisher-defined BIDS task: Task offlinecatch

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002034 DOI: https://doi.org/10.1007/s10548-019-00725-9

Primary Task 3: Publisher-defined BIDS task: Task onlinesham

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002034 DOI: https://doi.org/10.1007/s10548-019-00725-9

Normal Task 1: Resting / Continuous Segmentation (resting)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (no trial-level labels available))
- Notes: Continuous neurofeedback paradigm; alpha lateralization index may be computed from raw EEG as a continuous target if desired.

Data Quality Notes

- No trial-level event markers detected in any EEG files; only continuous recordings available.
- Real-time neurofeedback paradigm - EEG signal itself contains the task-relevant information.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Real-time EEG Feedback on Alpha Power Lateralization Leads to Behavioral Improvements in a Covert Attention Task`

170. openneuro_ds002336 - A multi-modal human neuroimaging dataset for data integration: simultaneous EEG and fMRI acquisition during a motor imagery neurofeedback task: XP1

Dataset: `openneuro_ds002336` | Year: 2021 | URL: https://openneuro.org/datasets/ds002336
Category: Action/Output | Subjects: 10 | Files (Completed): 107
Channels: 64 | Sampling Rate: 5000 Hz

Paradigm

Simultaneous EEG-fMRI acquisition during a kinesthetic motor imagery neurofeedback task. Subjects performed right-hand motor imagery or motor execution during sustained task blocks alternating with rest blocks, while receiving unimodal (EEG or fMRI) or bimodal neurofeedback. Each task block (Task-NF: neurofeedback, Task-ME: motor execution, Task-MI: motor imagery) is a sustained mental state lasting several seconds. BrainVision format with MRI artifact markers (TPULSE, R128) that must be excluded.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002336

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Rest`	93 (files)	long	raw	Rest / baseline block
`Task-NF`	60 (files)	long	raw	Neurofeedback task block
`Task-ME`	19 (files)	long	raw	Motor execution task block
`Task-MI`	14 (files)	long	raw	Motor imagery task block
`Response/R128`	14	admin	raw	BrainVision response trigger / MRI sync - exclude
`Stimulus/S 99`	14	admin	raw	BrainVision stimulus code 99 - likely admin/sync
`Stimulus/S 2`	14	admin	raw	BrainVision stimulus code 2 - likely admin/sync

Event ID	Count (total)	Type	Meta Level	Meaning
`Pulse Artifact/R`	7	admin	raw	MRI gradient pulse artifact marker - exclude
`Time 0/`	7	admin	raw	MRI timing reference marker - exclude
`TPULSE/TSTART`	7	admin	raw	MRI T-pulse start - exclude
`TPULSE/TPEAK`	7	admin	raw	MRI T-pulse peak - exclude
`TPULSE/TEND`	7	admin	raw	MRI T-pulse end - exclude

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus/S 99`, `Stimulus/S 2`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds002336 DOI: https://doi.org/10.18112/openneuro.ds002336.v2.0.2

Primary Task 2: Publisher-defined BIDS task: Fmri NF

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002336 DOI: https://doi.org/10.18112/openneuro.ds002336.v2.0.2

Primary Task 3: Publisher-defined BIDS task: Eegfmri NF

- Task Type: classification/segmentation

- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002336 DOI: https://doi.org/10.18112/openneuro.ds002336.v2.0.2

Normal Task 1: Motor Imagery / Neurofeedback State Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: MRI artifact markers (TPULSE/*, Pulse Artifact/R, Time 0/, R128) are all admin markers - excluded. High sampling rate (5000 Hz); downsample before epoching. Task-ME and Task-MI are sparse (14-19 files).

Event	y	Meaning
`Rest`	0	Rest / baseline block
`Task-NF`	1	Neurofeedback task block
`Task-ME`	2	Motor execution block
`Task-MI`	3	Motor imagery block
## Data Quality Notes		

- MRI gradient artifact contamination present; TPULSE markers indicate artifact regions.
- High sampling rate (5000 Hz); downsampling to 250-1000 Hz recommended.
- Task-ME and Task-MI blocks are sparsely present (subset of sessions only).
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Lioi, G., et al. (2019). Simultaneous MRI-EEG during a motor imagery neurofeedback task: an open access brain imaging dataset for multi-modal data integration. BioRxiv.`

171. openneuro_ds002338 - A multi-modal human neuroimaging dataset for data integration: simultaneous EEG and fMRI acquisition during a motor imagery neurofeedback task: XP2

Dataset: `openneuro_ds002338` | Year: 2022 | URL: https://openneuro.org/datasets/ds002338
Category: Action/Output | Subjects: 16 | Files (Completed): 169 | Channels: 64.0 | Sampling Rate: 5000.0 Hz

Paradigm

Participants performed right-hand motor imagery and received neurofeedback (1D or 2D display) during simultaneous EEG-fMRI acquisition to learn to regulate sensorimotor rhythms. The task alternated between sustained Rest blocks and Task-NF (neurofeedback) blocks. MRI gradient artifacts are marked with TPULSE markers which must be excluded. This is XP2 of a two-experiment series; XP1 is ds002336.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002338

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Rest`	101 (files)	long	raw	Rest / baseline block
`Task-NF`	101 (files)	long	raw	Neurofeedback motor imagery task block
`Response/R128`	68	admin	raw	BrainVision response trigger / MRI sync - exclude
`Stimulus/S 99`	68	admin	raw	BrainVision admin code - exclude
`Stimulus/S 2`	68	admin	raw	BrainVision admin code - exclude
`Stimulus/S101`	39	admin	raw	BrainVision admin code - exclude
`Pulse Artifact/R`	34	admin	raw	MRI gradient pulse artifact - exclude
`Time 0/`	34	admin	raw	MRI timing reference - exclude
`TPULSE/TSTART`	34	admin	raw	MRI T-pulse start - exclude

Event ID	Count (total)	Type	Meta Level	Meaning
TPULSE/TPEAK	34	admin	raw	MRI T-pulse peak - exclude
TPULSE/TEND	34	admin	raw	MRI T-pulse end - exclude
Stimulus/S 35	2	admin	raw	Sparse BrainVision code - exclude

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
- long: sustained-state marker (>=2 s), for epoch_by_long_event_hdf5
- rest: resting-state segment marker, for epoch_by_segmentation_hdf5
- admin: system/boundary marker, exclude from epoch target_events

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Stimulus/S 99, Stimulus/S 2, Stimulus/S101, Stimulus/S 35
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds002338 DOI: https://doi.org/10.18112/openneuro.ds002338.v2.0.2

Primary Task 2: Publisher-defined BIDS task: 1d NF

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002338 DOI: https://doi.org/10.18112/openneuro.ds002338.v2.0.2

Primary Task 3: Publisher-defined BIDS task: MIpost

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)

- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002338 DOI: https://doi.org/10.18112/openneuro.ds002338.v2.0.2

Normal Task 1: Motor Imagery Neurofeedback State Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: All Stimulus/S, TPULSE/, Pulse Artifact/R, Time 0/, and R128 are MRI/system admin markers - excluded. High sampling rate (5000 Hz); downsample before epoching.

Event	y	Meaning
`Rest`	0	Rest / baseline block
`Task-NF`	1	Motor imagery neurofeedback block
## Data Quality Notes		

- MRI gradient artifacts contaminate EEG; TPULSE markers indicate artifact windows.
- High sampling rate (5000 Hz); downsampling recommended.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Simultaneous MRI-EEG during a motor imagery neurofeedback task: an open access brain imaging dataset for multi-modal data integration`

172. openneuro_ds002720 - A dataset recorded during development of a tempo-based brain-computer music interface

Dataset: `openneuro_ds002720` | Year: 2020 | URL: https://openneuro.org/datasets/ds002720
Category: Action/Output | Subjects: 19 | Files (Completed): 165 | Channels: 19.0 | Sampling Rate: 1000.0 Hz

Paradigm

Participants used kinaesthetic motor imagery (imagining squeezing a ball) or relaxation to intentionally modulate the tempo of music in a continuous brain-computer music interface (BCMI) task. Event code 1 = motor_imagery (ball squeezing imagination) and code 2 = relaxation (rest), each lasting several seconds. The BCI decoded the EEG to adjust music tempo in real-time, creating a closed-loop feedback system.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002720

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`motor_imagery` (code 1)	143 (files)	long	raw	Sustained motor imagery - imagining squeezing a ball
`relaxation` (code 2)	143 (files)	long	raw	Sustained relaxation period

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)

- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds002720 DOI: https://doi.org/10.18112/openneuro.ds002720.v1.0.1

Normal Task 1: Motor Imagery BCI Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s (motor imagery window), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Motor imagery BCI task with multi-second imagination periods. Long 4-second epoch window captures the full motor imagery event. Specific kernel decodes raw codes (1->motor_imagery, 2->relaxation).

Event	y	Meaning
`motor_imagery`	0	Motor imagery - imagining squeezing a ball
`relaxation`	1	Relaxation / rest period
## Data Quality Notes		

- 19-channel EEG is low density but suitable for BCI motor imagery decoding.
- Count column (143 files) indicates files-with-event, not trial count per file.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `A dataset recorded during development of a tempo-based brain-computer music interface`

173. openneuro_ds003810 - Motor Imagery vs Rest - Low-Cost EEG System

Dataset: `openneuro_ds003810` | Year: 2021 | URL: https://openneuro.org/datasets/ds003810
Category: Action/Output | Subjects: 10 | Files (Completed): 50
Channels: 15 | Sampling Rate: 125 Hz

Paradigm

Participants performed kinesthetic motor imagery of grasping movements with the dominant hand during EEG recording using a low-cost consumer-grade EEG system. Sessions included a preliminary run of actual hand movements followed by motor imagery blocks alternating with resting-state baselines. OpenViBE (OVTK) event triggers mark trial onset, cue type, feedback, and session boundaries. The study evaluates BCI performance using motor imagery and demonstrates applicability of affordable EEG hardware.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003810

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`OVTK_GDF_Right`	50	long	raw	Right-hand motor imagery cue onset
`OVTK_GDF_Tongue`	50	long	raw	Tongue motor imagery cue onset (second class)
`OVTK_GDF_Start_Of_Trial`	50	short	raw	Trial start marker
`OVTK_GDF_Cross_On_Screen`	50	short	raw	Fixation cross display (inter-trial)
`OVTK_GDF_Feedback_Continuous`	50	short	raw	Continuous BCI feedback onset
`OVTK_GDF_End_Of_Trial`	50	short	raw	Trial end marker
`OVTK_GDF_Correct`	50	short	raw	Correct classification feedback
`OVTK_GDF_Incorrect`	50	short	raw	Incorrect classification feedback
`OVTK_StimulationId_BaselineStart`	50	rest	raw	Resting baseline period start

Event ID	Count (total)	Type	Meta Level	Meaning
OVTK_StimulationId_BaselineStop	50	rest	raw	Resting baseline period end
OVTK_StimulationId_Beep	50	short	raw	Auditory beep cue for trial start
OVTK_StimulationId_Train	48	short	raw	Training phase marker
OVTK_StimulationId_ExperimentStart	46	admin	raw	Experiment start marker
OVTK_StimulationId_ExperimentStop	48	admin	raw	Experiment stop marker
OVTK_GDF_End_Of_Session	48	admin	raw	Session end marker

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: OVTK_StimulationId_BaselineStart, OVTK_StimulationId_BaselineStop, OVTK_StimulationId_Beep, OVTK_StimulationId_Train, OVTK_StimulationId_ExperimentStart, OVTK_StimulationId_ExperimentStop
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds003810 DOI: https://doi.org/10.1016/j.heliyon.2020.e03425

Primary Task 2: Publisher-defined BIDS task: MIvs Rest RUN2

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003810 DOI: https://doi.org/10.1016/j.heliyon.2020.e03425

Primary Task 3: Publisher-defined BIDS task: MIvs Rest RUN3

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003810 DOI: https://doi.org/10.1016/j.heliyon.2020.e03425

Normal Task 1: Motor imagery category classification (binary, long event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Motor imagery periods are typically 4-6 s; use long-event epoching. 10 subjects with 5 files each (50 total). Low-cost 15-channel EEG at 125 Hz; limited spatial and temporal resolution compared to research-grade systems.

Event	y	Meaning
`OVTK_GDF_Right`	1	Right hand motor imagination period
`OVTK_GDF_Tongue`	0	Tongue movement imagination period (control type)
## Data Quality Notes		

- Low-cost EEG system; lower signal quality and spatial resolution than research-grade systems.
- Low sampling rate (125 Hz); limits temporal resolution and applicable frequency range.
- `OVTK_StimulationId_ExperimentStart/Stop` and `OVTK_GDF_End_Of_Session` are admin markers; exclude from epoching.

References

- Reference: `Motor Imagery vs Rest using a low-cost EEG system. OpenNeuro ds003810.`

174. openneuro_ds004022 - Multimodal EEG and fNIRS Biosignal Acquisition during Motor Imagery Tasks in Patients with Orthopedic Impairment

Dataset: `openneuro_ds004022` | Year: 2022 | URL: https://openneuro.org/datasets/ds004022
Category: Action/Output | Subjects: 7 | Files (Completed): 21
Channels: 18 | Sampling Rate: 500 Hz

Paradigm

Participants with orthopedic impairment performed four distinct motor imagery tasks (Reach, Twist, Lift, and Grasp) guided by visual cues across three experimental sessions. EEG and fNIRS were recorded simultaneously to study motor imagery neural patterns in a clinical population for BCI development. Each trial began with a rest cue (S 1) followed by a task cue (S 2-S 10), with S 7-S 10 encoding the four MI conditions.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004022

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`S 2`	21 files	short	raw	Cue onset (task start)
`S 7`	21 files	short	raw	Motor imagery cue - task 1 (Reach)
`S 8`	21 files	short	raw	Motor imagery cue - task 2 (Twist)
`S 9`	21 files	short	raw	Motor imagery cue - task 3 (Lift)
`S 10`	21 files	short	raw	Motor imagery cue - task 4 (Grasp)
`S 3`	21 files	short	raw	Rest period cue
`S 4`	21 files	short	raw	Rest period cue (variant)
`S 5`	21 files	short	raw	Feedback/response marker
`S 6`	21 files	short	raw	Feedback/response marker
`S 1`	21 files	short	raw	Trial start / baseline cue

Event ID	Count (total)	Type	Meta Level	Meaning
condition 12	21 files	admin	raw	Condition block marker

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: S 2, S 7, S 8, S 9, S 10, S 3, S 4, S 5
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004022 DOI: https://doi.org/10.18112/openneuro.ds004022.v1.0.0

Normal Task 1: Four-Class Motor Imagery (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Only 7 subjects; small sample size limits generalization. condition 12 is an admin/block marker to exclude. 3 sessions per subject (21 files total). Each session has 40 trials per MI class.

Event	y	Meaning
S 7	0	Motor imagery - Reach
S 8	1	Motor imagery - Twist
S 9	2	Motor imagery - Lift
S 10	3	Motor imagery - Grasp
## Data Quality Notes		

- Only 7 subjects with orthopedic impairment - very small clinical sample
- 18-channel EEG with motor cortex coverage; suitable for BCI but limited spatial resolution
- condition 12 is a block marker to exclude from epoching

References

- Reference: `Multimodal EEG and fNIRS Biosignal Acquisition during Motor Imagery Tasks in Patients with Orthopedic Impairment`

175. openneuro_ds004444 - The BMI-HDEEG dataset 1

Dataset: openneuro_ds004444 | Year: 2023 | URL: https://openneuro.org/datasets/ds004444
Category: Action/Output | Subjects: 465 | Files (Completed): 465
Channels: 130 | Sampling Rate: 1000 Hz

Paradigm

Brain-computer interfacing task based on sensorimotor rhythms (SMR) using high-density scalp EEG. Subjects performed motor imagery of four limb movements (left hand, right hand, feet, tongue) following visual cues. This is the first of four BMI-HDEEG datasets, enabling classification of motor imagery across all four classes.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004444

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
1	465xx	long	raw	Motor imagery cue - class 1 (left hand MI)
2	465xx	long	raw	Motor imagery cue - class 2 (right hand MI)
3	465xx	long	raw	Motor imagery cue - class 3 (feet MI)
4	465xx	long	raw	Motor imagery cue - class 4 (tongue MI)

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]

- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004444 DOI: https://doi.org/10.18112/openneuro.ds004444.v1.0.1

Normal Task 1: Motor Imagery Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Numerical codes 1-4 decoded by specific kernel to semantic MI labels. Extended epoch window (-0.5 to 4.0 s) captures full motor imagery period. High-density 130-channel EEG.

Event	y	Meaning
`left_hand_MI`	0	Left hand motor imagery
`right_hand_MI`	1	Right hand motor imagery
`feet_MI`	2	Feet motor imagery
`tongue_MI`	3	Tongue motor imagery
## Data Quality Notes		

- Numerical event codes (1-4) require kernel-level decoding to semantic MI labels
- 130-channel high-density EEG with extended epochs
- Large dataset (465 files); batch processing required

References

- Reference: `High-density scalp electroencephalogram dataset during sensorimotor rhythm-based brain-computer interfacing. Sci Data 10, 385 (2023)`

176. openneuro_ds004446 - The BMI-HDEEG dataset 2

Dataset: `openneuro_ds004446` | Year: 2023 | URL: https://openneuro.org/datasets/ds004446
Category: Action/Output | Subjects: 237 | Files (Completed): 237
Channels: 130 | Sampling Rate: 1000 Hz

Paradigm

A high-density EEG dataset focused on sensorimotor rhythm-based brain-computer interfacing (BCI) with three motor imagery classes (left hand, right hand, feet). This is the second of four BMI-HDEEG datasets, using the same high-density setup as dataset 1 but with a three-class motor imagery design.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004446

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`1`	237xx	long	raw	Motor imagery cue - class 1 (left hand MI)
`2`	237xx	long	raw	Motor imagery cue - class 2 (right hand MI)
`3`	237xx	long	raw	Motor imagery cue - class 3 (feet MI)

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)

- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004446 DOI: https://doi.org/10.18112/openneuro.ds004446.v1.0.1

Normal Task 1: Motor Imagery Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Numerical codes 1-3 decoded by specific kernel to semantic MI labels. Same paradigm as dataset 1 (BMI-HDEEG) but 3-class design and different subjects.

Event	y	Meaning
`left_hand_MI`	0	Left hand motor imagery
`right_hand_MI`	1	Right hand motor imagery
`feet_MI`	2	Feet motor imagery
## Data Quality Notes		

- Numerical event codes (1-3) require kernel-level decoding to semantic MI labels
- 130-channel high-density EEG with extended epochs
- 237 files; smaller than dataset 1

References

- Reference: `High-density scalp electroencephalogram dataset during sensorimotor rhythm-based brain-computer interfacing. Sci Data 10, 385 (2023)`

177. openneuro_ds004447 - The BMI-HDEEG dataset 3

Dataset: `openneuro_ds004447` | Year: 2023 | URL: https://openneuro.org/datasets/ds004447
Category: Action/Output | Subjects: 418 | Files (Completed): 418
Channels: 130 | Sampling Rate: 1000 Hz

Paradigm

A brain-computer interface (BCI) task based on sensorimotor rhythms (SMR) recorded with high-density scalp EEG. Subjects performed motor imagery of four limb movements (left hand, right hand, feet, tongue) following visual cues. This is the third of four BMI-HDEEG datasets with a four-class design, though tongue and feet classes appear in fewer files.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004447

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`1`	418xx	long	raw	Motor imagery cue - class 1 (left hand MI)
`2`	418xx	long	raw	Motor imagery cue - class 2 (right hand MI)
`3`	91xx	long	raw	Motor imagery cue - class 3 (feet MI)
`4`	91xx	long	raw	Motor imagery cue - class 4 (tongue MI)

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]

- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004447 DOI: https://doi.org/10.18112/openneuro.ds004447.v1.0.1

Normal Task 1: Motor Imagery Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Numerical codes 1-4 decoded by specific kernel. Classes 3 and 4 appear in only 91 files (subset of subjects). Binary left/right classification is the most balanced sub-task.

Event	y	Meaning
`left_hand_MI`	0	Left hand motor imagery
`right_hand_MI`	1	Right hand motor imagery
`feet_MI`	2	Feet motor imagery
`tongue_MI`	3	Tongue motor imagery
## Data Quality Notes		

- Numerical event codes (1-4) require kernel-level decoding
- Classes 3 and 4 (feet/tongue) only appear in 91 of 418 files
- 130-channel high-density EEG with extended epochs

References

- Reference: `High-density scalp electroencephalogram dataset during sensorimotor rhythm-based brain-computer interfacing. Sci Data 10, 385 (2023).`

178. openneuro_ds004448 - The BMI-HDEEG dataset 4

Dataset: openneuro_ds004448 | Year: 2023 | URL: https://openneuro.org/datasets/ds004448
Category: Action/Output | Subjects: 280 | Files (Completed): 280
Channels: 130 | Sampling Rate: 1000 Hz

Paradigm

Participants performed a sensorimotor rhythm-based brain-computer interface task using high-density scalp EEG. This is the fourth BMI-HDEEG dataset with a two-class (binary) motor imagery design (left hand vs. right hand). Only one event code is present in the data, suggesting the class label is encoded differently.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004448

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
1	280xx	long	raw	Motor imagery cue - class 1

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://openneuro.org/datasets/ds004448 DOI: https://doi.org/10.18112/openneuro.ds004448.v1.0.2

Normal Task 1: Motor Imagery Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`

- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only one numerical code (1) visible in locator_meta; actual binary class label likely encoded in events.tsv metadata columns or file-level metadata. Specific kernel required.

Event	y	Meaning
`left_hand_MI`	0	Left hand motor imagery
`right_hand_MI`	1	Right hand motor imagery
## Data Quality Notes		

- Only one event code in metadata; class label may be in events.tsv columns rather than trial_type
- 130-channel high-density EEG with extended epochs
- 280 files; binary MI design

References

- Reference: `High-density scalp electroencephalogram dataset during sensorimotor rhythm-based brain-computer interfacing. Sci Data 10, 385 (2023)`

179. openneuro_ds004505 - Real World Table Tennis

Dataset: openneuro_ds004505 | Year: 2023 | URL: https://openneuro.org/datasets/ds004505
Category: Action/Output | Subjects: 19 | Files (Completed): 19 | Channels: 64 | Sampling Rate: 500 Hz

Paradigm

Participants played real table tennis matches in two conditions: cooperative (rallying) and competitive (point-scoring). EEG was recorded during actual gameplay using a mobile EEG system. Events mark the condition type and specific ball-hit moments (moving_serve vs stationary_serve shots). The study investigates motor cortex dynamics during ecological real-world sport.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004505

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
moving_hit	~19xN	short	raw	Ball hit during moving serve condition
stationary_hit	~19xN	short	raw	Ball hit during stationary serve condition
cooperative	~19xN	long	raw	Cooperative play condition block
competitive	~19xN	long	raw	Competitive play condition block
moving_serve	~19xN	long	raw	Moving serve condition block
stationary_serve	~19xN	long	raw	Stationary serve condition block
STATUS	~19xN	admin	raw	BrainVision hardware status marker
M 1	~19xN	admin	raw	Miscellaneous hardware marker

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Table Tennis

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004505 DOI: https://doi.org/10.3390/s22155867

Normal Task 1: Hit Type Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: STATUS and M 1 are admin events - exclude from target_events. cooperative/competitive/moving_serve/stationary_serve are long condition blocks. Focus on discrete hit events for epoch-based analysis.

Event	y	Meaning
`moving_hit`	0	Ball hit in moving serve condition
`stationary_hit`	1	Ball hit in stationary serve condition
## Data Quality Notes		

- Real-world mobile EEG with significant motion artifacts expected
- STATUS and M 1 are hardware markers, not task events

References

- Reference: `Real World Table Tennis`

180. openneuro_ds006519 - Dataset of Intracranial EEG during Cortical Stimulations Evoking Negative Motor Responses

Dataset: `openneuro_ds006519` | Year: 2025 | URL: https://openneuro.org/datasets/ds006519
Category: Action/Output | Subjects: 23 | Files (Completed): 35 | Channels: 33 | Sampling Rate: 4096 Hz

Paradigm

Patients undergoing presurgical evaluation for drug-resistant epilepsy received intracranial electrical stimulation to map cortical function. The stimulation protocol targeted regions that, when stimulated, evoked negative motor responses (involuntary movement inhibition or arrest). EEG was recorded from intracranial electrodes during pre-stimulation (prestim) and post-stimulation (poststim) periods to characterize neural activity changes associated with negative motor mapping.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006519

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Comment/prestim`	35	short	raw	Pre-stimulation baseline period onset
`Comment/poststim`	35	short	raw	Post-stimulation period onset

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Comment/prestim`, `Comment/poststim`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Dcs

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification

- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006519 DOI: https://doi.org/10.18112/openneuro.ds006519.v1.0.0

Normal Task 1: Pre- vs Post-Stimulation Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Binary classification of pre- vs post-stimulation neural states. Intracranial EEG from epilepsy patients; electrode locations vary across subjects. Very high sampling rate (4096 Hz); consider downsampling.

Event	y	Meaning
`Comment/prestim`	0	Pre-stimulation baseline period
`Comment/poststim`	1	Post-stimulation response period
## Data Quality Notes		

- Intracranial EEG dataset; electrode montage is patient-specific and non-standard.
- Very high sampling rate (4096 Hz); downsampling to <=1000 Hz recommended.
- Small dataset (35 files, 23 subjects); limited sample size.

References

- Reference: `Dataset of intracranial EEG during cortical stimulations evoking negative motor responses`

181. openneuro_ds007327 - EEG During Sport-Related Motor Imagery and Observation Tasks

Dataset: openneuro_ds007327 | Year: 2026 | URL: https://openneuro.org/datasets/ds007327
Category: Action/Output | Subjects: 35 | Files (Completed): 105 | Channels: 88 | Sampling Rate: 1000 Hz

Paradigm

EEG was recorded during two sports-related tasks (ball passing and dribbling) to study motor intention and motor observation. The paradigm uses a 2x2 design crossing motor intention (MI = motor intention, MO = motor observation) with movement execution modality, yielding four compound conditions: MIMI (imagine intention), MIMO (imagine observation), MOMI (observe intention), MOMO (observe observation). Additional single-factor conditions (MI, MO, MO_MI) and a static/rest baseline are included.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds007327

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
MOMI	8396	short	raw	Motor observation of intention trials
MIMO	8394	short	raw	Motor imagination of observation trials
MOMO	8394	short	raw	Motor observation of observation trials
MIMI	8335	short	raw	Motor imagination of intention trials
static	4313	short	raw	Static baseline condition
MO	4200	short	raw	Motor observation condition
MO_MI	4198	short	raw	Motor observation with motor intention
MI	4195	short	raw	Motor intention condition
rest	4073	short	raw	Resting/baseline period

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: The official dataset page describes sport-related motor imagery and motor observation conditions that support a primary motor-intention decoding benchmark. Source: https://openneuro.org/datasets/ds007327

Normal Task 1: Motor Intention/Observation Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 9-class design; 2x2 factorial core (MIMI/MIMO/MOMI/MOMO ~8300 each) plus single-factor and baseline conditions (~4000 each). 105 files = 35 subjects x 3 task types (ballpass, dribble, passing).

Event	y	Meaning
`MIMI`	0	Motor imagination x intention
`MIMO`	1	Motor imagination x observation
`MOMI`	2	Motor observation x intention
`MOMO`	3	Motor observation x observation
`MI`	4	Motor intention
`MO_MI`	5	Motor observation with intention
`static`	6	Static baseline
`MO`	7	Motor observation
`rest`	8	Rest baseline
## Data Quality Notes		

- High channel count (88) includes 24 BIP channels for EMG/kinematic data; exclude BIP channels from EEG analysis.
- 35 subjects x 3 task files = 105 files; verify task structure.
- Apply bandpass filter (0.5-40 Hz), remove BIP channels, and artifact reject prior to epoching.

References

- No paper reference available

182. other_highgammadataset - High-Gamma EEG Motor Imagery Dataset

Dataset: `other_highgammadataset` | Year: 2017 | URL: https://gin.g-node.org/robintibor/high-gamma-dataset/src/master/data
Category: Action/Output | Subjects: 14 | Files (Completed): 28 | Channels: 133 | Sampling Rate: 500 Hz

Paradigm

Fourteen subjects performed four-class cued motor imagery (left hand, right hand, feet, tongue) while high-density EEG was recorded from 128+ channels using a NeurOne amplifier (Mega Electronics Ltd, Kuopio, FI) with a WaveGuard Original cap (ANT, Enschede, NL) at 500 Hz (Schirrmeister et al., 2017). Each subject contributed two sessions: a training set and a test set. Per session, 40-225 trials per class were recorded depending on subject. This dataset is notably used to evaluate deep learning models (EEGNet, ShallowConvNet, DeepConvNet) for motor imagery BCI and is one of the highest-density publicly available MI datasets.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision:
> https://gin.g-node.org/robintibor/high-gamma-dataset/src/master/data

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`left_hand`	~4200 total	short	raw	Left-hand motor imagery cue onset
`right_hand`	~4200 total	short	raw	Right-hand motor imagery cue onset
`feet`	~1400 total	short	raw	Feet motor imagery cue onset
`tongue`	~1400 total	short	raw	Tongue motor imagery cue onset

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Trial counts per session are variable (40-225 per class). Approximate totals across all 28 files.

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://doi.org/10.1002/hbm.23730

Normal Task 1: 4-Class Motor Imagery Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`left_hand`	0	Left-hand motor imagery
`right_hand`	1	Right-hand motor imagery
`feet`	2	Feet motor imagery
`tongue`	3	Tongue motor imagery

Normal Task 2: Left vs. Right Hand Motor Imagery (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 4.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: `left_hand` -> 0, `right_hand` -> 1 (discard feet and tongue trials).

Data Quality Notes

- No age or sex information available in the public release.
- High channel count (128+ EEG); high-gamma frequency analysis (60-300 Hz) is a primary use case.
- Trial counts are imbalanced across classes (more left/right hand than feet/tongue); balance before 4-class training.
- Two sessions per subject (train/test): separate by filename suffix for proper evaluation.

References

- Reference: Schirrmeister RT et al. (2017). Deep learning with convolutional neural networks for EEG decoding and visualization. Human Brain Mapping, 38(11), 5391-5420. https://doi.org/10.1002/hbm.23730

183. other_openbmi - OpenBMI Motor Imagery EEG Dataset

Dataset: `other_openbmi` | Year: 2019 | URL: https://gigadb.org/dataset/view/id/100542/File_page/5
Category: Action/Output | Subjects: 54 | Files (Completed): 108 | Channels: 62 | Sampling Rate: 1000 Hz

Paradigm

Fifty-four subjects (ages 19-32, mixed sex) performed two-class cued motor imagery of the left and right hand across two sessions each (Lee et al., 2019). EEG was recorded from 62 channels (BrainAmp, Brain Products; Ag/AgCl cap) at 1000 Hz. Each session contained 100 trials per class (50 left + 50 right hand MI), yielding 200 trials per session per subject. The motor imagery epoch lasts 3 seconds. Trial onset times and class labels are stored in MATLAB struct fields (`EEG_MI_train.t` for sample indices and `EEG_MI_train.y_class` for labels); the kernel extracts these and creates 3-second MNE annotations.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://gigadb.org/dataset/view/id/100542/File_page/5

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`left hand MI`	5400	short	raw	Left-hand motor imagery trial onset (50/session x 2 sessions x 54 subjects)
`right hand MI`	5400	short	raw	Right-hand motor imagery trial onset (50/session x 2 sessions x 54 subjects)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Left- vs right-hand motor imagery labels (with paradigm-specific extensions where available).

- Evidence: OpenBMI benchmark and associated publication define MI decoding as a core supervised task. Source: https://doi.org/10.1093/gigascience/giz002

Normal Task 1: Binary Motor Imagery Classification - Left vs. Right Hand (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 3.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: The annotation duration is set to 3.0 s by the kernel (matching the MI trial length). Balance: exactly 50 trials per class per session; perfectly balanced.

Event	y	Meaning
`left hand MI`	0	Left-hand motor imagery
`right hand MI`	1	Right-hand motor imagery
## Data Quality Notes		

- Subject demographics: 54 subjects, ages 19-32, mixed sex.
- Two sessions per subject enable cross-session analysis and session-to-session learning stability.
- High sampling rate (1000 Hz); consider downsampling to 250 Hz for computational efficiency.
- MATLAB struct-based event extraction; requires `EEG_MI_train` field to be present in `.mat` file.
- 62-channel standard 10-20 montage with Ag/AgCl electrodes.

References

- Reference: Lee MH et al. (2019). EEG Dataset and OpenBMI Toolbox for Three BCI Paradigms: An Investigation into BCI Illiteracy. GigaScience, 8(5), giz002. https://doi.org/10.1093/gigascience/giz002

184. physionet_eegmmidb - EEG Motor Movement/Imagery Database

Dataset: `physionet_eegmmidb` | Year: 2009 | URL: https://physionet.org/content/eegmmidb/1.0.0/
Category: Action/Output | Subjects: 109 | Files (Completed): 1526 | Channels: 64 | Sampling Rate: 160 Hz

Paradigm

One hundred and nine volunteers performed a series of motor movement and motor imagery tasks, recorded with 64 EEG electrodes (international 10-10 system) at 160 Hz using the BCI2000 system (Schalk et al., 2004). Each subject completed 14 runs (R01-R14): two baseline runs (eyes open and eyes closed), and twelve task runs organized in three repeating cycles of four run types. Task runs alternate between real movements and mental imagery of the same movements. Two movement classes are used: left/right fist, and both fists/both feet. Events T0 (rest), T1, and T2 are annotated within each run; T1/T2 meanings differ by run number.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://physionet.org/content/eegmmidb/1.0.0/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`eyes open`	109	rest	raw	Baseline recording with eyes open (R01)
`eyes closed`	109	rest	raw	Baseline recording with eyes closed (R02)
`Baseline`	~1200	rest	raw	Rest/inter-trial interval in task runs (T0)
`Open Left Fist Movement`	~327	short	raw	Real left-fist movement onset (R03/07/11 T1)
`Open Right Fist Movement`	~327	short	raw	Real right-fist movement onset (R03/07/11 T2)
`Imagine Opening Left Fist Movement`	~327	short	raw	Left-fist motor imagery onset (R04/08/12 T1)
`Imagine Opening Right Fist Movement`	~327	short	raw	Right-fist motor imagery onset (R04/08/12 T2)

Event ID	Count (total)	Type	Meta Level	Meaning
`Open Both Fists Movement`	~327	short	raw	Real both-fists movement onset (R05/09/13 T1)
`Open Both Feet Movement`	~327	short	raw	Real both-feet movement onset (R05/09/13 T2)
`Imagine Opening Both Fists Movement`	~327	short	raw	Both-fists motor imagery onset (R06/10/14 T1)
`Imagine Opening Both Feet Movement`	~327	short	raw	Both-feet motor imagery onset (R06/10/14 T2)

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Total counts are approximate across all 109 subjects x 3 repetition cycles. Per-subject per-run counts: ~20 T1 + 20 T2 per task run.

Tasks

Primary Task 1: Motor imagery decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Imagery class labels (e.g., left/right hand, feet, tongue; dataset-specific)
- Evidence: Dataset references indicate MI BCI paradigm as core benchmark. Source: https://physionet.org/content/eegmmidb/1.0.0/ DOI: https://doi.org/10.13026/C28G6P

Normal Task 1: Left vs. Right Fist Motor Imagery (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 4.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Use only runs R04, R08, R12 (imagery sessions). Run numbers are encoded in the filename (positions 5-7, e.g., `S001R04.edf`). Exclude baseline runs (R01, R02) and movement runs (R03, R07, R11) for pure imagery analysis.

Event	y	Meaning
`Imagine Opening Left Fist Movement`	0	Left-fist motor imagery (R04/08/12)
`Imagine Opening Right Fist Movement`	1	Right-fist motor imagery (R04/08/12)

Normal Task 2: Both Fists vs. Both Feet Motor Imagery (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 4.0 s, target_events = see Target Definition

- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`Imagine Opening Both Fists Movement`	0	Both-fists motor imagery (R06/10/14)
`Imagine Opening Both Feet Movement`	1	Both-feet motor imagery (R06/10/14)

Normal Task 3: 4-Class Motor Imagery (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 4.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`Imagine Opening Left Fist Movement`	0	Left-fist MI
`Imagine Opening Right Fist Movement`	1	Right-fist MI
`Imagine Opening Both Fists Movement`	2	Both-fists MI
`Imagine Opening Both Feet Movement`	3	Both-feet MI
## Data Quality Notes		

- Age and sex information are not available in the public metadata.
- Known data quality issues: several subjects have noisy recordings; EEG.physionet.org community notes suggest subjects S088, S089, S092, S100, S104 may have unusual recordings.
- T1/T2 event meaning changes by run number; always filter by run before assigning class labels.
- `Baseline` (T0) events in task runs are rest periods and should be excluded from MI classification targets.
- Low sampling rate (160 Hz); sufficient for motor imagery but limits high-frequency analysis.

References

- Reference: Schalk G, McFarland DJ, Hinterberger T, Birbaumer N, Wolpaw JR (2004). BCI2000: A general-purpose brain-computer interface (BCI) system. IEEE Transactions on Biomedical Engineering, 51(6), 1034-1043. https://physionet.org/content/eegmmidb/1.0.0/

185. physionet_erpbci - ERP-Based Brain-Computer Interface Recordings

Dataset: `physionet_erpbci` | Year: 2013 | URL: https://physionet.org/content/erpbci/1.0.0/
Category: Action/Output | Subjects: 21 | Files (Completed): 245 | Channels: 70 | Sampling Rate: 2048 Hz

Paradigm

Participants spelled characters using a standard 6x6 matrix speller while EEG was recorded with a BioSemi ActiveTwo system (64 EEG + 2 earlobe reference + 4 EOG channels) at 2048 Hz (Riccio et al., 2013). Each row and column of the 6x6 character matrix was randomly intensified for 100 ms with a 50 ms gap (150 ms SOA). Each row/column flashed approximately 20 times per trial, and participants mentally counted target character flashes to sustain attention. The kernel processes raw row/column flash events and classifies each as `seen` (target - the row or column containing the attended character flashed) or `unseen` (non-target) for both rows and columns separately.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://physionet.org/content/erpbci/1.0.0/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`seen (row)`	varies	short	raw	Target row flash (attended character's row lit up)
`seen (column)`	varies	short	raw	Target column flash (attended character's column lit up)
`unseen (row)`	varies	short	raw	Non-target row flash
`unseen (column)`	varies	short	raw	Non-target column flash

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Each 6x6 speller has 6 rows + 6 columns = 12 flashes per sequence; 2 are target (1 row + 1 column), 10 are non-target.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://physionet.org/content/erpbci/1.0.0/ DOI: https://doi.org/10.13026/C2101S

Normal Task 1: P300 Target vs. Non-Target Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.1 s, tmax = 0.8 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Combine `seen (row)` and `seen (column)` as the positive class (y=1); class imbalance ~1:5 (2 target vs 10 non-target per sequence). EOG channels (VEOGL, VEOGR, HEOGL, HEOGR) should be excluded from EEG features.

Event	y	Meaning
`seen (row)`	1	P300 target - attended row flash
`seen (column)`	1	P300 target - attended column flash
`unseen (row)`	0	Non-target row flash
`unseen (column)`	0	Non-target column flash

Normal Task 2: Row vs. Column P300 Speller (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.1 s, tmax = 0.8 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Separate row and column targets for character-level decoding. Use `seen (row)` to identify the target row and `seen (column)` to identify the target column; their intersection determines the spelled character.

Data Quality Notes

- Very high sampling rate (2048 Hz); consider downsampling to 256 or 512 Hz for computational efficiency.
- Class imbalance: 2 target flashes vs. 10 non-target flashes per sequence (1:5 ratio); balance with oversampling or cost-sensitive learning.
- EOG channels present (4 channels); apply artifact rejection before P300 classification.
- Age and sex information are not available.

References

- Reference: Riccio A et al. (2013). Interfacing Brain with Computer to Improve Communication and Rehabilitation after Spinal Cord Injury. Frontiers in Neuroengineering. Goldberger AL et al. (2000). PhysioBank, PhysioToolkit, and PhysioNet. https://physionet.org/content/erpbci/1.0.0/

Chapter 4. Sensory/Response

Datasets in this chapter: 52. Basic stimulus-response, ERP/SSVEP/RSVP, or simple attention tasks.

186. openneuro_ds001810 - EEG study of the attentional blink; before, during, and after transcranial Direct Current Stimulation (tDCS)

Dataset: `openneuro_ds001810` | Year: 2019 | URL: https://openneuro.org/datasets/ds001810
Category: Sensory/Response | Subjects: 40 | Files (Completed): 527 | Channels: 73.0 | Sampling Rate: 512.0 Hz

Paradigm

Participants performed an attentional blink (AB) task using a Rapid Serial Visual Presentation (RSVP) stream to identify two targets (T1 and T2) embedded in a stream of distractors. EEG was recorded before, during, and after receiving anodal or cathodal transcranial Direct Current Stimulation (tDCS) to study how cortical excitability modulates the attentional blink - the impaired detection of T2 when it follows T1 within ~500 ms. BioSemi STATUS channel encodes trial conditions as numeric codes.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds001810

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`T1_present_T2_present_lag3`	large	short	raw	T1 and T2 both present, short lag (within AB window)
`T1_present_T2_absent_lag3`	large	short	raw	T1 present, T2 absent, short lag
`T1_absent_T2_present`	large	short	raw	T1 absent, T2 present
`T1_T2_lag8`	large	short	raw	T1 and T2 at long lag (outside AB window)
`T1_onset`	large	short	raw	T1 target onset
`T2_onset`	large	short	raw	T2 target onset
`CM_baseline` (61440)	261 files	admin	raw	BioSemi CM_in_range baseline - exclude

Event ID	Count (total)	Type	Meta Level	Meaning
CM_out_of_range (61694)	263 files	admin	raw	BioSemi CM status - exclude
stimulus_onset (61468)	large	short	raw	General stimulus onset

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
- long: sustained-state marker (>=2 s), for epoch_by_long_event_hdf5
- rest: resting-state segment marker, for epoch_by_segmentation_hdf5
- admin: system/boundary marker, exclude from epoch target_events

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: stimulus_onset
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Attentional blink

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds001810 DOI: https://doi.org/10.18112/openneuro.ds001810.v1.1.0

Normal Task 1: Attentional Blink Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: BioSemi STATUS codes decoded via specific kernel (TODO: verify exact code mapping from original paper doi.org/10.1111/j.1469-8986.2010.01081.x). CM_baseline (61440) and CM_out_of_range (61694) are admin markers excluded. Regression target: response_time.

Event	y	Meaning
T1_present_T2_present_lag3	0	T2 detected within AB window
T1_present_T2_absent_lag3	1	T2 missed within AB window

Event	y	Meaning
`T1_absent_T2_present`	2	T2 present without T1
`T1_T2_lag8`	3	T2 detected outside AB window (control)
`T1_onset`	4	T1 target onset
`T2_onset`	5	T2 target onset
## Data Quality Notes		

- BioSemi STATUS channel encodes all triggers numerically; specific kernel maps codes to human-readable labels.
- `61440` (CM_in_range) and `61694` (CM_out_of_range) are BioSemi hardware status codes - exclude from analysis.
- Large dataset (527 files, 40 subjects x pre/during/post x anodal/cathodal conditions).
- Verify that event code mapping is correct against the original paper before downstream use.

References

- Reference: `EEG study of the attentional blink; before, during, and after transcranial Direct Current Stimulation (tDCS)`

187. openneuro_ds002218 - Auditory and Visual Rhythm Omission EEG

Dataset: openneuro_ds002218 | Year: 2019 | URL: https://openneuro.org/datasets/ds002218
Category: Sensory/Response | Subjects: 18 | Files (Completed): 18
Channels: 32 | Sampling Rate: 256 Hz

Paradigm

Participants passively perceived rhythmic auditory tone sequences and visual flashing stimuli that occasionally omitted an expected beat, to study predictive neural activity (mismatch responses) versus sensory evoked responses. The paradigm investigates how the brain generates predictions based on temporal regularities and detects violations of expected rhythmic patterns. Only BioSemi STATUS admin markers are detectable in the locator metadata; no decoded trial events are available from the locator pipeline.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002218

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
STATUS	18 (files)	admin	raw	BioSemi system status marker - exclude from epoch

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Experiment

- Task Type: classification/segmentation

- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: The accompanying paper studies neural entrainment and omission responses for this auditory/visual rhythm paradigm. Source: https://openneuro.org/datasets/ds002218 DOI: https://doi.org/10.1111/ejn.15314

Normal Task 1: Resting / Continuous Segmentation (resting)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null(only STATUS admin events; no trial markers decoded))
- Notes: STATUS is a BioSemi CM_in_range hardware marker. If events.tsv contains decoded rhythm onset/omission events (separate from the locator metadata), they could be used for ERP analysis - verify directly from raw events.tsv.

Data Quality Notes

- Only `STATUS` events found in locator metadata - BioSemi admin markers only.
- The actual auditory/visual rhythm and omission events may be encoded in the `events.tsv` files but were not decoded by the locator pipeline; check events.tsv directly.
- Verify channel count consistency across subjects before pooling.

References

- Reference: Comstock DC, Ross JM, Balasubramaniam R. Modality-specific frequency band activity during neural entrainment to auditory and visual rhythms. European Journal of Neuroscience. DOI: https://doi.org/10.1111/ejn.15314

188. openneuro_ds002578 - Visual Oddball Task (256 channels)

Dataset: `openneuro_ds002578` | Year: 2021 | URL: https://openneuro.org/datasets/ds002578
Category: Sensory/Response | Subjects: N/A | Files (Completed): 2 | Channels: 256.0 | Sampling Rate: 256.0 Hz

Paradigm

A visual oddball task designed to study selective attention using event-related potentials with high-density 256-channel electrode coverage. Despite the task description implying trial-level stimuli (standard vs. oddball), no event markers were detected in the BIDS EEG files. The dataset contains only 2 completed files and is a very small subset.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002578

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
(none)	-	-	raw	No event markers detected in EEG files

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://openneuro.org/datasets/ds002578 DOI: https://doi.org/10.1523/JNEUROSCI.3477-07.2007

Normal Task 1: Resting / Continuous Segmentation (resting)

- Task Type: regression

- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (no trial-level labels available))
- Notes: Only 2 completed files available - very small dataset. High-density 256-channel EEG provides spatial richness. Check events.tsv directly for potential trial markers not captured in locator pipeline.

Data Quality Notes

- Only 2 completed EEG files - extremely limited dataset size.
- No event markers detected despite visual oddball paradigm description.
- High-density 256-channel array; verify electrode positions from channel info files.

References

- Reference: `Visual Oddball Task (256 channels)`

189. openneuro_ds002680 - Go-nogo categorization and detection task

Dataset: openneuro_ds002680 | Year: 2021 | URL: https://openneuro.org/datasets/ds002680
Category: Sensory/Response | Subjects: N/A | Files (Completed): 350 | Channels: 31.0 | Sampling Rate: 1000.0 Hz

Paradigm

Participants performed a visual go/no-go paradigm involving rapid animal categorization and image recognition tasks with brief 20 ms stimulus presentations. Go trials required a button-press response when an animal was detected (or a target category matched); no-go trials required withholding response. Each run contains approximately 100 stimulus events and ~50 response events, suggesting roughly 50% go rate. The paradigm studies rapid visual processing and response inhibition.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, reaction time, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002680

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stimulus`	~35,000 (350x100)	short	raw	Visual stimulus onset (20 ms image presentation)
`response`	~18,000 (350x52)	short	raw	Button-press go response

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `reaction_time`, `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`

- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stimulus`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Gonogo

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002680 DOI: https://doi.org/10.1016/j.cogbrainres.2003.11.010

Normal Task 1: Stimulus-Locked ERP / Reaction Time Regression (regression)

- Task Type: regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to stimulus onset), target_events = see Target Definition
- Label Route: `misc`
- Target Definition: N/A (null (regression only; stimulus serves as epoch anchor))
- Notes: Go/no-go structure: ~100 stimuli per run, ~52 responses (go trials). Regression target is response_time on go trials. For classification, go vs no-go labels would need to be inferred from presence/absence of a response after each stimulus.
- Regression target: `response_time` (reaction time from stimulus to response, from misc channel)

Data Quality Notes

- Large dataset: 350 runs; verify subject/session structure from BIDS metadata.
- ~50% go rate per run based on stimulus (100) vs response (52) counts.
- 1000 Hz sampling rate; consider downsampling to 250 Hz for efficiency.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Go-nogo categorization and detection task`

190. openneuro_ds002814 - A Multimodal Neuroimaging Dataset to Study Spatiotemporal Dynamics of Visual Processing in Humans

Dataset: `openneuro_ds002814` | Year: 2021 | URL: https://openneuro.org/datasets/ds002814
Category: Sensory/Response | Subjects: N/A | Files (Completed): 168 | Channels: 68.0 | Sampling Rate: 1200.0 Hz

Paradigm

A multimodal neuroimaging study (EEG + MEG/MRI) investigating the spatiotemporal dynamics of visual processing in humans. Despite the dataset title implying an active visual processing task, no event markers are detectable in the BIDS EEG files. The visual stimulation protocol may be encoded in other modality files or events are not available in the EEG files processed by the locator pipeline.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002814

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
(none)	-	-	raw	No event markers detected in EEG files

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: Publisher-defined BIDS task: Task category Selectivity

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002814 DOI: https://doi.org/10.18112/openneuro.ds002814.v1.3.0

Primary Task 2: Publisher-defined BIDS task: TODO: full task name for category Selectivity

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds002814 DOI: https://doi.org/10.18112/openneuro.ds002814.v1.3.0

Normal Task 1: Resting / Continuous Segmentation (resting)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (no trial-level labels available))
- Notes: No event markers found in EEG locator metadata. High sampling rate (1200 Hz); downsampling recommended. Part of a multimodal dataset - check MEG/MRI files for corresponding event timing.

Data Quality Notes

- No event markers detected in any of the 168 EEG files.
- High sampling rate (1200 Hz); downsampling required before most analyses.
- Part of multimodal dataset; MEG or MRI-derived event timing may be applicable if aligned.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `A Multimodal Neuroimaging Dataset to Study Spatiotemporal Dynamics of Visual Processing in Humans`

191. openneuro_ds002893 - Auditory-Visual Shift Study

Dataset: openneuro_ds002893 | Year: 2022 | URL: https://openneuro.org/datasets/ds002893
Category: Sensory/Response | Subjects: 49 | Files (Completed): 52 | Channels: 36.0 | Sampling Rate: 250.0 Hz

Paradigm

An interleaved dual-oddball task in which subjects selectively attended to either auditory or visual stimuli while switching between modalities based on spoken and printed attention cue instructions. The study investigated modality-specificity of sensory aging in vision and audition using event-related potentials. Attention states (attend_auditory, attend_visual) are sustained conditions lasting multiple trials; shift_attention marks the transition cue between modalities.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002893

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
attend_auditory	51 (files)	long	raw	Sustained auditory attention block
attend_visual	51 (files)	long	raw	Sustained visual attention block
shift_attention	49 (files)	admin	raw	Attention shift cue - transition marker between blocks

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - long: sustained-state marker (>=2 s), for epoch_by_long_event_hdf5
> - rest: resting-state segment marker, for epoch_by_segmentation_hdf5
> - admin: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Target vs non-target stimulus events

- Evidence: P300/oddball paradigm appears as core study objective. Source: https://openneuro.org/datasets/ds002893 DOI: https://doi.org/10.18112/openneuro.ds002893.v2.0.0

Normal Task 1: Attention Modality Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `shift_attention` is a transition cue - it marks the moment of modality switching, not a sustained state; treat as admin. The `attend_*` events mark the onset of sustained attention blocks of multiple seconds.

Event	y	Meaning
`attend_auditory`	0	Sustained auditory attention block
`attend_visual`	1	Sustained visual attention block
## Data Quality Notes		

- `shift_attention` marks attention shift cues - not a sustained state; exclude from classification target.
- Count column reflects files-with-event (51 subjects out of 52 files), not per-session trial count.
- Older adult participants (aging study); verify age distribution from participants.tsv.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Modality-specificity of sensory aging in vision and audition: evidence from event-related potentials. Brain research, 1215, pp.53-68.`

192. openneuro_ds003061 - EEG data from an auditory oddball task

Dataset: openneuro_ds003061 | Year: 2022 | URL: https://openneuro.org/datasets/ds003061
Category: Sensory/Response | Subjects: 39 | Files (Completed): 39
Channels: 79 | Sampling Rate: 256 Hz

Paradigm

An auditory three-stimulus oddball task in which participants pressed a key in response to infrequent target tones among frequent standard tones and rare distractor tones. The paradigm is designed to elicit P300 event-related potentials. Event labels stimulus (tone onset) and response (keypress) are present in all 39 files; STATUS appears as a BioSemi admin marker in 2 files.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, reaction time, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003061

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
stimulus	39 (files)	short	raw	Auditory tone stimulus onset
response	39 (files)	short	raw	Participant keypress response
STATUS	2 (files)	admin	raw	BioSemi system status marker - exclude

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

MISC Label Summary

- Route: misc
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: reaction_time, response_time
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: stimulus, STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://openneuro.org/datasets/ds003061 DOI: https://doi.org/10.18112/openneuro.ds003061.v1.1.2

Normal Task 1: Stimulus-Locked Auditory ERP/Regression (binary + regression)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: STATUS is a BioSemi CM_in_range admin marker - excluded. response marks keypresses; reaction time computed per trial. The events.tsv trial_type may further distinguish standard, target, and distractor tone types - check for sub-classification.

Event	y	Meaning
stimulus	0	Auditory tone onset

- Regression target:response_time(reaction time from stimulus to response, from misc channel)

Data Quality Notes

- STATUS is a BioSemi hardware marker - not a task event; exclude from target_events.
- response events mark keypresses; sub-classification by tone type (standard/target/distractor) requires events.tsv lookup.
- 79-channel BioSemi EEG; check consistent montage across subjects.
- Verify channel count consistency across subjects before pooling.

References

- Reference: EEG data from an auditory oddball task

193. openneuro_ds003190 - Assessment of the visual stimuli properties in P300 paradigm

Dataset: `openneuro_ds003190` | Year: 2020 | URL: https://openneuro.org/datasets/ds003190
Category: Sensory/Response | Subjects: 19 | Files (Completed): 384
Channels: 9 | Sampling Rate: 256 Hz

Paradigm

A P300 ERP experiment evaluating the effects of stimulus count and visual presentation styles (standard flash vs. cartoon face) on EEG brain activity. The experiment used a P300-based BCI paradigm with target and non-target stimulus flashes. Codes 1-9 represent different stimulus conditions or counts; codes 100-203 range encode specific stimulus configurations. The dataset has 19 subjects with many runs (384 files total).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003190

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`1`	382 (files)	short	raw	P300 stimulus condition 1 (non-target flashx)
`2`	382 (files)	short	raw	P300 stimulus condition 2 (non-target flashx)
`3`	382 (files)	short	raw	P300 stimulus condition 3
`4`	382 (files)	short	raw	P300 stimulus condition 4
`200`	382 (files)	short	raw	P300 stimulus configuration 200
`201`	382 (files)	short	raw	P300 stimulus configuration 201
`202`	382 (files)	short	raw	P300 stimulus configuration 202
`203`	382 (files)	short	raw	P300 stimulus configuration 203
`101`	363 (files)	short	raw	P300 target flash condition 101

Event ID	Count (total)	Type	Meta Level	Meaning
102	354 (files)	short	raw	P300 target flash condition 102
103	368 (files)	short	raw	P300 target flash condition 103
104	370 (files)	short	raw	P300 target flash condition 104
5	326 (files)	short	raw	P300 stimulus condition 5
105	305 (files)	short	raw	P300 target flash condition 105
6	224 (files)	short	raw	P300 stimulus condition 6
106	212 (files)	short	raw	P300 target flash condition 106
7	169 (files)	short	raw	P300 stimulus condition 7
107	161 (files)	short	raw	P300 target flash condition 107
8	112 (files)	short	raw	P300 stimulus condition 8
108	110 (files)	short	raw	P300 target flash condition 108
9	56 (files)	short	raw	P300 stimulus condition 9
109	47 (files)	short	raw	P300 target flash condition 109

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://openneuro.org/datasets/ds003190 DOI: https://doi.org/10.18112/openneuro.ds003190.v1.0.1

Normal Task 1: P300 Target vs Non-Target Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Specific kernel decodes numeric codes into semantic labels (target_flash, nontarget_flash). 9-channel EEG is very sparse; focus on occipital and parietal channels for P300. Regression target `response_time` available.

Event	y	Meaning
`target_flash`	0	Target stimulus flash (P300 target)
`nontarget_flash`	1	Non-target stimulus flash
## Data Quality Notes		

- Very sparse 9-channel EEG; limited spatial coverage.
- 384 files across 19 subjects = ~20 runs/subject; verify session structure.
- Numeric trigger codes require specific kernel to decode semantic P300 target/non-target labels.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Assessment of the visual stimuli properties in P300 paradigm`

194. openneuro_ds003490 - EEG: 3-Stim Auditory Oddball and Rest in Parkinson's

Dataset: `openneuro_ds003490` | Year: 2021 | URL: https://openneuro.org/datasets/ds003490
Category: Sensory/Response | Subjects: 50 | Files (Completed): 75
Channels: 67 | Sampling Rate: 500 Hz

Paradigm

A three-stimulus auditory oddball task (standard tones, target tones requiring button-press response, and novel distractor tones) combined with resting-state (eyes open and eyes closed) EEG recordings in Parkinson's disease patients and age-matched healthy controls. The study aims to identify auditory P300 and mismatch negativity differences between PD patients and controls. STATUS is a BioSemi admin marker.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003490

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Standard Tone`	75 (files)	short	raw	Frequent standard auditory tone (non-target)
`Target Tone`	75 (files)	short	raw	Infrequent target tone (requires button press)
`Novel Tone`	75 (files)	short	raw	Rare novel distractor tone
`Eyes Closed`	75 (files)	long	raw	Eyes-closed resting state block
`Eyes Open`	75 (files)	long	raw	Eyes-open resting state block
`STATUS`	75 (files)	admin	raw	BioSemi system status marker - exclude

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `STATUS`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://openneuro.org/datasets/ds003490 DOI: https://doi.org/10.18112/openneuro.ds003490.v1.1.0

Normal Task 1: Auditory Tone Type Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 0.8 s (relative to tone onset, P300 window), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `STATUS` is BioSemi admin marker - excluded. Tone events are short stimuli (~50 ms), not sustained states; `epoch_by_event_hdf5` is appropriate. Eyes-open/closed are separate resting blocks - do not mix with tone targets. PD vs HC group labels available in participants.tsv.

Event	y	Meaning
`Standard Tone`	0	Frequent standard tone (non-target)
`Novel Tone`	1	Rare novel distractor tone (P3a)
`Target Tone`	2	Infrequent target tone (P3b)

Normal Task 2: Resting State Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`Eyes Open`	0	Eyes-open resting block
`Eyes Closed`	1	Eyes-closed resting block
## Data Quality Notes		

- `STATUS` is BioSemi hardware marker - exclude.
- Dataset includes both Parkinson's patients and age-matched controls; group label from participants.tsv.
- Three-stimulus oddball design provides Standard/Target/Novel tone categories for ERP analysis.

- Verify channel count consistency across subjects before pooling.

References

- Reference: `EEG: 3-Stim Auditory Oddball and Rest in Parkinson's`

195. openneuro_ds003522 - EEG: Three-Stimulus Auditory Oddball and Rest in Acute and Chronic TBI

Dataset: openneuro_ds003522 | Year: 2021 | URL: https://openneuro.org/datasets/ds003522
Category: Sensory/Response | Subjects: 62 | Files (Completed): 196
Channels: 65 | Sampling Rate: 500 Hz

Paradigm

This study investigates EEG markers in mild traumatic brain injury (mTBI) using a three-stimulus auditory oddball task and resting-state recordings. Participants (sub-acute mTBI patients, chronic mTBI patients, and healthy controls) passively listened to standard, novel, and target tones while performing a target detection task. Resting-state blocks with eyes open and eyes closed were also recorded. The P3a and P3b ERP components - reflecting bottom-up and top-down attentional processes - are the primary measures examined as TBI biomarkers.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003522

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Standard Tone`	194	short	raw	Frequent standard auditory tone (non-target)
`Novel Tone`	194	short	raw	Rare novel/distractor tone eliciting P3a
`Target Tone`	194	short	raw	Rare target tone requiring button press (P3b)
`Eyes Open`	196	rest	raw	Eyes-open resting-state block marker
`Eyes Closed`	196	rest	raw	Eyes-closed resting-state block marker
`STATUS`	196	admin	raw	System status marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`

- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://doi.org/10.1016/j.neuropsychologia.2019.107125

Normal Task 1: Oddball three-category classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Classic 3-stimulus oddball. Standard tones are ~80% frequent (~184/file), novel and target each ~10% (~38/file). Class imbalance: undersample standards or weight loss. Eyes-open/closed events are resting-state block markers lasting several minutes each and are not trial-level stimuli.

Event	y	Meaning
Standard Tone	0	Standard frequent tone
Novel Tone	1	Novel interference tone (P3a)
Target Tone	2	Target pitch (P3b)
## Data Quality Notes		

- Eyes Open/Closed markers are resting block delimiters, not instantaneous trial events; do not epoch them as stimuli.
- Some files contain "Eyes Open: Every 1000 ms" style sub-event annotations; these are timing markers within rest blocks.
- Clinical groups (acute mTBI, chronic mTBI, controls) should be used as stratification variables.

References

- Reference: ERPs predict symptomatic distress and recovery in sub-acute mild traumatic brain injury. Neuropsychologia, 2019. DOI: 10.1016/j.neuropsychologia.2019.107125

196. openneuro_ds003570 - EEG: Improvisation and Musical Structures (Auditory Oddball Chords)

Dataset: `openneuro_ds003570` | Year: 2021 | URL: https://openneuro.org/datasets/ds003570
Category: Sensory/Response | Subjects: 34 | Files (Completed): 34
Channels: 64 | Sampling Rate: 2048 Hz

Paradigm

Participants listened to sequences of three-chord musical progressions in an oddball paradigm designed to detect functional and exemplar deviants occurring within a stream of standard chord progressions. The study investigates neural responses (mismatch negativity, P600) to harmonic violations and musical structure deviants, probing the auditory system's predictive coding of musical sequences. Only STATUS system markers were detected in the EEG data; the chord-level event annotations may be stored externally.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003570

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
STATUS	34	admin	raw	System status marker (only detected event)

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: STATUS
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://openneuro.org/datasets/ds003570 DOI: https://doi.org/10.18112/openneuro.ds003570.v1.0.0

Normal Task 1: Continuous EEG segmentation

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `stim`
- Target Definition: N/A (null (no labels, for unsupervised analysis))
- Notes: Only STATUS admin markers detected; no chord-level event annotations in EEG triggers. High sampling rate (2048 Hz). If events.tsv contains chord onset information, epoching by event may be feasible with custom preprocessing.

Data Quality Notes

- Very high sampling rate (2048 Hz); high memory requirements.
- No usable task events detected in EEG triggers beyond STATUS admin marker.
- Chord-level event timing may require reconstruction from audio or behavioral logs.

References

- Reference: `EEG dataset on improvisation and musical structures. OpenNeuro ds003570.`

197. openneuro_ds003645 - Face Processing MEEG Dataset with HED Annotation

Dataset: openneuro_ds003645 | Year: 2023 | URL: https://openneuro.org/datasets/ds003645
Category: Sensory/Response | Subjects: 18 | Files (Completed): 114
Channels: 395 | Sampling Rate: 1100 Hz

Paradigm

Participants performed a simple perceptual task judging the spatial symmetry of famous, unfamiliar, and scrambled faces during simultaneous MEG and EEG (MEEG) recording. This is a replication of the Wakeman and Henson (2015) dataset with Hierarchical Event Descriptor (HED) annotations added. The study serves as a reference dataset for multimodal neuroimaging analysis methods, with face symmetry judgment as the overt task while examining neural responses to face identity and familiarity.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003645

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
-	-	-	raw	No EEG trigger markers detected; events encoded in HED annotations or MEEG-specific channels

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Face Perception

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)

- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003645 DOI: https://doi.org/10.18112/openneuro.ds003645.v2.0.2

Normal Task 1: Continuous EEG segmentation

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (HED annotation requires additional parsing))
- Notes: 395-channel MEEG dataset (MEG + EEG combined); only EEG channels are relevant here. Very high channel count. Face stimuli (famous/unfamiliar/scrambled) are annotated via HED; standard BIDS event reading should recover trial_type if events.tsv is properly formatted.

Data Quality Notes

- MEEG dataset; 395 channels include both MEG and EEG sensors. Isolate EEG channels before analysis.
- No EEG trigger events detected in the EEG .set files; events may be in MEEG-format files or HED sidecar.
- Very high sampling rate (1100 Hz) and channel count; high computational requirements.

References

- Reference: `Wakeman and Henson (2015) / Robbins et al. (2021). Face processing MEEG dataset with HED annotation.`

198. openneuro_ds003690 - EEG, ECG and Pupil Data from Young and Older Adults: Rest and Auditory Cued Reaction Time Tasks

Dataset: `openneuro_ds003690` | Year: 2021 | URL: https://openneuro.org/datasets/ds003690
Category: Sensory/Response | Subjects: 75 | Files (Completed): 375
Channels: 66 | Sampling Rate: 500 Hz

Paradigm

Young and older adults performed auditory-cued simple reaction time and go/no-go tasks to investigate age-related differences in neural and physiological activity. An auditory cue preceded each trial; participants pressed a button to go stimuli and withheld responses to no-go stimuli. Error feedback tones were provided after commission errors. Resting-state EEG was also recorded. The study examines how aging affects preparatory neural activity, inhibitory control, and pupil dilation responses.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: reaction time
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003690

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`cue`	375	short	raw	Auditory warning cue preceding stimulus
`go`	300	short	raw	Go stimulus (respond with button press)
`no-go`	150	short	raw	No-go stimulus (withhold response)
`button press`	300	short	raw	Participant button-press response
`error of commission`	64	short	raw	Commission error (response to no-go)
`error feedback tone`	179	short	raw	Auditory error feedback tone
`task start`	320	short	raw	Task block start marker
`task end`	375	short	raw	Task block end marker

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `reaction_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

Tasks

Primary Task 1: Publisher-defined BIDS task: Gonogo

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003690 DOI: https://doi.org/10.1016/j.neurobiolaging.2018.09.028

Primary Task 2: Publisher-defined BIDS task: Passive

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003690 DOI: https://doi.org/10.1016/j.neurobiolaging.2018.09.028

Primary Task 3: Publisher-defined BIDS task: Simple RT

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003690 DOI: https://doi.org/10.1016/j.neurobiolaging.2018.09.028

Normal Task 1: Go/No-go classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition

- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Go:No-go ratio is 2:1 (~300 go vs ~150 no-go); mild class imbalance. 375 files from 75 subjects x 5 sessions each. Age group (young/older) in participants.tsv can be used as a grouping variable.

Event	y	Meaning
`go`	1	Go stimulation (reaction required)
`no-go`	0	No-go stimulation (requires suppression)

Normal Task 2: Correct/Error Suppression Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Commission errors (64 total) are rare compared to correct inhibitions; severe class imbalance requires oversampling or weighted loss.

Event	y	Meaning
`no-go` (correct inhibition)	0	Correct inhibition no-go
`error of commission`	1	Error response (key pressed during no-go)
## Data Quality Notes		

- 66-channel EEG; includes ECG and pupil data (non-EEG channels should be excluded).
- Longitudinal design with 5 sessions per subject; verify session consistency.
- Age group comparison (young vs older) is the primary experimental variable.

References

- Reference: `Age-related differences in EEG, ECG and pupilography during auditory cued reaction time tasks. OpenNeuro ds003690.`

199. openneuro_ds003800 - Auditory Gamma Entrainment

Dataset: openneuro_ds003800 | Year: 2021 | URL: https://openneuro.org/datasets/ds003800
Category: Sensory/Response | Subjects: 8 | Files (Completed): 24
Channels: 19 | Sampling Rate: 250 Hz

Paradigm

Elderly participants with dementia received 40 Hz amplitude-modulated (AM) auditory stimulation to induce gamma-band entrainment of brain oscillations. The paradigm alternated between active 40 Hz AM stimulation (Stimulus) periods and quiet rest periods. The study investigates whether auditory gamma entrainment can modulate neural oscillations in a dementia population, potentially as a therapeutic intervention. EEG was recorded using a standard 10-20 system.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003800

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus`	13	long	raw	40 Hz AM auditory stimulation period onset
`Rest`	13	long	raw	Resting/quiet period

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Auditory Gamma Entrainment

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003800 DOI: https://doi.org/10.18112/openneuro.ds003800.v1.0.0

Primary Task 2: Publisher-defined BIDS task: Rest

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003800 DOI: https://doi.org/10.18112/openneuro.ds003800.v1.0.0

Normal Task 1: Stimulation period vs resting period (binary, long event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Stimulation and rest periods are sustained states (likely 1-5 min each); use long-event epoching. Only 8 subjects and 24 files - very small dataset. 19-channel EEG (10-20 system).

Event	y	Meaning
`Stimulus`	1	40 Hz AM auditory stimulation activation period
`Rest`	0	Rest/quiet period
## Data Quality Notes		

- Very small dataset (8 subjects, 24 files); results may not generalize.
- Elderly dementia population; data quality may be variable.
- 19-channel 10-20 EEG; limited spatial resolution.
- 250 Hz sampling rate; adequate for gamma entrainment analysis up to 125 Hz.

References

- Reference: `Auditory Gamma Entrainment in Elderly with Dementia. OpenNeuro ds003800.`

200. openneuro_ds003825 - Human electroencephalography recordings from 50 subjects for 22,248 images from 1,854 object concepts

Dataset: `openneuro_ds003825` | Year: 2022 | URL: https://openneuro.org/datasets/ds003825
Category: Sensory/Response | Subjects: 50 | Files (Completed): 100
Channels: 64 | Sampling Rate: 250 Hz

Paradigm

Participants viewed a large-scale set of 22,248 images spanning 1,854 object concepts presented in rapid serial visual presentation (RSVP) streams at 10 Hz while performing a fixation color change detection task. The study aimed to record high-resolution neural representations of everyday objects across a large stimulus set. Each image was presented for 100 ms in continuous streams, and participants responded to a concurrent fixation task to maintain attention.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003825

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`E 1`	~1,237,200	short	raw	Image onset (RSVP stimulus)
`E 2`	~1,237,200	short	raw	Second trial-type marker (redundant or condition flag)
`E 3`	~4,200	short	raw	Block/sequence boundary or target event

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Rsvp

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003825 DOI: https://doi.org/10.1167/13.10.1

Normal Task 1: RSVP Image Viewing (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Extremely large dataset (~1.2M epochs per event type across 50 subjects). E 1 and E 2 occur in equal counts per subject (~22,248 each); E 3 is rare (~84 per subject) and may indicate special events or fixation targets. Consider subsampling for practical use.

Event	y	Meaning
`E 1`	0	RSVP image onset (primary stimulus stream)
`E 2`	1	Secondary condition marker
## Data Quality Notes		

- Data from derivatives/eeglab directory; preprocessed with EEGLAB
- Very high epoch count (~24,648 E 1 events per subject); memory management required during HDF5 generation
- Sub-06 has fewer events (~12,360), suggesting a partial recording

References

- Reference: `Grootswagers, T., Zhou, I., Robinson, A.K. et al. Human EEG recordings for 1,854 concepts presented in rapid serial visual presentation streams. Sci Data 9, 3 (2022).`

201. openneuro_ds004010 - MAVIS

Dataset: openneuro_ds004010 | Year: 2022 | URL: https://openneuro.org/datasets/ds004010
Category: Sensory/Response | Subjects: 24 | Files (Completed): 24
Channels: 64 | Sampling Rate: 1000 Hz

Paradigm

A multisensory detection task (MAVIS) in which participants identified auditory and visual targets embedded within simultaneous audio-visual noise streams to investigate selective attention and crossmodal sensory processing. The dataset contains continuous EEG recordings without discrete event markers, suggesting the stimuli were presented as ongoing streams rather than discrete trials.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004010

Event Structure

No event markers detected (no_events). This dataset contains continuous EEG recordings without trial-level annotations.

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

Event ID	Count (total)	Type	Meta Level	Meaning
no_events	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Publisher-defined BIDS task: MAVIS

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)

- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004010 DOI: https://doi.org/10.18112/openneuro.ds004010.v1.0.0

Normal Task 1: Continuous EEG Segmentation (resting/continuous)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: None (no trial-level events available)
- Notes: No event markers present. Use continuous segmentation for downstream tasks such as subject identification or spectral analysis. Task condition labels (if any) must come from external behavioral logs or stimulus delivery system.

Data Quality Notes

- No trial-level event markers; only continuous EEG available
- Stimulus delivery information may be in auxiliary files outside the BIDS structure
- 64 channels at 1000 Hz provides good temporal resolution for auditory processing analysis

References

- Reference: `MAVIS`

202. openneuro_ds004018 - EEG recordings for 200 object images presented in RSVP sequences at 5Hz or 20Hz

Dataset: `openneuro_ds004018` | Year: 2022 | URL: https://openneuro.org/datasets/ds004018
Category: Sensory/Response | Subjects: 2 | Files (Completed): 2
Channels: 63 | Sampling Rate: 1000 Hz

Paradigm

Rapid Serial Visual Presentation (RSVP) of 200 object images at two presentation frequencies (5 Hz and 20 Hz) to investigate the temporal dynamics of visual object representations. Images were categorized as "stars" or "boats" (two superordinate categories), allowing investigation of how presentation rate affects category-level neural decoding. This is a very small dataset (2 subjects).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004018

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stars`	2 files	short	raw	RSVP onset - star/celestial category image
`boats`	2 files	short	raw	RSVP onset - boat/vehicle category image

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

Tasks

Primary Task 1: Publisher-defined BIDS task: Rsvp

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004018 DOI: https://doi.org/10.1016/j.neuroimage.2018.12.046

Normal Task 1: Raw-meta task

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Needs verification
- Kernel Notes: Exclude admin markers from target labels.

Normal Task 2: Super-meta task

- Task Type: regression/classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target / Label: Needs verification
- Kernel Notes: Derive and version super-meta in kernel.

Data Quality Notes

- Only 2 subjects - extremely limited statistical power for group-level analysis
- RSVP at 5 Hz and 20 Hz: at 20 Hz, images appear for only 50 ms (near threshold for conscious processing)
- Verify that `stars` and `boats` events correspond to onset markers and not sustained states

References

- Reference: `The representational dynamics of visual objects in rapid serial visual processing streams. NeuroImage, 188, 668-679`

203. openneuro_ds004024 - TMS-EEG-MRI-fMRI-DWI data on paired associative stimulation and connectivity (Shirley Ryan AbilityLab, Chicago, IL)

Dataset: `openneuro_ds004024` | Year: 2022 | URL: https://openneuro.org/datasets/ds004024
Category: Sensory/Response | Subjects: 497 files | Files (Completed): 497
Channels: 69 | Sampling Rate: 20000 Hz

Paradigm

A multi-modal neuroimaging study using Paired Associative Stimulation (PAS) combined with TMS-EEG to investigate cortical connectivity and neuroplasticity. Participants received precisely timed TMS pulses paired with peripheral nerve stimulation, and EEG was recorded at very high sampling rate (20 kHz) to capture TMS-evoked potentials. The study also collected MRI, fMRI, and DWI data. This is a clinical/neurophysiology dataset focusing on brain connectivity assessment.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004024

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus/A`	345 files	short	raw	TMS or PAS stimulus onset
`Out/A`	378 files	short	raw	Stimulus output marker
`SB/A`	33 files	short	raw	Sub-threshold baseline stimulus
`Video/B`	32 files	short	raw	Video instruction marker
`New Segment/`	497 files	admin	raw	Recording segment boundary - exclude

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`

- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus/A`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Cc PAS

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004024 DOI: https://doi.org/10.18112/openneuro.ds004024.v1.0.1

Primary Task 2: Publisher-defined BIDS task: Rest

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004024 DOI: https://doi.org/10.18112/openneuro.ds004024.v1.0.1

Primary Task 3: Publisher-defined BIDS task: Sp TMS

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004024 DOI: https://doi.org/10.18112/openneuro.ds004024.v1.0.1

Normal Task 1: TMS-Evoked Potential Epoching (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: New Segment/ is an admin boundary marker and must be excluded. Very high sampling rate (20 kHz) - downsampling to 1-5 kHz strongly recommended before HDF5 generation. The TMS artifact (first ~10 ms post-pulse) requires specialized cleaning before analysis.

Event	y	Meaning
`Stimulus/A`	0	TMS/PAS stimulus pulse - main evoked potential event
`SB/A`	1	Sub-threshold baseline TMS pulse

Event	y	Meaning
## Data Quality Notes		

- Very high sampling rate (20,000 Hz) - downsampling required
- TMS artifact contaminates first ~10 ms post-stimulus; specialized TMS-EEG artifact removal (e.g., SSP, ICA) is required
- New Segment/ is an admin boundary marker to exclude

References

- Paper: `EEG-BIDS, an extension to the brain imaging data structure for electroencephalography. Scientific Data, 6, 103`

204. openneuro_ds004043 - The time-course of feature-based attention effects dissociated from temporal expectation and target-related processes

Dataset: `openneuro_ds004043` | Year: 2022 | URL: https://openneuro.org/datasets/ds004043
Category: Sensory/Response | Subjects: 20 | Files (Completed): 40
Channels: 63 | Sampling Rate: 250 Hz

Paradigm

Participants viewed rapid sequences of overlaid oriented grating pairs (presented at ~10 Hz) and detected a target orientation while attention was cued to different feature dimensions (orientation or color). The study dissociates the time-course of feature-based attention effects from temporal expectation and target-detection processes using EEG frequency-tagging and ERP methods.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004043

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`E 1`	20 files	short	raw	Grating stimulus onset - condition 1 (e.g., attended feature)
`E 2`	20 files	short	raw	Grating stimulus onset - condition 2
`E 3`	20 files	short	raw	Grating stimulus onset - condition 3 (e.g., target/distractor)

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Temporal expectation

- Task Type: classification/segmentation

- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004043 DOI: https://doi.org/10.1101/530352

Normal Task 1: Attention Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 20 subjects x 2 sessions = 40 files. E 1/E 2/E 3 are EEGLAB-style markers; full decoding requires consulting the original study events.tsv. Balanced across conditions per session.

Event	y	Meaning
`E 1`	0	Attention condition 1
`E 2`	1	Attention condition 2
`E 3`	2	Attention condition 3 (target or distractor)
## Data Quality Notes		

- Events encoded as generic E markers; semantic meaning requires events.tsv inspection
- 20 subjects x 2 files suggests two sessions or two task conditions per subject
- 250 Hz sampling rate; adequate for ERP/steady-state visual evoked potential analysis

References

- Reference: `Undivided attention: The temporal effects of attention dissociated from decision, memory, and expectation`

205. openneuro_ds004151 - Effect of obesity on inhibitory control in preadolescents during stop-signal task. An event-related potentials study

Dataset: `openneuro_ds004151` | Year: 2022 | URL: https://openneuro.org/datasets/ds004151
Category: Sensory/Response | Subjects: 57 | Files (Completed): 57
Channels: 128 | Sampling Rate: 500 Hz

Paradigm

Preadolescents (obese and normal-weight, ages 9-10) performed a stop-signal task to investigate the impact of obesity on reactive inhibitory control using ERPs. Participants respond to a go stimulus (trigger code 1) but must suppress the response when a stop signal follows (trigger code 2). The study tests whether obese children show electrophysiological differences in inhibition-related brain activity (N2, P3 components) compared to normal-weight peers.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004151

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`1`	~14,364	short	raw	Go trial stimulus onset
`2`	~6,156	short	raw	Stop-signal trial (inhibition required)

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Stop signal task

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1016/j.ijpsycho.2021.04.003

Normal Task 1: Raw-meta task

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Needs verification
- Kernel Notes: Exclude admin markers from target labels.

Normal Task 2: Super-meta task

- Task Type: regression/classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target / Label: Needs verification
- Kernel Notes: Derive and version super-meta in kernel.

Data Quality Notes

- Event IDs are numeric (1, 2); decoded from stop-signal paradigm description
- 128-channel EGI cap; verify consistent montage across subjects
- Class imbalance: ~70% go trials vs ~30% stop-signal trials

References

- Reference: `Effect of obesity on inhibitory control in preadolescents during stop-signal task (DOI: 10.1016/j.ijpsycho.2021.04.003)`

206. openneuro_ds004252 - Rotation-tolerant representations elucidate the time course of high-level object processing

Dataset: `openneuro_ds004252` | Year: 2022 | URL: https://openneuro.org/datasets/ds004252
Category: Sensory/Response | Subjects: 1 | Files (Completed): 1
Channels: 127 | Sampling Rate: 1000 Hz

Paradigm

A single participant viewed visual stimuli of objects at various rotations to investigate the neural time course of rotation-tolerant, high-level object representations. A rapid serial visual presentation (RSVP) design was used with three event types encoding distinct stimulus categories or conditions. The study is a single-subject pilot or proof-of-concept recording.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004252

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Event/E 1`	14400	short	raw	Stimulus condition 1 (object/rotation category A)
`Event/E 2`	14400	short	raw	Stimulus condition 2 (object/rotation category B)
`Event/E 3`	120	short	raw	Stimulus condition 3 (object/rotation category C)

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Rotation-tolerant object representation decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Stimulus category labels across rotated object presentations (Event/E1-E3 mapping per protocol).
- Evidence: Dataset and title indicate decoding of high-level object representations across viewpoint rotation. Source: https://openneuro.org/datasets/ds004252 DOI: https://doi.org/10.18112/openneuro.ds004252.v1.0.2

Normal Task 1: Object Category Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only 1 subject; not suitable for cross-subject generalization. Event/E 3 count (120) is far lower than E 1 and E 2 (14400 each) - severe class imbalance. Decode exact condition mapping from paper.

Event	y	Meaning
`Event/E 1`	0	Object/rotation condition 1
`Event/E 2`	1	Object/rotation condition 2
`Event/E 3`	2	Object/rotation condition 3
## Data Quality Notes		

- Single subject; results not generalizable across subjects
- 127 channels (1 reference electrode excluded)
- Severe class imbalance: E 1 and E 2 have 14400 trials each vs. E 3 with only 120

References

- Reference: `Rotation-tolerant representations elucidate the time course of high-level object processing`

207. openneuro_ds004256 - Encoding of Sound Source Elevation in Human Cortex

Dataset: `openneuro_ds004256` | Year: 2022 | URL: https://openneuro.org/datasets/ds004256
Category: Sensory/Response | Subjects: 53 | Files (Completed): 53
Channels: 64 | Sampling Rate: 500 Hz

Paradigm

Participants performed an auditory deviant detection task and a one-back sound localization task to investigate the cortical encoding of sound source elevation. Stimuli consisted of sounds presented from different vertical elevations, with subjects indicating perceived location. The study uses a multiclass design with conditions likely corresponding to different elevation angles.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004256

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus/S 1`	53x320	short	raw	Auditory stimulus condition 1 (elevation angle)
`Stimulus/S 2`	53x320	short	raw	Auditory stimulus condition 2 (elevation angle)
`Stimulus/S 3`	53x320	short	raw	Auditory stimulus condition 3 (elevation angle)
`Stimulus/S 4`	53x320	short	raw	Auditory stimulus condition 4 (elevation angle)
`Stimulus/S 5`	23x320	short	raw	Auditory stimulus condition 5 (elevation angle)
`Stimulus/S 6`	23x320	short	raw	Auditory stimulus condition 6 (elevation angle)
`Stimulus/S 7`	23x96	short	raw	Auditory stimulus condition 7 (deviant/rare)
`New Segment/`	53	admin	raw	Recording segment boundary

Event ID	Count (total)	Type	Meta Level	Meaning
BAD boundary	53	admin	raw	Bad epoch boundary marker
EDGE boundary	53	admin	raw	Edge boundary artifact marker

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Stimulus/S 1, Stimulus/S 2, Stimulus/S 3, Stimulus/S 4, Stimulus/S 5, Stimulus/S 6, Stimulus/S 7
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Deviantdetection

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004256 DOI: https://doi.org/10.18112/openneuro.ds004256.v1.0.5

Primary Task 2: Publisher-defined BIDS task: Oneback

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004256 DOI: https://doi.org/10.18112/openneuro.ds004256.v1.0.5

Normal Task 1: Sound Elevation Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.

- Notes: S 5/S 6/S 7 only present in 23 of 53 subjects; consider two-task splits. BAD boundary and EDGE boundary are admin events - exclude from target_events.

Event	y	Meaning
`Stimulus/S 1`	0	Auditory stimulus condition 1
`Stimulus/S 2`	1	Auditory stimulus condition 2
`Stimulus/S 3`	2	Auditory stimulus condition 3
`Stimulus/S 4`	3	Auditory stimulus condition 4
`Stimulus/S 5`	4	Auditory stimulus condition 5
`Stimulus/S 6`	5	Auditory stimulus condition 6
`Stimulus/S 7`	6	Auditory stimulus condition 7 (deviant)
## Data Quality Notes		

- S 5, S 6, S 7 appear in only 23 subjects (possibly a different task condition block)
- BAD boundary and EDGE boundary markers must not be used as target events
- Balance classes by undersampling; verify event counts per subject before pooling

References

- Reference: `Encoding of Sound Source Elevation in Human Cortex`

208. openneuro_ds004347 - Symmetry perception and affective responses: a combined EEG/EMG study

Dataset: openneuro_ds004347 | Year: 2022 | URL: https://openneuro.org/datasets/ds004347
Category: Sensory/Response | Subjects: 24 | Files (Completed): 24
Channels: 73 | Sampling Rate: 512 Hz

Paradigm

Participants performed a visual perception task identifying whether stimuli were regular (symmetric) or random (asymmetric) patterns to investigate symmetry perception and affective responses. EEG and EMG were simultaneously recorded to capture both neural and facial muscle activity. No trial-level event markers are present in the EEG files; the dataset is processed as continuous recordings.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004347

Event Structure

No event markers detected (`no_events`). This dataset contains continuous EEG recordings without trial-level annotations.

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Event ID	Count (total)	Type	Meta Level	Meaning
`no_events`	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Publisher-defined BIDS task: Jacobsen

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification

- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004347 DOI: https://doi.org/10.1016/j.neuropsychologia.2012.10.003

Normal Task 1: Continuous Segmentation (resting/segmentation)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (unsupervised segmentation)
- Notes: No trial markers in EEG files; use sliding window segmentation. Subject-level labels (symmetric vs. random condition blocks) may be available from experimental design metadata.

Data Quality Notes

- No trial-level event markers in the EEG files
- 73 channels includes EMG/EOG channels that should be excluded from EEG analysis
- Continuous recordings suitable for spectral or connectivity analysis

References

- Reference: `Symmetry perception and affective responses: a combined EEG/EMG study.`

209. openneuro_ds004356 - Subcortical responses to music and speech are alike while cortical responses diverge

Dataset: `openneuro_ds004356` | Year: 2024 | URL: https://openneuro.org/datasets/ds004356
Category: Sensory/Response | Subjects: 22 | Files (Completed): 24
Channels: 34 | Sampling Rate: 10000 Hz

Paradigm

The study measures subcortical Auditory Brainstem Responses (ABR) to continuous clicks, music genres, and speech stimuli using a deconvolution method. Participants passively listened to 12 different audio categories (Chinese speech, English speech, 8 music genres, acoustic guitar, and click trains) to compare subcortical and cortical neural encoding across stimulus types.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004356

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`click`	22x10	long	raw	Continuous click train stimulus
`acoustic`	22x40	long	raw	Acoustic guitar stimulus
`classical`	22x40	long	raw	Classical music stimulus
`jazz`	22x40	long	raw	Jazz music stimulus
`pop`	22x40	long	raw	Pop music stimulus
`metal`	22x40	long	raw	Metal music stimulus
`hiphop`	22x40	long	raw	Hip-hop music stimulus
`chn_aud`	22x40	long	raw	Chinese speech stimulus
`eng_aud`	22x40	long	raw	English speech stimulus
`news`	22x40	long	raw	News speech stimulus
`talk`	22x40	long	raw	Talk speech stimulus
`interview`	22x40	long	raw	Interview speech stimulus

Event ID	Count (total)	Type	Meta Level	Meaning
lecture	22x40	long	raw	Lecture speech stimulus

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Musicvs Speech

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004356 DOI: https://doi.org/10.1101/2022.10.14.512309

Normal Task 1: Music vs Speech Classification (binary)

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s (relative to event onset), overlap = 0.5, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Each stimulus block is a continuous audio segment (many seconds); use long event epoching. Sampling rate is 10 kHz (ABR recording). Consider subcortical ABR analysis vs. cortical EEG analysis separately.

Event	y	Meaning
acoustic	0	Music stimulus
classical	0	Music stimulus
jazz	0	Music stimulus
pop	0	Music stimulus
metal	0	Music stimulus
hiphop	0	Music stimulus
chn_aud	1	Speech stimulus
eng_aud	1	Speech stimulus
news	1	Speech stimulus
talk	1	Speech stimulus
interview	1	Speech stimulus
lecture	1	Speech stimulus

Event	y	Meaning
## Data Quality Notes		

- Very high sampling rate (10 kHz) designed for subcortical ABR; bandpass filtering required for cortical analysis
- 2 subjects have 2 files each (24 files, 22 subjects)
- Balanced stimulus presentation (40 trials per condition for most categories)

References

- Reference: `Subcortical responses to music and speech are alike while cortical responses diverge (Shan et al., 2024)`

210. openneuro_ds004357 - Features-EEG

Dataset: openneuro_ds004357 | Year: 2024 | URL: https://openneuro.org/datasets/ds004357
Category: Sensory/Response | Subjects: 16 | Files (Completed): 16
Channels: 127 | Sampling Rate: 1000 Hz

Paradigm

Participants viewed rapid serial visual presentation (RSVP) streams of Gabor-like stimuli at 6.67 Hz and 20 Hz while performing an orthogonal fixation color change detection task. Three event types encode different feature or condition categories, enabling investigation of how visual features are dynamically encoded in EEG responses.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004357

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Event/E 1`	16x~16000	short	raw	Stimulus feature condition 1
`Event/E 2`	16x~16000	short	raw	Stimulus feature condition 2
`Event/E 3`	16x~60	short	raw	Stimulus feature condition 3 (rare)

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Rsvp

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)

- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004357 DOI: https://doi.org/10.18112/openneuro.ds004357.v1.0.1

Normal Task 1: Visual Feature Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Event/E 3 count (~60 per file) is far lower than E 1 and E 2 (~16000 each) - severe class imbalance. Decode exact condition mapping from paper. Similar structure to ds004252.

Event	y	Meaning
`Event/E 1`	0	Stimulus feature condition 1
`Event/E 2`	1	Stimulus feature condition 2
`Event/E 3`	2	Stimulus feature condition 3
## Data Quality Notes		

- Severe class imbalance: E 1 and E 2 have ~16000 trials each vs. E 3 with ~60 per subject
- 127-channel high-density EEG
- RSVP paradigm at 6.67 Hz and 20 Hz; stimuli are very brief

References

- Reference: `Mapping the Dynamics of Visual Feature Coding: Insights into Perception and Integration`

211. openneuro_ds004381 - Intraoperative EEG dataset during medianus-tibialis stimulation with 8 different rates

Dataset: openneuro_ds004381 | Year: 2024 | URL: https://openneuro.org/datasets/ds004381
Category: Sensory/Response | Subjects: 18 | Files (Completed): 770
Channels: 4 | Sampling Rate: 20000 Hz

Paradigm

Intraoperative recording of Somatosensory Evoked Potentials (SEP) elicited by medianus and tibial nerve stimulation at eight different repetition rates to optimize signal-to-noise ratio for intraoperative monitoring. Recordings were made during neurosurgery using a minimal-channel invasive EEG setup with very high sampling rate for subcortical potential resolution.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004381

Event Structure

No event markers detected (no_events). This dataset contains continuous SEP recordings without trial-level BIDS annotations.

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

Event ID	Count (total)	Type	Meta Level	Meaning
no_events	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Publisher-defined BIDS task: Sep Rate

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]

- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004381 DOI: https://doi.org/10.18112/openneuro.ds004381.v1.0.2

Normal Task 1: Continuous Segmentation (segmentation)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (unsupervised segmentation)
- Notes: No BIDS trial event markers; stimulation rate (8 levels) encoded in filename/metadata. SEP analysis requires specialized averaging pipeline rather than standard epoch classification.

Data Quality Notes

- Very high sampling rate (20 kHz) for subcortical SEP; downsampling required for standard EEG analysis
- Only 4 channels (intraoperative minimal setup)
- 770 files across 18 subjects (many runs per subject, 8 stimulation rates)

References

- Reference: `Optimization of signal-to-noise ratio in short-duration SEP recordings by variation of stimulation rate`

212. openneuro_ds004388 - Somatosensory evoked potentials in the human spinal cord to mixed nerve stimulation

Dataset: `openneuro_ds004388` | Year: 2023 | URL: https://openneuro.org/datasets/ds004388
Category: Sensory/Response | Subjects: 40 | Files (Completed): 399
Channels: 115 | Sampling Rate: 10000 Hz

Paradigm

The dataset records somatosensory evoked potentials (SEPs) in response to mixed median and tibial nerve stimulation, alongside a resting state condition. Simultaneous EEG and epidural spinal cord recordings (ESG) were acquired to characterize the spinal and cortical processing of somatosensory signals.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004388

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stimulus`	399x~500	long	raw	Electrical nerve stimulation onset

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stimulus`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Alternating

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004388 DOI: https://doi.org/10.18112/openneuro.ds004388.v1.0.0

Primary Task 2: Publisher-defined BIDS task: Median

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004388 DOI: https://doi.org/10.18112/openneuro.ds004388.v1.0.0

Primary Task 3: Publisher-defined BIDS task: Tibial

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004388 DOI: https://doi.org/10.18112/openneuro.ds004388.v1.0.0

Normal Task 1: SEP Stimulus Epoching (long event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s (relative to event onset), overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only one event class; suitable for evoked potential analysis or regression on stimulation parameters. Multiple nerve sites and stimulation rates encoded in file naming conventions.

Event	y	Meaning
`stimulus`	0	Nerve stimulation onset
## Data Quality Notes		

- Very high sampling rate (10 kHz) for SEP/ESG; downsampling required for standard EEG analysis
- 115 channels includes spinal cord (ESG) and peripheral nerve (ENG/EMG) channels
- 399 files across 40 subjects (multiple runs/conditions per subject)

References

- Reference: `Somatosensory evoked potentials in the human spinal cord to mixed nerve stimulation`

213. openneuro_ds004389 - Somatosensory evoked potentials in the human spinal cord to mixed and sensory nerve stimulation

Dataset: `openneuro_ds004389` | Year: 2023 | URL: https://openneuro.org/datasets/ds004389
Category: Sensory/Response | Subjects: 26 | Files (Completed): 260
Channels: 90 | Sampling Rate: 10000 Hz

Paradigm

Simultaneous EEG, epidural spinal cord (ESG), nerve conduction (ENG), and EMG recordings during resting state and various conditions of mixed and sensory nerve stimulation of the arms and legs to evoke somatosensory potentials. The study compares spinal cord vs. cortical potentials for different stimulation types and sites.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004389

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`stimulus`	260x~1500	long	raw	Electrical nerve stimulation onset

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stimulus`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Mediansensory

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004389 DOI: https://doi.org/10.18112/openneuro.ds004389.v1.0.0

Primary Task 2: Publisher-defined BIDS task: Medianmixed

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004389 DOI: https://doi.org/10.18112/openneuro.ds004389.v1.0.0

Primary Task 3: Publisher-defined BIDS task: Tibialmixed

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004389 DOI: https://doi.org/10.18112/openneuro.ds004389.v1.0.0

Normal Task 1: SEP Stimulus Epoching (long event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s (relative to event onset), overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only one event class; suitable for evoked potential analysis. Multiple nerve sites (median mixed, median sensory, tibial) and stimulation conditions encoded in file/run naming.

Event	y	Meaning
`stimulus`	0	Nerve stimulation onset
## Data Quality Notes		

- Very high sampling rate (10 kHz) for SEP/ESG; downsampling required for standard EEG analysis
- 90 channels includes ESG, ENG, EMG, EOG, ECG channels - filter to EEG channels only
- 260 files across 26 subjects (multiple runs/conditions per subject)

References

- Reference: `Somatosensory evoked potentials in the human spinal cord to mixed and sensory nerve stimulation.`

214. openneuro_ds004502 - Anticipatory differences between Attention and Expectation

Dataset: `openneuro_ds004502` | Year: 2023 | URL: https://openneuro.org/datasets/ds004502
Category: Sensory/Response | Subjects: 38 | Files (Completed): 38
Channels: 63 | Sampling Rate: 1000 Hz

Paradigm

An experimental task investigating neural mechanisms of anticipation by comparing stimulus-driven attention and predictive expectation. Participants attended to auditory or visual stimuli with varying validity cues to disentangle attention (stimulus-driven) from expectation (predictive) effects on neural anticipatory activity.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004502

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`S 17`	38xx	short	raw	BrainVision trigger - decode from events.tsv
`S 18`	38xx	short	raw	BrainVision trigger - decode from events.tsv
`S 19`	38xx	short	raw	BrainVision trigger - decode from events.tsv
`S 20`	38xx	short	raw	BrainVision trigger - decode from events.tsv
`S 21`	38xx	short	raw	BrainVision trigger - decode from events.tsv
`S 22`	38xx	short	raw	BrainVision trigger - decode from events.tsv
`S 23`	38xx	short	raw	BrainVision trigger - decode from events.tsv

Event ID	Count (total)	Type	Meta Level	Meaning
S 24	38xx	short	raw	BrainVision trigger - decode from events.tsv
S 33...S 57	38xx	short	raw	BrainVision trigger codes (22 codes) - decode from events.tsv

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: S 17, S 18, S 19, S 20, S 21, S 22, S 23, S 24
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Attexp

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004502 DOI: https://doi.org/10.18112/openneuro.ds004502.v1.0.1

Normal Task 1: Attention vs Expectation Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: 30 distinct BrainVision trigger codes (S 17-S 57 range) require semantic decoding from events.tsv. Grouping into attention vs. expectation conditions requires understanding the trigger code mapping.

Event	y	Meaning
S 17...S 24	0	Attention condition trials (S1x range)
S 33...S 57	1	Expectation condition trials (S3x-S5x range)
## Data Quality Notes		

- 30 distinct trigger codes require semantic decoding from events.tsv metadata

- All 30 codes appear in all 38 files with consistent counts
- 63 channels at 1000 Hz (BrainVision system)

References

- Reference: `Anticipatory differences between Attention and Expectation`

215. openneuro_ds004563 - Vicarious touch: overlapping neural patterns between seeing and feeling touch

Dataset: openneuro_ds004563 | Year: 2023 | URL: https://openneuro.org/datasets/ds004563
Category: Sensory/Response | Subjects: 29 | Files (Completed): 29 | Channels: 64 | Sampling Rate: 512 Hz

Paradigm

Participants either saw someone else being touched (vicarious touch, event 4) or felt touch themselves (direct touch, event 1). EEG was recorded to investigate overlapping neural patterns between observed and experienced tactile stimulation. The study tests whether vicarious touch engages somatosensory cortex similarly to directly felt touch.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004563

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
4	~29xN	short	raw	Seeing touch (vicarious touch condition)
1	~29xN	short	raw	Feeling touch (direct touch condition)

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

Tasks

Primary Task 1: Publisher-defined BIDS task: Touch decoding

- Task Type: classification/segmentation

- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004563 DOI: https://doi.org/10.1101/2022.06.21.497107

Normal Task 1: Raw-meta task

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Needs verification
- Kernel Notes: Exclude admin markers from target labels.

Normal Task 2: Super-meta task

- Task Type: regression/classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target / Label: Needs verification
- Kernel Notes: Derive and version super-meta in kernel.

Data Quality Notes

- 29 subjects with binary condition structure
- 64 channels at 512 Hz

References

- Reference: `Vicarious touch: overlapping neural patterns between seeing and feeling touch`

216. openneuro_ds004574 - Cross-modal Oddball Task

Dataset: openneuro_ds004574 | Year: 2023 | URL: https://openneuro.org/datasets/ds004574
Category: Sensory/Response | Subjects: 30 | Files (Completed): 30 | Channels: 64 | Sampling Rate: 512 Hz

Paradigm

Participants performed an oddball task with cross-modal stimuli (visual and auditory). Standard stimuli (S 1), deviant stimuli (S 2), and rare stimuli (S 3) were presented in mixed modality streams. The study investigates the mismatch negativity (MMN) and P300 components elicited by deviant stimuli across sensory modalities.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004574

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`S 1`	~30xN	short	raw	Standard stimulus
`S 2`	~30xN	short	raw	Deviant stimulus
`S 3`	~30xN	short	raw	Rare/target stimulus
`boundary`	~30xN	admin	raw	Recording boundary marker
`S255`	~30xN	admin	raw	BrainVision overflow/system marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `S 1`, `S 2`, `S 3`, `S255`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: ERP target detection (P300/Oddball)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Target vs non-target stimulus events
- Evidence: P300/oddball paradigm appears as core study objective. Source: https://openneuro.org/datasets/ds004574 DOI: https://doi.org/10.1101/2022.07.26.22278079

Normal Task 1: Oddball Stimulus Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: boundary and S255 are admin events - exclude from target_events. S255 is a BrainVision system marker (overflow/sync), not a task event.

Event	y	Meaning
`S 1`	0	Standard stimulus
`S 2`	1	Deviant stimulus
`S 3`	2	Rare/target stimulus
## Data Quality Notes		

- boundary and S255 must be excluded from epoching
- S255 is a BrainVision system marker, not a stimulus event
- 30 subjects with standard oddball structure

References

- Reference: `Cross-modal Oddball Task`

217. openneuro_ds004579 - Interval Timing Task

Dataset: openneuro_ds004579 | Year: 2023 | URL: https://openneuro.org/datasets/ds004579
Category: Sensory/Response | Subjects: 30 | Files (Completed): 30 | Channels: 64 | Sampling Rate: 512 Hz

Paradigm

Participants performed an interval timing task where they estimated durations of different intervals. BrainVision S-codes (S 1-S 7) encode different timing conditions or interval lengths. Participants produced or reproduced time intervals by button press (R 3). The study investigates neural oscillations and temporal processing mechanisms.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004579

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
S 1	~30xN	short	raw	Timing condition 1
S 2	~30xN	short	raw	Timing condition 2
S 3	~30xN	short	raw	Timing condition 3
S 4	~30xN	short	raw	Timing condition 4
S 5	~30xN	short	raw	Timing condition 5
S 6	~30xN	short	raw	Timing condition 6
S 7	~30xN	short	raw	Timing condition 7
R 3	~30xN	short	raw	Button press response
boundary	~30xN	admin	raw	Recording boundary marker
S255	~30xN	admin	raw	BrainVision overflow/system marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `S  1`, `S  2`, `S  3`, `S  4`, `S  5`, `S  6`, `S  7`, `S255`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Interval Timing

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004579 DOI: https://doi.org/10.1101/2022.07.26.22278079

Normal Task 1: Timing Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: boundary and S255 are admin events - exclude from target_events. R 3 is a response event - can be used as an additional classification target. S255 is a BrainVision system marker (overflow/sync), not a task event.

Event	y	Meaning
`S  1`	0	Timing condition 1
`S  2`	1	Timing condition 2
`S  3`	2	Timing condition 3
`S  4`	3	Timing condition 4
`S  5`	4	Timing condition 5
`S  6`	5	Timing condition 6
`S  7`	6	Timing condition 7
## Data Quality Notes		

- boundary and S255 must be excluded from epoching
- S255 is a BrainVision system marker, not a task event
- 30 subjects with 7 timing conditions

References

- Reference: `Interval Timing Task`

218. openneuro_ds004580 - Simon-conflict Task

Dataset: `openneuro_ds004580` | Year: 2023 | URL: https://openneuro.org/datasets/ds004580
Category: Sensory/Response | Subjects: 30 | Files (Completed): 30 | Channels: 64 | Sampling Rate: 512 Hz

Paradigm

Participants performed the Simon conflict task in which stimulus location (left/right) could be congruent or incongruent with the required response direction. S 1 and S 2 encode congruent and incongruent trial types respectively; S 3 marks rare/catch trials. The study investigates conflict monitoring and executive control neural signatures (N2, P3 ERP components).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004580

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`S 1`	30x384	short	raw	Congruent trial (stimulus side matches response side)
`S 2`	30x383	short	raw	Incongruent trial (stimulus side opposite to response side)
`S 3`	~30xN	short	raw	Rare/catch trial
`boundary`	~30xN	admin	raw	Recording boundary marker
`S255`	~30xN	admin	raw	BrainVision overflow/system marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.

- Candidate Trigger Labels: `S 1`, `S 2`, `S 3`, `S255`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Simon

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004580 DOI: https://doi.org/10.1101/2022.07.26.22278079

Normal Task 1: Congruent vs Incongruent Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: boundary and S255 are admin events - exclude from target_events. S255 is a BrainVision system marker (overflow/sync), not a task event. S 3 (rare trials) can be optionally included as a third class.

Event	y	Meaning
`S 1`	0	Congruent trial
`S 2`	1	Incongruent trial
## Data Quality Notes		

- boundary and S255 must be excluded from epoching
- Balanced S 1 and S 2 counts (~384 vs ~383 per subject)
- 30 subjects with consistent congruent/incongruent structure

References

- Reference: `Simon-conflict Task`

219. openneuro_ds004587 - IllusionGameEEG_data

Dataset: openneuro_ds004587 | Year: 2024 | URL: https://openneuro.org/datasets/ds004587
Category: Sensory/Response | Subjects: 103 | Files (Completed): 114 | Channels: 64 | Sampling Rate: 10000 Hz

Paradigm

Participants performed perceptual judgements on visual targets embedded within three classic visual illusions - Ebbinghaus, Muller-Lyer, and Vertical-Horizontal - to measure individual differences in illusion sensitivity and perceptual bias. The study investigates how prior experience and personality shape perceptual decision-making. EEG was recorded at 10 kHz; actual stimulus-event markers appear not to have been stored in events.tsv.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004587

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
New Segment/LostSamples: 2	370	admin	raw	Lost-samples boundary marker (exclude)
New Segment/	115	admin	raw	BrainVision segment boundary (exclude)
New Segment/LostSamples: 3	111	admin	raw	Lost-samples boundary marker (exclude)
New Segment/LostSamples: 4	6	admin	raw	Lost-samples boundary marker (exclude)
Comment/motion	9	admin	raw	Motion artifact annotation (exclude)
Comment/ro post	6	admin	raw	Post-recording comment (exclude)
Comment/error	3	admin	raw	Error annotation (exclude)
Comment/rc pre	3	admin	raw	Pre-recording comment (exclude)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: IG

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004587 DOI: https://doi.org/10.18112/openneuro.ds004587.v1.0.0

Normal Task 1: Continuous Task EEG (segmentation)

- Task Type: regression
- Epoch Method: `segmentation`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: None
- Notes: All events in events.tsv are administrative markers or artifact annotations. No stimulus/response trial events were captured. Trial structure may be recoverable from separate behavioral logs. Use sliding-window segmentation.

Data Quality Notes

- All events are admin; no stimulus-locked epochs possible from events.tsv alone.
- Very high sampling rate (10 kHz) - downsample before analysis.
- Paper reference (ARSQ 2.0) may be a metadata mismatch; verify README.

References

- Reference: `The ARSQ 2.0 reveals age and personality effects on mind-wandering experiences`

220. openneuro_ds004602 - Registered Replication Report of ERN/Pe Psychometrics

Dataset: openneuro_ds004602 | Year: 2023 | URL: https://openneuro.org/datasets/ds004602
Category: Sensory/Response | Subjects: 182 | Files (Completed): 546 | Channels: 129 | Sampling Rate: 500 Hz

Paradigm

Participants completed Flanker, Stroop, and Go/no-go tasks to evaluate the psychometric reliability and convergent/divergent validity of error-related ERP components (ERN and Pe). The study tests whether error-related components are stable within individuals across tasks and sessions. Three task files per subject yield the 546-file count. cor/err mark correct/error responses; con/inc mark congruent/incongruent Flanker/Stroop trials; go/ng/neu mark Go/no-go trial types.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004602

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
cor	169236	short	raw	Correct response (all tasks)
go	58251	short	raw	Go trial (Go/no-go task)
con	54498	short	raw	Congruent trial (Flanker/Stroop)
inc	47242	short	raw	Incongruent trial (Flanker/Stroop)
err	24198	short	raw	Error response (all tasks)
neu	20890	short	raw	Neutral trial condition
ng	8636	short	raw	No-go trial (Go/no-go task)
boundary	545	admin	raw	Segment boundary marker (exclude)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Mixed

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004602 DOI: https://doi.org/10.18112/openneuro.ds004602.v1.0.1

Normal Task 1: Error vs Correct Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: boundary (545) is admin - exclude. cor (169,236) >> err (24,198) - significant class imbalance; undersample cor or use weighted loss. con/inc/go/ng/neu usable for separate task-level analyses.

Event	y	Meaning
`cor`	0	Correct response (ERN/Pe absent)
`err`	1	Error response (ERN/Pe present)

Normal Task 2: Congruent vs Incongruent (binary, Flanker/Stroop)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 54,498 vs 47,242 - reasonably balanced. Filter by Flanker/Stroop task files only.

Event	y	Meaning
`con`	0	Congruent trial
`inc`	1	Incongruent trial
## Data Quality Notes		

- boundary (545) is admin - exclude.
- 3 task files per subject (Flanker, Stroop, Go/no-go); filter by task for task-specific analyses.
- High channel count (129) may include non-EEG channels - verify channel types.

References

- Reference: `Registered Replication Report of ERN/Pe Psychometrics`

221. openneuro_ds004603 - Visual Attribute-Specific Contextual Trajectory Paradigm

Dataset: `openneuro_ds004603` | Year: 2023 | URL: https://openneuro.org/datasets/ds004603
Category: Sensory/Response | Subjects: 37 | Files (Completed): 37 | Channels: 65 | Sampling Rate: 1024 Hz

Paradigm

Participants observed sequences of visual stimuli that either followed or violated an established contextual trajectory in one of three visual attributes - brightness (color), size, or orientation. The paradigm tests predictive coding by contrasting EEG responses to expected (step) stimuli against unexpected violations and a no-trajectory control condition. Each sequence comprised four ordered steps followed by a target or violation stimulus.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004603

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`step_1`	31368	short	raw	Sequence step 1 - first ordered stimulus in trajectory
`step_2`	31367	short	raw	Sequence step 2
`step_3`	31367	short	raw	Sequence step 3
`step_4`	31367	short	raw	Sequence step 4 - final step before target/violation
`control`	14203	short	raw	Control condition - no established trajectory
`siz_vio`	4736	short	raw	Size trajectory violation
`ori_vio`	4735	short	raw	Orientation trajectory violation
`col_vio`	4735	short	raw	Color/brightness trajectory violation
`catch`	2958	short	raw	Catch trial requiring button-press response
`initalising_triggers`	1	admin	raw	System initialisation trigger (exclude)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `initalising_triggers`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: CTP

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004603 DOI: https://doi.org/10.18112/openneuro.ds004603.v1.1.0

Normal Task 1: Violation Detection (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `initalising_triggers` (1 total) is admin - exclude. Sequence steps (step_1-step_4) can be used for prediction build-up ERP analysis.

Event	y	Meaning
`control`	0	No-trajectory control
`siz_vio`	1	Size violation
`ori_vio`	2	Orientation violation
`col_vio`	3	Color violation
## Data Quality Notes		

- Exclude `initalising_triggers` from all analysis.
- Catch trials have a motor response component - treat separately or exclude from violation analysis.

References

- Reference: `Visual Attribute-Specific Contextual Trajectory Paradigm`

222. openneuro_ds004745 - 8-Channel SSVEP EEG Dataset with Artifact Trials

Dataset: openneuro_ds004745 | Year: 2023 | URL: https://openneuro.org/datasets/ds004745
Category: Sensory/Response | Subjects: 6 | Files (Completed): 6
Channels: 8 | Sampling Rate: 1000 Hz

Paradigm

Participants performed Steady-State Visual Evoked Potential (SSVEP) tasks at stimulation frequencies of 2 Hz, 4 Hz, and 8 Hz, under both static artifact-free and voluntary movement artifact conditions. The dataset was created to test artifact removal algorithms for SSVEP-based BCIs under realistic conditions with deliberate motion contamination. Multiple trigger codes mark different frequency and artifact conditions.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004745

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
10	44	short	raw	Trigger code 10 - likely artifact or rest condition
4	38	short	raw	4 Hz SSVEP frequency onset
2	36	short	raw	2 Hz SSVEP frequency onset
1	36	short	raw	Trigger code 1
3	36	short	raw	Trigger code 3
5	36	short	raw	Trigger code 5
6	36	short	raw	Trigger code 6
7	36	short	raw	Trigger code 7
8	38	short	raw	8 Hz SSVEP frequency onset

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: SSVEP target/frequency decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification] | tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `stim` or `Annotation`
- Target Definition: Stimulus frequency or target index
- Evidence: SSVEP paradigm is explicitly stated in dataset metadata/reference. Source: https://openneuro.org/datasets/ds004745 DOI: https://doi.org/10.1109/EMBC46164.2021.9629771

Normal Task 1: SSVEP frequency condition classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only 6 subjects - very small dataset. Full trigger decode needed from events.tsv. Deliberate motion artifacts present in some trials.

Event	y	Meaning
`2`	0	2 Hz SSVEP condition
`4`	1	4 Hz SSVEP condition
`8`	2	8 Hz SSVEP condition
`10`	3	Artifact/rest condition
## Data Quality Notes		

- Only 6 subjects and 8 channels - limited for generalization.
- Deliberate motion artifacts present in some trials; note artifact condition labels.

References

- Reference: `Kumaravel et al., (IEEE EMBC 2021)`

223. openneuro_ds004816 - EEG Attention RSVP Experiment 1

Dataset: openneuro_ds004816 | Year: 2023 | URL: https://openneuro.org/datasets/ds004816
Category: Sensory/Response | Subjects: N/A | Files (Completed): 40 | Channels: 63 | Sampling Rate: 1000 Hz

Paradigm

A Rapid Serial Visual Presentation (RSVP) task investigating the neural dynamics of prioritizing task-relevant information using stimuli composed of small letters on large objects. Event codes E 1 and E 2 are the dominant condition markers (69,120 each total); codes 1 and 0 appear 31,104 times each; E 3 appears 1,920 times. The E 1/E 2 pair likely marks the two main stimulus streams (letter-prioritized vs object-prioritized). Codes 1/0 mark target-present vs target-absent trials. Event/E x variants are the same conditions from different recordings.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004816

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
E 1	69120	short	raw	RSVP condition 1 (primary stream)
E 2	69120	short	raw	RSVP condition 2 (secondary stream)
1	31104	short	raw	Target-present marker
0	31104	short	raw	Target-absent marker
Event/E 1	6912	short	raw	RSVP condition 1 (alternate format)
Event/E 2	6912	short	raw	RSVP condition 2 (alternate format)
E 3	1920	short	raw	RSVP condition 3 (rare)
Event/E 3	192	short	raw	RSVP condition 3 (alternate format, rare)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Rsvp

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004816 DOI: https://doi.org/10.51628/001c.21174

Normal Task 1: RSVP Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `Event/E 1` and `Event/E 2` are alternate-format versions of the same codes; merge with `E 1`/`E 2` if needed. `E 3` (1,920) and `Event/E 3` (192) are rare - exclude or treat as separate class. 5 Hz RSVP; verify stimulus duration from events.tsv.

Event	y	Meaning
`E 1`	0	RSVP condition 1
`E 2`	1	RSVP condition 2
`1`	2	Target-present
`0`	3	Target-absent
## Data Quality Notes		

- `Event/E x` variants likely from different recording format; merge with `E x` before epoching.
- `E 3` and `Event/E 3` are rare codes - may represent catch trials or errors.
- High-count RSVP paradigm; very large epoch counts per subject.

References

- Reference: `Grootswagers T., Robinson A.K., Shatek S.M., Carlson T.A. (2021). The neural dynamics underlying prioritisation of task-relevant information. Neurons, Behaviour, Data Analysis, and Theory, 5(1)`

224. openneuro_ds004817 - EEG-attention-rsvp-exp2

Dataset: openneuro_ds004817 | Year: 2023 | URL: https://openneuro.org/datasets/ds004817
Category: Sensory/Response | Subjects: 40 | Files (Completed): 40
Channels: 63 | Sampling Rate: 1000 Hz

Paradigm

A Rapid Serial Visual Presentation (RSVP) task (Experiment 2) investigating the neural dynamics of prioritizing task-relevant information, using stimuli consisting of small objects superimposed on large letters. Participants performed target detection in rapid streams. Experiment 2 is a companion to Experiment 1 (ds004816) with different stimulus configurations (objects on letters rather than letters on objects).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004817

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`E 1`	69137	short	raw	RSVP event type 1 (task-relevant stimulus)
`E 2`	69137	short	raw	RSVP event type 2 (task-irrelevant stimulus)
`1`	29376	short	raw	Trigger code 1 (response or condition marker)
`0`	29376	short	raw	Trigger code 0
`Event/E 1`	10385	short	raw	RSVP event type 1 (alternate format)
`Event/E 2`	10385	short	raw	RSVP event type 2 (alternate format)
`E 3`	1921	short	raw	RSVP event type 3
`Event/E 3`	289	short	raw	RSVP event type 3 (alternate format)

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`

- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Rsvp

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004817 DOI: https://doi.org/10.51628/001c.21174

Normal Task 1: RSVP target classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Companion to ds004816 (Experiment 1). Event/E 1 and Event/E 2 are identical events in different naming format - treat as same class or aggregate.

Event	y	Meaning
E 1	0	RSVP event type 1
E 2	1	RSVP event type 2
E 3	2	RSVP event type 3
1	3	Response/condition code 1
0	4	Response/condition code 0
## Data Quality Notes		

- E 1/Event/E 1 and E 2/Event/E 2 are duplicate event formats - aggregate for analysis.
- Companion dataset: ds004816 is Experiment 1.

References

- Reference: Grootswagers T., Robinson A.K., Shatek S.M., Carlson T.A. (2021). The neural dynamics underlying prioritisation of task-relevant information. Neurons, Behaviour, Data Analysis, and Theory, 5(1)

225. openneuro_ds004951 - Braille Letters EEG

Dataset: `openneuro_ds004951` | Year: 2024 | URL: https://openneuro.org/datasets/ds004951
Category: Sensory/Response | Subjects: 23 | Files (Completed): 23 | Channels: 64 | Sampling Rate: 1000 Hz

Paradigm

Participants identified Braille letters presented via tactile stimulation to left or right index fingers while EEG was recorded. The study investigates cortical plasticity by comparing sighted controls and congenitally blind individuals in processing Braille letter information. Stimulus codes S1-S16 mark individual Braille letter presentations (3,316-3,319 each); S101 and S222 (63,609/63,607) dominate and likely mark response-correct/response-incorrect feedback or block boundaries; S200 (10,535) is a block marker; S253 (9,211) and S254/S255 are admin/system markers.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004951

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus/S101`	63609	short	raw	Response feedback / block marker A
`Stimulus/S222`	63607	short	raw	Response feedback / block marker B
`Stimulus/S200`	10535	short	raw	Block boundary / condition marker
`Stimulus/S253`	9211	admin	raw	Admin / response marker (exclude)
`Stimulus/S 16`	3319	short	raw	Braille letter 16 onset
`Stimulus/S 6`	3319	short	raw	Braille letter 6 onset
`Stimulus/S 15`	3319	short	raw	Braille letter 15 onset
`Stimulus/S 11`	3318	short	raw	Braille letter 11 onset
`Stimulus/S 3`	3318	short	raw	Braille letter 3 onset
`Stimulus/S 10`	3317	short	raw	Braille letter 10 onset
`Stimulus/S 1-S 16`	~3316-3319 each	short	raw	Individual Braille letter onsets (16 letters)
`Stimulus/S255`	~437	admin	raw	BrainVision admin sync marker (exclude)

Event ID	Count (total)	Type	Meta Level	Meaning
`New Segment/`	rare	admin	raw	BrainVision segment boundary (exclude)

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus/S101`, `Stimulus/S222`, `Stimulus/S200`, `Stimulus/S253`, `Stimulus/S 16`, `Stimulus/S 6`, `Stimulus/S 15`, `Stimulus/S 11`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Letters

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004951 DOI: https://doi.org/10.18112/openneuro.ds004951.v1.0.0

Normal Task 1: Braille Letter Identification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `New Segment/`, `Stimulus/S253`, `Stimulus/S254`, `Stimulus/S255` are admin - exclude. S101/S222 (63k each) are very high-frequency feedback/block markers - exclude from classification. S200 is a block boundary - exclude.

Event	y	Meaning
`Stimulus/S 1`	0	Braille letter 1
`Stimulus/S 2`	1	Braille letter 2
`Stimulus/S 3`	2	Braille letter 3
`Stimulus/S 4`	3	Braille letter 4
`Stimulus/S 5`	4	Braille letter 5
`Stimulus/S 6`	5	Braille letter 6
`Stimulus/S 7`	6	Braille letter 7
`Stimulus/S 8`	7	Braille letter 8
`Stimulus/S 9`	8	Braille letter 9
`Stimulus/S 10`	9	Braille letter 10

Event	y	Meaning
Stimulus/S 11	10	Braille letter 11
Stimulus/S 12	11	Braille letter 12
Stimulus/S 13	12	Braille letter 13
Stimulus/S 14	13	Braille letter 14
Stimulus/S 15	14	Braille letter 15
Stimulus/S 16	15	Braille letter 16
## Data Quality Notes		

- Stimulus/S101 and Stimulus/S222 are very high-frequency (63k each) - likely feedback or block markers, exclude from classification.
- New Segment/, Stimulus/S253, Stimulus/S254, Stimulus/S255 are admin/system - exclude.
- Dataset includes sighted controls and congenitally blind participants; group label in participants.tsv.

References

- Reference: The transformation of sensory to perceptual braille letter representations in the visually deprived brain

226. openneuro_ds005087 - Rapid Hemifield Object EEG

Dataset: openneuro_ds005087 | Year: 2024 | URL: https://openneuro.org/datasets/ds005087
Category: Sensory/Response | Subjects: 80 | Files (Completed): 80 | Channels: 63 | Sampling Rate: 1000 Hz

Paradigm

Participants viewed object and word stimuli presented at 5 Hz in rapid visual streams to the left hemifield, right hemifield, or central visual field while performing a red target detection task. Event codes E 1/E 2 (184,320 each) and E 3 (960) mark the three presentation positions (left/right/center hemifield). Numeric codes 2/3/1 (92,160/46,080/46,080) likely encode stimulus categories or object identities within each presentation stream.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005087

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
E 1	184320	short	raw	Hemifield/position condition 1
E 2	184320	short	raw	Hemifield/position condition 2
2	92160	short	raw	Stimulus category/identity code 2
3	46080	short	raw	Stimulus category/identity code 3
1	46080	short	raw	Stimulus category/identity code 1
E 3	960	short	raw	Hemifield/position condition 3 (rare)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Rsvp

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005087 DOI: https://doi.org/10.31234/osf.io/a3bpd

Normal Task 1: Visual Hemifield Presentation Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `E 3` (960) is rare - exclude or treat as separate class. 5 Hz RSVP streams; very short inter-stimulus interval. Verify code meanings from events.tsv (Robinson et al., 2025).

Event	y	Meaning
`E 1`	0	Hemifield/position condition 1
`E 2`	1	Hemifield/position condition 2
`1`	2	Stimulus category code 1
`2`	3	Stimulus category code 2
`3`	4	Stimulus category code 3
## Data Quality Notes		

- Verify full event decode from events.tsv or Robinson et al., 2025.
- 5 Hz RSVP - confirm exact stimulus duration from events.tsv.
- `E 3` (960) is rare relative to E 1/E 2 (184k each); exclude or treat separately.

References

- Reference: `Robinson A.K., Grootswagers T., Shatek S., Behrmann M., Carlson T.A. (2025). Dynamics of visual object coding within and across the hemispheres: Objects in the periphery. Science Advances, 11, eadq0889`

227. openneuro_ds005106 - Human Infant EEG for 200 Object Images in Rapid Visual Streams

Dataset: `openneuro_ds005106` | Year: 2024 | URL: https://openneuro.org/datasets/ds005106
Category: Sensory/Response | Subjects: 42 | Files (Completed): 42 | Channels: 32 | Sampling Rate: 500 Hz

Paradigm

Infants viewed 200 distinct object images presented in rapid visual streams (RSVP) while EEG was recorded to study the development of visual object representations. Each numeric trigger code corresponds to one of 200 object IDs; code -1 is a baseline/inter-stimulus marker. The dataset enables decoding of object-specific neural representations in the infant brain.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005106

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`-1`	43105	short	raw	Baseline / inter-stimulus marker
`155`	220	short	raw	Object image 155 onset
`123`	220	short	raw	Object image 123 onset
`72`	219	short	raw	Object image 72 onset
`147`	219	short	raw	Object image 147 onset
`(~196 more object codes)`	~219 each	short	raw	Individual object image onsets (IDs 1-200)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Fix

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005106 DOI: https://doi.org/10.1167/13.10.1

Normal Task 1: Object Image Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Code -1 is a baseline/ITI marker - exclude from classification. ~200 object classes with ~219 occurrences each. Representational similarity analysis (RSA) is a primary use case.

Event	y	Meaning
(numeric codes 1-200)	0-199	Object image ID (200 classes)
## Data Quality Notes		

- ~200 unique object trigger codes - each code represents one object image.
- Code -1 is a baseline/ITI marker and should be excluded.
- Infant EEG - expect high noise and movement artifacts.

References

- Reference: `Human Infant EEG Recordings for 200 Object Images Presented in Rapid Visual Streams`

228. openneuro_ds005169 - Intracranial EEG During Cortical Stimulation Evoking Visual Effects

Dataset: openneuro_ds005169 | Year: 2024 | URL: https://openneuro.org/datasets/ds005169
Category: Sensory/Response | Subjects: 22 | Files (Completed): 112 | Channels: 82 | Sampling Rate: 4096 Hz

Paradigm

Intracranial EEG was recorded from drug-resistant epilepsy patients undergoing presurgical evaluation during direct electrical stimulation (DES) of cortical sites that evoke visual hallucinations and perceptual effects. Comment/prestim (112 total) marks pre-stimulation baseline periods and Comment/poststim (111) marks post-stimulation response windows. UUID-format Comment events (2-10 per file) are patient-specific or trial-specific annotations.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005169

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
Comment/prestim	112	long	raw	Pre-stimulation baseline period
Comment/poststim	111	long	raw	Post-stimulation response window
Comment/[UUID]	2-10/file	admin	raw	Patient/trial-specific annotation (UUID format, exclude)
Comment/[electrode] [mA] SYM	~2/file	admin	raw	Stimulation parameter annotation (exclude)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Comment/prestim, Comment/poststim
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Dcs

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1002/hbm.25749

Normal Task 1: Pre vs Post Stimulation (binary)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: UUID-format and electrode/mA Comment events are admin - exclude. Very high sampling rate (4096 Hz) - downsample before processing. iEEG data; stimulation artifact present in poststim windows.

Event	y	Meaning
`Comment/prestim`	0	Pre-stimulation baseline
`Comment/poststim`	1	Post-stimulation response
## Data Quality Notes		

- Very high sampling rate (4096 Hz) - downsample to <=1000 Hz before analysis.
- Intracranial EEG - different noise profile from scalp EEG; stimulation artifacts expected.
- UUID-format Comment events are patient-specific annotations - exclude from epoching.

References

- Reference: `Imaging the effective networks associated with cortical function through intracranial high-frequency stimulation. DOI: 10.1002/hbm.25749`

229. openneuro_ds005363 - Object Recognition in Healthy Aging (ORHA) - EEG

Dataset: `openneuro_ds005363` | Year: 2024 | URL: https://openneuro.org/datasets/ds005363
Category: Sensory/Response | Subjects: 43 | Files (Completed): 43 | Channels: 64 | Sampling Rate: 1000 Hz

Paradigm

Participants viewed images across five visual categories (faces, animals, places, objects, and likely one additional) to investigate visual object representations and how they change with healthy aging. S65-S69 encode the five stimulus categories; S99 is a high-frequency event likely marking fixations or trial separators. The study uses representational similarity analysis to track age-related changes in neural object coding.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005363

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus/S 99`	21460	short	raw	Fixation/trial separator (high-frequency onset)
`Stimulus/S 66`	4508	short	raw	Visual category 2
`Stimulus/S 67`	4463	short	raw	Visual category 3
`Stimulus/S 65`	4421	short	raw	Visual category 1
`Stimulus/S 69`	4351	short	raw	Visual category 5
`Stimulus/S 68`	4285	short	raw	Visual category 4
`Stimulus/S 4`-`Stimulus/S 57`	~1377 each	short	raw	Individual exemplar image onsets (60+ items)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus/S 99`, `Stimulus/S 66`, `Stimulus/S 67`, `Stimulus/S 65`, `Stimulus/S 69`, `Stimulus/S 68`, `Stimulus/S 4`, `Stimulus/S 57`

- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Objrecog

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005363 DOI: https://doi.org/10.18112/openneuro.ds005363.v1.0.0

Normal Task 1: Visual Category Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: S99 (21,460 total) is a high-frequency fixation/separator marker - exclude. S4-S57 encode individual exemplar images (60+ codes, ~1377 each); use for RSA analysis.

Event	y	Meaning
`Stimulus/S 65`	0	Visual category 1
`Stimulus/S 66`	1	Visual category 2
`Stimulus/S 67`	2	Visual category 3
`Stimulus/S 68`	3	Visual category 4
`Stimulus/S 69`	4	Visual category 5
## Data Quality Notes		

- S99 is a very high-frequency marker (21,460 total) - likely fixation onset, exclude from category decoding.
- 60+ exemplar codes (~1377 each) suitable for RSA.

References

- Reference: `Healthy aging delays and dedifferentiates high-level visual representations`

230. openneuro_ds005406 - EEG Frequency Tagging Reveals the Integration of Dissimilar Observed Actions

Dataset: `openneuro_ds005406` | Year: 2024 | URL: https://openneuro.org/datasets/ds005406
Category: Sensory/Response | Subjects: 29 | Files (Completed): 29 | Channels: 64 | Sampling Rate: 1000 Hz

Paradigm

A frequency-tagging EEG study measuring steady-state visual evoked potentials (SSVEP) as participants observed dissimilar human actions presented in rapid visual sequences. The study uses neural entrainment at different tagging frequencies to measure the integration of distinct action components (e.g., arm and leg movements). Four action-pair conditions are encoded as S-code pairs (S11/12, S21/22, S31/32, S41/42).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005406

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus/S 41`	231	short	raw	Action condition 4, sequence start
`Stimulus/S 21`	231	short	raw	Action condition 2, sequence start
`Stimulus/S 22`	231	short	raw	Action condition 2, sequence end
`Stimulus/S 42`	230	short	raw	Action condition 4, sequence end
`Stimulus/S 31`	230	short	raw	Action condition 3, sequence start
`Stimulus/S 32`	230	short	raw	Action condition 3, sequence end
`Stimulus/S 11`	230	short	raw	Action condition 1, sequence start
`Stimulus/S 12`	230	short	raw	Action condition 1, sequence end
`New Segment/`	29	admin	raw	BrainVision segment boundary (exclude)
`Stimulus/S255`	24	admin	raw	S255 admin sync trigger (exclude)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus/S 41`, `Stimulus/S 21`, `Stimulus/S 22`, `Stimulus/S 42`, `Stimulus/S 31`, `Stimulus/S 32`, `Stimulus/S 11`, `Stimulus/S 12`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: SSVEP target/frequency decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification] | tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `stim` or `Annotation`
- Target Definition: Stimulus frequency or target index
- Evidence: SSVEP paradigm is explicitly stated in dataset metadata/reference. Source: https://openneuro.org/datasets/ds005406 DOI: https://doi.org/10.1101/2024.05.10.593473v1

Normal Task 1: Action Integration Condition Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: New Segment/ (29) and Stimulus/S255 (24) are admin - exclude. Four action conditions with start/end markers each.

Event	y	Meaning
`Stimulus/S 11`	0	Action condition 1 start
`Stimulus/S 12`	1	Action condition 1 end
`Stimulus/S 21`	2	Action condition 2 start
`Stimulus/S 22`	3	Action condition 2 end
`Stimulus/S 31`	4	Action condition 3 start
`Stimulus/S 32`	5	Action condition 3 end
`Stimulus/S 41`	6	Action condition 4 start
`Stimulus/S 42`	7	Action condition 4 end
## Data Quality Notes		

- New Segment/ and Stimulus/S255 are administrative - exclude.
- Frequency-tagging paradigm; SSVEP analysis may be more appropriate than traditional ERP epoching.

References

- Reference: `EEG frequency tagging reveals the integration of dissimilar observed actions`

231. openneuro_ds005586 - EEG responses to the number of objects in partially occluded and uncovered scenes

Dataset: `openneuro_ds005586` | Year: 2024 | URL: https://openneuro.org/datasets/ds005586
Category: Sensory/Response | Subjects: 23 | Files (Completed): 23 | Channels: 63 | Sampling Rate: 1000 Hz

Paradigm

Participants passively viewed game boards depicting varying numbers of game pieces under partial occlusion and subsequent uncovering conditions. The study investigates EEG responses to numerosity perception under occlusion, measuring visual evoked potentials to quantify object tracking. Stimulus codes encode number of objects (1 or 2 digits) and condition (occluded vs uncovered).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005586

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus/S 95`	14399	short	raw	Catch / fixation stimulus
`Stimulus/S 21`	6884	short	raw	Stimulus condition (2-digit code: object count x condition)
`Stimulus/S 11`	6875	short	raw	Stimulus condition (2-digit code: object count x condition)
`Stimulus/S 15`	2241	short	raw	Stimulus condition
`Stimulus/S127`	1413	short	raw	Stimulus condition (3-digit code)
`Stimulus/S223`	1299	short	raw	Stimulus condition (3-digit code)
`Stimulus/S111`	903	short	raw	Stimulus condition (3-digit code)
`Stimulus/S124`	866	short	raw	Stimulus condition (3-digit code)
`Stimulus/S224`	866	short	raw	Stimulus condition (3-digit code)
`Stimulus/S226`	864	short	raw	Stimulus condition (3-digit code)

Event ID	Count (total)	Type	Meta Level	Meaning
Stimulus/S126	864	short	raw	Stimulus condition (3-digit code)
Stimulus/S215	864	short	raw	Stimulus condition (3-digit code)
Stimulus/S115	864	short	raw	Stimulus condition (3-digit code)
Stimulus/S118	863	short	raw	Stimulus condition (3-digit code)
Stimulus/S218	863	short	raw	Stimulus condition (3-digit code)

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Stimulus/S 95, Stimulus/S 21, Stimulus/S 11, Stimulus/S 15, Stimulus/S127, Stimulus/S223, Stimulus/S111, Stimulus/S124
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Passive Viewing

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005586 DOI: https://doi.org/10.18112/openneuro.ds005586.v2.0.0

Normal Task 1: Object Numerosity / Occlusion (epoch_by_event)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Stimulus codes encode object count x occlusion condition; decode from events.tsv. New Segment/ is admin and excluded.

Event	y	Meaning
Stimulus/S 95	0	Catch/fixation
Stimulus/S127	1	Condition code 127
Stimulus/S223	2	Condition code 223
Stimulus/S111	3	Condition code 111
Stimulus/S 21	4	Condition code 21

Event	y	Meaning
Stimulus/S 11	5	Condition code 11
Stimulus/S117	6	Condition code 117
Stimulus/S124	7	Condition code 124
Stimulus/S224	8	Condition code 224
Stimulus/S227	9	Condition code 227
Stimulus/S118	10	Condition code 118
Stimulus/S218	11	Condition code 218
Stimulus/S122	12	Condition code 122
Stimulus/S217	13	Condition code 217
Stimulus/S222	14	Condition code 222
Stimulus/S212	15	Condition code 212
Stimulus/S123	16	Condition code 123
Stimulus/S113	17	Condition code 113
Stimulus/S213	18	Condition code 213
Stimulus/S112	19	Condition code 112
Stimulus/S226	20	Condition code 226
Stimulus/S211	21	Condition code 211
Stimulus/S126	22	Condition code 126
Stimulus/S221	23	Condition code 221
Stimulus/S121	24	Condition code 121
Stimulus/S216	25	Condition code 216
Stimulus/S116	26	Condition code 116
Stimulus/S214	27	Condition code 214
Stimulus/S114	28	Condition code 114
## Data Quality Notes		

- Small dataset (23 subjects, 23 files); verify that all subjects completed the same number of trials.
- `New Segment/` is an admin event and should be excluded.
- Apply bandpass filter (1-40 Hz) and artifact rejection prior to epoching.

References

- Reference: `EEG responses to the number of objects in partially occluded and uncovered scenes`

232. openneuro_ds005589 - A multi-subject and multi-session EEG dataset for modelling human visual object recognition

Dataset: `openneuro_ds005589` | Year: 2024 | URL: https://openneuro.org/datasets/ds005589
Category: Sensory/Response | Subjects: 32 | Files (Completed): 1592 | Channels: 133 | Sampling Rate: 1000 Hz

Paradigm

Participants underwent Rapid Serial Visual Presentation (RSVP) at 5 Hz and a low-speed visual presentation task to record brain responses to visual object recognition across multiple image categories. Codes 1-20 correspond to object categories in the low-speed task; codes 21-27 to RSVP categories; code 99 is catch trials; codes 252/254 are feedback. Multiple sessions were recorded per subject.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005589

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`252`	141374	short	raw	Correct response feedback
`1-20`	~80332 each	short	raw	Object category codes 1-20 (low-speed presentation)
`99`	~157200	short	raw	Catch trial
`254`	~40000	short	raw	Incorrect response feedback
`21-27`	~798 each	short	raw	Object category codes 21-27 (RSVP task)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Visual object recognition category decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Object category codes (1-20 low-speed, 21-27 RSVP); catch/feedback codes handled separately.
- Evidence: Dataset explicitly targets multi-session visual object recognition modeling from EEG. Source: https://openneuro.org/datasets/ds005589 DOI: https://doi.org/10.18112/openneuro.ds005589.v1.0.3

Normal Task 1: Visual Object Recognition (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 30 event classes. Primary task: decode object category from EEG (codes 1-20 or 21-27). Codes 252/254 and 99 may be used for filtering.

Event	y	Meaning
1	0	Object category 1
2	1	Object category 2
3	2	Object category 3
4	3	Object category 4
5	4	Object category 5
6	5	Object category 6
7	6	Object category 7
8	7	Object category 8
9	8	Object category 9
10	9	Object category 10
11	10	Object category 11
12	11	Object category 12
13	12	Object category 13
14	13	Object category 14
15	14	Object category 15
16	15	Object category 16
17	16	Object category 17
18	17	Object category 18
19	18	Object category 19
20	19	Object category 20
99	20	Catch trial
252	21	Correct feedback
254	22	Incorrect feedback
21	23	RSVP category 21
22	24	RSVP category 22

Event	y	Meaning
23	25	RSVP category 23
24	26	RSVP category 24
25	27	RSVP category 25
26	28	RSVP category 26
27	29	RSVP category 27
## Data Quality Notes		

- Large dataset (32 subjects x 1592 files); multi-session design - account for session effects.
- Apply bandpass filter (1-40 Hz) and baseline correction prior to analysis.

References

- Reference: `A multi-subject and multi-session EEG dataset for modelling human visual object recognition`

233. openneuro_ds005662 - A high-quality EEG dataset for studying visual touch perception

Dataset: openneuro_ds005662 | Year: 2025 | URL: https://openneuro.org/datasets/ds005662
Category: Sensory/Response | Subjects: N/A | Files (Completed): 80 | Channels: 65 | Sampling Rate: 2048 Hz

Paradigm

Participants viewed rapid streams of videos depicting touch to a hand or an object to investigate visual touch perception. The experiment used target and non-target trials to measure brain responses to observed touch. No event markers are present in the BIDS metadata; the EEG is stored as continuous recordings requiring segmentation for downstream analysis.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005662

Event Structure

No event markers detected (`no_events`). This dataset contains continuous EEG recordings without trial-level annotations in events.tsv.

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Event ID	Count (total)	Type	Meta Level	Meaning
`no_events`	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Publisher-defined BIDS task: Video

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005662 DOI: https://doi.org/10.18112/openneuro.ds005662.v2.0.1

Normal Task 1: Continuous Segmentation (resting)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5 s
- Label Route: `Annotation`
- Target Definition: N/A (null (no events))
- Notes: No trial-level events found. Treat as continuous EEG; sliding window segmentation only.

Data Quality Notes

- No event markers available - cannot perform event-locked epoching without additional annotation files.
- High sampling rate (2048 Hz); downsample to 500 Hz before processing.
- Apply bandpass filter (1-40 Hz) and artifact rejection prior to segmentation.

References

- Reference: `Validated Touch-Video Database (Smit & Rich, 2025)`

234. openneuro_ds006171 - EEG during Near-Threshold Visual Detection Tasks (No-Cue, 50%-Cue, 100%-Cue)

Dataset: `openneuro_ds006171` | Year: 2025 | URL: https://openneuro.org/datasets/ds006171
Category: Sensory/Response | Subjects: 26 | Files (Completed): 104 | Channels: 144 | Sampling Rate: 1024 Hz

Paradigm

Participants performed near-threshold visual detection tasks across three cueing conditions: no-cue (0% validity), noninformative cue (50% validity), and informative cue (100% validity). The study examines how spatial attention modulates near-threshold detection performance and associated EEG signatures. Stimuli were brief visual Gabor patches presented at or near detection threshold, and participants reported detection via button press. Behavioral columns (gabor_contrast, subjective_r, objective_r, response_time) stored in events.tsv enable regression analyses.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006171

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`128`	69653	admin	raw	BioSemi status boundary marker
`125`	23250	short	raw	100% validity cue - correct rejection (100pct_CR)
`124`	18239	short	raw	100% validity cue - false alarm (100pct_FA)
`2`	13793	short	raw	Response (detection report)
`1`	13790	short	raw	Trial start
`22`	6299	short	raw	50%-validity cue condition, stimulus B
`21`	6299	short	raw	50%-validity cue condition, stimulus A
`11`	6297	short	raw	No-cue condition, stimulus A
`12`	6295	short	raw	No-cue condition, stimulus B

Event ID	Count (total)	Type	Meta Level	Meaning
122	2753	short	raw	50% validity cue - miss (50pct_miss)
121	2650	short	raw	50% validity cue - hit (50pct_hit)
103	1530	short	raw	No-cue - false alarm (nocue_FA)
101	1530	short	raw	No-cue - hit (nocue_hit)
111	1529	short	raw	50% validity cue - hit (50pct_hit)
104	1529	short	raw	No-cue - correct rejection (nocue_CR)

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `response_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Near threshold visual detection task

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006171 DOI: https://doi.org/10.18112/openneuro.ds006171.v1.0.0

Normal Task 1: Near-Threshold Detection Outcome (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Specific kernel maps numeric BioSemi codes to semantic labels. `regression_target`: response_time. `continuous_cols`: response_time, gabor_contrast, subjective_r, objective_r. Code `128` is a

BioSemi boundary marker (admin; exclude). Key contrast: hit vs miss across cueing conditions.

Event	y	Meaning
`catch_trial`	0	Catch trial (no stimulus)
`catch_response`	1	Response during catch trial
`nocue_hit`	2	No-cue condition - hit
`nocue_miss`	3	No-cue condition - miss
`nocue_FA`	4	No-cue condition - false alarm
`nocue_CR`	5	No-cue condition - correct rejection
`50pct_hit`	6	50%-validity cue - hit
`50pct_miss`	7	50%-validity cue - miss
`50pct_FA`	8	50%-validity cue - false alarm
`50pct_CR`	9	50%-validity cue - correct rejection
`100pct_hit`	10	100%-validity cue - hit
`100pct_miss`	11	100%-validity cue - miss
`100pct_FA`	12	100%-validity cue - false alarm
`100pct_CR`	13	100%-validity cue - correct rejection
## Data Quality Notes		

- BioSemi 128/256-channel system; code `128` is a hardware boundary marker, not a stimulus.
- Continuous behavioral columns (gabor_contrast, subjective_r, objective_r, response_time) available for regression.
- Apply bandpass filter (0.1-40 Hz) and artifact rejection prior to epoching.

References

- Reference: `EEG data during three near-threshold visual detection tasks: a no-cue task, a noninformative cue task (50% validity), and an informative cue task (100% validity)`

235. openneuro_ds006547 - Visual EEG Study (BrainVision -> BIDS)

Dataset: `openneuro_ds006547` | Year: 2025 | URL: https://openneuro.org/datasets/ds006547
Category: Sensory/Response | Subjects: 31 | Files (Completed): 31 | Channels: 67 | Sampling Rate: 500 Hz

Paradigm

High-density EEG recordings were collected during a visual stimulation task using a BrainVision system, subsequently converted to BIDS format. Participants viewed visual stimuli under multiple conditions encoded by numeric BrainVision trigger codes (S2 through S56). The 30 distinct stimulus codes suggest a factorial or multi-condition visual paradigm covering perceptual and attentional manipulations.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006547

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus/S 5`	31	short	raw	Visual stimulus condition S5
`Stimulus/S 2`	31	short	raw	Visual stimulus condition S2
`Stimulus/S 42`	31	short	raw	Visual stimulus condition S42
`Stimulus/S 11`	31	short	raw	Visual stimulus condition S11
`Stimulus/S 51`	31	short	raw	Visual stimulus condition S51
`Stimulus/S 8`	31	short	raw	Visual stimulus condition S8
`Stimulus/S 45`	31	short	raw	Visual stimulus condition S45
`Stimulus/S 56`	31	short	raw	Visual stimulus condition S56
`Stimulus/S 3`	31	short	raw	Visual stimulus condition S3
`Stimulus/S 46`	31	short	raw	Visual stimulus condition S46
`Stimulus/S 21`	31	short	raw	Visual stimulus condition S21

Event ID	Count (total)	Type	Meta Level	Meaning
Stimulus/S 7	31	short	raw	Visual stimulus condition S7
Stimulus/S 12	31	short	raw	Visual stimulus condition S12
Stimulus/S 6	31	short	raw	Visual stimulus condition S6
Stimulus/S 16	31	short	raw	Visual stimulus condition S16
Stimulus/S 19	31	short	raw	Visual stimulus condition S19
Stimulus/S 44	31	short	raw	Visual stimulus condition S44
Stimulus/S 10	31	short	raw	Visual stimulus condition S10
Stimulus/S 55	31	short	raw	Visual stimulus condition S55
Stimulus/S 17	31	short	raw	Visual stimulus condition S17
Stimulus/S 41	31	short	raw	Visual stimulus condition S41
Stimulus/S 53	31	short	raw	Visual stimulus condition S53
Stimulus/S 50	31	short	raw	Visual stimulus condition S50
Stimulus/S 22	31	short	raw	Visual stimulus condition S22
Stimulus/S 20	31	short	raw	Visual stimulus condition S20
Stimulus/S 52	31	short	raw	Visual stimulus condition S52
Stimulus/S 14	31	short	raw	Visual stimulus condition S14
Stimulus/S 13	31	short	raw	Visual stimulus condition S13
Stimulus/S 54	31	short	raw	Visual stimulus condition S54
Stimulus/S 4	31	short	raw	Visual stimulus condition S4

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus/S 5`, `Stimulus/S 2`, `Stimulus/S 42`, `Stimulus/S 11`, `Stimulus/S 51`, `Stimulus/S 8`, `Stimulus/S 45`, `Stimulus/S 56`

- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Visual

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006547 DOI: https://doi.org/10.18112/openneuro.ds006547.v1.0.0

Normal Task 1: Visual Condition Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: 30 distinct stimulus codes; decode from events.tsv to determine condition grouping. All codes appear in all 31 files (perfectly balanced). BrainVision format; verify event alignment with EEG data.

Event	y	Meaning
`Stimulus/S 5`	0	Visual condition S5
`Stimulus/S 2`	1	Visual condition S2
`Stimulus/S 42`	2	Visual condition S42
`Stimulus/S 11`	3	Visual condition S11
`Stimulus/S 51`	4	Visual condition S51
`Stimulus/S 8`	5	Visual condition S8
`Stimulus/S 45`	6	Visual condition S45
`Stimulus/S 56`	7	Visual condition S56
`Stimulus/S 3`	8	Visual condition S3
`Stimulus/S 46`	9	Visual condition S46
`Stimulus/S 21`	10	Visual condition S21
`Stimulus/S 7`	11	Visual condition S7
`Stimulus/S 12`	12	Visual condition S12
`Stimulus/S 6`	13	Visual condition S6
`Stimulus/S 16`	14	Visual condition S16
`Stimulus/S 19`	15	Visual condition S19
`Stimulus/S 44`	16	Visual condition S44
`Stimulus/S 10`	17	Visual condition S10
`Stimulus/S 55`	18	Visual condition S55
`Stimulus/S 17`	19	Visual condition S17

Event	y	Meaning
`Stimulus/S 41`	20	Visual condition S41
`Stimulus/S 53`	21	Visual condition S53
`Stimulus/S 50`	22	Visual condition S50
`Stimulus/S 22`	23	Visual condition S22
`Stimulus/S 20`	24	Visual condition S20
`Stimulus/S 52`	25	Visual condition S52
`Stimulus/S 14`	26	Visual condition S14
`Stimulus/S 13`	27	Visual condition S13
`Stimulus/S 54`	28	Visual condition S54
`Stimulus/S 4`	29	Visual condition S4
## Data Quality Notes		

- BrainVision format converted to BIDS; verify event alignment with EEG data.
- Large number of distinct event types (30); group by experimental condition before classification.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to epoching.

References

- No paper reference available

236. openneuro_ds006777 - SFARI AVSRT EEG

Dataset: `openneuro_ds006777` | Year: 2025 | URL: https://openneuro.org/datasets/ds006777
Category: Sensory/Response | Subjects: 132 | Files (Completed): 132 | Channels: 73 | Sampling Rate: 512 Hz

Paradigm

An audiovisual simple reaction-time task (AVSRT) in which participants press a button as quickly as possible upon detecting auditory, visual, or simultaneous audiovisual stimuli. The paradigm measures unimodal vs. multimodal stimulus processing and associated reaction times. The dataset is from the SFARI (Simons Foundation Autism Research Initiative) collection, likely including participants with autism spectrum disorder and neurotypical controls.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: reaction time
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006777

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Response_button`	46353	short	raw	Participant button-press response
`Visual_stim`	16250	short	raw	Visual stimulus onset
`Audiovisual_stim`	16130	short	raw	Simultaneous audiovisual stimulus onset
`Auditory_stim`	15995	short	raw	Auditory stimulus onset

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `reaction_time`
- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.

- Candidate Trigger Labels: `Visual_stim`, `Audiovisual_stim`, `Auditory_stim`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Audiovisual reaction-time decoding and RT modeling

- Task Type: classification/regression
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation` and `misc`
- Target Definition: Stimulus modality labels (auditory/visual/audiovisual) and reaction-time target derived from stimulus-response pairing.
- Evidence: AVSRT paradigm is designed to compare modality effects and reaction time in simple response trials. Source: https://openneuro.org/datasets/ds006777 DOI: https://doi.org/10.18112/openneuro.ds006777.v1.0.0

Normal Task 1: Stimulus Modality Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Three balanced modality conditions (Auditory/Visual/Audiovisual ~16000 each) well-suited for multiclass decoding. `Response_button` is a motor response event; exclude from stimulus classification if needed.

Event	y	Meaning
`Response_button`	0	Button-press response
`Audiovisual_stim`	1	Simultaneous audiovisual stimulus
`Auditory_stim`	2	Auditory-only stimulus
`Visual_stim`	3	Visual-only stimulus
## Data Quality Notes		

- SFARI autism cohort; likely includes participants with ASD and neurotypical controls.
- `Response_button` is a motor event marker, not a stimulus; consider excluding from stimulus decoding.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to epoching.

References

- Reference: `SFARI AVSRT EEG`

237. physionet_mssvepdb - Multi-Stimulus SSVEP Database

Dataset: `physionet_mssvepdb` | Year: 2021 | URL: N/A
Category: Sensory/Response | Subjects: 11 | Files (Completed): 235 | Channels: 14 (Emotiv) or 256 (BrainProducts) | Sampling Rate: 128 Hz (dataset3) or 250 Hz (datasets 1-2)

Paradigm

Eleven subjects performed steady-state visual evoked potential (SSVEP) tasks across three recording datasets with different EEG hardware (Nakanishi et al., 2018). Subjects fixated on flickering visual stimuli at different frequencies while EEG was recorded. Datasets 1 and 2 used a BrainProducts system (256 channels, 250 Hz); dataset 3 used an Emotiv EPOC (14 channels, 128 Hz). Each recording corresponds to one SSVEP stimulus condition (frequency). The kernel creates a single whole-recording `SSVEP` annotation for each file; the stimulus frequency is encoded in the filename/subdirectory.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://www.physionet.org/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
SSVEP	235	long	raw	SSVEP stimulus period (spans entire recording); frequency encoded in filename

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Stimulus frequency information must be parsed from the filename or subdirectory (e.g., frequency in Hz). Each file corresponds to one stimulus frequency condition.

Tasks

Primary Task 1: SSVEP target/frequency decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification] | tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `stim` or `Annotation`
- Target Definition: Stimulus frequency or target index
- Evidence: SSVEP paradigm is explicitly stated in dataset metadata/reference. Source: https://www.physionet.org/ DOI: https://doi.org/10.1109/tbme.2017.2694818

Normal Task 1: SSVEP Frequency Classification (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 4.0 s, overlap = 2.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Frequency label derived from filename; e.g., map each stimulus frequency to a class index.
- Notes: Stimulus frequencies and their mapping to class indices must be parsed from file paths or metadata. Process datasets 1/2 (BrainProducts, 256ch, 250Hz) and dataset 3 (Emotiv, 14ch, 128Hz) separately due to different channel counts and sampling rates.

Data Quality Notes

- Hardware differences across datasets: datasets 1-2 (BrainProducts, 256 channels, 250 Hz) vs. dataset 3 (Emotiv EPOC, 14 channels, 128 Hz); do not mix datasets in cross-subject analysis without normalization.
- Frequency labels are encoded in filenames, not event annotations; parse filenames to obtain classification targets.
- Age range: 24-39 years; sex: ~171 male / 64 female recording sessions.
- For SSVEP analysis, focus on occipital channels (Oz, O1, O2, POz) from the BrainProducts recordings.

References

- Reference: Nakanishi M et al. (2018). Enhancing Detection of SSVEPs for a High-Speed Brain Speller Using Task-Related Component Analysis. IEEE Trans. Biomed. Eng. https://www.physionet.org/

Chapter 5. Biological State

Datasets in this chapter: 43. Task-free or state-monitoring data (rest/sleep/clinical monitoring).

238. openneuro_ds001787 - EEG meditation study

Dataset: `openneuro_ds001787` | Year: 2024 | URL: https://openneuro.org/datasets/ds001787
Category: Biological State | Subjects: 24 | Files (Completed): 40 | Channels: 80.0 | Sampling Rate: 256.0 Hz

Paradigm

Subjects engaged in focused meditation sessions that were interrupted every two minutes by a brief probe assessing concentration level and mind-wandering. EEG was recorded continuously with stimulus markers at probe onsets and response markers at button-press responses. The study examined neural correlates of sustained attention and mind-wandering during meditation using ERP and time-frequency analysis.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: response_time, regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds001787

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`response`	40 (files)	short	raw	Participant button-press response to attention probe
`stimulus`	40 (files)	short	raw	Probe stimulus onset (attention check)
`STATUS`	5	admin	raw	BioSemi system status marker - exclude

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

MISC Label Summary

- Route: `misc`
- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `response_time`

- Kernel Note: Keep derivation source, unit, and version metadata.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `stimulus`, `STATUS`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Meditation

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds001787 DOI: https://doi.org/10.18112/openneuro.ds001787.v1.1.1

Normal Task 1: Stimulus-Response ERP (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `STATUS` is a BioSemi admin marker (count=5 files only) - excluded from target_events. Regression target: `response_time` from misc channel. The count column shows files-with-event, not total trial count.

Event	y	Meaning
`stimulus`	0	Probe stimulus onset
`response`	1	Button-press response
## Data Quality Notes		

- `STATUS` events are BioSemi system markers, not task events - do not epoch on these.
- Multiple `response` events may occur per `stimulus` probe; consider windowing to first response only.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `Arnaud Delorme (October 17, 2018; updated June 2024)`

239. openneuro_ds001849 - RS_TMSEEG_Data

Dataset: `openneuro_ds001849` | Year: 2020 | URL: https://openneuro.org/datasets/ds001849
Category: Biological State | Subjects: N/A | Files (Completed): 120 | Channels: 30.0 | Sampling Rate: 5000.0 Hz

Paradigm

Resting-state EEG data recorded in conjunction with Transcranial Magnetic Stimulation (TMS). Subjects were at rest (no active task) while TMS pulses were delivered; the R128 marker in BrainVision format marks a system/response trigger present in all files but does not indicate a meaningful task event. The primary scientific interest is resting-state oscillatory dynamics and TMS-evoked potentials.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds001849

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`R128`	120 (files)	admin	raw	BrainVision system/response trigger present in every file - not a task event

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: Publisher-defined BIDS task: Tmseegrest

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds001849 DOI: https://doi.org/10.18112/openneuro.ds001849.v1.0.2

Normal Task 1: Resting / Continuous Segmentation (resting)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (no task events; R128 is admin))
- Notes: R128 appears in all 120 files and is a BrainVision recording artifact marker. High sampling rate (5000 Hz); consider downsampling. TMS artifact rejection may be needed if TMS pulses are captured in recording.

Data Quality Notes

- R128 is a BrainVision system marker present in every file - it is not a stimulus or response event.
- High sampling rate (5000 Hz); significant downsampling required before most analyses.
- TMS artifacts may contaminate EEG within the first ~50 ms post-pulse; apply TMS artifact rejection if analyzing TMS-evoked potentials.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `RS_TMSEEG_Data`

240. openneuro_ds002778 - UC San Diego Resting State EEG Data from Patients with Parkinson's Disease

Dataset: `openneuro_ds002778` | Year: 2021 | URL: https://openneuro.org/datasets/ds002778
Category: Biological State | Subjects: N/A | Files (Completed): 46 | Channels: 41.0 | Sampling Rate: 512.0 Hz

Paradigm

Spontaneous scalp EEG recorded from patients with Parkinson's disease (PD) and healthy controls during resting-state conditions. The study investigated abnormal beta-band synchrony and beta waveform shape features (phase amplitude coupling, non-sinusoidal characteristics) as biomarkers of PD. All events in the BioSemi recording are system status markers (65536 = CM_in_range baseline, 130817 = CM status); no task events exist.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds002778

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`1`	44 (files)	admin	raw	BioSemi recording marker (onset of continuous record) - admin
`65536`	43 (files)	admin	raw	BioSemi CM_in_range baseline status code - exclude
`2`	1 (file)	admin	raw	BioSemi marker - sparse, likely admin
`130817`	1 (file)	admin	raw	BioSemi CM status code - exclude

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
> - `long`: sustained-state marker (>=2 s), for `epoch_by_long_event_hdf5`
> - `rest`: resting-state segment marker, for `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, exclude from epoch target_events

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://doi.org/10.1523/ENEURO.0151-19.2019

Normal Task 1: Resting / Continuous Segmentation (resting)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (all events are admin; PD vs HC labels from participants.tsv))
- Notes: 65536 is the BioSemi CM_in_range baseline status code - a hardware marker not a task event. PD vs healthy control group labels are in participants.tsv and can be used as subject-level binary labels. Specific kernel adds participant group annotation.

Data Quality Notes

- Pure resting-state dataset; all events are BioSemi hardware status codes.
- 65536 (CM_in_range) and 130817 are BioSemi system codes - do not epoch on these.
- PD vs HC group labels available in participants.tsv for disease classification.
- Verify channel count consistency across subjects before pooling.

References

- Paper: Characteristics of Waveform Shape in Parkinson's Disease Detected with Scalp Electroencephalography (DOI/ref: `10.1523/ENEURO.0151-19.2019`)

241. openneuro_ds003194 - Neuroepo multisession

Dataset: `openneuro_ds003194` | Year: 2022 | URL: https://openneuro.org/datasets/ds003194
Category: Biological State | Subjects: 25 | Files (Completed): 29
Channels: 19 | Sampling Rate: 200 Hz

Paradigm

Resting-state EEG recorded before and after a six-month Neuroepo drug administration period to evaluate neuroprotective effects in Parkinson's disease patients. The protocol includes resting-state (eyes closed / eyes open), hyperventilation periods, and photic stimulation sections. This is a clinical neurological assessment battery recorded in Spanish (event labels in Spanish).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003194

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`ojos cerrados`	29 (files)	long	raw	Eyes-closed resting state
`ojos abiertos`	28 (files)	long	raw	Eyes-open resting state
`recuperacion`	28 (files)	long	raw	Recovery period after hyperventilation
`hiperventilacion 1`	27 (files)	long	raw	Hyperventilation period 1
`hiperventilacion 2`	28 (files)	long	raw	Hyperventilation period 2
`hiperventilacion 3`	28 (files)	long	raw	Hyperventilation period 3
`hiperventilacion 4`	15 (files)	long	raw	Hyperventilation period 4
`photic stimulation`	11 (files)	long	raw	Photic stimulation block
`fotoestimulacion`	11 (files)	long	raw	Photic stimulation (Spanish label)
`discontinuity`	9 (files)	admin	raw	Recording discontinuity marker - exclude
`HPVOJOS ABIERTOS`	6 (files)	long	raw	Eyes-open during hyperventilation

Event ID	Count (total)	Type	Meta Level	Meaning
HEPERVENTILACION OJOS ABIERTOS	1 (file)	long	raw	Hyperventilation eyes-open variant

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: photic stimulation, fotoestimulacion
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Task pre nepo

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003194 DOI: https://doi.org/10.18112/openneuro.ds003194.v1.0.4

Primary Task 2: Publisher-defined BIDS task: Task 6m nepo

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003194 DOI: https://doi.org/10.18112/openneuro.ds003194.v1.0.4

Normal Task 1: Brain State Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: discontinuity is a recording discontinuity marker - excluded. All other events are sustained clinical states (>=2 s). photic stimulation and fotoestimulacion are equivalent labels (Spanish/English) for the same condition.

Event	y	Meaning
ojos cerrados	0	Eyes-closed resting state

Event	y	Meaning
ojos abiertos	1	Eyes-open resting state
recuperacion	2	Recovery period
hiperventilacion 2	3	Hyperventilation period 2
hiperventilacion 3	4	Hyperventilation period 3
hiperventilacion 1	5	Hyperventilation period 1
hiperventilacion 4	6	Hyperventilation period 4
photic stimulation	7	Photic stimulation
fotoestimulacion	8	Photic stimulation (Spanish)
HPVOJOS ABIERTOS	9	Eyes-open during hyperventilation
HEPERVENTILACION OJOS ABIERTOS	10	Hyperventilation eyes-open variant
## Data Quality Notes		

- Clinical recording from Parkinson's patients; expect higher artifact rate than healthy subjects.
- `photic stimulation` / `fotoestimulacion` are duplicate labels for the same condition.
- `discontinuity` events mark recording gaps - exclude from epoch analysis.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `EEG-BIDS, an extension to the brain imaging data structure for electroencephalography. Sci. data 6, 103 (2019)`

242. openneuro_ds003195 - Placebo Neuroepo multisession

Dataset: `openneuro_ds003195` | Year: 2022 | URL: https://openneuro.org/datasets/ds003195
Category: Biological State | Subjects: 20 | Files (Completed): 20
Channels: 19 | Sampling Rate: 200 Hz

Paradigm

Resting-state EEG recorded from Parkinson's disease patients who received a placebo (not active Neuroepo) during a six-month drug evaluation trial. Recordings were taken before and after the administration period. This is the placebo control arm companion to ds003194 (Neuroepo treatment). Protocol includes resting-state (eyes open/closed), hyperventilation, and recovery periods.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003195

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`ojos cerrados`	20 (files)	long	raw	Eyes-closed resting state
`ojos abiertos`	19 (files)	long	raw	Eyes-open resting state
`hiperventilacion 1`	19 (files)	long	raw	Hyperventilation period 1
`hiperventilacion 2`	19 (files)	long	raw	Hyperventilation period 2
`hiperventilacion 3`	19 (files)	long	raw	Hyperventilation period 3
`recuperacion`	19 (files)	long	raw	Recovery period after hyperventilation
`hiperventilacion 4`	12 (files)	long	raw	Hyperventilation period 4
`discontinuity`	8 (files)	admin	raw	Recording discontinuity marker - exclude
`photic stimulation`	3 (files)	long	raw	Photic stimulation block
`fotoestimulacion`	3 (files)	long	raw	Photic stimulation (Spanish label)
`HPVOJOS ABIERTOS`	2 (files)	long	raw	Eyes-open during hyperventilation

Event ID	Count (total)	Type	Meta Level	Meaning
hipervantilacion 4	1 (file)	long	raw	Hyperventilation period 4 (variant spelling)

Event Type Description:
- short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
- long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
- rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- admin: system/boundary marker, not used for epoch

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: photic stimulation, fotoestimulacion
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Task placebo 6m

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003195 DOI: https://doi.org/10.18112/openneuro.ds003195.v1.0.4

Primary Task 2: Publisher-defined BIDS task: Task placebo pre

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003195 DOI: https://doi.org/10.18112/openneuro.ds003195.v1.0.4

Normal Task 1: Brain State Classification (multiclass)

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: discontinuity is a recording gap marker - excluded. Sparse counts for photic stimulation (3 files) and HPVOJOS (2 files); consider merging equivalent Spanish/English labels. Placebo arm of Neuroepo trial (NCT04110678).

Event	y	Meaning
`ojos cerrados`	0	Eyes-closed resting state
`ojos abiertos`	1	Eyes-open resting state
`hiperventilacion 1`	2	Hyperventilation period 1
`hiperventilacion 2`	3	Hyperventilation period 2
`hiperventilacion 3`	4	Hyperventilation period 3
`recuperacion`	5	Recovery period
`hiperventilacion 4`	6	Hyperventilation period 4
`photic stimulation`	7	Photic stimulation
`fotoestimulacion`	8	Photic stimulation (Spanish)
`HPVOJOS ABIERTOS`	9	Eyes-open during hyperventilation
`hipervantilacion 4`	10	Hyperventilation period 4 (variant spelling)
## Data Quality Notes		

- Clinical recording from Parkinson's patients; expect higher artifact rate.
- `photic stimulation` and `fotoestimulacion` are equivalent labels - merge if needed.
- `hipervantilacion 4` is a spelling variant of `hiperventilacion 4` - treat as same condition.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `NCT04110678`

243. openneuro_ds003478 - EEG: Depression rest

Dataset: openneuro_ds003478 | Year: 2021 | URL: https://openneuro.org/datasets/ds003478
Category: Biological State | Subjects: 122 | Files (Completed): 243
Channels: 66 | Sampling Rate: 500 Hz

Paradigm

Resting-state EEG recording featuring alternating one-minute intervals of eyes-open and eyes-closed conditions in participants with varying scores on the Beck Depression Inventory (BDI). The study aims to identify EEG biomarkers of depression severity. Each session includes multiple alternating eyes-open and eyes-closed blocks, with `Start and Finish` markers indicating session boundaries. STATUS is a BioSemi admin marker.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, stim, misc
> Evidence Keywords: regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003478

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Eyes Open`	368 (files)	long	raw	Eyes-open resting state block (~1 min)
`Eyes Closed`	368 (files)	long	raw	Eyes-closed resting state block (~1 min)
`STATUS`	243 (files)	admin	raw	BioSemi system status marker - exclude
`Start and Finish`	184 (files)	admin	raw	Session start/end boundary marker - exclude

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

MISC Label Summary

- Route: `misc`
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification

- Kernel Note: Document derivation logic, source fields, units, and version tags.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `STATUS`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://openneuro.org/datasets/ds003478 DOI: https://doi.org/10.18112/openneuro.ds003478.v1.1.0

Normal Task 1: Eyes Open vs Eyes Closed Classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `STATUS` is BioSemi admin marker; `Start and Finish` marks session boundaries - both excluded. Eyes-open vs eyes-closed is the primary binary classification. BDI scores in participants.tsv can serve as continuous regression targets for depression severity prediction.

Event	y	Meaning
`Eyes Open`	0	Eyes-open resting state (~1 min block)
`Eyes Closed`	1	Eyes-closed resting state (~1 min block)
## Data Quality Notes		

- `STATUS` is BioSemi hardware marker - exclude.
- `Start and Finish` marks session boundaries - admin marker, exclude.
- Large dataset: 122 subjects, 243 files; subject-level BDI scores available for depression prediction.
- Verify channel count consistency across subjects before pooling.

References

- Reference: `EEG: Depression rest`

244. openneuro_ds003555 - Dataset of EEG Recordings of Pediatric Patients with Epilepsy Based on the 10-20 System

Dataset: `openneuro_ds003555` | Year: 2021 | URL: https://openneuro.org/datasets/ds003555
Category: Biological State | Subjects: 30 | Files (Completed): 257
Channels: 52 | Sampling Rate: 2000 Hz

Paradigm

Continuous sleep EEG recordings from pediatric patients with epilepsy, focused on identifying High-Frequency Oscillations (HFOs) as clinical biomarkers during N3 slow-wave sleep stages. The dataset was recorded using the standard 10-20 electrode system and is intended for automated HFO detection algorithm development and sleep stage analysis. No task-based paradigm was employed; recordings capture spontaneous brain activity during sleep.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003555

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
-	-	-	raw	No event markers detected; continuous sleep EEG recording

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Sleep stage classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Sleep stage labels (W/N1/N2/N3/REM; mapping dataset-specific)
- Evidence: Dataset and references explicitly center on PSG/EEG sleep scoring. Source: https://openneuro.org/datasets/ds003555 DOI: https://doi.org/10.18112/openneuro.ds003555.v1.0.1

Normal Task 1: Continuous sleep EEG segmentation

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (no label, for unsupervised or HFO detection))
- Notes: High sampling rate (2000 Hz) is appropriate for HFO detection (80-500 Hz). Sleep stage labels (if available from hypnogram) can serve as y labels for sleep classification tasks. No trial-level events present.

Data Quality Notes

- Very high sampling rate (2000 Hz); high memory requirements for processing.
- Pediatric epilepsy population; inter-individual variability in seizure history and medications.
- HFO detection requires high-frequency filtering (80-500 Hz); standard 0.5-40 Hz bandpass not appropriate for primary analysis goal.

References

- Reference: `Dataset of EEG recordings of pediatric patients with epilepsy based on the 10-20 system`

245. openneuro_ds003710 - APPLESEED Example Dataset

Dataset: `openneuro_ds003710` | Year: 2022 | URL: https://openneuro.org/datasets/ds003710
Category: Biological State | Subjects: 13 | Files (Completed): 48
Channels: 32 | Sampling Rate: 5000 Hz

Paradigm

Longitudinal spontaneous EEG recordings from infants at 4, 8, and 12 months of age during passive viewing of social and non-social stimuli (faces, speech, objects, water). The dataset validates the APPLESEED (Automated Preprocessing Pipe-Line for the Estimation of Scale-wise Entropy from EEG Data) pipeline for pediatric EEG preprocessing and entropy estimation. Stimuli include social (face, speech) and non-social (object, water) categories presented as short video clips, with attention-getter events to orient the infant.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003710

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`face`	48	short	raw	Face stimulus onset (social)
`speech`	48	short	raw	Speech stimulus onset (social)
`object`	48	short	raw	Object stimulus onset (non-social)
`water`	48	short	raw	Water stimulus onset (non-social)
`attention-getter`	48	short	raw	Attention-orienting stimulus before trial
`experimenter-pause`	45	admin	raw	Experimenter pause marker
`New Segment`	48	admin	raw	Recording segment boundary marker
`Comment`	48	admin	raw	Experimenter annotation

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: APPLESEED example

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003710 DOI: https://doi.org/10.1186/s12916-020-01683-x

Normal Task 1: Social vs non-social stimulus classification (binary)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s (relative to event onset), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Very high sampling rate (5000 Hz); downsample to 250-500 Hz before epoching. Infant EEG; high artifact rates expected. Only 13 subjects (48 files across 3 age points). `New Segment`, `Comment`, and `experimenter-pause` are admin markers.

Event	y	Meaning
`face`	1	Face stimulation (social)
`speech`	1	Verbal stimulation (social)
`object`	0	Object stimulus (non-social)
`water`	0	Water stimulation (non-social)
## Data Quality Notes		

- Extremely high sampling rate (5000 Hz); downsampling required before standard EEG analysis.
- Infant population; high motion artifacts and data loss expected.
- Small sample (13 subjects); longitudinal design with 3-4 files per subject across age points.
- `New Segment` and `Comment` markers should be excluded from epoching.

References

- Reference: `The Automated Preprocessing Pipe-Line for the Estimation of Scale-wise Entropy from EEG Data (APPLESEED): Development and validation for use in pediatric populations. OpenNeuro ds003710.`

246. openneuro_ds003768 - Simultaneous EEG and fMRI Signals During Sleep from Humans

Dataset: `openneuro_ds003768` | Year: 2026 | URL: https://openneuro.org/datasets/ds003768
Category: Biological State | Subjects: 33 | Files (Completed): 252
Channels: 32 | Sampling Rate: 5000 Hz

Paradigm

Simultaneous EEG-fMRI recordings were acquired during resting-state wakefulness and multiple sleep sessions (NREM, REM) to analyze spontaneous brain activity and sleep stage dynamics. Participants underwent extended sleep sessions in an MRI scanner while 32-channel EEG was recorded concurrently with fMRI. BrainVision numeric stimulus codes (S1, S2, S3) and response codes (R128) mark sleep stage transitions or scoring events. The dataset supports multimodal sleep neuroscience research.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003768

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Stimulus/S 1`	183	long	raw	BrainVision S1 trigger (sleep stage marker)
`Stimulus/S 2`	193	long	raw	BrainVision S2 trigger (sleep stage marker)
`Stimulus/S 3`	183	long	raw	BrainVision S3 trigger (sleep stage marker)
`Response/R128`	252	admin	raw	BrainVision R128 response trigger

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `Stimulus/S 1`, `Stimulus/S 2`, `Stimulus/S 3`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Sleep stage classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Sleep stage labels (W/N1/N2/N3/REM; mapping dataset-specific)
- Evidence: Dataset and references explicitly center on PSG/EEG sleep scoring. Source: https://openneuro.org/datasets/ds003768 DOI: https://doi.org/10.18112/openneuro.ds003768.v1.0.13

Primary Task 2: Publisher-defined BIDS task: Rest

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003768 DOI: https://doi.org/10.18112/openneuro.ds003768.v1.0.13

Normal Task 1: Sleep stage classification (multiclass, long event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: S1/S2/S3 likely encode sleep stage transitions (Wake, NREM1/2/3, REM); exact mapping must be confirmed from events.tsv or dataset documentation. Sleep stages are sustained states (>=2 s); use long-event epoching. Very high sampling rate (5000 Hz); downsample to 250 Hz for standard sleep scoring.

Event	y	Meaning
`Stimulus/S 1`	0	Sleep stage 1 (need to confirm the specific sleep stage from events.tsv)
`Stimulus/S 2`	1	Sleep Stage 2
`Stimulus/S 3`	2	Sleep Stage 3
## Data Quality Notes		

- Very high sampling rate (5000 Hz); downsample to 250-500 Hz before analysis.
- EEG-fMRI simultaneous recording; gradient artifacts present; requires MRI artifact removal.
- R128 is a BrainVision response/sync marker; treat as admin.
- 252 files from 33 subjects across multiple sleep sessions.

References

- Reference: `Albouy et al., Journal of Sleep Research, 2013. Simultaneous EEG and fMRI during sleep. OpenNeuro ds003768.`

247. openneuro_ds003775 - SRM Resting-State EEG

Dataset: openneuro_ds003775 | Year: 2022 | URL: https://openneuro.org/datasets/ds003775
Category: Biological State | Subjects: 111 | Files (Completed): 153
Channels: 64 | Sampling Rate: 1024 Hz

Paradigm

Four minutes of uninterrupted eyes-closed resting-state EEG recorded from healthy adult participants as part of a larger experimental paradigm. This dataset was collected to provide a normative baseline for comparing resting EEG characteristics across studies. The resting-state recording provides a standardized, task-free EEG sample suitable for spectral power analysis, functional connectivity, and individual difference studies.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003775

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
-	-	-	raw	No event markers detected; pure resting-state EEG

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Resteyesc

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds003775 DOI: https://doi.org/10.1111/ejn.14964

Normal Task 1: Resting state EEG segmentation

- Task Type: segmentation
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (null (no labels, used for unsupervised analysis or individual differences research))
- Notes: Pure 4-minute eyes-closed resting-state; 111 subjects, 153 files (some subjects may have multiple sessions). Suitable for individual alpha frequency, spectral power, and connectivity analyses. Large normative dataset.

Data Quality Notes

- Purely resting-state; no task events or stimuli.
- 153 files from 111 subjects; some subjects have multiple files (repeat sessions).
- 64-channel EEG at 1024 Hz; standard configuration for resting-state analysis.

References

- Reference: `Hatlestad-Hall, C., Rygvold, T. W., & Andersson, S. (2022). BIDS-structured resting-state electroencephalography (EEG) data extracted from an experimental paradigm. Data in Brief, 45, 108647.`

248. openneuro_ds003944 - EEG: First Episode Psychosis vs. Control Resting Task 1

Dataset: openneuro_ds003944 | Year: 2022 | URL: https://openneuro.org/datasets/ds003944
Category: Biological State | Subjects: 82 | Files (Completed): 82
Channels: 64 | Sampling Rate: 1000 Hz

Paradigm

A 5-minute eyes-open resting-state EEG recording comparing spontaneous brain activity between individuals with First Episode Psychosis (FEP) and age-matched healthy controls. The dataset is designed to identify EEG biomarkers of psychosis onset. No trial-level stimuli are presented; the label of interest is the clinical group membership (FEP vs. control) stored in participants.tsv.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003944

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
unknown	82	admin	raw	Unidentified system marker - not suitable for epoching

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://openneuro.org/datasets/ds003944 DOI: https://doi.org/10.18112/openneuro.ds003944.v1.0.1

Normal Task 1: FEP vs. Control Classification (binary, resting-state segmentation)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: None (label from participants.tsv group column)
- Notes: Purely resting-state dataset; segment continuously and assign subject-level diagnosis labels (FEP=1, control=0). No task events are available for epoch_by_event. Group label must be extracted from participants metadata.

Data Quality Notes

- No meaningful event markers; `unknown` events should be excluded
- Subject count not specified in header; 82 files suggests ~82 subjects
- Verify FEP/control group balance in participants.tsv before training

References

- No paper reference available

249. openneuro_ds003947 - EEG: First Episode Psychosis vs. Control Resting Task 2

Dataset: openneuro_ds003947 | Year: 2022 | URL: https://openneuro.org/datasets/ds003947
Category: Biological State | Subjects: 61 | Files (Completed): 61
Channels: 64 | Sampling Rate: 3000 Hz

Paradigm

Five minutes of resting-state EEG recording used to compare spontaneous brain activity between individuals with First Episode Psychosis (FEP) and healthy controls. This is a second independent resting-state dataset from the same clinical study series as ds003944, recorded at a higher sampling rate (3000 Hz). Group membership (FEP vs. control) serves as the classification label.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds003947

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
unknown	61	admin	raw	Unidentified system marker - not suitable for epoching

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://openneuro.org/datasets/ds003947 DOI: https://doi.org/10.18112/openneuro.ds003947.v1.0.1

Normal Task 1: FEP vs. Control Classification (binary, resting-state segmentation)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: None (label from participants.tsv group column)
- Notes: Purely resting-state dataset; segment continuously and assign subject-level diagnosis labels (FEP=1, control=0). High sampling rate (3000 Hz) - consider downsampling to 500 Hz before processing to reduce computational load.

Data Quality Notes

- No meaningful event markers; `unknown` events should be excluded
- Very high sampling rate (~3000 Hz) may require downsampling
- Companion dataset to ds003944 (Task 1); can be combined for larger resting FEP cohort

References

- No paper reference available

250. openneuro_ds004348 - Ear-EEG Sleep Monitoring 2017 (EESM17)

Dataset: `openneuro_ds004348` | Year: 2024 | URL: https://openneuro.org/datasets/ds004348
Category: Biological State | Subjects: 9 | Files (Completed): 36
Channels: 35 | Sampling Rate: 200 Hz

Paradigm

Nightly sleep monitoring and pre-sleep resting recordings using ear-EEG and partial polysomnography in a naturalistic home environment. Subjects wore ear-mounted EEG devices during sleep, allowing investigation of sleep stage classification and comparison between ear-EEG and conventional PSG signals.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004348

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Lights Off`	9	long	raw	Lights-off marker (sleep onset reference)
`Lights On`	9	long	raw	Lights-on marker (sleep end reference)
`Awake`	1	long	raw	Wakefulness annotation
`Artifact`	9	admin	raw	Artifact annotation
`Arousal`	9	admin	raw	Arousal annotation
`Beginning of Recording`	9	admin	raw	Recording start marker
`End of Study`	9	admin	raw	Recording end marker
`Montage`	9	admin	raw	Montage configuration event
`Started Analyzer - Sleep Events`	9	admin	raw	Analyzer start marker
`Started Analyzer - ECG`	9	admin	raw	ECG analyzer start
`Stopped Analyzer - ECG`	9	admin	raw	ECG analyzer stop

Event ID	Count (total)	Type	Meta Level	Meaning
`Started Analyzer - Auto-Staging`	9	admin	raw	Auto-staging start
`Stopped Analyzer - Auto-Staging`	9	admin	raw	Auto-staging stop
`512`	9	admin	raw	Numerical trigger code 512

Event Type Description:
- `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
- `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
- `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- `admin`: system/boundary marker, not used for epoch

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Sleep stage classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Sleep stage labels (W/N1/N2/N3/REM; mapping dataset-specific)
- Evidence: Dataset and references explicitly center on PSG/EEG sleep scoring. Source: https://openneuro.org/datasets/ds004348 DOI: https://doi.org/10.1186/s12938-017-0400-5

Normal Task 1: Sleep Staging (long event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s (relative to event onset), overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Sleep stage labels (N1/N2/N3/REM) are typically stored in annotation files, not event markers. Use Lights Off/On as block boundaries. The dataset is primarily suitable for sleep staging classification.

Event	y	Meaning
`Lights Off`	0	Sleep period start
`Lights On`	1	Sleep period end
## Data Quality Notes		

- Sleep stage annotations are in PSG annotation files, not directly as trial events
- Artifact markers must be excluded from analysis windows

- 35 channels includes non-EEG channels (ECG, respiratory belt, etc.)
- Only 9 subjects; limited generalization

References

- Reference: `Ear-EEG Sleep Monitoring 2017 (EESM17)`

251. openneuro_ds004504 - A dataset of EEG recordings from: Alzheimer's disease, Frontotemporal dementia and Healthy subjects

Dataset: openneuro_ds004504 | Year: 2024 | URL: https://openneuro.org/datasets/ds004504
Category: Biological State | Subjects: 88 | Files (Completed): 176
Channels: 19 | Sampling Rate: 500 Hz

Paradigm

Resting-state EEG recordings with eyes closed collected from healthy controls and patients with Alzheimer's disease (AD) and Frontotemporal Dementia (FTD). The study provides a clinical EEG dataset for developing diagnostic biomarkers and machine learning classifiers to differentiate neurodegenerative conditions from healthy aging.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004504

Event Structure

No event markers detected (no_events). This dataset contains resting-state EEG recordings without trial-level annotations.

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

Event ID	Count (total)	Type	Meta Level	Meaning
no_events	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: epoch_by_segmentation_hdf5 or epoch_by_long_event_hdf5

- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://openneuro.org/datasets/ds004504 DOI: https://doi.org/10.3390/diagnostics11081437

Normal Task 1: Dementia Classification (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (subject-level labels from participants.tsv)
- Notes: Subject-level diagnosis labels (HC/AD/FTD) in participants.tsv used as ground truth. 19-channel 10-20 system EEG; standard clinical montage. 2 sessions per subject (176 files / 88 subjects).

Data Quality Notes

- No trial-level event markers; pure resting-state dataset
- Subject diagnosis labels (HC/AD/FTD) available in participants.tsv
- Standard 10-20 montage (19 channels)
- 2 recordings per subject (176 files / 88 subjects)

References

- Reference: `A Dataset of Scalp EEG Recordings of Alzheimers Disease, Frontotemporal Dementia and Healthy Subjects from Routine EEG`

252. openneuro_ds004577 - Dataset containing resting EEG for a sample of 103 normal infants in the first year of life

Dataset: openneuro_ds004577 | Year: 2023 | URL: https://openneuro.org/datasets/ds004577
Category: Biological State | Subjects: 103 | Files (Completed): 103 | Channels: 128 | Sampling Rate: 500 Hz

Paradigm

Resting-state EEG recordings from 103 healthy infants (aged 1-12 months) during the first year of life. Recordings were made during natural infant rest/sleep states. Eyes-open and eyes-closed state markers are present but the primary data is continuous infant resting EEG. The dataset supports developmental neuroscience research on early brain maturation.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004577

Event Structure

No task event markers. State markers (eyes_closed, eyes_open) and artifact markers (discontinuity) are present but the dataset is primarily resting-state continuous EEG.

Event ID	Count (total)	Type	Meta Level	Meaning
`eyes_closed`	~103xN	rest	raw	Eyes-closed resting state
`eyes_open`	~103xN	rest	raw	Eyes-open resting state
`discontinuity`	~103xN	admin	raw	Recording discontinuity/artifact marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: EEG

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification

- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004577 DOI: https://doi.org/10.1016/j.earlhumdev.2011.05.010

Normal Task 1: Continuous Segmentation (resting/segmentation)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: N/A (unsupervised segmentation)
- Notes: Infant resting EEG without trial structure. discontinuity markers indicate artifact segments. Use sliding window segmentation; consider excluding segments surrounding discontinuity markers.

Data Quality Notes

- 103 infants aged 1-12 months; high variability in developmental stage
- 128 channels; high-density pediatric EEG cap
- discontinuity markers indicate artifact/movement artifacts in infant recordings

References

- Reference: `Dataset containing resting EEG for a sample of 103 normal infants in the first year of life`

253. openneuro_ds004584 - Rest Eyes Open (Parkinson's Disease)

Dataset: openneuro_ds004584 | Year: 2023 | URL: https://openneuro.org/datasets/ds004584
Category: Biological State | Subjects: 149 | Files (Completed): 149 | Channels: 63 | Sampling Rate: 500 Hz

Paradigm

Resting-state EEG was collected from 149 participants (100 with Parkinson's disease and 49 healthy controls) who sat quietly with eyes open for approximately two minutes. The study characterizes spontaneous neural oscillatory patterns to differentiate PD patients from controls. No active task was required; participants fixated on a cross and remained still.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004584

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`boundary`	149	admin	raw	Segment boundary marker inserted by recording software (exclude)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://openneuro.org/datasets/ds004584 DOI: https://doi.org/10.21203/rs.3.rs-2666578/v1

Normal Task 1: Resting State Segmentation (segmentation)

- Task Type: classification
- Epoch Method: `segmentation`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5

- Label Route: `Annotation`
- Target Definition: None (no task events)
- Notes: Only `boundary` admin markers present - pure resting-state dataset. Use sliding-window segmentation. PD vs. control group labels available from participants.tsv for downstream classification.

Data Quality Notes

- Only boundary markers present; no trial events for epoch-locked classification.
- PD vs. control labels available in participants.tsv.

References

- Reference: `Rest eyes open EEG dataset - Parkinson's disease and healthy controls`

254. openneuro_ds004635 - Gaffrey Lab Infant EEG Microstates Reliability

Dataset: openneuro_ds004635 | Year: 2024 | URL: https://openneuro.org/datasets/ds004635
Category: Biological State | Subjects: 48 | Files (Completed): 1
Channels: 129 | Sampling Rate: 1000 Hz

Paradigm

Infants watched a series of engaging and relaxing videos to facilitate recording of spontaneous EEG activity. The dataset was collected to assess the test-retest reliability of EEG microstate metrics in infants. The single aggregated file contains data from 48 infants with recording-boundary markers; no active task was required.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004635

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
bgin	10	long	raw	Beginning of a recording segment
TRSP	10	long	raw	Transition / segment boundary marker

> Event Type Description:
> - `short`: short stimulus onset marker (presentation duration <2 s), for `epoch_by_event_hdf5`
> - `long`: long-term status flag (retention period is usually >=2 s), used for `epoch_by_long_event_hdf5`
> - `rest`: Rest block tag, used for `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
> - `admin`: system/boundary marker, not used for epoch

Tasks

Primary Task 1: Publisher-defined BIDS task: Resting

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004635 DOI: https://doi.org/10.1038/35081509

Normal Task 1: Long-term classification of paragraph tags (binary)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Only 10 events of each type - very limited for supervised classification. Primary scientific use is resting-state microstate analysis. Single aggregated file covers all 48 infants.

Event	y	Meaning
`bgin`	0	Recording segment start
`TRSP`	1	Transition segment marker
## Data Quality Notes		

- Single file aggregating 48 infants - individual subject effects not separable.
- Only 10 events of each type; insufficient for robust supervised classification.

References

- Reference: `Gaffrey Lab Infant EEG Microstates Reliability`

255. openneuro_ds004902 - Resting-State EEG Dataset for Sleep Deprivation

Dataset: openneuro_ds004902 | Year: 2023 | URL: https://openneuro.org/datasets/ds004902
Category: Biological State | Subjects: 71 | Files (Completed): 218 | Channels: 61 | Sampling Rate: 500 Hz

Paradigm

Resting-state EEG recordings with eyes open and eyes closed were conducted under two conditions: normal sleep and 24-hour sleep deprivation. The study investigates how sleep loss modulates spontaneous brain activity. Subjects participated in two sessions (normal sleep vs sleep-deprived). Files are split by condition (eyesopen/eyesclosed) with 5-minute continuous blocks. Event marker S 33 (60 total) appears as a resting-state session marker in a subset of files; all other S-codes are rare system markers.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004902

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
S 33	60	rest	raw	Resting-state session marker (BrainVision)
S 45	7	admin	raw	Rare system marker (exclude)
S 44	7	admin	raw	Rare system marker (exclude)
S 55	7	admin	raw	Rare system marker (exclude)
S119	7	admin	raw	Rare system marker (exclude)
S 66	7	admin	raw	Rare system marker (exclude)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: S 33, S 45, S 44, S 55, S119, S 66
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://openneuro.org/datasets/ds004902 DOI: https://doi.org/10.18112/openneuro.ds004902.v1.0.8

Primary Task 2: Publisher-defined BIDS task: Eyesclosed

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004902 DOI: https://doi.org/10.18112/openneuro.ds004902.v1.0.8

Primary Task 3: Publisher-defined BIDS task: Eyesopen

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004902 DOI: https://doi.org/10.18112/openneuro.ds004902.v1.0.8

Normal Task 1: Sleep Deprivation Resting-State Segmentation (segmentation)

- Task Type: regression
- Epoch Method: `segmentation`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `Annotation`
- Target Definition: None
- Notes: Majority of files have no event markers - purely continuous resting-state. Use filename-derived or participants.tsv condition labels (eyesopen/eyesclosed x normal/deprived) for downstream classification. S 44/45/55/66/119 are rare admin system markers - exclude.

Data Quality Notes

- Most files have no event markers; condition derived from filename (eyesopen/eyesclosed).
- Session condition (normal sleep / sleep deprivation) in participants.tsv.
- S 44/45/55/66/119 are rare admin BrainVision system markers - exclude.

References

- Reference: `Xiang, C., Fan, X., Bai, D. et al. A resting-state EEG dataset for sleep deprivation. Sci Data 11, 427 (2024).`

256. openneuro_ds005178 - Ear-EEG Sleep Monitoring 2023 (EESM23)

Dataset: `openneuro_ds005178` | Year: 2024 | URL: https://openneuro.org/datasets/ds005178
Category: Biological State | Subjects: 10 | Files (Completed): 159 | Channels: 5 | Sampling Rate: 250 Hz

Paradigm

Naturalistic nightly sleep monitoring using ear-EEG (in-ear electrodes) and polysomnography (PSG) in an ecological home environment where participants self-applied the recording equipment. The study investigates the feasibility of home-based sleep staging using miniaturized ear-EEG compared to gold-standard PSG. The `trigger` event marks synchronization pulses between the ear-EEG and PSG systems.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005178

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`trigger`	175	long	raw	Synchronization trigger between ear-EEG and PSG

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `trigger`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Sleep stage classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Sleep stage labels (W/N1/N2/N3/REM; mapping dataset-specific)

- Evidence: Dataset and references explicitly center on PSG/EEG sleep scoring. Source: https://openneuro.org/datasets/ds005178 DOI: https://doi.org/10.3389/fnins.2023.987578

Normal Task 1: Sleep Monitoring Segmentation (segmentation)

- Task Type: classification
- Epoch Method: `segmentation`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `stim`
- Target Definition: None
- Notes: Only synchronization triggers present - no sleep stage labels in events.tsv. Sleep stage annotations from PSG should be used as external labels for downstream classification. Only 5 EEG channels (ear electrodes).

Data Quality Notes

- Only 5 channels (ear-EEG) - very limited spatial resolution.
- No sleep stage labels in events.tsv; PSG annotations needed for staging.
- Home-recorded data - subject-specific motion and environmental artifacts expected.

References

- Reference: `Ear-EEG Sleep Monitoring 2023 (EESM23)`

257. openneuro_ds005185 - Ear-EEG Sleep Monitoring 2019 (EESM19)

Dataset: `openneuro_ds005185` | Year: 2024 | URL: https://openneuro.org/datasets/ds005185
Category: Biological State | Subjects: 20 | Files (Completed): 516 | Channels: 25 | Sampling Rate: 500 Hz

Paradigm

Naturalistic multi-night sleep monitoring using ear-EEG and polysomnography (PSG) in a home environment collected in 2019. Participants self-applied in-ear EEG electrodes over multiple nights for sleep staging and feasibility assessment. Event markers are Danish-language protocol annotations (lights out, going to bed, waking up), synchronization pulses, and calibration periods. The dominant event is `trigger` (30,726 total) - a PSG synchronization pulse. Sleep stage labels are derived from PSG annotations rather than EEG event markers.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005185

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`trigger`	30726	admin	raw	Synchronization trigger between ear-EEG and PSG (exclude)
`Lights Out`	94	rest	raw	Lights out - sleep onset marker
`Gik i seng`	80	rest	raw	"Went to bed" (Danish)
`Biocalibrations`	79	admin	raw	Biocalibration period (exclude)
`Sync`	77	admin	raw	Synchronization marker (exclude)
`Start af maling`	75	admin	raw	"Start of recording" (Danish, exclude)
`Stod op`	70	rest	raw	"Got up" (Danish) - wake marker
`Biocalibrations start`	11	admin	raw	Biocalibration start (exclude)
`Vagen / vagen`	13	rest	raw	"Awake" (Danish)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `trigger`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Sleep stage classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Sleep stage labels (W/N1/N2/N3/REM; mapping dataset-specific)
- Evidence: Dataset and references explicitly center on PSG/EEG sleep scoring. Source: https://openneuro.org/datasets/ds005185 DOI: https://doi.org/10.1038/s41598-019-53115-3

Primary Task 2: Publisher-defined BIDS task: ASSR

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005185 DOI: https://doi.org/10.1038/s41598-019-53115-3

Primary Task 3: Publisher-defined BIDS task: Comfort

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005185 DOI: https://doi.org/10.1038/s41598-019-53115-3

Normal Task 1: Sleep Monitoring Segmentation (segmentation)

- Task Type: classification
- Epoch Method: `segmentation`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5
- Label Route: `stim`
- Target Definition: None
- Notes: All event markers are Danish-language protocol annotations or sync triggers - not suitable as EEG classification targets. Sleep stage labels (N1/N2/N3/REM/Wake) should be obtained from PSG annotation files. `trigger` (30,726) is a high-frequency sync pulse - exclude.

Data Quality Notes

- `trigger` (30,726) is a sync pulse - exclude from classification.
- All event markers are protocol annotations, not neural response labels.
- 25-channel ear-EEG with limited spatial resolution.
- PSG reference annotations required for sleep staging labels.

References

- Reference: `Ear-EEG Sleep Monitoring 2019 (EESM19)`

258. openneuro_ds005385 - Resting-State EEG Before and After Cognitive Activity Across the Adult Lifespan (5-Year Follow-Up)

Dataset: `openneuro_ds005385` | Year: 2024 | URL: https://openneuro.org/datasets/ds005385
Category: Biological State | Subjects: 608 | Files (Completed): 3264 | Channels: 65 | Sampling Rate: 1000 Hz

Paradigm

Resting-state EEG was recorded with eyes open and eyes closed before and after a two-hour block of cognitive tasks (working memory, attention, processing speed) across a lifespan cohort of adults. A 5-year longitudinal follow-up is included. BrainVision S-codes (S1-S207+) encode the specific resting-state condition (pre/post x eyes open/closed) and session number.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005385

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`boundary`	3375	admin	raw	BrainVision segment boundary (exclude)
`S 4-S 7`	~207 each	long	raw	Resting-state session markers (BrainVision S-codes)
`S 11-S 19`	~204-205 each	long	raw	Resting-state condition codes
`S 14-S 16`	68 each	long	raw	Resting-state condition (higher count subset)
`S196-S207`	~205-207 each	long	raw	Session/condition index codes

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `S 4`, `S 7`, `S 11`, `S 19`, `S 14`, `S 16`, `S196`, `S207`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://doi.org/10.2196/32352

Normal Task 1: Resting Condition Segmentation (long event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `boundary` (3375) is admin - exclude. S-codes encode resting condition and session; full decode from README/events.tsv required. 3264 files = 608 subjects x multiple sessions.

Event	y	Meaning
`S 4`	0	Resting condition S4
`S 5`	1	Resting condition S5
`S 6`	2	Resting condition S6
`S 7`	3	Resting condition S7
## Data Quality Notes		

- boundary markers (3375) are admin - exclude.
- Full S-code decode needed from README to identify pre/post and eyes-open/closed conditions.
- Large dataset (3264 files, 608 subjects); high variability across sessions and age groups.

References

- Reference: `Gajewski et al., 2022, doi: 10.2196/32352`

259. openneuro_ds005420 - Resting State EEG with Closed Eyes and Open Eyes in Females from 60 to 80 Years Old

Dataset: openneuro_ds005420 | Year: 2024 | URL: https://openneuro.org/datasets/ds005420
Category: Biological State | Subjects: 72 | Files (Completed): 72
Channels: 20 | Sampling Rate: 500 Hz

Paradigm

Spontaneous resting-state EEG was recorded in a cohort of females aged 60-80 years during alternating eyes-open and eyes-closed conditions. The dataset investigates age-related changes in spontaneous brain activity in older women. No event markers were included in events.tsv; the EEG is stored as continuous recordings. Eyes-open vs. eyes-closed condition can be inferred from the file naming or participants.tsv.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005420

Event Structure

No event markers detected (no_events). This dataset contains continuous resting-state EEG recordings without trial-level annotations.

> Event Type Description:
> - short: short stimulus onset marker (presentation duration <2 s), for epoch_by_event_hdf5
> - long: long-term status flag (retention period is usually >=2 s), used for epoch_by_long_event_hdf5
> - rest: Rest block tag, used for epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
> - admin: system/boundary marker, not used for epoch

Event ID	Count (total)	Type	Meta Level	Meaning
no_events	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Publisher-defined BIDS task: Oa

- Task Type: classification/segmentation
- Epoch Method: epoch_by_long_event_hdf5 or epoch_by_segmentation_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification

- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005420 DOI: https://doi.org/10.18112/openneuro.ds005420.v1.0.0

Primary Task 2: Publisher-defined BIDS task: Oc

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005420 DOI: https://doi.org/10.18112/openneuro.ds005420.v1.0.0

Normal Task 1: Resting-State Segmentation (segmentation)

- Task Type: segmentation
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5 s
- Label Route: `Annotation`
- Target Definition: N/A (null(no events; use file-level condition label for eyes-open/closed from filename or participants.tsv))
- Notes: No event markers. Only 20 EEG channels. Female-only sample aged 60-80. Eyes-open/closed condition may be in filename.

Data Quality Notes

- No event markers - purely continuous resting-state recordings.
- 20-channel montage; limited spatial coverage.
- Female-only cohort aged 60-80; demographic info in participants.tsv.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to segmentation.

References

- Reference: `EEG-BIDS, an extension to the brain imaging data structure for electroencephalography`

260. openneuro_ds006269 - Tethered EEG Recordings in Syngap1 Rats

Dataset: `openneuro_ds006269` | Year: 2025 | URL: https://openneuro.org/datasets/ds006269
Category: Biological State | Subjects: 40 | Files (Completed): 40 | Channels: 33 | Sampling Rate: 1000 Hz

Paradigm

Continuous 6-hour tethered EEG recordings were collected from wildtype and Syngap1 mutant rats to monitor spontaneous brain activity and examine circadian-specific neural states. The Syngap1 gene encodes a synaptic GTPase-activating protein and its haploinsufficiency is a model of intellectual disability. The dataset examines spontaneous EEG patterns (sleep/wake states, oscillations) across genotypes.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006269

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`unknown`	40	admin	raw	Unknown system marker - not usable for classification

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://doi.org/10.1016/j.celrep.2024.114733

Normal Task 1: Continuous Segmentation (long_event)

- Task Type: regression
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5 s, target_events = see Target Definition
- Label Route: `Annotation`

- Target Definition: N/A (no usable event markers; target_events: null)
- Notes: unknown is an uninformative system marker. Use subject-level metadata (wildtype vs. Syngap1 mutant genotype) from participants.tsv as classification labels.

Data Quality Notes

- Only unknown events present - no meaningful trial-level annotation.
- Labels must be derived from external genotype metadata (participants.tsv).
- Animal (rat) EEG data; electrode placement and artifact characteristics differ from human EEG.

References

- Paper: Key roles of C2/GAP domains in SYNGAP1-related pathophysiology (DOI: 10.1016/j.celrep.2024.114733)

261. openneuro_ds006525 - Resting EEG with Structural MRI

Dataset: openneuro_ds006525 | Year: 2025 | URL: https://openneuro.org/datasets/ds006525
Category: Biological State | Subjects: 34 | Files (Completed): 34 | Channels: 128 | Sampling Rate: 250 Hz

Paradigm

Spontaneous brain activity was recorded during resting-state EEG, supplemented by structural MRI scans. The dataset captures baseline neural dynamics in the absence of any task. Event markers include resting-state block onset (rsts), offset (rstf), and a session-begin marker (bgin), enabling segmentation of clean resting periods.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006525

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
bgin	20400	long	raw	Session begin marker
rsts	20400	rest	raw	Resting-state block start
rstf	34	rest	raw	Resting-state block finish/end
NRST	34	admin	raw	Non-resting state marker
DIN	2	admin	raw	Digital input trigger

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: epoch_by_segmentation_hdf5 or epoch_by_long_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: Annotation
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://openneuro.org/datasets/ds006525 DOI: https://doi.org/10.3389/fninf.2021.770608

Normal Task 1: Resting-State Segmentation (long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `rsts` and `rstf` mark the boundaries of resting blocks; segment within these boundaries. `NRST` may indicate periods outside resting state that should be excluded.

Event	y	Meaning
`bgin`	0	Session begin
`rsts`	1	Resting-state block start
`rstf`	2	Resting-state block end
`NRST`	3	Non-resting state period
`DIN`	4	Digital input trigger
## Data Quality Notes		

- High channel count (128) with 250 Hz sampling rate; EGI/Geodesic system likely.
- `NRST` may indicate periods outside resting state that should be excluded from analysis.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to segmentation.

References

- Reference: `Resting EEG`

262. openneuro_ds006695 - Validation of Sleep Staging with Forehead EEG Patch

Dataset: openneuro_ds006695 | Year: 2025 | URL: https://openneuro.org/datasets/ds006695
Category: Biological State | Subjects: 19 | Files (Completed): 19 | Channels: 3 | Sampling Rate: 500 Hz

Paradigm

This dataset validates a spectral sleep staging approach using a three-electrode forehead EEG patch against manual scoring from standard polysomnography (PSG). Overnight sleep recordings were collected using a minimally intrusive forehead device, and sleep stages (Wake, N1, N2, N3, REM) were scored both manually and algorithmically. The study examines whether simplified forehead EEG can reliably reproduce standard PSG hypnogram classifications.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006695

Event Structure

No event markers detected (no_events). This dataset contains continuous overnight EEG recordings without trial-level annotations.

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Event ID	Count (total)	Type	Meta Level	Meaning
no_events	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Sleep stage classification

- Task Type: classification
- Epoch Method: epoch_by_long_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Sleep stage labels (W/N1/N2/N3/REM; mapping dataset-specific)
- Evidence: Dataset and references explicitly center on PSG/EEG sleep scoring. Source: https://doi.org/10.3389/frsle.2024.1349537

Normal Task 1: Continuous Segmentation (segmentation)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5 s
- Label Route: `Annotation`
- Target Definition: N/A (no event markers; sleep stage labels from external PSG scoring)
- Notes: No EEG event markers available. Sleep stage labels (Wake/N1/N2/N3/REM) must be derived from PSG hypnogram annotations stored as separate scoring files. Very few channels (3); limited spatial resolution for advanced decoding.

Data Quality Notes

- Only 3 channels (forehead placement); very limited spatial information.
- Overnight recordings are long (hours); memory-efficient processing needed.
- Sleep stage labels require alignment with PSG hypnogram files.

References

- Paper: `Validation of spectral sleep scoring with polysomnography using forehead EEG device` (DOI: 10.3389/frsle.2024.1349537)

263. openneuro_ds006801 - Resting-State EEG Before and After Different Study Methods

Dataset: `openneuro_ds006801` | Year: 2025 | URL: https://openneuro.org/datasets/ds006801
Category: Biological State | Subjects: 21 | Files (Completed): 42 | Channels: 31 | Sampling Rate: 500 Hz

Paradigm

Resting-state EEG was recorded before and after an educational intervention in which participants engaged in active retrieval practice, passive review, or a control condition. The design examines how different study strategies affect resting-state neural oscillations. Each participant completed eyes-open and eyes-closed resting blocks. The 42 files correspond to pre- and post-intervention recordings for 21 subjects.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006801

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`New Segment/LostSamples`	1	admin	raw	Segment discontinuity marker

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://openneuro.org/datasets/ds006801 DOI: https://doi.org/10.18112/openneuro.ds006801.v1.0.0

Normal Task 1: Resting-State Segmentation (long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: N/A (no trial events; target_events: null)

- Notes: `New Segment/LostSamples` is an admin marker indicating signal discontinuity; never use as classification target. Labels for pre/post intervention and study condition must be derived from participants.tsv metadata.

Data Quality Notes

- `New Segment/LostSamples` is a signal discontinuity marker - exclude from all analyses.
- 42 files = 21 subjects x 2 sessions (pre/post intervention).
- Eyes-open vs eyes-closed blocks may be distinguished by duration or metadata.

References

- Reference: `The RECAP-EEG: Retrieval with Feedback and Cognitive Adaptation EEG Dataset`

264. openneuro_ds006921 - High-Density Resting-State EEG of Phantom Limb Pain and Controls

Dataset: openneuro_ds006921 | Year: 2025 | URL: https://openneuro.org/datasets/ds006921
Category: Biological State | Subjects: 152 | Files (Completed): 152 | Channels: 128 | Sampling Rate: 2400 Hz

Paradigm

High-density resting-state EEG recordings were collected from three groups: amputees with phantom limb pain (PLP), amputees without phantom limb pain, and healthy controls. Recordings were made during eyes-open and eyes-closed conditions. The dataset enables investigation of neural correlates associated with phantom limb pain, cortical reorganization following amputation, and resting-state oscillatory differences across groups.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds006921

Event Structure

No event markers detected (`no_events`). This dataset contains continuous resting-state EEG recordings without trial-level annotations.

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Event ID	Count (total)	Type	Meta Level	Meaning
`no_events`	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://openneuro.org/datasets/ds006921 DOI: https://doi.org/10.18112/openneuro.ds006921.v1.1.1

Primary Task 2: Publisher-defined BIDS task: EYESOPEN

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006921 DOI: https://doi.org/10.18112/openneuro.ds006921.v1.1.1

Primary Task 3: Publisher-defined BIDS task: EYESCLOSED

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds006921 DOI: https://doi.org/10.18112/openneuro.ds006921.v1.1.1

Normal Task 1: Resting-State Segmentation (segmentation)

- Task Type: segmentation
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5 s
- Label Route: `Annotation`
- Target Definition: N/A (no event markers; group labels from participants.tsv)
- Notes: No trial-level events. Group labels (PLP amputee / non-PLP amputee / healthy control) must be derived from participants.tsv metadata. Very high sampling rate (2400 Hz); downsample before analysis.

Data Quality Notes

- Very high sampling rate (2400 Hz); downsample to 500-1000 Hz for most analyses.
- 152 files may include multiple sessions per subject; verify session structure.
- High-density 128-channel system (likely EGI/Geodesic); non-standard montage.

References

- Reference: `High Density Resting State EEG of Phantom Limb Pain and Controls`

265. openneuro_ds007020 - EEG Mortality Dataset in Parkinson's Disease

Dataset: `openneuro_ds007020` | Year: 2025 | URL: https://openneuro.org/datasets/ds007020
Category: Biological State | Subjects: 94 | Files (Completed): 94 | Channels: 63 | Sampling Rate: 500 Hz

Paradigm

Resting-state EEG recordings (eyes open) were collected from Parkinson's disease (PD) patients and healthy controls to evaluate EEG-based biomarkers for mortality classification. The dataset enables investigation of spectral and connectivity biomarkers that predict mortality risk in PD. The sole event marker (`New Segment/`) indicates a recording segment boundary and carries no experimental meaning.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds007020

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`New Segment/`	94	admin	raw	Recording segment boundary marker

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://openneuro.org/datasets/ds007020 DOI: https://doi.org/10.1016/j.prdoa.2025.100409

Normal Task 1: Resting-State Segmentation (long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: N/A (no trial events; target_events: null)

- Notes: `New Segment/` is a BrainVision segment boundary marker and must never be used as a classification target. Group labels (PD patient / healthy control, mortality outcome) must be derived from clinical metadata in participants.tsv.

Data Quality Notes

- `New Segment/` is a BrainVision format boundary marker; exclude from all analyses.
- Labels for mortality prediction must be derived from clinical metadata in participants.tsv.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to segmentation.

References

- Reference: `EEG Mortality Dataset in Parkinson's Disease`

266. openneuro_ds007176 - Longitudinal EEG Test-Retest Reliability in Healthy Individuals

Dataset: `openneuro_ds007176` | Year: 2026 | URL: https://openneuro.org/datasets/ds007176
Category: Biological State | Subjects: 43 | Files (Completed): 300 | Channels: 60 | Sampling Rate: 1000 Hz

Paradigm

Longitudinal resting-state EEG recordings collected over four sessions spanning two years to evaluate test-retest reliability of quantitative EEG measures. Recordings are continuous resting-state without structured task events. The dataset enables assessment of EEG biomarker stability across sessions and time points.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds007176

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`0`	2	admin	raw	Null trigger code - no experimental meaning

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: CE

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1016/j.bspc.2026.109484

Primary Task 2: Publisher-defined BIDS task: OE

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://doi.org/10.1016/j.bspc.2026.109484

Normal Task 1: Resting-State Segmentation (long_event)

- Task Type: segmentation
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, overlap = 0.5 s, target_events = see Target Definition
- Label Route: `stim`
- Target Definition: N/A (no trial events; target_events: null)
- Notes: Only event code `0` present (2 total); this is a null trigger with no experimental meaning. Resting-state data; use segmentation across full recording. Session/time-point labels available from participants.tsv for longitudinal analysis.

Data Quality Notes

- No meaningful event markers; purely continuous resting-state EEG.
- 43 subjects x ~7 sessions/subject = 300 files; multi-session longitudinal design.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to segmentation.

References

- Paper: `Longitudinal test-retest reliability of quantitative EEG in healthy individuals using an automated preprocessing approach` (DOI: 10.1016/j.bspc.2026.109484)

267. openneuro_ds007181 - Structural MRI, Resting-State fMRI, and PSG/EEG Dataset of Zoster-Associated Neuralgia

Dataset: `openneuro_ds007181` | Year: 2026 | URL: https://openneuro.org/datasets/ds007181
Category: Biological State | Subjects: 59 | Files (Completed): 59 | Channels: 24 | Sampling Rate: 1024 Hz

Paradigm

Resting-state EEG (part of a PSG recording) was collected from patients with zoster-associated neuralgia and healthy controls, alongside structural MRI and resting-state fMRI. Manual sleep staging is available from PSG annotations. The dataset enables investigation of brain activity and sleep architecture differences between healthy controls and patients with herpes zoster-associated chronic pain.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds007181

Event Structure

No event markers detected (`no_events`). This dataset contains continuous PSG/EEG recordings without trial-level annotations.

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Event ID	Count (total)	Type	Meta Level	Meaning
`no_events`	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.

Tasks

Primary Task 1: Sleep stage classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Sleep stage labels (W/N1/N2/N3/REM; mapping dataset-specific)
- Evidence: Dataset and references explicitly center on PSG/EEG sleep scoring. Source: https://openneuro.org/datasets/ds007181 DOI: https://doi.org/10.18112/openneuro.ds007181.v1.0.1

Primary Task 2: Publisher-defined BIDS task: Rest

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds007181 DOI: https://doi.org/10.18112/openneuro.ds007181.v1.0.1

Normal Task 1: Continuous Segmentation (segmentation)

- Task Type: regression
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = 2.0 s, overlap = 0.5 s
- Label Route: `Annotation`
- Target Definition: N/A (no event markers; sleep stage labels from PSG scoring files)
- Notes: No EEG event markers available. Sleep stage labels (Wake/N1/N2/N3/REM) must be derived from PSG hypnogram annotations if present. Group labels (zoster neuralgia / healthy control) from participants.tsv.

Data Quality Notes

- No event markers present; continuous-only processing.
- PSG-derived sleep stage labels require alignment with EEG data if available.
- 24-channel PSG EEG system; non-standard montage compared to research-grade EEG.

References

- Reference: `Structural MRI, Resting-state fMRI, and PSG/EEG Dataset of Zoster-associated Neuralgia`

268. other_migrainedb - Ultra High-Density EEG - Interictal Migraine and Controls

Dataset: `other_migrainedb` | Year: 2020 | URL: https://kilthub.cmu.edu/articles/dataset/Ultra_high-density_EEG_recording_of_interictal_migraine_and_controls_sensory_and_rest/12636731
Category: Biological State | Subjects: 39 | Files (Completed): 117 | Channels: 144 | Sampling Rate: 512 Hz

Paradigm

Thirty-nine subjects (18 interictal migraine patients: M1-M18; 21 healthy controls: C1-C21) underwent high-density EEG recording (BioSemi ActiveTwo, 144 channels, 512 Hz) in three task conditions (Chiang et al., 2020): (1) SSVEP - steady-state visual evoked potential, flickering stimuli at 4 Hz and 6 Hz; (2) SSAEP - steady-state auditory evoked potential, tone sequences at 4 Hz and 6 Hz; (3) resting state. The dataset enables comparison of sensory processing in migraine patients vs. healthy controls in the interictal (between-attack) period.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://kilthub.cmu.edu/articles/dataset/Ultra_high-density_EEG_recording_of_interictal_migraine_and_controls_sensory_and_rest/12636731

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`4Hz vision stimulation start`	varies	short	raw	SSVEP 4 Hz flicker onset
`6Hz vision stimulation start`	varies	short	raw	SSVEP 6 Hz flicker onset
`4Hz vision feedback end`	varies	admin	raw	SSVEP 4 Hz block end marker
`6Hz vision feedback end`	varies	admin	raw	SSVEP 6 Hz block end marker
`4Hz auditory stimulation start`	varies	short	raw	SSAEP 4 Hz tone onset
`6Hz auditory stimulation start`	varies	short	raw	SSAEP 6 Hz tone onset
`4Hz auditory feedback end`	varies	admin	raw	SSAEP 4 Hz block end marker
`6Hz auditory feedback end`	varies	admin	raw	SSAEP 6 Hz block end marker
`resting state block start`	varies	rest	raw	Resting state block onset

Event ID	Count (total)	Type	Meta Level	Meaning
`resting state block end`	varies	admin	raw	Resting state block end marker

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: `4Hz vision stimulation start`, `6Hz vision stimulation start`, `4Hz auditory stimulation start`, `6Hz auditory stimulation start`
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: SSVEP target/frequency decoding

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification] | tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `stim` or `Annotation`
- Target Definition: Stimulus frequency or target index
- Evidence: SSVEP paradigm is explicitly stated in dataset metadata/reference. Source: https://kilthub.cmu.edu/articles/dataset/12636731 DOI: https://doi.org/10.21236/ada393961

Normal Task 1: SSVEP Frequency Classification - 4 Hz vs. 6 Hz (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 2.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`4Hz vision stimulation start`	0	4 Hz flicker stimulus
`6Hz vision stimulation start`	1	6 Hz flicker stimulus

Normal Task 2: Migraine Patient vs. Control - Resting State (epoch_by_segmentation)

- Task Type: segmentation
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: length = 5.0 s, overlap = 2.5 s (within `resting state block start` / end boundaries)
- Label Route: `Annotation`
- Target Definition: N/A (group label from subject ID: M-series = migraine, C-series = healthy)
- Notes: Group labels (migraine vs. control) are encoded in the subject ID (M/C prefix in filename). Apply the group label post-hoc after segmentation.

Data Quality Notes

- Group labels must be derived from the subject ID prefix (M for migraine, C for control).

- Age range: 19-54 years; sex: mixed male/female.
- High channel count (144); spatial filtering / source localization may be useful.
- Sensory task and resting state recordings provide complementary views of migraine-related cortical changes.

References

- Reference: Chiang AKI et al. (2020). Ultra high-density EEG recording of interictal migraine and controls sensory and rest. KiltHub CMU. https://kilthub.cmu.edu/articles/dataset/12636731

269. physionet_capslpdb - CAP Sleep Database

Dataset: `physionet_capslpdb` | Year: 2014 | URL: https://physionet.org/content/capslpdb/1.0.0/
Category: Biological State | Subjects: 108 | Files (Completed): 108 | Channels: 5-36 (variable) | Sampling Rate: 100-512 Hz (variable)

Paradigm

One hundred and eight patients from the Sleep Disorders Center, Ospedale Civile di Parma, Italy, underwent overnight polysomnographic (PSG) recording with detailed expert annotations (Terzano et al., 2002). The cohort includes 16 healthy controls and 92 patients with various sleep disorders: nocturnal frontal lobe epilepsy (NFLE, n=40), REM sleep behavior disorder (RBD, n=22), periodic limb movements (PLM, n=10), insomnia (n=9), narcolepsy (n=5), sleep-disordered breathing (SDB, n=4), and bruxism (n=2). Beyond standard sleep staging (Rechtschaffen & Kales), annotations include Cyclic Alternating Pattern (CAP) subtypes: phase A1 (high-amplitude synchronized EEG activity), A2 (mixed), and A3 (desynchronized EEG). Channel count and sampling rate vary across subjects.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://physionet.org/content/capslpdb/1.0.0/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`SLEEP-S0`	19495	long	raw	Wake stage (S0 = W)
`SLEEP-S1`	4642	long	raw	NREM Stage 1 - light sleep
`SLEEP-S2`	39192	long	raw	NREM Stage 2 - sleep spindles/K-complexes
`SLEEP-S3`	11953	long	raw	NREM Stage 3 - SWS
`SLEEP-S4`	13780	long	raw	NREM Stage 4 - deep SWS
`SLEEP-REM`	18935	long	raw	REM sleep
`SLEEP-MT`	11	admin	raw	Movement time (artifact/transition)
`MCAP-A1`	26788	short	raw	CAP phase A1 onset (synchronized EEG)
`MCAP-A2`	10519	short	raw	CAP phase A2 onset (mixed pattern)
`MCAP-A3`	14324	short	raw	CAP phase A3 onset (desynchronized EEG)

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Sleep stage classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Sleep stage labels (W/N1/N2/N3/REM; mapping dataset-specific)
- Evidence: Dataset and references explicitly center on PSG/EEG sleep scoring. Source: https://physionet.org/content/capslpdb/1.0.0/ DOI: https://doi.org/10.13026/C2VC79

Normal Task 1: Sleep Stage Classification (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 30.0 s (one R&K epoch), overlap = 0.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Exclude `SLEEP-MT` epochs. R&K 30-second epoch boundaries; set tmax = 30.0 s to match.

Event	y	Meaning
`SLEEP-S0`	0	Wake
`SLEEP-S1`	1	NREM Stage 1
`SLEEP-S2`	2	NREM Stage 2
`SLEEP-S3`	3	NREM Stage 3
`SLEEP-S4`	4	NREM Stage 4
`SLEEP-REM`	5	REM

Normal Task 2: CAP Phase A Subtype Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 3.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`MCAP-A1`	0	CAP Phase A1 (synchronized)
`MCAP-A2`	1	CAP Phase A2 (mixed)
`MCAP-A3`	2	CAP Phase A3 (desynchronized)
## Data Quality Notes		

- Channel count and sampling rate vary substantially across subjects (5-36 channels, 100-512 Hz); normalize before cross-subject analysis.
- Mixed clinical population: NFLE, RBD, PLM, insomnia, narcolepsy, SDB, bruxism, and healthy controls; group labels are encoded in the subject metadata.

- CAP annotations are specialized biomarkers of sleep instability; fewer publications use them compared to standard staging.

References

- Reference: Terzano MG et al. (2002). Atlas, rules, and recording techniques for the scoring of cyclic alternating pattern (CAP) in human sleep. Sleep Medicine, 3(2), 187-199. Goldberger AL et al. (2000). PhysioBank, PhysioToolkit, and PhysioNet. https://physionet.org/content/capslpdb/1.0.0/

270. physionet_chbmit - CHB-MIT Scalp EEG Database

Dataset: `physionet_chbmit` | Year: 2010 | URL: https://physionet.org/content/chbmit/1.0.0/
Category: Biological State | Subjects: 22 | Files (Completed): 686 | Channels: 23 | Sampling Rate: 256 Hz

Paradigm

Twenty-two pediatric patients (5 males aged 3-22; 17 females aged 1.5-19) with intractable seizures were monitored at Children's Hospital Boston following withdrawal of anti-seizure medication to evaluate surgical candidacy (Shoeb & Guttag, 2010). Long-term continuous EEG was recorded from 23 scalp channels (bipolar montage following the 10-20 system) at 256 Hz with 16-bit resolution. The dataset contains 686 EEG files and 182 seizure events in total. Seizure onset and offset times are documented in per-subject summary text files (`chbNN-summary.txt`); the kernel parses these to create `seizure` annotations spanning each ictal period.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://physionet.org/content/chbmit/1.0.0/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`seizure`	182	long	raw	Seizure period (onset to offset, variable duration)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Files without seizures have no annotations; these ictal-free recordings serve as the negative (interictal) class.

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Epileptic seizure detection (ictal vs non-ictal)

- Task Type: classification/detection
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification

- Label Route: `Annotation`
- Target Definition: Seizure interval labels from annotation files (ictal) vs background/interictal segments.
- Evidence: CHB-MIT is widely used for seizure detection benchmarking with annotated seizure intervals.
Source: https://physionet.org/content/chbmit/1.0.0/ DOI: https://doi.org/10.13026/C2K01R

Normal Task 1: Seizure Detection - Ictal vs. Interictal (epoch_by_long_event + custom)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5` (for ictal files) + `epoch_by_segmentation_hdf5` (for interictal files)
- Epoch Parameters: For seizure epochs: tmin = 0.0 s (annotation onset), use full duration; For interictal: sliding window 5.0 s, overlap = 2.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Files with no seizure annotations are entirely interictal; use `epoch_by_segmentation_hdf5` for those. Files with `seizure` annotations contain both ictal and pre/post-ictal segments; consider a buffer of 5-10 s before/after seizure onset as pre-ictal/post-ictal and exclude from clean interictal class. Severe class imbalance: seizure epochs (~182 events) vs. many hours of interictal EEG.

Event	y	Meaning
`seizure`	1	Ictal activity
(no annotation)	0	Interictal (seizure-free) baseline

Normal Task 2: Patient-Specific Seizure Detection (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event`
- Epoch Parameters: Needs verification
- Label Route: `Annotation`
- Target Definition: Needs verification.
- Notes: Train per patient; subjects chb17 appears in three sub-cases (chb17a, chb17b, chb17c) and should be treated as a single subject.

Data Quality Notes

- Severe class imbalance: the majority of recordings are seizure-free; balance by undersampling interictal or using cost-sensitive learning.
- Channel count varies: most files have 23 channels; some cases include 24 or 26 channels (extra ECG or vagal nerve stimulus channels); exclude non-EEG channels.
- Patient-specific model training is recommended; cross-patient generalization is difficult.
- Subject chb24 has unknown age and sex.
- Age range: 1.5-22 years (pediatric); EEG morphology differs significantly from adult norms.

References

- Reference: Shoeb AH, Guttag JV (2010). Application of machine learning to epileptic seizure detection. In Proceedings of the 27th ICML. Goldberger AL et al. (2000). PhysioBank, PhysioToolkit, and PhysioNet. Circulation, 101(23), e215-e220. https://physionet.org/content/chbmit/1.0.0/

271. physionet_hmcsleepstaging - HMC Sleep Staging Database

Dataset: `physionet_hmcsleepstaging` | Year: 2022 | URL: https://physionet.org/content/hmc-sleep-staging/1.1/
Category: Biological State | Subjects: 77 | Files (Completed): 77 | Channels: 8 | Sampling Rate: 256 Hz

Paradigm

Seventy-seven overnight polysomnographic recordings from the Haaglanden Medisch Centrum (HMC) Sleep Center, Netherlands, were collected and annotated using the AASM (American Academy of Sleep Medicine) scoring rules. EEG was recorded from 4 bipolar derivations (F4-M1, C4-M1, O2-M1, C3-M2), supplemented by chin EMG, two EOG channels (E1-M2, E2-M2), and ECG, all at 256 Hz. Expert sleep technicians scored each 30-second epoch as Wake, N1, N2, N3, or REM. Light-on and light-off events mark the intended sleep period boundaries.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://physionet.org/content/hmc-sleep-staging/1.1/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Sleep stage W`	12217	long	raw	Wake (30-second epoch)
`Sleep stage N1`	8103	long	raw	NREM Stage 1 (AASM)
`Sleep stage N2`	24969	long	raw	NREM Stage 2 (AASM)
`Sleep stage N3`	13243	long	raw	NREM Stage 3 - slow-wave sleep (AASM)
`Sleep stage R (REM)`	10974	long	raw	REM sleep (AASM)
`Lights off`	76	admin	raw	Start of intended sleep period
`Lights on`	76	admin	raw	End of intended sleep period

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Counts are totals across all 77 recordings. Each stage annotation spans exactly 30 seconds.

Tasks

Primary Task 1: Sleep stage classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Sleep stage labels (W/N1/N2/N3/REM; mapping dataset-specific)
- Evidence: Dataset and references explicitly center on PSG/EEG sleep scoring. Source: https://physionet.org/content/hmc-sleep-staging/1.1/ DOI: https://doi.org/10.13026/t79q

Normal Task 1: 5-Class Sleep Stage Classification - AASM (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 30.0 s, overlap = 0.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Exclude `Lights off` and `Lights on` events. Epoch window must match 30 s exactly. Consider restricting to the lights-off-lights-on interval to exclude periods far from sleep onset.

Event	y	Meaning
`Sleep stage W`	0	Wake
`Sleep stage N1`	1	NREM Stage 1
`Sleep stage N2`	2	NREM Stage 2
`Sleep stage N3`	3	NREM Stage 3 / SWS
`Sleep stage R (REM)`	4	REM

Normal Task 2: Wake vs. Sleep Binary Classification (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 30.0 s, overlap = 0.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`Sleep stage W`	0	Wake
`Sleep stage N1`	1	Any sleep stage
`Sleep stage N2`	1	Any sleep stage
`Sleep stage N3`	1	Any sleep stage
`Sleep stage R (REM)`	1	Any sleep stage
## Data Quality Notes		

- AASM scoring (N1/N2/N3/REM/W) as opposed to R&K (S1/S2/S3/S4/REM/W) used in older datasets; not directly comparable.
- ECG channel present; exclude from EEG features.
- Age and sex information are not available in the public metadata.
- N1 is relatively rare; class imbalance between stages is expected.

References

- Reference: Alvarez-Estevez D, Rijsman RM (2022). HMC Sleep Staging Database. PhysioNet. https://physionet.org/content/hmc-sleep-staging/1.1/

272. physionet_sleepedfx - Sleep-EDF Database Expanded

Dataset: `physionet_sleepedfx` | Year: 1992/2013 | URL: https://physionet.org/content/sleep-edfx/1.0.0/
Category: Biological State | Subjects: 58 | Files (Completed): 197 | Channels: 7 | Sampling Rate: 100 Hz

Paradigm

The Sleep-EDF Database Expanded contains whole-night polysomnographic (PSG) sleep recordings with expert-annotated sleep stage hypnograms (Kemp et al., 2000). Two study types are included: Sleep Cassette (SC, 39 subjects, 2 nights each = 78 recordings) and Sleep Treatment (ST, 19 subjects). EEG was recorded from 2 channels (Fpz-Cz and Pz-Oz) along with a horizontal EOG, submental EMG, and event/temperature markers. Sleep stages (W, 1, 2, 3, 4, REM) were scored in 30-second epochs by sleep technicians using Rechtschaffen & Kales criteria. Hypnogram annotations are loaded by the kernel from companion `*Hypnogram.edf` files adjacent to each PSG file.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://physionet.org/content/sleep-edfx/1.0.0/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Sleep stage W`	~24000	long	raw	Wake stage (30-second epoch)
`Sleep stage 1`	~3000	long	raw	NREM Stage 1 - light sleep
`Sleep stage 2`	~40000	long	raw	NREM Stage 2 - sleep spindles/K-complexes
`Sleep stage 3`	~5000	long	raw	NREM Stage 3 - slow-wave sleep (SWS)
`Sleep stage 4`	~3000	long	raw	NREM Stage 4 - deep slow-wave sleep
`Sleep stage R`	~9000	long	raw	REM sleep
`Movement time`	rare	admin	raw	Movement artifact period (exclude)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Counts are approximate totals across all 197 recordings. Each stage annotation spans exactly 30 seconds.

Tasks

Primary Task 1: Sleep stage classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Sleep stage labels (W/N1/N2/N3/REM; mapping dataset-specific)
- Evidence: Dataset and references explicitly center on PSG/EEG sleep scoring. Source: https://physionet.org/content/sleep-edfx/1.0.0/ DOI: https://doi.org/10.13026/C2X676

Normal Task 1: Sleep Stage Classification - 5-Class (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 30.0 s (one full 30-second epoch), overlap = 0.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Exclude `Movement time` epochs. Each annotation spans exactly 30 seconds - match epoch window exactly to annotation duration. Only PSG files (filenames containing `PSG` or `SC`) are processed by the kernel; Hypnogram files return unchanged raw objects.

Event	y	Meaning
`Sleep stage W`	0	Wake
`Sleep stage 1`	1	NREM Stage 1
`Sleep stage 2`	2	NREM Stage 2
`Sleep stage 3`	3	NREM Stage 3
`Sleep stage 4`	4	NREM Stage 4
`Sleep stage R`	5	REM

Normal Task 2: Wake vs. Sleep Binary Classification (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 30.0 s, overlap = 0.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`Sleep stage W`	0	Wake
`Sleep stage 1`	1	Any sleep (stages 1-4 and R)
`Sleep stage 2`	1	Any sleep
`Sleep stage 3`	1	Any sleep
`Sleep stage 4`	1	Any sleep
`Sleep stage R`	1	Any sleep
## Data Quality Notes		

- Only PSG files should be processed; Hypnogram files (matched companion files) are used for annotation only and are returned unchanged by the kernel.

- Class imbalance: Stage 2 is the most frequent stage; Wake also contributes large counts from lights-on periods at start/end of recording.
- Two EEG channels only (Fpz-Cz, Pz-Oz); limited spatial resolution.
- Age range is wide (18-101 years); SC study subjects are healthy adults, ST subjects had sleep disorders.
- SC study: 2 nights per subject; subject IDs encode night number in filename.

References

- Reference: Kemp B, Varri A, Rosa AC, Nielsen KD, Gade J (1992). A simple format for exchange of digitized polygraphic recordings. Electroencephalography and Clinical Neurophysiology, 82(5), 391-393. Goldberger AL et al. (2000). PhysioBank, PhysioToolkit, and PhysioNet. Circulation, 101(23), e215-e220. https://physionet.org/content/sleep-edfx/1.0.0/

273. physionet_ucddb - UCD Sleep Apnea Database

Dataset: physionet_ucddb | Year: 2011 | URL: https://physionet.org/content/ucddb/1.0.0/
Category: Biological State | Subjects: 25 | Files (Completed): 50 (Case B kernel; 25 PSG .rec + 25 ECG _lifecard.edf) | Channels: variable (PSG) | Sampling Rate: variable

Paradigm

Twenty-five patients suspected of sleep-disordered breathing underwent overnight polysomnographic (PSG) monitoring at University College Dublin (UCD). PSG files are stored in `.rec` format (EDF-compatible) and contain multiple physiological signals. Sleep stages were scored by expert technicians and stored in companion `_stage.txt` files (30-second epochs: Wake, Stage 1-4, REM). Companion `_lifecard.edf` ECG files are co-located per subject but are not EEG recordings and are skipped by the kernel (`-> unknown` annotations). The Case B kernel reconstructs continuous raw signals from the non-standard `.rec` format.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://physionet.org/content/ucddb/1.0.0/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`Sleep stage W`	4707	long	raw	Wake (30-second epoch)
`Sleep stage 1`	3016	long	raw	NREM Stage 1 (R&K)
`Sleep stage 2`	3403	long	raw	NREM Stage 2 (R&K)
`Sleep stage 3`	6985	long	raw	NREM Stage 3 - slow-wave sleep (R&K)
`Sleep stage 4`	673	long	raw	NREM Stage 4 - deep SWS (R&K)
`Sleep stage REM`	1990	long	raw	REM sleep
`Sleep stage 8`	15	admin	raw	Undefined/artifact epoch (exclude from classification)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Counts are totals across all 25 PSG files. `Sleep stage 8` indicates undefined or movement-time epochs. ECG `_lifecard.edf` files yield `unknown` annotations and should be excluded.

Tasks

Primary Task 1: Sleep stage classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Sleep stage labels (W/N1/N2/N3/REM; mapping dataset-specific)
- Evidence: The PhysioNet UCD Sleep Apnea Database release is explicitly structured around overnight PSG with stage annotations. Source: https://physionet.org/content/ucddb/1.0.0/ DOI: https://doi.org/10.13026/C26C7D

Normal Task 1: Sleep Stage Classification - 6-Class (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 30.0 s, overlap = 0.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Exclude `Sleep stage 8` (undefined epochs). ECG companion files (`_lifecard.edf`) yield `unknown` annotations and must not be used for sleep staging. Case B kernel: `.rec` files are read via `_read_edf_via_tempfile()`.

Event	y	Meaning
`Sleep stage W`	0	Wake
`Sleep stage 1`	1	NREM Stage 1
`Sleep stage 2`	2	NREM Stage 2
`Sleep stage 3`	3	NREM Stage 3
`Sleep stage 4`	4	NREM Stage 4
`Sleep stage REM`	5	REM

Normal Task 2: Sleep Apnea Context - Wake vs. Sleep (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event`
- Epoch Parameters: Needs verification
- Label Route: `Annotation`
- Target Definition: Needs verification.
- Notes: Sleep apnea-related breathing events are not included in the current EEG annotations; the dataset can be used for stage classification as a secondary target. Respiratory signals in the PSG recordings can supplement EEG for apnea detection but require custom parsing.

Data Quality Notes

- Case B kernel; `.rec` files require EDF-via-tempfile workaround; `_lifecard.edf` ECG files are excluded (-> `unknown` annotations in locator).
- Age and sex information may be in `SubjectDetails.xls` within the dataset; the kernel loads demographics from this file if available.
- R&K scoring system (stages 1-4 + REM); not directly comparable to AASM (N1/N2/N3) datasets.
- Small dataset (25 subjects); combine with other sleep databases for robust model training.

References

- Reference: Heneghan C et al. (2011). UCD Sleep Apnea Database. PhysioNet. DOI: https://doi.org/10.13026/C26C7D

274. sleepdata_shhs - sleepdata_shhs

Dataset: `sleepdata_shhs` | Year: 1995-2003 (SHHS-1: 1995-1998; SHHS-2: 2001-2003) | URL: https://sleepdata.org/datasets/shhs
Category: Biological State | Subjects: 6,441 (SHHS-1); 3,295 follow-up (SHHS-2) | Files (Completed): 5,786 EDF (SHHS-1) + 532 EDF (SHHS-2)
Channels: 14 (per EDF) | Sampling Rate: 125 Hz (EEG/EMG/ECG primary), 50 Hz (EOG), 10 Hz (respiratory), 1 Hz (SpO2/HR); exported EDF channels are resampled to 125 Hz

Paradigm

The Sleep Heart Health Study (SHHS) is a multi-center NIH/NHLBI cohort investigating cardiovascular and other outcomes of sleep-disordered breathing. Participants aged 40+ underwent unattended overnight home polysomnography (PSG), collected by certified technicians. SHHS-1 enrolled 6,441 participants from major epidemiological cohorts, and 3,295 participants completed a second PSG approximately 5 years later (SHHS-2). The dataset includes full-night EEG, EOG, EMG, ECG, respiratory, and oximetry signals with expert sleep-stage annotation in 30-second epochs.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://sleepdata.org/datasets/shhs

Event Structure

Annotations are available in both original Profusion XML and NSRR-processed XML (`*-nsrr.xml`). The NSRR XML files contain three high-level `EventType` groups:

Event ID	Count (total)	Type	Meta Level	Meaning
`Stages|Stages`	~100-400 annotations/file	long	raw	Sleep-stage labels in 30 s scoring epochs
`Arousals|Arousals`	variable	short/long	raw	Cortical arousal events
`Respiratory|Respiratory`	variable	short/long	raw	Respiratory events (apnea/hypopnea/desaturation-related)

Sleep Stage Labels (inside `EventConcept`)

Event ID	Count (total)	Type	Meta Level	Meaning
`Wake|0`	frequent	long	raw	Wake
`Stage 1|1`	lower frequency	long	raw	NREM Stage 1 (N1)
`Stage 2|2`	high frequency	long	raw	NREM Stage 2 (N2)
`Stage 3|3`	moderate	long	raw	Slow-wave sleep

Event ID	Count (total)	Type	Meta Level	Meaning
`Stage 4|4`	rare	long	raw	Slow-wave sleep (legacy R&K stage)
`REM|5`	moderate	long	raw	REM sleep

Event Type Description:
- `short`: brief event marker (for event-locked analysis)
- `long`: sustained-state marker (for long-event epoching, including sleep stages)
- `rest`: resting-state segment marker when explicitly present
- `admin`: boundary/system marker, exclude from target labels

Tasks

Primary Task 1: Sleep stage classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Sleep stage labels (W/N1/N2/N3/REM, dataset-specific mapping).
- Evidence: SHHS references and scoring protocol explicitly center on PSG/EEG sleep staging. Source: https://doi.org/10.5665/sleep.5774

Normal Task 1: Sleep Staging (5-class)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0 s, tmax = 30 s, overlap = 0.0 (standard staging), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Stage 4 is rare in many files; merging Stage 3 and Stage 4 is recommended for robust modeling.

Event	y	Meaning
`Wake|0`	0	Wake
`Stage 1|1`	1	N1
`Stage 2|2`	2	N2
`Stage 3|3` or `Stage 4|4`	3	N3/SWS
`REM|5`	4	REM

Normal Task 2: Sleep vs Wake Detection (binary)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0 s, tmax = 30 s, overlap = 0.0, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Useful baseline task when class granularity is reduced.

Event	y	Meaning
`Wake|0`	0	Awake

Event	y	Meaning
Any sleep stage (1/2/3/4/5)	1	Asleep

Normal Task 3: Arousal Detection (binary)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5 (or long-event segmentation if arousal duration labels are available)
- Epoch Parameters: tmin = -5.0 s, tmax = 5.0 s (event-centered), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Negative sampling strategy should be explicitly controlled to avoid label leakage.

Event	y	Meaning
Arousals|Arousals	1	Cortical arousal
Background non-arousal segments	0	Non-arousal

Normal Task 4: Respiratory Event Detection (binary)

- Task Type: classification
- Epoch Method: epoch_by_event_hdf5 or epoch_by_long_event_hdf5 (depends on event duration granularity)
- Epoch Parameters: task-dependent (for example, 10-30 s windows), target_events = see Target Definition
- Label Route: Annotation
- Target Definition: Event-to-label mapping table below.
- Notes: Respiratory subtype definitions should be verified per XML file and NSRR conversion version.

Event	y	Meaning
Respiratory|Respiratory (event windows)	1	Respiratory event
Non-event windows	0	Normal breathing/no event
## Data Quality Notes		

- Mixed-rate channels are exported at 125 Hz in EDF; originally low-rate channels (EOG/respiratory/SpO2/HR) are upsampled during export.
- Channel naming may vary across files (NEW AIR vs AIRFLOW), so channel selection should be robust to aliases.
- Annotation counts can differ between XML-derived event totals and summary CSV fields due to historical software conversion effects.
- Desaturation labels may be missing or partially inconsistent in some files; consider deriving desaturation from raw Sa02 traces when needed.
- Class imbalance is expected (N2 dominant; Wake/N1 relatively sparse; Stage 4 rare).
- Recordings are unattended home PSG and therefore may have higher motion/environmental artifact than in-lab PSG.
- SHHS-2 ECG can differ in effective native sampling relative to SHHS-1; handle ECG separately if exact spectral comparability is required.

References

- Quan, S.F. et al. (1997). The Sleep Heart Health Study: design, rationale, and methods. Sleep, 20(12), 1077-1085.

- Redline, S. et al. (1998). Methods for obtaining and analyzing unattended polysomnography data for a multicenter study. Sleep, 21(7), 759-767.
- Dean, D.A. et al. (2016). Scaling Up Scientific Discovery in Sleep Medicine: The National Sleep Research Resource. Sleep, 39(5), 1151-1164. DOI: https://doi.org/10.5665/sleep.5774
- Zhang, G.Q. et al. (2018). The National Sleep Research Resource: making data findable, accessible, interoperable, reusable and promoting new research. Sleep Medicine, 10(5), 367-376.
- NSRR SHHS dataset page: https://sleepdata.org/datasets/shhs

275. tuh_eeg - TUH EEG Corpus (Base)

Dataset: `tuh_eeg` | Year: 2020 | URL: https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg/v2.0.1/
Category: Biological State | Subjects: ~14987 | Files (Completed): 69652 | Channels: 17-128 | Sampling Rate: 250-1000 Hz

Paradigm

The Temple University Hospital EEG Corpus (v2.0.1) is the largest publicly available clinical EEG archive, containing approximately 69,652 EDF recordings from ~14,987 de-identified patients (Obeid & Picone, 2016). Recordings span routine clinical EEG sessions performed for neurological evaluation (epilepsy monitoring, encephalopathy, post-operative assessment, etc.). Three standard TCP (Temporal Central Parasagittal) referential montages are used: `01_tcp_ar` (average reference), `02_tcp_le` (linked ears), and `03_tcp_ar_a` (alternating average reference). Channel counts vary (17-128) and multiple sampling rates are present (250, 256, 400, 512, 1000 Hz). No structured experiment events exist; EDF annotations are clinical technician notes in free text.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision:
> https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg/v2.0.1/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
unknown	69652	admin	raw	Clinical EEG with unstructured technician annotations; no ML-ready event labels

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> No structured classification annotations. The base corpus is not labeled for any specific ML task; use specialized TUH subsets (tuh_eeg_abnormal, tuh_eeg_seizure, etc.) for supervised learning.

Tasks

Primary Task 1: Resting-state analysis baseline

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification

- Label Route: `Annotation`
- Target Definition: Condition/group labels from metadata when available
- Evidence: Dataset is primarily resting-state or spontaneous-state EEG. Source: https://isip.piconepress.com/projects/tuh_eeg/ DOI: https://doi.org/10.3389/fnins.2016.00196

Normal Task 1: Resting-State Segmentation (epoch_by_segmentation)

- Task Type: segmentation
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: length = 5.0 s, overlap = 2.5 s
- Label Route: `Annotation`
- Target Definition: N/A (no labels; use for pretraining / unsupervised learning)
- Notes: The base corpus is best used for self-supervised pretraining or large-scale representation learning. Labels (patient age, sex, montage type) can be derived from the EDF header or `eegunity_description` field parsed by the kernel. Ensure montage consistency before cross-recording analysis: process each montage type (01_tcp_ar, 02_tcp_le, 03_tcp_ar_a) separately or re-reference uniformly.

Data Quality Notes

- No structured ML annotations; this corpus is used as a pretraining source, not for supervised classification.
- Three TCP montages with differing channel layouts; normalize before cross-recording analysis.
- Clinical recordings: variable length, variable channel count, variable sampling rate.
- Sex available from EDF header (M/F/unknown).
- Age is not reliably available in the public release.
- Very large dataset (70k files): batch-processing and memory management are critical.

References

- Reference: Obeid I, Picone J (2016). The Temple University Hospital EEG Data Corpus. Frontiers in Neuroscience, 10, 196. https://isip.piconepress.com/projects/tuh_eeg/

276. tuh_eeg_abnormal - TUH EEG Abnormal Corpus

Dataset: `tuh_eeg_abnormal` | Year: 2022 | URL: https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_abnormal/v3.0.1/
Category: Biological State | Subjects: ~2983 sessions | Files (Completed): 2983 | Channels: 27-36 | Sampling Rate: 250-512 Hz

Paradigm

The TUH EEG Abnormal Corpus (v3.0.1) is a clinically annotated subset of the TUH EEG Corpus where each recording has been classified as normal or abnormal by board-certified neurologists (Lopez et al., 2015). Recordings are routine clinical EEG sessions acquired in an outpatient setting at Temple University Hospital. The normal/abnormal label reflects the overall clinical impression of the EEG recording, not individual event annotations. The label is encoded in the directory path (`normal/` or `abnormal/`) and extracted by the kernel to create a single whole-recording annotation.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision:
> https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_abnormal/v3.0.1/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`normal:1`	1517	long	raw	Normal EEG recording (full-recording label)
`abnormal:1`	1466	long	raw	Abnormal EEG recording (full-recording label)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Each recording has exactly one annotation spanning its full duration. `normal:1` = one "normal" annotation. Label derived from parent directory (`normal/` or `abnormal/`).

Tasks

Primary Task 1: Normal vs abnormal EEG recording classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Recording-level normal/abnormal diagnostic label.

- Evidence: TUH Abnormal Corpus is explicitly curated for normal-versus-abnormal EEG classification. Source: https://isip.piconepress.com/projects/tuh_eeg/ DOI: https://doi.org/10.3389/fnins.2016.00196

Normal Task 1: Normal vs. Abnormal EEG Classification (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 5.0 s, overlap = 2.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: The annotation spans the entire recording; use `epoch_by_long_event_hdf5` with sliding windows. Parse the label prefix before the colon (`:`) to extract the class name. Near-balanced classes: 1517 normal vs. 1466 abnormal.

Event	y	Meaning
`normal:1`	0	Normal EEG
`abnormal:1`	1	Abnormal EEG
## Data Quality Notes		

- Sex is not reliably available in this subset.
- Variable channel count (27-36) and sampling rate (250-512 Hz) across recordings; normalize before cross-recording analysis.
- Whole-recording global labels; local event patterns within recordings are not annotated.
- Train/dev split is encoded in directory path; respect the split for proper evaluation.

References

- Reference: Lopez S et al. (2015). Analysis of Factors that Affect EEG Signal Quality. EMBC 2015. Obeid I, Picone J (2016). The Temple University Hospital EEG Data Corpus. https://isip.piconepress.com/projects/tuh_eeg/

277. tuh_eeg_epilepsy - TUH EEG Epilepsy Corpus

Dataset: `tuh_eeg_epilepsy` | Year: 2022 | URL: https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_epilepsy/v2.0.1/
Category: Biological State | Subjects: ~2298 sessions | Files (Completed): 2298 | Channels: 17-41 | Sampling Rate: 250-1000 Hz

Paradigm

The TUH EEG Epilepsy Corpus (v2.0.1) is a clinically labeled subset of the TUH EEG Corpus where each recording is classified as epilepsy or no epilepsy based on patients' established clinical diagnoses (not real-time EEG pattern) recorded in hospital notes. Unlike tuh_eeg_seizure, the epilepsy label reflects a patient-level diagnosis, not the presence of ictal activity in the specific recording. The label is extracted from the directory path (`00_epilepsy/` or `01_no_epilepsy/`) and assigned as a single whole-recording annotation by the kernel.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision:
> https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_epilepsy/v2.0.1/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`epilepsy:1`	1785	long	raw	Patient has a diagnosis of epilepsy (whole-recording label)
`no epilepsy:1`	513	long	raw	Patient does not have epilepsy (whole-recording label)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Each recording has exactly one annotation spanning its full duration.

Tasks

Primary Task 1: Epilepsy vs non-epilepsy classification

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`

- Target Definition: Patient/record-level epilepsy label from TUH Epilepsy corpus metadata.
- Evidence: TUH Epilepsy Corpus is specifically assembled for epilepsy diagnosis classification research. Source: https://isip.piconepress.com/projects/tuh_eeg/ DOI: https://doi.org/10.3389/fnins.2016.00196

Normal Task 1: Epilepsy Patient Classification (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 5.0 s, overlap = 2.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Parse label prefix before the colon. Class imbalance: 1785 epilepsy vs. 513 no-epilepsy (~3.5:1); apply class-balancing. Label is a patient-level diagnosis, not an EEG event; the EEG recording may or may not contain ictal activity.

Event	y	Meaning
`epilepsy:1`	1	Epilepsy diagnosis
`no epilepsy:1`	0	No epilepsy diagnosis
## Data Quality Notes		

- Class imbalance: epilepsy (77.6%) vs. no epilepsy (22.4%); balance before training.
- Label caveat: The epilepsy label is a clinical diagnosis from hospital records, not annotation of seizure events within the recording; some epilepsy-labeled recordings may be interictal.
- Variable channels (17-41) and sampling rates (250-1000 Hz); normalize before cross-recording analysis.
- Sex is not reliably available.

References

- Reference: TUH EEG Epilepsy Corpus v2.0.1. Obeid I, Picone J (2016). The Temple University Hospital EEG Data Corpus. https://isip.piconepress.com/projects/tuh_eeg/

278. tuh_eeg_events - TUH EEG Events Corpus

Dataset: `tuh_eeg_events` | Year: 2022 | URL: https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_events/v2.0.1/
Category: Biological State | Subjects: ~370 | Files (Completed): 518 | Channels: 24-33 | Sampling Rate: 250 Hz

Paradigm

The TUH EEG Events Corpus (v2.0.1) provides time-stamped annotations of neurological events in 518 clinical EEG recordings from ~370 unique patients (Shah et al., 2018). Expert neurologists annotated six event types at temporal and spatial resolution using companion `.rec` sidecar files (4-column format: channel, start_time, stop_time, label_code). Events include epileptiform discharges, background EEG, and artifact. All recordings are sampled at 250 Hz with 24-33 channels.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision:
> https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_events/v2.0.1/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`background`	varies	long	raw	Normal background EEG activity
`spike and sharp wave`	varies	short	raw	Spike or sharp wave discharge
`generalized periodic epileptiform discharges`	varies	short	raw	GPEDs - generalized periodic epileptiform pattern
`periodic lateralized epileptiform discharges`	varies	short	raw	PLEDs - lateralized epileptiform pattern
`eye movement`	varies	short	raw	Eye movement artifact
`artifact`	varies	short	raw	Non-specific artifact

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Label codes from `.rec` files: 1=spike and sharp wave, 2=generalized periodic epileptiform discharges, 3=periodic lateralized epileptiform discharges, 4=eye movement, 5=artifact, 6=background.

Tasks

Primary Task 1: Neurological EEG event detection/classification

- Task Type: classification/detection
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event classes from expert annotations (e.g., spikes, periodic discharges, artifacts, background).
- Evidence: TUH EEG Events Corpus provides time-stamped multi-class event annotations as the primary benchmark target. Source: https://isip.piconepress.com/projects/tuh_eeg/ DOI: https://doi.org/10.1109/globalsip.2013.6736803

Normal Task 1: EEG Event Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Exclude `eye movement` and `artifact` events from classification targets. For binary detection: background (y=0) vs. any epileptiform event (y=1). `.rec` sidecar files must be present alongside `.edf` files.

Event	y	Meaning
`background`	0	Normal background EEG
`spike and sharp wave`	1	Epileptiform spike/sharp wave
`generalized periodic epileptiform discharges`	2	GPEDs
`periodic lateralized epileptiform discharges`	3	PLEDs

Normal Task 2: Epileptiform vs. Normal EEG Detection (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.5 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`background`	0	Normal EEG
`spike and sharp wave`	1	Epileptiform
`generalized periodic epileptiform discharges`	1	Epileptiform
`periodic lateralized epileptiform discharges`	1	Epileptiform
## Data Quality Notes		

- `.rec` sidecar files required; if missing, no annotations are set.
- Background annotations are long events; epileptiform events are short - class length mismatch may cause imbalance.

- Uniform sampling rate (250 Hz) and consistent channel count (24-33); relatively homogeneous compared to other TUH subsets.
- Sex is not reliably available.

References

- Reference: Shah V et al. (2018). The Temple University Hospital EEG Event Corpus. Frontiers in Neuroscience, 12, 862. https://isip.piconepress.com/projects/tuh_eeg/

279. tuh_eeg_seizure - TUH EEG Seizure Corpus

Dataset: `tuh_eeg_seizure` | Year: 2022 | URL: https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_seizure/v2.0.3/
Category: Biological State | Subjects: ~675 | Files (Completed): 7361 | Channels: 17-128 | Sampling Rate: 250-1000 Hz

Paradigm

The TUH EEG Seizure Corpus (v2.0.3) is the largest publicly available seizure detection dataset, containing 7,361 clinical EEG recordings from ~675 unique patients with time-stamped seizure annotations (Shah et al., 2020). Expert neurologists labeled each segment as background (bckg) or one of five seizure types using companion CSV sidecar files (channel, start_time, stop_time, label). The dataset is pre-split into train and dev sets (directory path contains `/train/` or `/dev/`). Recording lengths range from a few minutes to several hours.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision:
> https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_seizure/v2.0.3/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`bckg`	~75000	long	raw	Background - no seizure activity
`gnsz`	varies	long	raw	Generalized non-specific seizure
`fnsz`	varies	long	raw	Focal non-specific seizure
`cpsz`	varies	long	raw	Complex partial seizure
`absz`	varies	long	raw	Absence seizure
`tnsz`	varies	long	raw	Tonic seizure

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> `bckg` (background) is overwhelmingly the most frequent label. Seizure events are annotated with onset, offset, and type from CSV sidecars.

Tasks

Primary Task 1: Seizure event detection and localization

- Task Type: classification/detection
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Seizure vs background labels with temporal seizure boundaries.
- Evidence: TUH Seizure Corpus is primarily designed for automated seizure detection from clinical EEG. Source: https://isip.piconepress.com/projects/tuh_eeg/ DOI: https://doi.org/10.1109/globalsip.2013.6736803

Normal Task 1: Seizure Detection - bckg vs. Seizure (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s (annotation onset), duration = annotation duration, overlap = 0.0 s for initial segmentation; or sliding window 5.0 s, overlap = 2.5 s on annotated segments, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Extreme class imbalance: `bckg` >> all seizure types combined. Undersample background or use cost-sensitive learning. CSV sidecars required alongside EDF files.

Event	y	Meaning
`bckg`	0	Background / no seizure
`gnsz`	1	Generalized seizure
`fnsz`	1	Focal seizure
`cpsz`	1	Complex partial seizure
`absz`	1	Absence seizure
`tnsz`	1	Tonic seizure

Normal Task 2: Seizure Type Classification (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: Use annotation duration (seizure-type segments only), target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Use only seizure-type annotations (gnsz=0, fnsz=1, cpsz=2, absz=3, tnsz=4); exclude `bckg`.
- Notes: Severe class imbalance across seizure types; some types (absz, tnsz) are rare.

Data Quality Notes

- Extreme class imbalance: background constitutes >80% of annotations; severely balance before training.
- Variable channel count (17-128) and sampling rate (250-1000 Hz); normalize per recording.
- Train/dev split is pre-defined; respect it for evaluation. Split encoded in file path (`/train/`, `/dev/`).
- Sex is not reliably available.
- Long recordings may span multiple seizure episodes; temporal context is important.

References

- Reference: Shah V et al. (2020). The Temple University Hospital EEG Seizure Corpus. Frontiers in Neural Engineering. https://isip.piconepress.com/projects/tuh_eeg/

280. tuh_eeg_slowing - TUH EEG Slowing Corpus

Dataset: `tuh_eeg_slowing` | Year: 2022 | URL: https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_slowing/v2.0.1/
Category: Biological State | Subjects: ~47 | Files (Completed): 112 | Channels: 27-41 | Sampling Rate: 250-512 Hz

Paradigm

The TUH EEG Slowing Corpus (v2.0.1) contains 112 clinical EEG recordings with time-stamped annotations for EEG slowing, seizure activity, and background segments. Expert annotators labeled each segment using companion CSV sidecar files (channel, start_time, stop_time, label). EEG slowing (diffuse or focal slow-wave activity) is a neurological biomarker of conditions such as encephalopathy, stroke, or post-ictal states. The corpus enables the development of algorithms to automatically detect and localize EEG slowing.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision:
> https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_slowing/v2.0.1/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`seiz`	varies	long	raw	Seizure activity
`slow`	varies	long	raw	EEG slowing (pathological slow-wave activity)
`bckg`	varies	long	raw	Background - normal EEG

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Multiple annotations may appear in a single recording (e.g., `bckg + slow`, `bckg + seiz`). Per the CSV analysis, top events include `seiz:22`, `seiz:43`, `slow:64`, and `bckg:43,slow:63`.

Tasks

Primary Task 1: EEG slowing detection (focal/generalized vs background)

- Task Type: classification/detection
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Slowing-related event labels against normal background segments.

- Evidence: TUH Slowing Corpus provides curated slowing annotations for automated slowing detection tasks. Source: https://isip.piconepress.com/projects/tuh_eeg/ DOI: https://doi.org/10.3389/fnins.2016.00196

Normal Task 1: EEG Slowing Detection - Normal vs. Slowing (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, use annotation duration, overlap = 0.0 s; or sliding window 5.0 s, overlap = 2.5 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Exclude `seiz` events if slowing-specific detection is the goal, or include as a third class. CSV sidecars required.

Event	y	Meaning
`bckg`	0	Normal background EEG
`slow`	1	EEG slowing

Normal Task 2: 3-Class EEG State Classification (epoch_by_long_event)

- Task Type: classification
- Epoch Method: `epoch_by_long_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, use annotation duration, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`bckg`	0	Background
`slow`	1	Slowing
`seiz`	2	Seizure
## Data Quality Notes		

- Small dataset (112 files, ~47 subjects); limited sample size.
- CSV sidecars required; if missing, the kernel raises a ValueError.
- Variable sampling rate (250-512 Hz); normalize before cross-recording analysis.
- Annotations may overlap (e.g., slowing + seizure in the same segment); handle compound annotations carefully.
- Sex is not reliably available.

References

- Reference: TUH EEG Slowing Corpus v2.0.1. Obeid I, Picone J (2016). The Temple University Hospital EEG Data Corpus. https://isip.piconepress.com/projects/tuh_eeg/

Chapter 6. Others

Datasets in this chapter: 6. Does not clearly fit the above categories.

281. openneuro_ds004075 - what_are_we_talking_about

Dataset: `openneuro_ds004075` | Year: 2022 | URL: https://openneuro.org/datasets/ds004075
Category: Others | Subjects: N/A | Files (Completed): 115
Channels: 64.0 | Sampling Rate: 1000.0 Hz

Paradigm

The provided title 'what_are_we_talking_about' without an accompanying README is too vague to determine a specific experimental paradigm.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: regression target
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004075

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`no_events`	N/A	admin	raw	No discrete event markers detected; use continuous segmentation or external metadata labels.
## MISC Label Summary				

- Route: `misc`
- Role: Stores derived labels (super meta) not directly present in raw event IDs.
- Candidate Labels: Needs verification
- Kernel Note: Document derivation logic, source fields, units, and version tags.

Tasks

Primary Task 1: Publisher-defined BIDS task: Context03

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`

- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004075 DOI: https://doi.org/10.18112/openneuro.ds004075.v1.0.0

Primary Task 2: Publisher-defined BIDS task: Context09

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004075 DOI: https://doi.org/10.18112/openneuro.ds004075.v1.0.0

Primary Task 3: Publisher-defined BIDS task: Context10

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004075 DOI: https://doi.org/10.18112/openneuro.ds004075.v1.0.0

Normal Task 1: Raw-meta task

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Needs verification
- Kernel Notes: Exclude admin markers from target labels.

Normal Task 2: Super-meta task

- Task Type: regression/classification
- Epoch Method: `epoch_by_event_hdf5` or `epoch_by_long_event_hdf5`
- Epoch Parameters: Needs verification, target_events = see Target Definition
- Label Route: `misc`
- Target Definition: Continuous target value as defined by kernel and label route.
- Regression Target / Label: Needs verification
- Kernel Notes: Derive and version super-meta in kernel.

Data Quality Notes

- Verify channel count consistency across subjects before pooling.
- Apply bandpass filter (0.5-40 Hz) and artifact rejection prior to epoching.

References

- No paper reference available

282. openneuro_ds004784 - Phantom EEG Dataset with Motion, Muscle, and Eye Artifacts

Dataset: openneuro_ds004784 | Year: 2023 | URL: https://openneuro.org/datasets/ds004784
Category: Others | Subjects: N/A | Files (Completed): 10 | Channels: 264 | Sampling Rate: 512 Hz

Paradigm

Technical validation study using an electrically conductive head phantom to simulate brain activity under various artifact conditions (motion, muscle, eye movements) for testing EEG cleaning algorithms. Code 65471 appears in all 10 files (20 total events); code 65343 appears in all 10 files (10 total events). These likely mark artifact-on vs artifact-off conditions or different artifact types.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004784

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
65471	20	short	raw	Artifact condition marker A (e.g., artifact-on)
65343	10	short	raw	Artifact condition marker B (e.g., clean condition)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Publisher-defined BIDS task: Mixed

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_long_event_hdf5` or `epoch_by_segmentation_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, overlap = Needs verification, target_events = [Needs verification] | segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004784 DOI: https://doi.org/10.3390/s23198214

Normal Task 1: Artifact Condition Classification (binary)

- Task Type: classification

- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Very small dataset (10 files, 30 total events). Verify code meanings from dataset README. 264 channels - ultra-high density EEG phantom. Class imbalance 2:1 (20 vs 10).

Event	y	Meaning
`65471`	0	Artifact condition A
`65343`	1	Artifact condition B
## Data Quality Notes		

- Very small dataset (10 files, 30 events total) - insufficient for standard classification.
- 264-channel phantom EEG; not standard scalp EEG configuration.
- Designed for artifact algorithm validation, not neural decoding.

References

- Reference: `Phantom EEG Dataset with Motion, Muscle, and Eye Artifacts and Example Scripts`

283. openneuro_ds004843 - Visual Situational Awareness EEG (T16)

Dataset: `openneuro_ds004843` | Year: 2023 | URL: https://openneuro.org/datasets/ds004843
Category: Others | Subjects: 7 | Files (Completed): 7 | Channels: 70 | Sampling Rate: 256 Hz

Paradigm

The `VisualSituationalAwareness` task investigates neural correlates of situational awareness during visual monitoring. Subjects viewed structured visual scenes with EEG recorded across multiple runs. The 5-digit hierarchical trigger codes encode stimulus category, load level, and response type. Codes 22301/22302 (3,384 each) and 22501/22502 (2,331/2,325) dominate; code 32000 (1,099) likely marks scene/trial boundaries. Codes ending in 01/02 mark paired conditions (onset/offset or left/right).

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds004843

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`22301`	3384	short	raw	Condition 2-2-3, variant 01
`22302`	3384	short	raw	Condition 2-2-3, variant 02
`22501`	2331	short	raw	Condition 2-2-5, variant 01
`22502`	2325	short	raw	Condition 2-2-5, variant 02
`22102`	1327	short	raw	Condition 2-2-1, variant 02
`22101`	1325	short	raw	Condition 2-2-1, variant 01
`32000`	1099	admin	raw	Scene/trial boundary marker (exclude)
`22601`	436	short	raw	Condition 2-2-6, variant 01
`22602`	436	short	raw	Condition 2-2-6, variant 02
`42001`	382	short	raw	Condition 4-2-0, variant 01

Event ID	Count (total)	Type	Meta Level	Meaning
42002	382	short	raw	Condition 4-2-0, variant 02
22001	372	short	raw	Condition 2-2-0, variant 01
22002	372	short	raw	Condition 2-2-0, variant 02
12201	306	short	raw	Condition 1-2-2, variant 01
12202	306	short	raw	Condition 1-2-2, variant 02

Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: `stim`
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: Needs verification
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Visual Situational Awareness

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)
- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds004843 DOI: https://doi.org/10.18112/openneuro.ds004843.v1.0.0

Normal Task 1: Visual Situational Awareness (multiclass)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: `32000` (1,099) is a scene/trial boundary - exclude. Very small dataset (7 files); balance classes by undersampling. 5-digit codes require README or paper decode.

Event	y	Meaning
22301	0	Condition 22301
22302	1	Condition 22302
22501	2	Condition 22501
22502	3	Condition 22502
22101	4	Condition 22101

Event	y	Meaning
22102	5	Condition 22102
22601	6	Condition 22601
22602	7	Condition 22602
## Data Quality Notes		

- Only 7 files - very small dataset for training.
- 5-digit hierarchical codes require decode from README or paper.
- 32000 is a boundary/transition marker - exclude from epoching.

References

- Reference: T16 - Visual Situational Awareness EEG

284. openneuro_ds005787 - NOD-EEG

Dataset: openneuro_ds005787 | Year: 2025 | URL: https://openneuro.org/datasets/ds005787
Category: Others | Subjects: N/A | Files (Completed): 896 | Channels: 64 | Sampling Rate: 250 Hz

Paradigm

The NOD-EEG dataset contains 64-channel EEG recordings from a stimulus-response paradigm. Each trial includes a stimulus onset (stim_on), participant button-press response (resp), and block boundary markers (begin, end). The precise experimental task and stimuli are described in the dataset README.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (Annotation, stim, misc) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation, stim
> Web Reference Used for Decision: https://openneuro.org/datasets/ds005787

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
resp	2273060	short	raw	Participant button-press response
stim_on	112000	short	raw	Stimulus onset
begin	896	long	raw	Block begin marker
end	896	long	raw	Block end marker

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

STIM Label Summary

- Route: stim
- Role: Trigger-channel or stimulus-marker based labeling.
- Candidate Trigger Labels: stim_on
- Kernel Note: Keep trigger decoding table versioned and auditable.

Tasks

Primary Task 1: Publisher-defined BIDS task: Image Net

- Task Type: classification/segmentation
- Epoch Method: epoch_by_event_hdf5
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: Annotation
- Target Definition: Event/condition labels for this BIDS task (dataset-specific mapping)

- Evidence: OpenNeuro metadata.tasksCompleted and dataset readme. Source: https://openneuro.org/datasets/ds005787 DOI: https://doi.org/10.18112/openneuro.ds005787.v1.0.0

Normal Task 1: Stimulus-Response (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = -0.2 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Very high count for `resp` (2.27M total); verify that events are correctly timestamped. `begin`/`end` mark block boundaries.

Event	y	Meaning
`resp`	0	Button-press response
`stim_on`	1	Stimulus onset
`begin`	2	Block begin
`end`	3	Block end
## Data Quality Notes		

- Very high total event count for `resp`; verify no duplicate events.
- Apply bandpass filter (1-40 Hz) and artifact rejection prior to epoching.

References

- Reference: `EEG-BIDS, an extension to the brain imaging data structure for electroencephalography. Scientific Data, 6, 103`

285. physionet_motionartifact - EEG/fNIRS Motion Artifact Dataset

Dataset: `physionet_motionartifact` | Year: 2018 | URL: https://physionet.org/content/motion-artifact/1.0.0/
Category: Others | Subjects: 32 | Files (Completed): 32 | Channels: 10 (EEG) or 12 (fNIRS) | Sampling Rate: 2048 Hz (EEG), 200 Hz (fNIRS)

Paradigm

Thirty-two recordings (23 EEG + 9 fNIRS) were collected from subjects performing various physical activities: cycling, running, walking, push-ups, pull-ups, stretching, and rest (Schultz & Kluge, 2018). The purpose is to provide a benchmark dataset for motion artifact detection and removal algorithms. EEG was recorded from 10 channels (gel electrodes) at 2048 Hz; fNIRS from 12 channels at 200 Hz. Each recording corresponds to one subject performing one activity. Activity labels are encoded in the filename (recording ID: `eeg_1` through `eeg_23`; `fnirs_1` through `fnirs_9`) and documented in a companion README.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 1 + Type 3
> Why: Raw markers are sufficient for primary tasks.
> Primary Label Routes: Annotation
> Web Reference Used for Decision: https://physionet.org/content/motion-artifact/1.0.0/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
(none)	-	-	raw	No event annotations present; activity label is implicit in recording ID

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude

Tasks

Primary Task 1: Motion artifact detection and activity-aware artifact benchmarking

- Task Type: classification/segmentation
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: segment_length = Needs verification, overlap = Needs verification
- Label Route: `Annotation`
- Target Definition: Recording-level activity condition and motion-artifact contamination labels derived from recording ID / dataset protocol.
- Evidence: The PhysioNet motion-artifact release is explicitly provided as an EEG/fNIRS motion artifact benchmark dataset. Source: https://physionet.org/content/motion-artifact/1.0.0/ DOI: https://doi.org/10.13026/C2988P

Normal Task 1: Physical Activity Classification - Resting-State Segmentation (epoch_by_segmentation)

- Task Type: classification
- Epoch Method: `epoch_by_segmentation_hdf5`
- Epoch Parameters: length = 5.0 s, overlap = 2.5 s
- Label Route: `Annotation`
- Target Definition: N/A - activity labels must be assigned post-hoc from filename metadata (see notes)
- Notes: No event annotations are present; the kernel only records the recording ID in the description field. To assign activity labels for supervised learning, map recording IDs to physical activities using the dataset README. For artifact detection tasks, all recordings can be treated as motion-contaminated (except rest recordings).

Data Quality Notes

- No structured event annotations; classification labels must be derived from filename-based recording IDs.
- Mixed signal types: EEG (eeg_1-eeg_23, 10 channels, 2048 Hz) and fNIRS (fnirs_1-fnirs_9, 12 channels, 200 Hz) in the same locator; process these file types separately.
- Age and sex information are not available.
- Primary use case is motion artifact removal/detection benchmarking, not cognitive task decoding.

References

- Reference: Schultz T, Kluge T. Motion artifact dataset for EEG and fNIRS. PhysioNet. DOI: https://doi.org/10.13026/C2988P

286. tuh_eeg_artifact - TUH EEG Artifact Corpus

Dataset: `tuh_eeg_artifact` | Year: 2022 | URL: https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_artifact/v3.0.1/
Category: Others | Subjects: ~310 sessions | Files (Completed): 310 | Channels: 27-128 | Sampling Rate: 250-1000 Hz

Paradigm

The TUH EEG Artifact Corpus (v3.0.1) provides time-stamped, channel-level artifact annotations on 310 clinical EEG recordings selected from the TUH EEG Corpus. Expert annotators labeled artifact segments with type and temporal boundaries, stored in companion CSV sidecar files. Each annotation includes: channel name, start time, stop time, label, and confidence score. Multiple artifact types may co-occur within a recording.

Kernel Responsibilities

- Type 1 (Raw-meta extraction only): Extract and normalize raw labels from events/trigger streams.
- Type 2 (Raw + Super meta integration): Derive and merge high-level labels that are not directly represented in raw events.
- Type 3 (Label-route orchestration): Route final labels to EEGUnity-compatible channels (`Annotation`, `stim`, `misc`) with reproducible schema.

> Selected Mode: Type 2 + Type 3
> Why: Derived targets are needed beyond raw markers.
> Primary Label Routes: Annotation, misc
> Evidence Keywords: confidence
> Web Reference Used for Decision: https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_artifact/v3.0.1/

Event Structure

Event ID	Count (total)	Type	Meta Level	Meaning
`eyem`	varies	short	raw	Eye movement artifact
`musc`	varies	short	raw	Muscle (EMG) artifact
`elec`	varies	short	raw	Electrode artifact (pop, movement)
`chew`	varies	short	raw	Chewing artifact
`shiv`	varies	short	raw	Shivering artifact
`elpp`	varies	short	raw	Electrode pop
`null`	varies	admin	raw	No artifact (clean segment)

> Event Type: short=stimulus onset <2s; long=sustained state >=2s; rest=resting marker; admin=exclude
>
> Artifact annotations are channel-level and time-stamped. Multiple artifact types may appear in a single recording; combined labels (e.g., `musc_elec`, `eyem_musc`) are also present.

MISC Label Summary

- Route: `misc`

- Role: Stores derived/continuous labels that are not native raw event IDs.
- Candidate Labels: `confidence`
- Kernel Note: Keep derivation source, unit, and version metadata.

Tasks

Primary Task 1: Artifact event detection and artifact-type classification

- Task Type: classification/detection
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = Needs verification, tmax = Needs verification, target_events = [Needs verification]
- Label Route: `Annotation`
- Target Definition: Artifact class labels from annotated event intervals (e.g., eye, muscle, movement/electrode artifacts).
- Evidence: The TUAR release documentation explicitly cites artifact detection and classification as the benchmark use case and points to the corresponding publication. Source: https://isip.piconepress.com/projects/tuh_eeg/downloads/tuh_eeg_artifact/v3.0.1/ DOI: https://doi.org/10.1109/SPMB52430.2021.9672302

Normal Task 1: Artifact Type Classification (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.
- Notes: Exclude `null` segments. Combined labels (e.g., `musc_elec`) require a decision: either assign to the primary artifact type or treat as a separate class. CSV sidecars must be present alongside EDF files.

Event	y	Meaning
`eyem`	0	Eye movement
`musc`	1	Muscle (EMG)
`elec`	2	Electrode artifact
`chew`	3	Chewing
`shiv`	4	Shivering
`elpp`	5	Electrode pop

Normal Task 2: Artifact vs. Clean EEG Detection (epoch_by_event)

- Task Type: classification
- Epoch Method: `epoch_by_event_hdf5`
- Epoch Parameters: tmin = 0.0 s, tmax = 1.0 s, target_events = see Target Definition
- Label Route: `Annotation`
- Target Definition: Event-to-label mapping table below.

Event	y	Meaning
`null`	0	Clean EEG segment
`eyem`	1	Any artifact
`musc`	1	Any artifact
`elec`	1	Any artifact

Event	y	Meaning
chew	1	Any artifact
## Data Quality Notes		

- Annotations are at the channel level; aggregate to recording level or use channel-specific labels depending on the task.
- Combined label types (e.g., `eyem_musc`) create label ambiguity; standardize before training.
- Variable channel count and sampling rate; normalize before cross-recording analysis.
- Sex is not reliably available.

References

- Reference: Buckwalter G, Chhin S, Rahman S, Obeid I, Picone J. (2021). Recent Advances in the TUH EEG Corpus: Improving the Interrater Agreement for Artifacts and Epileptiform Events. IEEE Signal Processing in Medicine and Biology Symposium (SPMB). DOI: https://doi.org/10.1109/SPMB52430.2021.9672302