

Maximal Marginal Relevance ExampleSelector

The MaxMarginalRelevanceExampleSelector selects examples based on a combination of which examples are most similar to the inputs, while also optimizing for diversity. It does this by finding the examples with the embeddings that have the greatest cosine similarity with the inputs, and then iteratively adding them while penalizing them for closeness to already selected examples.

```
from langchain.prompts.example_selector import MaxMarginalRelevanceExampleSelector
from langchain.vectorstores import FAISS
from langchain.embeddings import OpenAIEmbeddings
from langchain.prompts import FewShotPromptTemplate, PromptTemplate

example_prompt = PromptTemplate(
    input_variables=["input", "output"],
    template="Input: {input}\nOutput: {output}",
)

# These are a lot of examples of a pretend task of creating antonyms.
examples = [
    {"input": "happy", "output": "sad"},
    {"input": "tall", "output": "short"},
    {"input": "energetic", "output": "lethargic"},
    {"input": "sunny", "output": "gloomy"},
    {"input": "windy", "output": "calm"},
]
```

```
example_selector = MaxMarginalRelevanceExampleSelector.from_examples(
    # This is the list of examples available to select from.
    examples,
    # This is the embedding class used to produce embeddings which are used to
    # measure semantic similarity.
    OpenAIEmbeddings(),
    # This is the VectorStore class that is used to store the embeddings and do a
    # similarity search over.
    FAISS,
    # This is the number of examples to produce.
    k=2
)

mmr_prompt = FewShotPromptTemplate(
```

[Skip to main content](#)

```
example_prompt=example_prompt,  
prefix="Give the antonym of every input",  
suffix="Input: {adjective}\nOutput:",  
input_variables=["adjective"],  
)
```

```
# Input is a feeling, so should select the happy/sad example as the first one  
print(mmr_prompt.format(adjective="worried"))
```

Give the antonym of every input

Input: happy
Output: sad

Input: windy
Output: calm

Input: worried
Output:

```
# Let's compare this to what we would just get if we went solely off of similarity  
similar_prompt = FewShotPromptTemplate(  
    # We provide an ExampleSelector instead of examples.  
    example_selector=example_selector,  
    example_prompt=example_prompt,  
    prefix="Give the antonym of every input",  
    suffix="Input: {adjective}\nOutput:",  
    input_variables=["adjective"],  
)  
similar_prompt.example_selector.k = 2  
print(similar_prompt.format(adjective="worried"))
```

Give the antonym of every input

Input: happy
Output: sad

Input: windy
Output: calm

Input: worried
Output: