



ORACLE PL/SQL

Tcs



Sai Majji

SQL

1. What is Oracle?
 - a) Oracle is a programming language
 - b) Oracle is a database
 - c) Oracle is a scripting language
 - d) Oracle is an operating system

Ans: oracle is Database. Oracle is a relational database management system. Oracle DB, or just Oracle, is another name for it. Oracle Corporation is the company that produces and sells it. Lawrence Ellison and other engineers built it in 1977.

2. Which of the following database was designed first for enterprise grid computing?
 - a) Oracle database
 - b) SQL
 - c) MongoDB
 - d) Google database

Ans: Oracle database

Note:

The features of Oracle Database features are:

- i) **Availability:** Because of the Oracle Data Guard feature, it ensures that databases are always available.
- ii) **Security:** To prevent unwanted access, Oracle has a system for controlling and accessing the database.
- iii) **Scalability:** It has capabilities such as RAC (Real Application Cluster) and Portability, which allow an Oracle database to scale up or down depending on usage.
- iv) **Performance:** Oracle Advanced Compression, Oracle Database In-Memory, Oracle Real Application Testing, and Oracle Times Ten Application-Tier Database Cache are some of the speed enhancement solutions available.
- v) **Analytics:** Oracle has the following solutions in the field of analytics:
 - a) OLAP (Oracle Analytic Processing)
 - b) Oracle Advanced Analytics
- vi) **Management:** Oracle Multitenant is a database management system that combines a single container database with a number of pluggable databases in a single unified design.

Advantages for Oracle DB

The following are the advantages of an Oracle database:

Performance: Oracle has procedures and principles that help us to get high levels of database performance.

Portability: The Oracle database can be ported on all different platforms than any of its competitors.

Backup and Recovery: Using the Oracle database, it is simple to perform a rapid recovery using RMAN (Recovery Manager) feature.

PL/SQL: One of the greatest benefits of using the Oracle database is to support PL/SQL extension for procedural programming.

Multiple Database: Oracle database allows several database instances management on a single server.

Flashback Technology: It enables user to recover data that has been wrongly deleted or lost due to human errors.

3. What is Oracle database used for?
- a) Creating backup for data
 - b) Accessing database servers
 - c) **Store and retrieve relevant data**
 - d) Both a & c

Ans: An Oracle database is a collection of data that is viewed as if it were a single entity. A database's main goal is to store and retrieve relevant data. The key to tackling information management issues is a database server.

4. Which of the following components comprise an Oracle architecture?
- a) Tablespaces
 - b) Datafiles
 - c) Database related background processes
 - d) **All of the Mentioned**

Ans: Oracle architecture consists of DB process, Table space, Datafiles.

5. Which of the following package procedure is UNRESTRICTED in Oracle?
 - a) CLEAR_BLOCK
 - b) **USER_EXIT**
 - c) CALL_INPUT
 - d) EXECUTE_QUERY

6. Oracle server configuration is dedicated for
 - a) **One server process – One user process**
 - b) Many server processes – Many user processes
 - c) Many server processes – One user process
 - d) One server process – Many user processes

7. Which of the following is not included in DML (Data Manipulation Language)?
 - a) UPDATE
 - b) **CREATE**
 - c) INSERT
 - d) DELETE

8. Which of the following keyword is used with Data Control Language (DCL) statements?
 - a) INSERT
 - b) SELECT
 - c) **GRANT**
 - d) DELETE

9. Which of the following command is used to obtain the structure of an Oracle table?
 - a) DESC TABLE [TableName].
 - b) STRUCTURE [TableName].
 - c) **DESCRIBE [TableName]. Or Desc Tablename**
 - d) DESCRIBE STRUCTURE [TableName].

10. Which of the following is not a type of SQL statement?
 - a) Data Definition Language (DDL)
 - b) Data Control Language (DCL)
 - c) **Data Communication Language (DCL)**
 - d) Data Manipulation Language (DML)

11. Which of the following is/are the DDL statements?
 - A) Drop
 - B) Alter
 - C) Create
 - D) **All of the Mentioned**

12. The SQL statement

SELECT SUBSTR('123456789', INSTR('abcbabcabc', 'b'), 4) FROM DUAL;

- a) 2345
- b) 456789
- c) 6789
- d) 1234

Ans: INSTR function in SQL is used to find the starting location of a pattern in a string. The syntax for the INSTR function is as follows :INSTR(str,pattern):Find the starting location of pattern in string str and SUBSTR Function:- The Substring function in SQL is used to grab a portion of the stored data.

13. Which of the following command is used to SELECT only one copy of each set of duplicable rows in SQL?

- a) SELECT UNIQUE
- b) SELECT DIFFERENT
- c) SELECT DISTINCT
- d) All of the Mentioned

14. Which of the following is not a component of a data warehouse?

- a) Data metadata
- b) Data extraction/cleaning/preparation programs
- c) Data warehouse data
- d) None of the Mentioned

15. Which of the following is the oldest database model?

- a) Deductive
- b) Physical
- c) Network
- d) Relational

16. Which of the SQL statements is correct?

- a) SELECT Username AND Password FROM Users
- b) SELECT Username, Password FROM Users (syntax)
- c) SELECT Username, Password WHERE Username = 'user1'
- d) None of the Mentioned

17. Find the temperature in increasing order of all cities

- a) SELECT city FROM weather ORDER BY temperature;
- b) SELECT city, temperature FROM weather;
- c) SELECT city, temperature FROM weather ORDER BY temperature;
- d) SELECT city, temperature FROM weather ORDER BY city;

Ans: All are optional. Its presence or absence doesn't change the output.
Unlike DISTINCT, it allows duplicates in the output.

18. _____ clause is an additional filter that is applied to the result.

- a) Select
- b) Group-by
- c) **Having**
- d) Order by

Ans: The HAVING clause was added to SQL because the WHERE keyword could not be used with aggregate functions.

19. Which command is used for removing a table and all its data from the database:

- a) Create command
- b) **Drop table command**
- c) Alter table command
- d) All of the Mentioned

Ans: The DROP INDEX statement is used to delete an index in a table.

20. Which command allows the removal of all rows from a table but flushes a table more efficiently since no rollback information is retained:

- a) **TRUNCATE command**
- b) Create command
- c) Drop table command
- d) Alter table command

Ans : The SQL TRUNCATE TABLE command is used to delete complete data from an existing table .You can also use DROP TABLE command to delete complete table but it would remove complete table structure form the database and you would need to re-create this table once again if you wish you store some data.

21. TRUNCATE statement in SQL is a –

- a) DML statement
- b) **DDL statement**
- c) DCL statement
- d) TCL statement

22. In SQL, which command is used to add new rows to a table?

- a) Alter Table
- b) Add row
- c) **Insert**
- d) Append

Ans: Alter Table will change the structure of the table

23. Stack is also called _____
- a) First In First Out (LIFO)
 - b) Last In First Out (FIFO)
 - c) **First In Last Out (FILO)**
 - d) First Come First Served (FCFS)

Ans: **Stack works on the First In Last Out.**

24. What does SQL stand for?

- ☒ **Structured Query Language** Your answer
- ☐ Structured Question Language
- ☐ Strong Question Language

25. Which SQL statement is used to extract data from a database?

- ☒ **SELECT** Your answer
- ☐ EXTRACT
- ☐ GET
- ☐ OPEN

26. Which SQL statement is used to update data in a database?

- ☒ **UPDATE** Your answer
- ☐ MODIFY
- ☐ SAVE AS
- ☐ SAVE

27. Which SQL statement is used to delete data from a database?

- ☒ **DELETE** Your answer
- ☐ COLLAPSE
- ☐ REMOVE

28. Which SQL statement is used to insert new data in a database?

- ☒ **INSERT INTO** Your answer
- ☐ INSERT NEW
- ☐ ADD NEW
- ☐ ADD RECORD

29. With SQL, how do you select a column named "FirstName" from a table named "Persons"?

- ☐ SELECT FirstName FROM Persons Your answer
- ☐ EXTRACT FirstName FROM Persons
- ☐ SELECT Persons.FirstName

30. With SQL, how do you select all the columns from a table named "Persons"?

- ☐ SELECT * FROM Persons Your answer
- ☐ SELECT [all] FROM Persons
- ☐ SELECT *.Persons
- ☐ SELECT Persons

31. With SQL, how do you select all the records from a table named "Persons" where the value of the column "FirstName" is "Peter"?

- ☐ SELECT * FROM Persons WHERE FirstName='Peter' Your answer
- ☐ SELECT [all] FROM Persons WHERE FirstName LIKE 'Peter'
- ☐ SELECT [all] FROM Persons WHERE FirstName='Peter'
- ☐ SELECT * FROM Persons WHERE FirstName<>'Peter'

31. With SQL, how do you select all the records from a table named "Persons" where the value of the column "FirstName" starts with an "a"?

- ☐ SELECT * FROM Persons WHERE FirstName LIKE 'a%' Your answer
- ☐ SELECT * FROM Persons WHERE FirstName='%a%'
- ☐ SELECT * FROM Persons WHERE FirstName LIKE '%a'
- ☐ SELECT * FROM Persons WHERE FirstName='a'

32. The OR operator displays a record if ANY conditions listed are true. The AND operator displays a record if ALL of the conditions listed are true

- ☐ True Your answer
- ☐ False

33. With SQL, how do you select all the records from a table named "Persons" where the "FirstName" is "Peter" and the "LastName" is "Jackson"?

- ☐ SELECT * FROM Persons WHERE FirstName='Peter' AND LastName='Jackson' Your answer
- ☐ SELECT * FROM Persons WHERE FirstName<>'Peter' AND LastName<>'Jackson'
- ☐ SELECT FirstName='Peter', LastName='Jackson' FROM Persons

34. With SQL, how do you select all the records from a table named "Persons" where the "LastName" is alphabetically between (and including) "Hansen" and "Pettersen"?

- ☐ SELECT * FROM Persons WHERE LastName BETWEEN 'Hansen' AND 'Pettersen' Your answer
- ☐ SELECT * FROM Persons WHERE LastName>'Hansen' AND LastName<'Pettersen'
- ☐ SELECT LastName>'Hansen' AND LastName<'Pettersen' FROM Persons

35. Which SQL statement is used to return only different values?

- ☐ SELECT DISTINCT Your answer
- ☐ SELECT DIFFERENT
- ☐ SELECT UNIQUE

36. Which SQL keyword is used to sort the result-set?

- ☐ ORDER BY Your answer
 - ☐ SORT BY
 - ☐ SORT
 - ☐ ORDER
-

37. With SQL, how can you return all the records from a table named "Persons" sorted descending by "FirstName"?

- ☐ `SELECT * FROM Persons ORDER BY FirstName DESC` Your answer
- ☐ `SELECT * FROM Persons SORT BY 'FirstName' DESC`
- ☐ `SELECT * FROM Persons ORDER FirstName DESC`
- ☐ `SELECT * FROM Persons SORT 'FirstName' DESC`

38. With SQL, how can you insert a new record into the "Persons" table?

- ☐ `INSERT INTO Persons VALUES ('Jimmy', 'Jackson')` Your answer
- ☐ `INSERT ('Jimmy', 'Jackson') INTO Persons`
- ☐ `INSERT VALUES ('Jimmy', 'Jackson') INTO Persons`

39. With SQL, how can you insert "Olsen" as the "LastName" in the "Persons" table?

- ☐ `INSERT INTO Persons (LastName) VALUES ('Olsen')` Your answer
- ☐ `INSERT INTO Persons ('Olsen') INTO LastName`
- ☐ `INSERT ('Olsen') INTO Persons (LastName)`

40. How can you change "Hansen" into "Nilsen" in the "LastName" column in the Persons table?

- ☐ `UPDATE Persons SET LastName='Hansen' INTO LastName='Nilsen'` Your answer
- ☐ `MODIFY Persons SET LastName='Hansen' INTO LastName='Nilsen'`
- ☐ `MODIFY Persons SET LastName='Nilsen' WHERE LastName='Hansen'`
- ☐ `UPDATE Persons SET LastName='Nilsen' WHERE LastName='Hansen'` Correct answer

41. With SQL, how can you delete the records where the "FirstName" is "Peter" in the Persons Table?

- ☐ `DELETE FROM Persons WHERE FirstName = 'Peter'` Your answer
- ☐ `DELETE FirstName='Peter' FROM Persons`
- ☐ `DELETE ROW FirstName='Peter' FROM Persons`

42. With SQL, how can you return the number of records in the "Persons" table?

- ☐ `SELECT COUNT(*) FROM Persons` Your answer
- ☐ `SELECT COLUMNS(*) FROM Persons`
- ☐ `SELECT LEN(*) FROM Persons`
- ☐ `SELECT NO(*) FROM Persons`

43. What is the most common type of join?

- ☐ INNER JOIN Your answer
- ☐ JOINED
- ☐ INSIDE JOIN
- ☐ JOINED TABLE

44. Which operator is used to select values within a range?

- ☐ BETWEEN Your answer
- ☐ WITHIN
- ☐ RANGE

45. The NOT NULL constraint enforces a column to not accept NULL values.

- ☐ True Your answer
- ☐ False
- ☐ Which operator is used to search for a specified pattern in a column?
- ☐ LIKE Your answer
- ☐ GET
- ☐ FROM

46. Which SQL statement is used to create a database table called 'Customers'?

- ☐ CREATE TABLE Customers Your answer
- ☐ CREATE DB Customers
- ☐ CREATE DATABASE TABLE Customers
- ☐ CREATE DATABASE TAB Customers

47. Which of the following constraints can be defined only at the column level?

- ☐ Unique
- ☐ Not Null
- ☐ Check
- ☐ Primary key

48. How can the user change "Scaler" into "Interviewbit" in the "Name" column in the Users table?

Update Users Set Name = 'Interviewbit' WHERE Name='Scaler'

51. Which statement is used to delete all rows in a table without having the action logged?

- ☐ DELETE

- REMOVE
- DROP
- TRUNCATE

Explanation : TRUNCATE statement removes all rows in a table without logging the individual row deletions. This statement is similar to the DELETE statement without the WHERE clause.

52. SQL Views are also known as

- Simple tables
- Virtual tables
- Complex tables
- Actual Tables

53. How many Primary keys can have in a table?

- Only 1
- Only 2
- Depends on no of Columns
- Depends on DBA

Explanation: A table can only have one primary key, but it can have multiple unique constraints. You should explicitly define a table's primary key in the CREATE TABLE statement.

54. Which of the following is not Constraint in SQL?

- Primary Key
- Not Null
- Check
- Union

Explanation: Constraint specifies the rule to allow or restrict what data will be stored in a table. The PRIMARY KEY, NOT NULL, and CHECK are the constraints that specify rules for data insertion.

UNION is an operator that combines two or more results from multiple SELECT queries into a single result set.

55. Which of the following is not a valid aggregate function?

- ☐ COUNT
- ☒ COMPUTE
- ☐ SUM
- ☐ MAX

Explanation : Aggregate function is used to perform calculations on multiple values and return the output in a single value. It is mostly used with the SELECT statement. COUNT, SUM, and MAX are all aggregate functions.

COMPUTE is not an aggregate function. It is used to generate totals as an additional column at the end of the result set.

56. Which data manipulation command is used to combines the records from one or more tables?

- ☐ SELECT
- ☐ PROJECT
- ☒ JOIN
- ☐ PRODUCT

Explanation : JOIN command is used with the SELECT statement to retrieve data from multiple tables. It must be needed whenever we want to fetch records from two or more tables.

57. Which operator is used to compare a value to a specified list of values?

- ☐ ANY
- ☒ BETWEEN
- ☐ ALL
- ☐ IN

Explanation : The IN operator easily tests the expression if it matches any value in a specified list of values. It reduces the use of multiple OR conditions.

The WHERE or HAVING clause uses the ANY and ALL operators. ANY gives the result when any subquery value matches the specified condition. The ALL give the result when all subquery values match the specified condition.

The BETWEEN operator selects values only in the given range.

58. What operator tests column for absence of data

- NOT Operator
- Exists Operator
- IS NULL Operator
- None of the above

Explanation : The IS NULL operator is used to testing the empty values in the table's column. It returns true if column values are NULL.

The NOT operator gives the result only when the specified condition is not true.

The EXISTS operator used in combination with a subquery, and if a subquery returns any record, this operator returns true. Otherwise it will return false.

59. In which of the following cases a DML statement is not executed?

- When existing rows are modified.
- When a table is deleted.
- When some rows are deleted.
- All of the above

Explanation : The DML statement is used to access and manipulate the data in an existing table. Therefore, it cannot be used in table deletion.

60. If we have not specified ASC or DESC after a SQL ORDER BY clause, the following is used by default

- DESC
- ASC
- There is no default value
- None of the mentioned

Explanation : If we have not specified any sorting with the ORDER BY clause, SQL always uses the ASC as a default sorting order. SQL treats Null as the lowest possible values while sorting.

61. Which of the following statement is true?

- ☒ TRUNCATE free the table space while DELETE does not.
- ☐ Both TRUNCATE and DELETE statements free the table's space.
- ☐ Both TRUNCATE and DELETE statement does not free the table's space.
- ☐ DELETE free the table space while TRUNCATE does not.

Explanation : The TRUNCATE statement in SQL removes all data from the table and free the table's space.

SQL's DELETE statement removes all data from the table but does not free the table's space.

62. What is returned by INSTR ('JAVAT POINT', 'P')?

- ☐ 6
- ☒ 7
- ☐ POINT
- ☐ JAVAT

Explanation : The INSTR function searches the string for substring and returns the numeric value of the specified character's first occurrence.

63. A command that lets you change one or more field in a table is:

- ☐ INSERT
- ☒ MODIFY
- ☐ LOOK-UP
- ☐ All of the above

Explanation : The modify command is used to change one or more columns in the existing table. It is generally used with ALTER TABLE statement as follows.

Syntax: Alter table Tablename modify (column_name , column_datatype);

64. Which of the following is true about the HAVING clause?

- ☐ Similar to the WHERE clause but is used for columns rather than groups.
- ☐ Similar to WHERE clause but is used for rows rather than columns.
- ☐ Similar to WHERE clause but is used for groups rather than rows.
- ☐ Acts exactly like a WHERE clause.

Explanation : The HAVING clause is always used with the GROUP BY clause and returns the rows where the condition is TRUE.

65. SELECT ROUND (65.726, -1) FROM DUAL;

- ☐ is illegal
- ☐ garbage
- ☐ 726
- ☒ 70

Explanation : Here, the ROUND() function statement will produce the rounded result of the given number 65.726 from the left of decimal point up to 1.

66. Which command is used to change the definition of a table in SQL?

- ☐ CREATE
- ☐ UPDATE
- ☒ ALTER
- ☐ SELECT

Explanation : The ALTER statement is used to change our table's definition, such as table name, column name, column constraint, etc. It also allows us to add or delete an existing column in a table. This statement must be used with ADD, DROP, and MODIFY clauses according to the situation.

67. Which type of JOIN is used to returns rows that do not have matching values?

- ☐ Natural JOIN
- ☒ Outer JOIN
- ☐ EQUI JOIN
- ☐ All of the above

Explanation : OUTER JOIN is the only join that returned the unmatched rows in one or both tables. It can be classified into the following types:

- ☐ LEFT JOIN that shows only the unmatched rows from the left table.
- ☐ RIGHT JOIN that shows only the unmatched rows from the right table.
- ☐ FULL OUTER JOIN that shows the unmatched rows from both tables.

EQUI JOIN shows records for equality or matching column(s) values of the relative tables.

A Natural join can only be performed if at least one common attribute exists between two relations (the attribute should be the same name and domain).

68. A CASE SQL statement is _____?

- ☐ A way to establish a loop in SQL.
- ☒ A way to establish an IF-THEN-ELSE in SQL
- ☐ A way to establish a data definition in SQL
- ☐ All of the above.

Explanation : A CASE statement is one of the control flow function that allows us to write an if-else or if-then-else logic in a SQL query. This expression validates various conditions and shows the output when the first condition is true, and stops traversing. If any condition is not true, it executes the else block. It shows a null value if the else block is not found.

Syntax:

CASE

```
WHEN condition1 THEN result1
WHEN condition2 THEN result2
WHEN conditionN THEN resultN
ELSE result
```

END;

69. Which of the following is the basic approaches for joining tables?

- ☐ Union JOIN
- ☐ Natural JOIN
- ☐ Subqueries
- ☒ All of the above

Explanation : We already know that Union and Natural are the approaches for joining two or more tables.

A subquery is a query nested into another SQL query. It can be embedded with SELECT, INSERT, UPDATE or DELETE statement. A subquery is known as the inner query. In many cases, we can use the subquery instead of a JOIN. Therefore, option D is the correct choice.

70. Group of operations that form a single logical unit of work is known as

- ☐ View
- ☐ Network
- ☐ Unit
- ☒ Transaction

Explanation : A transaction is a sequential group of statements such as select, insert, update or delete to perform as one single logical unit of work that can be committed or rolled back

71. Which of the following is the correct order of a SQL statement?

- SELECT, GROUP BY, WHERE, HAVING
- SELECT, WHERE, GROUP BY, HAVING
- SELECT, HAVING, WHERE, GROUP BY
- SELECT, WHERE, HAVING, GROUP BY

Explanation : In SQL statements, the WHERE clause always comes before GROUP BY, and the HAVING clause always comes after GROUP BY. Therefore, option B is the correct choice.

72. What is the difference between a PRIMARY KEY and a UNIQUE KEY?

- Primary key can store null value, whereas a unique key cannot store null value.
- We can have only one primary key in a table while we can have multiple unique keys
- Primary key cannot be a date variable whereas unique key can be
- None of these

Explanation : The primary key is a single or combination of the field that identifies each record in a table uniquely. It cannot take a NULL value. A table can have only one primary key. Also, we can create a date variable as a primary key in a table.

Unique key also determines each row of the table uniquely, but it can take null value into. A table can have more than one unique key. We cannot create a date variable as a unique key in a table.

73. Which operator is used to compare the NULL values in SQL?

- Equal
- IN
- IS
- None of Above

Explanation : In SQL, we can use the IS operator to compare a NULL. This operator can be used with select, insert, update, and delete commands.

The IN is a conditional operator used to reduce the use of multiple OR conditions in select, insert, update, and delete commands.

The EQUAL operator is used to check whether the given expressions are equal or not. The condition becomes true if the expressions are equal and then return matched records.

74. Which of the following statement is correct regarding the difference between TRUNCATE, DELETE and DROP command?

- I. DELETE operation can be rolled back but TRUNCATE and DROP operations cannot be rolled back.
- II. TRUNCATE and DROP operations can be rolled back but DELETE operations cannot be rolled back.
- III. DELETE is an example of DML, but TRUNCATE and DROP are examples of DDL.
- IV. All are an example of DDL.

- I and III
- II and III
- II and IV
- II and IV

Explanation : DELETE is used to remove existing records from the database. DELETE command is a DML statement so that it can be rolled back.

DROP is used to delete the whole table, including its structure. DROP is a DDL command that lost the data permanently, and it cannot be rolled back.

TRUNCATE is used to delete the whole records, but it preserves the table's schema or structure. TRUNCATE is a DDL command, so it cannot be rolled back.

75. When the wildcard in a WHERE clause is useful?

- When an exact match is required in a SELECT statement.
- When an exact match is not possible in a SELECT statement.
- When an exact match is required in a CREATE statement.
- When an exact match is not possible in a CREATE statement.

76. _____ is NOT a type of constraint in SQL language?

- FOREIGN KEY
- PRIMARY KEY
- UNIQUE
- ALTERNATE KEY

77. Find the cities name with the condition and temperature from table 'whether' where condition = sunny or cloudy but temperature >= 60.

- SELECT city, temperature, condition FROM weather WHERE condition = 'cloudy' AND condition = 'sunny' OR temperature >= 60
- SELECT city, temperature, condition FROM weather WHERE condition = 'cloudy' OR condition = 'sunny' OR temperature >= 60
- SELECT city, temperature, condition FROM weather WHERE condition = 'sunny' OR condition = 'cloudy' AND temperature >= 60
- SELECT city, temperature, condition FROM weather WHERE condition = 'sunny' AND condition = 'cloudy' AND temperature >= 60

78. Which of the following statement is correct to display all the cities with the condition, temperature, and humidity whose humidity is in the range of 60 to 75 from the 'whether' table?

- SELECT * FROM weather WHERE humidity IN (60 to 75)
- SELECT * FROM weather WHERE humidity BETWEEN 60 AND 75
- SELECT * FROM weather WHERE humidity NOT IN (60 AND 75)
- SELECT * FROM weather WHERE humidity NOT BETWEEN 60 AND 75

79. Which statement is used to get all data from the student table whose name starts with p?

- ☐ SELECT * FROM student WHERE name LIKE '%p%';
- ☒ SELECT * FROM student WHERE name LIKE 'p%';
- ☐ SELECT * FROM student WHERE name LIKE '_p%';
- ☐ SELECT * FROM student WHERE name LIKE '%p';

80. _____ is a constraint that can be defined only at the column level?

- ☐ UNIQUE
- ☒ NOT NULL
- ☐ CHECK
- ☐ PRIMARY KEY

Explanation : The SQL NOT NULL constraint prevents inserting NULL values into the specified column. It enforces that a value must be defined for this column cannot accept a NULL value. Hence, we can say that the NOT NULL constraint can be defined only at the column level.

81. Which of the following operator can be used with a multiple-row subquery?

- ☐ =
- ☐ BETWEEN
- ☒ NOT IN
- ☐ <>

Explanation : The multiple-row subqueries produces multiple rows of results. We can only use the NOT IN operator in SQL can only be used with multiple-row subqueries. And all other operators must be used with single row subquery only. Therefore, BETWEEN, '=', and '<>' operators work with single row subquery. Hence option C is the correct choice.

82. Which of the following is a SQL aggregate function?

- ☐ LEFT
- ☒ AVG
- ☐ JOIN
- ☐ LEN

SQL has several arithmetic functions to do math on the numbers, such as summing up, taking average, retrieved from the column. They are:

AVG() :- Average of the column

COUNT() :- Number of records

MAX() :- maximum of the column

MIN() :- minimum of the column

SUM() :- Sum of the column

83. The SQL statement

SELECT SUBSTR('123456789', INSTR('abcabcabc', 'b'), 4) FROM DUAL;

- ☐ 6789
- ☒ 2345
- ☐ 1234
- ☐ 456789

**84. The SQL statement

SELECT SUBSTR('abcdefghij', INSTR('123321234', '2', 3, 2), 2) FROM DUAL;

prints

- ☒ gh
- ☐ 23
- ☐ bc
- ☐ ab

Explanation : Another form of **INSTR** function used in ORACLE is:

INSTR (*str*, *pattern*, [*starting position*, [*nth location*]]): Finds the starting location of the *nth* occurrence of *pattern* beginning in the *starting position-th* position in string *str*.

Example: - SELECT INSTR('kolkata', 'a', 1, 2) FROM DUAL;

will output 7 as the starting location of 2nd occurrence of pattern 'a' from starting

position 1 in string 'kolkata' is 7.

In the above query INSTR('123321234', '2', 3, 2) will give the output 7 as the starting location of 2nd occurrence of pattern '2' from starting location three in string '123321234' is 7. Now SUBSTR function becomes SUBSTR('abcdefghij

85. What is the meaning of LIKE '%0%0%0%'

- Feature begins with two 0's
- Feature ends with two 0's
- Feature has more than two 0's
- Feature has two 0's in it, at any position

Sai Majji

Sai Majji

PL/SQL

1) Which of the following statements can be used to terminate a PL/SQL loop?

- ☐ GOTO
- ☒ EXIT WHEN
- ☐ CONTINUE WHEN
- ☐ KILL

2) Which of the following is not a PL/SQL unit?

- ☒ Table
- ☐ Type
- ☐ Trigger
- ☐ Package

3) Which of the following is true about scalar data types in PL/SQL?

- ☐ They hold single values with no internal components.
- ☐ Examples of scalar data types are NUMBER, DATE, or BOOLEAN.
- ☐ PL/SQL provides subtypes of data types.
- ☒ All are true.

4) Which keyword is used instead of the assignment operator to initialize variables?

- ☐ NOT NULL
- ☒ DEFAULT
- ☐ %TYPE
- ☐ %ROWTYPE

5) What value will be assigned to the variable declared as – counter
binary_integer;

- ☐ 0
- ☐ 1
- ☒ NULL
- ☐ None of the above.

6) What is the initial value of index for a reverse for loop?

- ☒ UPPER bound
- ☐ Lower bound
- ☐ 1
- ☐ Upper bound-Lower bound/2

7) Which of the following is not true about large object data types and in PL/SQL?

- ☐ BFILE is used to store large binary objects in operating system files outside the database.
- ☒ BLOB is used to store character data in the database.
- ☐ CLOB is used to store large blocks of character data in the database.
- ☐ NCLOB is used to store large blocks of NCHAR data in the database.

8) _____ types of literals are available in PL/SQL.

- A. 2
- B. 5
- C. 4
- D. 6

9) What is TRUE about PL/SQL functionalities?

- Conditions and loops are fundamental elements of procedural languages like PL/SQL.
- Various types and variables can be declared, as can procedures and functions, as well as types and variables of those types.
- Arrays can be used with it as well as handling exceptions (runtime errors).
- All of the above

10) PL/SQL text is made up of lexical units, which are groups of characters and can be classified as –

- Delimiters
- Identifiers
- Literals
- All of the above

Explanation:

PL/SQL text is made up of lexical units, which are groups of characters and can be classified as Delimiters, Identifiers, Literals and Comments.

11) A Variable in PL/SQL should not exceed –

- 10
- 20
- 30
- 40

12) Which of the following is/are TRUE about PL/SQL Variables?

- Variables serve as a means for programmers to temporarily store data during code execution.
- PL/SQL programs benefit from its use.
- There is nothing special about it other than being the name of a storage area.
- All of the above

13) PL/SQL Variables are by default –

- Case Sensitive
- Upper Case Sensitive
- Lower Case Sensitive
- Not Case Sensitive

14) PL/SQL Variable needs to be declared in the –

- Variable Section
- Declaration Section
- Initialization Section
- None of the above

15) The correct syntax to declare PL/SQL variable is –

- variable_name [CONSTANT] datatype [NOT NULL] [:= | DEFAULT initial_value]
- datatype [CONSTANT] variable_name [NOT NULL] [:= | DEFAULT initial_value]
- variable_name [CONSTANT] datatype [NULL] [:= | DEFAULT initial_value]
- datatype [CONSTANT] variable_name [NULL] [:= | DEFAULT initial_value]

16) In order to initialize a variable with the value other than NULL, it can be done using which method?

- The Assignment Operator
- The DEFAULT Keyword
- Both A. and B.
- None of the above

17) What is the name of the two variable scopes in PL/SQL?

- Local & Grind Variable
- Letter & Grind Variable
- Local & Global Variable
- Letter & Global Variable

18) What is the difference between Local & Global Variables?

- Variables in an outer block are defined as local variables since they cannot be accessed from the outside whereas the innermost block declares global variables.
- Variables in an inner block are defined as global variables since they cannot be accessed from the outside whereas the outermost block declares local variables.
- Variables in an outer block are defined as global variables since they can be accessed from the outside and the innermost block also declares global variables.
- Variables in an inner block are defined as local variables since they cannot be accessed from the outside whereas the outermost block declares global variables.

19) ___ are values used in PL/SQL blocks that do not change during execution.

- Variables
- Constants
- Functions
- Cursor

20) Choose the correct syntax to declare a constant.

- `constant_name CONSTANT datatype := VALUE;`
- `datatype CONSTANT constant_name := VALUE;`
- `constant_name CONSTANT datatype =: VALUE;`
- `datatype CONSTANT constant_name =: VALUE;`

Related Theory:

In case of constant_name in PL/SQL Constant –

1. Exactly like a variable name, it is a name for a constant.
2. A constant word doesn't change its value and is a reserved word.

A value is assigned to a constant in PL/SQL at the time of Declaration.

21) Which is the correct example of the literal of type Boolean.

- ☐ NULL
- ☐ TRUE
- ☒ Both A. and B.
- ☐ None of the above

Related Theory:

PL/SQL literals are case-sensitive.

22) Which of the following is NOT a type of PL/SQL literal?

- ☐ Numeric
- ☐ String
- ☐ Boolean
- ☒ Check

Explanation:

Type of PL/SQL literals are Numeric, Character, String, Boolean and Date & Time.

Related Theory:

Examples of Numeric literals are 1234, 12.22, 0 etc.

TRUE, FALSE, NULL etc. are Boolean literals.

23) Which of the following is a Character literal?

- ☐ B
- ☐ 4
- ☐ %
- ☒ All of the above

24) Which of the following is correct syntax of IF statement?

- IF-THEN statement
- IF-THEN-ELSE statement
- IF-THEN-ELSIF statement
- All of the above

Explanation:

Explanation: Different Syntax of If statements are –

1. IF-THEN statement
2. IF-THEN-ELSE statement
3. IF-THEN-ELSIF statement
4. IF-THEN-ELSIF-ELSE statement

You Need to understand the functionality of Each if statement .where it can be used.

25) CASE statement uses which keyword to work like IF statement?

- INTO
- AS
- WHEN
- IN

Related Theory:

The selectors in case of CASE statement are Variable, Function or Expression.

Evaluation of CASE statement is done TOP to BOTTOM.

26) By using PL/SQL ____, you can repeatedly execute one or more statements over and over again.

- Loops
- Cursor
- Variables
- Case

Note: PL/SQL Loops are also known as Iterative Control Statements.

27) What is the syntax of PL/SQL Loop?


```
LOOP  
END LOOP;  
Sequence of statements;
```

```
END LOOP;  
LOOP  
Sequence of statements;
```

```
LOOP  
Sequence of statements;  
END LOOP;
```

```
END LOOP;  
Sequence of statements;  
LOOP
```

28) How many types of PL/SQL Loops are there?

- ☐ 3
- ☒ 4
- ☐ 5
- ☐ 6

Simple/basic/Exit , while ,for, cursor for Loop

29) A/An _____ loop in PL/SQL ensures that at least one statement is executed before the loop terminates.

- ☐ While
- ☐ For
- ☐ Cursor For
- ☒ Exit

Note: While using PL/SQL Exit Loop –

1. The loop body should be initialized with a variable
2. Variables in the loop are incremented.
3. When you are ready to exit the loop, you should use the EXIT WHEN statement.

30) The PL/SQL ____ loop runs a series of statements as long as a condition is true, so it can be used in a series of statements.

- ☒ While
- ☐ Cursor For
- ☐ Basic
- ☐ For

Syntax for while:

```
WHILE <condition>  
LOOP statements;  
END LOOP;
```

31) When you want to execute a series of statements repeatedly, you use the PL/SQL ____ loop.

- ☐ Cursor For
- ☐ Cursor
- ☒ For
- ☐ While

Note: Please Observe the while and For loop use cases. (observe 30th & 31st)

32) The counter in PL/SQL FOR Loop is by default incremented by –

- ☐ 0
- ☒ 1
- ☐ 2
- ☐ NULL

33) PL/SQL ____ statement initiates the next iteration of a loop, skipping any code in between, by exiting the loop from the remainder in its body either conditionally or unconditionally.

- Condition
- Cursor
- Continue
- Check

→ Oracle 11g supports PL/SQL Continue statement.

34) A ____ statement in PL/SQL allows you to jump from this statement to a specific statement label within the same subprogram within a PL/SQL block.

- JUMP
- GOTO
- CONTINUE
- BLINK

→ The symbol in which the label_name is encapsulated in PL/SQL GOTO statement is << >>.

35) PL/SQL Procedure consists of –

- Header and Footer
- Body and Footer
- Header and Body
- None of the above

Note: Parameters and variables are contained in the header of the procedure

36) How much number of ways is there to pass the parameters in procedure?

- ☐ 1
- ☐ 2
- ☒ 3
- ☐ 4

Note: The pass parameters in procedure are –

1. IN
2. OUT
3. INOUT

37) What is the difference between PL/SQL Function and PL/SQL Procedure?

- ☐ PL/SQL function may or may not return the value whereas PL/SQL Procedure must have to return the value.
- ☒ PL/SQL Procedure may or may not return the value whereas PL/SQL Function must have to return the value.
- ☐ PL/SQL Function may or may not return the function whereas PL/SQL Procedure must have to return the function.
- ☐ None of the above

38) PL/SQL function must contain a –

- ☐ Follow Statement
- ☐ GOTO Statement
- ☒ Return Statement
- ☐ NULL Statement

39) In order to remove the PL/SQL function, which function is used?

- ☐ REMOVE FUNCTION
- ☐ DELETE FUNCTION
- ☐ ERASE FUNCTION
- ☒ DROP FUNCTION

40) In the contexts created by Oracle, a cursor represents a ____.

- ☐ Function
- ☐ Table
- ☒ Pointer
- ☐ None of the above

41) How many types of PL/SQL Cursor are there?

- A. 1
- B. 2
- C. 3
- D. 4

Note: Implicit, Explicit Cursor

42) The Implicit cursors are created in order to process the ____ statements.

- ☐ DDL
- ☐ DCL
- ☒ DML
- ☐ TCL

Note : DML statements such as INSERT, DELETE, UPDATE

Related Thoery:

%FOUND, %ROWCOUNT, %OPEN and %NOTFOUND are all the implicit cursor's attributes.(You need to Understand the Functionality of Each Attribute)

43) Which of the following is the correct syntax to create the Explicit Cursor?

- IS select_statement cursor_name CURSOR;
- CURSOR select_statement IS cursor_name;
- CURSOR cursor_name select_statement IS;
- CURSOR cursor_name IS select_statement;

Note : In the PL/SQL Block, Explicit cursors are defined in Declaration Section.

(You Must know the Steps to work on Explicit Cursor)

44) On the ____ statements, the explicit cursors are created which return rows more than one.

- DELETE
- CREATE
- SELECT
- UPDATE

45) Which of the following is the correct syntax to fetch the cursor?

- FETCH cursor_name INTO variable_list;
- FETCH variable_list INTO cursor_name;
- INTO cursor_name FETCH variable_list;
- INTO variable_list FETCH cursor_name;

46) Which clause is used to open the cursor?

- BEGIN
- START
- OPEN
- INITIATE

Note : CLOSE clause is used to close the cursor.

47) Which of the following is TRUE about PL/SQL Trigger?

- ☐ When certain conditions are met, a trigger stored in a database is triggered.
- ☐ A trigger is an application that executes or fires automatically when a certain event occurs.
- ☒ Both A. and B.
- ☐ None of the above

48) In which event(s) trigger is executed?

- ☐ DDL
- ☐ DML
- ☐ Database Operation
- ☒ All of the above

49) Which clause(s) is/are used to specify when the trigger will get executed?

- ☐ BEFORE
- ☐ AFTER
- ☐ INSTEAD OF
- ☒ All of the above

50) Which clause is used to create trigger on a view?

- ☐ BEFORE
- ☐ AFTER
- ☒ INSTEAD OF
- ☐ None of the above

Note: of column_name specifies the column name that is needed to be updated whereas ON table_name specified the table name that is associated with the trigger.

51) What does FOR EACH ROW clause do in Trigger syntax?

- A row-level trigger is specified, meaning that each row is affected by this trigger
- When the SQL statement is run, the trigger will be executed just once, which is what is called a table-level trigger
- Both A. and B.
- None of the above

52) WHEN condition is valid for which triggers?

- Table Level Triggers
- Row Level Triggers
- Column Level Triggers
- Database Level Triggers

Note: Table-level triggers do not have access to OLD and NEW references. Record-level triggers use OLD and NEW references.

AFTER keyword is used to query the table in the same trigger.

53) Which of the following is an advantage of trigger?

- Imposing authorizations for security
- Keeping track of table access events and logging them
- Auditing
- All of the above

54) Errors that are encountered during the execution of the program are referred to as ____ in PL/SQL.

- FUNCTION
- CURSOR
- EXCEPTION
- PROCEDURE

System-defined and User-defined exceptions are both the types of exceptions.

55) Which command is used in order to raise an exception explicitly?

- ☐ RISE
- ☐ ROSE
- ☒ RAISE
- ☐ RINSE

56) What is the syntax of User-defined exceptions?

- ☒ DECLARE my-exception EXCEPTION;
- ☐ DECLARE EXCEPTION;
- ☐ DECLARE my-exception;
- ☐ EXCEPTION;

57) When SELECT INTO returns no rows, which pre-defined exception is raised?

- ☐ ACCESS_INTO_NULL
- ☒ NO_DATA_FOUND
- ☐ NOT_LOGGED_ON
- ☐ VALUE_ERROR

58) When DUP_VAL_ON_INDEX exception does is raised?

- ☒ A unique index column with duplicate values is raised when this error occurs.
- ☐ The error is raised if an attempt is made to close an unopened cursor or perform a cursor operation without permission.
- ☐ When character strings are converted to numbers, it is raised if the string did not represent a valid number.
- ☐ An invalid username or password is used to log on to the database by a program.

59) Which exception is raised when there is an internal problem in PL/SQL?

- ☐ VALUE_ERROR
- ☐ INTERNAL_ERROR
- ☐ PROBLEM_ERROR
- ☒ PROGRAM_ERROR

60) A PL/SQL exception, which occurs when a memory error occurs?

- ZERO-DIVIDE
- VALUE_ERROR
- MEMORY_ERROR
- STORAGE_ERROR

61) The exception thrown when more than one row is returned from a SELECT INTO statement?

- MORE_THAN_ONE_ROW
- MORE_ROWS
- TOO_MANY_ROWS
- MANY_ROWS

62) When VALUE_ERROR exception is raised?

- Errors relating to arithmetic, conversion, truncation, or size constraints raise this signal.
- This error message appears when a number is divided by zero.
- Both A. and B.
- None of the above

63) When ZERO_DIVIDE exception is raised?

- This error message appears when a number is multiplied by zero.
- This error message appears when a number is divided by zero.
- This error message appears when a number is integrated by zero.
- This error message appears when a number is zero.

Sai Majji